

REPORT NO. MGA-94-DC005

DUMMY PERFORMANCE CALIBRATIONS

FMVSS 214 - SIDE IMPACT TEST

CHRYSLER CORPORATION
1994 DODGE INTREPID 4 DOOR SEDAN
NHTSA NO. CR0312

MGA PROVING GROUNDS
5000 WARREN ROAD
BURLINGTON, WI 53105



Test Date: June 1, 1994

Report Date: September 26, 1994

FINAL REPORT

Prepared For:

U. S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
MAIL CODE: NEF-30
400 SEVENTH STREET, S.W., ROOM 6115
Washington, D.C. 20590

TECHNICAL REPORT STANDARD TITLE PAGE

1. Report No. MGA-94-21405		2. Government Accession No.		3. Recipient's Catalog No.																			
4. Title and Subtitle Final Report for FMVSS 214 Compliance Testing of a 1994 Dodge Intrepid 4 Door Sedan NHTSA NO. CR0312				5. Report Date September 26, 1994																			
				6. Performing Organization Code MGA																			
7. Author(s) John Fleck and Homyoung Kim				8. Performing Organization Report No. MGA-DOT-214-05																			
9. Performing Organization Name and Address MGA Research Corporation 5000 Warren Road Burlington, WI 53105				10. Work Unit No.																			
				11. Contract or Grant No. DTNH22-93-C-02047																			
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Vehicle Safety Compliance (Mail Code: NEF-30) 400 Seventh St., S.W., Room 6115 Washington, D.C. 20590				13. Type of Report and Period Covered Final Report July 1994																			
				14. Sponsoring Agency Code NEF-30																			
15. Supplementary Notes																							
16. Abstract Compliance tests were conducted on the subject 1994 Dodge Intrepid 4 Door Sedan in accordance with the specifications of the Office of Vehicle Safety Compliance Test Procedure for the determination of FMVSS 214 compliance. The test was conducted at the MGA Research Proving Grounds and crash Test Center in Burlington, Wisconsin on June 3, 1994. The impact velocity of the Moving Barrier (MDB) was 32.7 mph and the ambient temperature of the struck side (driver's) of the target vehicle at the time of impact was 76°F. The test or target vehicle's performance is given below: <table border="0"> <thead> <tr> <th></th> <th><u>Driver's SID</u></th> <th><u>Left Rear SID</u></th> </tr> </thead> <tbody> <tr> <td>Thoracic Trauma Index (TTI)</td> <td>62 g's</td> <td>67 g's</td> </tr> <tr> <td>Pelvis Acceleration</td> <td>69 g's</td> <td>79 g's</td> </tr> <tr> <td>Upper Rib Acceleration</td> <td>51.2 g's</td> <td>78.4 g's</td> </tr> <tr> <td>Lower Rib</td> <td>59.9 g's</td> <td>78.2 g's</td> </tr> <tr> <td>Lower Spine</td> <td>63.1 g's</td> <td>55.2 g's</td> </tr> </tbody> </table>							<u>Driver's SID</u>	<u>Left Rear SID</u>	Thoracic Trauma Index (TTI)	62 g's	67 g's	Pelvis Acceleration	69 g's	79 g's	Upper Rib Acceleration	51.2 g's	78.4 g's	Lower Rib	59.9 g's	78.2 g's	Lower Spine	63.1 g's	55.2 g's
	<u>Driver's SID</u>	<u>Left Rear SID</u>																					
Thoracic Trauma Index (TTI)	62 g's	67 g's																					
Pelvis Acceleration	69 g's	79 g's																					
Upper Rib Acceleration	51.2 g's	78.4 g's																					
Lower Rib	59.9 g's	78.2 g's																					
Lower Spine	63.1 g's	55.2 g's																					
17. Key Words Side Impact Dummy (SID) Compliance Test FMVSS 214 Side Impact Protection				18. Distribution Statement Copies of this report are available from: NHTSA Technical Reference Division, Room 5108 (NAD-52), 400 Seventh Street, S.W. Washington, D.C. 20590 Telephone No. (202) 366-4946 Attn: Robert Hornickle																			
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 248																			
				22. Price																			

This Test Report was prepared for the U.S. Department of Transportation. National Highway Traffic Safety Administration, under Contract No. DTNH22-93-C-02047.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration. In the interest of information exchange. The opinions, finding and conclusions expressed in this publication are those of author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its content or use thereof. If trade or manufacturers' names or products are mentioned, it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Approved by:

John Fleck

Date: 9-22-94

John Fleck, Project Engineer

FINAL REPORT ACCEPTED BY:

Contract Technical Manager

Date: 10/4/94

TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1	PURPOSE AND TEST PROCEDURE	1-1
2	SUMMARY OF SIDE IMPACT TEST	2-1
3	SUMMARY OF TEST DATA	3-1
4	OCCUPANT AND VEHICLE INFORMATION	4-1
APPENDIX A	PHOTOGRAPHS	
APPENDIX B	DATA PLOTS	
APPENDIX C	SID CONFIGURATION AND PERFORMANCE VERIFICATION	
APPENDIX D	DUMMY AND VEHICLE CALIBRATION DATA	

LIST OF FIGURES

<u>Figure No.</u>		<u>Page No.</u>
1	PRE-TEST CONDITIONS	3-4
2	PRE- AND POST-TEST MEASUREMENTS	4-3
3	SIDE IMPACT DUMMY (SID) LONGITUDINAL CLEARANCE DIMENSIONS	4-4
4	SIDE IMPACT DUMMY (SID) LATERAL CLEARANCE DIMENSIONS	4-5
5	VEHICLE SIDE MEASUREMENT	4-6
6	VEHICLE EXTERIOR STATIC CRUSH	4-8
7	TEST VEHICLE ACCELEROMETER LOCATIONS AND DATA SUMMARY	4-17
8	MDB FACE DIMENSIONS	4-18
9	MOVING DEFORMABLE BARRIER (MDB) ACCELEROMETER LOCATIONS	4-21
10	HIGH SPEED CAMERA LOCATIONS AND DATA	4-22

LIST OF TABLES

<u>Table No.</u>		<u>Page No.</u>
1	GENERAL TEST AND VEHICLE PARAMETER DATA	3-2
2	TEST VEHICLE DATA	3-3
3	CRASH TEST SUMMARY FOR TEST VEHICLE	3-5
4	CRASH TEST SUMMARY FOR SIDE IMPACTOR	3-6
5	POST-TEST OBSERVATIONS	3-7
6	SIDE IMPACT DUMMY (SID) TEST DATA SUMMARY	4-2
7	TEST VEHICLE EXTERIOR PROFILES FROM REFERENCE PLANE AND STATIC CRUSH	4-7
8	EXTERIOR STATIC CRUSH FOR SIDE IMPACTOR	4-19
9	TEST VEHICLE ACCELEROMETER LOCATIONS AND DATA SUMMARY	4-20
10	FUEL SYSTEM INTEGRITY POST IMPACT TEST DATA	4-23
11	FMVSS NO. 301 STATIC ROLLOVER DATA SHEET	4-24

SECTION 1
PURPOSE AND TEST PROCEDURE

This side impact test is part of the FY 94 FMVSS 214 "Dynamic" compliance test program, sponsored by the National Highway Traffic Safety Administration (NHTSA), under Contract No. DTNH22-93-C-02047. The purpose of this test was to evaluate side impact protection in a 1994 Dodge Intrepid 4 Door Sedan.

This test was conducted using the Office of Vehicle Safety Compliance's FMVSS 214 test procedure (TP-214D-03, dated May 17, 1993).

MGA does not endorse or certify products. The manufacturer's name appears solely for identification purposes only.

SECTION 2

SUMMARY OF SIDE IMPACT TEST

A stationary 1994 Dodge Intrepid 4 Door Sedan was impacted on the left or driver's side by a Moving Deformable Barrier (MDB) which was moving forward in a 27° crabbed position to the monorail at a velocity of 32.7 mph on June 3, 1994. The orientation angle of the striking vehicle was 90° counterclockwise with respect to the longitudinal axis of the struck vehicle. Pre- and post-test photographs of the test vehicle, the moving deformable barrier (MDB), and the side impact dummies (SIDs) are shown in Appendix A.

Two restrained Side Impact Dummies (SIDs) were placed in the driver (Pos. #1) and left rear (Pos. #4) designated seating positions according to instructions specified in the Laboratory Test Procedure. The side impact event was documented by nine high speed cameras. Camera locations and other pertinent camera information can be found in this report. Appendix B contains the vehicle and dummy response data traces.

The SIDs were instrumented with the following accelerometers.

1. Left Upper Rib (LUR) uniaxial accelerometer (Y-direction)
2. Left Lower Rib (LLR) uniaxial accelerometer (Y-direction)
3. Lower Thoracic Spine (T₁₂) uniaxial accelerometer (Y-direction)
4. Pelvic (PEV) section uniaxial accelerometer (Y-direction)

The summary of the side impact dummy (SID) configuration and performance verification test data are shown in Appendix C.

The driver's Thoracic Trauma Index (TTI) was 62 g's. Maximum pelvic Y acceleration was 69 g's.

The left rear passenger's TTI was 67 g's. Maximum pelvic Y acceleration was 79 g's.

TEST NOTES

The moving barrier y-axis accelerometer positioned at the rear axle collected invalid data due to a bad connection of the data cable.

SECTION 3
SUMMARY OF TEST DATA

TABLE 1
GENERAL TEST AND VEHICLE PARAMETER DATA

TEST VEHICLE INFORMATION:

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan
 Vehicle NHTSA No.: CR0312 VIN: 2B3ED46TXRH212031
 Vehicle Body Color: Black Cherry Month & Year of Manufacture: 12-93
 Engine Data: 6 cylinders; CID; 3.3 Liter; cc
 Placement X Longitudinal; or Lateral
 Transmission: 4 speed; Manual; X Automatic; X Overdrive
 Final Drive: Rear Wheel Drive; X Frt. Wheel Drive; Four Wheel Drive
 Odometer Reading 69 miles
 Options: X A/C; X Pwr. Steering.; X Pwr. Brakes; X Pwr. Windows
 Power Seats; X Tilt Wheel; X Power Door Locks; Self Leveling System

DATA FROM TIRE PLACARD:

Tire Pressure (at capacity): 32 psi FRONT
32 psi REAR
 Recommended Tire Size: P205/70R15
 Tires on Test Vehicle: P205/70R15 Manufacturer: Michelin

Vehicle Capacity Data:

Number of Occupants: 2 Front; 3 Rear; N/A 3rd Seat 5 Total
 Type of Front Seats: X Bucket; Bench; Split Bench
 Type of Front Seat Back: Fixed; X Adjustable with X Lever
 Vehicle Maximum Capacity Loading = 865 lbs (A)
 No. of Occupants x 150 lbs. = 750 lbs (B)
 Cargo Capacity (A-B) = 115 lbs

WEIGHT OF TEST VEHICLE WITH MAXIMUM FLUIDS:

Right Front	=	<u>1062</u> lbs	Right Rear	=	<u>597</u> lbs
Left Front	=	<u>1077</u> lbs	Left Rear	=	<u>598</u> lbs
TOTAL FRONT	=	<u>2139</u> lbs	TOTAL REAR	=	<u>1195</u> lbs
% of Total Vehicle Weight	=	<u>64.2</u> %;	% of Total Weight	=	<u>35.8</u> %
TOTAL WEIGHT	=	<u>3334</u> lbs			

TABLE 2
TEST VEHICLE DATA

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan

Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

CALCULATION OF VEHICLE'S TARGET TEST WEIGHT:

Total Test Vehicle Delivered Weight with Maximum Fluids = 3334 lbs
Maximum Cargo Carrying Capacity of Test Vehicle = 115 lbs
Weight of 2 Side Impact Dummies (2 x 168 lbs.) = 336 lbs
TEST VEHICLE TARGET WEIGHT: = 3785 lbs

ACTUAL WEIGHT OF TEST VEHICLE WITH 2 DUMMIES AND CARGO:

Right Front	= <u>1088</u> lbs	Right Rear	= <u>709</u> lbs
Left Front	= <u>1215</u> lbs	Left Rear	= <u>757</u> lbs
TOTAL FRONT	= <u>2303</u> lbs	TOTAL REAR	= <u>1466</u> lbs
% of Total Weight	= <u>61.1</u> %	% of Total Weight	= <u>38.9</u> %
TOTAL TEST WEIGHT	= <u>3769</u> lbs		

TEST VEHICLE ATTITUDE (all dimensions in inches):

CURB WEIGHT ATTITUDE: (in)

Right Front 28.9 Left Front 28.8 Right Rear 29.9 Left Rear 29.2

FULLY LOADED WEIGHT ATTITUDE: (in)

Right Front 28.7 Left Front 28.2 Right Rear 27.9 Left Rear 27.7

TEST ATTITUDE: (in)

Right Front 28.9 Left Front 28.6 Right Rear 28.3 Left Rear 29.0

Test Vehicle Wheelbase: 113.5 inches

C.G. = 44.1 inches rearward of front wheel centerline

TOTAL VEHICLE LENGTH:

Right Side = 190.0 in
Centerline = 202.7 in
Left Side = 190.0 in

FIGURE 1
PRE-TEST CONDITIONS

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan

Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

FRONT SEAT CUSHION PLACEMENT:

Total Length of Adjustment Travel: 8.7 in

Total Number of Adjustment Positions or Detents: 23 Detents

Test Position: 12th From Front

FRONT SEAT BACK ADJUSTMENT POSITION:

Seat Back Angle = 15.5° degrees

SECOND POSITION SEAT:

Total Length of Fore/Aft Adjustment Travel: Non Adjustable

Seat Back Adjustment Position: Non Adjustable

ADJUSTABLE STEERING COLUMN POSITION:

Adjusted to mid position (2nd position from full down)

WINDOW POSITIONS:

Left Front closed Left Rear closed

Right Front removed Right Rear removed

Note: Windows will be in closed position on struck side of test vehicle and in open position on opposite side.

AMOUNT OF STODDARD SOLVENT IN FUEL TANK: Fuel system usable capacity = 18.0 gallons

Test Volume: 16.6 gallons (92.2% of capacity)

LOCATIONS OF IMPACT POINT ON TEST VEHICLE SIDE TO BE IMPACTED:

Wheelbase: = 113.5 in

Impact Point is 19.8 in rearward of front axle centerline (which is 37 inches forward of the wheelbase midpoint)

TABLE 3
CRASH TEST SUMMARY FOR TEST VEHICLE

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan

Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

Overall Length = 202.7 in; Overall Width = 72.6 in

TEST WEIGHT:

Right Front	=	<u>1088</u> lbs	Right Rear	=	<u>709</u> lbs
Left Front	=	<u>1215</u> lbs	Left Rear	=	<u>757</u> lbs
TOTAL FRONT	=	<u>2303</u> lbs	TOTAL REAR	=	<u>1466</u> lbs
TOTAL VEHICLE WEIGHT <u>3769</u> lbs					
Wheelbase = <u>113.5</u> in					
Longitudinal C.G. front Center of Front Axle			= <u>44.1</u> in		
Impact Angle with Respect to Impactor			= <u>90°</u> degrees		

MAXIMUM EXTERIOR STATIC CRUSH:

1. LEVEL 1 (10.4 in above ground) = 6.3 in
2. LEVEL 2 (19.3 in above ground) = 14.7 in
3. LEVEL 3 (24.3 in above ground) = 13.2 in
4. LEVEL 4 (34.5 in above ground) = 11.9 in
5. LEVEL 5 (51.5 in above ground) = 5.4 in

Maximum Post-Test Intrusion = 14.7 in

OCCUPANTS:

	<u>Front Passenger</u>	<u>Rear Passenger</u>
Type of Dummy	<u>SID</u>	<u>SID</u>
Restraints Used	<u>3 pt. lap &</u> <u>shoulder belt</u> <u>with airbag</u>	<u>3 pt. lap &</u> <u>shoulder belt</u>

INSTRUMENTATION:

Number of Vehicle Data Channels:	=	<u>16</u>
Number of Cameras: Onboard Vehicle	=	<u>3</u>
Offboard Vehicle	=	<u>4</u>
Deformable Barrier	=	<u>2</u>
TOTAL	=	<u>9</u>

TABLE 4

CRASH TEST SUMMARY FOR SIDE IMPACTORYear/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994POSITION OF IMPACT (MDB) ON MONORAIL:Crabbed 27° to leftMDB DETAILS:

Overall Width of Framework Carriage	=	<u>49.3</u> in
Overall Length of MDB (incl. honeycomb impact face)	=	<u>162</u> in
Wheelbase of Framework Carriage	=	<u>102</u> in
Tread of Framework Carriage (Front & Rear)	=	<u>74</u> in
C.G. Location Rearward of Front Axle	=	<u>43.4</u> in
C.G. Location From Center Line	=	<u>-.3</u> in
C.G. Location Above Ground Level	=	<u>19.2</u> in

MDB WEIGHT:

Left Front	=	<u>1095</u> lbs	Left Rear	=	<u>413</u> lbs
Right Front	=	<u>624</u> lbs	Right Rear	=	<u>858</u> lbs
TOTAL FRONT	=	<u>1719</u> lbs	TOTAL REAR	=	<u>1271</u> lbs
TOTAL MDB WEIGHT = <u>2990</u> lbs					

Impact Angle (MDB C/L to Target Vehicle C/L) = 90° degreesImpact Speed = Primary: 32.7 mph Secondary: 32.8 mphMAXIMUM STATIC CRUSH OF HONEYCOMB IMPACT FACE:

1. Row A Top of Stack (33 in)	=	<u>3.6</u> in
2. Row B Mid Stack (27 in)	=	<u>2.4</u> in
3. Row C Top of Bumper (21 in)	=	<u>2.6</u> in
4. Row D Center of Bumper (17 in)	=	<u>4.0</u> in

INSTRUMENTATION:Number of MDB Data Channels = 7

TABLE 5
POST-TEST OBSERVATIONS

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan

Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

VISIBLE DUMMY CONTACT POINTS:

	<u>LEFT FRONT SID</u>	<u>LEFT REAR SID</u>
Head	<u>none</u>	<u>to "C" Post</u>
Arm	<u>to door trim panel</u>	<u>to door trim panel</u>
Pelvis	<u>to door trim panel</u>	<u>to door trim panel</u>
Left Knee	<u>to door trim panel</u>	<u>to door trim panel</u>
Right Knee	<u>to left knee</u>	<u>to left knee</u>

DOOR OPENING:

	<u>LEFT SIDE</u>	<u>RIGHT SIDE</u>
Front	<u>remained closed</u>	<u>remained closed</u>
Rear	<u>remained closed</u>	<u>remained closed</u>

MDB DISTANCE FROM TARGET IMPACT POINT:

Horizontal: 0.0 in rearward Vertical: 0.9 in high

ARM REST LOCATIONS:

Front: 7.4 inches below window sill

Rear: 10.0 inches below window sill

SEAT CRUSH:

Driver Seat Back: 1.5 inches Driver Seat Cushion: 3.0 inches

Passenger Seat Back: 1.7 inches Passenger Seat Cushion: 5.4 inches

GLAZING DAMAGE:

Windshield cracked, both front and rear door glass broken

PILLAR PERFORMANCE:

No "A" or "B" pillar separation evident

SILL SEPARATION:

No sill separation noted

OTHER NOTABLE IMPACT EFFECTS:

None

SECTION 4
OCCUPANT AND VEHICLE INFORMATION

TABLE 6

SIDE IMPACT DUMMY (SID) TEST DATA SUMMARYYear/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

	Front Dummy ID # 269				Rear Dummy ID # 271			
	Pos. Direct.		Neg. Direct		Pos. Direct.		Neg. Direct	
	Max (g)	Time (msec)	Max (g)	Time (msec)	Max (g)	Time (msec)	Max (g)	Time (msec)
RIB ACCELERATIONS:								
	Upper Rib Lateral.....Y	41	-10.4	87	78.4	46	-14.2	72
	Upper Rib Lateral....Y(R)	41	-10.6	86	86.8	46	-22.3	72
	Lower Rib Lateral.....Y	43	-12.2	110	78.2	46	-29.5	71
	Lower Rib Lateral.....Y(R)	43	-12.4	110	75.2	46	-28.8	71
SPINE ACCELERATIONS:								
	Lower Lateral.....Y	45	-12.1	111	55.2	46	-13.5	77
	Lower Lateral.....Y(R)	45	-12.3	110	61.2	46	-13.6	77
PELVIC ACCELERATIONS:								
	Lateral.....Y	39	-16.9	98	79.0	39	-8.8	95
	Lateral.....Y(R)	39	-17.1	98	81.6	39	-7.7	94

REFERENCE:


Positive Direction - Longitudinal (X) = forward

Lateral (Y) = to right

Vertical (Z) = up

Note: Y(R) denotes redundant Y direction accelerometer.

FIGURE 2
PRE- AND POST-TEST MEASUREMENTS



D = Length at Centerline

R = Right Side Length

S = Left Side Length

T = Width at B Post

E & L = Bumper Thickness


J1 = To Pinch Weld

J2 = To Sill

Units: in

LOCATION	PRE-TEST	POST-TEST	Δ CHANGE
A	113.5	111.8	-1.7
B	44.4	43.4	-1.0
C	44.8	44.3	-0.5
D	202.7	199.5	-3.2
E	11.2	11.2	0
F	8.8	9.4	0.6
G	8.5	8.8	0.3
H	8.0	8.0	0
I	8.5	9.5	1.0
J1/J2	8.5/7.5	7.6/7.5	-0.9/0
K	10.4	10.8	0.4
L	13.1	13.1	0
M	12.5	12.5	0
N	24.8	22.5	-2.3
O	35.2	33.3	-1.9
P	51.3	45.4	-5.9
Q	16.7	15.8	-0.9
R	190.0	188.1	-1.9
S	190.0	189.8	-0.2
T	72.6	60.6	-12.0

FIGURE 3
SIDE IMPACT DUMMY (SID) LONGITUDINAL CLEARANCE DIMENSIONS



LEFT SIDE VIEW


NOTE: 2-DOOR VEHICLE SHOWN.
 REAR DUMMY PHX & PHZ
 MEASUREMENTS FOR A 4-DOOR
 VEHICLE WOULD USE THE C-POST
 STRIKER AS A REFERENCE POINT

NOTE: All dimensions are in inches

	DRIVER ID #269	LEFT REAR PASSENGER ID #271	
HH	15.8	N/A	
HW	24.8	N/A	
HB	N/A	30.9	
CD	20.8	CB	25.4
CS	12.8	N/A	
KDL	5.0	KBL	10.8
KDR	5.1	KBR	11.5
PA°	23.3°	23.3°	
PHX	8.0	10.9	
PHZ	4.0	12.8	

NOTE: 2-door vehicle shown. Rear dummy PHX & PHZ measurements for 4-door vehicle would use the C-post striker as reference point.

FIGURE 4
SIDE IMPACT DUMMY (SID) LATERAL CLEARANCE DIMENSIONS




NOTE: All dimensions are in inches

	DRIVER ID #269	LEFT REAR PASSENGER ID #271
HR	4.4	5.0
HS	11.4	9.8
AD	5.9	4.1
HD	6.0	7.5

FIGURE 5
VEHICLE SIDE MEASUREMENTS

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan
Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994



As tested height measurements are with respect to ground along the vertical 33" line shown above:

<u>33" Side Profile</u>	
Level 5 @ Window Top	= <u>51.5</u> in
Level 4 @ Window Sill	= <u>34.5</u> in
Level 3 @ Mid Door	= <u>24.3</u> in
Level 2 @ Occupant H-Point	= <u>19.3</u> in
Level 1 @ Axle Centerline Height (or Sill Top Height	= <u>10.4</u> in

TABLE 7

TEST VEHICLE EXTERIOR PROFILES FROM REFERENCE PLANE AND STATIC CRUSH


LEVEL 1 AT AXLE CENTER LINE

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

Longitudinal Distance (in)	PRE-TEST (in)	POST-TEST (in)	STATIC CRUSH (in)
-72	---	---	---
-66	---	---	---
-60	---	---	---
-54	---	---	---
-48	---	---	---
-42	---	---	---
-36	---	---	---
-30	---	---	---
-24	---	---	---
-18	---	---	---
-12	---	---	---
-6	---	---	---
0	31.4	33.3	1.9 (impact point)
6	31.4	34.9	3.5
12	31.3	35.7	4.4
18	31.4	36.7	5.3
24	31.3	37.6	6.3
30	31.2	37.5	6.3
36	31.2	37.2	6.0
42	31.2	37.2	6.0
48	31.2	37.3	6.1
54	31.2	36.7	5.5
60	31.2	36.0	4.8
66	31.2	35.2	4.0
72	31.4	34.9	3.5
78	---	---	---
84	---	---	---
90	---	---	---
96	---	---	---
102	---	---	---
108	---	---	---
114	---	---	---
120	---	---	---
126	---	---	---
132	---	---	---
138	---	---	---

Reference plane is parallel to test vehicle longitudinal centerline
 Given dimensions = reference plane to car body

FIGURE 6
VEHICLE EXTERIOR STATIC CRUSH



LEVEL 1 AT AXLE CENTER LINE

TABLE 7

TEST VEHICLE EXTERIOR PROFILES FROM REFERENCE PLANE AND STATIC CRUSH


LEVEL 2 AT OCCUPANT H-POINT

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

Longitudinal Distance (in)	PRE-TEST (in)	POST-TEST (in)	STATIC CRUSH (in)
-72	---	---	---
-66	---	---	---
-60	---	---	---
-54	<u>32.0</u>	<u>32.0</u>	<u>0</u>
-48	<u>30.6</u>	<u>31.0</u>	<u>0.4</u>
-42	<u>29.5</u>	<u>30.0</u>	<u>0.5</u>
-36	<u>28.6</u>	<u>29.5</u>	<u>0.9</u>
-30	---	---	---
-24	---	---	---
-18	---	---	---
-12	---	---	---
-6	---	---	---
0	<u>27.8</u>	<u>36.4</u>	<u>8.6</u> (impact point)
6	<u>27.8</u>	<u>38.8</u>	<u>11.0</u>
12	<u>27.6</u>	<u>41.4</u>	<u>13.8</u>
18	<u>27.6</u>	<u>41.7</u>	<u>14.1</u>
24	<u>27.6</u>	<u>42.0</u>	<u>14.4</u>
30	<u>27.6</u>	<u>42.2</u>	<u>14.6</u>
36	<u>27.5</u>	<u>42.2</u>	<u>14.7</u>
42	<u>27.4</u>	<u>41.9</u>	<u>14.5</u>
48	<u>27.5</u>	<u>41.9</u>	<u>14.4</u>
54	<u>27.6</u>	<u>40.6</u>	<u>13.0</u>
60	<u>27.8</u>	<u>39.6</u>	<u>11.8</u>
66	<u>27.8</u>	<u>37.7</u>	<u>9.9</u>
72	<u>27.9</u>	<u>35.4</u>	<u>7.5</u>
78	---	---	---
84	---	---	---
90	---	---	---
96	---	---	---
102	---	---	---
108	<u>29.0</u>	<u>30.1</u>	<u>1.1</u>
114	<u>29.7</u>	<u>30.5</u>	<u>0.8</u>
120	<u>30.6</u>	<u>30.9</u>	<u>0.3</u>
126	<u>31.6</u>	<u>31.8</u>	<u>0.2</u>
132	<u>33.6</u>	<u>33.6</u>	<u>0</u>
138	---	---	---

Reference plane is parallel to test vehicle longitudinal centerline
 Given dimensions = reference plane to car body

FIGURE 6 (Cont'd)
VEHICLE EXTERIOR STATIC CRUSH



LEVEL 2 AT OCCUPANT H-POINT

TABLE 7

TEST VEHICLE EXTERIOR PROFILES FROM REFERENCE PLANE AND STATIC CRUSH


LEVEL 3 AT MID-DOOR

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

Longitudinal Distance (in)	PRE-TEST (in)	POST-TEST (in)	STATIC CRUSH (in)
-72	---	---	---
-66	---	---	---
-60	---	---	---
-54	33.6	35.2	1.6
-48	31.6	32.0	0.4
-42	30.2	30.8	0.6
-36	29.0	29.6	0.6
-30	---	---	---
-24	---	---	---
-18	---	---	---
-12	---	---	---
-6	27.4	29.1	1.7
0	27.5	35.9	8.4 (impact point)
6	27.4	39.1	11.7
12	27.4	39.4	12.0
18	27.3	39.3	12.0
24	27.2	39.3	12.1
30	27.1	39.3	12.2
36	27.0	39.3	12.3
42	27.0	40.2	13.2
48	27.0	39.4	12.4
54	27.0	38.7	11.7
60	27.0	38.3	11.3
66	27.1	36.3	9.2
72	27.2	36.3	9.1
78	27.3	30.4	3.1
84	---	---	---
90	---	---	---
96	---	---	---
102	---	---	---
108	28.5	29.4	0.9
114	29.4	30.0	0.6
120	30.3	30.7	0.4
126	31.7	31.9	0.2
132	34.5	34.3	-0.2
138	---	---	---

Reference plane is parallel to test vehicle longitudinal centerline
 Given dimensions = reference plane to car body

FIGURE 6
VEHICLE EXTERIOR STATIC CRUSH



LEVEL 3 AT MID-DOOR

TABLE 7

TEST VEHICLE EXTERIOR PROFILES FROM REFERENCE PLANE AND STATIC CRUSH


LEVEL 4 AT WINDOW SILL

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

Longitudinal Distance (in)	PRE-TEST (in)	POST-TEST (in)	STATIC CRUSH (in)
-72	---	---	---
-66	---	---	---
-60	---	---	---
-54	---	---	---
-48	33.9	34.2	0.3
-42	32.8	33.3	0.5
-36	31.9	32.7	0.8
-30	31.4	32.4	1.0
-24	31.1	32.2	1.1
-18	30.8	32.2	1.4
-12	30.7	32.0	1.3
-6	30.5	32.0	1.5
0	30.3	31.7	1.4 (impact point)
6	30.4	36.0	5.6
12	30.4	37.4	7.0
18	30.4	38.6	8.2
24	30.4	38.7	8.3
30	30.2	39.1	8.9
36	30.3	39.6	9.3
42	30.0	41.9	11.9
48	30.5	40.9	10.4
54	30.5	39.9	9.4
60	30.5	39.3	8.8
66	30.5	37.5	7.0
72	30.5	34.7	4.2
78	30.6	32.4	1.8
84	30.8	33.3	2.5
90	31.0	33.0	2.0
96	31.3	32.8	1.5
102	31.5	33.0	1.5
108	31.9	32.9	1.0
114	32.4	33.2	0.8
120	33.0	33.5	0.5
126	34.0	34.2	0.2
132	---	---	---
138	---	---	---

Reference plane is parallel to test vehicle longitudinal centerline
 Given dimensions = reference plane to car body

FIGURE 6
VEHICLE EXTERIOR STATIC CRUSH



LEVEL 4 AT WINDOW SILL

TABLE 7

TEST VEHICLE EXTERIOR PROFILES FROM REFERENCE PLANE AND STATIC CRUSH
LEVEL 5 AT WINDOW TOP

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan


Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

Longitudinal Distance (in)	PRE-TEST (in)	POST-TEST (in)	STATIC CRUSH (in)
-72	---	---	---
-66	---	---	---
-60	---	---	---
-54	---	---	---
-48	---	---	---
-42	---	---	---
-36	---	---	---
-30	---	---	---
-24	---	---	---
-18	---	---	---
-12	---	---	---
-6	---	---	---
0	---	---	---
6	---	---	---
12	---	---	---
18	---	---	---
24	42.1	44.1	2.0
30	41.8	44.6	2.8
36	41.9	45.4	3.5
42	41.9	45.9	4.0
48	41.9	47.3	5.4
54	42.1	45.7	3.6
60	42.2	45.0	2.8
66	42.4	44.6	2.2
72	---	---	---
78	---	---	---
84	---	---	---
90	---	---	---
96	---	---	---
102	---	---	---
108	---	---	---
114	---	---	---
120	---	---	---
126	---	---	---
132	---	---	---
138	---	---	---

(impactpoint)

Reference plane is parallel to test vehicle longitudinal centerline
Given dimensions = reference plane to car body

FIGURE 6
VEHICLE EXTERIOR STATIC CRUSH



LEVEL 5 AT WINDOW TOP

FIGURE 7

TEST VEHICLE ACCELEROMETER LOCATIONS AND DATA SUMMARY

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan

Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994





FIGURE 8
MDB FACE DIMENSIONS

Measurements in inches

A = 15.0
B = 22.0
C = 66.0
D = 66.0
E = 66.0



Measurements in inches

A = 11.0
B = 13.1
C = 21.1
D = 33.1




TABLE 8

EXTERIOR STATIC CRUSH FOR SIDE IMPACTORYear/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

Location	Top of Stack (33 inches)	Mid-Stack (27 inches)	Top of Bumper (21 inches)	Center of Bumper (17 inches)
Horizontal Distance From Center	Crush (inches)	Crush (inches)	Crush (inches)	Crush (inches)
32"	3.6	2.0	1.2	1.0
28"	1.9	0.5	1.1	1.2
24"	0.5	0.4	0.6	1.2
20"	-0.1	0.4	0.7	1.2
16"	-0.1	0.4	0.5	1.2
12"	-0.1	0.3	0.4	1.2
8"	-0.2	0.3	0.3	1.3
4"	-0.2	0.2	0.3	1.3
0"	-0.3	0.2	0.2	1.2
4"	-0.3	0.2	0.2	1.2
8"	-0.3	0.1	0.2	1.4
12"	-0.4	0.1	0.2	1.4
16"	-0.3	0.1	0.2	1.4
20"	-0.5	0.6	0.2	1.6
24"	-0.5	0.4	0.7	2.2
28"	0.6	0.6	1.9	3.5
32"	3.0	2.4	2.6	4.0

Left Side

Right Side

TABLE 9

TEST VEHICLE ACCELEROMETER LOCATIONS AND DATA SUMMARYYear/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

Accel. No.	Description	Coordinates (in)			Long. (X) Maximums		Lat. (Y) Maximums		Vert. (Z) Maximums		Resultant
		X	Y	Z	Pos.	Neg.	Pos.	Neg.	Pos.	Neg.	
1	Rt. Side Sill @ Front Seat	117.9	27.9	11.9	2.8	-3.2	23.4	-5.6	5.3	-6.6	23.4
2	Rt. Side Sill @ Rear Seat	84.4	28.3	11.5	2.2	-4.2	27.3	-6.8	4.1	-5.7	27.5
3	Rr. Floorpan Above Axle	40.0	0	19.0	4.3	-5.3	20.9	-3.4	15.0	-12.9	22.4
4	Left Side Sill @ Rr. Seat*	82.3	-26.8	8.8	---	---	45.9	-6.9	---	---	---
5	Left Side Sill @ Frt. Seat*	114.0	-26.8	8.8	---	---	66.3	-22.1	---	---	---
6	A-Post Lower	135.8	-29.5	16.3	---	---	68.0	-28.7	---	---	---
7	B-Post Lower	96.0	-30.4	17.5	---	---	222.8	-36.9	---	---	---
8	B-Post Mid	96.1	-30.4	30.0	---	---	152.8	-34.1	---	---	---
9	Right Rear Occupant Compartment	81.6	15.6	10.8	---	---	28.4	-7.6	---	---	---
10	Driver Left Seat Track	103.0	-21.5	11.0	---	---	60.5	-23.5	---	---	---


*Reference: X - Rear Bumper (+ Forward)
Y - Vehicle Centerline (+ To right)
Z - Ground Level (+ Up)

FIGURE 9

MOVING DEFORMABLE BARRIER (MDB) ACCELEROMETER LOCATIONS

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan

Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994




Accel. No.	Location	Coordinates (in)			Pos. Direct.		Neg. Direct.	
		X	Y	Z	Max (g)	Time (msec)	Max (g)	Time (msec)
1	MDB Center of Gravity							
	Longitudinal ... X				4.2	121	-10.2	32
	Lateral Y	-43.0	0	19.0	N/A	N/A	-15.9	37
	Vertical Z				12.7	46	-7.7	67
	Resultant R				20.8	40		
2	Rear Frame Member							
	Longitudinal ... X	-102.0	-24.6	24.5	4.0	168	-14.4	35
	Lateral Y				N/A	N/A	N/A	N/A

* Reference: X = Front Axle (+Forward)
Y = Vehicle Centerline (+ To Right)
Z = Ground Level (+ Up)

FIGURE 10
HIGH SPEED CAMERA LOCATIONS AND DATA

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan
 Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994



Camera No.	View	Coordinates (in)			Angle	Lens (mm)	Film Speed (fps)
		X*	Y*	Z*			
	Real Time					10	24
1	Top Pointer	0	15.0	193.7		13	1143
2	Top Wide	15.7	0	211.0		8	1205
3	Cart Pointer					35	1000
4	Cart					13	1010
5	Right Impact	63.8	-348.4	44.9	45°	35	930
6	Left Impact	-138.6	152.0	65.2	45°	13	1030
7	Onboard Hood					13	1000
8	Onboard Driver					7.5	893
9	Onboard Passenger					8	917

* Reference: (from point of impact)
 +X = Forward
 +Y = To Right
 +Z = Upward

TABLE 10
FUEL SYSTEM INTEGRITY POST IMPACT TEST DATA

FMVSS NO. 301

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan
Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

Test vehicle fuel tank filled to 92% to 94% of manufacturer's "useable" capacity and with electric fuel pump operating (if it will operate without engine operation). Part 572 test dummies located at each front designated seating position.

TEST VEHICLE IMPACT TYPE: X Side Impact MDB (32.7 mph)

FUEL SPILLAGE MEASUREMENT:


1. From impact until vehicle motion ceases
2. For 5 minute period after vehicle motion ceases
3. For next 25 minutes

ACTUAL	MAX ALLOWED
0	1 oz.
0	5 oz.
0	1 oz./1 MIN

SOLVENT SPILLAGE DETAILS:

None

TABLE 11

FMVSS NO. 301 STATIC ROLLOVER DATA SHEETYear/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994TEST PHASE: 0° - 90°I. DETERMINATION OF SOLVENT COLLECTION TIME PERIOD:

Rollover Fixture 90° Rotation Time 2 minutes 54 seconds
 (Spec. Range = 1 to 3 minutes)

FMVSS 301 Position Hold Time + 5 minutes 0 seconds

TOTAL 7 minutes 54 seconds

Next whole minute interval 8 minutes

II. FMVSS 301 REQUIREMENTS:

(1) Time Period

First 5 min FROM onset of rotation	6th min.	7th min.	8th min. if reqd.
------------------------------------	----------	----------	-------------------

(2) Maximum Allowable Solvent Spillage

5 ounces	1 ounce	1 ounce	1 ounce
----------	---------	---------	---------

III. ACTUAL TEST VEHICLE SOLVENT SPILLAGE:

0	0	0	0
---	---	---	---


Note: Record Spillage for whole minute intervals only as determined above.

IV. SOLVENT SPILLAGE LOCATIONS(S): None

TABLE 11
FMVSS NO. 301 STATIC ROLLOVER DATA SHEET (cont.)

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan
Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

TEST PHASE: 90° - 180°



I. DETERMINATION OF SOLVENT COLLECTION TIME PERIOD:

Rollover Fixture 90° Rotation Time 2 minutes 34 seconds
(Spec. Range = 1 to 3 minutes)

FMVSS 301 Position Hold Time + 5 minutes 0 seconds
TOTAL 7 minutes 34 seconds
Next whole minute interval 8 minutes

II. FMVSS 301 REQUIREMENTS:

(1) Time Period

First 5 min FROM onset of rotation	6th min.	7th min.	8th min. if reqd.
------------------------------------	----------	----------	-------------------

(2) Maximum Allowable Solvent Spillage

5 ounces	1 ounce	1 ounce	1 ounce
----------	---------	---------	---------


III. ACTUAL TEST VEHICLE SOLVENT SPILLAGE:

0	0	0	0
---	---	---	---

Note: Record Spillage for whole minute intervals only as determined above.

IV. SOLVENT SPILLAGE LOCATIONS(S): None

TABLE 11

FMVSS NO. 301 STATIC ROLLOVER DATA SHEET (cont.)Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door SedanVehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994TEST PHASE: 180° - 270°I. DETERMINATION OF SOLVENT COLLECTION TIME PERIOD:

Rollover Fixture 90° Rotation Time 2 minutes 17 seconds
 (Spec. Range = 1 to 3 minutes)

FMVSS 301 Position Hold Time + 5 minutes 0 seconds
 TOTAL 7 minutes 17 seconds
 Next whole minute interval 8 minutes

II. FMVSS 301 REQUIREMENTS:

(1) Time Period

First 5 min FROM onset of rotation	6th min.	7th min.	8th min. if reqd.
------------------------------------	----------	----------	-------------------

(2) Maximum Allowable Solvent Spillage

5 ounces	1 ounce	1 ounce	1 ounce
----------	---------	---------	---------

III. ACTUAL TEST VEHICLE SOLVENT SPILLAGE:

0	0	0	0
---	---	---	---


Note: Record Spillage for whole minute intervals only as determined above.

IV. SOLVENT SPILLAGE LOCATIONS(S): None

TABLE 11
FMVSS NO. 301 STATIC ROLLOVER DATA SHEET (cont.)

Year/Make/Model/Body Style: 1994/Dodge/Intrepid/4 Door Sedan
Vehicle NHTSA No.: CR0312 TEST DATE: June 3, 1994

TEST PHASE: 270° - 360°



I. DETERMINATION OF SOLVENT COLLECTION TIME PERIOD:

Rollover Fixture 90° Rotation Time 2 minutes 38 seconds
(Spec. Range = 1 to 3 minutes)

FMVSS 301 Position Hold Time + 5 minutes 0 seconds

TOTAL 7 minutes 38 seconds

Next whole minute interval 8 minutes

II. FMVSS 301 REQUIREMENTS:

(1) Time Period

First 5 min FROM onset of rotation	6th min.	7th min.	8th min. if reqd.
------------------------------------	----------	----------	-------------------

(2) Maximum Allowable Solvent Spillage

5 ounces	1 ounce	1 ounce	1 ounce
----------	---------	---------	---------

III. ACTUAL TEST VEHICLE SOLVENT SPILLAGE:

0	0	0	0
---	---	---	---

Note: Record Spillage for whole minute intervals only as determined above.

IV. SOLVENT SPILLAGE LOCATIONS(S): None

APPENDIX A - PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

	<u>Page No.</u>
Photo No. A-1 - Pre-Test Front View of Test Vehicle	A-1
Photo No. A-2 - Post-Test Front View of Test Vehicle	A-2
Photo No. A-3 - Pre-Test Rear View of Test Vehicle	A-3
Photo No. A-4 - Post-Test Rear View of Test Vehicle	A-4
Photo No. A-5 - Pre-Test Left Side View of Test Vehicle	A-5
Photo No. A-6 - Post-Test Left Side View of Test Vehicle	A-6
Photo No. A-7 - Pre-Test MDB Positioned Against Vehicle (left side)	A-7
Photo No. A-8 - Pre-Test MDB Positioned Against Vehicle (right side)	A-8
Photo No. A-9 - Pre-Test MDB Position Against Vehicle Overhead View	A-9
Photo No. A-10 - Post-Test MDB and Vehicle Left Side Front View	A-10
Photo No. A-11 - Post-Test MDB and Vehicle Right Side Rear View	A-11
Photo No. A-12 - Pre-Test MDB Top View	A-12
Photo No. A-13 - Post-Test MDB Top View	A-13
Photo No. A-14 - Pre-Test MDB Front View	A-14
Photo No. A-15 - Post-Test MDB Front View	A-15
Photo No. A-16 - Pre-Test MDB Left Side View	A-16
Photo No. A-17 - Post-Test MDB Left Side View	A-17
Photo No. A-18 - Pre-Test MDB Right Side View	A-18
Photo No. A-19 - Post-Test MDB Right Side View	A-19
Photo No. A-20 - Post-Test MDB and Vehicle Overhead View	A-20
Photo No. A-21 - Pre-Test Driver Dummy Right Side View	A-21
Photo No. A-22 - Post-Test Driver Dummy Right Side View	A-22
Photo No. A-23 - Pre-Test Driver Dummy Left Side View	A-23
Photo No. A-24 - Post-Test Driver Dummy Left Side View	A-24
Photo No. A-25 - Pre-Test Driver Dummy Left Side View (Door Open)	A-25
Photo No. A-26 - Post-Test Driver Dummy Impact	A-26
Photo No. A-27 - Pre-Test Passenger Dummy Right Side View	A-27
Photo No. A-28 - Post-Test Passenger Dummy Right Side View	A-28
Photo No. A-29 - Pre-Test Passenger Dummy Left Side View	A-29
Photo No. A-30 - Post-Test Passenger Dummy Left Side View	A-30

TABLE OF PHOTOGRAPHS

	<u>Page No.</u>
Photo No. A-31 - Pre-Test Passenger Dummy Left Side View (Door Open)	A-31
Photo No. A-32 - Post-Test Passenger Dummy Impact	A-32
Photo No. A-33 - Tire Placard	A-33
Photo No. A-34 - Vehicle Certification Label	A-34
Photo No. A-35 - Impact	A-35
Photo No. A-36 - Rollover 90°	A-36
Photo No. A-37 - Rollover 180°	A-37
Photo No. A-38 - Rollover 270°	A-38
Photo No. A-39 - Rollover 360°	A-39




Photo No. A-1 - Pre-Test Front View of Test Vehicle




Photo No. A-2 - Post-Test Front View of Test Vehicle

 **PRE-TEST**
FMVSS 214 COMPLIANCE
NHTSA NO. CR0312
1994 DODGE INTREPID

NHTSA NO. CR0312
30/15 90 DEG IMPACT (MD)
JUNE 3, 1994
MGA RESEARCH CORPORATION

Photo No. A-3 - Pre-Test Rear View of Test Vehicle



Photo No. A-4 - Post-Test Rear View of Test Vehicle




Photo No. A-5 - Pre-Test Left Side View of Test Vehicle

mga
mga research corporation
PRE-TEST
FMVSS 214 COMPLIANCE
NHTSA NO. CR0312
1994 DODGE INTREPID

Photo No. A-7 - Pre-Test MDB Positioned Against Vehicle (left side)




Photo No. A-8 - Pre-Test MDB Positioned Against Vehicle (right side)




Photo No. A-9 - Pre-Test MDB Position Against Vehicle Overhead View



Photo No. A-10 - Post-Test MDB and Vehicle Left Side Front View




Photo No. A-11 - Post-Test MDB and Vehicle Right Side Rear View




Photo No. A-12 - Pre-Test MDB Top View




Photo No. A-13 - Post-Test MDB Top View



Photo No. A-14 - Pre-Test MDB Front View




Photo No. A-15 - Post-Test MDB Front View



Photo No. A-16 - Pre-Test MDB Left Side View

POST-TEST
FMVSS 214 COMPLIANCE
NHTSA NO. CR0312
1994 DODGE INTREPID




Photo No. A-17 - Post-Test MDB Left Side View

FMVSS 214 COMPLIANCE
NHTSA NO. CR0312
1994 DODGE INTREPID




Photo No. A-18 - Pre-Test MDB Right Side View

POST-TEST
FHWSS 214 COMPLIANCE
NHTSA NO. CR0312
1994 DODGE INTREPID

Photo No. A-19 - Post-Test MDB Right Side View




Photo No. A-20 - Post-Test MDB and Vehicle Overhead View



Photo No. A-21 - Pre-Test Driver Dummy Right Side View



Photo No. A-22 - Post-Test Driver Dummy Right Side View



Photo No. A-23 - Pre-Test Driver Dummy Left Side View




Photo No. A-24 - Post-Test Driver Dummy Left Side View



Photo No. A-25 - Pre-Test Driver Dummy Left Side View (Door Open)




photo No. A-26 - Post-Test Driver Dummy Impact



Photo No. A-27 - Pre-Test Passenger Dummy Right Side View




Photo No. A-28 - Post-Test Passenger Dummy Right Side View



Photo No. A-29 - Pre-Test Passenger Dummy Left Side View




Photo No. A-30 - Post-Test Passenger Dummy Left Side View



Photo No. A-31 - Pre-Test Passenger Dummy Left Side View (Door Open)

POST-TEST
FMVSS 214 COMPLIANCE
NHTSA NO. CR0312
1994 DODGE INTREPID

Photo No. A-32 - Post-Test Passenger Dummy Impact

	VEHICLE CAPACITY OR LESS
1ST SEAT	* 3 PASS
2ND SEAT	3 PASS
LUGGAGE	115 LBS-52 KG
TOTAL	* 6 PASS
TOTAL WEIGHT	* 1015 LBS-461 KG
TIRE PRESSURE COLD	32 PSI 220 KPA FRONT AND REAR
*REDUCE VEHICLE CAPACITY TO 2 PASSENGERS IN 1ST SEAT- (685 LBS-309 KG) 5 PASS TOTALD WHEN EQUIPPED WITH BUCKET SEATS WITHOUT CENTER SEAT	
MINIMUM TIRE SIZE P205/70R15 95S STANDARD COLD	
SEE OWNER'S MANUAL FOR ADDITIONAL DATA	
PRINTED IN U.S.A. 4895 610	

Photo No. A-33 - Tire Placard

	VEHICLE CAPACITY OR LESS
1ST SEAT	12 PASS
2ND SEAT	2 PASS
3RD SEAT	17 SEAT-32 LB
TOTAL	31 PASS
TOTAL WEIGHT	~1015 LBS-44" L
1ST PASSENGER CASH	32.00
2ND PASSENGER CASH	220.00
	VEHICLE SEAT BELT

A-34




Photo No. A-35 - Impact

A-35




Photo No. A-36 - Rollover 90°



Photo No. A-37 - Rollover 180°



Photo No. A-38 - Rollover 270°

A-38




Photo No. A-39 - Rollover 360°

A-39

APPENDIX B - DATA PLOTS

Table of Data Plots

<u>Occupant:</u>	<u>Page No.</u>
Figure B-1 - Driver Upper Rib Y Acceleration vs. Time	B-1
Figure B-2 - Driver Upper Rib Y Velocity vs. Time	B-2
Figure B-3 - Driver Lower Rib Y Acceleration vs. Time	B-3
Figure B-4 - Driver Lower Rib Y Velocity vs. Time	B-4
Figure B-5 - Driver Lower Spine Y Acceleration vs. Time	B-5
Figure B-6 - Driver Lower Spine Y Velocity vs. Time	B-6
Figure B-7 - Driver Pelvis Y Acceleration vs. Time	B-7
Figure B-8 - Driver Pelvis Y Velocity vs. Time	B-8
Figure B-9 - Passenger Upper Rib Y Acceleration vs. Time	B-9
Figure B-10 - Passenger Upper Rib Y Velocity vs. Time	B-10
Figure B-11 - Passenger Lower Rib Y Acceleration vs. Time	B-11
Figure B-12 - Passenger Lower Rib Y Velocity vs. Time	B-12
Figure B-13 - Passenger Lower Spine Y Acceleration vs. Time	B-13
Figure B-14 - Passenger Lower Spine Y Velocity vs. Time	B-14
Figure B-15 - Passenger Pelvis Y Acceleration vs. Time	B-15
Figure B-16 - Passenger Pelvis Y Velocity vs. Time	B-16
 <u>Vehicle:</u>	
Figure B-17 - Left Front Sill Y Acceleration vs. Time	B-17
Figure B-18 - Left Front Sill Y Velocity vs. Time	B-18
Figure B-19 - Left Rear Sill Y Acceleration vs. Time	B-19
Figure B-20 - Left Rear Sill Y Velocity vs. Time	B-20
Figure B-21 - Right Front Sill X Acceleration vs. Time	B-21
Figure B-22 - Right Front Sill X Velocity vs. Time	B-22
Figure B-23 - Right Front Sill Y Acceleration vs. Time	B-23
Figure B-24 - Right Front Sill Y Velocity vs. Time	B-24
Figure B-25 - Right Front Sill Z Acceleration vs. Time	B-25
Figure B-26 - Right Front Sill Z Velocity vs. Time	B-26
Figure B-27 - Right Front Sill at Front Seat Resultant vs. Time	B-27
Figure B-28 - Right Rear Sill X Acceleration vs. Time	B-28
Figure B-29 - Right Rear Sill X Velocity vs. Time	B-29
Figure B-30 - Right Rear Sill Y Acceleration vs. Time	B-30
Figure B-31 - Right Rear Sill Y Velocity vs. Time	B-31

Table of Data Plots

	<u>Page No.</u>
<u>Vehicle (Cont'd):</u>	
Figure B-32 - Right Rear Sill Z Acceleration vs. Time	B-32
Figure B-33 - Right Rear Sill Z Velocity vs. Time	B-33
Figure B-34 - Right Rear Sill at Rear Seat Resultant vs. Time	B-34
Figure B-35 - Driver Seat Track Y Acceleration vs. Time	B-35
Figure B-36 - Driver Seat Track Y Velocity vs. Time	B-36
Figure B-37 - Rear Floorpan at Axle X Acceleration vs. Time	B-37
Figure B-38 - Rear Floorpan at Axle X Velocity vs. Time	B-38
Figure B-39 - Rear Floorpan at Axle Y Acceleration vs. Time	B-39
Figure B-40 - Rear Floorpan at Axle Y Velocity vs. Time	B-40
Figure B-41 - Rear Floorpan at Axle Z Acceleration vs. Time	B-41
Figure B-42 - Rear Floorpan at Axle Z Velocity vs. Time	B-42
Figure B-43 - Rear Floorpan at Axle Centerline Resultant vs. Time	B-43
Figure B-44 - Rear Seat Occupant Compartment Y Acceleration vs. Time	B-44
Figure B-45 - Rear Seat Occupant Compartment Y Velocity vs. Time	B-45
Figure B-46 - Left A Post Lower Y Acceleration vs. Time	B-46
Figure B-47 - Left A Post Lower Y Velocity vs. Time	B-47
Figure B-48 - Left B Post Mid Y Acceleration vs. Time	B-48
Figure B-49 - Left B Post Mid Y Velocity vs. Time	B-49
Figure B-50 - Left B Post Lower Y Acceleration vs. Time	B-50
Figure B-51 - Left B Post Lower Y Velocity vs. Time	B-51
Figure B-52 - Moving Barrier Center of Gravity X Acceleration vs. Time	B-52
Figure B-53 - Moving Barrier Center of Gravity X Velocity vs. Time	B-53
Figure B-54 - Moving Barrier Center of Gravity Y Acceleration vs. Time	B-54
Figure B-55 - Moving Barrier Center of Gravity Y Velocity vs. Time	B-55
Figure B-56 - Moving Barrier Center of Gravity Z Acceleration vs. Time	B-56
Figure B-57 - Moving Barrier Center of Gravity Z Velocity vs. Time	B-57
Figure B-58 - Moving Barrier Center of Gravity Resultant vs. Time	B-58
Figure B-59 - Moving Barrier Rear Axle X Acceleration vs. Time	B-59
Figure B-60 - Moving Barrier Rear Axle X Velocity vs. Time	B-60
Figure B-61 - Moving Barrier Rear Axle Y Acceleration vs. Time*	B-61
Figure B-62 - Moving Barrier Rear Axle Y Velocity vs. Time*	B-62
Figure B-63 - Right Hand Barrier Contact	B-63
Figure B-64 - Left Hand Barrier Contact	B-64

* No valid data collected

Table of Data Plots

Page No.

Redundant:

Figure B-65 - Driver Upper Rib Y Redundant Acceleration vs. Time	B-65
Figure B-66 - Driver Upper Rib Y Redundant Velocity vs. Time	B-66
Figure B-67 - Driver Lower Rib Y Redundant Acceleration vs. Time	B-67
Figure B-68 - Driver Lower Rib Y Redundant Velocity vs. Time	B-68
Figure B-69 - Driver Lower Spine Y Redundant Acceleration vs. Time	B-69
Figure B-70 - Driver Lower Spine Y Redundant Velocity vs. Time	B-70
Figure B-71 - Driver Pelvis Y Redundant Acceleration vs. Time	B-71
Figure B-72 - Driver Pelvis Y Redundant Velocity vs. Time	B-72
Figure B-73 - Passenger Upper Rib Y Redundant Acceleration vs. Time	B-73
Figure B-74 - Passenger Upper Rib Y Redundant Velocity vs. Time	B-74
Figure B-75 - Passenger Lower Rib Y Redundant Acceleration vs. Time	B-75
Figure B-76 - Passenger Lower Rib Y Redundant Velocity vs. Time	B-76
Figure B-77 - Passenger Lower Spine Y Redundant Acceleration vs. Time	B-77
Figure B-78 - Passenger Lower Spine Y Redundant Velocity vs. Time	B-78
Figure B-79 - Passenger Pelvis Y Redundant Acceleration vs. Time	B-79
Figure B-80 - Passenger Pelvis Y Redundant Velocity vs. Time	B-80

Filter: Class 180 (300 Hz)




Figure B-1 - Driver Upper Rib Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-2 - Driver Upper Rib Y Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-3 - Driver Lower Rib Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-4 - Driver Lower Rib Y Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-5 - Driver Lower Spine Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-6 - Driver Lower Spine Y Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-7 - Driver Pelvis Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-8 - Driver Pelvis Y Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-9 - Passenger Upper Rib Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-10 - Passenger Upper Rib Y Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-11 - Passenger Lower Rib Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-12 - Passenger Lower Rib Y Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-13 - Passenger Lower Spine Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-14 - Passenger Lower Spine Y Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-15 - Passenger Pelvis Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-16 - Passenger Pelvis Y Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-17 - Left Front Sill Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-18 - Left Front Sill Y Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-19 - Left Rear Sill Y Acceleration vs. Time

Filter: Class 180 (300 Hz)





Figure B-20 - Left Rear Sill Y Velocity vs. Time

Filter: Class 60 (100 Hz)



B-21

Figure B-21 - Right Front Sill X Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-22 - Right Front Sill X Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-23 - Right Front Sill Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-24 - Right Front Sill Y Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-25 - Right Front Sill Z Acceleration vs. Time

Filter: Class 180 (300 Hz)





Figure B-26 - Right Front Sill z Velocity vs. Time

Filter: Class 60 (100 Hz)



B-27

Figure B-27 - Right Front Sill at Front Seat Resultant vs. Time

Filter: Class 60 (100 Hz)




Figure B-28 - Right Rear Sill X Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-29 - Right Rear Sill X Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-30 - Right Rear Sill Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-31 - Right Rear Sill Y Velocity vs. Time

Filter: Class 60 (100 Hz)





Figure B-32 - Right Rear Sill Z Acceleration vs. Time

Filter: Class 180 (300 Hz)



B-33

Figure B-33 - Right Rear Sill Z Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-34 - Right Rear Sill at Rear Seat Resultant vs. Time

Filter: Class 60 (100 Hz)





Figure B-35 - Driver Seat Track Y Acceleration vs. Time


Filter: Class 180 (300 Hz)



B-36

Figure B-36 - Driver Seat Track Y Velocity vs. Time

Filter: Class 60 (100 Hz)



B-37

Figure B-37 - Rear Floorpan at Axle X Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-38 - Rear Floorpan at Axle X Velocity vs. Time

Filter: Class 60 (100 Hz)





Figure B-39 - Rear Floorpan at Axle Y Acceleration vs. Time

Filter: Class 180 (300 Hz)



B-40

Figure B-40 - Rear Floorpan at Axle Y Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-41 - Rear Floorpan at Axle Z Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-42 - Rear Floorpan at Axle Z Velocity vs. Time

Filter: Class 60 (100 Hz)





Figure B-43 - Rear Floorpan at Axle Centerline Resultant vs. Time


Filter: Class 60 (100 Hz)



B-44

Figure B-44 - Rear Seat Occupant Compartment Y Acceleration vs. Time

Filter: Class 180 (300 Hz)



B-45

Figure B-45 - Rear Seat Occupant Compartment Y Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-46 - Left A Post Lower Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-47 - Left A Post Lower Y Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-48 - Left B Post Mid Y Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-49 - Left B Post Mid Y Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-50 - Left B Post Lower Y Acceleration vs. Time

B-50

Filter: Class 180 (300 Hz)




Figure B-51 - Left B Post Lower Y Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-52 - Moving Barrier Center of Gravity X Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-53 - Moving Barrier Center of Gravity X Velocity vs. Time

Filter: Class 60 (100 Hz)





Figure B-54 - Moving Barrier Center of Gravity Y Acceleration vs. Time

Filter: Class 180 (300 Hz)



B-55

Figure B-55 - Moving Barrier Center of Gravity Y Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-56 - Moving Barrier Center of Gravity Z Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-57 - Moving Barrier Center of Gravity Z Velocity vs. Time

Filter: Class 60 (100 Hz)




Figure B-58 - Moving Barrier Center of Gravity Resultant vs. Time

Filter: Class 60 (100 Hz)




Figure B-59 - Moving Barrier Rear Axle X Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-60 - Moving Barrier Rear Axle X Velocity vs. Time

NO VALID DATA COLLECTED

B-61

Figure B-61 - Moving Barrier Rear Axle Y Acceleration vs. Time

NO VALID DATA COLLECTED

B-62

Figure B-62 - Moving Barrier Rear Axle Y Velocity vs. Time

Filter: Class 1000 (1650 Hz)




Figure B-63 - Right Hand Barrier Contact

Filter: Class 1000 (1650 Hz)





Figure B-64 - Left Hand Barrier Contact

Filter: Class 180 (300 Hz)



B-65

Figure B-65 - Driver Upper Rib Y Redundant Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-66 - Driver Upper Rib Y Redundant Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-67 - Driver Lower Rib Y Redundant Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-68 - Driver Lower Rib Y Redundant Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-69 - Driver Lower Spine Y Redundant Acceleration vs. Time

Filter: Class 180 (300 Hz)





Figure B-70 - Driver Lower Spine Y Redundant Velocity vs. Time

Filter: Class 180 (300 Hz)



B-71

Figure B-71 - Driver Pelvis Y Redundant Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-72 - Driver Pelvis Y Redundant Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-73 - Passenger Upper Rib Y Redundant Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-74 - Passenger Upper Rib Y Redundant Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-75 - Passenger Lower Rib Y Redundant Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-76 - Passenger Lower Rib Y Redundant Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-77 - Passenger Lower Spine Y Redundant Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-78 - Passenger Lower Spine Y Redundant Velocity vs. Time

Filter: Class 180 (300 Hz)




Figure B-79 - Passenger Pelvis Y Redundant Acceleration vs. Time

Filter: Class 180 (300 Hz)




Figure B-80 - Passenger Pelvis Y Redundant Velocity vs. Time

FINITE IMPULSE RESPONSE (FIR) FILTERED DATA

Table of Data Plots

	<u>Page No.</u>
Figure B-81 - Driver Upper Rib Y Acceleration vs. Time	B-81
Figure B-82 - Driver Upper Rib Y Redundant Acceleration vs. Time	B-82
Figure B-83 - Driver Lower Rib Y Acceleration vs. Time	B-83
Figure B-84 - Driver Lower Rib Y Redundant Acceleration vs. Time	B-84
Figure B-85 - Driver Lower Spine Y Acceleration vs. Time	B-85
Figure B-86 - Driver Lower Spine Y Redundant Acceleration vs. Time	B-86
Figure B-87 - Driver Pelvis Y Acceleration vs. Time	B-87
Figure B-88 - Driver Pelvis Y Redundant Acceleration vs. Time	B-88
Figure B-89 - Passenger Upper Rib Y Acceleration vs. Time	B-89
Figure B-90 - Passenger Upper Rib Y Redundant Acceleration vs. Time	B-90
Figure B-91 - Passenger Lower Rib Y Acceleration vs. Time	B-91
Figure B-92 - Passenger Lower Rib Y Redundant Acceleration vs. Time	B-92
Figure B-93 - Passenger Lower Spine Y Acceleration vs. Time	B-93
Figure B-94 - Passenger Lower Spine Y Redundant Acceleration vs. Time	B-94
Figure B-95 - Passenger Pelvis Y Acceleration vs. Time	B-95
Figure B-96 - Passenger Pelvis Y Redundant Acceleration vs. Time	B-96




Figure B-81 - Driver Upper Rib Y Acceleration vs. Time




Figure B-82 - Driver Upper Rib Y Redundant Acceleration vs. Time




Figure B-83 - Driver Lower Rib Y Acceleration vs. Time





Figure B-84 - Driver Lower Rib Y Redundant Acceleration vs. Time



B-85

Figure B-85 - Driver Lower Spine Y Acceleration vs. Time




Figure B-86 - Driver Lower Spine Y Redundant Acceleration vs. Time




Figure B-87 - Driver Pelvis Y Acceleration vs. Time




Figure B-88 - Driver Pelvis Y Redundant Acceleration vs. Time




Figure B-89 - Passenger Upper Rib Y Acceleration vs. Time




Figure B-90 - Passenger Upper Rib Y Redundant Acceleration vs. Time




Figure B-91 - Passenger Lower Rib Y Acceleration vs. Time




Figure B-92 - Passenger Lower Rib Y Redundant Acceleration vs. Time




Figure B-93 - Passenger Lower Spine Y Acceleration vs. Time




Figure B-94 - Passenger Lower Spine Y Redundant Acceleration vs. Time




Figure B-95 - Passenger Pelvis Y Acceleration vs. Time




Figure B-96 - Passenger Pelvis Y Redundant Acceleration vs. Time

APPENDIX C
SID CONFIGURATION AND PERFORMANCE VERIFICATION

REPORT NO.: MGA-94-21405

SAFETY COMPLIANCE TESTING FOR FMVSS 214
"SIDE IMPACT PROTECTION STUDY - PASSENGER CARS"

CHRYSLER CORPORATION
1994 DODGE INTREPID 4 DOOR SEDAN
NHTSA NO: CR0312

MGA PROVING GROUNDS
5000 WARREN ROAD
BURLINGTON, WI 53105



MGA Ref. No.: G93A-02

Test Date: June 3, 1994

Report Date: September 26, 1994

FINAL REPORT

Prepared For:

U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
MAIL CODE: NEF-30
400 SEVENTH STREET, SW ROOM 6115

TABLE OF CONTENTS

		<u>Page No.</u>
DUMMY S/N: 269	PRE-TEST CERTIFICATION DATA	1-1
DUMMY S/N: 271	PRE-TEST CERTIFICATION DATA	2-1
DUMMY S/N: 269	POST-TEST CERTIFICATION DATA	3-1
DUMMY S/N: 271	POST-TEST CERTIFICATION DATA	4-1
DUMMY S/N: 269	POST-TEST INSPECTION CHECKLIST	5-1
DUMMY S/N: 271	POST-TEST INSPECTION CHECKLIST	6-1
	VEHICLE AND DUMMY TEMPERATURE	7-1

PRE-TEST CERTIFICATION DATA

Driver Dummy Serial Number: 269

Calibration Test Results Summary

Dummy Serial Number: 269

Pre-Test Calibration

External Dimensions:	The dummy passed all external dimension requirements.
Thorax Impact Test:	The thorax passed all impact test requirements.
Pelvic Impact Test:	The pelvis passed all impact test requirements.
Abdominal Compression Test:	The abdomen passed all compression test requirements
Lumbar Flexion Test:	The lumbar passed all flexion test requirements


SIDE IMPACT DUMMY CONFIGURATION AND PERFORMANCE VERIFICATION DATA

DUMMY NO.: 269


DATE OF VERIFICATION: May 31, 1994

DESCRIPTION	SPECIFICATION	TEST RESULTS
SH - Seated Height	35.0" - 35.8"	35.6
RH - Rib Height	19.75 - 20.5"	20.3
HP - Hip Pivot Height	3.9" ref.	3.9
RD - Rib From Back Line	9.0" to 9.5"	9.3
KV - Knee Pivot From Back Line	20.1" - 20.7"	20.6
SW - Knee Pivot to Floor	19.3" - 19.9"	19.6
HW - Hip Width	14.0" - 15.4"	14.5

MEASUREMENTS BY:



APPROVED BY:



MGA RESEARCH CORPORATION

THORAX IMPACT TEST

SIDE IMPACT DUMMY (SID)


DATE: June 2, 1994


DUMMY NUMBER: 269

TEST NUMBER: D94842

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	30%
PROBE SPEED	13.8 - 14.2 fps	14.2
UPPER RIB	37 - 46 g's	39
LOWER RIB	37 - 46 g's	37
LOWER SPINE	15 - 22 g's	20


TEST MEETS SPECIFICATIONS

TECHNICIAN 

APPROVED BY 

06-02-1994 12:03

DUMMY CALIBRATION - THORAX IMPACT
DUMMY # 269
ACCELERATION (G'S) VS. TIME ((SECONDS))




06-02-1994 12:03

DUMMY CALIBRATION - THORAX IMPACT


DUMMY # 269

ACCELERATION (G'S) VS. TIME ((SECONDS))



06-02-1994 12:03

DUMMY CALIBRATION - THORAX IMPACT
DUMMY # 269
ACCELERATION (G'S) VS. TIME ((SECONDS))



MGA RESEARCH CORPORATION

PELVIS IMPACT TEST

SIDE IMPACT DUMMY (SID)

DATE: June 2, 1994

DUMMY NUMBER: 269

TEST NUMBER: D94843

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	30%
PROBE SPEED	13.8 - 14.2 fps	13.9
PELVIS ACCELERATION	40 - 60 g's	54

TEST MEETS SPECIFICATIONS

TECHNICIAN


Ha Chen

APPROVED BY

M Robbins

06-02-1994 09:08

DUMMY CALIBRATION - PELVIS IMPACT
DUMMY # 269
ACCELERATION (G'S) VS. TIME ((SECONDS))



MGA RESEARCH CORPORATION

ABDOMINAL COMPRESSION TEST
(PRELOAD = 10 LBS)

SIDE IMPACT DUMMY (SID)

DATE: June 1, 1994

DUMMY NUMBER: 269

TEST NUMBER: D94844

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	28%
FORCE @ 0.5 in	23.3 - 36.5 lbs	31.3
FORCE @ 0.75 in	36.7 - 49.8 lbs	42.5
FORCE @ 1.0 in	50 - 63 lbs	57
FORCE @ 1.3 in	73 - 88 lbs	79


TEST MEETS SPECIFICATIONS

TECHNICIAN *A. C. Chen*

APPROVED BY *J. D. Robbins*

DUMMY CALIBRATION - ABDOMEN COMPRESSION
 DUMMY # 269
 06-01-1994 09:44

ABDOMEN FORCE () VS. ABDOMEN DISPLACEMENT (INCHES)



MGA RESEARCH CORPORATION

LUMBAR FLEXION TEST

SIDE IMPACT DUMMY (SID)


DATE: June 1, 1994


DUMMY NUMBER: 269

TEST NUMBER: D94845

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	28%
FORCE @ 0°	0 - 6 lbs	0
FORCE @ 20°	22 - 34 lbs	24
FORCE @ 30°	34 - 46 lbs	38
FORCE @ 40°	46 - 58 lbs	51
RETURN ANGLE	12° maximum	9°


TEST MEETS SPECIFICATIONS

TECHNICIAN 

APPROVED BY 

DUMMY CALIBRATION - LUMBAR FLEXION
 DUMMY # 269
 FORCE () VS. TORSO ROTATION (DEGREES)

06-01-1994 11:58



PRE-TEST CERTIFICATION DATA

Passenger Dummy Serial Number: 271

Calibration Test Results Summary

Passenger Serial Number: 271

Pre-Test Calibration

External Dimensions:	The dummy passed all external dimension requirements.
Thorax Impact Test:	The thorax passed all impact test requirements.
Pelvic Impact Test:	The pelvis passed all impact test requirements.
Abdominal Compression Test:	The abdomen passed all compression test requirements
Lumbar Flexion Test:	The lumbar passed all flexion test requirements

SIDE IMPACT DUMMY CONFIGURATION AND PERFORMANCE VERIFICATION DATA

DUMMY NO.: 271

DATE OF VERIFICATION: June 2, 1994

DESCRIPTION	SPECIFICATION	TEST RESULTS
SH - Seated Height	35.0" - 35.8"	35.6
RH - Rib Height	19.75 - 20.5"	20.3
HP - Hip Pivot Height	3.9" ref.	3.9
RD - Rib From Back Line	9.0" to 9.5"	9.3
KV - Knee Pivot From Back Line	20.1" - 20.7"	20.4
SW - Knee Pivot to Floor	19.3" - 19.9"	19.5
HW - Hip Width	14.0" - 15.4"	14.3

MEASUREMENTS BY:



APPROVED BY:



MGA RESEARCH CORPORATION

THORAX IMPACT TEST

SIDE IMPACT DUMMY (SID)

DATE: June 2, 1994

DUMMY NUMBER: 271

TEST NUMBER: D94852


TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	30%
PROBE SPEED	13.8 - 14.2 fps	13.9
UPPER RIB	37 - 46 g's	42
LOWER RIB	37 - 46 g's	41
LOWER SPINE	15 - 22 g's	20

TEST MEETS SPECIFICATIONS


TECHNICIAN



APPROVED BY



DUMMY CALIBRATION - THORAX IMPACT
 DUMMY # 271
 06-02-1994 12:20
 ACCELERATION (G:S) VS. TIME ((SECONDS))




06-02-1994 12:20

DUMMY CALIBRATION - THORAX IMPACT

DUMMY # 271


ACCELERATION (G'S) VS. TIME ((SECONDS))



DUMMY CALIBRATION - THORAX IMPACT
DUMMY # 271

06-02-1994 12:20

() VS. TIME ((SECONDS))



MGA RESEARCH CORPORATION

PELVIS IMPACT TEST

SIDE IMPACT DUMMY (SID)


DATE: June 2, 1994


DUMMY NUMBER: 271

TEST NUMBER: D94853

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	30%
PROBE SPEED	13.8 - 14.2 fps	14.0
PELVIS ACCELERATION	40 - 60 g's	50


TEST MEETS SPECIFICATIONS

TECHNICIAN 

APPROVED BY 

06-02-1994 08:46

DUMMY CALIBRATION - PELVIS IMPACT
DUMMY # 271
ACCELERATION (G'S) VS. TIME ((SECONDS))



MGA RESEARCH CORPORATION
ABDOMINAL COMPRESSION TEST
(PRELOAD = 10 LBS)
SIDE IMPACT DUMMY (SID)

DATE: June 1, 1994

DUMMY NUMBER: 271

TEST NUMBER: D94854

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	28%
FORCE @ 0.5 in	23.3 - 36.5 lbs	30.3
FORCE @ 0.75 in	36.7 - 49.8 lbs	41.5
FORCE @ 1.0 in	50 - 63 lbs	55
FORCE @ 1.3 in	73 - 88 lbs	76

TEST MEETS SPECIFICATIONS

TECHNICIAN 


APPROVED BY 

06-01-1994 10:09

DUMMY CALIBRATION - ABDOMEN COMPRESSION

DUMMY # 271

ABDOMEN FORCE () VS. ABDOMEN DISPLACEMENT (INCHES)



MGA RESEARCH CORPORATION

LUMBAR FLEXION TEST

SIDE IMPACT DUMMY (SID)

DATE: June 1, 1994

DUMMY NUMBER: 271

TEST NUMBER: D94855

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	28%
FORCE @ 0°	0 - 6 lbs	0
FORCE @ 20°	22 - 34 lbs	30
FORCE @ 30°	34 - 46 lbs	40
FORCE @ 40°	46 - 58 lbs	48
RETURN ANGLE	12° maximum	3°

TEST MEETS SPECIFICATIONS

TECHNICIAN




APPROVED BY



DUMMY CALIBRATION - LUMBAR FLEXION
 DUMMY # 271
 FORCE () VS. TORSO ROTATION (DEGREES)

06-01-1994 12:50



POST-TEST CERTIFICATION DATA

Driver Dummy Serial Number: 269

Calibration Test Results Summary

Dummy Serial Number: 269

Post-Test Calibration

External Dimensions:	The dummy passed all external dimension requirements.
Thorax Impact Test:	The thorax did not passed post-test impact test requirements.*
Pelvis Impact Test:	The pelvis passed all impact test requirements.
Abdominal Compression Test:	The abdomen passed all compression test requirements.
Lumbar Flexion Test:	The lumbar passed all flexion test requirements.

* The thorax would not pass post-test impact requirements. The Vector Rib Wrap Assembly was replaced with a FTSS Rib Wrap Assembly. The ensuing thorax impacts did meet all test requirements and this data was used as pre-test calibration data for the next test.


SIDE IMPACT DUMMY CONFIGURATION AND PERFORMANCE VERIFICATION DATA

DUMMY NO.: 269


DATE OF VERIFICATION: June 6, 1994

DESCRIPTION	SPECIFICATION	TEST RESULTS
SH - Seated Height	35.0" - 35.8"	35.6
RH - Rib Height	19.75 - 20.5"	20.3
HP - Hip Pivot Height	3.9" ref.	3.9
RD - Rib From Back Line	9.0" to 9.5"	9.3
KV - Knee Pivot From Back Line	20.1" - 20.7"	20.5
SW - Knee Pivot to Floor	19.3" - 19.9"	19.4
HW - Hip Width	14.0" - 15.4"	14.5

MEASUREMENTS BY:



APPROVED BY:



MGA RESEARCH CORPORATION

THORAX IMPACT TEST

SIDE IMPACT DUMMY (SID)

DATE: June 6, 1994

DUMMY NUMBER: 269

TEST NUMBER: D94912

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	72°
RELATIVE HUMIDITY	10 - 70%	38%
PROBE SPEED	13.8 - 14.2 fps	14.1
UPPER RIB	37 - 46 g's	34*
LOWER RIB	37 - 46 g's	34*
LOWER SPINE	15 - 22 g's	17


* TEST DOES NOT MEET SPECIFICATION REQUIREMENTS

TECHNICIAN _____

APPROVED BY _____


06-06-1994 14:32

DUMMY CALIBRATION - THORAX IMPACT
DUMMY # 269
ACCELERATION (G'S) VS. TIME ((SECONDS))




06-06-1994 14:32

DUMMY CALIBRATION - THORAX IMPACT
DUMMY # 269
ACCELERATION (G'S) VS. TIME ((SECONDS))



06-06-1994 14:32

DUMMY CALIBRATION - THORAX IMPACT
DUMMY # 269
ACCELERATION (G'S) VS. TIME ((SECONDS))



MGA RESEARCH CORPORATION

PELVIS IMPACT TEST

SIDE IMPACT DUMMY (SID)

DATE: June 6, 1994

DUMMY NUMBER: 269

TEST NUMBER: D94913

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	72°
RELATIVE HUMIDITY	10 - 70%	38%
PROBE SPEED	13.8 - 14.2 fps	14.0
PELVIS ACCELERATION	40 - 60 g's	52

TEST MEETS SPECIFICATIONS

TECHNICIAN

Ha Cll

APPROVED BY


J. Robbins

06-06-1994 16:21

DUMMY CALIBRATION - PELVIS IMPACT

DUMMY # 269

ACCELERATION (G'S) VS. TIME ((SECONDS))



MGA RESEARCH CORPORATION
ABDOMINAL COMPRESSION TEST
(PRELOAD = 10 LBS)
SIDE IMPACT DUMMY (SID)

DATE: June 7, 1994


DUMMY NUMBER: 269

TEST NUMBER: D94914

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	40%
FORCE @ 0.5 in	23.3 - 36.5 lbs	32.1
FORCE @ 0.75 in	36.7 - 49.8 lbs	43.7
FORCE @ 1.0 in	50 - 63 lbs	58
FORCE @ 1.3 in	73 - 88 lbs	78

TEST MEETS SPECIFICATIONS

TECHNICIAN 


APPROVED BY 

06-07-1994 09:48

DUMMY CALIBRATION - ABDOMEN COMPRESSION

DUMMY # 269

ABDOMEN FORCE () VS. ABDOMEN DISPLACEMENT (INCHES)



MGA RESEARCH CORPORATION

LUMBAR FLEXION TEST

SIDE IMPACT DUMMY (SID)


DATE: June 7, 1994


DUMMY NUMBER: 269

TEST NUMBER: D94915

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	40%
FORCE @ 0°	0 - 6 lbs	0
FORCE @ 20°	22 - 34 lbs	22
FORCE @ 30°	34 - 46 lbs	36
FORCE @ 40°	46 - 58 lbs	50
RETURN ANGLE	12° maximum	4°


TEST MEETS SPECIFICATIONS

TECHNICIAN 

APPROVED BY 

06-07-1994 12:12

DUMMY CALIBRATION - LUMBAR FLEXION
DUMMY # 269
FORCE () VS. TORSO ROTATION (DEGREES)



POST-TEST CERTIFICATION DATA

Passenger Dummy Serial Number: 271

Calibration Test Results Summary

Dummy Serial Number: 271

Post-Test Calibration

External Dimensions:	The dummy passed all external dimension requirements.
Thorax Impact Test:	The thorax passed all impact test requirements.
Pelvis Impact Tests:	The pelvis passed all impact test requirements.
Adbominal Compression Test:	The abdomen passed all compression test requirements.
Lumbar Flexion Test:	The lumbar passed all flexion test requirements.

SIDE IMPACT DUMMY CONFIGURATION AND PERFORMANCE VERIFICATION DATA

DUMMY NO.: 271

DATE OF VERIFICATION: June 6, 1994

DESCRIPTION	SPECIFICATION	TEST RESULTS
SH - Seated Height	35.0" - 35.8"	35.6
RH - Rib Height	19.75 - 20.5"	20.2
HP - Hip Pivot Height	3.9" ref.	3.9
RD - Rib From Back Line	9.0" to 9.5"	9.4
KV - Knee Pivot From Back Line	20.1" - 20.7"	20.4
SW - Knee Pivot to Floor	19.3" - 19.9"	19.5
HW - Hip Width	14.0" - 15.4"	14.4

MEASUREMENTS BY: 

APPROVED BY: 

MGA RESEARCH CORPORATION

THORAX IMPACT TEST

SIDE IMPACT DUMMY (SID)


DATE: June 6, 1994


DUMMY NUMBER: 271

TEST NUMBER: D94922

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	72°
RELATIVE HUMIDITY	10 - 70%	38%
PROBE SPEED	13.8 - 14.2 fps	14.1
UPPER RIB	37 - 46 g's	42
LOWER RIB	37 - 46 g's	41
LOWER SPINE	15 - 22 g's	20

TEST MEETS SPECIFICATIONS

TECHNICIAN 


APPROVED BY 

06-06-1994 14:13

DUMMY CALIBRATION - THORAX IMPACT


DUMMY # 271

() VS. TIME ((SECONDS))



06-06-1994 14:09

DUMMY CALIBRATION - THORAX IMPACT
DUMMY # 271
ACCELERATION (G'S) VS. TIME ((SECONDS))




DUMMY CALIBRATION - THORAX IMPACT

DUMMY # 271

() VS. TIME ((SECONDS))

06-06-1994 14:14



MGA RESEARCH CORPORATION

PELVIS IMPACT TEST

SIDE IMPACT DUMMY (SID)


DATE: June 6, 1994


DUMMY NUMBER: 271

TEST NUMBER: D94923

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	72°
RELATIVE HUMIDITY	10 - 70%	38%
PROBE SPEED	13.8 - 14.2 fps	14.0
PELVIS ACCELERATION	40 - 60 g's	51

TEST MEETS SPECIFICATIONS

TECHNICIAN 


APPROVED BY 

06-06-1994 16:14

DUMMY CALIBRATION - PELVIS IMPACT

DUMMY # 271

ACCELERATION (G'S) VS. TIME ((SECONDS))



MGA RESEARCH CORPORATION
ABDOMINAL COMPRESSION TEST
(PRELOAD = 10 LBS)
SIDE IMPACT DUMMY (SID)


DATE: June 7, 1994

DUMMY NUMBER: 271

TEST NUMBER: D94924

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	40%
FORCE @ 0.5 in	23.3 - 36.5 lbs	27.4
FORCE @ 0.75 in	36.7 - 49.8 lbs	42.3
FORCE @ 1.0 in	50 - 63 lbs	55
FORCE @ 1.3 in	73 - 88 lbs	82

TEST MEETS SPECIFICATIONS


TECHNICIAN 
APPROVED BY 

DUMMY CALIBRATION - ABDOMEN COMPRESSION

DUMMY # 271

ABDOMEN FORCE () VS. ABDOMEN DISPLACEMENT (INCHES)

FORCE = 27.4 AT .5 INCHES DEFLECTION
FORCE = 42.3 AT .75 INCHES DEFLECTION
FORCE = 55.2 AT 1.0 INCHES DEFLECTION
FORCE = 81.8 AT 1.3 INCHES DEFLECTION



MGA RESEARCH CORPORATION

LUMBAR FLEXION TEST

SIDE IMPACT DUMMY (SID)


DATE: June 7, 1994


DUMMY NUMBER: 271

TEST NUMBER: D94925

TEST PARAMETER	SPECIFICATION	TEST RESULTS
TEMPERATURE	66 - 78° F	70°
RELATIVE HUMIDITY	10 - 70%	40%
FORCE @ 0°	0 - 6 lbs	0
FORCE @ 20°	22 - 34 lbs	24
FORCE @ 30°	34 - 46 lbs	34
FORCE @ 40°	46 - 58 lbs	48
RETURN ANGLE	12° maximum	4°


TEST MEETS SPECIFICATIONS

TECHNICIAN 

APPROVED BY 

DUMMY CALIBRATION - LUMBAR FLEXION
 DUMMY # Z71
 FORCE () VS. TORSO ROTATION (DEGREES)

06-07-1994 11:04



POST-TEST DRIVER DUMMY INSPECTION CHECKLIST

Type: Side Impact Dummy

Serial Number: 269

Inspected By: Jeff Robbins

Date: June 6, 1994

<u>Part</u>	<u>Items Checked</u>	<u>Comments</u>
Skin	visual inspection	OK
Head	visual, ballast, accelerometer mount	OK
Neck	visual, cable torque	OK
Spine box	visual, ballast, weldment, accelerometer mount	OK
Rib cage	visual, measure, stiffeners	DAMAGED
Sternum	visual	OK
Lumbar spine	visual	OK
Abdomen	visual	OK
Pelvis	visual, palpate, accelerometer mount	OK
Upper legs	visual	OK
Knees	visual, stops, inserts	OK
Lower legs	visual, range of motion	OK
Ankles	visual, range of motion	OK
Feet	visual, range of motion	OK
Joints	1 to 2 g range	OK
Other		

NOTES: (include component/problem/action/reason):

Four rivets on posterior side of rib wrap assembly failed. See post-test thorax impact for explanation.

POST-TEST PASSENGER DUMMY INSPECTION CHECKLIST

Type: Side Impact Dummy

Serial Number: 271

Inspected By: Jeff Robbins


Date: June 6, 1994

<u>Part</u>	<u>Items Checked</u>	<u>Comments</u>
Skin	visual inspection	OK
Head	visual, ballast, accelerometer mount	OK
Neck	visual, cable torque	OK
Spine box	visual, ballast, weldment, accelerometer mount	OK
Rib cage	visual, measure, stiffeners	Damaged
Sternum	visual	OK
Lumbar spine	visual	OK
Abdomen	visual	OK
Pelvis	visual, palpate, accelerometer mount	OK
Upper legs	visual	OK
Knees	visual, stops, inserts	OK
Lower legs	visual, range of motion	OK
Ankles	visual, range of motion	OK
Feet	visual, range of motion	OK
Joints	1 to 2 g range	OK
Other		

NOTES: (include component/problem/action/reason):

The front, upper left, rivet on the rib wrap assembly failed during impact. The dummy was post-test calibrated and the thoracic impact data fell within the specified requirements. This rib wrap assembly was then replaced with a NHTSA supplied rib wrap assembly. A pre test thoracic impact test was performed on the dummy with the new rib wrap assembly installed. This data also fell within the specified requirements.

VEHICLE AND DUMMY TEMPERATURE



A = Dummies installed in vehicle
 B = Test conducted

APPENDIX D
DUMMY AND VEHICLE CALIBRATION DATA

**DUMMY, VEHICLE AND LABORATORY INSTRUMENT CALIBRATION
INSTRUMENTS FOR DRIVER DUMMY NO. 269**

	DRIVER		
	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Upper Rib	AHRY3	Endevco	April 27, 1994
Lower Rib	AHT11	Endevco	April 27, 1994
Lower Spine	AHT13	Endevco	April 27, 1994
Pelvis	AHTN7	Endevco	April 27, 1994
Upper Rib Redundant	AGTH6	Endevco	March 31, 1994
Lower Rib Redundant	AHTY4	Endevco	April 27, 1994
Lower Spine Redundant	AGT06	Endevco	April 28, 1994
Pelvis Redundant	AGTF7	Endevco	April 27, 1994

INSTRUMENTS FOR PASSENGER DUMMY NO. 271

	LEFT REAR PASSENGER		
	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Upper Rib	AHTT3	Endevco	April 18, 1994
Lower Rib	AHTY2	Endevco	April 18, 1994
Lower Spine	AHT12	Endevco	April 18, 1994
Pelvis	AGWA4	Endevco	April 27, 1994
Upper Rib Redundant	AGTP7	Endevco	March 31, 1994
Lower Rib Redundant	AHT20	Endevco	April 27, 1994
Lower Spine Redundant	AHTB2	Endevco	April 28, 1994
Pelvis Redundant	AHWK8	Endevco	April 27, 1994

VEHICLE INSTRUMENT CALIBRATION

	VEHICLE ACCELEROMETERS		
	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
MDB CG X	MGA132	Entran	May 06, 1994
MDB CG Y	MGA007	Entran	May 06, 1994
MDB CG Z	MGA016	Entran	May 06, 1994
MDB Rear Axle X	MGA134	Entran	May 06, 1994
MDB Rear Axle Y	MGA147	Entran	May 06, 1994
Lower Left A-Post Y	AALL9	Endevco	June 02, 1994
Mid Left B-Post Y	ADA34	Endevco	June 02, 1994
Lower Left B-Post Y	MGA035	Entran	May 24, 1994
Trunk Centerline X	MGA029	Entran	June 02, 1994
Trunk Centerline Y	MGA045	Endevco	June 02, 1994
Trunk Centerline Z	MGA145	Entran	May 24, 1994
Right Front Sill X	AZ02	Endevco	April 25, 1994
Right Front Sill Y	MGA135	Entran	May 16, 1994
Right Front Sill Z	MGA126	Entran	May 24, 1994
Right Rear Sill X	MGA084	Entran	June 02, 1994
Right Rear Sill Y	MGA004	Entran	June 02, 1994
Right Rear Sill Z	MGA091	Entran	June 02, 1994
Right Rear Seat Occupant Compartment Y	MGA025	Entran	January 27, 1994
Left Front Sill Y	MGA160	Entran	May 16, 1994
Left Rear Sill Y	MGA144	Entran	May 16, 1994

Note: All Endevco accelerometers are Model No. 7264-2000
All Entran accelerometers are Model No. EGE-72