

REPORT NUMBER KAR21003-04

**NEW CAR ASSESSMENT PROGRAM
SIDE IMPACT TEST**

**GENERAL MOTORS CORPORATION
2001 PONTIAC GRAND PRIX
4 DOOR SEDAN
NHTSA NUMBER: M10117**

**PREPARED BY:
KARCO ENGINEERING
9270 HOLLY ROAD
ADELANTO, CALIFORNIA 92301**



DECEMBER 28, 2000

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
SAFETY PERFORMANCE STANDARDS
OFFICE OF CRASHWORTHINESS STANDARDS
MAIL CODE: NPS-10
400 SEVENTH STREET, SW, ROOM 5313
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, in response to Contract Number DTNH22-99-D-02041.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: _____
Mr. James E. Gorth, Project Engineer
KARCO Engineering

Date: December 28, 2000

Reviewed by: _____
Mr. Jerry L. Kratzke, Director of Operations
KARCO Engineering

Date: December 28, 2000

Approved by: _____
Mr. Frank D. Richardson, Program Manager
KARCO Engineering

Date: December 28, 2000

FINAL REPORT ACCEPTED BY:

Manager, Side Impact NCAP

Date of Acceptance

Technical Report Documentation Page

1. Report No. KAR21003-04	2. Government Accession No. 	3. Recipients Catalog No. 																			
4. Title and Subtitle Final Report of New Car Assessment Program Testing Side Impact Testing of a 2001 Pontiac Grand Prix 4 Door Sedan NHTSA NO. M10117		5. Report Date December 28, 2000																			
		6. Performing Organization Code KAR																			
7. Author(s) Mr. James E Gorth, Project Engineer, Karco Mr. Frank Richardson, Project Manager, Karco		8. Performing Organization Report No. KAR21003-04																			
9. Performing Organization Name and Address KARCO Engineering 9270 Holly Road Adelanto, CA 92301		10. Work Unit No. 																			
		11. Contract or Grant No. DTNH22-99-D-02041																			
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Safety Performance Standards Office of Crashworthiness Standards Mail Code: NPS-10 400 Seventh Street, SW, Room 5313 Washington, D.C. 20590		13. Type of Report and Period Covered Final Test Report Option Year 1																			
		14. Sponsoring Agency Code DOT/NHTSA/NRM/OCS																			
15. Supplementary Notes 																					
16. Abstract A 55/28 km/h 90° Moving Deformable Barrier Side Impact NCAP Test was conducted on the subject 2001 Pontiac Grand Prix 4 Door Sedan in accordance with the specifications of the Office of Crash Worthiness Standards Test Procedure for the generation of consumer information on vehicle side crash protection. The test was conducted at KARCO Engineering laboratories in Adelanto, California, on December 12, 2000. The impact velocity of the Moving Deformable Barrier was 61.71 km/h, and the ambient temperature at the struck (driver's) side of the vehicle was 7.8 °C. The target vehicle's maximum post test static crush was 459 mm located at level 2. The test vehicle's occupant performance is as follows: <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width: 40%;">Measurement Description</th> <th style="width: 20%;">Driver SID</th> <th style="width: 20%;">Passenger SID</th> </tr> </thead> <tbody> <tr> <td>Left Upper Rib (LUR) G's</td> <td style="text-align: center;">79.8</td> <td style="text-align: center;">69.7</td> </tr> <tr> <td>Left Lower Rib (LLR) G's</td> <td style="text-align: center;">79.6</td> <td style="text-align: center;">88.0</td> </tr> <tr> <td>Lower Spine (T₁₂) G's</td> <td style="text-align: center;">107.1</td> <td style="text-align: center;">80.9</td> </tr> <tr> <td>Thoracic Trauma Index (TTI) G's</td> <td style="text-align: center;">93</td> <td style="text-align: center;">84</td> </tr> <tr> <td>Pelvis (PEV) G's</td> <td style="text-align: center;">96</td> <td style="text-align: center;">100</td> </tr> </tbody> </table>				Measurement Description	Driver SID	Passenger SID	Left Upper Rib (LUR) G's	79.8	69.7	Left Lower Rib (LLR) G's	79.6	88.0	Lower Spine (T ₁₂) G's	107.1	80.9	Thoracic Trauma Index (TTI) G's	93	84	Pelvis (PEV) G's	96	100
Measurement Description	Driver SID	Passenger SID																			
Left Upper Rib (LUR) G's	79.8	69.7																			
Left Lower Rib (LLR) G's	79.6	88.0																			
Lower Spine (T ₁₂) G's	107.1	80.9																			
Thoracic Trauma Index (TTI) G's	93	84																			
Pelvis (PEV) G's	96	100																			
17. Key Words New Car Assessment Program (NCAP) Side Impact Moving Deformable Barrier (MDB) Side Impact Dummy (SID)		18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Admin. NHTSA Technical Reference Division 400 Seventh St., SW, Room 5108 Washington, DC 20590																			
19. Security Classification(of this report) UNCLASSIFIED	20. Security Classification(of this page) UNCLASSIFIED	21. No. of Pages 274	22. Price 																		

Form DOT F1700.7 (8-72)

TABLE OF CONTENTS

Section		Page
1	Purpose and Test Procedure	1
2	Summary of Side Impact Test	2
3	Side Impact Dummy (SID) and Vehicle Test Data	3
4	Occupant and Vehicle Information	11

Data Sheet No.		Page
1	General Test and Vehicle Parameter Data	4
2	Test Vehicle Summary of Results	8
3	Moving Deformable Barrier (MDB) Summary of Results	9
4	Post Test Observations	10
5	SID Injury Criteria and Sensor Data	12
6	Vehicle Pre-Test and Post-Test Measurements	13
7	SID Longitudinal Clearance Dimensions	14
8	SID Lateral Clearance Dimensions	15
9	Vehicle Side Measurements	16
10	Vehicle Exterior Crush Profiles	17
11	Vehicle Damage Profile Distances	19
12	Deformable Barrier Honeycomb Face Static Crush	20
13	Vehicle Accelerometer Locations and Data Summary	21
14	MDB Accelerometer Location and Data Summary	23
15	High Speed Camera Locations and Data	24
16	FMVSS 301 Fuel System Integrity Post Impact Data	25
17	FMVSS 301 Static Rollover Data Sheet	26

Appendix		
A	Photographs	A
B	SID, Vehicle, and MDB Response Data	B
C	SID Configuration and Performance Verification Data	C
D	Test Equipment List and Calibration Information	D

SECTION 1

PURPOSE and TEST PROCEDURE

1.1 PURPOSE

This Side Impact NCAP test is conducted as part of the FY' 2001 test program sponsored by the National Highway Traffic Safety Administration (NHTSA), under contract No. DTNH22-99-D-02041. The purpose of this test is to generate comparative side impact data on a 2001 Pontiac Grand Prix 4 Door Sedan manufactured by General Motors Corporation.

1.2 TEST PROCEDURE

The side impact test was conducted in accordance with the current National Highway Traffic Safety Administration (NHTSA), Office of Crashworthiness Standards (OCS), laboratory test procedure NCAP Side Impact Testing, dated July 1997 and the corresponding KARCO Engineering Test Procedure KTP-214D, dated November 18, 1998. The procedures for receiving, inspection, testing, and reporting of test results are described in the test procedures and are not repeated in this report.

SECTION 2

SUMMARY OF SIDE IMPACT TEST

2.1 SUMMARY OF SIDE IMPACT NCAP TEST

A model year 2001 Pontiac Grand Prix 4 Door Sedan was impacted on the left (driver's) side by a Moving Deformable Barrier (MDB) which was moving forward in a 27° crabbed position to the tow road guidance system at a velocity of 61.71 km/h. The specified impact velocity range is from 61.1 to 62.7 km/h. The test (target) vehicle was stationary and positioned 63° to the line of forward motion. The weight of the vehicle as tested was 1741 kg. and the test weight of the MDB was 1361 kg. The test was conducted at KARCO Engineering in Adelanto, California, on December 12, 2000.

One (1) real-time motion picture camera and eleven (11) high-speed motion picture cameras were used to document the impact event. The pre-test and post-test conditions were recorded by one (1) real-time motion picture camera. Camera locations and pertinent camera information is documented in the data sheets. Pre- and post-test photographs of the vehicle and SID can be found in Appendix A. Two 50th percentile adult male Side Impact Dummy's (SID's) were placed in the driver's and left rear passenger designated seating positions according to the test procedure. Each SID is instrumented with contact switches on the pelvis and thorax, and eleven accelerometers in the following locations:

- Left Upper Rib (LUR) uni-axial accelerometer (Y-axis primary and redundant)
- Left Lower Rib (LLR) uni-axial accelerometer (Y-axis primary and redundant)
- Lower Thoracic Spine (T12) uni-axial accelerometer (Y-axis primary and redundant)
- Pelvic (PEV) section uni-axial accelerometer (Y-axis primary and redundant)
- Head Center of Gravity (CG) tri-axial accelerometers (X, Y, and Z axes)

The test vehicle was instrumented with twenty-five (25) structural accelerometers and the MDB was instrumented with five (5) accelerometers and a one (1) contact switch on the right bumper to compare left side to right side bumper impact timing. All data channels were recorded with a fully self contained on-board Test Data Acquisition System (TDAS). The data was digitally sampled at 10,000 samples per second and processed per Appendix V of the Test Procedure.

2.2 GENERAL COMMENTS

The test vehicle sustained a maximum static crush of 459 mm at level 2, 1500mm rearward of the left vertical impact point. The driver SID, Serial No. 274 and the passenger SID, Serial No. 275 were calibrated just prior to this test. The SID injury criteria is summarized as follows:

Measurement	Units	Driver	Passenger
Thoracic Trauma Index (TTI)	G's	93	84
Peak Pelvic G's (PEV)	G's	96	100

Tests summaries and post-test observations are presented in Section 3. The vehicle, camera, and occupant measurements are presented in Section 4. Appendix A contains the still photograph prints. Appendix B contains the driver and passenger SID's, vehicle, and MDB response data traces. Appendix C contains the SID's Configuration and performance verification data. Appendix D contains the test equipment information.

SECTION 3
SIDE IMPACT DUMMY (SID) AND VEHICLE TEST DATA

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan
 Test Program: 55/28 km/h 90° Side Impact NCAP

NHTSA No. M10117
 Test Date: 12/12/00

CONVERSION FACTORS USED IN THIS REPORT*

Quantity	Typical Application	Std Units	Metric Unit	Multiply By
Mass	Vehicle Weight	lb	kg	0.4536
Linear Velocity	Impact Velocity	mile/h	km/h	1.609
Length or Distance	Measurements	in	mm	25.4
Volume	Fuel Systems	gal	liter	3.785
Volume	Small Fluids	oz	mL	29.573
Pressure	Tire Pressures	lbf/in ²	kPa	7.0
Volume	Liquid	gal	liter	3.785
Temperature	General Use	°F	°C	=(tf -32)/1.8
Force	Dynamic Forces	lbf	N	4.448
Moment	Torque	lbf/ft	Nm	1.355

* Based on the Recommended Practice in SAE J916, May 85

DATA SHEET NO. 1
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00

TEST VEHICLE INFORMATION

Make	Pontiac
Model	Grand Prix
Body Style	4 Door Sedan
NHTSA No.	M10117
VIN	1G2WK52J91F141031
Color	White
Delivery Date	11/21/00
Odometer Reading (mile)	76
Dealer	Rally
Transmission	4-Speed Automatic
Final Drive	Front
Number of Cylinders	6
Engine Displacement (L)	3.1
Engine Placement	Transverse

TEST VEHICLE OPTIONS

Driver Airbag	Yes
Passenger Airbag	Yes
Power Windows	Yes
Power Steering	Yes
Power Door Locks	Yes
Tilt Wheel	Yes
Air Conditioning	Yes
Power Brakes	Yes
Disc Brakes, Front	Yes
Disc Brakes, Rear	Yes
Anti-lock Brakes	Yes
AM/FM/Cassette	Yes
Anti-Theft System	No
Cruise Control	Yes

DATA FROM CERTIFICATION LABEL

Manufactured By	General Motors Corporation	GVWR (kg)	1958
Date of Manufacture	September-00	GAWR Front (kg)	1085
		GAWR Rear (kg)	873

DATA FROM TIRE PLACARD

Measured Parameter	Front	Rear
Maximum Tire Pressure (kPa)	210	210
Cold Pressure (kPa)	210	210
Recommend Tire Size	P205/70/R15	P205/70/R15
Tire Size on Vehicle	P205/70/R15	P205/70/R15
Tire Manufacturer	B. F. Goodrich	B. F. Goodrich

Measured Parameter	Front	Rear	Third	Total
Type of Seats	Bucket	Bench	Bench	
Number of Occupants	2	3	N/A	5
Capacity Wt. (VCW) (kg)				416
Cargo Weight (RCLW) (kg)				76

DATA SHEET NO. 1...(continued)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan
 Test Program: 55/28 km/h 90° Side Impact NCAP

NHTSA No.: M10117
 Test Date: 12/12/00

TEST VEHICLE WEIGHTS

	Units	As Delivered (UVW)			As Tested (ATW)		
		Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total
Left	kg	473	270		518	366	
Right	kg	499	268		513	344	
Ratio	%	64.4	35.6		59.2	40.8	
Totals	kg	972	538	1510	1031	710	1741

TARGET TEST WEIGHT CALCULATION*

Measured Parameter	Units	Value
Total Delivered Weight (UVW)	kg	1510
Weight of 2 P572F Side Impact Dummies	kg	161.5
Rated Cargo/Luggage Weight (RCLW)	kg	76
Calculated Vehicle Target Weight (TVTW)	kg	1748

*Actual As Tested Weight (ATW) will be TVTW -5/-10 kg

TEST VEHICLE ATTITUDES AND CG

	Units	LF	RF	LR	RR	CG (aft of front axle)
As Delivered	mm	733	735	746	735	1001
As Tested	mm	721	726	697	703	1147
Fully Loaded	mm	720	732	700	698	

GENERAL TEST VEHICLE DATA

Measurement Description	Units	Value
Test Vehicle Wheel base	mm	2812
Total Vehicle Length at Left Side	mm	3490
Total Vehicle Length at Centerline	mm	5003
Total Vehicle Length at Right Side	mm	3495
Weight of Ballast In Cargo Area	kg	52
Amount of Stoddard Solvent in Fuel Tank	Liters	61.5

TEST VEHICLE VERTICAL IMPACT LINE DATA

Measurement Description	Units	Value
Test Vehicle Wheel base	mm	2812
Target Impact Point Aft of Front Axle	mm	466
Actual Impact Point Aft of Front Axle	mm	488

DATA SHEET NO. 1...(continued)

GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No. M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00


NOMINAL DESIGN RIDING POSITION

The driver's seat back is positioned to the manufacturers designated angle. The procedure for the seat is as follows:

A slit is cut into fabric of the seat at the outboard edge, approximately 8-12 inches above the pivot point to expose the frame of the seat. An inclinometer is firmly placed against the flat portion of the frame surface and the seat back is adjusted to the manufacturers designated angle.

Driver seat back angle: 29.5° with a seated dummy

Rear seat back angle: 28° fixed, no adjustments



FRONT SEAT ASSEMBLY

SEAT FORE/AFT POSITIONS

The driver's seat and the rear middle seat are both adjustable. The fore/aft is set to the middle position for both seats.

Driver seat fore/aft total travel: 25 total detents

Rear seat fore/aft total travel: Seat is fixed, no adjustments

Driver seat fore/aft position: Seat set at the 13th detent

Rear seat fore/aft position: Seat is fixed, no adjustments

SEAT BELT UPPER ANCHORAGE

The test vehicle is equipped with an adjustable "D" ring anchorage for the driver's seat position. There are 4 positions or detents. The driver's "D" ring anchorage is placed in the 2nd position from uppermost. The rear seat anchor is fixed, no adjustments.

DATA SHEET NO. 1...(continued)

GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No. M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00

FUEL TANK CAPACITY DATA


The "Usable Capacity" of the standard equipment fuel tank is: 66.2 liters

The "Usable Capacity" of any optional equipment fuel tank is: N/A liters

92-94% of "Usable Capacity" for certification to FMVSS 301 requirement: 60.9 to 62.2 liters

Actual amount of Stoddard solvent added to vehicle for certification test: 61.5 liters


The test vehicle is equipped with an electric fuel pump. The fuel pump will operate for approximately three (3) seconds with the ignition in the "ON" position, after which the fuel pump automatically shuts off. The fuel filler door is located on the left rear fender.



VEHICLE FUEL TANK ASSEMBLY

STEERING COLUMN ADJUSTMENT

Steering wheel and column adjustments are made so that the steering wheel hub is at the geometric center of the locus it describes, when it is moved through its full range of motion. An aluminum plate is placed across the rim of the steering wheel, an inclinometer is placed onto the plate and the angle is measured. The column has 6 positions or detents and no geometric center exists. The tested vehicle has its steering column set to the 4th detent from uppermost as indicated by the drawing at right and the angle below.



STEERING COLUMN ASSEMBLY

Lowermost, position 1: 11°

Geometric center, position 2: 21°

Uppermost, position 3: 36°

DATA SHEET NO. 2
TEST VEHICLE SUMMARY OF RESULTS

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan
 Test Program: 55/28 km/h 90° Side Impact NCAP

NHTSA No.: M10117
 Test Date: 12/12/00

TEST VEHICLE WEIGHTS

	Units	As Delivered (UVW)			As Tested (ATW)		
		Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total
Left	kg	473	270		518	366	
Right	kg	499	268		513	344	
Weight Ratio	%	64.4	35.6		59.2	40.8	
Totals	kg	972	538	1510	1031	710	1741

MAXIMUM EXTERIOR STATIC CRUSH

Level	Measured Parameter	Units	Maximum Crush	Above Ground
Level 1	Sill Top Height	mm	299	236
Level 2	Occupant H-Point	mm	459	498
Level 3	Mid Door	mm	408	579
Level 4	Window Sill	mm	371	884
Level 5	Window Top	mm	155	1315
N/A	Maximum Penetration	mm	459	

INSTRUMENTATION

Driver SID Accelerometers	11
Passenger SID Accelerometers	11
Vehicle Structure Accelerometers	25
MDB Accelerometers	5
Total	52

16mm MOVIE COVERAGE

High Speed, Vehicle On-Board	3
High Speed, Off-Board	6
High Speed, MDB On-Board	2
Real Time, Panning	1
Total	12

DATA SHEET NO. 3
MOVING DEFORMABLE BARRIER (MDB) SUMMARY OF RESULTS

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan
 Test Program: 55/28 km/h 90° Side Impact NCAP

NHTSA No.: M10117
 Test Date: 12/12/00

MDB SPECIFICATIONS (mm)

Measurement Description	Length
Overall Width of Framework Carriage	1252
Overall Length Including Honeycomb Face	4115
Wheel base of Framework Carriage	2590
C.G. Location aft of Front Axle	1127

MDB WEIGHTS

	Units	Front Axle	Rear Axle	Total
Left	kg	384	308	
Right	kg	385	284	
Ratio	%	56.5	43.5	
Totals	kg	769	592	1361

SPEED AND IMPACT ANGLE DATA

Measured Parameter	Units	Requirement	Value
Trap No. 1 Velocity (Primary)	km/h	61.1 to 62.7	61.71
Trap No. 2 Velocity (Redn.)	km/h	61.1 to 62.7	62.21
MDB CL to Target Vehicle CL	degrees	88.5 to 91.5	89.5

MAXIMUM STATIC CRUSH OF HONEYCOMB FACE (mm)

Vertical Location			From Centerline		Max Crush
Row	Description	Height	Distance	Direction	
A	Center of Bumper	432	800	Right	87
B	Top of Bumper	533	800	Right	59
C	Mid Level	686	800	Right	79
D	Top of Stack	813	800	Right	136

MDB INSTRUMENTATION AND CAMERAS

Accelerometers	5
Contact Switches	2
High Speed Cameras	2

**DATA SHEET NO. 4
POST TEST OBSERVATIONS**

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan
Test Program: 55/28 km/h 90° Side Impact NCAP

NHTSA No.: M10117
Test Date: 12/12/00

TEST DUMMY INFORMATION AND CONTACT POINTS

Description	Front Seat SID	Rear Seat SID
Dummy Type / Serial No.	P572F, SID / No. 274	P572F, SID / No. 275
Head Contact	Headrest/D-ring/B-Pillar	C-Pillar/Headrest
Upper Torso Contact	Door Panel	Door Panel
Lower Torso Contact	Door Panel	Door Panel
Left Knee Contact	Steering Column	Knee
Right Knee Contact	Door Panel/Knee	Knee

POST TEST DOOR OPENING AND SEAT TRACK INFORMATION

Description	Front	Rear
Left Side Door Opening	Remained closed inoperable	Remained closed, inoperable
Right Side Door Opening	Remained closed operable	Remained closed, operable
Seat Movement	None	None
Seat Back Failure	None	None

POST TEST STRUCTURAL OBSERVATIONS

Critical Areas of Performance	Observations and Conclusions
Pillar Performance	Pillars pushed inward with no apparent failure
Sill Separation	No Apparent Visible Failure
Windshield Damage	Glazing Cracks on Struck Side Only
Window Damage	Both Left Side Windows Broke
Other Notable Effects	No significant items to note.

AIR BAG DEPLOYMENT

	Driver	Front Passenger	Rear Passenger
Front	No	No	N/A
Side	N/A	N/A	N/A

MDB LEFT EDGE IMPACT POINT DATA

Measured Parameter	Units	Requirement	Value
Horizontal Offset	mm	+/- 50	22 (right)
Vertical Offset	mm	+/- 20	13 (above)

SECTION 4
OCCUPANT AND VEHICLE INFORMATION

DATA SHEET NO. 5
SID INJURY CRITERIA AND SENSOR DATA

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00

THORAX AND PELVIS PEAK ACCELERATIONS, PRIMARY (FIR 100 Filtered)

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Upper Rib (LUR)	Y	G's	79.8	25.3	-21.6	73.2	69.7	33.2	-24.8	69.2
Lower Rib (LLR)	Y	G's	79.6	24.0	-23.3	74.3	88.0	34.7	-31.7	67.6
Lower Spine (T ₁₂)	Y	G's	107.1	28.5	-30.3	67.9	80.9	35.2	-57.5	64.2
Pelvis (PEV)	Y	G's	95.7	32.0	-34.2	75.3	99.5	25.1	-34.2	57.5

THORACIC TRAUMA INDEX (TTI) AND PELVIC ACCELERATION, PRIMARY (FIR 100 Filtered)

Location	Driver				Passenger			
	LUR	T ₁₂	TTI(g)	PEV(g)	LLR	T ₁₂	TTI(g)	PEV(g)
Primary Rib, Spine, and Pelvis	79.756	107.121	93	96	87.992	80.929	84	100

THORAX AND PELVIS PEAK ACCELERATIONS, REDUNDANT (FIR 100 Filtered)

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Upper Rib (LUR)	Y	G's	78.4	25.3	-22.4	73.0	70.2	33.3	-22.8	69.0
Lower Rib (LLR)	Y	G's	78.8	23.9	-23.3	74.2	88.9	34.8	-32.0	67.4
Lower Spine (T ₁₂)	Y	G's	107.7	28.5	-30.9	67.9	81.7	35.4	-56.6	64.1
Pelvis (PEV)	Y	G's	95.6	32.0	-34.4	75.4	99.1	25.1	-34.0	57.0

THORACIC TRAUMA INDEX (TTI) AND PELVIC ACCELERATION, REDUNDANT (FIR 100 Filtered)

Location	Driver				Passenger			
	LLR	T ₁₂	TTI(g)	PEV(g)	LLR	T ₁₂	TTI(g)	PEV(g)
Redundant Rib, Spine, and Pelvis	78.848	107.691	93	96	88.886	81.708	85	99

HEAD CG PEAK ACCELERATIONS (SAE CLASS 1000 Filtered)

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Head CG	X	G's	27.1	40.8	-23.3	76.6	10.4	173.0	-27.7	55.7
Head CG	Y	G's	58.0	39.1	-10.1	189.2	145.6	55.8	-14.9	31.5
Head CG	Z	G's	42.2	46.9	-13.6	37.4	58.7	56.1	-33.3	61.3
Head CG Resultant	N/A	G's	62.3	39.1			158.0	55.8		

HEAD INJURY CRITERIA (SAE CLASS 1000 Filtered)

Location	Driver				Passenger			
	HIC	T ¹	T ²	Avg G	HIC	T ¹	T ²	Avg G
Head CG	262.0	34.2	54.2	44.3	793.5	54.3	59.6	116.6

Positive Acceleration Polarities: Longitudinal (X) = Forward
 (Conforms to SAE J211) Lateral (Y) = Right
 Vertical (Z) = Down

DATA SHEET NO. 6


VEHICLE PRE-TEST AND POST-TEST MEASUREMENTS

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00



All Measurements in mm

Code	Measurement Description	Pre-Test	Post-Test	Difference
A	Wheelbase	2812	2715	97
B	Front Axle To FSOV	1105	1010	95
C	Rear Axle to RSOV	1086	1012	74
D	Total Length at Centerline	5003	4973	30
E	Front Bumper Thickness	356	366	-10
F	Front Bumper Bottom to Ground	185	198	-13
G	Sill Height at Front Wheel Well	196	216	-20
H	Sill Height at Front Door Leading Edge	198	216	-18
I	Sill Height at "B" Pillar	190	265	-75
J1	Sill Height at Rear Wheel Well	155	194	-39
J2	Pinch Weld Height at Rear Wheel Well	179	225	-46
K	Sill Height aft of Rear Wheel Well	220	254	-34
L	Rear Bumper Thickness	381	381	0
M	Rear Bumper Bottom to Ground	300	341	-41
N	Sill Height to Window Bottom Sill	595	595	0
O	Front Door Leading Edge to Impact CL	825	680	145
P	Rear Door Trailing Edge to Impact CL	1176	1153	23
Q	Front Window Opening	392	372	20
R	Right Side Length	3495	3405	90
S	Left Side Length	3490	3519	-29
T	Vehicle Width at "B" Post	1822	1563	259


DATA SHEET NO. 7
SID LONGITUDINAL CLEARANCE DIMENSIONS

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00




Driver Code	Pass. Code	Measurement Description	Driver		Passenger	
			Length(mm)	Angle(°)	Length(mm)	Angle(°)
HH		Head to Header	400	21		
HW		Head to Windshield	665			
HZ	HZ	Head to Roof	162	90	145	90
NR	NB	Nose to Rim/Nose to Seatback	485	11	597	22
CD	CB	Chest to Dash or Seatback	535	7	510	2
CS		Chest to Steering Wheel	360	11		
KDL	KBL	Left Knee to Dash or Seatback	170	23	230	
KDR	KBR	Right Knee to Dash or Seatback	160		230	
PA	PA	Pelvic Angle		23.5		25
PHX	PHX	H-Point to Striker (X-Axis)	200		311	
PHZ	PHZ	H-Point to Striker (Z-Axis)	146		380	

DATA SHEET NO. 8
SID LATERAL CLEARANCE DIMENSIONS

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan
 Test Program: 55/28 km/h 90° Side Impact NCAP

NHTSA No.: M10117
 Test Date: 12/12/00



FRONT VIEW OF DUMMY

Code	Measurement Description	Units	Driver	Passenger
HR	Head to Side Header	mm	209	258
HS	Head to Side Window	mm	335	349
AD	Arm to Door	mm	119	96
HD	H-Point to Door	mm	157	132


DATA SHEET NO. 9
VEHICLE SIDE MEASUREMENTS

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00



All Measurements Shown in mm

LEFT SIDE VIEW

Measurements are taken with vehicle in the as tested condition.

Measurements taken 900mm right of impact reference.

All measurements below in mm.

Level	Measurement Description	Height Above Ground
5	Window Top	1315
4	Window Sill	884
3	Mid Door	579
2	Occupant H-Point	498
1	Sill Top	236

DATA SHEET NO. 10 - VEHICLE EXTERIOR CRUSH PROFILES

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan
 Test Program: 55/28 km/h 90° Side Impact NCAP


NHTSA No.: M10117
 Test Date: 12/12/00

	Pre-Test					Post-Test					Difference				
	1	2	3	4	5	1	2	3	4	5	1	2	3	4	5
-900															
-750															
-600															
-450															
-300				801					753					48	
-150			913	821				846	779				67	42	
0	831	895	897	829		767	817	819	785		64	78	78	44	
150	831	890	896	832		752	640	614	714		79	250	282	118	
300	831	890	896	839		665	529	588	634		166	361	308	205	
450	832	890	895	837		642	494	567	567		190	396	328	270	
600	832	892	896	838		602	476	537	547		230	416	359	291	
750	832	892	897	840	574	589	464	525	540	501	243	428	372	300	73
900	831	893	897	842	586	560	449	501	529	491	271	444	396	313	95
1050	831	893	896	844	589	532	446	490	524	462	299	447	406	320	127
1200	831	889	892	844	589	570	456	484	513	434	261	433	408	331	155
1350	831	886	890	845	580	639	435	485	500	465	192	451	405	345	115
1500	831	883	886	842	574	698	424	487	488	482	133	459	399	354	92
1650	832	880	882	841	562	724	421	491	470	494	108	459	391	371	68
1800	833	877	880	839	549	784	429	511	483	486	49	448	369	356	63
1950	834	886	888	839		779	799	622	534		55	87	266	305	
2100			904	839				819	677				85	162	
2250				838					778					60	
2400				835					790					45	
2550				824					797					27	
2700				804					795					9	
2850				787					783					4	
3000				754					766					-12	

Pre-Test and Post-Test dimensions are actual distance from centerline of test vehicle.

DATA SHEET NO. 10...(continued)

18



Maximum Crush, Level 1: 299 mm at 1050 mm
 Maximum Crush, Level 2: 459 mm at 1500 mm
 Maximum Crush, Level 3: 408 mm at 1200 mm
 Maximum Crush, Level 4: 371 mm at 1650 mm
 Maximum Crush, Level 5: 155 mm at 1200 mm

Test Program: 55/28 km/h 90° Side Impact NCAP No.: M10117
 Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan
 Test Date: 12/12/00



KAR21003-04


DATA SHEET NO. 11
VEHICLE DAMAGE PROFILE DISTANCES

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00



TOP VIEW

Damage Profile Distances

DPD	Distance From Impact Point (mm)	Level	Pre-Test (mm)	Post-Test (mm)	Max Static Crush (mm)
1	-300	4	801	753	48
2	300	2	890	529	361
3	1050	2	893	446	447
4	1650	2	880	421	459
5	2250	4	838	778	60
6	3000	4	754	766	-12

Pre-Test and Post-Test measurements are distance from vehicle centerline.

DATA SHEET NO. 12


DEFORMABLE BARRIER HONEYCOMB FACE STATIC CRUSH

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00



DEFORMABLE BARRIER STATIC CRUSH

Stack	Distance Right of Center								C _L	Distance Left of Center							
Level	800	700	600	500	400	300	200	100	0	100	200	300	400	500	600	700	800
1	13	15	-10	-13	-8	2	5	2	6	7	13	19	25	31	41	54	87
2	-14	-22	-24	-23	-19	-14	-12	-11	-8	-4	2	10	14	22	28	40	59
3	-9	-33	-44	-40	-35	-31	-26	-19	-16	-14	-9	-4	2	8	22	42	79
4	11	-29	-44	-42	-37	-28	-24	-12	-12	-10	-7	0	8	19	48	91	136

All Dimensions in mm

DATA SHEET NO. 13

VEHICLE ACCELEROMETER LOCATION AND DATA SUMMARY



Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00

LEFT SIDE VIEW



No.	Location
1	Right Sill at Front Seat
2	Right Sill at Rear Seat
3	Rear Floorpan Above Axle
4	Left Sill at Rear Door
5	Left Sill at Front Door
6	Left Front Door Centerline
7	Right Rear Occupant Compartment
8	Left Front Door Mid-Rear
9	Left Front Door Upper Centerline

No.	Location
10	Left Rear Door Mid-Rear
11	Left Rear Door Upper Centerline
12	Left Lower B-Post
13	Left Middle B-Post
14	Left Lower A-Post
15	Left Middle A-Post
16	Front Seat Track
17	Rear Seat Track or Structure
18	Vehicle CG

DATA SHEET NO. 13

VEHICLE ACCELEROMETER LOCATION AND DATA SUMMARY

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00

VEHICLE ACCELEROMETER PEAK DATA AND PRE-TEST LOCATIONS

Loc. No.	Accelerometer Location	Measurements (mm)			Peak Values (G's)				
		X	Y	Z	Axis	Max	Time	Min	Time
1	Right Sill at Front Seat	2995	680	220	X	3.8	62.8	-5.4	15.4
					Y	21.7	8.1	-2.7	152.9
					Z	5.9	26.7	-3.9	9.8
					RES	21.9	8.1		
2	Right Sill at Rear Seat	2130	670	210	X	4.3	62.6	-5.0	15.9
					Y	20.7	8.6	-4.0	153.7
					Z	10.3	59.0	-9.5	19.9
					RES	21.2	8.9		
3	Rear Floorpan Above Axle	1120	70	485	X	3.3	59.4	-7.0	16.3
					Y	18.9	9.1	-3.4	133.6
					Z	10.6	21.2	-3.5	9.3
					RES	19.2	9.2		
4	Left Sill at Rear Door	2250	-750	190	Y	85.8	19.6	-18.3	58.8
5	Left Sill at Front Door	2850	-750	195	Y	42.8	23.8	-7.7	68.5
6	Front Door Centerline	2780	-840	735	Y	96.7	13.5	-57.8	22.7
7	Rear Occupant Compartment	2240	450	230	Y	22.5	8.4	-3.9	152.5
8	Front Door Mid-Rear	2420	-765	690	Y	147.6	12.4	-81.2	17.5 *
9	Front Door Upper Centerline	2835	-840	815	Y	167.3	13.9	-60.0	22.9 *
10	Rear Door Mid-Rear	1540	-780	700	Y	196.3	7.0	-57.7	23.0
11	Rear Door Upper Centerline	1820	-775	885	Y	134.4	13.2	-50.8	32.3
12	B-Post Lower	2290	-730	480	Y	193.7	2.9	-49.5	17.9
13	B-Post Middle	2290	-730	720	Y	167.2	3.2	-33.3	24.9
14	A-Post Lower	3335	-820	525	Y	98.4	2.9	-10.7	19.6
15	A-Post Middle	3335	-820	740	Y	50.1	2.8	-3.0	182.3
16	Front Seat Track	2810	-600	340	Y	53.7	13.7	-0.9	28.5
17	Rear Seat Structure				Y				**
18	Vehicle CG	2225	0	320	X	4.3	64.7	-7.5	37.5
					Y	24.2	19.4	-10.3	81.8
					Z	12.0	33.6	-10.5	24.1
					RES	25.2	19.4		

* Channels failed, check plot for failure times

** Not installed

DATA SHEET NO. 14

MDB ACCELEROMETER LOCATION AND DATA SUMMARY

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00


MDB ACCELEROMETER PEAK DATA AND LOCATIONS

Loc. No.	Accelerometer Location	Measurements (mm)			Peak Values (G's)				
		X	Y	Z	Axis	Max	Time	Min	Time
1	MDB CG	-1195	0	430	X	4.1	136.7	-18.7	41.0
					Y	4.1	149.6	-6.6	21.0
					Z	14.2	132.4	-12.4	144.3
					RES	19.9	40.9		
2	MDB Rear	-2642	-593	608	X	3.3	148.1	-20.3	39.4
					Y	2.3	103.8	-7.6	23.0

Reference Points X - MDB Front Axle Y - MDB Centerline Z - Ground Plane

MDB BUMPER CONTACT SWITCH DATA

Loc. No.	Contact Switch Location	Units	Peak and 50% Crossing Point			
			Max	Time	50%	Time
3	MDB Left Bumper (T=0)	% F.S	100.0	0.0	0.0	0.0
4	MDB Right Bumper	% F.S.	100.8	19.4	50.4	0.1




DATA SHEET NO. 15
HIGH SPEED CAMERA LOCATIONS AND DATA

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00



No.	Camera View	Location (mm)			Angle (deg.)	Lens (mm)	Film Speed (fr./sec.)
		X	Y	Z			
1	Overhead Overall	1676	-762	5486	-86	10	911
2	Overhead Close-up	-762	0	5791	-82	24	1007
3	MDB Onboard, Impact Point Close-Up	-2134	0	1143	-7	13	812
4	MDB Onboard, Centerline of Impact	-3048	-1676	1829	-4	13	982
5	Right Side, Ground Level, Overall	9144	18288	2210	-1	25	1060
6	Right Side, Ground Level, Close-up	0	18898	1524	0	60	1000
7	Left Side, Ground Level, Close-up	-2362	-5410	1448	-6	13	1020
8	Vehicle Onboard Front SID, Front	-305	1219	1478	-10	19	1006
9	Vehicle Onboard Front SID, Side	1624	914	1173	0	19	1011
10	Vehicle Onboard Rear SID, Side	1981	0	1173	0	10	1021
11	Front View In-line with Track	108051	229	1021	0	80	490
12	Real Time Coverage	3072	20040	2350	N/A	N/A	24

DATA SHEET NO. 16

FMVSS 301 FUEL SYSTEM INTEGRITY POST IMPACT DATA

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

NHTSA No.: M10117

Test Program: 55/28 km/h 90° Side Impact NCAP

Test Date: 12/12/00

Test Time: 11:32 AM

Temperature at Time of Impact: 7.8 °C


STODDARD SOLVENT SPILLAGE MEASUREMENTS

- A. From impact until vehicle motion ceases: 0.0 oz.
(Maximum Allowable = 1 ounce)
- B. For the 5 minute period after motion ceases: 0.0 oz.
(Maximum Allowable = 5 ounces)
- C. For the following 25 minutes: 0.0 oz.
(Maximum Allowable = 1 oz./minute)
- D. Spillage Details: No leakage occurred


DATA SHEET NO. 17
FMVSS 301 STATIC ROLLOVER DATA SHEET

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan
 Test Program: 55/28 km/h 90° Side Impact NCAP



NHTSA No.: M10117
 Test Date: 12/12/00




0° TO 90°




90° TO 180°



180° TO 270°



270° TO 360°



1. The specified fixture rollover rate for each 90° of rotation is 60 to 120 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. Details of Stoddard Solvent spillage locations:

No solvent leakage occurred during static rollover testing.

Rollover Test Phase	Rotation Time (sec.)	Hold Time (sec.)	Spillage (oz.)
0° TO 90°	82	300	0.0
90° TO 180°	82	300	0.0
180° TO 270°	78	300	0.0
270° TO 360°	82	300	0.0

APPENDIX A
PHOTOGRAPHS

LIST OF PHOTOGRAPHS

Figure		Page
A-1	Left Front as Received	A-1
A-2	Right Rear as Received	A-2
A-3	Vehicle's Certification Label	A-3
A-4	Vehicle's Tire Placard	A-4
A-5	Pre-test Front View	A-5
A-6	Post-test Front View	A-6
A-7	Pre-test Rear View	A-7
A-8	Post-test Rear View	A-8
A-9	Pre-test Left Side View (Struck Side)	A-9
A-10	Post-test Left Side View (Struck Side)	A-10
A-11	Pre-test Overall Overhead View (At Impact Position)	A-11
A-12	Pre-test Overall Overhead View	A-12
A-13	Post-test Overall Overhead View	A-13
A-14	Pre-test MDB Left Side View (At Impact Position)	A-14
A-15	Pre-test MDB Right Side View (At Impact Position)	A-15
A-16	Pre-test Impact Point Target Close-up	A-16
A-17	Post-test Impact Point Target Close-up	A-17
A-18	Pre-test Driver Dummy Left Side (Door Open)	A-18
A-19	Pre-test Driver Dummy Left Side	A-19
A-20	Post-test Driver Dummy Left Side	A-20
A-21	Pre-test Driver Dummy Clearance	A-21
A-22	Post-test Driver Dummy Clearance	A-22
A-23	Pre-test Driver Dummy (Inside View)	A-23
A-24	Post-test Driver Dummy (Inside View)	A-24
A-25	Pre-test Driver Door (Inside View)	A-25
A-26	Post-test Driver Dummy Contact Points (Inside View)	A-26
A-27	Pre-test Passenger Dummy Left Side (Door Open)	A-27
A-28	Pre-test Passenger Dummy Left Side View	A-28
A-29	Post-test Passenger Dummy Left Side View	A-29
A-30	Pre-test Passenger Dummy Clearance	A-30
A-31	Post-test Passenger Dummy Clearance	A-31
A-32	Pre-test Passenger Dummy (Inside View)	A-32
A-33	Post-test Passenger Dummy (Inside View)	A-33

LIST OF PHOTOGRAPHS, ...(Continued)

Figure		Page
A-34	Pre-test Passenger Door (Inside View)	A-34
A-35	Post-test Passenger Dummy Contact Points (Inside View)	A-35
A-36	Pre-test Front View of Deformable Barrier	A-36
A-37	Post-test Front View of Deformable Barrier	A-37
A-38	Pre-test Top View of Deformable Barrier	A-38
A-39	Post-test Top View of Deformable Barrier	A-39
A-40	Pre-test Right Side View of Deformable Barrier	A-40
A-41	Post-test Right Side View of Deformable Barrier	A-41
A-42	Pre-test Left Side View of Deformable Barrier	A-42
A-43	Post-test Left Side View of Deformable Barrier	A-43
A-44	Vehicle On Rollover Top View	A-44
A-45	Vehicle During Impact	A-45



Figure A-1: Left Front, as Received



Figure A-2: Right Rear, as Received




Figure A-3: Vehicle Certification Label




Figure A-4: Vehicle Tire Label



Figure A-5: Front View, Pre-Test





Figure A-7: Rear View, Pre-Test



Figure A-8: Rear View, Post-Test



Figure A-9: Left (Impacted) Side View, Pre-Test



Figure A-10: Left (Impacted) Side View, Post-Test




Figure A-11: Overhead Close-up View at Impact Position, Pre-Test



Figure A-12: Overhead Overall View, Pre-Test



Figure A-13: Overhead Overall View, Post-Test



Figure A-14: MDB Left Side View at Impact Position, Pre-Test



Figure A-15: MDB Right Side View at Impact Position, Pre-Test



Figure A-16: Impact Point Target Close-up, Pre-Test



Figure A-17: Impact Point Target Close-up, Post-Test



Figure A-18: Driver Dummy Left Side with Door Open, Pre-Test



Figure A-19: Driver Dummy Left Side, Pre-test



Figure A-20: Driver Dummy Left Side, Post-Test



Figure A-21: Driver Dummy Clearance, Pre-Test



Figure A-22: Driver Dummy Clearance, Post-Test



Figure A-23: Driver Dummy Inside View, Pre-Test



Figure A-24: Driver Dummy Inside View, Post-Test




Figure A-25: Driver Door Inside View, Pre-Test





Figure A-27: Passenger Dummy Left Side with Door Open, Pre-Test



Figure A-28: Passenger Dummy Left Side, Pre-Test



Figure A-29: Passenger Dummy Left Side, Post-Test



Figure A-30: Passenger Dummy Clearance, Pre-Test



Figure A-31: Passenger Dummy Clearance, Post-Test



Figure A-32: Passenger Dummy Inside View, Pre-Test



Figure A-33: Passenger Dummy Inside View, Post-Test



Figure A-34: Passenger Door Inside View, Pre-Test



Figure A-35: Passenger Dummy Contact Points Inside View, Post-Test




Figure A-36: Front View of Deformable Barrier, Pre-Test



Figure A-37: Front View of Deformable Barrier, Post-Test




Figure A-38: Top View of Deformable Barrier, Pre-Test



Figure A-39: Top View of Deformable Barrier, Post-Test




Figure A-40: Right Side View of Deformable Barrier, Pre-Test



Figure A-41: Right Side View of Deformable Barrier, Post-Test



Figure A-42: Left Side View of Deformable Barrier, Pre-Test



Figure A-43: Left Side View of Deformable Barrier, Post-Test



Figure A-44: Vehicle on Rollover Device, Top View



Figure A-45: Vehicle During Impact

APPENDIX B
SID, VEHICLE, AND MDB RESPONSE DATA

LIST OF DATA PLOTS, DRIVER SID

Data Plot		Page
B-1	Driver Head CG X	B-1
B-2	Driver Head CG X Velocity	B-2
B-3	Driver Head CG Y	B-3
B-4	Driver Head CG Y Velocity	B-4
B-5	Driver Head CG Z	B-5
B-6	Driver Head CG Z Velocity	B-6
B-7	Driver Head CG Resultant	B-7
B-8	Driver Upper Rib Primary Y	B-8
B-9	Driver Upper Rib Primary Y Velocity	B-9
B-10	Driver Lower Rib Primary Y	B-10
B-11	Driver Lower Rib Primary Y Velocity	B-11
B-12	Driver Lower Spine Primary Y	B-12
B-13	Driver Lower Spine Primary Y Velocity	B-13
B-14	Driver Pelvis Primary Y	B-14
B-15	Driver Pelvis Primary Y Velocity	B-15
B-16	Driver Upper Rib Redundant Y	B-16
B-17	Driver Upper Rib Redundant Y Velocity	B-17
B-18	Driver Lower Rib Redundant Y	B-18
B-19	Driver Lower Rib Redundant Y Velocity	B-19
B-20	Driver Lower Spine Redundant Y	B-20
B-21	Driver Lower Spine Redundant Y Velocity	B-21
B-22	Driver Pelvis Redundant Y	B-22
B-23	Driver Pelvis Redundant Y Velocity	B-23
B-24	Driver Thorax Contact	B-24
B-25	Driver Pelvis Contact	B-25

LIST OF DATA PLOTS, PASSENGER SID

Data Plot		Page
B-26	Passenger Head CG X	B-26
B-27	Passenger Head CG X Velocity	B-27
B-28	Passenger Head CG Y	B-28
B-29	Passenger Head CG Y Velocity	B-29
B-30	Passenger Head CG Z	B-30
B-31	Passenger Head CG Z Velocity	B-31
B-32	Passenger Head CG Resultant	B-32
B-33	Passenger Upper Rib Primary Y	B-33
B-34	Passenger Upper Rib Primary Y Velocity	B-34
B-35	Passenger Lower Rib Primary Y	B-35
B-36	Passenger Lower Rib Primary Y Velocity	B-36
B-37	Passenger Lower Spine Primary Y	B-37
B-38	Passenger Lower Spine Primary Y Velocity	B-38
B-39	Passenger Pelvis Primary Y	B-39
B-40	Passenger Pelvis Primary Y Velocity	B-40
B-41	Passenger Upper Rib Redundant Y	B-41
B-42	Passenger Upper Rib Redundant Y Velocity	B-42
B-43	Passenger Lower Rib Redundant Y	B-43
B-44	Passenger Lower Rib Redundant Y Velocity	B-44
B-45	Passenger Lower Spine Redundant Y	B-45
B-46	Passenger Lower Spine Redundant Y Velocity	B-46
B-47	Passenger Pelvis Redundant Y	B-47
B-48	Passenger Pelvis Redundant Y Velocity	B-48
B-49	Passenger Thorax Contact	B-49
B-50	Passenger Pelvis Contact	B-50

LIST OF DATA PLOTS, VEHICLE

Data Plot		Page
B-51	Right Sill at Front Seat X	B-51
B-52	Right Sill at Front Seat X Velocity	B-52
B-53	Right Sill at Front Seat Y	B-53
B-54	Right Sill at Front Seat Y Velocity	B-54
B-55	Right Sill at Front Seat Z	B-55
B-56	Right Sill at Front Seat Z Velocity	B-56
B-57	Right Sill at Front Seat Resultant	B-57
B-58	Right Sill at Rear Seat X	B-58
B-59	Right Sill at Rear Seat X Velocity	B-59
B-60	Right Sill at Rear Seat Y	B-60
B-61	Right Sill at Rear Seat Y Velocity	B-61
B-62	Right Sill at Rear Seat Z	B-62
B-63	Right Sill at Rear Seat Z Velocity	B-63
B-64	Right Sill at Rear Seat Resultant	B-64
B-65	Rear Floor Pan Above Axle X	B-65
B-66	Rear Floor Pan Above Axle X	B-66
B-67	Rear Floor Pan Above Axle Y	B-67
B-68	Rear Floor Pan Above Axle Y Velocity	B-68
B-69	Rear Floor Above Axle Z	B-69
B-70	Rear Floor Pan Above Axle Z Velocity	B-70
B-71	Rear Floor Above Axle Resultant	B-71
B-72	Left Sill at Rear Door Y	B-72
B-73	Left Sill at Rear Door Y Velocity	B-73
B-74	Left Sill at Front Door Y	B-74
B-75	Left Sill at Front Door Y Velocity	B-75
B-76	Left Front Door Centerline Y	B-76
B-77	Left Front Door Centerline Y Velocity	B-77
B-78	Right Rear Occupant Compartment Y	B-78
B-79	Right Rear Occupant Compartment Y Velocity	B-79

LIST OF DATA PLOTS, VEHICLE...(CONTINUED)


Data Plot		Page
B-80	Left Front Door Mid Rear Y	B-80
B-81	Left Front Door Mid Rear Y Velocity	B-81
B-82	Left Front Door Upper Centerline Y	B-82
B-83	Left Front Door Upper Centerline Y Velocity	B-83
B-84	Left Rear Door Mid Rear Y	B-84
B-85	Left Rear Door Mid Rear Y Velocity	B-85
B-86	Left Rear Door Upper Centerline Y	B-86
B-87	Left Rear Door Upper Centerline Y Velocity	B-87
B-88	Left B-Post Lower Y	B-88
B-89	Left B-Post Lower Y Velocity	B-89
B-90	Left B-Post Middle Y	B-90
B-91	Left B-Post Middle Y Velocity	B-91
B-92	Left A-Post Lower Y	B-92
B-93	Left A-Post Lower Y Velocity	B-93
B-94	Left A-Post Middle Y	B-94
B-95	Left A-Post Middle Y Velocity	B-95
B-96	Left Front Seat Track Y	B-96
B-97	Left Front Seat Track Y Velocity	B-97
B-98	Left Rear Seat Structure Y	B-98
B-99	Left Rear Seat Structure Y Velocity	B-99
B-100	Vehicle CG X	B-100
B-101	Vehicle CG X Velocity	B-101
B-102	Vehicle CG Y	B-102
B-103	Vehicle CG Y Velocity	B-103
B-104	Vehicle CG Z	B-104
B-105	Vehicle CG Z Velocity	B-105
B-106	Vehicle CG Resultant	B-106

LIST OF DATA PLOTS, MDB

Data Plot	Page
B-107 Moving Deformable Barrier CG X	B-107
B-108 Moving Deformable Barrier CG X Velocity	B-108
B-109 Moving Deformable Barrier CG Y	B-109
B-110 Moving Deformable Barrier CG Y Velocity	B-110
B-111 Moving Deformable Barrier CG Z	B-111
B-112 Moving Deformable Barrier CG Z Velocity	B-112
B-113 Moving Deformable Barrier CG Resultant	B-113
B-114 Moving Deformable Barrier Rear X	B-114
B-115 Moving Deformable Barrier Rear X Velocity	B-115
B-116 Moving Deformable Barrier Rear Y	B-116
B-117 Moving Deformable Barrier Rear Y Velocity	B-117
B-118 Moving Deformable Barrier Right Bumper Contact Time	B-118

LIST OF DATA PLOTS, FIR FILTER DATA


Data Plot	Page
B-119 Driver Upper Rib Primary Y	B-119
B-120 Driver Lower Rib Primary Y	B-120
B-121 Driver Lower Spine Primary Y	B-121
B-122 Driver Pelvis Primary Y	B-122
B-123 Driver Upper Rib Redundant Y	B-123
B-124 Driver Lower Rib Redundant Y	B-124
B-125 Driver Lower Spine Redundant Y	B-125
B-126 Driver Pelvis Redundant Y	B-126
B-127 Passenger Upper Rib Primary Y	B-127
B-128 Passenger Lower Rib Primary Y	B-128
B-129 Passenger Lower Spine Primary Y	B-129
B-130 Passenger Pelvis Primary Y	B-130
B-131 Passenger Upper Rib Redundant Y	B-131
B-132 Passenger Lower Rib Redundant Y	B-132
B-133 Passenger Lower Spine Redundant Y	B-133
B-134 Passenger Pelvis Redundant Y	B-134



Curve Description: Driver Head CG X
Maximum Value: 27.1 at 40.8 Milliseconds
Minimum Value: -23.3 at 76.6 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-001

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Head CG X Velocity
Maximum Value: 5.0 at 43.9 Milliseconds
Minimum Value: -27.1 at 113.4 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-001

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Driver Head CG Y

Maximum Value: 58.0 at 39.1 Milliseconds

Minimum Value: -10.1 at 189.2 Milliseconds

SAE Filter Class: 1000


Date of Test: 12/12/00

Curve Number: FIL-002

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Head CG Y Velocity
Maximum Value: 38.1 at 152.2 Milliseconds
Minimum Value: -1.1 at 31.0 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-002

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Head CG Z
Maximum Value: 42.2 at 46.9 Milliseconds
Minimum Value: -13.6 at 37.4 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-003

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Head CG Z Velocity
Maximum Value: 98.6 at 189.9 Milliseconds
Minimum Value: -2.7 at 40.1 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-003

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Head CG Resultant
Maximum Value: 62.3 at 39.1 Milliseconds
Minimum Value: 0.1 at 4.2 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: RES-001

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Upper Rib Primary Y
Maximum Value: 122.8 at 151.1 Milliseconds
Minimum Value: -75.4 at 151.6 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-004

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Driver Upper Rib Primary Y Velocity

Maximum Value: 42.2 at 68.3 Milliseconds

Minimum Value: 0.0 at 11.1 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-004

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Lower Rib Primary Y
Maximum Value: 171.3 at 151.1 Milliseconds
Minimum Value: -128.2 at 151.5 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-005

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Driver Lower Rib Primary Y Velocity

Maximum Value: 40.7 at 69.3 Milliseconds

Minimum Value: 0.0 at 11.5 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-005

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Lower Spine Primary Y
Maximum Value: 116.6 at 28.1 Milliseconds
Minimum Value: -32.9 at 67.2 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: FIL-006

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Driver Lower Spine Primary Y Velocity

Maximum Value: 51.7 at 53.0 Milliseconds

Minimum Value: 0.0 at 14.0 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-006

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Pelvis Primary Y
Maximum Value: 98.3 at 31.7 Milliseconds
Minimum Value: -35.0 at 74.7 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-007

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Pelvis Primary Y Velocity
Maximum Value: 47.1 at 47.4 Milliseconds
Minimum Value: 0.0 at 3.6 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-007

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Upper Rib Redundant Y
Maximum Value: 122.7 at 151.0 Milliseconds
Minimum Value: -80.7 at 151.5 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-008

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Driver Upper Rib Redundant Y Velocity

Maximum Value: 42.8 at 68.3 Milliseconds

Minimum Value: 0.0 at 1.7 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-008

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Lower Rib Redundant Y
Maximum Value: 165.4 at 151.0 Milliseconds
Minimum Value: -134.5 at 151.5 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-009

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Driver Lower Rib Redundant Y Velocity

Maximum Value: 41.6 at 69.2 Milliseconds

Minimum Value: 0.0 at 5.2 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-009

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Lower Spine Redundant Y
Maximum Value: 117.4 at 28.1 Milliseconds
Minimum Value: -33.5 at 67.2 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: FIL-010

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Driver Lower Spine Redundant Y Velocity

Maximum Value: 51.8 at 52.6 Milliseconds

Minimum Value: 0.0 at 0.3 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-0010

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Pelvis Redundant Y
Maximum Value: 98.7 at 30.9 Milliseconds
Minimum Value: -35.1 at 74.1 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-011

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Pelvis Redundant Y Velocity
Maximum Value: 47.5 at 47.8 Milliseconds
Minimum Value: 0.0 at 0.0 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-011

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Thorax Contact
Maximum Value: 108.1 at 13.0 Milliseconds
Crossing Point: 50% at 12.8 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-012

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Pelvis Contact
Maximum Value: 104.5 at 20.3 Milliseconds
Crossing Point: 50% at 20.2 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-013

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Head CG X
Maximum Value: 10.4 at 173.0 Milliseconds
Minimum Value: -27.7 at 55.7 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-014

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Head CG X Velocity
Maximum Value: 1.4 at 39.1 Milliseconds
Minimum Value: -20.4 at 134.6 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-014

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Head CG Y
Maximum Value: 145.6 at 55.8 Milliseconds
Minimum Value: -14.9 at 31.5 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-015

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Head CG Y Velocity
Maximum Value: 46.1 at 114.5 Milliseconds
Minimum Value: -5.1 at 41.1 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-015

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Head CG Z
Maximum Value: 58.7 at 56.1 Milliseconds
Minimum Value: -33.3 at 61.3 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-016

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Head CG Z Velocity
Maximum Value: 44.3 at 189.9 Milliseconds
Minimum Value: -1.9 at 28.9 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-016

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Head CG Resultant
Maximum Value: 158.0 at 55.8 Milliseconds
Minimum Value: 0.1 at 1.7 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: RES-014

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Upper Rib Primary Y
Maximum Value: 96.2 at 152.9 Milliseconds
Minimum Value: -60.3 at 62.7 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-017

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Pass. Upper Rib Primary Y Velocity

Maximum Value: 44.2 at 65.6 Milliseconds

Minimum Value: 0.0 at 0.1 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-017

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Lower Rib Primary Y
Maximum Value: 133.8 at 152.9 Milliseconds
Minimum Value: -97.9 at 60.7 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-018

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Lower Rib Primary Y Velocity
Maximum Value: 47.0 at 49.2 Milliseconds
Minimum Value: 0.0 at 0.0 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-018

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Lower Spine Primary Y
Maximum Value: 86.0 at 35.8 Milliseconds
Minimum Value: -56.8 at 64.8 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: FIL-019

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Pass. Lower Spine Primary Y Velocity

Maximum Value: 51.8 at 49.6 Milliseconds

Minimum Value: 0.0 at 0.0 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-019

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Pelvis Primary Y
Maximum Value: 107.1 at 24.5 Milliseconds
Minimum Value: -35.9 at 55.7 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-020

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Pelvis Primary Y Velocity
Maximum Value: 48.4 at 39.0 Milliseconds
Minimum Value: 0.0 at 5.3 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-020

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Upper Rib Redundant Y
Maximum Value: 86.1 at 32.4 Milliseconds
Minimum Value: -48.8 at 62.7 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-021

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Pass. Upper Rib Redundant Y Velocity

Maximum Value: 44.2 at 65.5 Milliseconds

Minimum Value: 0.0 at 0.1 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-021

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Pass. Lower Rib Redundant Y

Maximum Value: 126.2 at 152.8 Milliseconds

Minimum Value: -108.0 at 60.6 Milliseconds

SAE Filter Class: 1000


Date of Test: 12/12/00

Curve Number: FIL-022

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Pass. Lower Rib Redundant Y Velocity

Maximum Value: 46.6 at 49.2 Milliseconds

Minimum Value: 0.0 at 5.1 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-022

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Lower Spine Redundant Y
Maximum Value: 86.8 at 35.7 Milliseconds
Minimum Value: -55.3 at 64.8 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: FIL-023

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Pass. Lower Spine Redundant Y Velocity

Maximum Value: 51.6 at 49.7 Milliseconds

Minimum Value: 0.0 at 1.5 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-023

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Pelvis Redundant Y
Maximum Value: 107.3 at 24.4 Milliseconds
Minimum Value: -37.0 at 55.8 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-024

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Pass. Pelvis Redundant Y Velocity

Maximum Value: 48.5 at 39.1 Milliseconds

Minimum Value: 0.0 at 2.1 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-024

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Thorax Contact
Maximum Value: 108.2 at 12.9 Milliseconds
Crossing Point: 50% at 12.7 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-025

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Pelvis Contact
Maximum Value: 105.3 at 110.9 Milliseconds
Crossing Point: 50% at 13.9 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-026

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Front Seat X
Maximum Value: 3.8 at 62.8 Milliseconds
Minimum Value: -5.4 at 15.4 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-027

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Front Seat X Velocity
Maximum Value: 0.1 at 3.9 Milliseconds
Minimum Value: -3.5 at 43.4 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-027

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Front Seat Y
Maximum Value: 21.7 at 8.1 Milliseconds
Minimum Value: -2.7 at 152.9 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-028

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Front Seat Y Velocity
Maximum Value: 21.5 at 101.6 Milliseconds
Minimum Value: 0.0 at 0.0 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-028

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Front Seat Z
Maximum Value: 5.9 at 26.7 Milliseconds
Minimum Value: -3.9 at 9.8 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-029

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Front Seat Z Velocity
Maximum Value: 4.2 at 157.2 Milliseconds
Minimum Value: -1.2 at 23.8 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-029

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Front Seat Resultant
Maximum Value: 21.9 at 8.1 Milliseconds
Minimum Value: 0.4 at 140.1 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: RES-027

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Rear Seat X
Maximum Value: 4.3 at 62.6 Milliseconds
Minimum Value: -5.0 at 15.9 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-030

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Rear Seat X Velocity
Maximum Value: 0.6 at 182.8 Milliseconds
Minimum Value: -2.9 at 44.4 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-030

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Rear Seat Y
Maximum Value: 20.7 at 8.6 Milliseconds
Minimum Value: -4.0 at 153.7 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-031

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Rear Seat Y Velocity
Maximum Value: 29.0 at 103.5 Milliseconds
Minimum Value: 0.0 at 2.5 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-031

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Rear Seat Z
Maximum Value: 10.3 at 59.0 Milliseconds
Minimum Value: -9.5 at 19.9 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-032

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Right Sill at Rear Seat Z Velocity

Maximum Value: 5.4 at 163.4 Milliseconds

Minimum Value: -1.6 at 22.0 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-032

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Sill at Rear Resultant
Maximum Value: 21.2 at 8.9 Milliseconds
Minimum Value: 0.4 at 147.8 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: RES-030

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Rear Floor Above Axle X
Maximum Value: 3.3 at 59.4 Milliseconds
Minimum Value: -7.0 at 16.3 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-033

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Rear Floor Above Axle X Velocity
Maximum Value: 0.5 at 12.1 Milliseconds
Minimum Value: -3.3 at 54.7 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-033

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Rear Floor Above Axle Y
Maximum Value: 18.9 at 9.1 Milliseconds
Minimum Value: -3.4 at 133.6 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-034

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Rear Floor Above Axle Z Velocity
Maximum Value: 4.0 at 178.2 Milliseconds
Minimum Value: -0.4 at 16.4 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-035

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Rear Floor Above Axle Z
Maximum Value: 10.6 at 21.2 Milliseconds
Minimum Value: -3.5 at 9.3 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-035

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Rear Floor Above Axle Y Velocity
Maximum Value: 37.5 at 104.3 Milliseconds
Minimum Value: 0.0 at 2.1 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-034

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Rear Floor Above Axle Resultant
Maximum Value: 19.2 at 9.2 Milliseconds
Minimum Value: 0.0 at 0.7 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: RES-033

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Sill at Rear Door Y
Maximum Value: 85.8 at 19.6 Milliseconds
Minimum Value: -18.3 at 58.8 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-036

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Sill at Rear Door Y Velocity
Maximum Value: 33.7 at 45.3 Milliseconds
Minimum Value: -0.1 at 0.9 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-036

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Sill at Front Door Y
Maximum Value: 42.8 at 23.8 Milliseconds
Minimum Value: -7.7 at 68.5 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-037

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Sill at Front Door Y Velocity
Maximum Value: 24.2 at 43.1 Milliseconds
Minimum Value: 0.0 at 1.5 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-037

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Front Door Centerline Y
Maximum Value: 96.7 at 13.5 Milliseconds
Minimum Value: -57.8 at 22.7 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-038

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Front Door CL Y Velocity
Maximum Value: 47.6 at 19.5 Milliseconds
Minimum Value: 0.0 at 1.0 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-038

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Rear Occ. Compartment Y
Maximum Value: 22.5 at 8.4 Milliseconds
Minimum Value: -3.9 at 152.5 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-039

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Right Rear Occ. Comp. Y Velocity
Maximum Value: 27.2 at 102.2 Milliseconds
Minimum Value: 0.0 at 2.6 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-039

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Left Front Door Mid Rear Y *

Maximum Value: 147.6 at 12.4 Milliseconds

Minimum Value: -81.2 at 17.5 Milliseconds

SAE Filter Class: 60

Date of Test: 12/12/00


Curve Number: FIL-040

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

*Channel failed at 22.0 Msec.





Curve Description: Left Front Door Mid Rear Y Velocity *

Maximum Value: 49.9 at 14.7 Milliseconds

Minimum Value: 0.0 at 0.0 Milliseconds

SAE Filter Class: 180

Date of Test: 12/12/00


Curve Number: IN1-040

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

*Channel failed at 22.0 Msec.





Curve Description: Left Front Door Upper CL Y *

Maximum Value: 167.3 at 13.9 Milliseconds

Minimum Value: -60.0 at 22.9 Milliseconds

SAE Filter Class: 60

Date of Test: 12/12/00


Curve Number: FIL-041

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

*Channel failed at 30.5 Msec.





Curve Description: Left Front Door Upper CL Y Velocity *

Maximum Value: 47.9 at 21.3 Milliseconds

Minimum Value: -0.1 at 0.8 Milliseconds

SAE Filter Class: 180

Date of Test: 12/12/00


Curve Number: IN1-041

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

*Channel failed at 30.5 Msec.






Curve Description: Left Rear Door Mid Rear Y
Maximum Value: 196.3 at 7.0 Milliseconds
Minimum Value: -57.7 at 23.0 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-042

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Left Rear Door Mid Rear Y Velocity

Maximum Value: 45.5 at 43.3 Milliseconds

Minimum Value: -4.8 at 2.5 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-042

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Rear Door Upper CL Y
Maximum Value: 134.4 at 13.2 Milliseconds
Minimum Value: -50.8 at 32.3 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-043

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Rear Door Upper CL Y Velocity
Maximum Value: 47.0 at 22.0 Milliseconds
Minimum Value: -1.4 at 3.5 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-043

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left B-Post Lower Y
Maximum Value: 193.7 at 2.9 Milliseconds
Minimum Value: -49.5 at 17.9 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-044

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left B-Post Lower Y Velocity
Maximum Value: 50.5 at 16.4 Milliseconds
Minimum Value: -0.4 at 0.4 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-044

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan



B-90




Curve Description: Left B-Post Middle Y
Maximum Value: 167.2 at 3.2 Milliseconds
Minimum Value: -33.3 at 24.9 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-045

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan



KAR21003-04




Curve Description: Left B-Post Middle Y Velocity
Maximum Value: 43.7 at 20.5 Milliseconds
Minimum Value: -0.3 at 0.6 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-045

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan



B-92



Curve Description: Left A-Post Lower Y

Maximum Value: 98.4 at 2.9 Milliseconds

Minimum Value: -10.7 at 19.6 Milliseconds

SAE Filter Class: 60

Date of Test: 12/12/00


Curve Number: FIL-046

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan




KAR21003-04



Curve Description: Left A-Post Lower Y Velocity
Maximum Value: 20.7 at 162.7 Milliseconds
Minimum Value: -0.2 at 0.9 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-046

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left A-Post Middle Y
Maximum Value: 50.1 at 2.8 Milliseconds
Minimum Value: -3.0 at 182.3 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-047

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left A-Post Middle Y Velocity
Maximum Value: 24.6 at 162.9 Milliseconds
Minimum Value: 0.0 at 0.9 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-047

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Front Seat Track Y
Maximum Value: 53.7 at 13.7 Milliseconds
Minimum Value: -0.9 at 28.5 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-048

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Left Front Seat Track Y Velocity
Maximum Value: 18.2 at 143.4 Milliseconds
Minimum Value: 0.0 at 0.0 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-048

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Left Rear Seat Structure Y **

Maximum Value: 0.0 at 0.0 Milliseconds

Minimum Value: 0.0 at 0.0 Milliseconds

SAE Filter Class: 60

Date of Test: 12/12/00


Curve Number: FIL-049

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

** Not Installed





Curve Description: Left Rear Seat Structure Y Velocity **

Maximum Value: 0.0 at 0.0 Milliseconds

Minimum Value: 0.0 at 0.0 Milliseconds

SAE Filter Class: 180

Date of Test: 12/12/00


Curve Number: IN1-049

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan

** Not Installed






Curve Description: Vehicle CG X
Maximum Value: 4.3 at 64.7 Milliseconds
Minimum Value: -7.5 at 37.5 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-050

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Vehicle CG X Velocity
Maximum Value: 0.2 at 9.1 Milliseconds
Minimum Value: -4.1 at 98.4 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-050

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Vehicle CG Y
Maximum Value: 24.2 at 19.4 Milliseconds
Minimum Value: -10.3 at 81.8 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-051

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Vehicle CG Y Velocity
Maximum Value: 27.6 at 80.7 Milliseconds
Minimum Value: 0.0 at 2.1 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-051

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Vehicle CG Z
Maximum Value: 12.0 at 33.6 Milliseconds
Minimum Value: -10.5 at 24.1 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-052

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Vehicle CG Z Velocity
Maximum Value: 1.6 at 82.7 Milliseconds
Minimum Value: -4.6 at 30.3 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-052

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Vehicle CG Resultant
Maximum Value: 25.2 at 19.4 Milliseconds
Minimum Value: 0.2 at 130.2 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: RES-050

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB CG X
Maximum Value: 4.1 at 136.7 Milliseconds
Minimum Value: -18.7 at 41.0 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-053

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB CG X Velocity
Maximum Value: 55.0 at 0.0 Milliseconds
Minimum Value: 20.8 at 98.2 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-053

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB CG Y
Maximum Value: 4.1 at 149.6 Milliseconds
Minimum Value: -6.6 at 21.0 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-054

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: MDB CG Y Velocity

Maximum Value: 28.2 at 4.5 Milliseconds

Minimum Value: 20.1 at 164.6 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-054

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB CG Z
Maximum Value: 14.2 at 132.4 Milliseconds
Minimum Value: -12.4 at 144.3 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-055

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB CG Z Velocity
Maximum Value: 2.4 at 137.0 Milliseconds
Minimum Value: -1.6 at 49.2 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-055

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB CG Resultant
Maximum Value: 19.9 at 40.9 Milliseconds
Minimum Value: 0.6 at 177.3 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: RES-053

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB Rear X
Maximum Value: 3.3 at 148.1 Milliseconds
Minimum Value: -20.3 at 39.4 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-056

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB Rear X Velocity
Maximum Value: 55.0 at 0.1 Milliseconds
Minimum Value: 18.2 at 93.9 Milliseconds
SAE Filter Class: 180
Date of Test: 12/12/00
Curve Number: IN1-056

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB Rear Y
Maximum Value: 2.3 at 103.8 Milliseconds
Minimum Value: -7.6 at 23.0 Milliseconds
SAE Filter Class: 60
Date of Test: 12/12/00
Curve Number: FIL-057

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: MDB Rear Y Velocity

Maximum Value: 28.2 at 8.1 Milliseconds

Minimum Value: 21.0 at 66.9 Milliseconds

SAE Filter Class: 180


Date of Test: 12/12/00

Curve Number: IN1-057

Test Program: 55/28 km/h Side Impact NCAP No.: M10117

Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: MDB Right Bumper Contact
Maximum Value: 100.8 at 19.4 Milliseconds
Crossing Point: 50% at 0.1 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00
Curve Number: FIL-058

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Upper Rib Primary Y
Maximum Value: 79.8 at 25.3 Milliseconds
Minimum Value: -21.6 at 73.2 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-004

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Lower Rib Primary Y
Maximum Value: 79.6 at 24.0 Milliseconds
Minimum Value: -23.3 at 74.3 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-005

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Lower Spine Primary Y
Maximum Value: 107.1 at 28.5 Milliseconds
Minimum Value: -30.3 at 67.9 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-006

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Pelvis Primary Y
Maximum Value: 95.7 at 32.0 Milliseconds
Minimum Value: -34.2 at 75.3 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-007

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Upper Rib Redundant Y
Maximum Value: 78.4 at 25.3 Milliseconds
Minimum Value: -22.4 at 73.0 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-008

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Lower Rib Redundant Y
Maximum Value: 78.8 at 23.9 Milliseconds
Minimum Value: -23.3 at 74.2 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-009

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Lower Spine Redundant Y
Maximum Value: 107.7 at 28.5 Milliseconds
Minimum Value: -30.9 at 67.9 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-010

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Driver Pelvis Redundant Y
Maximum Value: 95.6 at 32.0 Milliseconds
Minimum Value: -34.4 at 75.4 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-011

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Upper Rib Primary Y
Maximum Value: 69.7 at 33.2 Milliseconds
Minimum Value: -24.8 at 69.2 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-017

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Lower Rib Primary Y
Maximum Value: 88.0 at 34.7 Milliseconds
Minimum Value: -31.7 at 67.6 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-018

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Lower Spine Primary Y
Maximum Value: 80.9 at 35.2 Milliseconds
Minimum Value: -57.5 at 64.2 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-019

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Pelvis Primary Y
Maximum Value: 99.5 at 25.1 Milliseconds
Minimum Value: -34.2 at 57.5 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-020

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Upper Rib Redundant Y
Maximum Value: 70.2 at 33.3 Milliseconds
Minimum Value: -22.8 at 69.0 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-021

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Lower Rib Redundant Y
Maximum Value: 88.9 at 34.8 Milliseconds
Minimum Value: -32.0 at 67.4 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-022

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan






Curve Description: Pass. Lower Spine Redundant Y
Maximum Value: 81.7 at 35.4 Milliseconds
Minimum Value: -56.6 at 64.1 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-023

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan





Curve Description: Pass. Pelvis Redundant Y
Maximum Value: 99.1 at 25.1 Milliseconds
Minimum Value: -34.0 at 57.0 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/12/00
Curve Number: FIR-024

Test Program: 55/28 km/h Side Impact NCAP No.: M10117
Test Vehicle: 2001 Pontiac Grand Prix 4 Door Sedan



APPENDIX C
SID CONFIGURATION AND PERFORMANCE VERIFICATION DATA

APPENDIX C
PRE-TEST SID CONFIGURATION AND PERFORMANCE VERIFICATION DATA



Performance Verification Data Side Impact Dummy (SID) External Dimensions

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: N/A

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory temperature	°C	20.4 to 22.1	21.1	Pass
Laboratory relative humidity	%	10 to 70	30	Pass
SH- Seated Height	mm	889 to 909	906	Pass
HP- Hip Point Height	mm	99 (reference)	99	Pass
RH- Rib Height	mm	502 to 520	512	Pass
KH- Knee Pivot From Back Line	mm	511 to 526	520	Pass
KV- Knee Pivot From Floor	mm	490 to 505	495	Pass
HW- Hip Width	mm	356 to 391	365	Pass
Overall Test Results				Pass

Laboratory Technician

December 11, 2000

Test Date

Approved By

Date



Performance Verification Data

Side Impact Dummy (SID)

Thorax Lateral Impact

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: TI11C

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	4.21 to 4.33	4.27	Pass
Left Upper Rib Acceleration	G's	37.0 to 46.0	42.0	Pass
Left Lower Rib Acceleration	G's	37.0 to 46.0	41.1	Pass
Thoracic Spine Acceleration	G's	15.0 to 22.0	21.8	Pass
Overall Test Results				Pass

Laboratory Technician


December 9, 2000

Test Date

Approved By


Date

C-3

Curve Description: Left Upper Rib Y AccelerationMaximum Value: 42.0 at 5.6 MillisecondsMinimum Value: -12.2 at 20.8 MillisecondsSAE Filter Class: FIR 100Date of Test: 12/9/00Test Program: SID Thorax Lateral Impact TestTest Information: SID S/N: 274 Test I.D.: TI11C

KAR21003-04

C-4




Curve Description: Left Lower Rib Y Acceleration
Maximum Value: 41.1 at 5.3 Milliseconds
Minimum Value: -9.1 at 18.7 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/9/00

Test Program: SID Thorax Lateral Impact Test
Test Information: SID S/N: 274 Test I.D.: TI11C



KAR21003-04

C-5



Curve Description: Lower Spine Y Acceleration
Maximum Value: 21.8 at 12.0 Milliseconds
Minimum Value: -5.2 at 40.3 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/9/00

Test Program: SID Thorax Lateral Impact Test
Test Information: SID S/N: 274 Test I.D.: TI11C



KAR21003-04



Performance Verification Data

Side Impact Dummy (SID)

Left Side Pelvis Lateral Impact

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: PI11G

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	4.21 to 4.33	4.33	Pass
Pelvis Acceleration	G's	40.0 to 60.0	41.1	Pass
Acceleration Time Above 20 G's	Msec.	3.0 to 7.0 Msec.	6.0	Pass
Is Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician


December 9, 2000

Test Date

Approved By

Date

C-7



Curve Description: Pelvis Y Axis Acceleration
Maximum Value: 41.1 at 10.3 Milliseconds
Minimum Value: -7.9 at 26.2 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/9/00

Test Program: Left Side Pelvis Lateral Impact
Test Information: SID S/N: 274 Test I.D.: PI11G



KAR21003-04



Performance Verification Data Side Impact Dummy (SID) Abdominal Compression Test

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: AB12E

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°F	66 to 78	70	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Force at 0.5 Inches of Displacement	Pounds	23.0 to 36.0	29.3	Pass
Force at 0.75 Inches of Displacement	Pounds	36.0 to 50.0	42.7	Pass
Force at 1.0 Inches of Displacement	Pounds	50.0 to 63.0	59.4	Pass
Force at 1.3 Inches of Displacement	Pounds	73.0 to 88.0	82.2	Pass
Overall Test Results				Pass

Laboratory Technician


December 10, 2000

Test Date

Approved By

Date

C-9

Curve Description: Abdomen Force vs. DisplacementForce at 0.5 In.: 29.3 PoundsForce at 0.75 In.: 42.7 PoundsForce at 1.0 In.: 59.4 PoundsForce at 1.3 In.: 82.2 PoundsDate of Test: 12/10/00Test Program: Hybrid II Abdominal CompressionTest Information: SID S/N: 274 Test I.D.: AB12E

KAR21003-04



Performance Verification Data Side Impact Dummy (SID) Head Drop Calibration

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: HD12E

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°F	66 to 78	70	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Peak Resultant Acceleration	G's	210.0 to 260.0	250.5	Pass
Peak Lateral Acceleration	G's	≤10.0	4.5	Pass
Time Above 100 G's	Msec.	0.9 to 1.5	1.0	Pass
Is Resultant Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician


December 10, 2000

Test Date

Approved By

Date

C-11




Curve Description: Head Resultant Acceleration
Maximum Value: 250.5 at 1.5 Milliseconds
Minimum Value: 0.7 at 0.0 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/10/00

Test Program: Hybrid II Head Drop Calibration
Test Information: SID S/N: 274 Test I.D.: HD12E



KAR21003-04

C-12



Curve Description: Head Y Axis Acceleration
Maximum Value: 4.5 at 2 Milliseconds
Minimum Value: -2.6 at 3.1 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/10/00

Test Program: Hybrid II Head Drop Calibration
Test Information: SID S/N: 274 Test I.D.: HD12E



KAR21003-04



Performance Verification Data Side Impact Dummy (SID) External Dimensions

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: N/A

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory temperature	°C	20.4 to 22.1	21.1	Pass
Laboratory relative humidity	%	10 to 70	30	Pass
SH- Seated Height	mm	889 to 909	905	Pass
HP- Hip Point Height	mm	99 (reference)	99	Pass
RH- Rib Height	mm	502 to 520	510	Pass
KH- Knee Pivot From Back Line	mm	511 to 526	520	Pass
KV- Knee Pivot From Floor	mm	490 to 505	495	Pass
HW- Hip Width	mm	356 to 391	360	Pass
Overall Test Results				Pass

Laboratory Technician

December 11, 2000

Test Date

Approved By

Date



Performance Verification Data Side Impact Dummy (SID) Thorax Lateral Impact

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: TI11D

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	4.21 to 4.33	4.27	Pass
Left Upper Rib Acceleration	G's	37.0 to 46.0	38.8	Pass
Left Lower Rib Acceleration	G's	37.0 to 46.0	38.4	Pass
Thoracic Spine Acceleration	G's	15.0 to 22.0	21.1	Pass
Overall Test Results				Pass

Laboratory Technician


December 9, 2000

Test Date

Approved By

Date

C-15



Curve Description: Left Upper Rib Y Acceleration

Maximum Value: 38.8 at 7.0 Milliseconds

Minimum Value: -12.8 at 22.2 Milliseconds

SAE Filter Class: FIR 100


Date of Test: 12/9/00

Test Program: SID Thorax Lateral Impact Test

Test Information: SID S/N: 275 Test I.D.: TI11D




KAR21003-04



Curve Description: Left Lower Rib Y Acceleration
Maximum Value: 38.4 at 6.8 Milliseconds
Minimum Value: -9.5 at 23.0 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/9/00

Test Program: SID Thorax Lateral Impact Test
Test Information: SID S/N: 275 Test I.D.: TI11D





Curve Description: Lower Spine Y Acceleration
Maximum Value: 21.1 at 13.5 Milliseconds
Minimum Value: -4.3 at 34.4 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/9/00

Test Program: SID Thorax Lateral Impact Test
Test Information: SID S/N: 275 Test I.D.: TI11D





Performance Verification Data Side Impact Dummy (SID) Left Side Pelvis Lateral Impact

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: PI11H

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	4.21 to 4.33	4.33	Pass
Pelvis Acceleration	G's	40.0 to 60.0	41.9	Pass
Acceleration Time Above 20 G's	Msec.	3.0 to 7.0 Msec.	6.7	Pass
Is Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician


December 9, 2000

Test Date

Approved By

Date

C-19



Curve Description: Pelvis Y Axis Acceleration
Maximum Value: 41.9 at 10.6 Milliseconds
Minimum Value: -8.3 at 26.9 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/9/00

Test Program: Left Side Pelvis Lateral Impact
Test Information: SID S/N: 275 Test I.D.: PI11H



KAR21003-04



Performance Verification Data Side Impact Dummy (SID) Abdominal Compression Test

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: AB12F

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°F	66 to 78	70	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Force at 0.5 Inches of Displacement	Pounds	23.0 to 36.0	29.5	Pass
Force at 0.75 Inches of Displacement	Pounds	36.0 to 50.0	42.5	Pass
Force at 1.0 Inches of Displacement	Pounds	50.0 to 63.0	59.4	Pass
Force at 1.3 Inches of Displacement	Pounds	73.0 to 88.0	81.6	Pass
Overall Test Results				Pass

Laboratory Technician


December 10, 2000

Test Date

Approved By

Date

C-21



Curve Description: Abdomen Force vs. Displacement

Force at 0.5 In.: 29.5 Pounds

Force at 0.75 In.: 42.5 Pounds

Force at 1.0 In.: 59.4 Pounds

Force at 1.3 In.: 81.6 Pounds

Date of Test: 12/10/00

Test Program: Hybrid II Abdominal Compression

Test Information: SID S/N: 275 Test I.D.: AB12F



KAR21003-04



Performance Verification Data Side Impact Dummy (SID) Head Drop Calibration

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: HD12F

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°F	66 to 78	70	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Peak Resultant Acceleration	G's	210.0 to 260.0	244.1	Pass
Peak Lateral Acceleration	G's	≤10.0	4.8	Pass
Time Above 100 G's	Msec.	0.9 to 1.5	1.0	Pass
Is Resultant Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician


December 10, 2000

Test Date

Approved By

Date

C-23




Curve Description: Head Resultant Acceleration
Maximum Value: 244.1 at 1.5 Milliseconds
Minimum Value: 0.8 at 0.0 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/10/00

Test Program: Hybrid II Head Drop Calibration
Test Information: SID S/N: 275 Test I.D.: HD12F



KAR21003-04

C-24



Curve Description: Head Y Axis Acceleration

Maximum Value:	4.8	at	1.4	Milliseconds
Minimum Value:	-4.6	at	3	Milliseconds
SAE Filter Class:	1000			
Date of Test:	12/10/00			

Test Program: Hybrid II Head Drop Calibration

Test Information: SID S/N: 275 Test I.D.: HD12F



KAR21003-04

APPENDIX C
POST-TEST SID CONFIGURATION AND PERFORMANCE VERIFICATION DATA



Performance Verification Data Side Impact Dummy (SID) External Dimensions

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: N/A

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory temperature	°C	20.4 to 22.1	21.1	Pass
Laboratory relative humidity	%	10 to 70	30	Pass
SH- Seated Height	mm	889 to 909	906	Pass
HP- Hip Point Height	mm	99 (reference)	99	Pass
RH- Rib Height	mm	502 to 520	515	Pass
KH- Knee Pivot From Back Line	mm	511 to 526	520	Pass
KV- Knee Pivot From Floor	mm	490 to 505	500	Pass
HW- Hip Width	mm	356 to 391	365	Pass
Overall Test Results				Pass

Laboratory Technician

December 13, 2000

Test Date

Approved By

Date



Performance Verification Data Side Impact Dummy (SID) Thorax Lateral Impact

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: TI12A

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	4.21 to 4.33	4.27	Pass
Left Upper Rib Acceleration	G's	37.0 to 46.0	40.0	Pass
Left Lower Rib Acceleration	G's	37.0 to 46.0	38.8	Pass
Thoracic Spine Acceleration	G's	15.0 to 22.0	18.5	Pass
Overall Test Results				Pass


Laboratory Technician

December 13, 2000

Test Date

Approved By

Date



Curve Description: Left Upper Rib Y Acceleration

Maximum Value: 40.0 at 11.2 Milliseconds

Minimum Value: -15.5 at 23.8 Milliseconds

SAE Filter Class: FIR 100


Date of Test: 12/13/00

Test Program: SID Thorax Lateral Impact Test

Test Information: SID S/N: 274 Test I.D.: TI12A




C-28

Curve Description: Left Lower Rib Y AccelerationMaximum Value: 38.8 at 10.8 MillisecondsMinimum Value: -12.9 at 23.5 MillisecondsSAE Filter Class: FIR 100Date of Test: 12/13/00Test Program: SID Thorax Lateral Impact TestTest Information: SID S/N: 274 Test I.D.: TI12A

KAR21003-04

C-29



Curve Description: Lower Spine Y Acceleration
Maximum Value: 18.5 at 17.6 Milliseconds
Minimum Value: -4.7 at 39.0 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/13/00

Test Program: SID Thorax Lateral Impact Test
Test Information: SID S/N: 274 Test I.D.: TI12A



KAR21003-04



Performance Verification Data

Side Impact Dummy (SID)

Left Side Pelvis Lateral Impact

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: PI12A

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	4.21 to 4.33	4.33	Pass
Pelvis Acceleration	G's	40.0 to 60.0	43.4	Pass
Acceleration Time Above 20 G's	Msec.	3.0 to 7.0 Msec.	6.7	Pass
Is Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician


December 13, 2000

Test Date

Approved By

Date

C-31



Curve Description: Pelvis Y Axis Acceleration
Maximum Value: 43.4 at 10.2 Milliseconds
Minimum Value: -9.2 at 23.8 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/13/00

Test Program: Left Side Pelvis Lateral Impact
Test Information: SID S/N: 274 Test I.D.: PI12A



KAR21003-04



Performance Verification Data Side Impact Dummy (SID) Abdominal Compression Test

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: AB12G

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°F	66 to 78	70	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Force at 0.5 Inches of Displacement	Pounds	23.0 to 36.0	29.3	Pass
Force at 0.75 Inches of Displacement	Pounds	36.0 to 50.0	42.7	Pass
Force at 1.0 Inches of Displacement	Pounds	50.0 to 63.0	59.4	Pass
Force at 1.3 Inches of Displacement	Pounds	73.0 to 88.0	82.2	Pass
Overall Test Results				Pass

Laboratory Technician


December 12, 2000

Test Date

Approved By

Date

C-33

Curve Description: Abdomen Force vs. DisplacementForce at 0.5 In.: 29.3 PoundsForce at 0.75 In.: 42.7 PoundsForce at 1.0 In.: 59.4 PoundsForce at 1.3 In.: 82.2 PoundsDate of Test: 12/12/00Test Program: Hybrid II Abdominal CompressionTest Information: SID S/N: 274 Test I.D.: AB12G

KAR21003-04



Performance Verification Data Side Impact Dummy (SID) Head Drop Calibration

ATD Serial No.: 274

Part Serial No.: N/A

Test I.D.: HD12G

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°F	66 to 78	70	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Peak Resultant Acceleration	G's	210.0 to 260.0	245.5	Pass
Peak Lateral Acceleration	G's	≤10.0	7.7	Pass
Time Above 100 G's	Msec.	0.9 to 1.5	1.1	Pass
Is Resultant Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician


December 12, 2000

Test Date

Approved By

Date

C-35




Curve Description: Head Resultant Acceleration
Maximum Value: 245.5 at 1.4 Milliseconds
Minimum Value: 1.3 at 0.0 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00

Test Program: Hybrid II Head Drop Calibration
Test Information: SID S/N: 274 Test I.D.: HD12G



KAR21003-04



Curve Description: Head Y Axis Acceleration
Maximum Value: 0.9 at 2.4 Milliseconds
Minimum Value: -7.7 at 1.4 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00

Test Program: Hybrid II Head Drop Calibration
Test Information: SID S/N: 274 Test I.D.: HD12G





Performance Verification Data Side Impact Dummy (SID) External Dimensions

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: N/A

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory temperature	°C	20.4 to 22.1	21.1	Pass
Laboratory relative humidity	%	10 to 70	30	Pass
SH- Seated Height	mm	889 to 909	905	Pass
HP- Hip Point Height	mm	99 (reference)	99	Pass
RH- Rib Height	mm	502 to 520	510	Pass
KH- Knee Pivot From Back Line	mm	511 to 526	520	Pass
KV- Knee Pivot From Floor	mm	490 to 505	495	Pass
HW- Hip Width	mm	356 to 391	360	Pass
Overall Test Results				Pass

Laboratory Technician

December 13, 2000

Test Date

Approved By

Date



Performance Verification Data Side Impact Dummy (SID) Thorax Lateral Impact

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: TI12B

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	4.21 to 4.33	4.27	Pass
Left Upper Rib Acceleration	G's	37.0 to 46.0	39.4	Pass
Left Lower Rib Acceleration	G's	37.0 to 46.0	39.1	Pass
Thoracic Spine Acceleration	G's	15.0 to 22.0	18.5	Pass
Overall Test Results				Pass


Laboratory Technician

December 13, 2000

Test Date

Approved By

Date




Curve Description: Left Upper Rib Y Acceleration
Maximum Value: 39.4 at 5.9 Milliseconds
Minimum Value: -15.0 at 21.0 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/13/00

Test Program: SID Thorax Lateral Impact Test
Test Information: SID S/N: 275 Test I.D.: TI12B



C-40



Curve Description: Left Lower Rib Y Acceleration

Maximum Value: 39.1 at 5.7 Milliseconds

Minimum Value: -12.2 at 13.3 Milliseconds

SAE Filter Class: FIR 100

Date of Test: 12/13/00


Test Program: SID Thorax Lateral Impact Test

Test Information: SID S/N: 275 Test I.D.: TI12B



KAR21003-04

C-41



Curve Description: Lower Spine Y Acceleration
Maximum Value: 18.5 at 12.4 Milliseconds
Minimum Value: -4.5 at 33.6 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/13/00

Test Program: SID Thorax Lateral Impact Test
Test Information: SID S/N: 275 Test I.D.: TI12B



KAR21003-04



Performance Verification Data

Side Impact Dummy (SID)

Left Side Pelvis Lateral Impact

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: PI12B

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	4.21 to 4.33	4.33	Pass
Pelvis Acceleration	G's	40.0 to 60.0	42.3	Pass
Acceleration Time Above 20 G's	Msec.	3.0 to 7.0 Msec.	6.8	Pass
Is Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician


December 13, 2000

Test Date

Approved By

Date

C-43



Curve Description: Pelvis Y Axis Acceleration
Maximum Value: 42.3 at 9.8 Milliseconds
Minimum Value: -8.9 at 23.7 Milliseconds
SAE Filter Class: FIR 100
Date of Test: 12/13/00

Test Program: Left Side Pelvis Lateral Impact
Test Information: SID S/N: 275 Test I.D.: PI12B



KAR21003-04



Performance Verification Data Side Impact Dummy (SID) Abdominal Compression Test

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: AB12H

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°F	66 to 78	70	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Force at 0.5 Inches of Displacement	Pounds	23.0 to 36.0	29.7	Pass
Force at 0.75 Inches of Displacement	Pounds	36.0 to 50.0	42.3	Pass
Force at 1.0 Inches of Displacement	Pounds	50.0 to 63.0	59.0	Pass
Force at 1.3 Inches of Displacement	Pounds	73.0 to 88.0	80.7	Pass
Overall Test Results				Pass

Laboratory Technician


December 12, 2000

Test Date

Approved By

Date

C-45



Curve Description: Abdomen Force vs. Displacement

Force at 0.5 In.: 29.7 Pounds

Force at 0.75 In.: 42.3 Pounds

Force at 1.0 In.: 59.0 Pounds

Force at 1.3 In.: 80.7 Pounds

Date of Test: 12/12/00

Test Program: Hybrid II Abdominal Compression

Test Information: SID S/N: 275 Test I.D.: AB12H



KAR21003-04



Performance Verification Data Side Impact Dummy (SID) Head Drop Calibration

ATD Serial No.: 275

Part Serial No.: N/A

Test I.D.: HD12H

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°F	66 to 78	70	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Peak Resultant Acceleration	G's	210.0 to 260.0	228.3	Pass
Peak Lateral Acceleration	G's	≤10.0	7.0	Pass
Time Above 100 G's	Msec.	0.9 to 1.5	1.0	Pass
Is Resultant Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician


December 12, 2000

Test Date

Approved By

Date

C-47




Curve Description: Head Resultant Acceleration
Maximum Value: 228.3 at 1.3 Milliseconds
Minimum Value: 1.4 at 0.0 Milliseconds
SAE Filter Class: 1000
Date of Test: 12/12/00

Test Program: Hybrid II Head Drop Calibration
Test Information: SID S/N: 275 Test I.D.: HD12H



KAR21003-04

C-48



Curve Description: Head Y Axis Acceleration

Maximum Value: 0.8 at 2.3 Milliseconds

Minimum Value: -7.0 at 1.3 Milliseconds

SAE Filter Class: 1000

Date of Test: 12/12/00

Test Program: Hybrid II Head Drop Calibration

Test Information: SID S/N: 275 Test I.D.: HD12H



KAR21003-04

APPENDIX D
TEST EQUIPMENT LIST AND CALIBRATION INFORMATION

**55/28 km/h Side Impact NCAP
Instrumentation Data Channel Assignments
Driver S.I.D. Serial Number 274
12/12/00
2001 Pontiac Gand Prix 4 Door Sedan**

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
1	Head CG	X	KEAC086	Accel.,1/2 bridge	Endevco	7264-2000X	G
2	Head CG	Y	KEAC087	Accel.,1/2 bridge	Endevco	7264-2000Y	G
3	Head CG	Z	KEAC088	Accel.,1/2 bridge	Endevco	7264-2000Z	G
4	Upper Rib Primary	Y	KEAC070	Accel.,1/2 bridge	Endevco	7264-2000X	G
5	Lower Rib, Primary	Y	KEAC071	Accel.,1/2 bridge	Endevco	7264-2000Y	G
6	Lower Spine, Primary	Y	KEAC072	Accel.,1/2 bridge	Endevco	7264-2000Z	G
7	Pelvis, Primary	Y	KEAC090	Accel.,Full bridge	Endevco	7264-2000X	G
8	Upper Rib Redundant	Y	KEAC076	Accel.,1/2 bridge	Endevco	7264-2000X	G
9	Lower Rib, Redundant	Y	KEAC077	Accel.,1/2 bridge	Endevco	7264-2000Y	G
10	Lower Spine, Redundant	Y	KEAC078	Accel.,1/2 bridge	Endevco	7264-2000Z	G
11	Pelvis, Redundant	Y	KEAC089	Accel.,1/2 bridge	Endevco	7264-2000X	G
12	Thorax Contact	N/A	T0	Contact Switch	Tapeswitch	8 oz. Yellow	%
13	Pelvis Contact	N/A	T0	Contact Switch	Tapeswitch	8 oz. Yellow	%

55/28 km/h Side Impact NCAP
Instrumentation Data Channel Assignments
Passenger S.I.D. Serial Number 275
12/12/00
2001 Pontiac Gand Prix 4 Door Sedan

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
14	Head CG	X	KEAC069	Accel.,1/2 bridge	Endevco	7264-2000X	G
15	Head CG	Y	KEAC080	Accel.,1/2 bridge	Endevco	7264-2000Y	G
16	Head CG	Z	KEAC082	Accel.,1/2 bridge	Endevco	7264-2000Z	G
17	Upper Rib Primary	Y	KEAC066	Accel.,1/2 bridge	Endevco	7264-2000X	G
18	Lower Rib, Primary	Y	KEAC067	Accel.,1/2 bridge	Endevco	7264-2000Y	G
19	Lower Spine, Primary	Y	KEAC068	Accel.,1/2 bridge	Endevco	7264-2000Z	G
20	Pelvis, Primary	Y	KEAC079	Accel.,1/2 bridge	Endevco	7264-2000X	G
21	Upper Rib Redundant	Y	KEAC073	Accel.,1/2 bridge	Endevco	7264-2000X	G
22	Lower Rib, Redundant	Y	KEAC074	Accel.,1/2 bridge	Endevco	7264-2000Y	G
23	Lower Spine, Redundant	Y	KEAC075	Accel.,1/2 bridge	Endevco	7264-2000Z	G
24	Pelvis, Redundant	Y	KEAC081	Accel.,1/2 bridge	Endevco	7264-2000X	G
25	Thorax Contact	Y	T0	Contact Switch	Tapeswitch	8 oz. Yellow	%
26	Pelvis Contact	Y	T0	Contact Switch	Tapeswitch	8 oz. Yellow	%

55/28 km/h Side Impact NCAP
Instrumentation Data Channel Assignments
Vehicle Accelerometers
12/12/00

2001 Pontiac Gand Prix 4 Door Sedan

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
27	Right at Sill Front Seat	X	KETX2A	Accel., Triax	I.C. Sensor	3031-200	G
28	Right at Sill Front Seat	Y	KETX2B	Accel., Triax	I.C. Sensor	3031-200	G
29	Right at Sill Front Seat	Z	KETX2C	Accel., Triax	I.C. Sensor	3031-200	G
30	Right at Sill Rear Seat	X	KETX3A	Accel., Triax	I.C. Sensor	3031-500	G
31	Right at Sill Rear Seat	Y	KETX3B	Accel., Triax	I.C. Sensor	3031-500	G
32	Right at Sill Rear Seat	Z	KETX3C	Accel., Triax	I.C. Sensor	3031-500	G
33	Rear Floorpan Above Axle	X	KETX4A	Accel., Triax	I.C. Sensor	3031-500	G
34	Rear Floorpan Above Axle	Y	KETX4B	Accel., Triax	I.C. Sensor	3031-500	G
35	Rear Floorpan Above Axle	Z	KETX4C	Accel., Triax	I.C. Sensor	3031-500	G
36	Left Sill at Rear Door	Y	KEVA012	Accel., Vehicle block	I.C. Sensor	3031-500	G
37	Left Sill at Front Door	Y	KEVA001	Accel., Vehicle block	I.C. Sensor	3031-500	G
38	Left Front Door Centerline	Y	ICST004X	Accel., Triax	I.C. Sensor	3031-500	G
39	Rear Occupant Compartment	Y	KEVA006	Accel., Vehicle block	I.C. Sensor	3031-200	G
40	Left Front Door Mid-Rear	Y	ICST004Y	Accel., Triax	I.C. Sensor	3031-500	G
41	Left Front Door Upper Centerline	Y	ICST004Z	Accel., Triax	I.C. Sensor	3031-500	G
42	Rear Door Mid-Rear	Y	ICST005X	Accel., Triax	I.C. Sensor	3031-500	G
43	Rear Door Upper Centerline	Y	ICST005Y	Accel., Triax	I.C. Sensor	3031-500	G
44	B-Post Lower	Y	KEBX2A	Accel., Biax	I.C. Sensor	3031-500	G
45	B-Post Middle	Y	KEBX2B	Accel., Biax	I.C. Sensor	3031-500	G
46	A-Post Lower	Y	KEBX1A	Accel., Biax	I.C. Sensor	3031-200	G
47	A-Post Middle	Y	KEBX1B	Accel., Biax	I.C. Sensor	3031-500	G
48	Front Seat Track	Y	KEIC008Y	Single	I.C. Sensor	3031-500	G
49	Rear Seat Structure	Y	N/A	N/A	N/A	N/A	N/A
50	Vehicle CG	X	KETX2A	Accel., Triax	I.C. Sensor	3031-200	G
51	Vehicle CG	Y	KETX2B	Accel., Triax	I.C. Sensor	3031-200	G
52	Vehicle CG	Z	KETX2C	Accel., Triax	I.C. Sensor	3031-200	G

**55/28 km/h Side Impact NCAP
Instrumentation Data Channel Assignments
Moving Deformable Barrier
12/12/00
2001 Pontiac Gand Prix 4 Door Sedan**

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
53	MDB CG	X	ICST001X	Accel., Triax	I.C. Sensor	3031-100	G
54	MDB CG	Y	ICST001Y	Accel., Triax	I.C. Sensor	3031-100	G
55	MDB CG	Z	ICST001Z	Accel., Triax	I.C. Sensor	3031-100	G
56	MDB Rear Centerline	X	ICST002X	Accel., Biax	I.C. Sensor	3031-100	G
57	MDB Rear Centerline	Y	ICST002Y	Accel., Biax	I.C. Sensor	3031-100	G
58	Right Bumper Contact	N/A	T0	Contact Switch	Tapeswitch	40 oz. Grey	%