

REPORT NUMBER KAR22001-05

**NEW CAR ASSESSMENT PROGRAM
FRONTAL BARRIER IMPACT TEST**

**DAEWOO MOTOR COMPANY
2002 DAEWOO NUBIRA SE
4-DOOR SEDAN**

NHTSA NUMBER: M20502

**PREPARED BY:
KARCO ENGINEERING, LLC
9270 HOLLY ROAD
ADELANTO, CALIFORNIA 92301**



MAY 6, 2002

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
SAFETY PERFORMANCE STANDARDS
OFFICE OF CRASHWORTHINESS STANDARDS
MAIL CODE: NPS-10
400 SEVENTH STREET, SW, ROOM 5313
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, in response to Contract Number DTNH22-01-D-02005.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned, it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: _____
Mr. James E. Gorth, Project Engineer
KARCO Engineering, LLC

Date: May 6, 2002

Reviewed by: _____
Mr. Jerry L. Kratzke, Director of Operations
KARCO Engineering, LLC

Date: May 6, 2002

Approved by: _____
Mr. Frank D. Richardson, Program Manager
KARCO Engineering, LLC

Date: May 6, 2002

FINAL REPORT ACCEPTED BY:

Manager, New Car Assessment Program

Date of Acceptance

COTR, NCAP Frontal Impact Program

Date of Acceptance

Technical Report Documentation Page

1. Report No. KAR21001-05		2. Government Accession No.		3. Recipients Catalog No.	
4. Title and Subtitle Final Report of New Car Assessment Program Testing of a 2002 Daewoo Nubira SE 4-Door Sedan NHTSA No. M20502				5. Report Date May 6, 2002	
				6. Performing Organization Code KAR	
7. Author(s) Mr. James E Gorth, Project Engineer, Karco Mr. Frank Richardson, Project Manager, Karco				8. Performing Organization Report No. KAR21001-05	
9. Performing Organization Name and Address KARCO Engineering, LLC 9270 Holly Road Adelanto, CA 92301				10. Work Unit No.	
				11. Contract or Grant No. DTNH22-01-D-02005	
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Safety Performance Standards Office of Crashworthiness Standards Mail Code: NPS-10 400 Seventh Street, SW, Room 5313 Washington, D.C. 20590				13. Type of Report and Period Covered Final Test Report Option Year 1	
				14. Sponsoring Agency Code DOT/NHTSA/NRM/OCS	
15. Supplementary Notes					
16. Abstract A 35 mph (56.3 km/h) frontal barrier impact was conducted on a 2002 Daewoo Nubira SE 4-Door Sedan at KARCO Engineering, LLC on 4/23/02. This test was conducted to obtain data indicant of FMVSS 208, 212, 219 (partial), 301, and footwell intrusion performance. The impact velocity is 55.9 km/h. The ambient temperature at the barrier face at the time of impact is 25.0 degrees Celcius. The vehicle's maximum post test static crush is 568 mm at the vehicle centerline. The test vehicle is equipped with a 3-point continuous belt system and second generation supplemental airbags in both front outboard seating positions. With respect to FMVSS 208 "Occupant Crash Protection", the occupant injury criteria summary is as follows:					
Measurement Description		Units	Threshold	Driver ATD	Passenger ATD
Head Injury Criteria (HIC)		N/A	1000	723.8	499.2
Max. Thorax Accel. (3 msec Clip)		G's	60	50.9	47.7
Left Femur force		Newtons	10000	-3987.5	-6227.2
Right Femur Force		Newtons	10000	-2714.7	-4568.4
17. Key Words 56.3 km/h NCAP Frontal Barrier Impact Test New Car Assessment Program (NCAP) 2002 Daewoo Nubira SE 4-Door Sedan NHTSA No. M20502				18. Distribution Statement Copies of this report available from: NHTSA Technical Reference Division National Highway Traffic Safety Admin. 400 Seventh St., SW, Room 5108 Washington, DC 20590	
19. Security Classification(this report) Unclassified		20. Security Classification(this page) Unclassified		21. No. of Pages 349	22. Price

TABLE OF CONTENTS

<u>Section</u>	<u>Description</u>	<u>Page</u>
1	Purpose and Summary of Test M20502	1
2	Occupant and Vehicle Information Data Sheets	3

<u>Data Sheet</u>	<u>Description</u>	<u>Page</u>
1	Crash Test Summary	4
2	General Test and Vehicle Parameter Data	5
3	Post Impact Data	7
4	Test Vehicle Information	8
5	Dummy Positioning in Vehicle	10
6	Seatbelt Positioning Data	12
7	Vehicle Accelerometer Location and Data Summary	13
8	Hybrid III ATD Injury Criteria and Sensor Data	14
9	Seatbelt Assessment Test Data	17
10	Summary of FMVSS 212 Data	18
11	Windshield Zone Intrusion FMVSS 219 Data (Partial)	19
12	FMVSS 301 Fuel System Integrity Post Impact Data	20
13	FMVSS 301 Static Rollover Data	21
14	Vehicle Measurements	22
15	Camera Locations	24
16	Photographic Reference Target Locations	25
17	Vehicle Intrusion Measurements	26
18	Fixed Barrier Load Cell Locations	30
19	Accident Investigation Division Data	31
20	Dummy/Vehicle Temperature Stabilization	32

<u>Appendix</u>	<u>Description</u>	<u>Appendix</u>
A	Photographs	A
B	Dummy and Vehicle Response Data Traces	B
C	Load Cell Barrier Data Traces	C
D	Instrumentation and Data Channel Assignments	D
E	Dummy Calibration Data Traces and Tables	E
F	Owners Manual	F
G	Nine Accelerometer Head Array Data	G

SECTION 1

PURPOSE AND SUMMARY OF TEST M20502

1.1 PURPOSE

This 35 mph (56.3 km/h) frontal barrier impact test is part of the Vehicle Barrier Impact Testing Program sponsored by the National Highway Traffic Safety Administration (NHTSA) under Contract No. DTNH22-01-D-02005. The purpose of this test was to obtain vehicle crashworthiness and occupant restraint system performance data for an impact speed in excess of the current 30 mph (48.3 km/h) requirements.

The 35 mph (56.3 km/h) frontal barrier impact test was conducted in accordance with the Office of Crashworthiness Standards Laboratory Test procedure.

1.2 SUMMARY

A load cell barrier consisting of 24 load cells was impacted by a 2002 Daewoo Nubira SE 4 Door Sedan at a velocity of 55.93 km/h. The test was performed at Karco Engineering, LLC on April 23, 2002. Pre- and post-test photographs of the vehicle and dummies can be found in Appendix A.

One real-time and 16 high-speed cameras were used to document the frontal barrier impact event. Camera locations and other pertinent camera information can be found in this report.

Two Part 572E, 50th percentile male anthropomorphic test devices (ATDs), were placed in the driver and right-front passenger seating positions according to dummy placement instructions specified in the Laboratory Indicant Test Procedure.

Both ATDs were fully instrumented with nine accelerometer array head, chest and pelvis triaxial accelerometers, chest displacement potentiometers, six-axis upper neck transducers, right/left femur load cells, and lower leg instrumentation. Seat belt load cells were also placed on the driver's and passenger's lap and shoulder belts to measure dummy torso and pelvic section loading. The driver (position 1) ATD (Serial No. 35) and the right-front passenger (position 2) ATD (Serial No. 34) were calibrated two tests prior to this test.

One Hundred and Nine (109) channels of data were recorded using an on-board data acquisition system. Appendix B contains the vehicle and dummy response data traces. Appendix C contains Load Cell Barrier information. Appendix D contains the Instrumentation Data Channel assignments. Appendix E contains the Dummy Calibration data and Appendix F contains the owner's manual instructions for the occupant and restraint systems. Appendix G contains Nine Accelerometer Head Array Data.

There was 100 percent windshield retention and no intrusion into the protected zone of the windshield during the impact event. There was no Stoddard solvent leakage after the event or during any phase of the static rollover.

The maximum static crush of the vehicle was 568 mm and both the driver and the passenger side doors remained closed and latched during the impact event and were operable without the aid of tools after the impact.

The driver's visible contact points were as follows: The driver ATD head and chest contacted the airbag, its abdomen had no contact and both knees contacted the steering column/dash.

The passenger's visible contact points were as follows: The passenger ATD head and chest contacted the airbag, its abdomen had no contact and both knees contacted the glove box.

Occupant injury data is contained in table below.

OCCUPANT DATA SUMMARY						
ATD Position	HIC	Clip (g)	Chest Disp (mm)	Left Femur (N)	Right Femur (N)	Belt Spool (mm)
Driver	723.8	50.9	-42.7	-3987.5	-2714.7	92.6
Passenger	499.2	47.7	-45.0	-6227.2	-4568.4	41.3

SECTION 2
OCCUPANT AND VEHICLE INFORMATION/DATA SHEETS

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

NHTSA No.: M20502

Test Program: 2002 NHTSA 35mph NCAP

Test Date: 4/23/02

CONVERSION FACTORS USED IN THIS REPORT*

Quantity	Typical Application	Std Units	Metric Unit	Multiply By
Mass	Vehicle Weight	lb	kg	0.4536
Linear Velocity	Impact Velocity	mile/h	km/h	1.609
Length or Distance	Measurements	in	mm	25.4
Volume	Fuel Systems	gal	liter	3.785
Volume	Small Fluids	oz	mL	29.573
Pressure	Tire Pressures	lbf/in ²	kPa	7.0
Volume	Liquid	gal	liter	3.785
Temperature	General Use	°F	°C	$= (tf - 32) / 1.8$
Force	Dynamic Forces	lbf	N	4.448
Moment	Torque	lbf/ft	Nm	1.355

* Based on the Recommended Practice in SAE J916, May 85

DATA SHEET NO. 1
CRASH TEST SUMMARY

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
Test Date: 4/23/02

PRIMARY IMPACT DATA

Measured Parameter	Units	Value
Velocity at Impact	km/h	55.93
Test Weight	kg	1485
Impact Angle	degrees	0
Average Rebound	mm	706
Maximum Static Crush	mm	568

DOOR OPENING AND SEAT TRACK INFORMATION

Description	Driver	Passenger
Front Door Opening	Remained closed & latched, opened w/o the aid of tools	Remained closed & latched, opened w/o the aid of tools
Rear Door Opening	Remained closed & latched, opened w/o the aid of tools	Remained closed & latched, opened w/o the aid of tools
Seat Track Shift (mm)	None	None
Seat Back Failure	None	None

TEST DUMMY INFORMATION

Description	Driver	Passenger
Dummy Type / Serial No.	50% Male Hybrid III / No. 35	50% Male Hybrid III / No. 34
Head Contact	Airbag	Airbag
Chest Contact	Airbag	Airbag
Abdomen Contact	None	Airbag
Left Knee Contact	Steering Column/Dash	Glove Box
Right Knee Contact	Steering Column/Dash	Glove Box

16mm MOVIE COVERAGE

High Speed	16
Real Time	1
Total	17

DATA CHANNELS

Driver ATD Sensors	46
Passenger ATD Sensors	46
Belt Assessment Sensors	8
Vehicle Structure Accelerometers	9
Rigid Barrier Load Cells	24
Total	133

DATA SHEET NO. 2
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02

TEST VEHICLE INFORMATION

Make	Daewoo
Model	Nubira
Body Style	4-Door Sedan
NHTSA No.	M20502
VIN	KLAJC52Z32K729001
Color	Red
Delivery Date	4/12/02
Odometer Reading (mi.)	25
Dealer	Haddad Daewoo
Transmission	5-Speed Manual
Final Drive	Front
Type/No. Cylinders	In-Line 4
Engine Displacement (L)	2.0
Engine Placement	Transverse
Front Seat Side Airbag	No

TEST VEHICLE OPTIONS

Driver Front Airbag	Yes
Pass. Front Airbag	Yes
Power Windows	Yes
Pre-Tensioners	Yes
Power Door Locks	No
Tilt Wheel	No
Air Conditioning	Yes
Power Brakes	Yes
Disc Brakes, Front	Yes
Disc Brakes, Rear	Yes
Anti-lock Brakes	No
Head Airbag	No
Load Limiter	Yes
Cruise Control	No
Bucket Seats	Yes

DATA FROM CERTIFICATION LABEL

Manufactured By	Daewoo Motor Company	GVWR (kg)	1674
Date of Manufacture	July-01	GAWR Front (kg)	890
		GAWR Rear (kg)	950

DATA FROM TIRE PLACARD

Measured Parameter	Front	Rear
Max. Tire Pressure (kPa)	210	210
Cold Pressure (kPa)	210	210
Recommend Tire Size	P185/65R14	P185/65R14
Tire Size on Vehicle	P185/65R14	P185/65R14
Tire Manufacturer	Kumho	Kumho

VEHICLE SEATING AND CAPACITY WEIGHT INFORMATION

Measured Parameter	Front	Rear	Third	Total
Type of Seats	Bucket	Bench	None	
Number of Occupants	2	3		5
Capacity Wt. (VCW) (kg)				400
Cargo Weight (RCLW) (kg)				59

DATA SHEET NO. 2...(CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02

TEST VEHICLE WEIGHTS

	Units	As Delivered (UVW)			As Tested (ATW)		
		Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total
Left	kg	388	252		429	326	
Right	kg	397	248		426	304	
Ratio	%	61.1	38.9		57.6	42.4	
Totals	kg	785	500	1285	855	630	1485

TARGET TEST WEIGHT CALCULATION

Measured Parameter	Units	Value
Total Delivered Weight (UVW)	kg	1285
Weight of 2 P572 ATD's	kg	152
Rated Cargo/Luggage Weight (RCLW)	kg	59
Calculated Vehicle Target Weight (TVTW)	kg	1496

TEST VEHICLE ATTITUDE AND CG

	Units	LF	RF	LR	RR	CG (aft of front axle)
As Delivered	mm	651	659	635	638	1001
As Tested	mm	630	634	592	601	1091

Vehicle Wheel base (mm): 2574

Weight of Ballast secured in cargo area (kg): 0

Vehicle Components Removed: _____

* Ballast weight does not include cameras, instrumentation, and brake abort system.

FUEL SYSTEM DATA

Fuel System Capacity From Owner's Manual (L): 51.9

Usable Capacity Figure Furnished by COTR (L): 51.1

Actual Test Volume with entire fuel System Filled (L): 47.3

Test Fluid Type: Stoddard Solvent ; Specific Gravity: 0.764

Kinematic Viscosity: as per ASTM Standard D484-71 ; Color: Red

Is Vehicle Fuel Pump Electric or Mechanical?: Electric

If electric, does pump operate with ignition switch "ON" & engine "OFF"? Yes

Fuel System Particulars: Driver side filler door, tank mounted at rear.

**DATA SHEET NO. 3
POST IMPACT DATA**

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

NHTSA No.: M20502

Test Program: 2002 NHTSA 35mph NCAP

Test Date: 4/23/02

Measured Parameter	Units	Requirement	Value
Trap No. 1 Velocity (Primary)	km/h	55.51 to 57.12	55.93
Trap No. 1 Entry Distance	mm	< 1524	1524
Trap No. 1 Exit Distance	mm	< 1524	305
Trap No. 2 Velocity (Redundant)	km/h	55.51 to 57.12	55.97
Trap No. 2 Entry Distance	mm	< 1524	1524
Trap No. 2 Exit Distance	mm	< 1524	305

VEHICLE STATIC CRUSH

Measured Parameter	Units	Pre-Test	Post-Test	Difference
Left Side	mm	4366	3877	-489
Center	mm	4487	3919	-568
Right Side	mm	4366	3823	-543

VEHICLE REBOUND FROM BARRIER

Measured Parameter	Units	Value
Left Side	mm	709
Center	mm	663
Right Side	mm	746
Average	mm	706

DATA SHEET NO. 4
TEST VEHICLE INFORMATION


Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
Test Date: 4/23/02

NOMINAL DESIGN RIDING POSITION

The driver and passenger seat backs are positioned to the manufacturers designated angle. The procedure is as follows: A special application tool with pointed probes is inserted through the fabric to make contact with the rigid portion of the lower seat frame assembly, approximately 13 inches above the pivot point of the seat back. An inclinometer is placed against the flat surface of the tool and the seat back angle is measured directly from the dial face.

Driver seat back angle: 14.5° with a seated dummy
Passenger seat back angle: 14.5° with a seated dummy



SEAT FORE/AFT POSITIONS

Both driver and passenger seats have 20 positions or detents. The first or forward most position is counted as number one (1). The fore/aft position is set aft of the middle position for both driver and passenger.

Driver seat fore/aft total travel: 20 seating positions or detents
Driver seat fore/aft position: 11th detent from forward most
Passenger seat fore/aft total travel: 20 seating positions or detents
Passenger seat fore/aft position: 11th detent from forward most

SEAT BELT UPPER ANCHORAGE

The test vehicle is equipped with adjustable anchorages for both driver and passenger seat positions. There are 5 positions or detents for the driver and 6 positions for the passenger. Both the driver and the passenger anchorages are placed in the 3rd position from the bottom.

DATA SHEET NO. 4...(CONTINUED)
TEST VEHICLE INFORMATION


Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02

FUEL TANK CAPACITY DATA

The "Usable Capacity" of the standard equipment fuel tank is:	<u>51.1</u>	liters
The "Usable Capacity" of any optional equipment fuel tank is:	<u>N/A</u>	liters
"Usable Capacity" used for certification tests FMVSS 301 requirements:	<u>47.0 to 48.0</u>	liters
Actual amount of Stoddard solvent added to vehicle for certification test:	<u>47.3</u>	liters

The test vehicle is equipped with an electric fuel pump. The fuel pump operates for approximately two seconds after the ignition is placed in the "ON" position, after which the fuel pump automatically shuts off. The fuel filler door is located on the right rear fender. The standard fuel tank occupies the area under the rear seat. Fuel lines run inside the right frame rail to the engine compartment.




VEHICLE FUEL TANK ASSEMBLY

STEERING COLUMN ADJUSTMENT

Steering wheel and column adjustments are made so that the steering wheel hub is at the geometric center of the locus it describes when moved through its full range of motion. An aluminum plate is placed across the rim of the steering wheel, an inclinometer is placed on the plate and the angle is measured.

NOTE: STEERING COLUMN IS FIXED ON THIS VEHICLE



STEERING COLUMN ASSEMBLY

Lowermost; position 1:	<u>N/A</u>
Geometric center; position 2:	<u>69°</u>
Uppermost position 3:	<u>N/A°</u>

DATA SHEET NO. 5
DUMMY POSITIONING IN VEHICLE

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
Test Date: 4/23/02


TEST DUMMY POSITION MEASUREMENTS

Code	Measurement Description	Driver		Passenger	
		Length (mm)	Angle (°)	Length (mm)	Angle (°)
WA	Windshield Angle		64		
SWA	Steering Wheel Angle		21		
SCA	Steering Column Angle		69		
SA	Seat Back Angle		15		15
HZ	Head to Roof (Z)	168	90	162	90
HH	Head to Header	283		283	
HW	Head to Windshield	608		598	
HR	Head to Side Header (Y)	241		238	
NR	Nose to Rim	446	11		
CD	Chest to Dash	568		548	
CS	Chest to Steering Hub	368			
RA	Rim to Abdomen	225			
KDL	Left Knee to Dash	145	34	140	
KDR	Right Knee to Dash	163		190	18
PA	Pelvic Angle		24		24
TA	Tibia Angle		38		41
KK	Knee to Knee (Y)	334		285	
ST	Striker to Head	595	4	590	1
SK	Striker to Knee	536	84	537	84
SH	Striker to H-Point	206		202	
SHY	Striker to H-Point (Y)	222		240	
HS	Head to Side Window	297		298	
HD	H-Point to Door (Y)	173		190	
AD	Arm to Door (Y)	118		57	

DATA SHEET NO. 5...(CONTINUED) **DUMMY POSITIONING IN VEHICLE**

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02




DUMMY MEASUREMENTS FOR FRONT SEAT OCCUPANTS

DATA SHEET NO. 6 **SEATBELT POSITIONING DATA**

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02



SEAT BELT POSITIONING MEASUREMENTS

Measurement Description	Units	Driver	Passenger
TBI - Dummy C/L to Lap/Shoulder Belt Intersect	mm	210	220
PBU - Top surface of reference to belt upper edge	mm	375	310
PBL - Top surface of reference to belt lower edge	mm	295	245
Lap Belt tension	Newton's	10	10
Shoulder Belt tension	N/A	Retractor	Retractor

DATA SHEET NO. 7 - VEHICLE ACCELEROMETER LOCATION AND DATA SUMMARY

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

NHTSA No.: M20502



Test Program: 2002 NHTSA 35mph NCAP

Test Date: 4/23/02

VEHICLE ACCELEROMETER PEAK DATA AND PRE-TEST LOCATIONS

No.	Accelerometer Location	Measurements (mm)			Peak Values				
		X	Y	Z	Units	Max	Time	Min	Time
1	Left Rear X-Member	1730	-640	340	G's	2.5	158.3	-54.6	41.0
2	Right Rear X-Member	1730	640	340	G's	1.4	139.0	-40.1	40.9
3	Engine Top	3790	0	785	G's	54.7	40.4	-176.6	30.5
4	Engine Bottom	3770	0	210	G's	34.3	41.0	-141.4	25.2
5	Left Brake Caliper	3700	-695	200	G's	5.0	60.6	-83.0	41.1
6	Right Brake Caliper	3700	695	200	G's	19.8	67.6	-71.8	45.0
7	Instrument Panel	2900	-105	1010	G's	29.8	94.5	-53.6	58.3
8	Left Rear X-Member (Z-Axis)	1730	-610	340	G's	12.0	38.4	-8.4	42.1
9	Right Rear X-Member (Z-Axis)	1730	610	340	G's	8.9	90.4	-5.2	50.7

Reference Planes: X=From Rear Surface of Vehicle, Y=Vehicle Centerline, Z=Ground Plane



DATA SHEET NO. 8 - HYBRID III ATD INJURY CRITERIA AND SENSOR DATA

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

NHTSA No.: M20502

Test Program: 2002 NHTSA 35mph NCAP

Test Date: 4/23/02

HEAD PRIMARY PEAK ACCELERATIONS

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Head CG	X	G's	31.6	176.0	-62.5	82.0	21.7	204.4	-48.3	79.6
Head CG	Y	G's	3.9	156.4	-13.3	95.8	11.1	206.2	-21.3	32.8
Head CG	Z	G's	26.5	49.2	-7.3	110.6	30.6	75.5	-3.3	133.6
Head CG Resultant	N/A	G's	63.8	82.0			57.1	79.1		

CHEST PRIMARY PEAK ACCELERATIONS

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Chest CG	X	G's	5.4	149.2	-51.3	60.9	3.1	146.2	-48.3	73.0
Chest CG	Y	G's	5.9	104.4	-9.7	54.7	7.0	54.2	-2.0	122.1
Chest CG	Z	G's	16.5	48.2	-12.8	107.2	10.6	49.2	-13.6	101.7
Chest CG Resultant	N/A	G's	51.8	60.9			48.4	73.0		

FEMUR PEAK FORCES

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Left Femur	Z	Newtons	983.2	45.3	-3987.5	58.4	824.7	48.5	-6227.2	57.3
Right Femur	Z	Newtons	1580.4	48.0	-2714.7	64.2	441.7	45.5	-4568.4	54.1

SEAT BELT SENSOR PEAK VALUES

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Shoulder Belt Pullout	N/A	MM	92.6	82.3	-14.8	37.5	41.3	94.1	-12.6	299.6
Shoulder Belt Stretch	N/A	MM/CM	0.00	0.0	0.00	0.0	0.00	0.0	0.00	0.0 *
Lap Belt Force	N/A	Newtons	8535.6	53.8	9.7	0.0	6903.9	55.2	-1.7	0.0
Shoulder Belt Force	N/A	Newtons	6185.3	70.0	-22.6	208.5	5865.7	73.4	10.0	0.0

* Not used with pre-tensioner

PRIMARY HEAD INJURY CRITERIA (HIC)

Location	Driver				Passenger			
	HIC	T ¹	T ²	Avg G	HIC	T ¹	T ²	Avg G
Head CG Primary	723.8	59.7	95.6	52.7	499.2	59.8	95.7	45.4

PRIMARY CHEST CLIP (3MSEC)

Location	Driver			Passenger		
	CLIP	T ¹	T ²	CLIP	T ¹	T ²
Chest CG Primary	50.9	58.8	61.8	47.7	71.7	74.7

DATA SHEET NO. 8...(continued)

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

NHTSA No.: M20502

Test Program: 2002 NHTSA 35mph NCAP

Test Date: 4/23/02

PELVIC PEAK ACCELERATIONS

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Pelvis	X	G's	11.2	97.0	-65.1	53.1	7.5	105.8	-85.4	52.8
Pelvis	Y	G's	13.4	90.6	-15.3	63.7	6.1	146.1	-8.0	79.1
Pelvis	Z	G's	8.7	45.1	-25.0	62.5	3.7	218.2	-23.0	70.2
Pelvis Resultant	N/A	G's	69.0	60.2			85.9	52.8		

UPPER NECK PEAK FORCES AND MOMENTS

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Neck Force	X	Newtons	279.5	92.2	-393.3	52.6	236.9	215.6	-669.6	117.4
Neck Force	Y	Newtons	325.5	189.6	-272.1	109.1	338.5	62.5	-264.5	101.4
Neck Force	Z	Newtons	2205.6	75.7	-522.4	192.9	1965.9	75.5	-349.5	241.9
Neck Force Resultant	N/A	Newtons	2205.7	75.7			1975.1	75.6		
Neck Moment	X	N•m	15.2	60.8	-20.5	70.9	5.9	48.6	-34.6	63.3
Neck Moment	Y	N•m	28.6	94.6	-35.7	201.2	55.4	132.0	-32.4	247.7
Neck Moment	Z	N•m	14.5	88.9	-10.9	141.7	28.8	81.1	-9.6	134.6
Neck Moment Resultant	N/A	N•m	36.6	201.2			56.5	132.0		

FOOT PEAK ACCELERATIONS

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Left Foot Aft	X	G's	11.0	75.7	-31.2	42.6	9.2	97.0	-87.9	44.7
Left Foot Aft	Z	G's	5.5	152.7	-46.0	43.4	12.4	50.2	-76.4	47.0
Left Foot Fore	Z	G's	8.8	152.9	-56.7	31.1	22.4	69.2	-96.4	47.5
Right Foot Aft	X	G's	31.3	101.1	-167.2	44.0	24.9	76.5	-80.3	44.8
Right Foot Aft	Z	G's	7.8	66.6	-110.3	41.5	4.2	152.2	-38.0	78.7
Right Foot Fore	Z	G's	37.8	57.6	-208.9	37.0	13.5	23.8	-93.5	37.6

UPPER AND LOWER TIBIA PEAK FORCES AND MOMENTS

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Left Upper Moment	X	N•m	34.1	62.8	-14.1	78.3	38.1	82.0	-85.4	50.5
Left Upper Moment	Y	N•m	53.5	58.0	-72.5	50.1	90.2	50.4	-135.1	47.2
Right Upper Moment	X	N•m	89.3	43.4	-85.7	44.6	48.7	48.9	-33.2	40.0
Right Upper Moment	Y	N•m	36.1	104.6	-140.3	43.6	18.3	112.0	-82.9	43.4
Left Lower Moment	X	N•m	29.7	55.2	-6.3	79.3	56.3	51.2	-35.8	46.8
Left Lower Moment	Y	N•m	58.1	88.0	-31.4	44.8	73.4	54.7	-62.1	47.7
Left Lower Force	Z	Newtons	152.4	129.2	-2268.8	83.7	156.6	122.9	-3183.4	45.3
Right Lower Moment	X	N•m	48.2	42.4	-150.7	45.3	88.6	48.7	-8.9	38.5
Right Lower Moment	Y	N•m	76.6	88.1	-77.1	39.4	68.0	77.6	-33.7	41.2
Right Lower Force	Z	Newtons	186.1	133.7	-4802.0	44.0	123.5	137.1	-2688.1	78.8

DATA SHEET NO. 8...(continued)Test Vehicle: 2002 Daewoo Nubira SE 4 Door SedanNHTSA No.: M20502Test Program: 2002 NHTSA 35mph NCAPTest Date: 4/23/02**CHEST PEAK DISPLACEMENTS**

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Chest CG	X	MM	0.2	16.6	-42.7	77.9	0.2	6.0	-45.0	71.5

HEAD REDUNDANT PEAK ACCELERATIONS

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Head CG	X	G's	33.1	176.2	-63.3	82.2	21.7	204.5	-47.1	78.9
Head CG	Y	G's	3.5	156.5	-12.8	95.9	11.4	205.9	-18.5	33.9
Head CG	Z	G's	25.7	48.5	-7.4	105.5	31.2	75.5	-3.1	133.3
Head CG Resultant	N/A	G's	64.4	82.2			56.3	78.9		

CHEST REDUNDANT PEAK ACCELERATIONS

Location	Axis	Units	Driver				Passenger			
			Max	Time	Min	Time	Max	Time	Min	Time
Chest CG	X	G's	7.7	136.2	-52.4	60.9	3.3	143.6	-47.8	73.0
Chest CG	Y	G's	5.6	104.3	-9.2	54.5	8.1	54.3	-1.9	121.2
Chest CG	Z	G's	15.7	48.1	-12.8	104.6	10.8	49.2	-14.0	101.9
Chest CG Resultant	N/A	G's	52.8	60.9			47.9	73.0		

REDUNDANT HEAD INJURY CRITERIA (HIC)

Location	Driver				Passenger			
	HIC	T ¹	T ²	Avg G	HIC	T ¹	T ²	Avg G
Head CG Redundant	720.7	60.0	95.9	52.6	487.0	59.9	95.8	44.9

REDUNDANT CHEST CLIP (3MSEC)

Location	Driver			Passenger		
	CLIP	T ¹	T ²	CLIP	T ¹	T ²
Chest CG Redundant	51.7	58.9	61.9	47.3	71.9	74.9

DATA SHEET NO. 9
SEATBELT ASSESSMENT TEST DATA

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02

SEAT BELT PLACEMENT MEASUREMENTS

Measurement Description	Units	Driver	Passenger
TBI - Dummy C/L to Lap/Shoulder Belt Intersect	mm	210	220
PBU - Top surface of reference to belt upper edge	mm	375	310
PBL - Top surface of reference to belt lower edge	mm	295	245
Lap Belt tension	Newton's	10	10
Shoulder Belt tension	N/A	Retractor	Retractor

BELT LENGTH DATA

Measurement Description	Units	Driver	Passenger
Retractor reel to 'D' ring	mm	700	700
Shoulder belt length as measured on ATD	mm	835	865
Lap belt length as measured on ATD	mm	813	800
Remainder of belt on reel	mm	702	670
Total belt length for continuous webbing systems	mm	3050	3035

SHOULDER BELT SPOOL-OFF DATA

Measurement Description	Units	Driver	Passenger
As determined mechanically	mm	Broken	8.0
As determined electronically	mm	92.6	41.3
As determined by photography	mm		

BELT STRETCH DATA

Measurement Description	Units	Driver	Passenger
Electronically between shoulder belt load cell and "D" ring	mm/cm	*	*
Mechanically	mm/cm	None	None

*Not used with shoulder belt pre-tensioner systems.

DATA SHEET NO. 10
SUMMARY OF FMVSS 212 DATA

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02


Windshield Mounting Details: Windshield glass is secured to the vehicle frame with a rubber type adhesive. No molding covers the windshield periphery at any point.

The standard requires that the posttest retention measurement be a minimum of 75 percent of the pretest total periphery measurement for vehicles not equipped with occupant passive restraints and 50 percent for each side of the windshield for vehicles that are equipped with occupant passive restraints.

Temperature of windshield molding during test: 21.1 °C

WINDSHIELD PERIPHERY MEASUREMENTS

Measurement	Pre-Test(mm)	Post-Test (mm)	% of Retention
Left Side	2042	2042	100
Right Side	2042	2042	100
Total	4084	4084	100




WINDSHIELD DIMENSIONS

Item	Units	Segment Length	Molding Width
A	mm	1071	14
B	mm	1453	20
C	mm	780	14

DATA SHEET NO. 11
WINDSHIELD ZONE INTRUSION FMVSS 219 DATA (PARTIAL)

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02



**WINDSHIELD AND
PROTECTED ZONE**

Item	Units	Value
A	mm	1071
B	mm	410
C	mm	1453
D	mm	780
E	mm	481
F	mm	620

AREA OF PROTECTED ZONE FAILURES

- A. Provide coordinates of the area that the protected zone was penetrated more than 0.25 in. by a vehicle component other than one that is normally in contact with the windshield.

X	Y
N/A	N/A
N/A	N/A
N/A	N/A
N/A	N/A

- B. Provide coordinates of the area beneath the protected zone that the inner surface of the windshield was penetrated by a vehicle component.

X	Y
N/A	N/A
N/A	N/A
N/A	N/A
N/A	N/A

DATA SHEET NO. 12
FMVSS 301 FUEL SYSTEM INTEGRITY POST IMPACT DATA

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
Test Date: 4/23/02

Test Time: 11:53 A.M.

Temperature at Time of Impact 25.0 Deg. C


STODDARD SOLVENT SPILLAGE MEASUREMENTS

- A. From impact until vehicle motion ceases: 0.0 oz.
(Maximum Allowable = 1 ounce)
- B. For the 5 minute period after motion ceases: 0.0 oz.
(Maximum Allowable = 5 ounces)
- C. For the following 25 minutes: 0.0 oz.
(Maximum Allowable = 1 oz./minute)
- D. Spillage Location Details: No leakage occurred


DATA SHEET NO. 13
FMVSS 301 STATIC ROLLOVER DATA

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP



NHTSA No.: M20502
 Test Date: 4/23/02




0° to 90°




90° to 180°



180° to 270°



270° to 360°



1. The specified fixture rollover rate for each 90° of rotation is 60 to 120 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. No solvent leakage occurred during rollover.

Test Phase	Rotation Time (sec.)	Hold Time (sec.)	Spillage (oz.)
0° to 90°	83	300	0
90° to 180°	80	300	0
180° to 270°	77	300	0
270° to 360°	80	300	0

DATA SHEET NO. 14
VEHICLE MEASUREMENTS

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
Test Program: 2002 NHTSA 35mph NCAP


NHTSA No.: M20502
Test Date: 4/23/02

No.	Measurement Description	Units	Pre-Test	Post-Test	Difference
1	Total length of vehicle at centerline	mm	4487	3919	-568
2	RSOV to front of engine	mm	3903	3602	-301
3	RSOV to firewall centerline	mm	3372	3286	-86
4	RSOV to leading edge of right door	mm	3003	3002	-1
5	RSOV to leading edge of left door	mm	3006	2992	-14
6	RSOV to lower leading edge of right door	mm	3038	3029	-9
7	RSOV to lower leading edge of left door	mm	3028	3020	-8
8	RSOV to upper trailing edge of right door	mm	2017	2013	-4
9	RSOV to upper trailing edge of left door	mm	2016	2005	-11
10	RSOV to lower trailing edge of right door	mm	2051	2046	-5
11	RSOV to lower trailing edge of left door	mm	2052	2035	-17
12	RSOV to bottom of right 'A' pillar	mm	2988	2978	-10
13	RSOV to bottom of left 'A' pillar	mm	2992	2975	-17
14	RSOV to firewall on right side	mm	3318	3267	-51
15	RSOV to firewall of left side	mm	3327	3208	-119
16	RSOV to steering column	mm	2695	2664	-31
17	Center of steering column to left 'A' pillar	mm	380	397	17
18	Center of steering column to headlining	mm	455	530	75
19	RSOV to right side of front bumper	mm	4366	3823	-543
20	RSOV to left side of front bumper	mm	4366	3877	-489
21	Length of engine block	mm	485	485	0
RD	RSOV to right side of dash panel	mm	2825	2804	-21
CD	RSOV to center of dash panel	mm	2798	2735	-63
LD	RSOV to left side of dash panel	mm	2827	2798	-29

DATA SHEET NO. 14...(CONTINUED)
VEHICLE MEASUREMENTS

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02



DATA SHEET NO. 15
CAMERA LOCATIONS

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
Test Date: 4/23/02

No.	Camera View	Location (mm)			Angle (Deg.)	Film Plane to Head	Lens (mm)	Speed (fps)
		X	Y	Z				
1	Right Side, Real Time	3454	10973	1245	0	1651	Zoom	24
2	Left Side, No. 1	2000	-8250	1270	0	7897	13	1030
3	Left Side, No. 2	1060	-6370	1470	-2	6139	25	1020
4	Left Side, No. 3	6500	-10580	4640	-16	11511	65	900
5	Left Side, No. 4	1460	-8250	3340	-17	8169	19	900
6	Left Side, No. 5	1460	-8250	2970	-16	8089	19	980
7	Right Side, No. 1	2400	8150	1410	-3	7791	15	N/A
8	Right Side, No. 2	1000	7180	1410	-3	6945	35	1020
9	Right Side, No. 3	7860	8900	2800	-9	10281	80	980
10	Right Side, No. 4	2750	9600	1500	-2	9251	50	1010
11	Overhead Overall	250	0	4460	-86	N/A	13	1090
12	Front View, Driver	2970	-380	1330	-43	N/A	12	980
13	Front View, Passenger	2970	380	1330	-55	N/A	13	1170
14	Pit Camera, Engine	650	0	-1360	-90	N/A	10	N/A
15	Pit Camera, Fuel Tank	3760	0	-1680	-55	N/A	10	1090
16	Driver Belt	3120	-330	1450	-6	N/A	13	780
17	Passenger Belt	3120	330	1450	-6	N/A	13	740
18	Left Side Extra	N/A	N/A	N/A	N/A	N/A	N/A	N/A

X - Barrier Face Y - Monorail Centerline Z - Ground




DATA SHEET NO. 16 **PHOTOGRAPHIC REFERENCE TARGET LOCATIONS**

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02

All Dimensions
 in mm

Item	Value
A	368
B	879
C	2242
D	605
E	1646
F	155
G	1763
H	1097
I	1376
J	844
K	844
L	1416
M	1063
N	1422
O	843
P	843
Q	1386



DATA SHEET NO. 17
VEHICLE INTRUSION MEASUREMENTS

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP


NHTSA No.: M20502
 Test Date: 4/23/02

DOOR OPENING WIDTH

Item	Description	Units	Pre-Test	Post-Test	Difference
A	Left Side Upper	mm	901	877	-24
B	Left Side Lower	mm	862	851	-11
D	Right Side Upper	mm	902	872	-30
E	Right Side Lower	mm	844	830	-14

WHEELBASE MEASUREMENTS

Item	Description	Units	Pre-Test	Post-Test	Difference
C	Left Side Wheel base	mm	2574	2473	-101
F	Right Side Wheel base	mm	2574	2477	-97



DATA SHEET NO. 17...(CONTINUED)
VEHICLE INTRUSION MEASUREMENTS


Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02

DRIVER COMPARTMENT INTRUSION

Item	Description	Units	Pre-Test	Post-Test	Difference
AB	Door Opening (Inside window jam)	mm	901	877	-24
CX	Left Knee Bolster to X	mm	273	260	-13
DX	Right Knee Bolster to X	mm	266	259	-7
EX	Brake Pedal to X	mm	595	539	-56
FX	Foot Rest to X	mm	570	599	29
GX	Center of Steering Wheel Hub to X	mm	65	103	38


X = Left Front Seat Outboard Anchor Bolt Head



DATA SHEET NO. 17...(CONTINUED)
VEHICLE INTRUSION MEASUREMENTS

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02



1 Measurement reference point for X and Z-axis is the forward outboard seat mounting bolt.

2 Columns A through D are evenly spaced.

3 Rows 1 and 2 are on the toe kick portion of the floor pan. Rows 3,4 and 5 are located on the most level portion of the floor pan.

Row 3 will be at the intersection of the toe kick and the level sections of the floor pan.

DRIVER FLOOR PAN X-AXIS

	Pre-Test				Post-Test				Difference			
	A	B	C	D	A	B	C	D	A	B	C	D
1		623	619	622		568	563	571		-55	-56	-51
2		523	519	520		512	508	506		-11	-11	-14
3	424	421	419	418	411	409	406	405	-13	-12	-13	-13
4	325	321	320	319	316	309	307	305	-9	-12	-13	-14
5	225	221	220	219	217	210	207	205	-8	-11	-13	-14

DRIVER FLOOR PAN Z-AXIS

	Pre-Test				Post-Test				Difference			
	A	B	C	D	A	B	C	D	A	B	C	D
1		-46	-46	-66		-59	-81	-89		-13	-35	-23
2		-89	-85	-92		-132	-129	-142		-43	-44	-50
3	-85	-100	-92	-101	-124	-122	-131	-143	-39	-22	-39	-42
4	-86	-101	-92	-101	-121	-119	-122	-121	-35	-18	-30	-20
5	-102	-97	-101	-88	-110	-105	-115	-116	-8	-8	-14	-28

DATA SHEET NO. 17...(CONTINUED) **VEHICLE INTRUSION MEASUREMENTS**

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP


NHTSA No.: M20502
 Test Date: 4/23/02

Measurement reference point for X and Z axis is the forward outboard seat mounting bolt.

Columns A through D are evenly spaced.

Rows 1 and 2 are on the toe kick portion of the floor pan. Rows 3,4, and 5 are located on the most level portion of the floor pan.

Row 3 will be at the intersection of the toe kick and the level sections of the floor pan.



PASSENGER FLOOR PAN X-AXIS

	Pre-Test				Post-Test				Difference			
	A	B	C	D	A	B	C	D	A	B	C	D
1	628	630	631		594	599	597		-34	-31	-34	
2	545	546	547		552	550	560		7	4	13	
3	442	443	444	446	453	455	461	459	11	12	17	13
4	342	342	344	346	353	355	361	359	11	13	17	13
5	242	242	244	245	251	255	260	259	9	13	16	14

PASSENGER FLOOR PAN Z-AXIS


	Pre-Test				Post-Test				Difference			
	A	B	C	D	A	B	C	D	A	B	C	D
1	-45	-27	-13		-58	-36	-10		-13	-9	3	
2	-92	-83	-72		-145	-121	-120		-53	-38	-48	
3	-95	-88	-88	-88	-137	-123	-125	-127	-42	-35	-37	-39
4	-103	-92	-90	-88	-135	-115	-113	-108	-32	-23	-23	-20
5	-103	-93	-90	-90	-117	-101	-100	-100	-14	-8	-10	-10

DATA SHEET NO. 18
FIXED BARRIER LOAD CELL LOCATIONS

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02

36 Load Cell Rigid Barrier (NHTSA Standard)
Load Cell Locations on Fixed Barrier



6 Groups of 6 Load Cells Each

The Data is presented in Appendix C with the following requirements:

- 1.) Data from 36 individual load cells
- 2.) Sum data from 6 groupings shown above (6 cells/group)
- 3.) Total or sum of all 36 individual load cells
- 4.) Sum of all 36 individual load cells vs. vehicle dynamic crush

DATA SHEET NO. 19
ACCIDENT INVESTIGATION DIVISION DATA

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
 Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
 Test Date: 4/23/02

VEHICLE INFORMATION

VIN: KLAJC52Z32K729001
 Vehicle Size Category: 4-Door Sedan

Wheel base (mm): 2574
 Test Weight (kg): 1485

ACCELEROMETER DATA

Accelerometer Location: Left rear floor pan
 Cal. Procedure/Interval: 6 months / drop test
 Integration Algorithm: NHTSA Standard
 Impact Velocity (km/h): 55.93
 Velocity Change (km/h): 64.7


Linearity: Good

Time of Separation (msec): 71.5

CRUSH PROFILE

Collision Deformation Classification: 12FDEW6 Midpoint of Damage: Vehicle Centerline
 Damage Region Length (mm): 1231 Impact Mode: Full Frontal


No.	Measurement Description	Units	Pre-Test	Post-Test	Difference
C1	Crush zone 1 at left side	mm	121	610	-489
C2	Crush zone 2 on left side	mm	62	590	-528
C3	Crush zone 3 on left side	mm	43	595	-552
C4	Crush zone 4 on right side	mm	43	610	-567
C5	Crush zone 5 on right side	mm	66	634	-568
C6	Crush zone 6 at right side	mm	121	664	-543



DATA SHEET NO. 20
DUMMY/VEHICLE TEMPERATURE STABILIZATION

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan
Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502
Test Date: 4/23/02



APPENDIX A

PHOTOGRAPHS

LIST OF PHOTOGRAPHS

Figure		Page
A-1	Right Front, as Received	A-1
A-2	Left Rear, as Received	A-2
A-3	Vehicle Certification Label	A-3
A-4	Vehicle Tire Label	A-4
A-5	Front View, Pre-Test	A-5
A-6	Front View, Post-Test	A-6
A-7	Left Side View, Pre-Test	A-7
A-8	Left Side View, Post-Test	A-8
A-9	Right Side View, Pre-Test	A-9
A-10	Right Side View, Post-Test	A-10
A-11	Right Front View, Pre-Test	A-11
A-12	Right Front View, Post-Test	A-12
A-13	Left Rear View, Pre-Test	A-13
A-14	Left Rear View, Post-Test	A-14
A-15	Windshield, Pre-Test	A-15
A-16	Windshield, Post-Test	A-16
A-17	Engine Compartment, Pre-Test	A-17
A-18	Engine Compartment, Post-Test	A-18
A-19	Fuel Cap, Pre-Test	A-19
A-20	Fuel Cap, Post-Test	A-20
A-21	Front Underside, Pre-Test	A-21
A-22	Front Underside, Post-Test	A-22
A-23	Rear Underside, Pre-Test	A-23
A-24	Rear Underside, Post-Test	A-24
A-25	Driver Dummy Front View, Pre-Test	A-25
A-26	Driver Dummy Front View, Post-Test	A-26
A-27	Driver Dummy Through Window, Pre-Test	A-27
A-28	Driver Dummy Through Window, Post-Test	A-28
A-29	Driver Dummy Door Open, Pre-Test	A-29
A-30	Driver Dummy Door Open, Post-Test	A-30
A-31	Driver Dummy 90° To Vehicle, Pre-Test	A-31
A-32	Driver Dummy 90° to Vehicle, Post-Test	A-32

LIST OF PHOTOGRAPHS...(Continued)

Figure		Page
A-33	Driver Dummy Feet, Pre-Test	A-33
A-34	Driver Dummy Feet and Knee Contact, Post-Test	A-34
A-35	Driver Side Knee Bolster, Pre-Test	A-35
A-36	Driver Side Knee Bolster, Post-Test	A-36
A-37	Driver Side Floor Pan, Pre-Test	A-37
A-38	Driver Side Floor Pan, Post-Test	A-38
A-39	Driver Dummy Head, Post-Test	A-39
A-40	Driver Dummy Contact, Post-Test	A-40
A-41	Passenger Dummy Front View, Pre-Test	A-41
A-42	Passenger Dummy Front View, Post-Test	A-42
A-43	Passenger Dummy Through Window, Pre-Test	A-43
A-44	Passenger Dummy Through Window, Post-Test	A-44
A-45	Passenger Dummy Door Open, Pre-Test	A-45
A-46	Passenger Dummy Door Open, Post-Test	A-46
A-47	Passenger Dummy 90° to Vehicle, Pre-Test	A-47
A-48	Passenger Dummy 90° to Vehicle, Post-Test	A-48
A-49	Passenger Dummy Feet, Pre-Test	A-49
A-50	Passenger Dummy Feet and Knee Contact, Post-Test	A-50
A-51	Passenger Side Floor Pan, Pre-Test	A-51
A-52	Passenger Side Floor Pan, Post-Test	A-52
A-53	Passenger Side Knee Bolster, Pre-Test	A-53
A-54	Passenger Side Knee Bolster, Post-Test	A-54
A-55	Passenger Head, Post-Test	A-55
A-56	Passenger Dummy Contact, Post-Test	A-56
A-57	³ / ₄ Left Rear View of Doors After Impact	A-57
A-58	³ / ₄ Right Rear View of Doors After Impact	A-58
A-59	Vehicle on Rollover Device	A-59
A-60	Vehicle During Impact	A-60



Figure A-1: Right Front, as Received



Figure A-2: Left Rear, as Received

MFD. BY DAEWOO MOTOR CO., LTD., REPUBLIC OF KOREA
DATE GVWR GAWR FRT GAWR RR

7/01 3690LB 1962LB 2094LB

THIS VEHICLE CONFORMS TO ALL APPLICABLE
FEDERAL MOTOR VEHICLE SAFETY, BUMPER,
AND THEFT PREVENTION STANDARDS IN EFFECT
ON THE DATE OF MANUFACTURE SHOWN ABOVE

KLAJC52Z32K729001

PASS. CAR
P.N. 90 245 195

Figure A-3: Vehicle Certification Label




Figure A-4: Vehicle Tire Label



Figure A-5: Front View, Pre-Test



Figure A-6: Front View, Post-Test



Figure A-7: Left Side View, Pre-Test



Figure A-8: Left Side View, Post-Test



Figure A-9: Right Side View, Pre-Test



Figure A-10: Right Side View, Post-Test



Figure A-11: Right Front View, Pre-Test



Figure A-12: Right Front View, Post-Test



Figure A-13: Left Rear View, Pre-Test



Figure A-14: Left Rear View, Post-Test



Figure A-15: Windshield, Pre-Test



Figure A-16: Windshield, Post-Test



Figure A-17: Engine Compartment, Pre-Test



Figure A-18: Engine Compartment, Post-Test



Figure A-19: Fuel Cap, Pre-test



Figure A-20: Fuel Cap, Post-Test




Figure A-21: Front Underside, Pre-Test




Figure A-22: Front Underside, Post-Test




Figure A-23: Rear Underside, Pre-Test



Figure A-24: Rear Underside, Post-Test



Figure A-25: Driver Dummy Front View, Pre-Test



Figure A-26: Driver Dummy Front View, Post-Test



Figure A-27: Driver Dummy Through Window, Pre-Test



Figure A-28: Driver Dummy Through Window, Post-Test



Figure A-29: Driver Dummy Door Open, Pre-Test



Figure A-30: Driver Dummy Door Open, Post-Test



Figure A-31: Driver Dummy 90° To Vehicle, Pre-Test



Figure A-32: Driver Dummy 90° To Vehicle, Post-Test



Figure A-33: Driver Dummy Feet, Pre-Test



Figure A-34: Driver Dummy Feet and Knee Contact, Post-Test



Figure A-35: Driver Side Knee Bolster, Pre-Test



Figure A-36: Driver Side Knee Bolster, Post-Test



Figure A-37: Driver Side Floor Pan, Pre-Test



Figure A-38: Driver Side Floor Pan, Post-Test



Figure A-39: Driver Dummy Head, Post-Test




Figure A-40: Driver Dummy Contact, Post-Test




Figure A-41: Passenger Dummy Front View, Pre-Test



Figure A-42: Passenger Dummy Front View, Post-Test



Figure A-43: Passenger Dummy Through Window, Pre-Test



Figure A-44: Passenger Dummy Through Window, Post-Test



Figure A-45: Passenger Dummy Door Open, Pre-Test



Figure A-46: Passenger Dummy Door Open, Post-Test



Figure A-47: Passenger Dummy 90° To Vehicle, Pre-Test



Figure A-48: Passenger Dummy 90° To Vehicle, Post-Test




Figure A-49: Passenger Dummy Feet, Pre-Test



Figure A-50: Passenger Dummy Feet and Knee Contact, Post-Test



Figure A-51: Passenger Side Floor Pan, Pre-Test



Figure A-52: Passenger Side Floor Pan, Post-Test



Figure A-53: Passenger Side Knee Bolster, Pre-Test



Figure A-54: Passenger Side Knee Bolster, Post-Test



Figure A-55: Passenger Head, Post-Test



Figure A-56: Passenger Dummy Contact, Post-Test



Figure A-57: ^{3/4}Left Rear View of Doors Closed After Impact



Figure A-58: $\frac{3}{4}$ Right Rear View of Doors Closed After Impact



Figure A-59: Vehicle on Rollover Device



Figure A-60: Vehicle During Impact

APPENDIX B

DATA PLOTS

LIST OF DATA PLOTS

Data Plot		Page
B-1	Driver Head Primary X	B-1
B-2	Driver Head Primary X Velocity	B-2
B-3	Driver Head Primary X Displacement	B-3
B-4	Driver Head Primary Y	B-4
B-5	Driver Head Primary Z	B-5
B-6	Driver Head Resultant Primary	B-6
B-7	Driver Head Redundant X	B-7
B-8	Driver Head Redundant X Velocity	B-8
B-9	Driver Head Redundant X Displacement	B-9
B-10	Driver Head Redundant Y	B-10
B-11	Driver Head Redundant Z	B-11
B-12	Driver Head Resultant Redundant	B-12
B-13	Driver Neck Force X	B-13
B-14	Driver Neck Force Y	B-14
B-15	Driver Neck Force Z	B-15
B-16	Driver Neck Force Resultant	B-16
B-17	Driver Neck Moment X	B-17
B-18	Driver Neck Moment Y	B-18
B-19	Driver Neck Moment Z	B-19
B-20	Driver Neck Moment Resultant	B-20
B-21	Driver Chest Primary X	B-21
B-22	Driver Chest Primary X Velocity	B-22
B-23	Driver Chest Primary X Displacement	B-23
B-24	Driver Chest Primary Y	B-24
B-25	Driver Chest Primary Z	B-25
B-26	Driver Chest Primary Resultant	B-26
B-27	Driver Chest Redundant X	B-27
B-28	Driver Chest Redundant X Velocity	B-28
B-29	Driver Chest Redundant X Displacement	B-29
B-30	Driver Chest Redundant Y	B-30
B-31	Driver Chest Redundant Z	B-31
B-32	Driver Chest Redundant Resultant	B-32
B-33	Driver Chest Displacement X	B-33

LIST OF DATA PLOTS...(Continued)

Data Plot	Page
B-34 Driver Pelvis X	B-34
B-35 Driver Pelvis X Velocity	B-35
B-36 Driver Pelvis X Displacement	B-36
B-37 Driver Pelvis Y	B-37
B-38 Driver Pelvis Z	B-38
B-39 Driver Pelvis Resultant	B-39
B-40 Driver Left Femur Force	B-40
B-41 Driver Right Femur Force	B-41
B-42 Driver Left Upper Tibia Moment X	B-42
B-43 Driver Left Upper Tibia Moment Y	B-43
B-44 Driver Right Upper Tibia Moment X	B-44
B-45 Driver Right Upper Tibia Moment Y	B-45
B-46 Driver Left Lower Tibia Moment X	B-46
B-47 Driver Left Lower Tibia Moment Y	B-47
B-48 Driver Left Lower Tibia Force Z	B-48
B-49 Driver Right Lower Tibia Moment X	B-49
B-50 Driver Right Lower Tibia Moment Y	B-50
B-51 Driver Right Lower Tibia Force Z	B-51
B-52 Driver Left Foot Aft X	B-52
B-53 Driver Left Foot Aft Z	B-53
B-54 Driver Left Foot Fore Z	B-54
B-55 Driver Right Foot Aft X	B-55
B-56 Driver Right Foot Aft Z	B-56
B-57 Driver Right Foot Fore Z	B-57
B-58 Driver Lap Belt Force	B-58
B-59 Driver Shoulder Belt Force	B-59
B-60 Driver Shoulder Belt Pullout	B-60
B-61 Driver Shoulder Belt Elongation	B-61
B-62 Passenger Head Primary X	B-62
B-63 Passenger Head Primary X Velocity	B-63
B-64 Passenger Head Primary X Displacement	B-64
B-65 Passenger Head Primary Y	B-65
B-66 Passenger Head Primary Z	B-66
B-67 Passenger Head Resultant Primary	B-67

LIST OF DATA PLOTS...(Continued)


Data Plot	Page
B-68 Passenger Head Redundant X	B-68
B-69 Passenger Head Redundant X Velocity	B-69
B-70 Passenger Head Redundant X Displacement	B-70
B-71 Passenger Head Redundant Y	B-71
B-72 Passenger Head Redundant Z	B-72
B-73 Passenger Head Resultant Redundant	B-73
B-74 Passenger Neck Force X	B-74
B-75 Passenger Neck Force Y	B-75
B-76 Passenger Neck Force Z	B-76
B-77 Passenger Neck Force Resultant	B-77
B-78 Passenger Neck Moment X	B-78
B-79 Passenger Neck Moment Y	B-79
B-80 Passenger Neck Moment Z	B-80
B-81 Passenger Neck Moment Resultant	B-81
B-82 Passenger Chest Primary X	B-82
B-83 Passenger Chest Primary X Velocity	B-83
B-84 Passenger Chest Primary X Displacement	B-84
B-85 Passenger Chest Primary Y	B-85
B-86 Passenger Chest Primary Z	B-86
B-87 Passenger Chest Primary Resultant	B-87
B-88 Passenger Chest Redundant X	B-88
B-89 Passenger Chest Redundant X Velocity	B-89
B-90 Passenger Chest Redundant X Displacement	B-90
B-91 Passenger Chest Redundant Y	B-91
B-92 Passenger Chest Redundant Z	B-92
B-93 Passenger Chest Redundant Resultant	B-93
B-94 Passenger Chest Displacement X	B-94
B-95 Passenger Pelvis X	B-95
B-96 Passenger Pelvis X Velocity	B-96
B-97 Passenger Pelvis X Displacement	B-97
B-98 Passenger Pelvis Y	B-98
B-99 Passenger Pelvis Z	B-99
B-100 Passenger Pelvis Resultant	B-100
B-101 Passenger Left Femur Force	B-101

LIST OF DATA PLOTS...(Continued)

<u>Data Plot</u>	<u>Page</u>
B-102 Passenger Right Femur Force	B-102
B-103 Passenger Left Upper Tibia Moment X	B-103
B-104 Passenger Left Upper Tibia Moment Y	B-104
B-105 Passenger Right Upper Tibia Moment X	B-105
B-106 Passenger Right Upper Tibia Moment Y	B-106
B-107 Passenger Left Lower Tibia Moment X	B-107
B-108 Passenger Left Lower Tibia Moment Y	B-108
B-109 Passenger Left Lower Tibia Force Z	B-109
B-110 Passenger Right Lower Tibia Moment X	B-110
B-111 Passenger Right Lower Tibia Moment Y	B-111
B-112 Passenger Right Lower Tibia Force Z	B-112
B-113 Passenger Left Foot Aft X	B-113
B-114 Passenger Left Foot Aft Z	B-114
B-115 Passenger Left Foot Fore Z	B-115
B-116 Passenger Right Foot Aft X	B-116
B-117 Passenger Right Foot Aft Z	B-117
B-118 Passenger Right Foot Fore Z	B-118
B-119 Passenger Lap Belt Force	B-119
B-120 Passenger Shoulder Belt Force	B-120
B-121 Passenger Shoulder Belt Pullout	B-121
B-122 Passenger Shoulder Belt Elongation	B-122
B-123 Vehicle Left Rear X	B-123
B-124 Vehicle Left Rear X Velocity	B-124
B-125 Vehicle Left Rear X Displacement	B-125
B-126 Vehicle Right Rear X	B-126
B-127 Vehicle Right Rear X Velocity	B-127
B-128 Vehicle Right Rear X Displacement	B-128
B-129 Vehicle Engine Top	B-129
B-130 Vehicle Engine Top Velocity	B-130
B-131 Vehicle Engine Top Displacement	B-131
B-132 Vehicle Engine Bottom	B-132
B-133 Vehicle Engine Bottom Velocity	B-133
B-134 Vehicle Engine Bottom Displacement	B-134
B-135 Vehicle Left Brake Caliper	B-135
B-136 Vehicle Left Brake Caliper Velocity	B-136

LIST OF DATA PLOTS...(Continued)

<u>Data Plot</u>		<u>Page</u>
B-137	Vehicle Left Brake Caliper Displacement	B-137
B-138	Vehicle Right Brake Caliper	B-138
B-139	Vehicle Right Brake Caliper Velocity	B-139
B-140	Vehicle Right Brake Caliper Displacement	B-140
B-141	Vehicle Instrument Panel	B-141
B-142	Vehicle Instrument Panel Velocity	B-142
B-143	Vehicle Instrument Panel Displacement	B-143
B-144	Vehicle Left Rear Z	B-144
B-145	Vehicle Left Rear Z Velocity	B-145
B-146	Vehicle Left Rear Z Displacement	B-146
B-147	Vehicle Right Rear Z	B-147
B-148	Vehicle Right Rear Z Velocity	B-148
B-149	Vehicle Right Rear Z Displacement	B-149



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Primary X	001	FIL	G's	31.6	176.0	-62.5	82.0	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Primary X Velocity	001	IN1	KMH	55.9	0.0	-39.9	151.7	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Primary X Displ.	001	IN2	CM	105.6	84.9	-13.0	299.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Primary Y	002	FIL	G's	3.9	156.4	-13.3	95.8	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Primary Z	003	FIL	G's	26.5	49.2	-7.3	110.6	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Resultant Primary	001	RES	G's	63.8	82.0	0.1	19.7	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Redundant X	004	FIL	G's	33.1	176.2	-63.3	82.2	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Redundant X Velocity	004	IN1	KMH	55.9	9.1	-38.7	149.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Redundant X Displ.	004	IN2	CM	106.3	85.2	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Redundant Y	005	FIL	G's	3.5	156.5	-12.8	95.9	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Redundant Z	006	FIL	G's	25.7	48.5	-7.4	105.5	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Resultant Redundant	004	RES	G's	64.4	82.2	0.0	2.4	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Neck Force X	007	FIL	Newtons	279.5	92.2	-393.3	52.6	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Neck Force Y	008	FIL	Newtons	325.5	189.6	-272.1	109.1	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Neck Force Z	009	FIL	Newtons	2205.6	75.7	-522.4	192.9	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Neck Force Resultant	007	RES	Newtons	2205.7	75.7	0.5	1.6	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Neck Moment X	010	FIL	Nm	15.2	60.8	-20.5	70.9	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Neck Moment Y	011	FIL	Nm	28.6	94.6	-35.7	201.2	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Neck Moment Z	012	FIL	Nm	14.5	88.9	-10.9	141.7	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Neck Moment Resultant	010	RES	Nm	36.6	201.2	0.1	17.5	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Primary X	013	FIL	G's	5.4	149.2	-51.3	60.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Primary X Velocity	013	IN1	KMH	56.0	9.4	-21.1	112.4	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Primary X Displ.	013	IN2	CM	89.7	77.5	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Primary Y	014	FIL	G's	5.9	104.4	-9.7	54.7	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-25



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Primary Z	015	FIL	G's	16.5	48.2	-12.8	107.2	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Resultant Primary	013	RES	G's	51.8	60.9	0.0	5.7	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Redundant X	016	FIL	G's	7.7	136.2	-52.4	60.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Redundant X Velocity	016	IN1	KMH	55.9	9.0	-23.1	113.2	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Redundant X Displ.	016	IN2	CM	88.2	76.2	-7.4	299.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-30



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Redundant Y	017	FIL	G's	5.6	104.3	-9.2	54.5	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Redundant Z	018	FIL	G's	15.7	48.1	-12.8	104.6	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Resultant Redundant	016	RES	G's	52.8	60.9	0.0	3.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Chest Displacement X	019	FIL	MM	0.2	16.6	-42.7	77.9	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Pelvis X	020	FIL	G's	11.2	97.0	-65.1	53.1	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Pelvis X Velocity	020	IN1	KMH	55.9	4.1	-6.2	82.4	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Pelvis X Displ.	020	IN2	CM	81.7	69.8	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Pelvis Y	021	FIL	G's	13.4	90.6	-15.3	63.7	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Pelvis Z	022	FIL	G's	8.7	45.1	-25.0	62.5	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Pelvis Resultant	023	RES	G's	69.0	60.2	0.0	0.2	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Left Femur Force	023	FIL	Newtons	983.2	45.3	-3987.5	58.4	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Right Femur Force	024	FIL	Newtons	1580.4	48.0	-2714.7	64.2	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Left Upper Tibia Moment X	025	FIL	Nm	34.1	62.8	-14.1	78.3	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Left Upper Tibia Moment Y	026	FIL	Nm	53.5	58.0	-72.5	50.1	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Right Upper Tibia Moment X	027	FIL	Nm	89.3	43.4	-85.7	44.6	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Right Upper Tibia Moment Y	028	FIL	Nm	36.1	104.6	-140.3	43.6	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Left Lower Tibia Moment X	029	FIL	Nm	29.7	55.2	-6.3	79.3	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Left Lower Tibia Moment Y	030	FIL	Nm	58.1	88.0	-31.4	44.8	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Left Lower Tibia Force Z	031	FIL	Newtons	152.4	129.2	-2268.8	83.7	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Right Lower Tibia Moment X	032	FIL	Nm	48.2	42.4	-150.7	45.3	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-50



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Right Lower Tibia Moment Y	033	FIL	Nm	76.6	88.1	-77.1	39.4	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Right Lower Tibia Force Z	034	FIL	Newtons	186.1	133.7	-4802.0	44.0	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-52



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Left Foot Aft X	035	FIL	G's	11.0	75.7	-31.2	42.6	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Left Foot Aft Z	036	FIL	G's	5.5	152.7	-46.0	43.4	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Left Foot Fore Z	037	FIL	G's	8.8	152.9	-56.7	31.1	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-55



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Right Foot Aft X	038	FIL	G's	31.3	101.1	-167.2	44.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Right Foot Aft Z	039	FIL	G's	7.8	66.6	-110.3	41.5	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Right Foot Fore Z	040	FIL	G's	37.8	57.6	-208.9	37.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Lap Belt Force	041	FIL	Newtons	8535.6	53.8	9.7	0.0	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-59



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Shoulder Belt Force	042	FIL	Newtons	6185.3	70.0	-22.6	208.5	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-60



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Shoulder Belt Pullout	043	FIL	MM	92.6	82.3	-14.8	37.5	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



* Not used with pre-tensioner

Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Shoulder Belt Elongation	044	FIL	MM/CM	0.00	0.0	0.00	0.0	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Primary X	045	FIL	G's	21.7	204.4	-48.3	79.6	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-63



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Primary X Velocity	045	IN1	KMH	56.0	19.2	-39.3	198.3	180



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-64



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Primary X Displ.	045	IN2	CM	113.5	94.6	-34.1	299.9	180



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-65



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Primary Y	046	FIL	G's	11.1	206.2	-21.3	32.8	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Primary Z	047	FIL	G's	30.6	75.5	-3.3	133.6	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Resultant Primary	045	RES	G's	57.1	79.1	0.1	5.3	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Redundant X	048	FIL	G's	21.7	204.5	-47.1	78.9	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-69



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Redundant X Velocity	048	IN1	KMH	55.9	0.5	-36.9	171.0	180



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-70



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Redundant X Displ.	048	IN2	CM	113.4	95.1	-24.4	299.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Redundant Y	049	FIL	G's	11.4	205.9	-18.5	33.9	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Redundant Z	050	FIL	G's	31.2	75.5	-3.1	133.3	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Resultant Redundant	048	RES	G's	56.3	78.9	0.2	1.2	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Neck Force X	051	FIL	Newtons	236.9	215.6	-669.6	117.4	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Neck Force Y	052	FIL	Newtons	338.5	62.5	-264.5	101.4	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Neck Force Z	053	FIL	Newtons	1965.9	75.5	-349.5	241.9	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Neck Force Resultant	051	RES	Newtons	1975.1	75.6	0.0	6.4	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Neck Moment X	054	FIL	Nm	5.9	48.6	-34.6	63.3	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Neck Moment Y	055	FIL	Nm	55.4	132.0	-32.4	247.7	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Neck Moment Z	056	FIL	Nm	28.8	81.1	-9.6	134.6	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Neck Moment Resultant	054	RES	Nm	56.5	132.0	0.1	10.6	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-82



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Primary X	057	FIL	G's	3.1	146.2	-48.3	73.0	180



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-83



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Primary X Velocity	057	IN1	KMH	55.9	4.5	-20.7	116.7	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Primary X Displ.	057	IN2	CM	90.3	77.8	-17.6	299.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-85



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Primary Y	058	FIL	G's	7.0	54.2	-2.0	122.1	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Primary Z	059	FIL	G's	10.6	49.2	-13.6	101.7	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Resultant Primary	057	RES	G's	48.4	73.0	0.0	4.4	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Redundant X	060	FIL	G's	3.3	143.6	-47.8	73.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-89



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Redundant X Velocity	060	IN1	KMH	55.9	5.4	-19.2	116.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Redundant X Displ.	060	IN2	CM	91.2	78.5	-2.4	299.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-91



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Redundant Y	061	FIL	G's	8.1	54.3	-1.9	121.2	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Redundant Z	062	FIL	G's	10.8	49.2	-14.0	101.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Resultant Redundant	060	RES	G's	47.9	73.0	0.0	9.7	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-94



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Chest Displacement X	063	FIL	MM	0.2	6.0	-45.0	71.5	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Pelvis X	064	FIL	G's	7.5	105.8	-85.4	52.8	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Pelvis X Velocity	064	IN1	KMH	56.0	7.2	-8.1	85.8	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Pelvis X Displ.	064	IN2	CM	81.7	69.8	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Pelvis Y	065	FIL	G's	6.1	146.1	-8.0	79.1	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Pelvis Z	066	FIL	G's	3.7	218.2	-23.0	70.2	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Pelvis Resultant	066	RES	G's	85.9	52.8	0.0	1.5	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Left Femur Force	067	FIL	Newtons	824.7	48.5	-6227.2	57.3	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Right Femur Force	068	FIL	Newtons	441.7	45.5	-4568.4	54.1	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Left Upper Tibia Moment X	069	FIL	Nm	38.1	82.0	-85.4	50.5	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Left Upper Tibia Moment Y	070	FIL	Nm	90.2	50.4	-135.1	47.2	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-105



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Right Upper Tibia Moment X	071	FIL	Nm	48.7	48.9	-33.2	40.0	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Right Upper Tibia Moment Y	072	FIL	Nm	18.3	112.0	-82.9	43.4	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Left Lower Tibia Moment X	073	FIL	Nm	56.3	51.2	-35.8	46.8	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Left Lower Tibia Moment Y	074	FIL	Nm	73.4	54.7	-62.1	47.7	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Left Lower Tibia Force Z	075	FIL	Newtons	156.6	122.9	-3183.4	45.3	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Right Lower Tibia Moment X	076	FIL	Nm	88.6	48.7	-8.9	38.5	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-111



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Right Lower Tibia Moment Y	077	FIL	Nm	68.0	77.6	-33.7	41.2	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Right lower Tibia Force Z	078	FIL	Newtons	123.5	137.1	-2688.1	78.8	600




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Left Foot Aft X	079	FIL	G's	9.2	97.0	-87.9	44.7	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-114



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Left Foot Aft Z	080	FIL	G's	12.4	50.2	-76.4	47.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Left Foot Fore Z	081	FIL	G's	22.4	69.2	-96.4	47.5	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Right Foot Aft X	082	FIL	G's	24.9	76.5	-80.3	44.8	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Right Foot Aft Z	083	FIL	G's	4.2	152.2	-38.0	78.7	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Right Foot Fore Z	084	FIL	G's	13.5	23.8	-93.5	37.6	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Lap Belt Force	085	FIL	Newtons	6903.9	55.2	-1.7	0.0	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-120



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Shoulder Belt Force	086	FIL	Newtons	5865.7	73.4	10.0	0.0	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-121



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Shoulder Belt Pullout	087	FIL	MM	41.3	94.1	-12.6	299.6	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



* Not used with pre-tensioner

Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Shoulder Belt Elongation	088	FIL	MM/CM	0.00	0.0	0.00	0.0	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-123



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Left Rear X	089	FIL	G's	2.5	158.3	-54.6	41.0	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-124



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Left Rear X Velocity	089	IN1	KMH	55.9	0.0	-8.8	132.2	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Left Rear X Displ.	089	IN2	CM	65.3	71.4	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Right Rear X	090	FIL	G's	1.4	139.0	-40.1	40.9	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Right Rear X Velocity	090	IN1	KMH	55.9	0.0	-9.7	120.1	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Right Rear X Displ.	090	IN2	CM	66.0	70.8	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-129



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Engine Top	091	FIL	G's	54.7	40.4	-176.6	30.5	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-130



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Engine Top Velocity	091	IN1	KMH	56.0	14.1	-9.9	64.5	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Engine Top Displacement	091	IN2	CM	40.8	32.3	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-132



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Engine Bottom	092	FIL	G's	34.3	41.0	-141.4	25.2	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Engine Bottom Velocity	092	IN1	KMH	55.9	0.0	-2.0	126.4	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Engine Bottom Displacement	092	IN2	CM	45.4	86.9	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-135



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Left Brake Caliper	093	FIL	G's	5.0	60.6	-83.0	41.1	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Left Brake Caliper Velocity	093	IN1	KMH	56.5	7.6	-2.6	117.8	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Left Brake Caliper Displ.	093	IN2	CM	61.3	82.3	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Right Brake Caliper	094	FIL	G's	19.8	67.6	-71.8	45.0	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-139



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Right Brake Caliper Velocity	094	IN1	KMH	56.6	7.5	-1.4	60.7	180



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-140



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Right Brake Caliper Displ.	094	IN2	CM	88.2	299.9	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Instrument Panel	095	FIL	G's	29.8	94.5	-53.6	58.3	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-142



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Instrument Panel Velocity	095	IN1	KMH	55.9	0.0	-11.9	81.1	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Instrument Panel Displacement	095	IN2	CM	66.7	67.6	0.0	0.0	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Left Rear Z	096	FIL	G's	12.0	38.4	-8.4	42.1	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-145



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Left Rear Z Velocity	096	IN1	KMH	6.4	108.1	-2.0	299.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Left Rear Z Displ.	096	IN2	CM	11.9	220.9	0.0	17.6	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

B-147



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Right Rear Z	097	FIL	G's	8.9	90.4	-5.2	50.7	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

B-148



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Right Rear Z Velocity	097	IN1	KMH	5.6	109.8	-1.3	299.9	180




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Vehicle Right Rear Z Displ.	097	IN2	CM	12.1	245.8	0.0	12.0	180



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02


Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

APPENDIX C

LOAD CELL BARRIER DATA PLOTS

C-1



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force A2	099	FIL	Newtons	1527.8	11.3	-1523.6	31.0	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-2



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force A3	100	FIL	Newtons	2519.0	12.5	-1399.2	4.9	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-3



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force A4	101	FIL	Newtons	2225.6	25.9	-1197.0	43.8	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-4



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force A5	102	FIL	Newtons	28958.0	75.3	-709.2	4.0	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-5



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force A6	103	FIL	Newtons	15071.8	27.0	-1411.7	20.6	60

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02


Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



KAR22001-05

C-6



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force A7	104	FIL	Newtons	7498.9	26.1	-578.8	134.7	60

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02


Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



KAR22001-05

C-7



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force A8	105	FIL	Newtons	5522.2	56.1	-781.1	18.8	60

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02


Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



KAR22001-05

C-8



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force A9	106	FIL	Newtons	2341.1	23.3	-1060.0	44.1	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-9



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force B2	108	FIL	Newtons	7967.1	11.4	-995.3	4.2	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-10



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force B3	109	FIL	Newtons	71357.6	14.0	-441.5	0.8	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-11



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force B4	110	FIL	Newtons	60798.9	60.7	-67.4	174.6	60

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02


Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



KAR22001-05

C-12



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force B5	111	FIL	Newtons	71970.3	50.6	-57.9	159.7	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-13



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force B6	112	FIL	Newtons	88718.5	28.2	-27.7	159.1	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-14



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force B7	113	FIL	Newtons	95765.2	24.8	-548.6	1.2	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-15



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force B8	114	FIL	Newtons	9776.0	52.2	-242.4	3.5	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-16



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force B9	115	FIL	Newtons	818.6	40.0	-975.5	44.2	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-17



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force C2	117	FIL	Newtons	35008.9	40.3	-1084.7	6.2	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-18



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force C3	118	FIL	Newtons	46238.6	32.9	-990.0	4.5	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-19



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force C4	119	FIL	Newtons	36387.3	48.9	-703.2	1.6	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-20



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force C5	120	FIL	Newtons	18658.6	49.6	-382.9	1.2	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-21



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force C6	121	FIL	Newtons	28289.8	25.8	-412.7	1.5	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-22



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force C7	122	FIL	Newtons	13046.8	49.7	-796.6	4.8	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-23



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force C8	123	FIL	Newtons	42820.7	38.3	-181.1	6.7	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-24



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Barrier Force C9	124	FIL	Newtons	830.8	40.1	-1040.6	44.3	60

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02


Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



KAR22001-05

C-25



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Barrier Force Sum Group 1	001	SUM	Newtons	80532.2	13.5	-1379.5	3.0	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Barrier Force Sum Group 2	002	SUM	Newtons	210413.5	51.9	-317.1	159.4	60




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

C-27



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Barrier Force Sum Group 3	003	SUM	Newtons	112725.2	24.7	-712.2	1.5	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-28



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Barrier Force Sum Group 4	004	SUM	Newtons	73273.0	39.5	-1887.2	5.0	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-29



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Barrier Force Sum Group 5	005	SUM	Newtons	79311.7	49.1	-1484.1	1.4	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-30



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Barrier Force Sum Group 6	006	SUM	Newtons	55863.2	38.5	-842.9	4.3	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-31



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Barrier Force Total Sum	007	SUM	Newtons	484738.0	27.8	-1061.5	172.7	60



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan


Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

C-32



Curve Description	CURNO	Type	Units	Max	CM	Energy (Joules)	SAE Class
Barrier Force Total Sum vs. Displ.	001	XVY	Newtons	484738.0	39.3	185624.0	60/180



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05

BARRIER LOAD CELL SUMMARY DATA

Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

NHTSA No.: M20502

Test Program: 2002 NHTSA 35mph NCAP

Test Date: 4/23/02

Location	Max	Time	Min	Time
Driver Barrier Force A2	1527.8	11.3	-1523.6	31.0
Driver Barrier Force A3	2519.0	12.5	-1399.2	4.9
Driver Barrier Force A4	2225.6	25.9	-1197.0	43.8
Driver Barrier Force A5	28958.0	75.3	-709.2	4.0
Driver Barrier Force A6	15071.8	27.0	-1411.7	20.6
Driver Barrier Force A7	7498.9	26.1	-578.8	134.7
Driver Barrier Force A8	5522.2	56.1	-781.1	18.8
Driver Barrier Force A9	2341.1	23.3	-1060.0	44.1
Driver Barrier Force B2	7967.1	11.4	-995.3	4.2
Driver Barrier Force B3	71357.6	14.0	-441.5	0.8
Driver Barrier Force B4	60798.9	60.7	-67.4	174.6
Driver Barrier Force B5	71970.3	50.6	-57.9	159.7
Driver Barrier Force B6	88718.5	28.2	-27.7	159.1
Driver Barrier Force B7	95765.2	24.8	-548.6	1.2
Driver Barrier Force B8	9776.0	52.2	-242.4	3.5
Driver Barrier Force B9	818.6	40.0	-975.5	44.2
Driver Barrier Force C2	35008.9	40.3	-1084.7	6.2
Driver Barrier Force C3	46238.6	32.9	-990.0	4.5
Driver Barrier Force C4	36387.3	48.9	-703.2	1.6
Driver Barrier Force C5	18658.6	49.6	-382.9	1.2
Driver Barrier Force C6	28289.8	25.8	-412.7	1.5
Driver Barrier Force C7	13046.8	49.7	-796.6	4.8
Driver Barrier Force C8	42820.7	38.3	-181.1	6.7
Driver Barrier Force C9	830.8	40.1	-1040.6	44.3
Barrier Force Sum Group 1	80532.2	13.5	-1379.5	3.0
Barrier Force Sum Group 2	210413.5	51.9	-317.1	159.4
Barrier Force Sum Group 3	112725.2	24.7	-712.2	1.5
Barrier Force Sum Group 4	73273.0	39.5	-1887.2	5.0
Barrier Force Sum Group 5	79311.7	49.1	-1484.1	1.4
Barrier Force Sum Group 6	55863.2	38.5	-842.9	4.3
Barrier Force Total Sum	484738.0	27.8	-1061.5	172.7

Locations A1,B1,C1, and D1 through D9 (12 locations) were not recorded.

APPENDIX D

INSTRUMENTATION DATA CHANNEL ASSIGNMENTS

2002 NHTSA 35mph NCAP
Instrumentation Data Channel Assignments
Driver A.T.D. Serial Number 34
4/23/02
2002 Daewoo Nubira SE 4 Door Sedan

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
1	HEAD, PRIMARY	X	KEAC039	Accel.,1/2 bridge	Endevco	7264-2000	G
2	HEAD, PRIMARY	Y	KEAC038	Accel.,1/2 bridge	Endevco	7264-2000	G
3	HEAD, PRIMARY	Z	KEAC027	Accel.,1/2 bridge	Endevco	7264-2000	G
4	HEAD, REDUNDANT	X	KEAC031	Accel.,1/2 bridge	Endevco	7264-2000	G
5	HEAD, REDUNDANT	Y	KEAC032	Accel.,1/2 bridge	Endevco	7264-2000	G
6	HEAD, REDUNDANT	Z	KEAC026	Accel.,1/2 bridge	Endevco	7264-2000	G
7	NECK FORCE	X	GPUN02FX	Load cell, six axis neck	R. A. Denton	1716A	N
8	NECK FORCE	Y	GPUN02FY	Load cell, six axis neck	R. A. Denton	1716A	N
9	NECK FORCE	Z	GPUN02FZ	Load cell, six axis neck	R. A. Denton	1716A	N
10	NECK MOMENT	X	GPUN02MX	Load cell, six axis neck	R. A. Denton	1716A	Nm
11	NECK MOMENT	Y	GPUN02MY	Load cell, six axis neck	R. A. Denton	1716A	Nm
12	NECK MOMENT	Z	GPUN02MZ	Load cell, six axis neck	R. A. Denton	1716A	Nm
13	CHEST , PRIMARY	X	GPAC031	Accel., 1/2 bridge	Endevco	7264-2000	G
14	CHEST , PRIMARY	Y	GPAC024	Accel., 1/2 bridge	Endevco	7264-2000	G
15	CHEST , PRIMARY	Z	GPAC029	Accel., 1/2 bridge	Endevco	7264-2000	G
16	CHEST , REDUNDANT	X	KEAC023	Accel.,1/2 bridge	Endevco	7264-200	G
17	CHEST , REDUNDANT	Y	KEAC022	Accel.,1/2 bridge	Endevco	7264-200	G
18	CHEST , REDUNDANT	Z	KEAC024	Accel.,1/2 bridge	Endevco	7264-200	G
19	CHEST DISPLACEMENT	X	GPCP001	Rotary Pot Chest	Servo	14CBI	MM
20	PELVIS, PRIMARY	X	KEAC019	Accel.,1/2 bridge	Endevco	7264-200	G
21	PELVIS, PRIMARY	Y	KEAC020	Accel.,1/2 bridge	Endevco	7264-200	G
22	PELVIS, PRIMARY	Z	KEAC021	Accel.,1/2 bridge	Endevco	7264-200	G
23	LEFT FEMUR FORCE	Z	KEFF001	Load cell, Femur	R.A. Denton	2121	N
24	RIGHT FEMUR FORCE	Z	KEFF002	Load cell, Femur	R.A. Denton	2121	N

**2002 NHTSA 35mph NCAP
Instrumentation Data Channel Assignments
Driver A.T.D. Serial Number 34
4/23/02
2002 Daewoo Nubira SE 4 Door Sedan**

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
25	UP. TIBIA LEFT MOM.	X	GPUT09MX	2 ch., Upper tibia gage	R. A. Denton	1583	Nm
26	UP. TIBIA LEFT MOM.	Y	GPUT09MY	2 ch., Upper tibia gage	R. A. Denton	1583	Nm
27	UP. TIBIA RIGHT MOM.	X	GPUT09MX	2 ch., Upper tibia gage	R. A. Denton	1583	Nm
28	UP. TIBIA RIGHT MOM.	Y	GPUT09MY	2 ch., Upper tibia gage	R. A. Denton	1583	Nm
29	LWR. TIBIA LEFT MOM.	X	GPLT09MX	3 ch., lower tibia gage	R. A. Denton	3093	Nm
30	LWR. TIBIA LEFT MOM.	Y	GPLT09MY	3 ch., lower tibia gage	R. A. Denton	3093	Nm
31	LWR. TIBIA LEFT FORCE	Z	GPLT09FZ	3 ch., lower tibia gage	R. A. Denton	3093	N
32	LWR. TIBIA RIGHT MOM.	X	GPLT09MX	3 ch., lower tibia gage	R. A. Denton	3093	Nm
33	LWR. TIBIA RIGHT MOM.	Y	GPLT09MY	3 ch., lower tibia gage	R. A. Denton	3093	Nm
34	LWR. TIBIA RIGHT FORCE	Z	GPLT09FZ	3 ch., lower tibia gage	R. A. Denton	3093	N
35	FOOT LEFT, AFT	X	KEIC003X	Accel., Foot Triax	I.C. Sensor	3031-500	G
36	FOOT LEFT, AFT	Z	KEIC003Y	Accel., Foot Triax	I.C. Sensor	3031-500	G
37	FOOT LEFT, FORE	Z	KEIC003Z	Accel., Foot Triax	I.C. Sensor	3031-500	G
38	FOOT RIGHT, AFT	X	KEIC004X	Accel., Foot Triax	I.C. Sensor	3031-500	G
39	FOOT RIGHT, AFT	Z	KEIC004Y	Accel., Foot Triax	I.C. Sensor	3031-500	G
40	FOOT RIGHT, FORE	Z	KEIC004Z	Accel., Foot Triax	I.C. Sensor	3031-500	G
41	LAP BELT FORCE	X	KELC003	Load cell, Seat belt	Lebow	3371	N
42	SHOULDER BELT FORCE	X	KELC004	Load cell, Seat belt	Lebow	3371	N
43	SHOULDER BELT SPOOL	X	KEPP001	Pullout pot	Celesco	PTX101-0030	CM
44	SHOULDER BELT ELONG.	X	KEEP001	Linear pot., belt stretch	E.T.I.	LCP8-10 10K	MM/CM

**2002 NHTSA 35mph NCAP
Instrumentation Data Channel Assignments
Passenger A.T.D. Serial Number 35
4/23/02
2002 Daewoo Nubira SE 4 Door Sedan**

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
45	HEAD, PRIMARY	X	GPAC027	Accel., 1/2 bridge	Endevco	7264-2000	G
46	HEAD, PRIMARY	Y	GPAC002	Accel., 1/2 bridge	Endevco	7264-2000	G
47	HEAD, PRIMARY	Z	GPAC003	Accel., 1/2 bridge	Endevco	7264-2000	G
48	HEAD, REDUNDANT	X	GPAC032	Accel., 1/2 bridge	Endevco	7264-2000	G
49	HEAD, REDUNDANT	Y	GPAC021	Accel., 1/2 bridge	Endevco	7264-2000	G
50	HEAD, REDUNDANT	Z	GPAC026	Accel., 1/2 bridge	Endevco	7264-2000	G
51	NECK FORCE	X	GPUN01FX	Load cell, six axis neck	R. A. Denton	1716A	N
52	NECK FORCE	Y	GPUN01FY	Load cell, six axis neck	R. A. Denton	1716A	N
53	NECK FORCE	Z	GPUN01FZ	Load cell, six axis neck	R. A. Denton	1716A	N
54	NECK MOMENT	X	GPUN01MX	Load cell, six axis neck	R. A. Denton	1716A	Nm
55	NECK MOMENT	Y	GPUN01MY	Load cell, six axis neck	R. A. Denton	1716A	Nm
56	NECK MOMENT	Z	GPUN01MZ	Load cell, six axis neck	R. A. Denton	1716A	Nm
57	CHEST , PRIMARY	X	GPAC005	Accel., 1/2 bridge	Endevco	7264-2000	G
58	CHEST , PRIMARY	Y	GPAC011	Accel., 1/2 bridge	Endevco	7264-2000	G
59	CHEST , PRIMARY	Z	GPAC010	Accel., 1/2 bridge	Endevco	7264-2000	G
60	CHEST , REDUNDANT	X	GPAC034	Accel., 1/2 bridge	Endevco	7264-2000	G
61	CHEST , REDUNDANT	Y	GPAC023	Accel., 1/2 bridge	Endevco	7264-2000	G
62	CHEST , REDUNDANT	Z	GPAC020	Accel., 1/2 bridge	Endevco	7264-2000	G
63	CHEST DISPLACEMENT	X	GPCP002	Rotary Pot Chest	Servo	14CBI	MM
64	PELVIS, PRIMARY	X	GPAC025	Accel., 1/2 bridge	Endevco	7264-2000	G
65	PELVIS, PRIMARY	Y	GPAC022	Accel., 1/2 bridge	Endevco	7264-2000	G
66	PELVIS, PRIMARY	Z	GPAC019	Accel., 1/2 bridge	Endevco	7264-2000	G
67	LEFT FEMUR FORCE	Z	KEFF003	Load cell, Femur	R.A. Denton	2121	N
68	RIGHT FEMUR FORCE	Z	KEFF004	Load cell, Femur	R.A. Denton	2121	N

2002 NHTSA 35mph NCAP
Instrumentation Data Channel Assignments
Passenger A.T.D. Serial Number 35
4/23/02
2002 Daewoo Nubira SE 4 Door Sedan

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
69	UP. TIBIA LEFT MOM.	X	GPUT09MX	2 ch., Upper tibia gage	R. A. Denton	1583	Nm
70	UP. TIBIA LEFT MOM.	Y	GPUT09MY	2 ch., Upper tibia gage	R. A. Denton	1583	Nm
71	UP. TIBIA RIGHT MOM.	X	GPUT09MX	2 ch., Upper tibia gage	R. A. Denton	1583	Nm
72	UP. TIBIA RIGHT MOM.	Y	GPUT09MY	2 ch., Upper tibia gage	R. A. Denton	1583	Nm
73	LWR. TIBIA LEFT MOM.	X	GPLT09MX	3 ch., lower tibia gage	R. A. Denton	3093	Nm
74	LWR. TIBIA LEFT MOM.	Y	GPLT09MY	3 ch., lower tibia gage	R. A. Denton	3093	Nm
75	LWR. TIBIA LEFT FORCE	Z	GPLT09FZ	3 ch., lower tibia gage	R. A. Denton	3093	N
76	LWR. TIBIA RIGHT MOM.	X	GPLT09MX	3 ch., lower tibia gage	R. A. Denton	3093	Nm
77	LWR. TIBIA RIGHT MOM.	Y	GPLT09MY	3 ch., lower tibia gage	R. A. Denton	3093	Nm
78	LWR. TIBIA RIGHT FORCE	Z	GPLT09FZ	3 ch., lower tibia gage	R. A. Denton	3093	N
79	FOOT LEFT, AFT	X	KEIC002X	Accel., Foot Triax	I.C. Sensor	3031-500	G
80	FOOT LEFT, AFT	Z	KEIC002Y	Accel., Foot Triax	I.C. Sensor	3031-500	G
81	FOOT LEFT, FORE	Z	KEIC002Z	Accel., Foot Triax	I.C. Sensor	3031-500	G
82	FOOT RIGHT, AFT	X	KEIC001X	Accel., Foot Triax	I.C. Sensor	3031-500	G
83	FOOT RIGHT, AFT	Z	KEIC001Y	Accel., Foot Triax	I.C. Sensor	3031-500	G
84	FOOT RIGHT, FORE	Z	KEIC001Z	Accel., Foot Triax	I.C. Sensor	3031-500	G
85	LAP BELT FORCE	X	KELC001	Load cell, Seat belt	Lebow	3371	N
86	SHOULDER BELT FORCE	X	KELC002	Load cell, Seat belt	Lebow	3371	N
87	SHOULDER BELT SPOOL	X	KEPP001	Pullout pot	Celesco	PTX101-0030	MM
88	SHOULDER BELT ELONG.	X	KEEP001	Linear pot., belt stretch	E.T.I.	LCP8-10 10K	MM/CM

**2002 NHTSA 35mph NCAP
Instrumentation Data Channel Assignments
Vehicle Accelerometers
4/23/02
2002 Daewoo Nubira SE 4 Door Sedan**

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
89	Left Rear	X	KEVA005	Accel., Vehicle block	I.C. Sensor	3031-500	G
90	Right Rear	X	KEVA002	Accel., Pre-Amp	I.C.S/Karco	3031-500	G
91	Engine Top	X	KEVA012	Accel., Vehicle block	I.C. Sensor	3031-500	G
92	Engine Bottom	X	KEVA008	Accel., Vehicle block	I.C. Sensor	3031-500	G
93	Left Brake Caliper	X	KEVA007	Accel., Vehicle block	I.C. Sensor	3031-500	G
94	Right Brake Caliper	X	KEVA001	Accel., Vehicle block	I.C. Sensor	3031-500	G
95	Instrument Panel	X	KEVA011	Accel., Vehicle block	I.C. Sensor	3031-200	G
96	Left Rear	Z	KEVA010	Accel., Vehicle block	I.C. Sensor	3031-200	G
97	Right Rear	Z	KEVA006	Accel., Vehicle block	I.C. Sensor	3031-200	G

**2002 NHTSA 35mph NCAP
Instrumentation Data Channel Assignments
Rigid Load Cell Barrier
4/23/02
2002 Daewoo Nubira SE 4 Door Sedan**

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
98	BARRIER FORCE A1	X	BARRIER	Not Used	N/A	N/A	N/A
99	BARRIER FORCE A2	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
100	BARRIER FORCE A3	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
101	BARRIER FORCE A4	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
102	BARRIER FORCE A5	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
103	BARRIER FORCE A6	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
104	BARRIER FORCE A7	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
105	BARRIER FORCE A8	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
106	BARRIER FORCE A9	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
107	BARRIER FORCE B1	X	BARRIER	Not Used	N/A	N/A	N/A
108	BARRIER FORCE B2	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
109	BARRIER FORCE B3	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
110	BARRIER FORCE B4	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
111	BARRIER FORCE B5	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
112	BARRIER FORCE B6	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
113	BARRIER FORCE B7	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
114	BARRIER FORCE B8	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
115	BARRIER FORCE B9	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N

**2002 NHTSA 35mph NCAP
Instrumentation Data Channel Assignments
Rigid Load Cell Barrier
4/23/02
2002 Daewoo Nubira SE 4 Door Sedan**

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
116	BARRIER FORCE C1	X	BARRIER	Not Used	N/A	N/A	N/A
117	BARRIER FORCE C2	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
118	BARRIER FORCE C3	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
119	BARRIER FORCE C4	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
120	BARRIER FORCE C5	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
121	BARRIER FORCE C6	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
122	BARRIER FORCE C7	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
123	BARRIER FORCE C8	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
124	BARRIER FORCE C9	X	BARRIER	Load Cell, LCB	Lebow	1220-FS	N
125	BARRIER FORCE D1	X	BARRIER	Not Used	N/A	N/A	N/A
126	BARRIER FORCE D2	X	BARRIER	Not Used	N/A	N/A	N/A
127	BARRIER FORCE D3	X	BARRIER	Not Used	N/A	N/A	N/A
128	BARRIER FORCE D4	X	BARRIER	Not Used	N/A	N/A	N/A
129	BARRIER FORCE D5	X	BARRIER	Not Used	N/A	N/A	N/A
130	BARRIER FORCE D6	X	BARRIER	Not Used	N/A	N/A	N/A
131	BARRIER FORCE D7	X	BARRIER	Not Used	N/A	N/A	N/A
132	BARRIER FORCE D8	X	BARRIER	Not Used	N/A	N/A	N/A
133	BARRIER FORCE D9	X	BARRIER	Not Used	N/A	N/A	N/A

**2002 NHTSA 35mph NCAP
Instrumentation Data Channel Assignments
Nine Accelerometer Head Array Channels
4/23/02
2002 Daewoo Nubira SE 4 Door Sedan**

CH.	LOCATION	AXIS	IDENT. NO.	DESCRIPTION	MFR	MODEL	UNITS
134	Driver Head CG	X	KEAC039	Accel.,1/2 bridge	Endevco	7264-2000	G
135	Driver Head CG	Y	KEAC038	Accel.,1/2 bridge	Endevco	7264-2000	G
136	Driver Head CG	Z	KEAC027	Accel.,1/2 bridge	Endevco	7264-2000	G
137	Driver Y-arm	Z	GPAC016	Accel., 1/2 bridge	Endevco	7264-2000	G
138	Driver Y-arm	X	GPAC015	Accel., 1/2 bridge	Endevco	7264-2000	G
139	Driver X-arm	Z	GPAC004	Accel., 1/2 bridge	Endevco	7264-2000	G
140	Driver X-arm	Y	GPAC018	Accel., 1/2 bridge	Endevco	7264-2000	G
141	Driver Z-arm	X	GPAC006	Accel., 1/2 bridge	Endevco	7264-2000	G
142	Driver Z-arm	Y	GPAC007	Accel., 1/2 bridge	Endevco	7264-2000	G
143	Passenger Head CG	X	GPAC027	Accel., 1/2 bridge	Endevco	7264-2000	G
144	Passenger Head CG	Y	GPAC002	Accel., 1/2 bridge	Endevco	7264-2000	G
145	Passenger Head CG	Z	GPAC003	Accel., 1/2 bridge	Endevco	7264-2000	G
146	Passenger Y-arm	Z	GPAC012	Accel., 1/2 bridge	Endevco	7264-2000	G
147	Passenger Y-arm	X	GPAC001	Accel., 1/2 bridge	Endevco	7264-2000	G
148	Passenger X-arm	Z	GPAC036	Accel., 1/2 bridge	Endevco	7264-2000	G
149	Passenger X-arm	Y	GPAC014	Accel., 1/2 bridge	Endevco	7264-2000	G
150	Passenger Z-arm	X	GPAC030	Accel., 1/2 bridge	Endevco	7264-2000	G
151	Passenger Z-arm	Y	GPAC037	Accel., 1/2 bridge	Endevco	7264-2000	G

* Duplicate of Head CG Primary Channels

APPENDIX E

DUMMY CALIBRATION DATA



Hybrid III Calibration Data Sheet

Hybrid III 50th Percentile Male

Knee Impact Test

ATD Serial No.: 034

Location: Left Knee

Test I.D.: LK01A

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Pendulum Velocity at T=0	m/sec	2.07 to 2.13	2.12	Pass
Peak Probe Force	N	4715 to 5782	5431	Pass
Overall Test Results				Pass

ATD Serial No.: 034

Location: Right Knee


Test I.D.: RK01A

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Pendulum Velocity at T=0	m/sec	2.07 to 2.13	2.10	Pass
Peak Probe Force	N	4715 to 5782	5695	Pass
Overall Test Results				Pass

Laboratory Technician

April 1, 2002


Test Date



Curve Description: Probe Force
Maximum Value: 5431.0 at 2.5 Milliseconds
Minimum Value: -33.5 at 7.5 Milliseconds
SAE Filter Class: 600
Date of Test: 4/1/02
ATD Serial No.: 034

Test Program: Hybrid III Knee Impact Test
Test Information: Location: Left Knee Test I.D.: LK01A





Curve Description: Probe Force

Maximum Value: 5694.7 at 2.4 Milliseconds

Minimum Value: -72.8 at 7.4 Milliseconds

SAE Filter Class: 600

Date of Test: 4/1/02

ATD Serial No.: 034

Test Program: Hybrid III Knee Impact Test

Test Information: Location: Right Knee Test I.D.: RK01A





Hybrid III Calibration Data Sheet

Hybrid III 50th Percentile Male

Knee Slider Test

ATD Serial No.: 034

Location: Left Knee

Test I.D.: KS001

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		°C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Velocity at T=0		m/sec	2.70 to 2.80	2.77	Pass
Impact Force at:	10 mm	kN	1.26 to 1.72	1.68	Pass
	18 mm	kN	2.27 to 3.096	2.98	Pass
Overall Test Results					Pass

ATD Serial No.: 034

Location: Right Knee


Test I.D.: KS002

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		°C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Velocity at T=0		m/sec	2.70 to 2.80	2.71	Pass
Impact Force at:	10 mm	kN	1.26 to 1.72	1.55	Pass
	18 mm	kN	2.27 to 3.096	2.94	Pass
Overall Test Results					Pass

Laboratory Technician

April 1, 2002

Test Date



Curve Description: Femur Force vs. Knee Displacement

Femur Force: 1677 at 10.0 mm

Femur Force: 2983 at 18.0 mm

SAE Filter Class: 600

Date of Test: 4/1/02

ATD Serial No.: 034


Test Program:

Hybrid III Knee Shear Test

Test Information:

Location: Left Knee Test I.D.: KS001





Curve Description: Femur Force vs. Knee Displacement

Femur Force: 1546 at 10.0 mm

Femur Force: 2938 at 18.0 mm

SAE Filter Class: 600

Date of Test: 4/1/02

ATD Serial No.: 034

Test Program: Hybrid III Knee Shear Test

Test Information: Location: Right Knee Test I.D.: KS002





Hybrid III Calibration Data Sheet

50TH Percentile Male

Head Drop Calibration

ATD Serial No.: 034

Part Serial No.: N/A

Test I.D.: HD01A


Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Peak Resultant Acceleration	G's	225.0 to 275.0	244.3	Pass
Peak Lateral Acceleration	G's	≤15.0	2.0	Pass
Is Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician

April 1, 2002

Test Date

E-8



Curve Description: Head Resultant Acceleration

Maximum Value:	<u>244.3</u>	at	<u>2.0</u>	Milliseconds
Minimum Value:	<u>0.0</u>	at	<u>-1.2</u>	Milliseconds
SAE Filter Class:	<u>1000</u>			
Date of Test:	<u>4/1/02</u>			
ATD Serial No.:	<u>034</u>			


Testing Program: Hybrid III Head Drop Calibration (Male)

Test Information: S/N of Part: N/A Test I.D.: HD01A



KAR22001-05

E-9



Curve Description: Head Acceleration Y Axis

Maximum Value: 2.0 at 1.8 Milliseconds

Minimum Value: -1.2 at 7.4 Milliseconds

SAE Filter Class: 1000

Date of Test: 4/1/02

ATD Serial No.: 034

Testing Program: Hybrid III Head Drop Calibration (Male)

Test Information: S/N of Part: N/A Test I.D.: HD01A



KAR22001-05



Hybrid III Calibration Data Sheet

50TH Percentile Male

Thorax Impact Test

ATD Serial No.: 034

Part Serial No.: N/A


Test I.D.: CH01A

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.2	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	6.58 to 6.82	6.68	Pass
Peak Probe Force	Newtons	5159 to 5893	5349	Pass
Peak Sternum Displacement	CM	6.35 to 7.26	7.09	Pass
Internal Hysteresis	%	69 to 85	74.0	Pass
Overall Test Results				Pass

Laboratory Technician

April 2, 2002

Test Date



Curve Description: Probe Force vs. Chest Displacement

Probe Force: 5348.9 Newtons

Chest Displ.: 7.09 Centimeters

SAE Filter Class: 180

Date of Test: 4/2/02

ATD Serial No.: 034

Testing Program: Hybrid III Thorax Impact Test

Test Information: S/N of Part: N/A Test I.D.: CH01A





Hybrid III Calibration Data Sheet

50TH Percentile Male

Neck Flexion Test

ATD Serial No.: 034

Part Serial No.: N/A


Test I.D.: NF02A

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		°C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Velocity		m/s	6.89 to 7.13	7.04	Pass
Pendulum Deceleration	10 Msec.	G's	22.5 to 27.5	23.2	Pass
	20 Msec.	G's	17.6 to 22.6	18.8	Pass
	30 Msec.	G's	12.5 to 18.5	17.4	Pass
Peak Pendulum Decel. after 30 Msec.		G's	≤ 29.0	17.4	Pass
Deceleration Decay, Time to Cross 5 G's		Msec.	34.0 to 42.0	38.5	Pass
Maximum "D" Plane Rotation	Maximum	Degrees	64.0 to 78.0	72.0	Pass
	Time	Msec.	57.0 to 64.0	60.6	Pass
"D" Plane Rotation Decay, Time To Zero Crossing		Msec.	113.0 to 128.0	118.6	Pass
Moment About Occipital Condyle	Maximum	N·m	84.1 to 108.5	88.8	Pass
	Time	Msec.	47.0 to 58.0	56.3	Pass
Positive Moment Decay, Time To Zero Crossing		Msec.	97.0 to 107.0	101.8	Pass
Overall Test Results					Pass

Laboratory Technician

April 2, 2002

Test Date




Curve Description: Pendulum Deceleration

Maximum Value:	<u>23.3</u>	at	<u>9.2</u>	Milliseconds
Minimum Value:	<u>-2.3</u>	at	<u>87.9</u>	Milliseconds
SAE Filter Class:	<u>60</u>			
Date of Test:	<u>4/2/02</u>			
ATD Serial No.:	<u>034</u>			

Testing Program: Hybrid III Neck Flexion Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NF02A






Curve Description: Neck Force X

Maximum Value:	828.0	at	54.1	Milliseconds
Minimum Value:	-151.7	at	164.9	Milliseconds
SAE Filter Class:	60			
Date of Test:	4/2/02			
ATD Serial No.:	034			

Testing Program: Hybrid III Neck Flexion Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NF02A






Curve Description: "D" Plane Rotation

Maximum Value:	72.0	at	60.6	Milliseconds
Minimum Value:	-46.7	at	182.6	Milliseconds
SAE Filter Class:	60			
Date of Test:	4/2/02			
ATD Serial No.:	034			

Testing Program: Hybrid III Neck Flexion Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NF02A





Curve Description: Moment About Occipital Condyles

Maximum Value: 88.8 at 56.3 Milliseconds

Minimum Value: -27.6 at 14.1 Milliseconds

SAE Filter Class: 60

Date of Test: 4/2/02

ATD Serial No.: 034

Testing Program: Hybrid III Neck Flexion Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NF02A





Hybrid III Calibration Data Sheet

50TH Percentile Male

Neck Extension Test

ATD Serial No.: 034

Part Serial No.: N/A


Test I.D.: NE01C

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		°C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Velocity		m/s	5.95 to 6.19	6.02	Pass
Pendulum Deceleration	10 Msec.	G's	17.2 to 21.2	18.8	Pass
	20 Msec.	G's	14.0 to 19.0	17.3	Pass
	30 Msec.	G's	11.0 to 16.0	14.9	Pass
Peak Pendulum Decel. after 30 Msec.		G's	≤ 22.0	14.9	Pass
Deceleration Decay, Time to Cross 5 G's		Msec.	38.0 to 46.0	38.1	Pass
Maximum "D" Plane Rotation	Maximum	Degrees	81.0 to 106.0	88.5	Pass
	Time	Msec.	72.0 to 82.0	78.8	Pass
"D" Plane Rotation Decay, Time To Zero Crossing		Msec.	147.0 to 174.0	148.3	Pass
Moment About Occipital Condyle	Maximum	N•m	-52.9 to- 79.9	-74.2	Pass
	Time	Msec.	65.0 to 79.0	67.6	Pass
Negative Moment Decay, Time To Zero Crossing		Msec.	120.0 to 148.0	133.2	Pass
Overall Test Results					Pass

Laboratory Technician

April 2, 2002

Test Date




Curve Description:	Pendulum Deceleration		
Maximum Value:	18.8	at	10.2 Milliseconds
Minimum Value:	-1.7	at	43.6 Milliseconds
SAE Filter Class:	60		
Date of Test:	4/2/02		
ATD Serial No.:	034		

Testing Program:	Hybrid III Neck Extension Test (Male)
------------------	---------------------------------------

Test Information:	S/N of Part: N/A Test I.D.: NE01C
-------------------	-----------------------------------






Curve Description: Neck Force X

Maximum Value:	252.4	at	183.7	Milliseconds
Minimum Value:	-611.6	at	65.9	Milliseconds
SAE Filter Class:	60			
Date of Test:	4/2/02			
ATD Serial No.:	034			

Testing Program: Hybrid III Neck Extension Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NE01C






Curve Description: "D" Plane Rotation

Maximum Value:	88.5	at	78.8	Milliseconds
Minimum Value:	-35.9	at	195.5	Milliseconds
SAE Filter Class:	60			
Date of Test:	4/2/02			
ATD Serial No.:	034			

Testing Program: Hybrid III Neck Extension Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NE01C





Curve Description: Moment About Occipital Condyles
Maximum Value: 32.2 at 179.2 Milliseconds
Minimum Value: -74.2 at 67.6 Milliseconds
SAE Filter Class: 60
Date of Test: 4/2/02
ATD Serial No.: 034

Testing Program: Hybrid III Neck Extension Test (Male)
Test Information: S/N of Part: N/A Test I.D.: NE01C





Hybrid III Calibration Data Sheet

50TH Percentile Male

External Measurements

ATD Serial No.: 034

Part Serial No.: N/A

Test I.D.: N/A

External Measurement Data				
Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory temperature	°C	20.4 to 22.1	20.9	Pass
Laboratory relative humidity	%	10 to 70	35	Pass
A - Total sitting height	mm	879 to 889	880	Pass
B - Shoulder pivot height	mm	505 to 521	520	Pass
C - "H" point height	mm	84 to 89	85	Pass
D - "H" point from seat back	mm	135 to 140	135	Pass
E - Shoulder pivot from back	mm	84 to 94	85	Pass
F - Thigh clearance	mm	140 to 155	150	Pass
G - Elbow back to wrist pivot	mm	290 to 305	295	Pass
H - Skull cap to back line	mm	41 to 46	45	Pass
I - Shoulder to elbow length	mm	330 to 345	335	Pass
J - Elbow rest height	mm	190 to 211	200	Pass
K - Buttock to knee length	mm	579 to 604	585	Pass
L - Popliteal length	mm	429 to 455	445	Pass
M - Knee pivot height	mm	485 to 500	490	Pass
N - Buttock popliteal length	mm	452 to 477	460	Pass
O - Chest depth	mm	213 to 229	220	Pass
P - Foot length	mm	251 to 267	260	Pass
V - Shoulder breadth	mm	422 to 437	430	Pass
W - Foot breadth	mm	91 to 107	95	Pass
Y - Chest circumference	mm	970 to 1001	995	Pass
Z - Waist circumference	mm	836 to 866	850	Pass
AA - Location for chest circumference	mm	429 to 434	430	Pass
BB - Location for waist circumference	mm	226 to 231	230	Pass
Overall Test Results				Pass

Laboratory Technician

April 3, 2002

Test Date



Hybrid III Calibration Data Sheet

Hybrid III 50th Percentile Male

Knee Impact Test

ATD Serial No.: 035

Location: Left Knee

Test I.D.: LK01B

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Pendulum Velocity at T=0	m/sec	2.07 to 2.13	2.10	Pass
Peak Probe Force	N	4715 to 5782	5561	Pass
Overall Test Results				Pass

ATD Serial No.: 035

Location: Right Knee


Test I.D.: RK01B

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Pendulum Velocity at T=0	m/sec	2.07 to 2.13	2.09	Pass
Peak Probe Force	N	4715 to 5782	5624	Pass
Overall Test Results				Pass

Laboratory Technician

April 1, 2002


Test Date



Curve Description: Probe Force
Maximum Value: 5560.7 at 2.4 Milliseconds
Minimum Value: -22.1 at 8.0 Milliseconds
SAE Filter Class: 600
Date of Test: 4/1/02
ATD Serial No.: 035

Test Program: Hybrid III Knee Impact Test
Test Information: Location: Left Knee Test I.D.: LK01B





Curve Description: Probe Force

Maximum Value: 5623.6 at 2.5 Milliseconds

Minimum Value: -25.3 at 7.3 Milliseconds

SAE Filter Class: 600

Date of Test: 4/1/02

ATD Serial No.: 035

Test Program: Hybrid III Knee Impact Test

Test Information: Location: Right Knee Test I.D.: RK01B





Hybrid III Calibration Data Sheet

Hybrid III 50th Percentile Male

Knee Slider Test

ATD Serial No.: 035

Location: Left Knee

Test I.D.: KS003

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		°C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Velocity at T=0		m/sec	2.70 to 2.80	2.73	Pass
Impact Force at:	10 mm	kN	1.26 to 1.72	1.69	Pass
	18 mm	kN	2.27 to 3.096	2.98	Pass
Overall Test Results					Pass

ATD Serial No.: 035

Location: Right Knee


Test I.D.: KS004

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		°C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Velocity at T=0		m/sec	2.70 to 2.80	2.78	Pass
Impact Force at:	10 mm	kN	1.26 to 1.72	1.54	Pass
	18 mm	kN	2.27 to 3.096	2.94	Pass
Overall Test Results					Pass

Laboratory Technician

April 1, 2002

Test Date



Curve Description: Femur Force vs. Knee Displacement

Femur Force: 1686 at 10.0 mm

Femur Force: 2977 at 18.0 mm

SAE Filter Class: 600

Date of Test: 4/1/02

ATD Serial No.: 035


Test Program:

Hybrid III Knee Shear Test

Test Information:

Location: Left Knee Test I.D.: KS003





Curve Description: Femur Force vs. Knee Displacement

Femur Force: 1539 at 10.0 mm

Femur Force: 2937 at 18.0 mm

SAE Filter Class: 600

Date of Test: 4/1/02

ATD Serial No.: 035

Test Program: Hybrid III Knee Shear Test

Test Information: Location: Right Knee Test I.D.: KS004





Hybrid III Calibration Data Sheet

50TH Percentile Male

Head Drop Calibration

ATD Serial No.: 035

Part Serial No.: N/A


Test I.D.: HD01B

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Peak Resultant Acceleration	G's	225.0 to 275.0	244.7	Pass
Peak Lateral Acceleration	G's	≤15.0	1.4	Pass
Is Acceleration Unimodal?	Yes/No	Yes	Yes	Pass
Overall Test Results				Pass

Laboratory Technician

April 1, 2002

Test Date




Curve Description: Head Resultant Acceleration

Maximum Value:	<u>244.7</u>	at	<u>1.9</u>	Milliseconds
Minimum Value:	<u>0.3</u>	at	<u>-1.2</u>	Milliseconds
SAE Filter Class:	<u>1000</u>			
Date of Test:	<u>4/1/02</u>			
ATD Serial No.:	<u>035</u>			

Testing Program: Hybrid III Head Drop Calibration (Male)

Test Information: S/N of Part: N/A Test I.D.: HD01B





Curve Description: Head Acceleration Y Axis

Maximum Value: 1.4 at 1.7 Milliseconds

Minimum Value: -1.0 at -1.1 Milliseconds

SAE Filter Class: 1000

Date of Test: 4/1/02

ATD Serial No.: 035

Testing Program: Hybrid III Head Drop Calibration (Male)

Test Information: S/N of Part: N/A Test I.D.: HD01B





Hybrid III Calibration Data Sheet

50TH Percentile Male

Thorax Impact Test

ATD Serial No.: 035

Part Serial No.: N/A


Test I.D.: CH01B

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.2	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Velocity	m/s	6.58 to 6.82	6.74	Pass
Peak Probe Force	Newtons	5159 to 5893	5285	Pass
Peak Sternum Displacement	CM	6.35 to 7.26	7.03	Pass
Internal Hysteresis	%	69 to 85	73.3	Pass
Overall Test Results				Pass

Laboratory Technician

April 2, 2002

Test Date



Curve Description: Probe Force vs. Chest Displacement

Probe Force: 5285.3 Newtons

Chest Displ.: 7.03 Centimeters

SAE Filter Class: none

Date of Test: 4/2/02

ATD Serial No.: 035

Testing Program: Hybrid III Thorax Impact Test

Test Information: S/N of Part: N/A Test I.D.: CH01B





Hybrid III Calibration Data Sheet

50TH Percentile Male

Neck Flexion Test

ATD Serial No.: 035

Part Serial No.: N/A


Test I.D.: NF02B

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		°C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Velocity		m/s	6.89 to 7.13	7.04	Pass
Pendulum Deceleration	10 Msec.	G's	22.5 to 27.5	23.0	Pass
	20 Msec.	G's	17.6 to 22.6	20.0	Pass
	30 Msec.	G's	12.5 to 18.5	17.6	Pass
Peak Pendulum Decel. after 30 Msec.		G's	≤ 29.0	17.6	Pass
Deceleration Decay, Time to Cross 5 G's		Msec.	34.0 to 42.0	38.6	Pass
Maximum "D" Plane Rotation	Maximum	Degrees	64.0 to 78.0	67.2	Pass
	Time	Msec.	57.0 to 64.0	60.5	Pass
"D" Plane Rotation Decay, Time To Zero Crossing		Msec.	113.0 to 128.0	116.7	Pass
Moment About Occipital Condyle	Maximum	N•m	84.1 to 108.5	86.8	Pass
	Time	Msec.	47.0 to 58.0	52.5	Pass
Positive Moment Decay, Time To Zero Crossing		Msec.	97.0 to 107.0	101.0	Pass
Overall Test Results					Pass

Laboratory Technician

April 2, 2002

Test Date




Curve Description: Pendulum Deceleration

Maximum Value:	<u>23.0</u>	at	<u>9.5</u>	Milliseconds
Minimum Value:	<u>-2.9</u>	at	<u>86.6</u>	Milliseconds
SAE Filter Class:	<u>60</u>			
Date of Test:	<u>4/2/02</u>			
ATD Serial No.:	<u>035</u>			

Testing Program: Hybrid III Neck Flexion Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NF02B






Curve Description: Neck Force X

Maximum Value:	818.4	at	41.7	Milliseconds
Minimum Value:	-138.6	at	164.5	Milliseconds
SAE Filter Class:	60			
Date of Test:	4/2/02			
ATD Serial No.:	035			

Testing Program: Hybrid III Neck Flexion Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NF02B






Curve Description: "D" Plane Rotation

Maximum Value:	67.2	at	60.5	Milliseconds
Minimum Value:	-41.3	at	182.7	Milliseconds
SAE Filter Class:	60			
Date of Test:	4/2/02			
ATD Serial No.:	035			

Testing Program: Hybrid III Neck Flexion Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NF02B





Curve Description: Moment About Occipital Condyles

Maximum Value: 86.8 at 52.5 Milliseconds

Minimum Value: -23.4 at 13.8 Milliseconds

SAE Filter Class: 60

Date of Test: 4/2/02

ATD Serial No.: 035

Testing Program: Hybrid III Neck Flexion Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NF02B





Hybrid III Calibration Data Sheet

50TH Percentile Male

Neck Extension Test

ATD Serial No.: 035

Part Serial No.: N/A


Test I.D.: NE01D

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		°C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Velocity		m/s	5.95 to 6.19	6.10	Pass
Pendulum Deceleration	10 Msec.	G's	17.2 to 21.2	17.9	Pass
	20 Msec.	G's	14.0 to 19.0	15.3	Pass
	30 Msec.	G's	11.0 to 16.0	14.9	Pass
Peak Pendulum Decel. after 30 Msec.		G's	≤ 22.0	14.9	Pass
Deceleration Decay, Time to Cross 5 G's		Msec.	38.0 to 46.0	41.1	Pass
Maximum "D" Plane Rotation	Maximum	Degrees	81.0 to 106.0	88.2	Pass
	Time	Msec.	72.0 to 82.0	76.9	Pass
"D" Plane Rotation Decay, Time To Zero Crossing		Msec.	147.0 to 174.0	152.8	Pass
Moment About Occipital Condyle	Maximum	N•m	-52.9 to- 79.9	-71.4	Pass
	Time	Msec.	65.0 to 79.0	66.5	Pass
Negative Moment Decay, Time To Zero Crossing		Msec.	120.0 to 148.0	139.0	Pass
Overall Test Results					Pass

Laboratory Technician

April 2, 2002
Test Date

E-40




Curve Description:	Pendulum Deceleration		
Maximum Value:	18.0	at	8.9 Milliseconds
Minimum Value:	-1.9	at	75.5 Milliseconds
SAE Filter Class:	60		
Date of Test:	4/2/02		
ATD Serial No.:	035		

Testing Program:	Hybrid III Neck Extension Test (Male)
Test Information:	S/N of Part: N/A Test I.D.: NE01D



KAR22001-05

E-41



Curve Description: Neck Force X


Maximum Value:	256.2	at	186.9	Milliseconds
Minimum Value:	-577.0	at	70.8	Milliseconds
SAE Filter Class:	60			
Date of Test:	4/2/02			
ATD Serial No.:	035			

Testing Program: Hybrid III Neck Extension Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NE01D



KAR22001-05



Curve Description: "D" Plane Rotation


Maximum Value:	88.2	at	76.9	Milliseconds
Minimum Value:	-36.6	at	200.9	Milliseconds
SAE Filter Class:	60			
Date of Test:	4/2/02			
ATD Serial No.:	035			

Testing Program: Hybrid III Neck Extension Test (Male)

Test Information: S/N of Part: N/A Test I.D.: NE01D



E-43



Curve Description: Moment About Occipital Condyles
Maximum Value: 31.5 at 183.2 Milliseconds
Minimum Value: -71.4 at 66.5 Milliseconds
SAE Filter Class: 60
Date of Test: 4/2/02
ATD Serial No.: 035

Testing Program: Hybrid III Neck Extension Test (Male)
Test Information: S/N of Part: N/A Test I.D.: NE01D



KAR22001-05



Hybrid III Calibration Data Sheet

50TH Percentile Male

External Measurements

ATD Serial No.: 035

Part Serial No.: N/A

Test I.D.: N/A

External Measurement Data				
Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory temperature	°C	20.4 to 22.1	20.9	Pass
Laboratory relative humidity	%	10 to 70	35	Pass
A - Total sitting height	mm	879 to 889	885	Pass
B - Shoulder pivot height	mm	505 to 521	515	Pass
C - "H" point height	mm	84 to 89	85	Pass
D - "H" point from seat back	mm	135 to 140	135	Pass
E - Shoulder pivot from back	mm	84 to 94	90	Pass
F - Thigh clearance	mm	140 to 155	145	Pass
G - Elbow back to wrist pivot	mm	290 to 305	300	Pass
H - Skull cap to back line	mm	41 to 46	45	Pass
I - Shoulder to elbow length	mm	330 to 345	340	Pass
J - Elbow rest height	mm	190 to 211	195	Pass
K - Buttock to knee length	mm	579 to 604	600	Pass
L - Popliteal length	mm	429 to 455	440	Pass
M - Knee pivot height	mm	485 to 500	495	Pass
N - Buttock popliteal length	mm	452 to 477	470	Pass
O - Chest depth	mm	213 to 229	225	Pass
P - Foot length	mm	251 to 267	255	Pass
V - Shoulder breadth	mm	422 to 437	425	Pass
W - Foot breadth	mm	91 to 107	105	Pass
Y - Chest circumference	mm	970 to 1001	980	Pass
Z - Waist circumference	mm	836 to 866	860	Pass
AA - Location for chest circumference	mm	429 to 434	430	Pass
BB - Location for waist circumference	mm	226 to 231	230	Pass
Overall Test Results				Pass

Laboratory Technician


April 3, 2002

Test Date

APPENDIX G

NINE ACCELEROMETER HEAD ARRAY DATA

G-1



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Primary X	134	FIL	G's	31.6	176.0	-62.5	82.0	1000
Driver NAHA Yarm-X	138	FIL	G's	30.6	175.9	-60.6	73.3	1000
Driver NAHA Zarm-X	141	FIL	G's	45.6	176.1	-66.1	86.7	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502

KAR22001-05



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Primary Y	135	FIL	G's	3.9	156.4	-13.3	95.8	1000
Driver NAHA Xarm-Y	140	FIL	G's	8.8	55.0	-17.6	66.7	1000
Driver NAHA Zarm-Y	142	FIL	G's	15.8	155.7	-16.8	101.6	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Driver Head Primary Z	136	FIL	G's	26.5	49.2	-7.3	110.6	1000
Driver NAHA Xarm-Z	139	FIL	G's	32.4	53.6	-10.3	94.3	1000
Driver NAHA Yarm-Z	137	FIL	G's	28.0	49.2	-6.3	109.3	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Primary X	143	FIL	G's	21.7	204.4	-48.3	79.6	1000
Passenger NAHA Yarm-X	147	FIL	G's	19.7	211.3	-42.8	66.9	1000
Passenger NAHA Zarm-X	150	FIL	G's	39.6	204.5	-47.3	79.5	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Primary Y	144	FIL	G's	11.1	206.2	-21.3	32.8	1000
Passenger NAHA Xarm-Y	149	FIL	G's	5.0	207.6	-19.4	32.9	1000
Passenger NAHA Zarm-Y	151	FIL	G's	23.6	205.7	-17.8	95.8	1000




Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502



Curve Description	CURNO	Type	Units	Max	Time	Min	Time	SAE Class
Passenger Head Primary Z	145	FIL	G's	30.6	75.5	-3.3	133.6	1000
Passenger NAHA Xarm-Z	148	FIL	G's	37.3	63.3	-11.6	134.6	1000
Passenger NAHA Yarm-Z	146	FIL	G's	28.3	65.1	-3.6	134.1	1000



Test Vehicle: 2002 Daewoo Nubira SE 4 Door Sedan

Test Date: 4/23/02

Test Program: 2002 NHTSA 35mph NCAP

NHTSA No.: M20502