

REPORT NUMBER: TWG-CAL06-02


NEW CAR ASSESSMENT PROGRAM (NCAP)
SIDE AIRBAG OUT-OF-POSITION INJURY TESTING

2006 TOYOTA 4RUNNER
FOUR DOOR MULTIPURPOSE VEHICLE

NHTSA NUMBER: M65104TWG2

CALSPAN CORPORATION TEST NUMBER: 8642-TWG-19

CALSPAN CORPORATION
TRANSPORTATION SCIENCES CENTER
P.O. BOX 400
BUFFALO, NEW YORK 14225



June 7, 2006

FINAL REPORT

U. S. DEPARTMENT OF TRANSPORTATION
National Highway Traffic Safety Administration
Rulemaking
Office of Crashworthiness Standards
Mail Code: NVS-111
400 Seventh Street, SW, Room No. 5313
Washington, DC 20590

This Final Test Report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, under Contract No. DTNH22-03-D-22005. This document is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The United States Government assumes no liability for its contents or use thereof.

Prepared By:

Patrick G. MacDiarmid, Jr., Project Engineer

Approved By:

David J. Travale, Program Manager
Transportation Sciences Center

Approval Date:

FINAL REPORT ACCEPTANCE BY:

Accepted By:

Acceptance Date:

TECHNICAL REPORT STANDARD TITLE PAGE							
1. Report No. TWG-CAL06-02		2. Government Accession No.		3. Recipient's Catalog No.			
4. Title and Subtitle Final Report NHTSA No.: M65104TWG2				5. Report Date June 7, 2006			
				6. Performing Organization Code CAL			
7. Author(s) Patrick G. MacDiarmid, Jr., Project Engineer David J. Travale, Program Manager				8. Performing Organization Report No. 8642-TWG-19			
9. Performing Organization Name and Address Calspan Corporation Transportation Sciences Center P.O. Box 400 Buffalo, New York 14225				10. Work Unit No.			
				11. Contract or Grant No. DTNH22-03-D-22005			
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Crashworthiness Standards Mail Code: NVS-111 400 Seventh SW, Room 5313 Washington, D.C. 20590				13. Type of Report and Period Covered Final Report, June 8, 2006			
				14. Sponsoring Agency Code NVS-111			
15. Supplementary Notes							
16. Abstract This side impact out-of-position test was performed in conjunction with a New Car Assessment Program (NCAP). This test was conducted at the Calspan Corporation Crash Test Facility in Buffalo, New York, on June 7, 2006.							
Injury Summary							
HIC15	HIC36	Clip (g's)	Chest Displacement (mm)	NIJ NTF	NIJ NTE	NIJ NCF	NIJ NCE
22.8	23.5	32.8	-3.0	0.4	0.76	0.37	0.64
17. Key Words New Car Assessment Program (NCAP) Side Airbag Out-of-Position				18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Administration Technical Reference Division Room 5111 (NAD-52) 400 Seventh St., S.W. Washington, D.C. 20590 Telephone No. (202) 366-4946 ATTN: Robert Hornicle			
19. Security Classification of Report UNCLASSIFIED		20. Security Classification of Page UNCLASSIFIED		21. No. of Pages 33		22. Price	

TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1	PURPOSE AND SUMMARY OF TEST	1-1
2	DATA SHEETS	2-1
	Data Sheet 1 – Test Summary	2-1
	Data Sheet 2 – Vehicle Parameter Data	2-2
	Data Sheet 3 – Dummy Positioning in Vehicle	2-3
	Data Sheet 4 – Dummy Injury Criteria Values	2-4
A	PHOTOGRAPHS	A-1
B	CHILD DUMMY RESPONSE DATA TRACES	B-1
C	TEST EQUIPMENT LIST AND CALIBRATION INFORMATION	C-1

TABLE OF PHOTOGRAPHS

<u>Figure</u>	<u>Photograph Title</u>	<u>Page</u>
Figure A- 1	PRE-TEST VEHICLE LEFT SIDE VIEW	A- 3
Figure A- 2	POST-TEST VEHICLE LEFT SIDE VIEW	A- 3
Figure A- 3	VEHICLE CERTIFICATION PLACARD	A- 4
Figure A- 4	VEHICLE TIRE PLACARD	A- 4
Figure A- 5	PRE-TEST DUMMY FRONTAL VIEW	A- 5
Figure A- 6	POST-TEST DUMMY FRONTAL VIEW	A- 5
Figure A- 7	PRE-TEST LEFT SIDE OF DUMMY VIEW	A- 6
Figure A- 8	POST-TEST LEFT SIDE OF DUMMY VIEW	A- 6
Figure A- 9	PRE-TEST RIGHT SIDE OF DUMMY VIEW	A- 7
Figure A- 10	POST-TEST RIGHT SIDE OF DUMMY VIEW	A- 7

TABLE OF DATA PLOTS

PLOT	PLOT NAME[UNITS, CHANNEL FILTER CLASS]	PAGE
1	P2 Head x [g, CFC_1000]	B-3
2	P2 Head y [g, CFC_1000]	B-3
3	P2 Head z [g, CFC_1000]	B-3
4	P2 Head Resultant [g, CFC_1000]	B-3
5	P2 Upper Neck Fx [N, CFC_1000]	B-4
6	P2 Upper Neck Fy [N, CFC_1000]	B-4
7	P2 Upper Neck Fz [N, CFC_1000]	B-4
8	P2 Upper Neck F Resultant [N, CFC_1000]	B-4
9	P2 Upper Neck Mx [N-m, CFC_600]	B-5
10	P2 Upper Neck My [N-m, CFC_600]	B-5
11	P2 Upper Neck Mz [N-m, CFC_600]	B-5
12	P2 Upper Neck M Resultant [N-m, CFC_600]	B-5
13	P2 Lower Neck Fx [N, CFC_1000]	B-6
14	P2 Lower Neck Fy [N, CFC_1000]	B-6
15	P2 Lower Neck Fz [N, CFC_1000]	B-6
16	P2 Lower Neck F Resultant [N, CFC_1000]	B-6
17	P2 Lower Neck Mx [N-m, CFC_600]	B-7
18	P2 Lower Neck My [N-m, CFC_600]	B-7
19	P2 Lower Neck Mz [N-m, CFC_600]	B-7
20	P2 Lower Neck M Resultant [N-m, CFC_600]	B-7
21	P2 Upper Sternum Ax [g, CFC_180]	B-8
22	P2 Lower Sternum Ax [g, CFC_180]	B-8
23	P2 Chest x [g, CFC_180]	B-9
24	P2 Chest y [g, CFC_180]	B-9
25	P2 Chest z [g, CFC_180]	B-9
26	P2 Chest Resultant [g, CFC_180]	B-9
27	P2 Chest Compression [mm, CFC_600]	B-10
28	P2 Pelvic x [g, CFC_1000]	B-11
29	P2 Pelvic y [g, CFC_1000]	B-11
30	P2 Pelvic z [g, CFC_1000]	B-11
31	P2 Pelvic Resultant [g, CFC_1000]	B-11
32	P2 Left Femur Fz [N, CFC_600]	B-12
33	P2 Right Femur Fz [N, CFC_600]	B-12

SECTION 1

PURPOSE AND SUMMARY OF TEST M65104TWG2

1.1 PURPOSE

The purpose of this test was to obtain data in a static out-of-position side impact. These data constitute part of the general consumer information collected by the New Car Assessment Program (NCAP) sponsored by the National Highway Traffic Safety Administration (NHTSA) under contract No. DTNH22-03-D-22005.

1.2 SUMMARY

The effects of both a seat-mounted side airbag and a curtain airbag deployment in a 2006 Toyota 4Runner with an out-of-position six-year-old child were evaluated. The test was performed by Calspan Corporation on June 7, 2006. Pre-and post-test photographs of the vehicle and dummy can be found in Appendix A.

One high-speed digital camera was used to document the side airbag deployment event. The camera was placed in perpendicular the right-front seat centerline as to capture the deployment event. The recorded image rate is 1000 frames per second.

One part 572, Hybrid III six-year-old child anthropomorphic test device (ATD), was placed in the right front seat situated in the forward facing position according to dummy placement instructions specified in the Recommended Procedures for Evaluating Occupant Injury Risk from Deploying Side Airbags as prepared by the Side Airbag Out-of-Position Injury Technical Working Group (TWG).

The child dummy was instrumented with head, chest, upper and lower sternum and pelvic triaxial accelerometers. In addition upper and lower six axial neck force and moment load cell sensors and left and right femur load cell sensors were utilized.

Twenty-six channels of data were recorded using an on-board data acquisition system. Appendix A contains photographs. Appendix B contains dummy response data traces. Appendix C contains the Instrumentation Data Channel assignments.

The Hybrid III six-year-old child dummy's visible contact points were as follows: The seat airbag to the right scapula and right side of the posterior thorax and pelvis and the curtain airbag to the top and the back of the head.

The six-year old child dummy was placed on the outboard edge of foam block, aligning the upper spine with the deployment trajectory of the airbag. The dummy's head was placed in between the seat bolster and pillar trim to minimize the fore-aft clearance between the neck and the seatback. The head remained in its neutral orientation. The legs were aligned such that they crossed the heel placement points but the feet did overhang the seat cushion. The dummy was then positioned so the dummy's neck/torso junction was aligned vertically with the top edge of the airbag module. While maintaining the neck/torso top of the airbag module alignment, the vehicle door was closed and the pelvis was moved outboard until it made contact the door trim/armrest. The outboard forearm was placed on the armrest. The inboard arm was positioned such that the upper arm contacted the seat back and the fingertips contacted the booster seat. The dummy's arms were then bent at the elbow until the fingers contacted the booster seat. This orientation complies with section 3.3.3.5 of the TWG Recommended Procedures for Evaluating Occupant Injury Risk from Deploying Side Airbags as defined by Lund, et al and the Technical Working Group First Revision dated July, 2003.

SECTION 2

DATA SHEET NO. 1

TEST SUMMARY

TEST CONFIGURATION INFORMATION:

	TEST DATA	DESCRIPTION
Seating Position:	P2	Right Front Seating Position
Test:	3.3.3.5*	Forward facing Hybrid-III six-year-old child dummy on booster block
Airbag:	Seat; Side Rail	Bolster mounted thorax side airbag and side curtain airbag.
Booster Block	300mm x 450 mm x 75 mm	Block consisted of HD36 foam with a density of 44.8 g/L
ATD Type/Serial No.:	P572N/186	Hybrid III six-year-old child dummy

*- Procedure as defined by Lund, et al and the Technical Working Group dated July, 2003

<u>Number of Data Channels</u>	26	
<u>Number of Cameras:</u>	0	<u>Real Time</u>
	1	<u>High Speed Digital</u>
	0	<u>High Speed Film</u>

VISIBLE DUMMY CONTACT POINTS

Head Contact:	The back (occipital) and the top (parietal) of the head by the side curtain.
Upper Torso Contact:	Side airbag to the right scapula and right side of the posterior thorax
Lower Torso Contact:	Side airbag to the right side of the pelvis (ilium)
Left Knee Contact:	None
Right Knee Contact:	None

DATA SHEET 2

VEHICLE PARAMETER DATA

TEST VEHICLE INFORMATION:

Year/Make/Model/Body Style: 2006 Toyota 4Runner MPV‡

NHTSA No. : M65104 ; VIN: JTEBU14R368054023 ; Color: Grey

Engine Data: 6 cylinders; - CID; 4.0 Liters; - cc

Placement: x Longitudinal or In-Line; - Transverse or Lateral

Transmission Data: 5 speeds; - Manual; x Automatic; x Overdrive

Final Drive: - Rear Wheel Drive; - Front Wheel Drive; x Four Wheel Drive

AUTOMATIC DOOR LOCKS:

Is test vehicle equipped with Automatic Door Locks (ADLs)? x Yes; - No;

Does vehicle owner's manual describe how to deactivate ADLs? x Yes; - No; - N/A

DEALER AND DELIVERY INFORMATION:

Date Received: 1/30/06 ; Odometer Reading 227 km

Selling Dealer: Superior Toyota

Dealer Address: 5615 Peach St Erie, Pa 16509

TEST VEHICLE OPTIONS:

x AC; x Power Steering; x Power Brakes; x Power Locks; - Power Seats

x ABS; x Tilt Wheel; x Stability Control x Traction Control - Anti-Theft

SAFETY BELT FEATURES:

Driver: x Pretensioner (Shoulder); x Load Limiter; x Adjustable Anchorage

Passenger: x Pretensioner (Shoulder); x Load Limiter; x Adjustable Anchorage

AIRBAG FEATURES:

Position	Frontal	Knee Bolster	Side Torso	Side Head/Torso Combination	Side Curtain
Driver:	Yes	N/A	Yes	N/A	Yes
Passenger:	Yes	N/A	Yes	N/A	Yes
Rear Passenger:	No	N/A	No	N/A	Yes

DATA FROM VEHICLE'S CERTIFICATION LABEL:

Vehicle Manufactured by: Toyota Motor Corporation

Date of Manufacture 09/05

GVWR: 2535 kg; GAWR: 1160 kg FRONT; 1390 kg REAR

VEHICLE CAPACITY DATA:

Type of Front Seats: - Bench; x Bucket; - Split Bench

Number of Occupants: 2 Front; 3 Rear; 5 Total

Vehicle Capacity Weight (VCW) = 431 kg

No. of Occupants x 68.04 kg = 340.2 kg

Rated Cargo/Luggage Weight (RCLW) = 90.8 kg

‡ This vehicle had previously been tested in an NCAP frontal impact on February 14, 2006.

DATA SHEET NO. 3

CHILD DUMMY POSITIONING IN VEHICLE

NHTSA No. M65104TWG2

Measurement		Value
Total Fore/Aft Travel (mm)		240
Test Distance Rearward of Full-Forward (mm)		150
Total Fore/Aft Travel (Detents)		17
Placed in Position #		10
Seat Back Angle	SA (°)	23
Airbag Module Width	AMW (mm)	100
Airbag Width	ABW (mm)	450
Airbag Module Length	AML (mm)	320
Airbag Length	ABL (mm)	430
Top of Airbag Module to Head/Neck Junction	AN (mm)	85
Head CG to Door Panel/Window	HD (mm)	177
Head to Seat Back Centerline	HSC (mm)	168
Head to B-Pillar (cg)	HB (mm)	135
Head to Roof, Z (top of the head)	HZ (mm)	193
Head to Header	HHH (mm)	668
Chest to Dash	CD (mm)	592
Chest to Seatback	CS (mm)	-188
Right Arm to Seat Back Centerline	RACL (mm)	307
Right Arm to Seat Back Centerline	RACL (°)	60
Left Arm to Seat Back Centerline	LACL (mm)	0
Left Arm to Seat Back Centerline	LACL (°)	80
Right Arm to Door Panel	RA (mm)	0
Left Arm to Door Panel	LA (mm)	330
Knee to Knee	KK (mm)	105
Toe to Toe	TT (mm)	135
Right Knee to Seat Cushion Centerline	KSCR (mm)	80
Left Knee to Seat Cushion Centerline	KSCL (mm)	0
Right Toe to Seat Cushion Centerline	TSCR (mm)	0
Left Toe to Seat Cushion Centerline	TSCL (mm)	135
Nose to Dash	ND (mm)	654
Nose to Seatback	NS (mm)	238
Nose to Header	NR (mm)	277
Foam Block Depth	(mm)	300
Foam Block Width	(mm)	450
Foam Block Thickness	(mm)	75
HD36 foam density	(g/L)	44.8

DATA SHEET 4

CHILD DUMMY INJURY CRITERIA VALUES

NHTSA No. M65104TWG2

		MAXIMUM VALUE			
		Position #2			
DESCRIPTION	Unit	Maximum	Time (ms)	Minimum	Time (ms)
Head X	g	37.4	13.6	-20.4	20.7
Head Y	g	4.2	14.4	-32.9	19.3
Head Z	g	56.9	19.3	-24.6	13.6
Head Resultant	g	65.9	19.3	0.0	-10.3
Upper Neck Fx	N	449.6	14.7	-126.1	31.6
Upper Neck Fy	N	65.1	19.9	-251.8	20.6
Upper Neck Fz	N	546.7	18.8	-404.4	20.6
Upper Neck F Resultant	N	660.3	17.8	0.1	-12.8
Upper Neck Mx	N-m	6.7	15.5	-10.3	26.7
Upper Neck My	N-m	38.6	14.4	-27.9	31.8
Upper Neck Mz	N-m	1.7	87.0	-6.2	34.8
Upper Neck M Resultant	N-m	39.1	14.4	0.0	-7.7
Lower Neck Fx	N	219.2	17.3	-495.1	9.0
Lower Neck Fy	N	126.1	22.7	-246.5	7.1
Lower Neck Fz	N	364.6	17.7	-109.4	43.2
Lower Neck F Resultant	N	557.4	7.9	0.1	-5.2
Lower Neck Mx	N-m	8.4	90.4	-13.9	17.4
Lower Neck My	N-m	11.6	162.7	-58.8	17.5
Lower Neck Mz	N-m	4.9	7.7	-13.5	14.8
Lower Neck M Resultant	N-m	61.4	17.5	0.0	-6.5
Upper Sternum Ax	g	81.5	10.2	-30.7	17.9
Lower Sternum Ax	g	60.5	10.9	-11.9	29.1
Chest X	g	62.5	7.3	-1.5	22.4
Chest Y	g	1.7	7.0	-17.5	9.1
Chest Z	g	4.2	23.7	-2.4	9.4
Chest Resultant	g	62.6	7.3	0.0	-18.4
Chest Displacement	mm	0.3	67.0	-3.0	11.7
Pelvic X	g	3.0	15.6	-8.1	14.3
Pelvic Y	g	2.4	192.2	-5.9	199.9
Pelvic Z	g	3.8	20.9	-8.1	9.9
Pelvic Resultant	g	9.9	14.3	0.0	-9.5
Left Femur	N	51.5	186.7	-104.4	14.7
Right Femur	N	82.3	153.3	-45.0	12.9

DATA SHEET 4

CHILD DUMMY INJURY CRITERIA VALUES (CONTINUED)

NHTSA No. M65104TWG2

	HEAD INJURY CRITERIA (HIC)							
	HIC15				HIC36			
	HIC	t ₁ (msec)	t ₂ (msec)	Average Acceleration t ₁ to t ₂	HIC	t ₁ (msec)	t ₂ (msec)	Average Acceleration t ₁ to t ₂
Position #2 – Right Front	22.8	11.1	20.9	22.2	23.5	9.4	45.4	13.4

	CLIP SUMMARY*			
	CLIP (g's)	t ₁ (msec)	t ₂ (msec)	CSI
Position #2 – Right Front	32.8	6.4	9.4	68.1

* The maximum chest resultant acceleration is defined as the maximum acceleration which exceeds 0.003 seconds in duration.

Position 2 Neck Injury Summary (HIII 6 year old – Out of Position)

Nij V10	Nij	Time (ms)	Z Force (N)	X Force (N)	Y Moment (N-m)
Ntf	0.40	17.2	467.1	403.7	21.7
Nte	0.76	31.8	174.6	-123.6	-25.7
Ncf	0.37	12.9	-226.7	334.6	27.0
Nce	0.64	34.7	-70.7	-46.4	-22.8

Peak Tension (CFC1000) 546.7 N

Peak Compression (CFC1000) 404.4 N

Critical Values

Nij Intercepts			Peak Limits	
Tension (CVt)	2880 N	Extension (mCVe)	37 N-m	Tension 1890 N
Compression (CVc)	2880 N	Flexion (mCVf)	93 N-m	Compression -1820 N

Condyle Offset -0.01778

APPENDIX A

PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

<u>Figure</u>	<u>Photograph Title</u>	<u>Page</u>
Figure A- 1	PRE-TEST VEHICLE LEFT SIDE VIEW	A- 3
Figure A- 2	POST-TEST VEHICLE LEFT SIDE VIEW	A- 3
Figure A- 3	VEHICLE CERTIFICATION PLACARD	A- 4
Figure A- 4	VEHICLE TIRE PLACARD	A- 4
Figure A- 5	PRE-TEST DUMMY FRONTAL VIEW	A- 5
Figure A- 6	POST-TEST DUMMY FRONTAL VIEW	A- 5
Figure A- 7	PRE-TEST LEFT SIDE OF DUMMY VIEW	A- 6
Figure A- 8	POST-TEST LEFT SIDE OF DUMMY VIEW	A- 6
Figure A- 9	PRE-TEST RIGHT SIDE OF DUMMY VIEW	A- 7
Figure A- 10	POST-TEST RIGHT SIDE OF DUMMY VIEW	A- 7



Figure A-1: Pre-Test Vehicle Left Side View



Figure A-2: Post-Test Vehicle Left Side View



Figure A-3: Vehicle Certification Placard



Figure A-4: Vehicle Tire Placard



Figure A-5: Pre-Test Dummy Frontal View



Figure A-6: Post-Test Dummy Frontal View



Figure A-7: Pre-Test Left Side of Dummy View



Figure A-8: Post-Test Left Side of Dummy View




Figure A-9: Pre-Test Right Side of Dummy View



Figure A-10: Post-Test Right Side of Dummy View

APPENDIX B





CHILD DUMMY RESPONSE DATA TRACES

TABLE OF DATA PLOTS

PLOT	PLOT NAME[UNITS, CHANNEL FILTER CLASS]	PAGE
1	P2 Head x [g, CFC_1000]	B-3
2	P2 Head y [g, CFC_1000]	B-3
3	P2 Head z [g, CFC_1000]	B-3
4	P2 Head Resultant [g, CFC_1000]	B-3
5	P2 Upper Neck Fx [N, CFC_1000]	B-4
6	P2 Upper Neck Fy [N, CFC_1000]	B-4
7	P2 Upper Neck Fz [N, CFC_1000]	B-4
8	P2 Upper Neck F Resultant [N, CFC_1000]	B-4
9	P2 Upper Neck Mx [N-m, CFC_600]	B-5
10	P2 Upper Neck My [N-m, CFC_600]	B-5
11	P2 Upper Neck Mz [N-m, CFC_600]	B-5
12	P2 Upper Neck M Resultant [N-m, CFC_600]	B-5
13	P2 Lower Neck Fx [N, CFC_1000]	B-6
14	P2 Lower Neck Fy [N, CFC_1000]	B-6
15	P2 Lower Neck Fz [N, CFC_1000]	B-6
16	P2 Lower Neck F Resultant [N, CFC_1000]	B-6
17	P2 Lower Neck Mx [N-m, CFC_600]	B-7
18	P2 Lower Neck My [N-m, CFC_600]	B-7
19	P2 Lower Neck Mz [N-m, CFC_600]	B-7
20	P2 Lower Neck M Resultant [N-m, CFC_600]	B-7
21	P2 Upper Sternum Ax [g, CFC_180]	B-8
22	P2 Lower Sternum Ax [g, CFC_180]	B-8
23	P2 Chest x [g, CFC_180]	B-9
24	P2 Chest y [g, CFC_180]	B-9
25	P2 Chest z [g, CFC_180]	B-9
26	P2 Chest Resultant [g, CFC_180]	B-9
27	P2 Chest Compression [mm, CFC_600]	B-10
28	P2 Pelvic x [g, CFC_1000]	B-11
29	P2 Pelvic y [g, CFC_1000]	B-11
30	P2 Pelvic z [g, CFC_1000]	B-11
31	P2 Pelvic Resultant [g, CFC_1000]	B-11
32	P2 Left Femur Fz [N, CFC_600]	B-12
33	P2 Right Femur Fz [N, CFC_600]	B-12





2006 TWG Test 2 2006 Toyota 4Runner

M65104TWG2 - June 07, 2006







2006 TWG Test 2 2006 Toyota 4Runner





M65104TWG2 - June 07, 2006







2006 TWG Test 2 2006 Toyota 4Runner M65104TWG2 - June 07, 2006




2006 TWG Test 2 2006 Toyota 4Runner **M65104TWG2 - June 07, 2006**







2006 TWG Test 2 2006 Toyota 4Runner M65104TWG2 - June 07, 2006




2006 TWG Test 2 2006 Toyota 4Runner
M65104TWG2 - June 07, 2006



2006 TWG Test 2 2006 Toyota 4Runner M65104TWG2 - June 07, 2006







2006 TWG Test 2 2006 Toyota 4Runner
M65104TWG2 - June 07, 2006





2006 TWG Test 2 2006 Toyota 4Runner

M65104TWG2 - June 07, 2006



2006 TWG Test 2 2006 Toyota 4Runner
M65104TWG2 - June 07, 2006



APPENDIX C

TEST EQUIPMENT LIST AND CALIBRATION INFORMATION

TEST EQUIPMENT LIST AND CALIBRATION INFORMATION

P572N INSTRUMENTATION

	POSITION #2 (RIGHT FRONT) SERIAL NO.: 186		
	SERIAL NUMBER	MANUFACTURER	CALIBRATION DATE
HEAD AX	AC-04J04I20-Z23	ENTRAN	11-Apr-06
HEAD AY	AC-04J04I01-R12	ENTRAN	14-Apr-06
HEAD AZ	AC-02I02I16-A08	ENTRAN	14-Apr-06
UPPER NECK FX	LC-175Fx	DENTON	03-May-06
UPPER NECK FY	LC-175Fy	DENTON	03-May-06
UPPER NECK FZ	LC-175Fz	DENTON	03-May-06
UPPER NECK MX	LC-175Mx	DENTON	03-May-06
UPPER NECK MY	LC-175My	DENTON	03-May-06
UPPER NECK MZ	LC-175Mz	DENTON	03-May-06
LOWER NECK FX	LC-138Fx	DENTON	18-May-06
LOWER NECK FY	LC-138Fy	DENTON	18-May-06
LOWER NECK FZ	LC-138Fz	DENTON	18-May-06
LOWER NECK MX	LC-138Mx	DENTON	18-May-06
LOWER NECK MY	LC-138My	DENTON	18-May-06
LOWER NECK MZ	LC-138Mz	DENTON	18-May-06
UPPER STERNUM AX	AC-02A16-A26	ENTRAN	14-Apr-06
LOWER STERNUM AX	AC-99H12-F24	ENTRAN	11-Apr-06
CHEST AX	AC-04J04I08-F25	ENTRAN	11-Apr-06
CHEST AY	AC-03E03E20-N05	ENTRAN	11-Apr-06
CHEST AZ	AC-03E03D30-N08	ENTRAN	10-Apr-06
CHEST DISPLACEMENT X	DS-186	SERVO	10-May-06
PELVIS AX	AC-04J04I01-R06	ENTRAN	22-May-06
PELVIS AY	AC-03E03D30-N03	ENTRAN	14-Apr-06
PELVIS AZ	AC-03D03D16-F04	ENTRAN	10-Apr-06
LEFT FEMUR FZ	LC-247	DENTON	18-May-06
RIGHT FEMUR FZ	LC-248	DENTON	16-May-06