


REPORT NO. 208-MGA-2006-DC014

DUMMY PERFORMANCE CALIBRATIONS
FMVSS 208

**Hyundai Motor Company
2006 HMC Tucson MPV
NHTSA No.: C60510**

**PREPARED BY:
MGA RESEARCH CORPORATION
5000 WARREN ROAD
BURLINGTON, WI 53105**



Test Date: June 9, 2006 - March 26, 2007

Report Date: May 4, 2007

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
OFFICE OF ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
MAIL CODE: NVS-220
400 SEVENTH STREET, S.W., ROOM 6115
WASHINGTON, D.C. 20590**

TABLE OF CONTENTS

			<u>Page No.</u>
DUMMY S/N:	506	PRE-TEST CERTIFICATION DATA	1-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	506	POST-TEST CERTIFICATION DATA	2-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	516	PRE-TEST CERTIFICATION DATA	3-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	516	POST-TEST CERTIFICATION DATA	4-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	125	PRE-TEST CERTIFICATION DATA	5-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	125	POST-TEST CERTIFICATION DATA	6-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	505	PRE-TEST CERTIFICATION DATA	7-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	505	POST-TEST CERTIFICATION DATA	8-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	505	PRE-TEST CERTIFICATION DATA	9-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	505	POST-TEST CERTIFICATION DATA	10-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	505	PRE-TEST CERTIFICATION DATA	11-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	505	POST-TEST CERTIFICATION DATA	12-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	507	PRE-TEST CERTIFICATION DATA	13-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	507	POST-TEST CERTIFICATION DATA	14-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	511	PRE-TEST CERTIFICATION DATA	15-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	511	POST-TEST CERTIFICATION DATA	16-1
		PASSED ALL CALIBRATION CHECKS	

TABLE OF CONTENTS

			<u>Page No.</u>
DUMMY S/N:	510	PRE-TEST CERTIFICATION DATA	17-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	510	POST-TEST CERTIFICATION DATA	18-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	124	PRE-TEST CERTIFICATION DATA	19-1
		PASSED ALL CALIBRATION CHECKS	
DUMMY S/N:	124	POST-TEST CERTIFICATION DATA	20-1
		PASSED ALL CALIBRATION CHECKS	

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #506, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	785.6
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	453.1
C	H-POINT HEIGHT	Reference	81.3-86.3	85.3
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	146.9
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	75.4
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	127.8
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249.3
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.7
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	279.8
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	191.3
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	531.2
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	370.1
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	408.4
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	425.9

HYBRID III 5 th SN #506, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	183.1
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.1
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	473.8
S	HEAD BREADTH	The widest part of the head	137.1-147.3	142.3
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	178.9
U	HIP BREADTH	The widest part of the hip	299.7-314.9	301.7
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	361.2
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	84.1
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	540.1
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	863.9
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	770.5
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 506 Test Date 3/15/07

Technician Jessica Gall

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.3</u> |
| Record the minimum temperature | <u>20.9</u> |
| Record the maximum humidity | <u>25%</u> |
| Record the minimum humidity | <u>22%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	256
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	3

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.

Jessica Hall
Signature

3/15/07
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test ID: D07701

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	24	Pass
Peak Resultant Acceleration	G's	250 to 300	256	Pass
Peak Lateral Acceleration	G's	+/- 15	3.3	Pass
Unimodal	NA	Yes	Yes	Pass
Oscillations	NA	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician

3/15/07
Test Date



Approved By




Test Desc: Head Drop
Componet ID: D07701

Test Date: 3/15/07
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (g's) vs TIME (s)



HEAD Y (G'S) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 506 Test Date 3/16/07

Technician Joe Fleck

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

☒ N/A, ONLY one flexion test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.9

Record the minimum temperature 20.7

Record the maximum humidity 31%

Record the minimum humidity 29%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.06 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.3 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.2 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	5.9 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>81</u> Nm @ <u>78</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	87 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.

Joe Fleck
Signature

3/16/07
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07702

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.7	Pass
Laboratory Relative Humidity		%	10 to 70	29	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.06	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.3	Pass
	20 msec	m/sec	4.0 to 5.0	4.2	Pass
	30 msec	m/sec	5.8 to 7.0	5.9	Pass
D Plane Rotation	Max	deg	77 to 91	78	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	81	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	87	Pass
Overall Results					Pass



Laboratory Technician

3/16/07

Test Date




Approved By




Test Desc: Neck Flexion
Componet ID: D07702

Test Date: 3/16/07
Velocity: 23.148 ft/s, 7.06 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D07702

Test Date: 3/16/07
Velocity: 23.148 ft/s, 7.06 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 506

Test Date 3/16/07

Technician Jessica Gall

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.9

Record the minimum temperature 20.7

Record the maximum humidity 31%

Record the minimum humidity 29%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.05 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.7 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.3 m/s
Plane D Rotation		Peak moment* -65 Nm $\leq$ moment $\leq$ -53 Nm during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	-54 Nm @ 112 degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	104 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.

Jessica Hall
Signature

3/16/07
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07703

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.9	Pass
Laboratory Relative Humidity		%	10 to 70	31	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.05	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.7	Pass
	30 msec	m/sec	4.6 to 5.6	5.3	Pass
D Plane Rotation	Max	deg	99 to 114	112	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-54	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	104	Pass
Overall Results					Pass


Laboratory Technician



3/16/07
Test Date


Approved By



Test Desc: Neck Extension
Componet ID: D07703


Test Date: 3/16/07
Velocity: 19.84 ft/s, 6.05 m/s





Test Desc: Neck Extension
Componet ID: D07703

Test Date: 3/16/07
Velocity: 19.84 ft/s, 6.05 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 506

Test Date 3/15/07

Technician Jessica Gall

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 25%

Record the minimum humidity 22%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.68 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	50 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	3920 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	3990 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	70%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.

Jessica Hall
Signature

3/15/07
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07704

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.1	Pass
Relative Humidity	%	10 to 70	25	Pass
Probe Speed	m/s	6.59 to 6.83	6.68	Pass
Peak Deflection	mm	50 to 58	50	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	3.9	Pass
Internal Hysteresis	%	69 to 85	70	Pass
Peak Force 18 mm - 50 mm	N	≤ 4,600 N	3,990	Pass
Overall Test Results				Pass


Laboratory Technician


3/15/07
Test Date


Approved By



Test Desc: Thorax Impact
Componet ID: D07704

Test Date: 3/15/07
Velocity: 21.93 ft/s, 6.68 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 506 Test Date 3/15/07

Technician Tim Bratz

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
☒ N/A, ONLY one thorax impact test performed
- ☒ 2. The test fixture conforms to the specifications in Figure 13B.
- ☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
☐ with legs below the femurs.
☒ without legs below the femurs.
- ☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.3</u> |
| Record the minimum temperature | <u>20.9</u> |
| Record the maximum humidity | <u>25%</u> |
| Record the minimum humidity | <u>22%</u> |
- ☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
- ☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
- ☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
- ☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))
- ☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- ☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- ☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
- | | |
|---|------------|
| Record reference plane angle (max. allowed 20°) | <u>18°</u> |
|---|------------|
- ☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	18°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	349 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	24°


Signature

3/15/07
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07707

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.9	Pass
Laboratory Relative Humidity	%	10 to 70	22	Pass
Initial Angle	deg	0 to 20	18	Pass
Return Angle	deg	+/- 8	24	Pass
Force at 45 deg	N	320 to 390	349	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

03/15/2007
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 506

Test Date 3/15/07

Technician Jessica Gall

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 25%

Record the minimum humidity 22%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3610 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Hall
Signature


3/15/07
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07706

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	24	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.61	Pass
Overall Test Results				Pass


Laboratory Technician


3/15/07
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D07706

Test Date: 3/15/07
Velocity: 6.89 ft/s, 2.10 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 506

Test Date 3/15/07

Technician Jessica Gall

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 25%

Record the minimum humidity 22%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.09 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3470 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Gall
Signature

3/15/07
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07705

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	24	Pass
Probe Speed	m/sec	2.07 to 2.13	2.09	Pass
Maximum Force	kN	3.45 to 4.06	3.47	Pass
Overall Test Results				Pass



Laboratory Technician

3/15/07

Test Date




Approved By



Test Desc: Right Knee
Componet ID: D07705

Test Date: 3/15/07
Velocity: 6.86 ft/s, 2.09 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 506 Test Date 3/26/07

Technician Jessica Gall

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))

Record the maximum temperature	<u>21.3</u>
Record the minimum temperature	<u>20.7</u>
Record the maximum humidity	<u>51%</u>
Record the minimum humidity	<u>42%</u>
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	273
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	5

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.

Jessica Hall
Signature

3/26/07
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test ID: D07801

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	42	Pass
Peak Resultant Acceleration	G's	250 to 300	273	Pass
Peak Lateral Acceleration	G's	+/- 15	4.9	Pass
Unimodal	NA	Yes	Yes	Pass
Oscillations	NA	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician



3/26/07
Test Date


Approved By



Test Desc: Head Drop
Componet ID: D07801

Test Date: 3/26/07
Velocity: 0 ft/s, 0 m/s



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 506

Test Date 3/26/07

Technician Joe Fleck

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

☒ N/A, ONLY one flexion test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.7

Record the maximum humidity 51%

Record the minimum humidity 42%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 86; Back 88.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.06 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.7 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.5 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>80</u> Nm @ <u>78</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	82 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.

Joe Fleck
Signature

3/26/07
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07802

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.7	Pass
Laboratory Relative Humidity		%	10 to 70	51	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.06	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.5	Pass
	20 msec	m/sec	4.0 to 5.0	4.7	Pass
	30 msec	m/sec	5.8 to 7.0	6.5	Pass
D Plane Rotation	Max	deg	77 to 91	78	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	80	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	82	Pass
Overall Results					Pass



Laboratory Technician

3/26/07

Test Date




Approved By




Test Desc: Neck Flexion
Componet ID: D07802

Test Date: 3/26/07
Velocity: 23.15 ft/s, 7.06 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D07802

Test Date: 3/26/07
Velocity: 23.15 ft/s, 7.06 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 506

Test Date 3/27/07

Technician Jessica Gall

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

 1. It has been at least 30 minutes since the last extension test. (572.137(q))

X N/A, ONLY one extension test performed

X 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

X 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.7

Record the maximum humidity 50%

Record the minimum humidity 46%

X 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

X 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 86; Back 88.

X 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.05 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.9 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.8 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.4 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-56</u> Nm @ <u>110</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	97 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.

Jessica Hall
Signature


3/27/07
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07803

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.7	Pass
Laboratory Relative Humidity		%	10 to 70	46	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.05	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.9	Pass
	20 msec	m/sec	3.1 to 3.9	3.8	Pass
	30 msec	m/sec	4.6 to 5.6	5.4	Pass
D Plane Rotation	Max	deg	99 to 114	110	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-56	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	97	Pass
Overall Results					Pass


 Laboratory Technician

3/27/07
 Test Date



 Approved By




Test Desc: Neck Extension
Componet ID: D07803

Test Date: 3/27/07
Velocity: 19.84 ft/s, 6.05 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Extension
Componet ID: D07803

Test Date: 3/27/07
Velocity: 19.84 ft/s, 6.05 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 506

Test Date 3/27/07

Technician Jessica Gall

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.1

Record the minimum temperature 20.7

Record the maximum humidity 50%

Record the minimum humidity 46%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.77 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	3920 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	3920 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	69%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.

Jessica Hall
Signature

3/27/07
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07804

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.1	Pass
Relative Humidity	%	10 to 70	50	Pass
Probe Speed	m/s	6.59 to 6.83	6.77	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	3.9	Pass
Internal Hysteresis	%	69 to 85	69	Pass
Peak Force 18 mm - 50 mm	N	≤ 4,600 N	3,920	Pass
Overall Test Results			Pass	

Jessica Hall
Laboratory Technician


3/27/07
Test Date

David Winkelbauer
Approved By



Test Desc: Thorax Impact
Componet ID: D07804

Test Date: 3/27/07
Velocity: 22.22 ft/s, 6.77 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 506

Test Date 3/27/07

Technician Tim Bratz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

X N/A, ONLY one thorax impact test performed

X 2. The test fixture conforms to the specifications in Figure 13B.

X 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

 with legs below the femurs.

X without legs below the femurs.

X 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.7

Record the maximum humidity 50%

Record the minimum humidity 46%

X 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

X 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

X 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

X 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

X 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

X 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

X 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 18°

X 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	18°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	355 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	24°


Signature

3/27/07
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07807

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	50	Pass
Initial Angle	deg	0 to 20	18	Pass
Return Angle	deg	+/- 8	24	Pass
Force at 45 deg	N	320 to 390	355	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

03/27/2007
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 506

Test Date 3/27/07

Technician Jessica Gall

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.7

Record the maximum humidity 50%

Record the minimum humidity 46%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3470 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Hall
Signature

3/27/07
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07806

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	50	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.47	Pass
			Overall Test Results	Pass



Laboratory Technician

3/27/07

Test Date




Approved By



Test Desc: Left Knee
Componet ID: D07806

Test Date: 3/27/07
Velocity: 6.944 ft/s, 2.12 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 506

Test Date 3/27/07

Technician Jessica Gall

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

X N/A, ONLY one knee impact test performed

X 2. The test fixture conforms to the specifications in Figure 14B.

X 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

X 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.7

Record the maximum humidity 50%

Record the minimum humidity 46%

X 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

X 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

X 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

X 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

X 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3660 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Hall
Signature

3/27/07
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 506

Test I.D: D07805

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	50	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.66	Pass
Overall Test Results				Pass

Jessica Gall
Laboratory Technician


3/27/07
Test Date

David Winkelbauer
Approved By



Test Desc: Right Knee
Componet ID: D07805

Test Date: 3/27/07
Velocity: 6.944 ft/s, 2.12 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #506, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	785.6
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	453.1
C	H-POINT HEIGHT	Reference	81.3-86.3	85.3
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	146.9
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	75.4
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	127.8
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249.3
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.7
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	279.8
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	191.3
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	531.2
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	370.1
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	408.4
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	425.9

HYBRID III 5 th SN #506, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	183.1
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.1
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	473.8
S	HEAD BREADTH	The widest part of the head	137.1-147.3	142.3
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	178.9
U	HIP BREADTH	The widest part of the hip	299.7-314.9	301.7
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	361.2
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	84.1
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	540.1
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	863.9
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	770.5
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 506

Test Date 3/26/07

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Hall
Signature

3/27/07
Date

Describe the repair or replacement of parts:

Checked by

David Winkelbauer
Signature

3/27/07
Date

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #516, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	783.2
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.8
C	H-POINT HEIGHT	Reference	81.3-86.3	83.9
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	147.4
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	78.3
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	128.5
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249.5
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	45.6
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	283.9
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	196.9
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	542.1
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	359.9
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	400.1
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	436.4

HYBRID III 5 th SN #516, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	177.8
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.1
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	480.4
S	HEAD BREADTH	The widest part of the head	137.1-147.3	143.2
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.3
U	HIP BREADTH	The widest part of the hip	299.7-314.9	302.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	361.9
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	82.1
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	545.3
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	865.4
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	783.3
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 516 Test Date 3/16/07

Technician Jessica Gall

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.3</u> |
| Record the minimum temperature | <u>20.9</u> |
| Record the maximum humidity | <u>26%</u> |
| Record the minimum humidity | <u>22%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	268
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	3

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.

Jessica Hall
Signature


3/16/07
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test ID: D07711

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.9	Pass
Laboratory Relative Humidity	%	10 to 70	26	Pass
Peak Resultant Acceleration	G's	250 to 300	268	Pass
Peak Lateral Acceleration	G's	+/- 15	3.3	Pass
Unimodal	NA	Yes	Yes	Pass
Oscillations	NA	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician

3/16/07
Test Date



Approved By




Test Desc: Head Drop
Componet ID: D07711

Test Date: 3/16/07
Velocity: 0 ft/s, 00 m/s

PEAK RESULTANT ACCELERATION (g's) vs TIME (s)



HEAD Y (G'S) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 516 Test Date 3/16/07

Technician Joe Fleck

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

☒ N/A, ONLY one flexion test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 26%

Record the minimum humidity 22%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		6.89 m/s $\leq$ speed $\leq$ 7.13 m/s	7.06 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	2.1 m/s $\leq \Delta V \leq$ 2.5 m/s	2.5 m/s
	@ 20 ms	4.0 m/s $\leq \Delta V \leq$ 5.0 m/s	4.7 m/s
	@30ms	5.8 m/s $\leq \Delta V \leq$ 7.0 m/s	6.5 m/s
Plane D Rotation		Peak moment* 69 Nm $\leq$ moment $\leq$ 83 Nm during the following rotation range $77^\circ \leq$ angle $\leq 91^\circ$	<u>80</u> Nm @ <u>81</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm 80 ms $\leq$ time $\leq$ 100ms	84 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.

Joe Fleck

Signature

3/16/07

Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07712

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21	Pass
Laboratory Relative Humidity		%	10 to 70	24	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.06	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.5	Pass
	20 msec	m/sec	4.0 to 5.0	4.7	Pass
	30 msec	m/sec	5.8 to 7.0	6.5	Pass
D Plane Rotation	Max	deg	77 to 91	81	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	80	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	84	Pass
Overall Results					Pass



Laboratory Technician

3/16/07

Test Date





Approved By



Test Desc: Neck Flexion
Componet ID: D07712


Test Date: 3/16/07
Velocity: 23.15 ft/s, 7.06 m/s





Test Desc: Neck Flexion
Componet ID: D07712

Test Date: 3/16/07
Velocity: 23.15 ft/s, 7.06 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 516 Test Date 3/16/07

Technician Jessica Gall

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 26%

Record the minimum humidity 22%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		5.95 m/s $\leq$ speed $\leq$ 6.19 m/s	5.98 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	1.5 m/s $\leq \Delta V \leq$ 1.9 m/s	1.9 m/s
	@ 20 ms	3.1 m/s $\leq \Delta V \leq$ 3.9 m/s	3.7 m/s
	@ 30ms	4.6 m/s $\leq \Delta V \leq$ 5.6 m/s	5.2 m/s
Plane D Rotation		Peak moment* -65 Nm $\leq$ moment $\leq$ -53 Nm during the following rotation range $99^\circ \leq$ angle $\leq 114^\circ$	-56 Nm @ 111 degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm 94 ms $\leq$ time $\leq$ 114 ms	97 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.

Jessica Hall
Signature


3/16/07
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07713

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21	Pass
Laboratory Relative Humidity		%	10 to 70	24	Pass
Pendulum Speed		m/sec	5.95 to 6.19	5.98	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.9	Pass
	20 msec	m/sec	3.1 to 3.9	3.7	Pass
	30 msec	m/sec	4.6 to 5.6	5.2	Pass
D Plane Rotation	Max	deg	99 to 114	111	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-56	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	97	Pass
Overall Results					Pass


 Laboratory Technician

3/16/07



Test Date


 Approved By



Test Desc: Neck Extension
Componet ID: D07713


Test Date: 3/16/07
Velocity: 19.61 ft/s, 5.98 m/s





Test Desc: Neck Extension
Componet ID: D07713

Test Date: 3/16/07
Velocity: 19.61 ft/s, 5.98 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 516

Test Date 3/19/07

Technician Dave Wilcox

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 25%

Record the minimum humidity 22%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.77 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	50 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4110 N
Peak force** between 18.0 and 50.0 mm chest compression	peak force $\leq 4600 \text{ N}$	4290 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	70%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

 X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.



Signature

3/15/07

Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07714

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	20.8	Pass
Relative Humidity	%	10 to 70	26	Pass
Probe Speed	m/s	6.59 to 6.83	6.77	Pass
Peak Deflection	mm	50 to 58	50	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.1	Pass
Internal Hysteresis	%	69 to 85	70	Pass
Peak Force 18 mm - 50 mm	N	≤ 4,600 N	4,290	Pass
Overall Test Results				Pass



Laboratory Technician

3/19/07

Test Date




Approved By



Test Desc: Thorax Impact
Componet ID: D07714

Test Date: 3/19/07
Velocity: 22.222 ft/s, 6.77 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 516 Test Date 3/16/07

Technician Joe Fleck

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

☐ with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 26%

Record the minimum humidity 22%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 14°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^{\circ} \pm 0.5^{\circ}$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^{\circ} \pm 0.5^{\circ}$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^{\circ}$	14°
Torso rotation rate	$0.5^{\circ}/s \leq \text{rate} \leq 1.5^{\circ}/s$	1.0
Force at $45^{\circ} \pm 0.5^{\circ}$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	340 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^{\circ}$	20°



 Signature

3/16/07

 Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07717

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	24	Pass
Initial Angle	deg	0 to 20	14	Pass
Return Angle	deg	+/- 8	20	Pass
Force at 45 deg	N	320 to 390	340	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass



Laboratory Technician

3/16/07

Test Date



Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 516

Test Date 3/15/07

Technician Jessica Gall

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 25%

Record the minimum humidity 22%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3590 N

*Force = impactor mass x deceleration (572.136(b)(2))

 X 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Hall
Signature


3/15/07
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07716

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	24	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.59	Pass
Overall Test Results				Pass



Laboratory Technician

3/15/07

Test Date




Approved By



Test Desc: Left Knee
Componet ID: D07716

Test Date: 3/15/07
Velocity: 6.89 ft/s, 2.10 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 516

Test Date 3/15/07

Technician Jessica Gall

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 26%

Record the minimum humidity 22%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3520 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Hall
Signature


3/15/07
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07715

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	24	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.52	Pass
Overall Test Results				Pass



Laboratory Technician

3/15/07

Test Date




Approved By



Test Desc: Right Knee
Componet ID: D07715

Test Date: 3/15/07
Velocity: 6.89 ft/s, 2.10 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)Dummy Serial Number 516 Test Date 3/26/07Technician Jessica Gall☐ Pretest calibration
☒ Post test calibration verificationTest attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.3</u> |
| Record the minimum temperature | <u>20.7</u> |
| Record the maximum humidity | <u>51%</u> |
| Record the minimum humidity | <u>46%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	276
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-5

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.

Jessica Hall
Signature

3/26/07
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test ID: D07811

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	42	Pass
Peak Resultant Acceleration	G's	250 to 300	276	Pass
Peak Lateral Acceleration	G's	+/- 15	-5	Pass
Unimodal	NA	Yes	Yes	Pass
Oscillations	NA	within 10% of peak	Yes	Pass
Overall Test Results				Pass



Laboratory Technician

3/26/07

Test Date





Approved By



Test Desc: Head Drop
Componet ID: D07811

Test Date: 3/26/07
Velocity: 0 ft/s, 0 m/s



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 516 Test Date 3/27/07

Technician Joe Fleck

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.1</u> |
| Record the minimum temperature | <u>20.7</u> |
| Record the maximum humidity | <u>51%</u> |
| Record the minimum humidity | <u>46%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
Record findings and actions: No Deterioration. Hardness Front 86; Back 88.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.06 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.6 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.4 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>76</u> Nm @ <u>88</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	84 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.

Joe Fleck

Signature

3/27/07

Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07812

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.7	Pass
Laboratory Relative Humidity		%	10 to 70	50	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.06	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.6	Pass
	30 msec	m/sec	5.8 to 7.0	6.4	Pass
D Plane Rotation	Max	deg	77 to 91	88	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	76	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	84	Pass
Overall Results				Pass	



Laboratory Technician

3/27/07

Test Date




Approved By




Test Desc: Neck Flexion
Componet ID: D07812

Test Date: 3/27/07
Velocity: 23.15 ft/s, 7.06 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D07812

Test Date: 3/27/07
Velocity: 23.15 ft/s, 7.06 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 516 Test Date 3/27/07

Technician Jessica Gall

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))
☒ N/A, ONLY one extension test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.1</u> |
| Record the minimum temperature | <u>20.7</u> |
| Record the maximum humidity | <u>51%</u> |
| Record the minimum humidity | <u>46%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
Record findings and actions: No Deterioration. Hardness Front 86; Back 88.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		5.95 m/s $\leq$ speed $\leq$ 6.19 m/s	6.12 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	1.5 m/s $\leq \Delta V \leq$ 1.9 m/s	1.9 m/s
	@ 20 ms	3.1 m/s $\leq \Delta V \leq$ 3.9 m/s	3.7 m/s
	@ 30ms	4.6 m/s $\leq \Delta V \leq$ 5.6 m/s	5.1 m/s
Plane D Rotation		Peak moment* -65 Nm $\leq$ moment $\leq$ -53 Nm during the following rotation range $99^\circ \leq$ angle $\leq 114^\circ$	-54 Nm @ 108 degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm 94 ms $\leq$ time $\leq$ 114 ms	104 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.

Jessica Hall
Signature


3/27/07
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07813

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.7	Pass
Laboratory Relative Humidity		%	10 to 70	46	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.12	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.9	Pass
	20 msec	m/sec	3.1 to 3.9	3.7	Pass
	30 msec	m/sec	4.6 to 5.6	5.1	Pass
D Plane Rotation	Max	deg	99 to 114	108	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-54	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	104	Pass
Overall Results					Pass


 Laboratory Technician

3/27/07
 Test Date



 Approved By




Test Desc: Neck Extension
Componet ID: D07813

Test Date: 3/27/07
Velocity: 20.08 ft/s, 6.12 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Extension
Componet ID: D07813

Test Date: 3/27/07
Velocity: 20.08 ft/s, 6.12 m/s



that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table :

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.77 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4000 N
Peak force** between 18.0 and 50.0 mm chest compression	peak force $\leq 4600 \text{ N}$	4090 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	70%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

 X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.

Jessica Hall
Signature

3/28/07
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07814

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.1	Pass
Relative Humidity	%	10 to 70	50	Pass
Probe Speed	m/s	6.59 to 6.83	6.77	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.0	Pass
Internal Hysteresis	%	69 to 85	70	Pass
Peak Force 18 mm - 50 mm	N	≤ 4,600 N	4,090	Pass
Overall Test Results				Pass

Jessica Hall
Laboratory Technician


3/28/07
Test Date

David Winkelbauer
Approved By



Test Desc: Thorax Impact
Componet ID: D07814

Test Date: 3/28/07
Velocity: 22.222 ft/s, 6.77 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 516

Test Date 3/27/07

Technician Tim Bratz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

X N/A, ONLY one thorax impact test performed

X 2. The test fixture conforms to the specifications in Figure 13B.

X 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

 with legs below the femurs.

X without legs below the femurs.

X 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.7

Record the maximum humidity 51%

Record the minimum humidity 46%

X 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

X 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

X 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

X 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

X 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

X 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

X 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 18°

X 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^{\circ} \pm 0.5^{\circ}$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^{\circ} \pm 0.5^{\circ}$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^{\circ}$	18°
Torso rotation rate	$0.5^{\circ}/s \leq \text{rate} \leq 1.5^{\circ}/s$	1.0
Force at $45^{\circ} \pm 0.5^{\circ}$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	357 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^{\circ}$	22°


Signature

3/27/07
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07817

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	50	Pass
Initial Angle	deg	0 to 20	18	Pass
Return Angle	deg	+/- 8	22	Pass
Force at 45 deg	N	320 to 390	357	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

03/27/2007
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 516

Test Date 3/27/07

Technician Jessica Gall

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

X N/A, ONLY one knee impact test performed

X 2. The test fixture conforms to the specifications in Figure 14B

X 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

X 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.7

Record the maximum humidity 51%

Record the minimum humidity 46%

X 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

X 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

X 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

X 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

X 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3460 N

*Force = impactor mass x deceleration (572.136(b)(2))

 X 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Hall
Signature

3/27/07
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07816

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	50	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.46	Pass
Overall Test Results				Pass


Laboratory Technician


3/27/07
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D07816

Test Date: 3/27/07
Velocity: 6.944 ft/s, 2.12 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 516

Test Date 3/27/07

Technician Jessica Gall

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

X N/A, ONLY one knee impact test performed

X 2. The test fixture conforms to the specifications in Figure 14B.

X 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

X 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.7

Record the maximum humidity 51%

Record the minimum humidity 46%

X 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

X 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

X 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

X 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

X 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3480 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Hall
Signature


3/27/07
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 516

Test I.D: D07815

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	50	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.48	Pass
Overall Test Results				Pass


Laboratory Technician


3/27/07
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D07815

Test Date: 3/27/07
Velocity: 6.944 ft/s, 2.12 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #516, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	783.2
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.8
C	H-POINT HEIGHT	Reference	81.3-86.3	83.9
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	147.4
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	78.3
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	128.5
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249.5
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	45.6
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	283.9
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	196.9
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	542.1
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	359.9
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	400.1
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	436.4

HYBRID III 5 th SN #516, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	177.8
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.1
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	480.4
S	HEAD BREADTH	The widest part of the head	137.1-147.3	143.2
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.3
U	HIP BREADTH	The widest part of the hip	299.7-314.9	302.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	361.9
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	82.1
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	545.3
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	865.4
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	783.3
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 516

Test Date 3/26/07

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Hall
Signature

3/28/07
Date

Describe the repair or replacement of parts:

Checked by

David Winkelbauer
Signature

3/28/07
Date

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #125, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	785.2
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	448.6
C	H-POINT HEIGHT	Reference	81.3-86.3	86.0
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	146.7
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	83.5
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	127.5
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	248.3
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	43.4
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	285.4
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	192.9
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	542.7
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	356.8
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	394.2
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	428.5

HYBRID III 5 th SN #125, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	185.2
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	219.0
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	471.8
S	HEAD BREADTH	The widest part of the head	137.1-147.3	141.2
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	182.5
U	HIP BREADTH	The widest part of the hip	299.7-314.9	301.6
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	360.0
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	93.9
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	547.1
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	852.6
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	789.1
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	345.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 125 Test Date 2/5/07

Technician Justino Diaz

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>20.8</u> |
| Record the minimum temperature | <u>20.7</u> |
| Record the maximum humidity | <u>17%</u> |
| Record the minimum humidity | <u>11%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	263
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	9

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.

James Z. J.
Signature

2/5/07
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test ID: D07321

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	17	Pass
Peak Resultant Acceleration	G's	250 to 300	263	Pass
Peak Lateral Acceleration	G's	+/- 15	9	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician

02/05/2007
Test Date



Approved By




Test Desc: Head Drop
Componet ID: D07321

Test Date: 02/05/2007
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G's) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 125 Test Date 2/5/07

Technician Justino Diaz

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>20.8</u> |
| Record the minimum temperature | <u>20.7</u> |
| Record the maximum humidity | <u>17%</u> |
| Record the minimum humidity | <u>11%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
Record findings and actions: No Deterioration. Hardness Front 89; Back 90.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.08 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.8 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.8 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>73</u> Nm @ <u>85</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	86 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature


2/5/07
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07322

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.8	Pass
Laboratory Relative Humidity		%	10 to 70	17	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.08	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.8	Pass
	30 msec	m/sec	5.8 to 7.0	6.8	Pass
D Plane Rotation	Max	deg	77 to 91	85	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	73	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	86	Pass
Overall Results					Pass


Laboratory Technician



02/05/2007
Test Date


Approved By



Test Desc: Neck Flexion
Componet ID: D07322


Test Date: 02/05/2007
Velocity: 23.24 ft/s, 7.08 m/s





Test Desc: Neck Flexion
Componet ID: D07322

Test Date: 02/05/2007
Velocity: 23.24 ft/s, 7.08 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 125

Test Date 2/5/07

Technician Justino Diaz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 20.8

Record the minimum temperature 20.7

Record the maximum humidity 17%

Record the minimum humidity 11%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.14 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.7 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.4 m/s
Plane D Rotation		Peak moment* -65 Nm $\leq$ moment $\leq$ -53 Nm during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	-63 Nm @ 112 degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	96 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

2/5/07
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07323

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.8	Pass
Laboratory Relative Humidity		%	10 to 70	17	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.14	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.7	Pass
	30 msec	m/sec	4.6 to 5.6	5.4	Pass
D Plane Rotation	Max	deg	99 to 114	112	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-63	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	96	Pass
Overall Results					Pass


Laboratory Technician

02/05/2007



Test Date


Approved By



Test Desc: Neck Extension
Componet ID: D07323


Test Date: 02/05/2007
Velocity: 20.14 ft/s, 6.14 m/s





Test Desc: Neck Extension
Componet ID: D07323

Test Date: 02/05/2007
Velocity: 20.14 ft/s, 6.14 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 125

Test Date 2/5/07

Technician Justino Diaz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 20.8

Record the minimum temperature 20.7

Record the maximum humidity 17%

Record the minimum humidity 11%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))


Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.71 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	50 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4100 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4247 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	74%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

2/5/07
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07324

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	20.7	Pass
Relative Humidity	%	10 to 70	11	Pass
Probe Speed	m/s	6.59 to 6.83	6.71	Pass
Peak Deflection	mm	50 to 58	50	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.1	Pass
Internal Hysteresis	%	69 to 85	74	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4247	Pass
Overall Test Results				Pass


Laboratory Technician


02/05/2007
Test Date


Approved By



Test Desc: Thorax Impact
Componet ID: D07324

Test Date: 02/05/2007
Velocity: 22.01 ft/s, 6.71 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 125 Test Date 2/5/07

Technician Justino Diaz

☒ Pretest calibration
☐ Post test calibration verification


Test attempt no. 1 (when successive torso flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
☒ N/A, ONLY one thorax impact test performed
- ☒ 2. The test fixture conforms to the specifications in Figure 13B.
- ☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
☐ with legs below the femurs.
☒ without legs below the femurs.
- ☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>20.8</u> |
| Record the minimum temperature | <u>20.7</u> |
| Record the maximum humidity | <u>17%</u> |
| Record the minimum humidity | <u>11%</u> |
- ☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
- ☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
- ☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
- ☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))
- ☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- ☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- ☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
- | | |
|---|------------|
| Record reference plane angle (max. allowed 20°) | <u>17°</u> |
|---|------------|
- ☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	17°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	363 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	18°


Signature

2/5/07
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07327

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	11	Pass
Initial Angle	deg	0 to 20	17	Pass
Return Angle	deg	+/- 8	18	Pass
Force at 45 deg	N	320 to 390	363	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

02/05/2007
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 125

Test Date 2/5/07

Technician Justino Diaz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 20.8

Record the minimum temperature 20.7

Record the maximum humidity 17%

Record the minimum humidity 11%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))


X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3580 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

2/5/07
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07326

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	17	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.58	Pass
Overall Test Results				Pass


Laboratory Technician


02/05/2007
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D07326

Test Date: 02/05/2007
Velocity: 6.96 ft/s, 2.12 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 125

Test Date 2/5/07

Technician Justino Diaz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 20.8

Record the minimum temperature 20.7

Record the maximum humidity 17%

Record the minimum humidity 11%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))


☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3520 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

2/5/07
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07325

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	17	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.52	Pass
Overall Test Results				Pass


Laboratory Technician


02/05/2007
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D07325

Test Date: 02/05/2007
Velocity: 6.92 ft/s, 2.11 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 125 Test Date 2/8/07

Technician Justino Diaz

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>20.9</u> |
| Record the minimum temperature | <u>20.6</u> |
| Record the maximum humidity | <u>14%</u> |
| Record the minimum humidity | <u>11%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm


Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	271
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-10

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

2/8/07
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test ID: D07371

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.6	Pass
Laboratory Relative Humidity	%	10 to 70	11	Pass
Peak Resultant Acceleration	G's	250 to 300	271	Pass
Peak Lateral Acceleration	G's	+/- 15	-9.8	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician



02/08/2007
Test Date


Approved By



Test Desc: Head Drop
Componet ID: D07371

Test Date: 02/08/2007
Velocity: 0 ft/s, 0 m/s



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 125

Test Date 2/9/07

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.9</u> |
| Record the minimum temperature | <u>21.4</u> |
| Record the maximum humidity | <u>14%</u> |
| Record the minimum humidity | <u>11%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
 Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
 Record findings and actions: No Deterioration. Hardness Front 86; Back 88.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.07 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.7 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.6 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>72</u> Nm @ <u>88</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	88 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

2/9/07
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07372

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.9	Pass
Laboratory Relative Humidity		%	10 to 70	11	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.07	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.7	Pass
	30 msec	m/sec	5.8 to 7.0	6.6	Pass
D Plane Rotation	Max	deg	77 to 91	88	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	72	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	88	Pass
Overall Results					Pass


 Laboratory Technician



02/09/2007
 Test Date


 Approved By



Test Desc: Neck Flexion
Componet ID: D07372


Test Date: 02/09/2007
Velocity: 23.19 ft/s, 7.07 m/s





Test Desc: Neck Flexion
Componet ID: D07372

Test Date: 02/09/2007
Velocity: 23.19 ft/s, 7.07 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 125

Test Date 2/9/07

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.9

Record the minimum temperature 21.4

Record the maximum humidity 14%

Record the minimum humidity 11%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 86; Back 88.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		5.95 m/s $\leq$ speed $\leq$ 6.19 m/s	6.06 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	1.5 m/s $\leq \Delta V \leq$ 1.9 m/s	1.7 m/s
	@ 20 ms	3.1 m/s $\leq \Delta V \leq$ 3.9 m/s	3.4 m/s
	@30ms	4.6 m/s $\leq \Delta V \leq$ 5.6 m/s	5.1 m/s
Plane D Rotation		Peak moment* -65 Nm $\leq$ moment $\leq$ -53 Nm during the following rotation range $99^\circ \leq$ angle $\leq 114^\circ$	-59 Nm @ 112 degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm 94 ms $\leq$ time $\leq$ 114 ms	103 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

2/9/07
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07373

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.9	Pass
Laboratory Relative Humidity		%	10 to 70	11	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.06	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.7	Pass
	20 msec	m/sec	3.1 to 3.9	3.4	Pass
	30 msec	m/sec	4.6 to 5.6	5.1	Pass
D Plane Rotation	Max	deg	99 to 114	112	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-59	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	103	Pass
Overall Results					Pass


 Laboratory Technician

02/09/2007



Test Date


 Approved By



Test Desc: Neck Extension
Componet ID: D07373


Test Date: 02/09/2007
Velocity: 19.89 ft/s, 6.06 m/s





Test Desc: Neck Extension
Componet ID: D07373

Test Date: 02/09/2007
Velocity: 19.89 ft/s, 6.06 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 125

Test Date 2/8/07

Technician Justino Diaz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 20.9

Record the minimum temperature 20.6

Record the maximum humidity 14%

Record the minimum humidity 11%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))


Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.82 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	50 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4330 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4395 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	74%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

2/8/07
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07374

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	20.6	Pass
Relative Humidity	%	10 to 70	11	Pass
Probe Speed	m/s	6.59 to 6.83	6.82	Pass
Peak Deflection	mm	50 to 58	50	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.3	Pass
Internal Hysteresis	%	69 to 85	74	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4395	Pass
Overall Test Results				Pass


Laboratory Technician


02/08/2007
Test Date


Approved By



Test Desc: Thorax Impact
Componet ID: D07374

Test Date: 02/08/2007
Velocity: 22.37 ft/s, 6.82 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 125 Test Date 2/9/07

Technician Tim Bratz

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
☒ N/A, ONLY one thorax impact test performed
- ☒ 2. The test fixture conforms to the specifications in Figure 13B.
- ☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
☐ with legs below the femurs.
☒ without legs below the femurs.
- ☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
Record the maximum temperature 21.9
Record the minimum temperature 21.4
Record the maximum humidity 14%
Record the minimum humidity 11%
- ☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
- ☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
- ☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
- ☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))
- ☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- ☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- ☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
Record reference plane angle (max. allowed 20°) 17°
- ☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	17°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	335 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	20°


Signature

2/9/07
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07377

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.9	Pass
Laboratory Relative Humidity	%	10 to 70	12	Pass
Initial Angle	deg	0 to 20	17	Pass
Return Angle	deg	+/- 8	20	Pass
Force at 45 deg	N	320 to 390	335	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

02/09/2007
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 125

Test Date 2/8/07

Technician Justino Diaz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 20.9

Record the minimum temperature 20.6

Record the maximum humidity 14%

Record the minimum humidity 11%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))


X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3530 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature


2/8/07
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07376

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.8	Pass
Laboratory Relative Humidity	%	10 to 70	11	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.53	Pass
Overall Test Results				Pass


Laboratory Technician


02/08/2007
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D07376

Test Date: 02/08/2007
Velocity: 6.88 ft/s, 2.10 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 125

Test Date 2/8/07

Technician Justino Diaz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 20.9

Record the minimum temperature 20.6

Record the maximum humidity 14%

Record the minimum humidity 11%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))


☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3560 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

2/8/07
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 125

Test I.D: D07375

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.8	Pass
Laboratory Relative Humidity	%	10 to 70	11	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.56	Pass
Overall Test Results				Pass


Laboratory Technician


02/08/2007
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D07375

Test Date: 02/08/2007
Velocity: 6.96 ft/s, 2.12 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #125, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	785.2
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	448.6
C	H-POINT HEIGHT	Reference	81.3-86.3	86.0
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	146.7
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	83.5
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	127.5
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	248.3
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	43.4
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	285.4
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	192.9
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	542.7
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	356.8
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	394.2
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	428.5

HYBRID III 5 th SN #125, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	185.2
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	219.0
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	471.8
S	HEAD BREADTH	The widest part of the head	137.1-147.3	141.2
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	182.5
U	HIP BREADTH	The widest part of the hip	299.7-314.9	301.6
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	360.0
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	93.9
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	547.1
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	852.6
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	789.1
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	345.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 125

Test Date 2/8/07

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Hall
Signature

2/9/07
Date

Describe the repair or replacement of parts:

Checked by

David Winkelbauer
Signature

2/9/07
Date

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #505, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	778.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.3
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.8
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	76.6
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	128.3
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	248.7
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.2
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	278.9
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	187.5
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	541.9
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	361.7
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	402.4
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	436.8

HYBRID III 5 th SN #505, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	188.7
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.3
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.1
S	HEAD BREADTH	The widest part of the head	137.1-147.3	141.4
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.8
U	HIP BREADTH	The widest part of the hip	299.7-314.9	302.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	359.1
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	84.2
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	531.7
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	853.2
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	773.2
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 505 Test Date 6/26/06

Technician Dave Wilcox

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.3</u> |
| Record the minimum temperature | <u>21.0</u> |
| Record the maximum humidity | <u>47%</u> |
| Record the minimum humidity | <u>43%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	278
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	1

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

6/26/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test ID: D061821


Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	46	Pass
Peak Resultant Acceleration	G's	250 to 300	278	Pass
Peak Lateral Acceleration	G's	+/- 15	1.4	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass



Laboratory Technician

06/26/2006

Test Date




Approved By




Test Desc: Head Drop
Componet ID: D061821

Test Date: 06/26/2006
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G'S) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 505

Test Date 6/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

☒ N/A, ONLY one flexion test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 21.0

Record the maximum humidity 47%

Record the minimum humidity 43%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	6.96 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.5 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.9 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.9 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>74</u> Nm @ <u>80</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	86 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature


6/26/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061822

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.2	Pass
Laboratory Relative Humidity		%	10 to 70	44	Pass
Pendulum Speed		m/sec	6.89 to 7.13	6.96	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.5	Pass
	20 msec	m/sec	4.0 to 5.0	4.9	Pass
	30 msec	m/sec	5.8 to 7.0	6.9	Pass
D Plane Rotation	Max	deg	77 to 91	80	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	74	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	86	Pass
Overall Results				Pass	


Laboratory Technician



06/26/2006
Test Date


Approved By



Test Desc: Neck Flexion
Componet ID: D061822


Test Date: 06/26/2006
Velocity: 22.85 ft/s, 6.96 m/s





Test Desc: Neck Flexion
Componet ID: D061822

Test Date: 06/26/2006
Velocity: 22.85 ft/s, 6.96 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 505

Test Date 6/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 21.0

Record the maximum humidity 47%

Record the minimum humidity 43%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.06 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.9 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.8 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.5 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-61</u> Nm @ <u>108</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	98 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

6/26/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061823

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.0	Pass
Laboratory Relative Humidity		%	10 to 70	43	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.06	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.9	Pass
	20 msec	m/sec	3.1 to 3.9	3.8	Pass
	30 msec	m/sec	4.6 to 5.6	5.5	Pass
D Plane Rotation	Max	deg	99 to 114	108	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-61	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	98	Pass
Overall Results				Pass	


Laboratory Technician

06/26/2006

Test Date





Approved By



Test Desc: Neck Extension
Componet ID: D061823


Test Date: 06/26/2006
Velocity: 19.87 ft/s, 6.06 m/s





Test Desc: Neck Extension
Componet ID: D061823

Test Date: 06/26/2006
Velocity: 19.87 ft/s, 6.06 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 505

Test Date 6/26/06

Technician Dave Wilcox

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.3

Record the minimum temperature 21.0

Record the maximum humidity 47%

Record the minimum humidity 43%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.65 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	53 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	3920 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	3872 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	70%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.



Signature

6/26/06

Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061824

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.2	Pass
Relative Humidity	%	10 to 70	47	Pass
Probe Speed	m/s	6.59 to 6.83	6.65	Pass
Peak Deflection	mm	50 to 58	53	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	3.9	Pass
Internal Hysteresis	%	69 to 85	70	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	3872	Pass
Overall Test Results				Pass



Laboratory Technician

06/26/2006

Test Date




Approved By



Test Desc: Thorax Impact
Componet ID: D061824

Test Date: 06/26/2006
Velocity: 21.81 ft/s, 6.65 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 505

Test Date 6/26/06

Technician Dave Wilcox

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

☐ with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 21.0

Record the maximum humidity 47%

Record the minimum humidity 43%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 18°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	18°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	379
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	20°



 Signature

6/26/06

 Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061827

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	45	Pass
Initial Angle	deg	0 to 20	18	Pass
Return Angle	deg	+/- 8	20	Pass
Force at 45 deg	N	320 to 390	379	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1. 0	Pass
			Overall Result	Pass



Laboratory Technician

06/26/2006

Test Date



Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 6/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 21.0

Record the maximum humidity 47%

Record the minimum humidity 43%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.13 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3770 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

6/26/06
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D061826

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.0	Pass
Laboratory Relative Humidity	%	10 to 70	46	Pass
Probe Speed	m/sec	2.07 to 2.13	2.13	Pass
Maximum Force	kN	3.45 to 4.06	3.77	Pass
Overall Test Results				Pass


Laboratory Technician


06/26/2006
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D061826

Test Date: 06/26/2006
Velocity: 6.98 ft/s, 2.13 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 6/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 21.0

Record the maximum humidity 47%

Record the minimum humidity 43%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3560 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

6/26/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D061825

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	46	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.56	Pass
Overall Test Results				Pass


Laboratory Technician


06/26/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D061825

Test Date: 06/26/2006
Velocity: 6.95 ft/s, 2.12 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 505 Test Date 7/12/06

Technician Dave Wilcox

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))

X N/A, ONLY one head drop performed

X 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))

X 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.

X 4. Accelerometers and their respective mounts are smooth and clean.

X 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.

X 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))

X 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))

Record the maximum temperature 21.2

Record the minimum temperature 20.8

Record the maximum humidity 48%

Record the minimum humidity 47%

X 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

X 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistant within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	293
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-9

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

7/12/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test ID: D061971

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.2	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Peak Resultant Acceleration	G's	250 to 300	293	Pass
Peak Lateral Acceleration	G's	+/- 15	-9.1	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass



Laboratory Technician

07/12/2006

Test Date





Approved By



Test Desc: Head Drop
Componet ID: D061971

Test Date: 07/12/2006
Velocity: 0 ft/s, 0 m/s



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 505 Test Date 7/12/06

Technician Tim Bratz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

X N/A, ONLY one flexion test performed

X 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

X 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.2

Record the minimum temperature 20.8

Record the maximum humidity 48%

Record the minimum humidity 47%

X 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

X 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

X 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		6.89 m/s $\leq$ speed $\leq$ 7.13 m/s	7.08 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	2.1 m/s $\leq \Delta V \leq$ 2.5 m/s	2.4 m/s
	@ 20 ms	4.0 m/s $\leq \Delta V \leq$ 5.0 m/s	4.6 m/s
	@ 30ms	5.8 m/s $\leq \Delta V \leq$ 7.0 m/s	6.5 m/s
Plane D Rotation		Peak moment* 69 Nm $\leq$ moment $\leq$ 83 Nm during the following rotation range 77° $\leq$ angle $\leq$ 91°	<u>72</u> Nm @ <u>81</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm 80 ms $\leq$ time $\leq$ 100ms	87 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

7/12/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061972

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.8	Pass
Laboratory Relative Humidity		%	10 to 70	47	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.08	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.6	Pass
	30 msec	m/sec	5.8 to 7.0	6.5	Pass
D Plane Rotation	Max	deg	77 to 91	81	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	72	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	87	Pass
Overall Results					Pass


Laboratory Technician


Approved By


07/12/2006
Test Date




Test Desc: Neck Flexion
Componet ID: D061972

Test Date: 07/12/2006
Velocity: 23.22 ft/s, 7.08 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D061972

Test Date: 07/12/2006
Velocity: 23.22 ft/s, 7.08 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 505 Test Date 7/12/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.2

Record the minimum temperature 20.8

Record the maximum humidity 48%

Record the minimum humidity 47%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		5.95 m/s $\leq$ speed $\leq$ 6.19 m/s	6.14 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	1.5 m/s $\leq \Delta V \leq$ 1.9 m/s	1.8 m/s
	@ 20 ms	3.1 m/s $\leq \Delta V \leq$ 3.9 m/s	3.8 m/s
	@ 30ms	4.6 m/s $\leq \Delta V \leq$ 5.6 m/s	5.5 m/s
Plane D Rotation		Peak moment* -65 Nm $\leq$ moment $\leq$ -53 Nm during the following rotation range $99^\circ \leq$ angle $\leq 114^\circ$	-60 Nm @ 108 degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm 94 ms $\leq$ time $\leq$ 114 ms	98 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

7/12/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061973

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.8	Pass
Laboratory Relative Humidity		%	10 to 70	47	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.14	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.8	Pass
	30 msec	m/sec	4.6 to 5.6	5.5	Pass
D Plane Rotation	Max	deg	99 to 114	108	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-60	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	98	Pass
Overall Results					Pass


Laboratory Technician

07/12/2006



Test Date


Approved By



Test Desc: Neck Extension
Componet ID: D061973


Test Date: 07/12/2006
Velocity: 20.14 ft/s, 6.14 m/s





Test Desc: Neck Extension
Componet ID: D061973

Test Date: 07/12/2006
Velocity: 20.14 ft/s, 6.14 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 505

Test Date 7/13/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.5

Record the minimum temperature 21.1

Record the maximum humidity 50%

Record the minimum humidity 47%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.66 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	52 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	3965 N
Peak force** between 18.0 and 50.0 mm chest compression	peak force $\leq 4600 \text{ N}$	3965 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	70%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

 X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

7/13/06
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061974

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.5	Pass
Relative Humidity	%	10 to 70	50	Pass
Probe Speed	m/s	6.59 to 6.83	6.66	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.0	Pass
Internal Hysteresis	%	69 to 85	70	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	3965	Pass
Overall Test Results				Pass


Laboratory Technician



Approved By

07/13/2006
Test Date



Test Desc: Thorax Impact
Componet ID: D061974

Test Date: 07/13/2006
Velocity: 21.85 ft/s, 6.66 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 505

Test Date 7/12/06

Technician Dave Wilcox

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
 X N/A, ONLY one thorax impact test performed
- X 2. The test fixture conforms to the specifications in Figure 13B.
- X 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
 with legs below the femurs.
 X without legs below the femurs.
- X 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.2</u> |
| Record the minimum temperature | <u>20.8</u> |
| Record the maximum humidity | <u>48%</u> |
| Record the minimum humidity | <u>47%</u> |
- X 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
- X 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
- X 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
- X 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))
- X 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- X 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- X 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
- | | |
|---|------------|
| Record reference plane angle (max. allowed 20°) | <u>17°</u> |
|---|------------|
- X 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^{\circ} \pm 0.5^{\circ}$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^{\circ} \pm 0.5^{\circ}$ of flexion for 10 seconds.
(572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket.
(572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle.
(572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^{\circ}$	17°
Torso rotation rate	$0.5^{\circ}/s \leq \text{rate} \leq 1.5^{\circ}/s$	1.0
Force at $45^{\circ} \pm 0.5^{\circ}$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	364 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^{\circ}$	18°



Signature

7/12/06

Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061977

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.2	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Initial Angle	deg	0 to 20	17	Pass
Return Angle	deg	+/- 8	18	Pass
Force at 45 deg	N	320 to 390	364	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result			Pass	



Laboratory Technician

07/12/2006

Test Date



Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 7/13/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.5

Record the minimum temperature 21.1

Record the maximum humidity 50%

Record the minimum humidity 47%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))


X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3720 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

7/13/06
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061976

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	47	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.72	Pass
Overall Test Results				Pass


Laboratory Technician



Approved By

07/13/2006
Test Date



Test Desc: Left Knee
Componet ID: D061976

Test Date: 07/13/2006
Velocity: 6.92 ft/s, 2.11 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 7/13/06

Technician Tim Bratz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

X N/A, ONLY one knee impact test performed

X 2. The test fixture conforms to the specifications in Figure 14B.

X 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

X 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.5

Record the minimum temperature 21.1

Record the maximum humidity 50%

Record the minimum humidity 47%

X 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

X 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

X 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

X 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

X 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3560 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

7/13/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D061975

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	47	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.56	Pass
Overall Test Results				Pass


Laboratory Technician


07/13/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D061975

Test Date: 07/13/2006
Velocity: 6.91 ft/s, 2.11 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #505, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	778.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.3
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.8
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	76.6
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	128.3
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	248.7
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.2
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	278.9
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	187.5
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	541.9
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	361.7
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	402.4
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	436.8

HYBRID III 5 th SN #505, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	188.7
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.3
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.1
S	HEAD BREADTH	The widest part of the head	137.1-147.3	141.4
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.8
U	HIP BREADTH	The widest part of the hip	299.7-314.9	302.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	359.1
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	84.2
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	531.7
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	853.2
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	773.2
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 505

Test Date 7/10/06

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Hall
Signature

7/13/06
Date

Describe the repair or replacement of parts:

Checked by
David Winkelbauer
Signature

7/13/06
Date

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #505, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	778.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.3
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.8
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	76.6
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	128.3
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	248.7
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.2
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	278.9
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	187.5
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	541.9
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	361.7
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	402.4
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	436.8

HYBRID III 5 th SN #505, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	188.7
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.3
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.1
S	HEAD BREADTH	The widest part of the head	137.1-147.3	141.4
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.8
U	HIP BREADTH	The widest part of the hip	299.7-314.9	302.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	359.1
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	84.2
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	531.7
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	853.2
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	773.2
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 505 Test Date 7/18/06

Technician Tim Bratz

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.8</u> |
| Record the minimum temperature | <u>20.7</u> |
| Record the maximum humidity | <u>46%</u> |
| Record the minimum humidity | <u>44%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	282
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	7

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

7/18/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test ID: D062041

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	44	Pass
Peak Resultant Acceleration	G's	250 to 300	282	Pass
Peak Lateral Acceleration	G's	+/- 15	6.6	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


 Laboratory Technician



07/18/2006
 Test Date


 Approved By



Test Desc: Head Drop
Componet ID: D062041

Test Date: 07/18/2006
Velocity: 0 ft/s, 0 m/s



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 505

Test Date 7/19/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

☒ N/A, ONLY one flexion test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 48%

Record the minimum humidity 44%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		6.89 m/s $\leq$ speed $\leq$ 7.13 m/s	7.08 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	2.1 m/s $\leq \Delta V \leq$ 2.5 m/s	2.4 m/s
	@ 20 ms	4.0 m/s $\leq \Delta V \leq$ 5.0 m/s	4.6 m/s
	@30ms	5.8 m/s $\leq \Delta V \leq$ 7.0 m/s	6.5 m/s
Plane D Rotation		Peak moment* 69 Nm $\leq$ moment $\leq$ 83 Nm during the following rotation range $77^\circ \leq$ angle $\leq 91^\circ$	<u>71</u> Nm @ <u>81</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm 80 ms $\leq$ time $\leq$ 100ms	87 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

7/19/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062042

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.3	Pass
Laboratory Relative Humidity		%	10 to 70	46	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.08	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.6	Pass
	30 msec	m/sec	5.8 to 7.0	6.5	Pass
D Plane Rotation	Max	deg	77 to 91	81	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	71	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	87	Pass
Overall Results					Pass


 Laboratory Technician

07/19/2006
 Test Date



 Approved By




Test Desc: Neck Flexion
Componet ID: D062042

Test Date: 07/19/2006
Velocity: 23.22 ft/s, 7.08 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D062042

Test Date: 07/19/2006
Velocity: 23.22 ft/s, 7.08 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 505 Test Date 7/19/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 48%

Record the minimum humidity 46%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		5.95 m/s $\leq$ speed $\leq$ 6.19 m/s	6.13 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	1.5 m/s $\leq \Delta V \leq$ 1.9 m/s	1.9 m/s
	@ 20 ms	3.1 m/s $\leq \Delta V \leq$ 3.9 m/s	3.8 m/s
	@ 30ms	4.6 m/s $\leq \Delta V \leq$ 5.6 m/s	5.5 m/s
Plane D Rotation		Peak moment* -65 Nm $\leq$ moment $\leq$ -53 Nm during the following rotation range $99^\circ \leq$ angle $\leq 114^\circ$	<u>-57</u> Nm @ <u>107</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm 94 ms $\leq$ time $\leq$ 114 ms	101 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

7/19/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062043

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	48	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.13	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.9	Pass
	20 msec	m/sec	3.1 to 3.9	3.8	Pass
	30 msec	m/sec	4.6 to 5.6	5.5	Pass
D Plane Rotation	Max	deg	99 to 114	107	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-57	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	101	Pass
Overall Results					Pass


Laboratory Technician

07/19/2006

Test Date





Approved By



Test Desc: Neck Extension
Componet ID: D062043


Test Date: 07/19/2006
Velocity: 20.12 ft/s, 6.13 m/s





Test Desc: Neck Extension
Componet ID: D062043

Test Date: 07/19/2006
Velocity: 20.12 ft/s, 6.13 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 505

Test Date 7/19/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 48%

Record the minimum humidity 44%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.61 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4020 N
Peak force** between 18.0 and 50.0 mm chest compression	peak force $\leq 4600 \text{ N}$	4043 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	70%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

7/19/06
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062044

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	20.9	Pass
Relative Humidity	%	10 to 70	48	Pass
Probe Speed	m/s	6.59 to 6.83	6.61	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.0	Pass
Internal Hysteresis	%	69 to 85	70	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4043	Pass
Overall Test Results				Pass


Laboratory Technician


07/19/2006
Test Date


Approved By



Test Desc: Thorax Impact
Componet ID: D062044

Test Date: 07/19/2006
Velocity: 21.7 ft/s, 6.61 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 505

Test Date 7/18/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

☐ with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.8

Record the minimum temperature 20.7

Record the maximum humidity 46%

Record the minimum humidity 44%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 18°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^{\circ} \pm 0.5^{\circ}$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^{\circ} \pm 0.5^{\circ}$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^{\circ}$	18°
Torso rotation rate	$0.5^{\circ}/s \leq \text{rate} \leq 1.5^{\circ}/s$	1.0
Force at $45^{\circ} \pm 0.5^{\circ}$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	357 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^{\circ}$	20°


Signature

7/18/06
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062047

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	46	Pass
Initial Angle	deg	0 to 20	18	Pass
Return Angle	deg	+/- 8	20	Pass
Force at 45 deg	N	320 to 390	357	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician

07/18/2006
Test Date


Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 7/18/06

Technician Dave Wilcox

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.8

Record the minimum temperature 20.7

Record the maximum humidity 46%

Record the minimum humidity 44%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3640 N

*Force = impactor mass x deceleration (572.136(b)(2))

 X 12. Plots of acceleration versus time and force versus time follow this sheet.



Signature

7/18/06

Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062046

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	45	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.64	Pass
Overall Test Results				Pass



Laboratory Technician

07/18/2006

Test Date




Approved By



Test Desc: Left Knee
Componet ID: D062046

Test Date: 07/18/2006
Velocity: 6.92 ft/s, 2.11 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 7/18/06

Technician Dave Wilcox

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.8

Record the minimum temperature 20.7

Record the maximum humidity 46%

Record the minimum humidity 44%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.08 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3530 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.

A handwritten signature in dark ink, appearing to be "J. H. White", written above a horizontal line.

Signature

7/18/06

Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062045

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	45	Pass
Probe Speed	m/sec	2.07 to 2.13	2.08	Pass
Maximum Force	kN	3.45 to 4.06	3.53	Pass
			Overall Test Results	Pass



Laboratory Technician

07/18/2006

Test Date




Approved By



Test Desc: Right Knee
Componet ID: D062045

Test Date: 07/18/2006
Velocity: 6.81 ft/s, 2.08 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 505 Test Date 7/20/06

Technician Jessica Gall

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))

☒ N/A, ONLY one head drop performed

☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))

☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.

☒ 4. Accelerometers and their respective mounts are smooth and clean.

☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.

☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))

☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))

Record the maximum temperature 21.0

Record the minimum temperature 20.8

Record the maximum humidity 48%

Record the minimum humidity 47%

☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	271
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	4

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.

Jessica Hall
Signature


7/20/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test ID: D062101

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.0	Pass
Laboratory Relative Humidity	%	10 to 70	47	Pass
Peak Resultant Acceleration	G's	250 to 300	271	Pass
Peak Lateral Acceleration	G's	+/- 15	3.7	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician



07/20/2006
Test Date


Approved By



Test Desc: Head Drop
Componet ID: D062101

Test Date: 07/20/2006
Velocity: 0 ft/s, 0 m/s



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 505

Test Date 7/21/06

Technician Joe Fleck

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.6</u> |
| Record the minimum temperature | <u>20.6</u> |
| Record the maximum humidity | <u>47%</u> |
| Record the minimum humidity | <u>42%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
 Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
 Record findings and actions: No Deterioration. Hardness Front 81; Back 89.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.13 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.6 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.4 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>72</u> Nm @ <u>79</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	87 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.

Joe Fleck
Signature

7/21/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062102

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.8	Pass
Laboratory Relative Humidity		%	10 to 70	43	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.13	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.6	Pass
	30 msec	m/sec	5.8 to 7.0	6.4	Pass
D Plane Rotation	Max	deg	77 to 91	79	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	72	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	87	Pass
Overall Results					Pass



Laboratory Technician

07/21/2006

Test Date




Approved By




Test Desc: Neck Flexion
Componet ID: D062102

Test Date: 07/21/2006
Velocity: 23.39 ft/s, 7.13 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D062102

Test Date: 07/21/2006
Velocity: 23.39 ft/s, 7.13 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 505 Test Date 7/21/06

Technician Jessica Gall

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.6

Record the minimum temperature 20.6

Record the maximum humidity 47%

Record the minimum humidity 42%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.11 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.7 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.5 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-55</u> Nm @ <u>104</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	98 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.

Jessica Hall
Signature


7/21/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062103

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.6	Pass
Laboratory Relative Humidity		%	10 to 70	42	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.11	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.7	Pass
	30 msec	m/sec	4.6 to 5.6	5.5	Pass
D Plane Rotation	Max	deg	99 to 114	104	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-55	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	98	Pass
Overall Results				Pass	


 Laboratory Technician



07/21/2006
 Test Date


 Approved By



Test Desc: Neck Extension
Componet ID: D062103


Test Date: 07/21/2006
Velocity: 20.06 ft/s, 6.11 m/s





Test Desc: Neck Extension
Componet ID: D062103

Test Date: 07/21/2006
Velocity: 20.06 ft/s, 6.11 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 505

Test Date 7/21/06

Technician Dave Wilcox

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.6

Record the minimum temperature 20.6

Record the maximum humidity 47%

Record the minimum humidity 42%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.71 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	52 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4090 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4090 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	70%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.



Signature

7/21/06

Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062104

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.3	Pass
Relative Humidity	%	10 to 70	44	Pass
Probe Speed	m/s	6.59 to 6.83	6.71	Pass
Peak Deflection	mm	50 to 58	52	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.1	Pass
Internal Hysteresis	%	69 to 85	70	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4090	Pass
Overall Test Results				Pass



Laboratory Technician

07/21/2006

Test Date




Approved By



Test Desc: Thorax Impact
Componet ID: D062104

Test Date: 07/21/2006
Velocity: 22.02 ft/s, 6.71 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 505

Test Date 7/20/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

☐ with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.0

Record the minimum temperature 20.8

Record the maximum humidity 48%

Record the minimum humidity 47%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 17°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	17°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	387 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	20°


Signature

7/20/06
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062107

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.8	Pass
Laboratory Relative Humidity	%	10 to 70	47	Pass
Initial Angle	deg	0 to 20	17	Pass
Return Angle	deg	+/- 8	20	Pass
Force at 45 deg	N	320 to 390	387	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician

07/20/2006
Test Date


Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 7/21/06

Technician Jessica Gall

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.6

Record the minimum temperature 20.6

Record the maximum humidity 47%

Record the minimum humidity 42%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3770 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Hall
Signature


7/21/06
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062106

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	47	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.77	Pass
Overall Test Results				Pass



Laboratory Technician

07/21/2006

Test Date




Approved By



Test Desc: Left Knee
Componet ID: D062106

Test Date: 07/21/2006
Velocity: 6.95 ft/s, 2.12 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 7/21/06

Technician Jessica Gall

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.6

Record the minimum temperature 20.6

Record the maximum humidity 47%

Record the minimum humidity 42%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3600 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.

Jessica Gall
Signature


7/21/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062105

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	47	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.60	Pass
Overall Test Results				Pass



Laboratory Technician

07/21/2006
Test Date




Approved By



Test Desc: Right Knee
Componet ID: D062105

Test Date: 07/21/2006
Velocity: 6.91 ft/s, 2.11 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #505, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	778.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.3
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.8
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	76.6
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	128.3
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	248.7
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.2
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	278.9
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	187.5
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	541.9
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	361.7
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	402.4
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	436.8

HYBRID III 5 th SN #505, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	188.7
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.3
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.1
S	HEAD BREADTH	The widest part of the head	137.1-147.3	141.4
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.8
U	HIP BREADTH	The widest part of the hip	299.7-314.9	302.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	359.1
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	84.2
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	531.7
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	853.2
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	773.2
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 505

Test Date 7/20/06

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Hall
Signature

7/21/06
Date

Describe the repair or replacement of parts:

Checked by

David Winkelbauer
Signature

7/21/06
Date

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #505, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	778.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.3
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.8
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	76.6
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	128.3
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	248.7
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.2
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	278.9
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	187.5
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	541.9
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	361.7
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	402.4
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	436.8

HYBRID III 5 th SN #505, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	188.7
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.3
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.1
S	HEAD BREADTH	The widest part of the head	137.1-147.3	141.4
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.8
U	HIP BREADTH	The widest part of the hip	299.7-314.9	302.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	359.1
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	84.2
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	531.7
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	853.2
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	773.2
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 505 Test Date 7/26/06

Technician Tim Bratz

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>20.7</u> |
| Record the minimum temperature | <u>20.6</u> |
| Record the maximum humidity | <u>48%</u> |
| Record the minimum humidity | <u>46%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	277
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-11

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

7/26/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test ID: D062151

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.6	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Peak Resultant Acceleration	G's	250 to 300	277	Pass
Peak Lateral Acceleration	G's	+/- 15	-11.4	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician

07/26/2006
Test Date



Approved By




Test Desc: Head Drop
Componet ID: D062151

Test Date: 07/26/2006
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G'S) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 505

Test Date 7/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

☒ N/A, ONLY one flexion test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 20.8

Record the minimum temperature 20.7

Record the maximum humidity 48%

Record the minimum humidity 46%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.01 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.2 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.4 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.4 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>75</u> Nm @ <u>80</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	90 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature


7/26/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062152

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.6	Pass
Laboratory Relative Humidity		%	10 to 70	47	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.01	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.2	Pass
	20 msec	m/sec	4.0 to 5.0	4.4	Pass
	30 msec	m/sec	5.8 to 7.0	6.4	Pass
D Plane Rotation	Max	deg	77 to 91	80	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	75	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	90	Pass
Overall Results				Pass	


Laboratory Technician

07/26/2006
Test Date



Approved By




Test Desc: Neck Flexion
Componet ID: D062152

Test Date: 07/26/2006
Velocity: 23.01 ft/s, 7.01 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D062152

Test Date: 07/26/2006
Velocity: 23.01 ft/s, 7.01 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 505

Test Date 7/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 20.7

Record the minimum temperature 20.6

Record the maximum humidity 48%

Record the minimum humidity 46%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.09 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.9 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.7 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.5 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-57</u> Nm @ <u>107</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	104 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature


7/26/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062153

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.6	Pass
Laboratory Relative Humidity		%	10 to 70	48	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.09	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.9	Pass
	20 msec	m/sec	3.1 to 3.9	3.7	Pass
	30 msec	m/sec	4.6 to 5.6	5.5	Pass
D Plane Rotation	Max	deg	99 to 114	107	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-57	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	104	Pass
Overall Results					Pass


Laboratory Technician

07/26/2006



Test Date


Approved By



Test Desc: Neck Extension
Componet ID: D062153


Test Date: 07/26/2006
Velocity: 19.99 ft/s, 6.09 m/s





Test Desc: Neck Extension
Componet ID: D062153

Test Date: 07/26/2006
Velocity: 19.99 ft/s, 6.09 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 505

Test Date 7/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 20.7

Record the minimum temperature 20.6

Record the maximum humidity 48%

Record the minimum humidity 46%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.73 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	52 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4160 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4145 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	69%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

7/26/06
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062154

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	20.7	Pass
Relative Humidity	%	10 to 70	48	Pass
Probe Speed	m/s	6.59 to 6.83	6.73	Pass
Peak Deflection	mm	50 to 58	52	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.2	Pass
Internal Hysteresis	%	69 to 85	69	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4145	Pass
Overall Test Results				Pass


Laboratory Technician


07/26/2006
Test Date


Approved By



Test Desc: Thorax Impact
Componet ID: D062154

Test Date: 07/26/2006
Velocity: 22.07 ft/s, 6.73 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 505

Test Date 7/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 20.7

Record the minimum temperature 20.6

Record the maximum humidity 48%

Record the minimum humidity 46%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 19°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	19°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	331 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	21°


Signature

7/26/06
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062157

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.6	Pass
Laboratory Relative Humidity	%	10 to 70	47	Pass
Initial Angle	deg	0 to 20	19	Pass
Return Angle	deg	+/- 8	21	Pass
Force at 45 deg	N	320 to 390	331	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician

07/26/2006
Test Date


Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 7/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 20.7

Record the minimum temperature 20.6

Record the maximum humidity 48%

Record the minimum humidity 46%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3780 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.

Signature



7/26/06


Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062156

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	47	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.78	Pass
Overall Test Results				Pass


Laboratory Technician


07/26/2006
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D062156

Test Date: 07/26/2006
Velocity: 6.91 ft/s, 2.11 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 7/26/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 20.7

Record the minimum temperature 20.6

Record the maximum humidity 48%

Record the minimum humidity 46%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3610 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature


7/26/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062155

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	46	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.61	Pass
Overall Test Results				Pass


Laboratory Technician


07/26/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D062155

Test Date: 07/26/2006
Velocity: 6.9 ft/s, 2.10 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 505 Test Date 8/1/06

Technician Dave Wilcox

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))

☒ N/A, ONLY one head drop performed

☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))

☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.

☒ 4. Accelerometers and their respective mounts are smooth and clean.

☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.

☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))

☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.6

Record the maximum humidity 51%

Record the minimum humidity 47%

☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	265
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	13

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

8/1/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test ID: D062251

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.7	Pass
Laboratory Relative Humidity	%	10 to 70	50	Pass
Peak Resultant Acceleration	G's	250 to 300	265	Pass
Peak Lateral Acceleration	G's	+/- 15	13.4	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass



Laboratory Technician

08/01/2006

Test Date




Approved By




Test Desc: Head Drop
Componet ID: D062251

Test Date: 08/01/2006
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G'S) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 505

Test Date 8/1/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.1</u> |
| Record the minimum temperature | <u>20.6</u> |
| Record the maximum humidity | <u>51%</u> |
| Record the minimum humidity | <u>47%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
 Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
 Record findings and actions: No Deterioration. Hardness Front 81; Back 89.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.05 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.6 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.5 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>74</u> Nm @ <u>79</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	87 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

8/1/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062252

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity		%	10 to 70	48	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.05	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.6	Pass
	30 msec	m/sec	5.8 to 7.0	6.5	Pass
D Plane Rotation	Max	deg	77 to 91	79	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	74	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	87	Pass
Overall Results					Pass


 Laboratory Technician



08/01/2006
 Test Date


 Approved By



Test Desc: Neck Flexion
Componet ID: D062252


Test Date: 08/01/2006
Velocity: 23.14 ft/s, 7.05 m/s





Test Desc: Neck Flexion
Componet ID: D062252

Test Date: 08/01/2006
Velocity: 23.14 ft/s, 7.05 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 505

Test Date 8/1/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.6

Record the maximum humidity 51%

Record the minimum humidity 47%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 81; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.16 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.6 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.3 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-55</u> Nm @ <u>105</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	101 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

8/1/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505


Test I.D: D062253

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.9	Pass
Laboratory Relative Humidity		%	10 to 70	47	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.16	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.6	Pass
	30 msec	m/sec	4.6 to 5.6	5.3	Pass
D Plane Rotation	Max	deg	99 to 114	105	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-55	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	101	Pass
Overall Results					Pass


Laboratory Technician

08/01/2006



Test Date


Approved By



Test Desc: Neck Extension
Componet ID: D062253


Test Date: 08/01/2006
Velocity: 20.2 ft/s, 6.16 m/s





Test Desc: Neck Extension
Componet ID: D062253

Test Date: 08/01/2006
Velocity: 20.2 ft/s, 6.16 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 505

Test Date 8/2/06

Technician Dave Wilcox

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 51%

Record the minimum humidity 49%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.61 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	3920 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	3909 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	69%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.



Signature

8/2/06

Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062254


Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.3	Pass
Relative Humidity	%	10 to 70	51	Pass
Probe Speed	m/s	6.59 to 6.83	6.61	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	3.9	Pass
Internal Hysteresis	%	69 to 85	69	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	3909	Pass
Overall Test Results				Pass



Laboratory Technician

08/02/2006

Test Date




Approved By



Test Desc: Thorax Impact
Componet ID: D062254

Test Date: 08/02/2006
Velocity: 21.67 ft/s, 6.61 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 505

Test Date 8/1/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

☐ with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.6

Record the maximum humidity 51%

Record the minimum humidity 47%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 19°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	19°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	360 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	21°


Signature

8/1/06
Date


MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062257

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.0	Pass
Laboratory Relative Humidity	%	10 to 70	51	Pass
Initial Angle	deg	0 to 20	19	Pass
Return Angle	deg	+/- 8	21	Pass
Force at 45 deg	N	320 to 390	360	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

08/01/2006
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 8/1/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.6

Record the maximum humidity 51%

Record the minimum humidity 47%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3800 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

8/1/06
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 505

Test I.D: D062256

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.6	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.80	Pass
Overall Test Results				Pass


Laboratory Technician



Approved By

08/01/2006
Test Date



Test Desc: Left Knee
Componet ID: D062256

Test Date: 08/01/2006
Velocity: 6.9 ft/s, 2.10 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 505

Test Date 8/1/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.1

Record the minimum temperature 20.6

Record the maximum humidity 51%

Record the minimum humidity 47%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3630 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

8/1/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 505

Test I.D: D062255

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.6	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.63	Pass
Overall Test Results				Pass


Laboratory Technician


08/01/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D062255

Test Date: 08/01/2006
Velocity: 6.91 ft/s, 2.11 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #505, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	778.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.3
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.8
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	76.6
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	128.3
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	248.7
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.2
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	278.9
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	187.5
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	541.9
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	361.7
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	402.4
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	436.8

HYBRID III 5 th SN #505, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	188.7
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	223.3
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.1
S	HEAD BREADTH	The widest part of the head	137.1-147.3	141.4
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.8
U	HIP BREADTH	The widest part of the hip	299.7-314.9	302.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	359.1
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	84.2
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	531.7
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	853.2
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	773.2
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 505

Test Date 7/28/06

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Hall
Signature

8/02/06
Date

Describe the repair or replacement of parts:

Checked by
David Winkelbauer
Signature

8/02/06
Date

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #507, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	781.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	455.4
C	H-POINT HEIGHT	Reference	81.3-86.3	84.0
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	148.0
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	79.2
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	130.3
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.8
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	280.1
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	201.0
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	544.1
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	356.5
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	394.0
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.2

HYBRID III 5 th SN #507, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	186.7
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	222.0
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.3
S	HEAD BREADTH	The widest part of the head	137.1-147.3	138.4
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	178.1
U	HIP BREADTH	The widest part of the hip	299.7-314.9	309.6
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	363.9
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	89.0
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	539.4
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	863.7
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	787.1
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	342.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	168.0

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 507

Test Date 8/25/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))

☒ N/A, ONLY one head drop performed

☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))

☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.

☒ 4. Accelerometers and their respective mounts are smooth and clean.

☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.

☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))

☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))

Record the maximum temperature 22.0

Record the minimum temperature 21.3

Record the maximum humidity 49%

Record the minimum humidity 48%

☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistant within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	260
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	6

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature


8/25/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 507

Test ID: D062571

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	22.0	Pass
Laboratory Relative Humidity	%	10 to 70	49	Pass
Peak Resultant Acceleration	G's	250 to 300	260	Pass
Peak Lateral Acceleration	G's	+/- 15	6.5	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician



08/25/2006
Test Date


Approved By



Test Desc: Head Impact
Componet ID: D062571

Test Date: 08/25/2006
Velocity: 0 ft/s, 0 m/s



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 507 Test Date 8/25/06

Technician Dave Wilcox

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>22.0</u> |
| Record the minimum temperature | <u>21.3</u> |
| Record the maximum humidity | <u>49%</u> |
| Record the minimum humidity | <u>48%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
Record findings and actions: No Deterioration. Hardness Front 89; Back 90.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.03 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.3 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.5 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.4 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>76</u> Nm @ <u>78</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	84 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

8/25/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D062572


Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.9	Pass
Laboratory Relative Humidity		%	10 to 70	49	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.03	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.3	Pass
	20 msec	m/sec	4.0 to 5.0	4.5	Pass
	30 msec	m/sec	5.8 to 7.0	6.4	Pass
D Plane Rotation	Max	deg	77 to 91	78	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	76	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	84	Pass
Overall Results				Pass	



Laboratory Technician

08/25/2006

Test Date




Approved By




Test Desc: Neck Flexion
Componet ID: D062572

Test Date: 08/25/2006
Velocity: 23.08 ft/s, 7.03 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D062572

Test Date: 08/25/2006
Velocity: 23.08 ft/s, 7.03 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 507

Test Date 8/25/06

Technician Dave Wilcox

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 22.0

Record the minimum temperature 21.3

Record the maximum humidity 49%

Record the minimum humidity 48%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.18 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.7 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.4 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-56</u> Nm @ <u>106</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	101 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

8/25/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D062573

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.8	Pass
Laboratory Relative Humidity		%	10 to 70	49	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.18	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.7	Pass
	30 msec	m/sec	4.6 to 5.6	5.4	Pass
D Plane Rotation	Max	deg	99 to 114	106	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-56	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	101	Pass
Overall Results					Pass



Laboratory Technician

08/25/2006

Test Date




Approved By




Test Desc: Neck Extension
Componet ID: D062573

Test Date: 08/25/2006
Velocity: 20.29 ft/s, 6.18 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Extension
Componet ID: D062573

Test Date: 08/25/2006
Velocity: 20.29 ft/s, 6.18 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 507

Test Date 8/25/06

Technician Dave Wilcox

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 22.0

Record the minimum temperature 21.3

Record the maximum humidity 49%

Record the minimum humidity 48%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.75 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	52 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4040 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4015 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	70%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.



Signature

8/25/06

Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D062574

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.3	Pass
Relative Humidity	%	10 to 70	49	Pass
Probe Speed	m/s	6.59 to 6.83	6.75	Pass
Peak Deflection	mm	50 to 58	52	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.0	Pass
Internal Hysteresis	%	69 to 85	70	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4015	Pass
Overall Test Results				Pass



Laboratory Technician

08/25/2006

Test Date




Approved By



Test Desc: Thorax Impact
Componet ID: D062574

Test Date: 08/25/2006
Velocity: 22.13 ft/s, 6.75 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 507

Test Date 8/25/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
☐ with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 22.0

Record the minimum temperature 21.3

Record the maximum humidity 49%

Record the minimum humidity 48%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 18°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	18°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	373 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	18°


Signature

8/25/06
Date


MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D062577

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.9	Pass
Laboratory Relative Humidity	%	10 to 70	49	Pass
Initial Angle	deg	0 to 20	18	Pass
Return Angle	deg	+/- 8	18	Pass
Force at 45 deg	N	320 to 390	373	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

08/25/2006
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 507

Test Date 8/25/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 22.0

Record the minimum temperature 21.3

Record the maximum humidity 49%

Record the minimum humidity 48%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3700 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.

Signature



8/25/06


Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D062576

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.70	Pass
Overall Test Results				Pass


Laboratory Technician


08/25/2006
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D062576

Test Date: 08/25/2006
Velocity: 6.92 ft/s, 2.11 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 507

Test Date 8/25/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 22.0

Record the minimum temperature 21.3

Record the maximum humidity 49%

Record the minimum humidity 48%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3650 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature


8/25/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 507

Test I.D: D062575

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.65	Pass
Overall Test Results				Pass


Laboratory Technician


08/25/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D062575

Test Date: 08/25/2006
Velocity: 6.88 ft/s, 2.10 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 507 Test Date 9/29/06

Technician Dave Wilcox

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.4</u> |
| Record the minimum temperature | <u>21.0</u> |
| Record the maximum humidity | <u>36%</u> |
| Record the minimum humidity | <u>34%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	252
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-9

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

9/29/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test ID: D062911


Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.2	Pass
Laboratory Relative Humidity	%	10 to 70	34	Pass
Peak Resultant Acceleration	G's	250 to 300	252	Pass
Peak Lateral Acceleration	G's	+/- 15	-8.7	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass



Laboratory Technician

09/29/2006

Test Date




Approved By




Test Desc: Head Drop
Componet ID: D062911

Test Date: 09/29/2006
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G'S) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 507 Test Date 9/29/06

Technician Justino Diaz

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.4</u> |
| Record the minimum temperature | <u>21.0</u> |
| Record the maximum humidity | <u>36%</u> |
| Record the minimum humidity | <u>34%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
Record findings and actions: No Deterioration. Hardness Front 86; Back 88.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.12 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.6 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.4 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>77</u> Nm @ <u>80</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	85 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

9/29/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D062912

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.4	Pass
Laboratory Relative Humidity		%	10 to 70	36	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.12	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.6	Pass
	30 msec	m/sec	5.8 to 7.0	6.4	Pass
D Plane Rotation	Max	deg	77 to 91	80	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	77	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	85	Pass
Overall Results				Pass	


Laboratory Technician

09/29/2006
Test Date



Approved By




Test Desc: Neck Flexion
Componet ID: D062912

Test Date: 09/29/2006
Velocity: 23.35 ft/s, 7.12 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D062912

Test Date: 09/29/2006
Velocity: 23.35 ft/s, 7.12 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 507

Test Date 9/29/06

Technician Justino Diaz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

 1. It has been at least 30 minutes since the last extension test. (572.137(q))

X N/A, ONLY one extension test performed

X 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

X 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.4

Record the minimum temperature 21.0

Record the maximum humidity 36%

Record the minimum humidity 34%

X 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

X 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 86; Back 88.

X 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.18 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.4 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.0 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-56</u> Nm @ <u>107</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	102 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature


9/29/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D062913

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.0	Pass
Laboratory Relative Humidity		%	10 to 70	35	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.18	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.4	Pass
	30 msec	m/sec	4.6 to 5.6	5.0	Pass
D Plane Rotation	Max	deg	99 to 114	107	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-56	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	102	Pass
Overall Results				Pass	


Laboratory Technician

09/29/2006

Test Date



Approved By




Test Desc: Neck Extension
Componet ID: D062913

Test Date: 09/29/2006
Velocity: 20.29 ft/s, 6.18 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Extension
Componet ID: D062913

Test Date: 09/29/2006
Velocity: 20.29 ft/s, 6.18 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 507

Test Date 9/29/06

Technician Dave Wilcox

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

X N/A, ONLY one thorax impact test performed

X 2. The test fixture conforms to the specifications in Figure 11B.

X 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

X 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.4

Record the minimum temperature 21.0

Record the maximum humidity 36%

Record the minimum humidity 34%

X 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

X - No damage

 - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

 - The following repairs or replacement was performed. Record _____

X 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

X 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.64 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	50 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4193 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4193 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	69%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

9/29/06
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D062914

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.1	Pass
Relative Humidity	%	10 to 70	35	Pass
Probe Speed	m/s	6.59 to 6.83	6.64	Pass
Peak Deflection	mm	50 to 58	50	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.2	Pass
Internal Hysteresis	%	69 to 85	69	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4193	Pass
Overall Test Results				Pass



Laboratory Technician

09/29/2006

Test Date




Approved By



Test Desc: Thorax Impact
Componet ID: D062914

Test Date: 09/29/2006
Velocity: 21.78 ft/s, 6.64 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 507

Test Date 9/29/06

Technician Justino Diaz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

X N/A, ONLY one thorax impact test performed

X 2. The test fixture conforms to the specifications in Figure 13B.

X 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

 with legs below the femurs.

X without legs below the femurs.

X 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.4

Record the minimum temperature 21.0

Record the maximum humidity 36%

Record the minimum humidity 34%

X 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

X 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

X 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

X 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

X 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

X 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

X 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 19°

X 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	19°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	384 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	20°


Signature

9/29/06
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 507

Test I.D: D062917

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	35	Pass
Initial Angle	deg	0 to 20	19	Pass
Return Angle	deg	+/- 8	20	Pass
Force at 45 deg	N	320 to 390	384	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician

09/29/2006
Test Date


Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 507

Test Date 9/29/06

Technician Justino Diaz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.4

Record the minimum temperature 21.0

Record the maximum humidity 36%

Record the minimum humidity 34%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))


X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3560 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature


9/29/06
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 507

Test I.D: D062916

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.2	Pass
Laboratory Relative Humidity	%	10 to 70	34	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.56	Pass
Overall Test Results				Pass


Laboratory Technician


09/29/2006
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D062916

Test Date: 09/29/2006
Velocity: 6.95 ft/s, 2.12 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 507

Test Date 9/29/06

Technician Justino Diaz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

 X N/A, ONLY one knee impact test performed

X 2. The test fixture conforms to the specifications in Figure 14B.

X 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

X 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.4

Record the minimum temperature 21.0

Record the maximum humidity 36%

Record the minimum humidity 34%

X 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

X 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

X 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

X 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

X 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))


X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.09 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3590 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

9/29/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 507

Test I.D: D062915

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.2	Pass
Laboratory Relative Humidity	%	10 to 70	34	Pass
Probe Speed	m/sec	2.07 to 2.13	2.09	Pass
Maximum Force	kN	3.45 to 4.06	3.59	Pass
Overall Test Results				Pass


Laboratory Technician


09/29/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D062915

Test Date: 09/29/2006
Velocity: 6.87 ft/s, 2.09 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #507, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	781.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	455.4
C	H-POINT HEIGHT	Reference	81.3-86.3	84.0
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	148.0
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	79.2
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	130.3
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.8
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	280.1
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	201.0
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	544.1
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	356.5
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	394.0
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.2

HYBRID III 5 th SN #507, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	186.7
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	222.0
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.3
S	HEAD BREADTH	The widest part of the head	137.1-147.3	138.4
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	178.1
U	HIP BREADTH	The widest part of the hip	299.7-314.9	309.6
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	363.9
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	89.0
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	539.4
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	863.7
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	787.1
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	342.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	168.0

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 507

Test Date 9/14/06

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Hall
Signature

9/29/06
Date

Describe the repair or replacement of parts:

Checked by

David Winkelbauer
Signature

9/29/06
Date

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #511, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	782.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	455.8
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.3
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	75.7
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	130.9
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	250.5
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	45.2
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	282.7
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	196.3
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	540.1
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	358.1
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	406.3
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.4

HYBRID III 5 th SN #511, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	186.4
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	222.3
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	476.3
S	HEAD BREADTH	The widest part of the head	137.1-147.3	142.9
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.5
U	HIP BREADTH	The widest part of the hip	299.7-314.9	299.9
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	361.2
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	83.7
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	539.4
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	851.9
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	762.4
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 511 Test Date 9/13/06

Technician Tim Bratz

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.6</u> |
| Record the minimum temperature | <u>21.5</u> |
| Record the maximum humidity | <u>51%</u> |
| Record the minimum humidity | <u>49%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	274
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-6

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

9/13/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 511

Test ID: D062791

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	50	Pass
Peak Resultant Acceleration	G's	250 to 300	274	Pass
Peak Lateral Acceleration	G's	+/- 15	-5.6	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician

09/13/2006
Test Date



Approved By




Test Desc: Head Drop
Componet ID: D062791

Test Date: 09/13/2006
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G'S) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 511

Test Date 9/14/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

☒ N/A, ONLY one flexion test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 52%

Record the minimum humidity 46%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 89.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.10 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.5 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.3 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>78</u> Nm @ <u>79</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	86 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

9/14/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 511

Test I.D: D062792

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.3	Pass
Laboratory Relative Humidity		%	10 to 70	52	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.10	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.5	Pass
	30 msec	m/sec	5.8 to 7.0	6.3	Pass
D Plane Rotation	Max	deg	77 to 91	79	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	78	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	86	Pass
Overall Results				Pass	


Laboratory Technician

09/14/2006
Test Date



Approved By




Test Desc: Neck Flexion
Componet ID: D062792

Test Date: 09/14/2006
Velocity: 23.3 ft/s, 7.10 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D062792

Test Date: 09/14/2006
Velocity: 23.3 ft/s, 7.10 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 511 Test Date 9/14/06

Technician Tim Bratz

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))
☒ N/A, ONLY one extension test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature	<u>21.3</u>
Record the minimum temperature	<u>20.9</u>
Record the maximum humidity	<u>52%</u>
Record the minimum humidity	<u>46%</u>
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
Record findings and actions: No Deterioration. Hardness Front 89; Back 89.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.19 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.6 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.1 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-58</u> Nm @ <u>109</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	101 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

9/14/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 511

Test I.D: D062793

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.3	Pass
Laboratory Relative Humidity		%	10 to 70	52	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.19	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.6	Pass
	30 msec	m/sec	4.6 to 5.6	5.1	Pass
D Plane Rotation	Max	deg	99 to 114	109	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-58	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	101	Pass
Overall Results					Pass


 Laboratory Technician

09/14/2006
 Test Date



 Approved By




Test Desc: Neck Extension
Componet ID: D062793

Test Date: 09/14/2006
Velocity: 20.3 ft/s, 6.19 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Extension
Componet ID: D062793

Test Date: 09/14/2006
Velocity: 20.3 ft/s, 6.19 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 511

Test Date 9/14/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 52%

Record the minimum humidity 46%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.81 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	54 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4160 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4076 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	70%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature


9/14/06
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE


ATD Serial No: 511

Test I.D: D062794

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	20.9	Pass
Relative Humidity	%	10 to 70	46	Pass
Probe Speed	m/s	6.59 to 6.83	6.81	Pass
Peak Deflection	mm	50 to 58	54	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.2	Pass
Internal Hysteresis	%	69 to 85	70	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4076	Pass
Overall Test Results				Pass


Laboratory Technician


09/14/2006
Test Date


Approved By



Test Desc: Thorax Impact
Componet ID: D062794

Test Date: 09/14/2006
Velocity: 22.35 ft/s, 6.81 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 511

Test Date 9/13/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

☐ with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.6

Record the minimum temperature 21.5

Record the maximum humidity 51%

Record the minimum humidity 49%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 15°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	15°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	385 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	17°


Signature


9/13/06
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 511

Test I.D: D062797

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	50	Pass
Initial Angle	deg	0 to 20	15	Pass
Return Angle	deg	+/- 8	17	Pass
Force at 45 deg	N	320 to 390	385	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician

09/13/2006
Test Date


Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 511

Test Date 9/14/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 52%

Record the minimum humidity 46%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3520 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.

Signature



9/14/06

Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 511

Test I.D: D062796

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.3	Pass
Laboratory Relative Humidity	%	10 to 70	46	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.52	Pass
Overall Test Results				Pass


Laboratory Technician


09/14/2006
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D062796

Test Date: 09/14/2006
Velocity: 6.89 ft/s, 2.10 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 511

Test Date 9/14/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 52%

Record the minimum humidity 46%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3630 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

9/14/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 511

Test I.D: D062795

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.9	Pass
Laboratory Relative Humidity	%	10 to 70	46	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.63	Pass
Overall Test Results				Pass


Laboratory Technician


09/14/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D062795

Test Date: 09/14/2006
Velocity: 6.9 ft/s, 2.10 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 511 Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.8</u> |
| Record the minimum temperature | <u>21.2</u> |
| Record the maximum humidity | <u>49%</u> |
| Record the minimum humidity | <u>38%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	253
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	12

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

9/18/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 511

Test ID: D062831

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Peak Resultant Acceleration	G's	250 to 300	253	Pass
Peak Lateral Acceleration	G's	+/- 15	11.6	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results			Pass	


Laboratory Technician

09/18/2006
Test Date



Approved By




Test Desc: Head Drop
Componet ID: D062831

Test Date: 09/18/2006
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G'S) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 511

Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.8</u> |
| Record the minimum temperature | <u>21.2</u> |
| Record the maximum humidity | <u>49%</u> |
| Record the minimum humidity | <u>38%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
 Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
 Record findings and actions: No Deterioration. Hardness Front 89; Back 89.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.07 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.3 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.5 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.4 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>77</u> Nm @ <u>78</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	86 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

9/18/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 511

Test I.D: D062832

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.7	Pass
Laboratory Relative Humidity		%	10 to 70	41	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.07	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.3	Pass
	20 msec	m/sec	4.0 to 5.0	4.5	Pass
	30 msec	m/sec	5.8 to 7.0	6.4	Pass
D Plane Rotation	Max	deg	77 to 91	78	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	77	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	86	Pass
Overall Results					Pass


 Laboratory Technician



09/18/2006
 Test Date


 Approved By



Test Desc: Neck Flexion
Componet ID: D062832


Test Date: 09/18/2006
Velocity: 23.19 ft/s, 7.07 m/s





Test Desc: Neck Flexion
Componet ID: D062832

Test Date: 09/18/2006
Velocity: 23.19 ft/s, 7.07 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 511 Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))
☒ N/A, ONLY one extension test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature	<u>21.8</u>
Record the minimum temperature	<u>21.2</u>
Record the maximum humidity	<u>49%</u>
Record the minimum humidity	<u>38%</u>
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
Record findings and actions: No Deterioration. Hardness Front 89; Back 89.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.14 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.6 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.2 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-55</u> Nm @ <u>107</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	105 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

9/18/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 507

Test I.D: D062833

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.7	Pass
Laboratory Relative Humidity		%	10 to 70	41	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.14	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.6	Pass
	30 msec	m/sec	4.6 to 5.6	5.2	Pass
D Plane Rotation	Max	deg	99 to 114	107	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-55	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	105	Pass
Overall Results					Pass


 Laboratory Technician



09/18/2006
 Test Date


 Approved By



Test Desc: Neck Extension
Componet ID: D062833


Test Date: 09/18/2006
Velocity: 20.14 ft/s, 6.14 m/s





Test Desc: Neck Extension
Componet ID: D062833

Test Date: 09/18/2006
Velocity: 20.14 ft/s, 6.14 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 511

Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.8

Record the minimum temperature 21.2

Record the maximum humidity 49%

Record the minimum humidity 38%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.65 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	52 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4196 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4196 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	69%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

9/18/06
Date


MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 511

Test I.D: D062834

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.2	Pass
Relative Humidity	%	10 to 70	38	Pass
Probe Speed	m/s	6.59 to 6.83	6.65	Pass
Peak Deflection	mm	50 to 58	52	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.2	Pass
Internal Hysteresis	%	69 to 85	69	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4196	Pass
Overall Test Results				Pass


Laboratory Technician



Approved By

09/18/2006
Test Date



Test Desc: Thorax Impact
Componet ID: D062834

Test Date: 09/18/2006
Velocity: 21.83 ft/s, 6.65 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 511 Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

☐ with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.8

Record the minimum temperature 21.2

Record the maximum humidity 49%

Record the minimum humidity 38%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 17°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	17°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	323 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	18°


Signature

9/18/06
Date


MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 511

Test I.D: D062837

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	43	Pass
Initial Angle	deg	0 to 20	17	Pass
Return Angle	deg	+/- 8	18	Pass
Force at 45 deg	N	320 to 390	323	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

09/18/2006
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 511

Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.8

Record the minimum temperature 21.2

Record the maximum humidity 49%

Record the minimum humidity 38%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))


X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3510 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

9/18/06

Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 511

Test I.D: D062836

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	45	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.51	Pass
Overall Test Results				Pass


Laboratory Technician


09/18/2006
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D062836

Test Date: 09/18/2006
Velocity: 6.92 ft/s, 2.11 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 511

Test Date 9/18/06

Technician Tim Bratz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

X N/A, ONLY one knee impact test performed

X 2. The test fixture conforms to the specifications in Figure 14B.

X 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

X 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.8

Record the minimum temperature 21.2

Record the maximum humidity 49%

Record the minimum humidity 38%

X 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

X 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

X 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

X 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

X 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3500 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

9/18/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 511

Test I.D: D062835

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	49	Pass
Probe Speed	m/sec	2.07 to 2.13	2.11	Pass
Maximum Force	kN	3.45 to 4.06	3.50	Pass
Overall Test Results				Pass


Laboratory Technician


09/18/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D062835

Test Date: 09/18/2006
Velocity: 6.91 ft/s, 2.11 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #511, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	782.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	455.8
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.3
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	75.7
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	130.9
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	250.5
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	45.2
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	282.7
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	196.3
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	540.1
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	358.1
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	406.3
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.4

HYBRID III 5 th SN #511, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	186.4
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	222.3
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	476.3
S	HEAD BREADTH	The widest part of the head	137.1-147.3	142.9
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.5
U	HIP BREADTH	The widest part of the hip	299.7-314.9	299.9
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	361.2
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	83.7
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	539.4
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	851.9
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	762.4
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	340.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	165.0

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 511

Test Date 9/15/06

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Hall
Signature

9/18/06
Date

Describe the repair or replacement of parts:

Checked by

David Winkelbauer
Signature

9/18/06
Date

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #510, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	786.2
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.0
C	H-POINT HEIGHT	Reference	81.3-86.3	84.1
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	148.3
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	82.7
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	133.9
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249.6
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.0
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	278.5
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	202.1
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	543.6
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	358.5
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	397.0
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.2

HYBRID III 5 th SN #510, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	181.0
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	221.4
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	482.0
S	HEAD BREADTH	The widest part of the head	137.1-147.3	138.6
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.9
U	HIP BREADTH	The widest part of the hip	299.7-314.9	301.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	351.4
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	79.0
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	539.5
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	876.4
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	788.3
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	334.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	168.0

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 510 Test Date 9/13/06

Technician Tim Bratz

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.6</u> |
| Record the minimum temperature | <u>21.5</u> |
| Record the maximum humidity | <u>51%</u> |
| Record the minimum humidity | <u>49%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	270
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-10

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

9/13/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 510

Test ID: D062781

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.5	Pass
Laboratory Relative Humidity	%	10 to 70	51	Pass
Peak Resultant Acceleration	G's	250 to 300	270	Pass
Peak Lateral Acceleration	G's	+/- 15	-10.4	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician

09/13/2006
Test Date



Approved By




Test Desc: Head Drop
Componet ID: D062781

Test Date: 09/13/2006
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G'S) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 510

Test Date 9/13/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

☒ N/A, ONLY one flexion test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.6

Record the minimum temperature 21.5

Record the maximum humidity 51%

Record the minimum humidity 49%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.13 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.7 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.6 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>74</u> Nm @ <u>85</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	86 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

9/13/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 510

Test I.D: D062782

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.6	Pass
Laboratory Relative Humidity		%	10 to 70	49	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.13	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.7	Pass
	30 msec	m/sec	5.8 to 7.0	6.6	Pass
D Plane Rotation	Max	deg	77 to 91	85	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	74	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	86	Pass
Overall Results					Pass


Laboratory Technician

09/13/2006
Test Date



Approved By




Test Desc: Neck Flexion
Componet ID: D062782

Test Date: 09/13/2006
Velocity: 23.38 ft/s, 7.13 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D062782

Test Date: 09/13/2006
Velocity: 23.38 ft/s, 7.13 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 510

Test Date 9/14/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 55%

Record the minimum humidity 46%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.18 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.9 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.7 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.2 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-57</u> Nm @ <u>107</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	98 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

9/14/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510


Test I.D: D062783

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.2	Pass
Laboratory Relative Humidity		%	10 to 70	55	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.18	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.9	Pass
	20 msec	m/sec	3.1 to 3.9	3.7	Pass
	30 msec	m/sec	4.6 to 5.6	5.2	Pass
D Plane Rotation	Max	deg	99 to 114	107	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-57	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	98	Pass
Overall Results					Pass


Laboratory Technician

09/14/2006



Test Date


Approved By



Test Desc: Neck Extension
Componet ID: D062783


Test Date: 09/14/2006
Velocity: 20.29 ft/s, 6.18 m/s





Test Desc: Neck Extension
Componet ID: D062783

Test Date: 09/14/2006
Velocity: 20.29 ft/s, 6.18 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 510

Test Date 9/14/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 55%

Record the minimum humidity 46%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.61 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4089 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4089 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	69%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

9/14/06
Date


MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D062784

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.3	Pass
Relative Humidity	%	10 to 70	52	Pass
Probe Speed	m/s	6.59 to 6.83	6.61	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.1	Pass
Internal Hysteresis	%	69 to 85	69	Pass
Peak Force 18 mm - 50 mm	N	< 4600 N	4089	Pass
Overall Test Results				Pass


Laboratory Technician



Approved By

09/14/2006
Test Date



Test Desc: Thorax Impact
Componet ID: D062784

Test Date: 09/14/2006
Velocity: 21.7 ft/s, 6.61 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 510

Test Date 9/13/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 13B.

☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

☐ with legs below the femurs.

☒ without legs below the femurs.

☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 21.6

Record the minimum temperature 21.5

Record the maximum humidity 51%

Record the minimum humidity 49%

☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 12°

☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	12°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	373 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	15°


Signature

9/13/06
Date


MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D062787

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.5	Pass
Laboratory Relative Humidity	%	10 to 70	51	Pass
Initial Angle	deg	0 to 20	12	Pass
Return Angle	deg	+/- 8	15	Pass
Force at 45 deg	N	320 to 390	373	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

09/13/2006
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 510

Test Date 9/14/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 55%

Record the minimum humidity 46%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3490 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

9/14/06
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 510

Test I.D: D062786

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.9	Pass
Laboratory Relative Humidity	%	10 to 70	46	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.49	Pass
Overall Test Results				Pass


Laboratory Technician


09/14/2006
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D062786

Test Date: 09/14/2006
Velocity: 6.95 ft/s, 2.12 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 510

Test Date 9/14/06

Technician Tim Bratz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.3

Record the minimum temperature 20.9

Record the maximum humidity 55%

Record the minimum humidity 46%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3680 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

9/14/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 510

Test I.D: D062785

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.9	Pass
Laboratory Relative Humidity	%	10 to 70	46	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.68	Pass
Overall Test Results				Pass


Laboratory Technician


09/14/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D062785

Test Date: 09/14/2006
Velocity: 6.88 ft/s, 2.10 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 510 Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>22.0</u> |
| Record the minimum temperature | <u>21.6</u> |
| Record the maximum humidity | <u>50%</u> |
| Record the minimum humidity | <u>40%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	255
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-3

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

9/18/06
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 510

Test ID: D062821

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	22.0	Pass
Laboratory Relative Humidity	%	10 to 70	49	Pass
Peak Resultant Acceleration	G's	250 to 300	255	Pass
Peak Lateral Acceleration	G's	+/- 15	-3.4	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician



09/18/2006
Test Date


Approved By



Test Desc: Head Drop
Componet ID: D062821

Test Date: 09/18/2006
Velocity: 0 ft/s, 0 m/s



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 510 Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>22.0</u> |
| Record the minimum temperature | <u>21.6</u> |
| Record the maximum humidity | <u>50%</u> |
| Record the minimum humidity | <u>40%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
Record findings and actions: No Deterioration. Hardness Front 89; Back 90.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.07 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.2 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.3 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.1 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>73</u> Nm @ <u>81</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	90 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

9/18/06
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D062822

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.6	Pass
Laboratory Relative Humidity		%	10 to 70	40	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.07	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.2	Pass
	20 msec	m/sec	4.0 to 5.0	4.3	Pass
	30 msec	m/sec	5.8 to 7.0	6.1	Pass
D Plane Rotation	Max	deg	77 to 91	81	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	73	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	90	Pass
Overall Results					Pass


Laboratory Technician



09/18/2006
Test Date


Approved By



Test Desc: Neck Flexion
Componet ID: D062822


Test Date: 09/18/2006
Velocity: 23.2 ft/s, 7.07 m/s





Test Desc: Neck Flexion
Componet ID: D062822

Test Date: 09/18/2006
Velocity: 23.2 ft/s, 7.07 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 510 Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))
☒ N/A, ONLY one extension test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>22.0</u> |
| Record the minimum temperature | <u>21.6</u> |
| Record the maximum humidity | <u>50%</u> |
| Record the minimum humidity | <u>40%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
Record findings and actions: No Deterioration. Hardness Front 89; Back 90.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.12 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.6 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.2 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-54</u> Nm @ <u>108</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	105 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

9/18/06
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 510

Test I.D: D062823

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.9	Pass
Laboratory Relative Humidity		%	10 to 70	40	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.12	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.6	Pass
	30 msec	m/sec	4.6 to 5.6	5.2	Pass
D Plane Rotation	Max	deg	99 to 114	108	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-54	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	105	Pass
Overall Results					Pass


 Laboratory Technician



09/18/2006
 Test Date


 Approved By



Test Desc: Neck Extension
Componet ID: D062823


Test Date: 09/18/2006
Velocity: 20.08 ft/s, 6.12 m/s





Test Desc: Neck Extension
Componet ID: D062823

Test Date: 09/18/2006
Velocity: 20.08 ft/s, 6.12 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 510

Test Date 9/18/06

Technician Dave Wilcox

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

X N/A, ONLY one thorax impact test performed

X 2. The test fixture conforms to the specifications in Figure 11B.

X 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

X 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 22.0

Record the minimum temperature 21.6

Record the maximum humidity 50%

Record the minimum humidity 40%

X 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

X - No damage

 - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

 - The following repairs or replacement was performed. Record _____

X 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

X 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.67 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4100 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4180 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	69%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.



Signature

9/18/06

Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D062824


Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.6	Pass
Relative Humidity	%	10 to 70	50	Pass
Probe Speed	m/s	6.59 to 6.83	6.67	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.1	Pass
Internal Hysteresis	%	69 to 85	69	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4180	Pass
Overall Test Results				Pass



Laboratory Technician

09/18/2006

Test Date




Approved By



Test Desc: Thorax Impact
Componet ID: D062824

Test Date: 09/18/2006
Velocity: 21.89 ft/s, 6.67 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 510

Test Date 9/18/06

Technician Tim Bratz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))

X N/A, ONLY one thorax impact test performed

X 2. The test fixture conforms to the specifications in Figure 13B.

X 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).

 with legs below the femurs.

X without legs below the femurs.

X 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))

Record the maximum temperature 22.0

Record the minimum temperature 21.6

Record the maximum humidity 50%

Record the minimum humidity 40%

X 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))

X 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))

X 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))

X 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

X 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))

X 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))

X 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))

Record reference plane angle (max. allowed 20°) 17°

X 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	17°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	359 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	19°


Signature

9/18/06
Date


MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D062827

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.9	Pass
Laboratory Relative Humidity	%	10 to 70	40	Pass
Initial Angle	deg	0 to 20	17	Pass
Return Angle	deg	+/- 8	19	Pass
Force at 45 deg	N	320 to 390	359	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician


Approved By

09/18/2006
Test Date

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 510

Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 22.0

Record the minimum temperature 21.6

Record the maximum humidity 50%

Record the minimum humidity 40%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3530 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature


9/18/06
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510


Test I.D: D062826

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Probe Speed	m/sec	2.07 to 2.13	2.10	Pass
Maximum Force	kN	3.45 to 4.06	3.53	Pass
Overall Test Results				Pass


Laboratory Technician

09/18/2006


Test Date


Approved By



Test Desc: Left Knee
Componet ID: D062826

Test Date: 09/18/2006
Velocity: 6.89 ft/s, 2.10 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 510

Test Date 9/18/06

Technician Tim Bratz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 22.0

Record the minimum temperature 21.6

Record the maximum humidity 50%

Record the minimum humidity 40%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.09 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3860 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

9/18/06
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D062825

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	48	Pass
Probe Speed	m/sec	2.07 to 2.13	2.09	Pass
Maximum Force	kN	3.45 to 4.06	3.86	Pass
Overall Test Results				Pass


Laboratory Technician


09/18/2006
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D062825

Test Date: 09/18/2006
Velocity: 6.87 ft/s, 2.09 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #510, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	786.2
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.0
C	H-POINT HEIGHT	Reference	81.3-86.3	84.1
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	148.3
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	82.7
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	133.9
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249.6
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.0
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	278.5
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	202.1
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	543.6
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	358.5
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	397.0
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.2

HYBRID III 5 th SN #510, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	181.0
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	221.4
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	482.0
S	HEAD BREADTH	The widest part of the head	137.1-147.3	138.6
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.9
U	HIP BREADTH	The widest part of the hip	299.7-314.9	301.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	351.4
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	79.0
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	539.5
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	876.4
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	788.3
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	334.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	168.0

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 510

Test Date 9/15/06

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Hall
Signature

9/18/06
Date

Describe the repair or replacement of parts:

Checked by

David Winkelbauer
Signature

9/18/06
Date

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #124, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	785.0
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	455.1
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.6
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	83.0
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	125.6
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	245.9
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	45.0
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	296.1
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	192.3
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	540.2
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	345.6
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	395.8
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.5

HYBRID III 5 th SN #124, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	176.0
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	219.4
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.0
S	HEAD BREADTH	The widest part of the head	137.1-147.3	138.6
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	186.2
U	HIP BREADTH	The widest part of the hip	299.7-314.9	310.7
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	354.9
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	82.0
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	547.1
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	881.0
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	786.3
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	357.4
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	169.8

DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 124 Test Date 1/30/07

Technician Dave Wilcox

☒ Pretest calibration
☐ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

- ☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
☒ N/A, ONLY one head drop performed
- ☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
- ☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
- ☒ 4. Accelerometers and their respective mounts are smooth and clean.
- ☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
- ☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
- ☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.2</u> |
| Record the minimum temperature | <u>21.0</u> |
| Record the maximum humidity | <u>17%</u> |
| Record the minimum humidity | <u>14%</u> |
- ☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage.
- ☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm

Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	267
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	6

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

1/30/07
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test ID: D07281

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.0	Pass
Laboratory Relative Humidity	%	10 to 70	14	Pass
Peak Resultant Acceleration	G's	250 to 300	267	Pass
Peak Lateral Acceleration	G's	+/- 15	6	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass



Laboratory Technician

01/30/2007

Test Date




Approved By




Test Desc: Head Drop
Componet ID: D07281

Test Date: 01/30/2007
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G's) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 124

Test Date 1/30/07

Technician Justino Diaz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))

☒ N/A, ONLY one flexion test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.2

Record the minimum temperature 21.0

Record the maximum humidity 17%

Record the minimum humidity 14%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.06 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.8 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.9 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>71</u> Nm @ <u>84</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	85 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature


1/30/07
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 124

Test I.D: D07282

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.2	Pass
Laboratory Relative Humidity		%	10 to 70	17	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.06	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.8	Pass
	30 msec	m/sec	5.8 to 7.0	6.9	Pass
D Plane Rotation	Max	deg	77 to 91	84	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	71	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	85	Pass
Overall Results					Pass


 Laboratory Technician



01/30/2007
 Test Date


 Approved By



Test Desc: Neck Flexion
Componet ID: D07282


Test Date: 01/30/2007
Velocity: 23.17 ft/s, 7.06 m/s





Test Desc: Neck Flexion
Componet ID: D07282

Test Date: 01/30/2007
Velocity: 23.17 ft/s, 7.06 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 124 Test Date 1/30/07

Technician Justino Diaz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 21.2

Record the minimum temperature 21.0

Record the maximum humidity 17%

Record the minimum humidity 14%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 89; Back 90.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.07 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.7 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.4 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.0 m/s
Plane D Rotation		Peak moment* -65 Nm $\leq$ moment $\leq$ -53 Nm during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	-60 Nm @ 112 degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	96 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

1/30/07
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test I.D: D07283

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.2	Pass
Laboratory Relative Humidity		%	10 to 70	17	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.07	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.7	Pass
	20 msec	m/sec	3.1 to 3.9	3.4	Pass
	30 msec	m/sec	4.6 to 5.6	5.0	Pass
D Plane Rotation	Max	deg	99 to 114	112	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-60	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	96	Pass
Overall Results					Pass


Laboratory Technician

01/30/2007



Test Date


Approved By



Test Desc: Neck Extension
Componet ID: D07283


Test Date: 01/30/2007
Velocity: 19.93 ft/s, 6.07 m/s





Test Desc: Neck Extension
Componet ID: D07283

Test Date: 01/30/2007
Velocity: 19.93 ft/s, 6.07 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 124

Test Date 1/29/07

Technician Justino Diaz

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 21.4

Record the minimum temperature 21.0

Record the maximum humidity 15%

Record the minimum humidity 13%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))


Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.83 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	50 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	3920 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4099 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	74%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

1/29/07
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE


ATD Serial No: 124

Test I.D: d07284

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.4	Pass
Relative Humidity	%	10 to 70	13	Pass
Probe Speed	m/s	6.59 to 6.83	6.83	Pass
Peak Deflection	mm	50 to 58	50	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	3.9	Pass
Internal Hysteresis	%	69 to 85	74	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4099	Pass
Overall Test Results				Pass


Laboratory Technician


01/29/2007
Test Date


Approved By



Test Desc: Thorax Impact
Componet ID: d07284

Test Date: 01/29/2007
Velocity: 22.40 ft/s, 6.83m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 124 Test Date 1/29/07

Technician Justino Diaz

☒ Pretest calibration
☐ Post test calibration verification


Test attempt no. 1 (when successive torso flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
☒ N/A, ONLY one thorax impact test performed
- ☒ 2. The test fixture conforms to the specifications in Figure 13B.
- ☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
☐ with legs below the femurs.
☒ without legs below the femurs.
- ☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>21.4</u> |
| Record the minimum temperature | <u>21.0</u> |
| Record the maximum humidity | <u>15%</u> |
| Record the minimum humidity | <u>13%</u> |
- ☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
- ☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
- ☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
- ☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))
- ☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- ☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- ☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
- | | |
|---|------------|
| Record reference plane angle (max. allowed 20°) | <u>15°</u> |
|---|------------|
- ☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	15°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	345 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	16°


Signature

1/29/07
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124


Test I.D: D07287

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	13	Pass
Initial Angle	deg	0 to 20	15	Pass
Return Angle	deg	+/- 8	16	Pass
Force at 45 deg	N	320 to 390	345	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass


Laboratory Technician

01/29/2007

Test Date


Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 124

Test Date 1/30/07

Technician Dave Wilcox

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.2

Record the minimum temperature 21.0

Record the maximum humidity 17%

Record the minimum humidity 14%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3550 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.



Signature

1/30/07

Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test I.D: D07286

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.0	Pass
Laboratory Relative Humidity	%	10 to 70	14	Pass
Probe Speed	m/sec	2.07 to 2.13	2.12	Pass
Maximum Force	kN	3.45 to 4.06	3.55	Pass
Overall Test Results				Pass



Laboratory Technician

01/30/2007

Test Date




Approved By



Test Desc: Left Knee
Componet ID: D07286

Test Date: 01/30/2007
Velocity: 6.97 ft/s, 2.12 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 124

Test Date 1/30/07

Technician Dave Wilcox

☒ Pretest calibration

☐ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B.

☒ 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 21.2

Record the minimum temperature 21.0

Record the maximum humidity 17%

Record the minimum humidity 14%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))

☒ 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.08 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3950 N

*Force = impactor mass x deceleration (572.136(b)(2))

☒ 12. Plots of acceleration versus time and force versus time follow this sheet.

A handwritten signature in dark ink, appearing to be "D. H. Allen", written over a horizontal line.

Signature

1/30/07

Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test I.D: D07285

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	21.0	Pass
Laboratory Relative Humidity	%	10 to 70	14	Pass
Probe Speed	m/sec	2.07 to 2.13	2.08	Pass
Maximum Force	kN	3.45 to 4.06	3.95	Pass
Overall Test Results				Pass



Laboratory Technician

01/30/2007

Test Date




Approved By



Test Desc: Right Knee
Componet ID: D07285

Test Date: 01/30/2007
Velocity: 6.81 ft/s, 2.08 m/s



DATA SHEET B3
HEAD DROP TEST (572.132)

Dummy Serial Number 124

Test Date 2/8/07

Technician Justino Diaz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

☐ 1. It has been at least 2 hours since the last head drop. (572.132(c)(5))

☒ N/A, ONLY one head drop performed

☒ 2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))

☒ 3. The head accelerometer mounting plate screws ((10-24 x 3/8 SHCS) are torqued to 9.0 Nm.

☒ 4. Accelerometers and their respective mounts are smooth and clean.

☒ 5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.

☒ 6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))

☒ 7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))

Record the maximum temperature 20.9

Record the minimum temperature 20.6

Record the maximum humidity 14%

Record the minimum humidity 11%

☒ 8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

- X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

- X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance 501mm

Record the left side distance 501mm

- X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish 656×10^{-6} mm

- X 13. The impact surface is rigidly supported. (572.132(c)(4))

- X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness 50.9 mm

Record width 604 mm


Record length 595 mm

- X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches $\pm$ 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

- X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	262
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	4

- X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

2/8/07
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test ID: D07361

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	20.6	Pass
Laboratory Relative Humidity	%	10 to 70	11	Pass
Peak Resultant Acceleration	G's	250 to 300	262	Pass
Peak Lateral Acceleration	G's	+/- 15	3.7	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


Laboratory Technician

02/08/2007
Test Date



Approved By




Test Desc: Head Drop
Componet ID: D07361

Test Date: 02/08/2007
Velocity: 0 ft/s, 0 m/s

PEAK RESULTANT ACCELERATION (G's) vs TIME (s)



HEAD Y (G's) vs TIME (s)



DATA SHEET B4
NECK FLEXION TEST (572.133)

Dummy Serial Number 124

Test Date 2/8/07

Technician Justino Diaz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
☒ N/A, ONLY one flexion test performed
- ☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- ☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|--------------------------------|-------------|
| Record the maximum temperature | <u>20.9</u> |
| Record the minimum temperature | <u>20.6</u> |
| Record the maximum humidity | <u>14%</u> |
| Record the minimum humidity | <u>11%</u> |
- ☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
 Record findings and actions: No Damage.
- ☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
 Record findings and actions: No Deterioration. Hardness Front 86; Back 88.
- ☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))
- ☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- ☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Flexion Test Results (572.133(b)(1) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$6.89 \text{ m/s} \leq \text{speed} \leq 7.13 \text{ m/s}$	7.09 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$2.1 \text{ m/s} \leq \Delta V \leq 2.5 \text{ m/s}$	2.4 m/s
	@ 20 ms	$4.0 \text{ m/s} \leq \Delta V \leq 5.0 \text{ m/s}$	4.7 m/s
	@30ms	$5.8 \text{ m/s} \leq \Delta V \leq 7.0 \text{ m/s}$	6.5 m/s
Plane D Rotation		Peak moment* $69 \text{ Nm} \leq \text{moment} \leq 83 \text{ Nm}$ during the following rotation range $77^\circ \leq \text{angle} \leq 91^\circ$	<u>70</u> Nm @ <u>91</u> degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm $80 \text{ ms} \leq \text{time} \leq 100 \text{ ms}$	87 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature


2/8/07
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test I.D: D07362

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.7	Pass
Laboratory Relative Humidity		%	10 to 70	11	Pass
Pendulum Speed		m/sec	6.89 to 7.13	7.09	Pass
Pendulum Deceleration	10 msec	m/sec	2.1 to 2.5	2.4	Pass
	20 msec	m/sec	4.0 to 5.0	4.7	Pass
	30 msec	m/sec	5.8 to 7.0	6.5	Pass
D Plane Rotation	Max	deg	77 to 91	91	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	69 to 83	70	Pass
Positive Moment Time Curve Decay to 10 Nm		msec	80 to 100	87	Pass
Overall Results					Pass


 Laboratory Technician



02/08/2007
 Test Date


 Approved By



Test Desc: Neck Flexion
Componet ID: D07362


Test Date: 02/08/2007
Velocity: 23.26 ft/s, 7.09 m/s





Test Desc: Neck Flexion
Componet ID: D07362

Test Date: 02/08/2007
Velocity: 23.26 ft/s, 7.09 m/s



DATA SHEET B5
NECK EXTENSION TEST (572.133)

Dummy Serial Number 124

Test Date 2/8/07

Technician Justino Diaz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

☐ 1. It has been at least 30 minutes since the last extension test. (572.137(q))

☒ N/A, ONLY one extension test performed

☒ 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))

☒ 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))

Record the maximum temperature 20.9

Record the minimum temperature 20.6

Record the maximum humidity 14%

Record the minimum humidity 11%

☒ 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.

Record findings and actions: No Damage.

☒ 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).

Record findings and actions: No Deterioration. Hardness Front 86; Back 88.

☒ 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

☒ 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))

☒ 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))

- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:

Neck Extension Test Results (572.133(b)(2) & (572.133(c)(4)(i & ii))

Parameter		Specification	Result
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.10 m/s
Pendulum ΔV with respect to impact speed	@ 10ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.6 m/s
	@30ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.1 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	<u>-58</u> Nm @ <u>111</u> degrees
Negative Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	102 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

2/8/07
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test I.D: D07363

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	20.6	Pass
Laboratory Relative Humidity		%	10 to 70	11	Pass
Pendulum Speed		m/sec	5.95 to 6.19	6.10	Pass
Pendulum Deceleration	10 msec	m/sec	1.5 to 1.9	1.8	Pass
	20 msec	m/sec	3.1 to 3.9	3.6	Pass
	30 msec	m/sec	4.6 to 5.6	5.1	Pass
D Plane Rotation	Max	deg	99 to 114	111	Pass
Occipital Condyle Moment within Deflection Corridor		Nm	-65 to -53	-58	Pass
Negative Moment Time Curve Decay to -10 Nm		msec	94 to 114	102	Pass
Overall Results					Pass


Laboratory Technician

02/08/2007

Test Date



Approved By




Test Desc: Neck Flexion
Componet ID: D07363

Test Date: 02/08/2007
Velocity: 20.02 ft/s, 6.10 m/s

PENDULUM DECELERATION (m/s) vs TIME (s)




NECK ROTATION (DEG) vs TIME (s)





Test Desc: Neck Flexion
Componet ID: D07363

Test Date: 02/08/2007
Velocity: 20.02 ft/s, 6.10 m/s



DATA SHEET B6
THORAX IMPACT TEST (572.134)

Dummy Serial Number 124

Test Date 2/8/07

Technician Justino Diaz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))

☒ N/A, ONLY one thorax impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 11B.

☒ 3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))

☒ 4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature 20.9

Record the minimum temperature 20.6

Record the maximum humidity 14%

Record the minimum humidity 11%

☒ 5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

☒ - No damage

☐ - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage _____

☐ - The following repairs or replacement was performed. Record _____

☒ 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))

☒ 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504)

that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.

- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

X 16. Complete the following table:

Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))


Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.82 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4100 N
Peak force** between 18.0 and 50.0 mm chest compression	$\text{peak force} \leq 4600 \text{ N}$	4139 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	73%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.


Signature

2/8/07
Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test I.D: D07364

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	20.9	Pass
Relative Humidity	%	10 to 70	11	Pass
Probe Speed	m/s	6.59 to 6.83	6.82	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	kN	3.9 to 4.4	4.1	Pass
Internal Hysteresis	%	69 to 85	73	Pass
Peak Force 18 mm - 50 mm	N	≤ 4600 N	4139	Pass
Overall Test Results				Pass


Laboratory Technician


02/08/2007
Test Date


Approved By



Test Desc: Thorax Impact
Componet ID: D07364

Test Date: 02/08/2007
Velocity: 22.39 ft/s, 6.82 m/s



DATA SHEET B7
TORSO FLEXION TEST (572.135)

Dummy Serial Number 124 Test Date 2/9/07

Technician Dave Wilcox

☐ Pretest calibration
☒ Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

- ☐ 1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
☒ N/A, ONLY one thorax impact test performed
- ☒ 2. The test fixture conforms to the specifications in Figure 13B.
- ☒ 3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
☐ with legs below the femurs.
☒ without legs below the femurs.
- ☒ 4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
Record the maximum temperature 21.9
Record the minimum temperature 21.7
Record the maximum humidity 14%
Record the minimum humidity 11%
- ☒ 5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
- ☒ 6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
- ☒ 7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
- ☒ 8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))
- ☒ 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- ☒ 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- ☒ 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
Record reference plane angle (max. allowed 20°) 16°
- ☒ 12. Attach the pull cable and the load cell. (572.135(c)(8))

- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at $45^\circ \pm 0.5^\circ$ of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at $45^\circ \pm 0.5^\circ$ of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), (572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle $\leq 20^\circ$	16°
Torso rotation rate	$0.5^\circ/\text{s} \leq \text{rate} \leq 1.5^\circ/\text{s}$	1.0
Force at $45^\circ \pm 0.5^\circ$	$320 \text{ N} \leq \text{force} \leq 390 \text{ N}$	354 N
Final ref. plane angle	Initial ref. plane angle $\pm 8^\circ$	18°



 Signature

2/9/07

 Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test I.D: D07367

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.9	Pass
Laboratory Relative Humidity	%	10 to 70	11	Pass
Initial Angle	deg	0 to 20	16	Pass
Return Angle	deg	+/- 8	18	Pass
Force at 45 deg	N	320 to 390	354	Pass
Upper Torso Deflection Rate	Deg/sec	0.5 to 1.5	1.0	Pass
Overall Result				Pass



Laboratory Technician

02/09/2007

Test Date



Approved By

DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136)

Dummy Serial Number 124

Test Date 2/8/07

Technician Justino Diaz

☐ Pretest calibration

☒ Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

☐ 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

☒ N/A, ONLY one knee impact test performed

☒ 2. The test fixture conforms to the specifications in Figure 14B

☒ 3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

☒ 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 20.9

Record the minimum temperature 20.6

Record the maximum humidity 14%

Record the minimum humidity 11%

☒ 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

☒ 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

☒ 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

☒ 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

☒ 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

☒ 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))


X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.09 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3510 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature


2/8/07
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test I.D: D07366

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.8	Pass
Laboratory Relative Humidity	%	10 to 70	11	Pass
Probe Speed	m/sec	2.07 to 2.13	2.09	Pass
Maximum Force	kN	3.45 to 4.06	3.51	Pass
Overall Test Results				Pass


Laboratory Technician


02/08/2007
Test Date


Approved By



Test Desc: Left Knee
Componet ID: D07366

Test Date: 02/08/2007
Velocity: 6.85 ft/s, 2.09 m/s



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136)

Dummy Serial Number 124

Test Date 2/8/07

Technician Justino Diaz

 Pretest calibration

X Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))

X N/A, ONLY one knee impact test performed

X 2. The test fixture conforms to the specifications in Figure 14B.

X 3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))

X 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature 20.9

Record the minimum temperature 20.6

Record the maximum humidity 14%

Record the minimum humidity 11%

X 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))

X 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))

X 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))

X 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))

X 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5))


X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.08 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3990 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

2/8/07
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 124

Test I.D: D07365

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.5	20.8	Pass
Laboratory Relative Humidity	%	10 to 70	11	Pass
Probe Speed	m/sec	2.07 to 2.13	2.08	Pass
Maximum Force	kN	3.45 to 4.06	3.99	Pass
Overall Test Results				Pass


Laboratory Technician


02/08/2007
Test Date


Approved By



Test Desc: Right Knee
Componet ID: D07365

Test Date: 02/08/2007
Velocity: 6.81 ft/s, 2.08 m/s



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #124, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	785.0
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	455.1
C	H-POINT HEIGHT	Reference	81.3-86.3	85.2
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	145.6
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	83.0
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	125.6
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	245.9
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	45.0
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	296.1
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	192.3
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	540.2
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	345.6
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	395.8
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.5

HYBRID III 5 th SN #124, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	176.0
P	FOOT LENGTH	Tip of toe to rear of heal	218.5-233.7	219.4
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.0
S	HEAD BREADTH	The widest part of the head	137.1-147.3	138.6
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	186.2
U	HIP BREADTH	The widest part of the hip	299.7-314.9	310.7
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	354.9
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	82.0
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	547.1
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	881.0
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	786.3
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	357.4
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	169.8

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number 124

Test Date 2/8/07

Technician Jessica Gall

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damaged	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber.			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X

Dummy Item	Inspect for	Comments	Damaged	OK
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Jessica Gall
Signature

2/9/07
Date

Describe the repair or replacement of parts:

Checked by

David Winkelbauer
Signature

2/9/07
Date