

REPORT NUMBER: MCW-DOT-08SN06C

DETERMINATION OF CHILD RESTRAINT SYSTEM CRASHWORTHINESS

**NEW CAR ASSESSMENT PROGRAM
SIDE IMPACT TEST**

2008 HONDA ACCORD 2-DOOR COUPE

NHTSA NUMBER: M85301

**PREPARED BY:
MEDICAL COLLEGE OF WISCONSIN
5000 WEST NATIONAL AVENUE
RESEARCH 151
MILWAUKEE, WISCONSIN 53295**



TEST DATE: 30 OCTOBER 2007

REPORT DATE: 07 NOVEMBER 2007

CRABI REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
RULEMAKING
OFFICE OF CRASHWORTHINESS STANDARDS
NVS-111
1200 NEW JERSEY AVE, SE, ROOM W43-410
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, in response to Contract Number DTNH22-03-D-42005.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: _____

Date:

Reviewed by: _____

Date:

Technical Report Documentation Page

1. Report No. MCW-DOT-08SN06C	2. Government Accession No.	3. Recipient's Catalog No.													
4. Title and Subtitle Final report of New Car Assessment Program (NCAP) Side Impact Testing of a 2008 Honda Accord 2-door coupe NHTSA number: 08SN06C		5. Report Date 07 November 2007													
		6. Performing Organization Code													
7. Author(s) John Humm, Mark Meyer, and Frank Pintar		8. Performing Organization Report No.													
9. Performing Organization Name and Address Medical College of Wisconsin 5000 W. National Ave. Research 151 Milwaukee, WI 53295		10. Work Unit No.													
		11. Contract or Grant No. DTNH22-03-D-42005													
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Rulemaking, Office of Crashworthiness Standards NVS-111 1200 New Jersey Ave, SE, Room W43-410 Washington, D.C. 20590		13. Type of Report and Period Covered:													
		14. Sponsoring Agency Code NVS-111													
15. Supplementary Notes															
16. Abstract A 55/28 km/h 90° Moving Deformable Barrier (MDB) New Car Assessment Program (NCAP) side impact was conducted on the subject Child Restraint System (CRS) Maxi Cosi Priori in conjunction with side impact testing on a 2008 Honda Accord 2-door coupe to obtain new car assessment and research data indicant of FMVSS No. 214D performance and in accordance with the specifications of the Office of Crashworthiness Standards Test Procedure for the determination of CRS crashworthiness. The test was conducted at the Medical College of Wisconsin (MCW) in Milwaukee, Wisconsin on 30 October 2007. The test vehicle's occupant performance is as follows: <table border="1" data-bbox="168 1289 1354 1402"> <thead> <tr> <th>Measurement Description</th> <th>Units</th> <th>Threshold</th> <th>Right Rear (P3)</th> </tr> </thead> <tbody> <tr> <td>Head Injury Criteria (HIC15)</td> <td>N/a</td> <td>390</td> <td>63.6</td> </tr> <tr> <td>3 msec. Chest Clip</td> <td>G's</td> <td>50</td> <td>35.4</td> </tr> </tbody> </table> The doors on the struck side of the vehicle did not separate from the body at the hinges or latches and the opposite doors did not open during the side impact event.				Measurement Description	Units	Threshold	Right Rear (P3)	Head Injury Criteria (HIC15)	N/a	390	63.6	3 msec. Chest Clip	G's	50	35.4
Measurement Description	Units	Threshold	Right Rear (P3)												
Head Injury Criteria (HIC15)	N/a	390	63.6												
3 msec. Chest Clip	G's	50	35.4												
17. Key Words New Car Assessment Program (NCAP) Side impact Side Impact Hybrid III Dummy (SID/HIII) Occupant side impact protection Child Restraint Airbag Interaction (CRABI)		18. Distribution Statement Copies of this report are available from: U.S. Department of Transportation National Highway Traffic Safety Administration Rulemaking, Office of Crashworthiness Standards NVS-111 1200 New Jersey Ave, SE, Room W43-410 Washington, D.C. 20590													
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 54	22. Price												

TABLE OF CONTENTS

<u>Section</u>		<u>Page</u> <u>No.</u>
1	Purpose and test procedure	1
2	Summary of NCAP side impact test	2
<u>Data Sheet</u>		<u>Page</u> <u>No.</u>
<u>No.</u>		
1	General test and vehicle parameter data	5
2	Post test observations	7
3	Vehicle pre test and post test measurements	8
4	CRABI longitudinal clearance dimensions	9
5	CRABI lateral clearance dimensions	10
6	CRS performance characteristics	11
7	CRS accelerometer locations	12
8	High speed camera locations and data	13
<u>Appendix</u>		
A	Photographs	A
B	CRABI 12-month-old configuration and performance verification data	B
C	Dummy calibration data	C

SECTION 1

PURPOSE AND TEST PROCEDURE

PURPOSE

This side impact test was conducted as part of the FY'08 test program sponsored by the National Highway Traffic Safety Administration (NHTSA), under Contract No. DTNH22-03-D-42005. The purpose of this test was to evaluate side impact protection of a manufactured by Honda of America Mfg., Inc. and obtain CRS performance data.

TEST PROCEDURE

The side impact test was conducted in accordance with the Laboratory Test Procedure for New Car Assessment Program Side Impact Testing dated November 2002 and of the Office of Crashworthiness Standards Test Procedure for the determination of CRS crashworthiness. The procedures for receiving, inspection, testing, and reporting of test results are described in the test procedures and are not repeated in this report.

SECTION 2

SUMMARY OF NCAP SIDE IMPACT TEST

A 2008 Honda Accord 2-door coupe was impacted on the left (driver's) side by a Moving Deformable Barrier (MDB) modeling a 90° impact as if the test vehicle were moving forward at 28 km/h perpendicular to and across the path of the MDB traveling forward at 55 km/h. Here the test vehicle was stationary and positioned 27° from perpendicular to the MDB tow road guidance system and the MDB was towed 27° ("crabbed") from the guidance system. [See p 26.] The 1643.7 kg test vehicle was impacted by the 1362.7 kg MDB traveling at a speed of 61.7 km/h (measured inline with the guidance system.) The test was conducted at the Medical College of Wisconsin on 30 October 2007.

One (1) CRABI 12-month-old Infant Crash Test Dummy was placed in a CRS in a designated seating position within the test vehicle: (1) rearward facing CRS, right rear passenger; serial number 074. The CRABI was instrumented in the following locations:

- Head center of gravity tri-axial (X, Y, Z) accelerometers (primary and redundant)
- Upper neck tri-axial (X, Y, Z) force load cells and tri-axial (X, Y, Z) moment load cells
- Chest tri-axial (X, Y, Z) accelerometers

The CRS was instrumented with six (6) structural accelerometers. All data channels were recorded with a fully self contained on-board DTS TDAS Pro Data Acquisition System. The data were digitally sampled at 12.5 kHz and processed according to SAEJ211-1 (March 1995).

One (1) high-speed video camera was used to document the impact event. Camera location and pertinent camera information are documented in the data sheets. Pre- and post-test photographs of the CRS and dummy can be found in Appendix A.

All of the above was conducted in accordance to the Laboratory Test Procedure for New Car Assessment Program Side Impact Testing dated November 2002 and the Office of Crashworthiness Standards.

2.2 GENERAL COMMENTS

Test summaries, post test observations, vehicle, camera, and occupant measurements are presented in datasheets 1-8. Appendix A contains the still photograph prints. Appendix B contains CRABI and CRS response data traces. Appendix C contains the CRABI's configuration and performance verification data.

OCCUPANT SUMMARY	
Injury criteria	CRABI (P3)
HIC15	63.6
T ₁ (ms)	70.0
T ₂ (ms)	85.0
3 Msec. Chest Clip	35.4

Head Injury Criterion (HIC) is the standardized calculation using resultant head acceleration to assess head injury. Generally, a higher HIC represents an increase in the likelihood of a serious head injury. HIC15 specifies a time 'window' of 15 milliseconds over which the integral is calculated. T₁ and T₂ represent the time of the lower and upper bounds of the window in which the HIC is calculated. Based on this separation, the maximum HIC value for an adult 50th percentile male anthropomorphic test dummy is 700. For a 12 month-old infant the value is reduced to 390.

The 3 msec. Chest Clip is a calculation using the resultant chest acceleration to assess thoracic injury. As the number increases, a greater probability of a serious thoracic injury also increases. The integral is calculated over a time window of 3 milliseconds. The maximum 3 msec. Chest Clip for an adult 50th percentile male anthropomorphic test dummy is 60, and 50 for a 12 month-old.

CHILD RESTRAINT SYSTEM INFORMATION	
Restraint type	Right rear (passenger) occupant Location 03 CRS
Manufacturer	Maxi Cosi
Model name	Priori
Model no.	22486-CRI
Type	Infant
Forward/rearward	Rearward

SUPPLEMENTAL RESTRAINT SYSTEM INFORMATION		
Restraint type	Right rear (passenger) occupant Location 03	
	Installed	Operation
Front airbag	No	N/a
Side airbag	No	N/a
Head airbag	No	N/a
Curtain airbag	Yes – side header	Did not deploy
Seat belt pretensioner	Yes	Yes
Seat belt load limiter	No	N/a

These test data and report can be found in detail on the NHTSA website at www.nhtsa.dot.gov.

A brief summary of the crash test can be located at www.safercar.gov

TEST NOTES

DATA SHEET NO. 1
GENERAL TEST AND VEHICLE PARAMETER DATA

VEHICLE INFORMATION		VEHICLE OPTIONS	
Year	2008	Air conditioning	Yes
Make	Honda	Anti-lock brakes	Yes
Model	Accord	AM/FM radio	Yes
Body style	2-door coupe	All wheel drive	No
NHTSA number	M85301	Combo bag	No
MCW test ID	08SN06	Console	Yes
VIN	1HGCS11398A000916	Cruise/speed control	Yes
Color	Blue pearl	Disc brakes	Yes – front and rear
Build date	September 2007	Frontal bag	Yes
Engine No. of cylinders	4	Head bag	Yes – front and rear
Engine Displacement (L)	2.4	Power brakes	Yes
Engine Placement	Lateral	Power door locks	Yes
Transmission	Manual 5 speed	Power steering	Yes
Final drive	Front wheel drive	Power windows	Yes
Delivery date	October 19, 2007	Torso bag	Yes – front only
Odometer reading	35	Tilt steering wheel	Yes

CERTIFICATION LABEL INFORMATION			
Manufacturer	Honda of America Mfg., Inc.	GVWR (kg)	1950
		GAWR front (kg)	1060
Date of manufacture	September 2007	GAWR rear (kg)	910

SEAT INFORMATION			
	Number of occupants	Seat type	Seat back type
Front	2	Bucket	Adjustable
Back	3	Split bench	Fixed
Third	0		
Total	5		

CARGO CAPACITY CALCULATION			
	Units	Value	Reference label
Vehicle maximum capacity	kg	386.4	(A)
Number of occupants (7) X 68.04 kg	kg	340.9	(B)
Cargo capacity (RCLW) †	kg	45.5	(C) = (A)-(B) †

† Note if RCLW is > 136.1 kg (300 lbs), use 136.1 kg

DATA SHEET NO. 1
GENERAL TEST AND VEHICLE PARAMETER DATA (CONTINUED)

TEST VEHICLE MASS INFORMATION				
	Units	As delivered	As tested	Fully loaded
Left front	kg	450	462.3	464.8
Right front	kg	423.6	426.4	426.7
Left rear	kg	272.7	385.9	388.1
Right rear	kg	296.8	369.1	370.4
Total front	kg	873.6	888.7	891.5
% Total front	%	60.5	54.1	54.0
Total rear	kg	569.5	755	758.5
%Total rear	%	39.5	45.9	46.0
Total	kg	1443.1	1643.7	1650.0

As delivered mass is vehicle mass with maximum fluids

Fully loaded mass is the as delivered mass + 1 or 2 ATD's + RCLW

As tested mass is the mass of test vehicle with 1 or 2 ATD's + instrumentation + ballast (if necessary)

CALCULATION OF TEST VEHICLE TARGET MASS			
	Units	Value	Reference label
As delivered test vehicle mass	kg	1443.1	(D)
Maximum cargo capacity (RCLW)	kg	45.5	(C)
Mass of SID HIII's (1 or 2)	kg	161.4	(E)
Test vehicle target mass (TVTW)	kg	1650.0	(D) + (C) + (E)

As tested mass must be 4.5 kg to 9 kg less than the test vehicle target mass


IMPACT LOCATION ON TEST VEHICLE	
Wheelbase	2740 mm
Nominal impact point	430 mm rearward of front axle
Actual impact point	407 mm rearward of front axle

**DATA SHEET NUMBER 2
POST TEST OBSERVATIONS**

TEST DUMMY INFORMATION AND CONTACT POINTS	
Description	Left rear seat
Dummy type / serial no.	CRABI 12-month-old Infant/074
Head contact	None
Chest contact	None
Abdomen contact	None
Left knee contact	None
Right knee contact	None
Left leg contact	None
Right leg contact	None
Left foot contact	Yes - seatback
Right foot contact	Yes - seatback


POST TEST DOOR OPENING AND SEAT TRACK INFORMATION	
Description	Rear (03 position)
Locked/unlocked doors	Unlocked
Door opening	None
Seat movement	None
Seat back failure	None

DATA SHEET NUMBER 3
VEHICLE PRE AND POST MEASUREMENTS




VEHICLE DIMENSIONS				
Code	Description	Pre test	Post test	Change
		mm	mm	mm
A	Wheelbase	2740	2710	-30
B	Front axle to front side of vehicle	678	691	13
C	Rear axle to rear side of vehicle	800	806	6
D	Total length at centerline	4855	4848	-7
E	Front bumper thickness	241	241	0
F	Front bumper bottom to ground	277	294	17
G	Sill height at front wheel well	227	206	-21
H	Sill height at front door leading edge	228	267	39
I	Sill height at b-pillar	240	257	17
J1	Sill height at rear wheel well	174	150	-24
J2	Pinch weld height at rear wheel well	245	248	3
K	Sill height aft of rear wheel well	278	235	-43
L	Rear bumper thickness	286	286	0
M	Rear bumper bottom to ground	332	287	-45
N	Sill height to window bottom sill	782	729	-53
O	Front door leading edge to impact C/L	1375	1359	-16
P	Rear door trailing edge to impact C/L	725	685	-40
Q	Front window opening	427	417	-10
R	Right side length	4218	4230	12
S	Left side length	4218	4207	-11
T	Vehicle width at b-pillar	1829	1659	-170

DATA SHEET NUMBER 4
CRABI LONGITUDINAL CLEARANCES



CRABI LONGITUDINAL CLEARANCE MEASUREMENTS			
Code	Measurement description	Units	Left rear seat
	ATD serial number	-	074
CB	Chest to seat back	mm	481
HZ	Head to roof	mm	454
KBL	Left knee to seat back	mm	232
KBR	Right knee to seat back	mm	232
NB	Nose to seat back	mm	558
SA	Seat back angle	°	24
TBL	Left toe to seat back	mm	126
TBR	Right toe to seat back	mm	129

DATA SHEET NUMBER 5
CRABI LATERAL CLEARANCES



CRABI LATERAL CLEARANCE MEASUREMENTS			
Code	Measurement description	Units	Left rear seat
-	ATD serial number	-	074
AD	Arm to door	mm	310
CD	Chest to door	mm	399
HD	H-point to door	mm	377
HS	Head to side window	mm	414
KK	Knee to knee	mm	94
FF	Foot to foot	mm	111

DATA SHEET NUMBER 6
CRS PERFORMANCE CHARACTERISTICS

CRS PERFORMANCE CHARACTERISTICS		
Location	CRS (P3)	
	Damage	Post-Test
Upper tether strap	N/a	N/a
Upper tether buckle	N/a	N/a
Upper tether hook	N/a	N/a
Vehicle upper tether anchor	N/a	N/a
Lower anchor strap	No	None
Lower anchor buckle	No	None
Lower anchor hooks	No	None
Vehicle lower CRS anchors	No	None
5-point harness connections	No	None
Cracks on CRS	No	None
Fabric tears on CRS	No	None
Vehicle seat structure	No	None
Vehicle seat fabric tears	No	None

DATA SHEET 7
CRS ACCELEROMETER LOCATIONS

TEST VEHICLE ACCELEROMETER LOCATIONS				
Loc. no.	Accelerometer location	Measurements (mm)		
		X	Y	Z
1	CRS	1374	336	-185
2	CRS base	1409	363	-142


Origin

X Rear bumper
 Y Midline of vehicle
 Z Top of rear bumper

Orientation

X +(X) Forward
 Y +(Y) Right
 Z +(Z) Down

DATA SHEET 8
HIGH-SPEED CAMERA LOCATIONS AND DATA SUMMARY



	View	Coordinates †			Angle °	Lens mm	Rate fps
		X	Y	Z			
		mm	mm	mm			
1	Overhead view of test vehicle	-309	-661	-4906	90	12.5	1000
2	Overhead close-up view of impact plane	-598	-146	-4432	90	16	1000
3	MDB onboard close-up view of impact point †	-2084	-90	-128	0.4	25.4	1000
4	MDB onboard view of driver dummy †	-2304	832	-903	4.0	13	1000
5	Right side ground level overall view	-597	12026	-984	2.8	50	1000
6	Left side ground level overall view	-1554	-3761	-961	6.1	25	1000
7	Test vehicle onboard driver front view	-429	-511	-470	12.2	25	1000
8	Test vehicle onboard driver side view	1702	894	-333	16.5	12.5	1000
9	Test vehicle onboard passenger side view	1698	1729	-334	16.4	12.5	1000
10	Real-time film coverage of test	-	-	-	-	-	-
11	Test vehicle onboard CRS view	-695	241	-619	46.5	12.5	1000

Origin

X

Y

Z

Impact Point

Impact Point

Impact Point

† Cameras triggered pre-impact

Orientation

X

Y

Z

+(X) Forward

+(Y) Right

+(Z) Down

APPENDIX A
PHOTOGRAPHS

LIST OF PHOTOGRAPHS

Figure	Photograph Description	Page
A-1	CRS label	A-3
A-2	Pre test frontal view	A-4
A-3	Post test frontal view	A-4
A-4	Pre test rear view	A-5
A-5	Post test rear view	A-5
A-6	Pre test left view	A-6
A-7	Post test left view	A-6
A-8	Pre test right view	A-7
A-9	Post test right view	A-7
A-10	Pre test front view (head and seatbelt)	A-8
A-11	Post test front view (head and seatbelt)	A-8
A-12	Pre test front view (seatbelt)	A-9
A-13	Post test front view (seatbelt)	A-9
A-14	Pre test right side in vehicle view	A-10
A-15	Post test right side in vehicle view	A-10
A-16	Pre test left side in vehicle view	A-11
A-17	Post test left side in vehicle view	A-11
A-18	Post test CRABI feet	A-12



Figure A-1: CRS label



Figure A-2: Pre test frontal view



Figure A-3: Post test frontal view



Figure A-4: Pre test rear view




Figure A-5: Post test rear view



Figure A-6: Pre test left side view



Figure A-7: Post test left side view



Figure A-8: Pre test right side



Figure A-9: Post test right side



Figure A-10: Pre test front view (head and seatbelt)



Figure A-11: Post test front view (head and seatbelt)



Figure A-12: Pre test front view (seatbelt)



Figure A-13: Post test front view (seatbelt)



Figure A-14: Pre test right side in vehicle view

Figure A-15: Post test right side in vehicle view



Figure A-16: Pre test left side in vehicle view

Figure A-17: Post test left side in vehicle view



Figure A-18: Post test CRABI feet

APPENDIX B
CRABI RESPONSE DATA

The following plots are provided in the test report

Data Plot	Description	Page
B-1	CRABI 074 head cg (x)	B-3
B-2	CRABI 074 head cg (y)	B-4
B-3	CRABI 074 head cg (z)	B-5
B-4	Upper neck force (x)	B-6
B-5	Upper neck force (y)	B-7
B-6	Upper neck force (z)	B-8
B-7	Upper neck moment (x)	B-9
B-8	Upper neck moment (y)	B-10
B-9	Upper neck moment (z)	B-11
B-10	CRABI 074 chest (x)	B-12
B-11	CRABI 074 chest (y)	B-13
B-12	CRABI 074 chest (z)	B-14
B-13	Child seat base (x)	B-15
B-14	Child seat base (y)	B-16
B-15	Child seat base (z)	B-17
B-16	Child seat (x)	B-18
B-17	Child seat (y)	B-19
B-18	Child seat (z)	B-20

Dummy, vehicle, and MDB response data can be found in the R&D section of the NHTSA website at:


www-nrd.nhtsa.dot.gov/database/nrd-11/veh_db.html.

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretigger Points	1250
Sensor Location	HDCG
Sensor Mnf & Model	ENDEVCO 7264C-2KTZ
Serial Number	P51665



CRABI 074 HEAD CG X XL



Max	24.19	G's	at	53.04	msec
Min	-18.34	G's	at	79.84	msec

08SN06V Plot 062

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000	Sensor Location	HDCG
Sampling Rate (Hz)	12500	Sensor Mnf & Model	ENDEVCO 7264C-2KTZ
Number of Points	10000	Serial Number	P51674
Pretrigger Points	1250		



CRABI 074 HEAD CG Y YL



Max	19.26	G's	at	367.68	msec
Min	-18.72	G's	at	77.36	msec

08SN06V Plot 063

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretrigger Points	1250
Sensor Location	HDCG
Sensor Mnf & Model	ENDEVCO 7264C-2KTZ
Serial Number	P51633



CRABI 074 HEAD CG Z ZL



Max	26.65	G's	at	61.04	msec
Min	-1.27	G's	at	589.84	msec

08SN06V Plot 064

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretigger Points	1250
Sensor Location	NEKU
Sensor Mnf & Model	DENTON 2554A_FX
Serial Number	2554A_FX_299



UPPER NECK LOADCELL XL



NWT	Max	400.70	NWT	at	70.08	msec
	Min	-25.46	NWT	at	36.00	msec

08SN06V Plot 065


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretigger Points	1250
Sensor Location	NEKU
Sensor Mnf & Model	DENTON 2554A_FY
Serial Number	2554A_FY_299



UPPER NECK LOADCELL YL



NWT	Max	72.96	NWT	at	118.56	msec
	Min	-123.03	NWT	at	68.96	msec

08SN06V Plot 066

Time (msec)


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000	Sensor Location	NEKU
Sampling Rate (Hz)	12500	Sensor Mnf & Model	DENTON 2554A_FZ
Number of Points	10000	Serial Number	2554A_FZ_299
Pretrigger Points	1250		



UPPER NECK LOADCELL Z1



Max	662.63	NWT	at	70.08	msec
Min	-163.83	NWT	at	374.40	msec

08SN06V Plot 067

Time (msec)

NWT


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC600
Sampling Rate (Hz)	12500
Number of Points	10000
Pretrigger Points	1250
Sensor Location	NEKU
Sensor Mnf & Model	DENTON 2554A_MX
Serial Number	2554A_MX_299



UPPER NECK LOADCELL XL



Max	5.66	NWM	at	78.96	msec
Min	-8.60	NWM	at	150.56	msec

08SN06V Plot 068

Time (msec)

NWM


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC600	Sensor Location	NEKU
Sampling Rate (Hz)	12500	Sensor Mnf & Model	DENTON 2554A_MY
Number of Points	10000	Serial Number	2554A_MY_299
Pretrigger Points	1250		



UPPER NECK LOADCELL YL



Max	1.80	NWM	at	609.76	msec
Min	-15.21	NWM	at	68.88	msec

08SN06V Plot 069

Time (msec)

NWM


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC600
Sampling Rate (Hz)	12500
Number of Points	10000
Pretrigger Points	1250
Sensor Location	NEKU
Sensor Mnf & Model	DENTON 2554A_MZ
Serial Number	2554A_MZ_299



UPPER NECK LOADCELL Z1



Max	4.05	NWM	at	368.00	msec
Min	-7.05	NWM	at	93.68	msec

08SN06V Plot 070

Time (msec)

NWM


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretrigger Points	1250
Sensor Location	CHST
Sensor Mnf & Model	ENDEVCO 7264C-2KTZ
Serial Number	P51677



CRABI 074 CHEST X XL



B-12

Max	15.55	G's	at	54.48	msec
Min	-10.55	G's	at	125.76	msec

08SN06V Plot 071

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000	Sensor Location	CHST
Sampling Rate (Hz)	12500	Sensor Mnf & Model	ENDEVCO 7264C-2KTZ
Number of Points	10000	Serial Number	P51641
Pretrigger Points	1250		



CRABI 074 CHEST Y YL



B-13

Max	14.27	G's	at	377.44	msec
Min	-30.74	G's	at	52.96	msec

08SN06V Plot 072

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretrigger Points	1250
Sensor Location	CHST
Sensor Mnf & Model	ENDEVCO 7264C-2KTZ
Serial Number	P51670



CRABI 074 CHEST Z ZL



B-14

Max	15.97	G's	at	59.12	msec
Min	-2.59	G's	at	4.9%	msec

08SN06V Plot 073

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretigger Points	1250
Sensor Location	SEBS
Sensor Mnf & Model	MSI 64-2000-10-360-XY
Serial Number	A011316



Child seat base acceleration XL



Max	26.68	G's	at	79.76	msec
Min	-32.48	G's	at	63.28	msec

08SN06V Plot 074

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretigger Points	1250
Sensor Location	SEBS
Sensor Mnf & Model	ENDEVCO 7264-2000TZ
Serial Number	J35981



Child seat base acceleration YL



Max	60.53	G's	at	81.28	msec
Min	-69.84	G's	at	79.52	msec

08SN06V Plot 075

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretrigger Points	1250
Sensor Location	SEBS
Sensor Mnf & Model	ENDEVCO 7264C-2KTZ-2-300
Serial Number	P22311



Child seat base acceleration ZL



B-17

Max	40.54	G's	at	78.48	msec
Min	-25.91	G's	at	80.88	msec

08SN06V Plot 076

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretrigger Points	1250
Sensor Location	SEAT
Sensor Mnf & Model	ENDEVCO 7264-2000
Serial Number	J44022



Child seat acceleration XL



Max	18.60	G's	at	79.84	msec
Min	-25.66	G's	at	45.60	msec

08SN06V Plot 077

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretrigger Points	1250
Sensor Location	SEAT
Sensor Mnf & Model	ENDEVCO 7264-2000
Serial Number	ET30J



Child seat acceleration YL



Max	43.03	G's	at	79.92	msec
Min	-19.60	G's	at	60.08	msec

08SN06V Plot 078

Time (msec)

G's


Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

Test ID	08SN06V
Date	10-30-2007
Description	2008 Honda Accord 2-Door Side NCAP Test

Filter Class	CFC1000
Sampling Rate (Hz)	12500
Number of Points	10000
Pretrigger Points	1250
Sensor Location	SEAT
Sensor Mnf & Model	ENDEVCO 7264C-2KTZ-2-300
Serial Number	P21898



Child seat acceleration ZL



Max	27.42	G's	at	60.80	msec
Min	-16.44	G's	at	43.12	msec

08SN06V Plot 079

Time (msec)

G's

Neuroscience Research Labs
5000 West National Ave
Research 151
Milwaukee, WI 53295

APPENDIX C
DUMMY CALIBRATION DATA

**VERIFICATION TEST RESULTS SUMMARY
PRE AND POST TEST**

CONFIGURED FOR LEFT SIDE IMPACT

Serial Number 074Test Sequences 1

TEST	PRE		POST	
	COMMENTS	BY	COMMENTS	BY
FRONT THORAX IMPACT	Pass all requirements	TRC	N/a	N/a
FRONT HEAD DROP	Pass all requirements	TRC	N/a	N/a
REAR HEAD DROP	Pass all requirements	TRC	N/a	N/a
NECK EXTENSION	Pass all requirements	TRC	N/a	N/a
NECK FLEXION	Pass all requirements	TRC	N/a	N/a

SUMMARY
SID H3 PRE AND POST VERIFICATION
CONFIGURED FOR LEFT SIDE IMPACT

TEST PARAMETER	SPEC	CRABI/074	
		PRE	POST
FRONT THORAX IMPACT			
Date	-	17Oct07	-
Sequential Test Number	-	1	-
Temperature (°C)	20.6-22.2	21.3	-
Relative Humidity (%)	10-70	61	-
Probe Speed (m/s)	4.9-5.1	5.07	-
Probe Force (N)	(-1514)-(-1796)	-1662.1	-
FRONT HEAD DROP			
Date	-	19Oct07	-
Sequential Test Number	-	1	-
Temperature (°C)	18.9-25.6	21.1	-
Relative Humidity (%)	10-70	55	-
Peak Head Resultant Acceleration (G's)	100-120	107.7	-
Peak Head Lateral Acceleration (G's)	(-15)-15	2.1	-
Is Acceleration Curve Unimodal w/in 17% of Peak	Yes	Yes	-
REAR HEAD DROP			
Date	-	19Oct07	-
Sequential Test Number	-	1	-
Temperature (°C)	18.9-25.6	21.0	-
Relative Humidity (%)	10-70	54	-
Peak Head Resultant Acceleration (G's)	55-71	64.1	-
Peak Head Lateral Acceleration (G's)	(-15)-15	1.5	-
Is Acceleration Curve Unimodal w/in 17% of Peak	Yes	Yes	-

TEST PARAMETER	SPEC	CRABI/074	
		PRE	POST
NECK EXTENSION			
Date	-	17Oct07	-
Sequential Test Number	-	1	-
Temperature (°C)	-	21.1	-
Relative Humidity (%)	-	62	-
Pendulum Velocity (m/s)	(-2.4)-(-2.6)	-2.47	-
Pendulum Integrated Velocity Change @ 6 ms (m/s)	0.8-1.2	0.99	-
Pendulum Integrated Velocity Change @ 10 ms (m/s)	1.5-2.1	1.75	-
Pendulum Integrated Velocity Change @ 14 ms (m/s)	2.2-2.9	2.37	-
Total Head D-Plane Rotation (°)	80-92	88.5	-
Total Neck Occipital Condyles Moment (Nm)	(-12)-(-23)	-14.8	-
Total Neck Occipital Condyles Moment Decay to -5 ms(Nm)	76-90	83.5	-
NECK FLEXION			
Date	-	17Oct07	-
Sequential Test Number	-	1	-
Temperature (°C)	20.6-22.2	21.2	-
Relative Humidity (%)	10-70	63	-
Pendulum Velocity (m/s)	5.1-5.3	5.22	-
Pendulum Integrated Velocity Change @ 10 ms (m/s)	(-1.6)-(-2.3)	-1.90	-
Pendulum Integrated Velocity Change @ 20 ms (m/s)	(-3.4)-(-4.2)	-3.78	-
Pendulum Integrated Velocity Change @ 25 ms (m/s)	(-4.3)-(-5.2)	-4.64	-
Total Head D-Plane Rotation (°)	(-75)-(-86)	-82.9	-
Total Neck Occipital Condyles Moment (Nm)	36-45	41.3	-
Total Neck Occipital Condyles Moment Decay to 5 ms(Nm)	60-80	74.8	-

**DUMMY INSPECTION LIST
PRE AND POST TEST**

CONFIGURED FOR LEFT SIDE IMPACT

		CRABI 074	
		PRE	POST
	Date	30Oct07	31Oct07
	Performed By	Mike Rawski	Mike Rawski
PART	INSPECTION	RESULT	RESULT
Skin	Visual	Pass	Pass
Head	Visual, Ballast, Accelerometer Mount	Pass	Pass
Neck	Visual and Palpated, Cable Torque	Pass	Pass
Spine Box	Visual, Ballast, Weldment, Accelerometer Mount	Pass	Pass
Rib Cage	Visual, Palpated, Measured, Stiffness	Pass	Pass
Sternum	Visual	Pass	Pass
Lumbar Spine	Visual	Pass	Pass
Abdomen	Visual	Pass	Pass
Pelvis	Visual, Palpated, Accelerometer Mount	Pass	Pass
Upper Legs	Visual	Pass	Pass
Knees	Visual, Stops, Inserts	Pass	Pass
Lower Legs	Visual, Range of Motion	Pass	Pass
Ankles	Visual, Range of Motion	Pass	Pass
Feet	Visual, Range of Motion	Pass	Pass
Joints	1 to 2 G Range	Pass	Pass
Other		N/a	N/a