

REPORT NUMBER: NCAP305I-MGA-2012-004

**NEW CAR ASSESSMENT PROGRAM (NCAP)
FMVSS No. 305 Indicant Test**

**GENERAL MOTORS OF CANADA LTD.
2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan
NHTSA No.: MC0118**

**MGA RESEARCH CORPORATION
5000 Warren Road
Burlington, WI 53105**



Test Date: March 2, 2012


Report Date: March 23, 2012

FINAL REPORT

**U.S. DEPARTMENT OF TRANSPORTATION
National Highway Traffic Safety Administration
Office of Crashworthiness Standards
Mail Code: NVS-111
1200 New Jersey Ave, SE
Room W43-410
Washington, DC 20590**

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof.

If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement.

Prepared by: 
Donna Janovicz, Project Manager

Approved by: 
Joe Fleck, Project Engineer

Approval Date: March 23, 2012

FINAL REPORT ACCEPTANCE BY OVSC:

Division Chief, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

COTR, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

Technical Report Documentation Page

<p>1. Report No. NCAP305I-MGA-2012-004</p>	<p>2. Government Accession No.</p>	<p>3. Recipient's Catalog No.</p>	
<p>4. Title and Subtitle Final Report of FMVSS 305 Compliance Testing of 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan, NHTSA No.: MC0118</p>		<p>5. Report Date March 23, 2012</p>	
		<p>6. Performing Organization Code MGA</p>	
<p>7. Author(s) Donna Janovicz, Project Manager Joe Fleck, Project Engineer</p>		<p>8. Performing Organization Report No. NCAP305I-MGA-2012-004</p>	
<p>9. Performing Organization Name and Address MGA Research Corporation 5000 Warren Road Burlington, WI 53105</p>		<p>10. Work Unit No.</p>	
		<p>11. Contract or Grant No. DTNH22-06-D-00028</p>	
<p>12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Crashworthiness Standards (NVS-111) 1200 New Jersey Ave, SE, Room W43-410 Washington, D.C. 20590</p>		<p>13. Type of Report and Period Covered Final Test Report March 2 to March 23, 2012</p>	
		<p>14. Sponsoring Agency Code NVS-111</p>	
<p>15. Supplementary Notes</p>			
<p>16. Abstract</p> <p>An FMVSS No. 305 Indicant test, in conjunction with an NCAP frontal barrier impact test was conducted on the subject 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan in accordance with the specifications of the applicable Office of Crashworthiness Standards Test Procedures for the generation of consumer information for the New Car Assessment Program (NCAP). No test failures were reported.</p>			
<p>17. Key Words New Car Assessment Program (NCAP) FMVSS 305 Indicant</p>		<p>18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Administration Technical Information Services Division, NPO-411 1200 New Jersey Ave, SE, Room E12-100 Washington, DC 20590 Email: tis@nhtsa.dot.gov FAX: 202-493-2833</p>	
<p>19. Security Classification of Report Unclassified</p>	<p>20. Security Classification of Page Unclassified</p>	<p>21. No. of Pages 44</p>	<p>22. Price</p>

TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1	Purpose of Test	1
2	Summary of Test Results	2
3	Data Sheets	3
 <u>Data Sheet</u>		 <u>Page No.</u>
1	Test Vehicle Specifications	4
2	Pre-Impact Data	6
3	Pre-Impact Electric Isolation Measurements and Calculations	7
4	Post-Impact Data	9
5	Static Rollover Test Data	11
 <u>Appendix</u>		
A	Photographs	A-1

SECTION 1
PURPOSE OF TEST

An FMVSS No. 305 Indicant test, in conjunction with an NCAP frontal barrier impact test was conducted on the subject 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan.

The Indicant test was conducted to determine compliance to the requirements of Federal Motor Vehicle Safety Standard (FMVSS) No. 305, "Electric-Powered Vehicles: Electrolyte Spillage and Electrical Shock Protection" for the purpose of providing consumer information.

This FMVSS No. 305 Indicant test is part of the FY12 New Car Assessment Program Test Program, sponsored by the National Highway Traffic Safety Administration (NHTSA), under contract DTNH22-06-D-00028.

SECTION 2 SUMMARY OF TEST RESULTS

A frontal barrier impact test was performed by MGA Research Corporation on a 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan on March 2, 2012. Electrical isolation measurements were taken immediately post-impact and observations were made related to electrolyte spillage and battery retention. A static rollover was subsequently performed on the subject vehicle and electrical isolation measurements were taken at each stage of the rollover.

Based on the test results, the 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan appears to meet the requirements for electrolyte spillage, electrical isolation, and battery retention during FMVSS No. 305 Indicant testing.

Data sheets, along with pre-test and post-test photographs of the test vehicle, are included in this report to document the test.

TEST NOTES

None

MGA does not endorse or certify products. The manufacturer's name appears solely for identification purposes.

**SECTION 3
DATA SHEETS**

**DATA SHEET NO. 1
TEST VEHICLE SPECIFICATIONS**

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan

NHTSA No. MC0118

TEST VEHICLE INFORMATION

Year/Make/Model/Body Style	2012 Buick Regal Premium II Group with
NHTSA No.	MC0118
Color	Quicksilver Metallic
Odometer Reading	65 miles

DATA FROM CERTIFICATION LABEL

Manufactured By	GENERAL MOTORS OF CANADA LTD.	GVWR (kg)	2097
Date of Manufacture	10/11	GAWR Front (kg)	1083
VIN:	2G4GT5GR7C9137725	GAWR Rear (kg)	1014

ELECTRIC VEHICLE PROPULSION SYSTEM

Type of Electric Vehicle (Electric/Hybrid):	Electric Assist / Gas
Electric Energy Storage/Device:	Lithium-Ion (Li-Ion) Battery
Nominal Voltage (V):	115.2 V
Is this vehicle equipped with an Automatic Propulsion Battery Disconnect?	Yes
Physical Location of the Automatic Propulsion Battery Disconnect:	Behind Right Rear Passenger Seat
Auxiliary Battery Type:	12 V Lead-Acid Battery

ELECTRIC ENERGY STORAGE CONVERSION/DEVICE SYSTEM DATA (COTR SUPPLIED)

Electrolyte Fluid Type:	Organic Carbonates
Electrolyte Fluid Specific Gravity:	1.1 - 1.2 gm/cc
Electrolyte Kinematic Viscosity (centistokes):	2.0 – 2.1 centipoise
Electrolyte Fluid Color:	Colorless
Electric Energy Storage/Conversion System Coolant Type, Color, Specific Gravity (if applicable):	Air Cooled
Location of Battery Modules:	<input checked="" type="checkbox"/> Inside Passenger Compartment
	<input type="checkbox"/> Outside Passenger Compartment
	Behind Right Rear Passenger Seat

**DATA SHEET NO. 1
TEST VEHICLE SPECIFICATIONS**

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan

NHTSA No. MC0118

ELECTRIC ENERGY STORAGE CONVERSION/DEVICE STATE OF CHARGE

<i>For all battery types:</i>	
Voltage range corresponding to useable energy of the battery:	
Minimum State of Charge:	108.0 V
Maximum State of Charge:	121.5 V
95% of Maximum State of Charge:	115.4 V
Test Voltage - No less than 95% of maximum State of Charge:	114.6 V
<i>For batteries that are rechargeable ONLY by an energy source on the vehicle:</i>	
Voltage range corresponding to useable energy of the battery:	
Minimum State of Charge:	108.0 V
Maximum State of Charge:	121.5 V
Test Voltage – Maximum practicable State of Charge within Normal Operating Range:	114.7 V

**DATA SHEET 2
PRE-IMPACT DATA**

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan

NHTSA No. MC0118

VEHICLE CHASSIS GROUND POINT(S) LOCATION(S)

Details of Vehicle Chassis Ground Point(s) & Location(s)	On Battery Control Module Mounting Stud
--	---

ELECTRIC ENERGY STORAGE/CONVERSION TEST POINTS

Details of Electric Energy Storage/Conversion System Test Points:	+ On Inverter Side of Contactor - On Battery "Negative" Node
---	---

**DATA SHEET 3
PRE-IMPACT ELECTRIC ISOLATION MEASUREMENTS & CALCULATIONS**

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan
 NHTSA No. MC0118

VOLTMETER INFORMATION

Make:	Fluke
Model:	11
Serial Number:	68541895
Internal Impedance Value (MΩ):	> 10 MΩ < 100 pF
Resolution (V):	.001 Volts
Last Calibration Date:	01/23/2012

ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM VOLTAGE

Measurement shall be made with Energy Storage/Conversion System connected to the vehicle propulsion system, and the vehicle in the “ready-to-drive” (propulsion system energized) position.

If voltage measurement is not at the voltage or within the normal operating voltage range specified by the manufacturer, the battery must be charged.

Vb (V):	114.7
---------	-------

ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM TO VEHICLE CHASSIS

Vehicle chassis point(s) determined and supplied to contractor by COTR.

V1 (V):	42.8
V2 (V):	45.2

ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM TO VEHICLE CHASSIS ACROSS RESISTOR

The known resistance Ro (in ohms) should be approximately 500 times the normal operating voltage of the vehicle (in volts) per SAE J1766.

Ro (Ω):	75500
---------	-------

V1' (V) Pre-Impact:	1.3
V2' (V) Pre-Impact:	1.4

DATA SHEET 3 (CONTINUED)
PRE-IMPACT ELECTRICAL ISOLATION MEASUREMENTS & CALCULATIONS

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan
 NHTSA No. MC0118

ELECTRICAL ISOLATION MEASUREMENT

Note: If measured voltage is zero and results in a division by zero, record "Zero Volts". This "zero voltage" condition is considered as being compliant.

V1' (V):	1.3
$R_{i1} = R_o (1 + V_2/V_1) [(V_1 - V_1')/V_1']$	
Ri1 (Ω):	4955536
V2' (V):	1.4
$R_{i2} = R_o (1 + V_1/V_2) [(V_2 - V_2')/V_2']$	
Ri2 (Ω):	4598723
Ri = The lesser of Ri1 and Ri2	
Ri Pre-Test ((Ω):	4598723
Ri/Vb (Ω/V):	40093
Minimum Electrical Isolation Value is 500 Ω/V	

Is the measured Electrical Isolation Value:	Yes, Pass	No, Fail
≥500 Ω/V without electrical isolation monitoring	X	
≥100 Ω/V with electrical isolation monitoring		

**DATA SHEET 4
POST-IMPACT DATA**

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan
 NHTSA No. MC0118

VOLTMETER INFORMATION

Make:	Fluke
Model:	11
Serial Number:	68541895
Internal Impedance Value (MΩ):	> 10 MΩ < 100 pF
Nominal Propulsion Battery Voltage (Vb) (V):	114.7

**ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM
VOLTAGE LOCATION OF MEASUREMENT**

Measurement is made from the side of the automatic disconnect connected to the electric powertrain.

Vb (V):	52.4
---------	------

ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM VOLTAGE

V1 =	32.5	V	Impact Time:	0	Minutes	57	s
V2 =	39.4	V	Impact Time:	1	Minutes	20	s
V1' =	0.9	V	Impact Time:	1	Minutes	6	s
V2' =	0.04	V	Impact Time:	1	Minutes	25	s

ELECTRICAL ISOLATION MEASUREMENT

Note: If measured voltage is zero and results in a division by zero, record "Zero Volts". This "zero voltage" condition is considered as being compliant.

$Ri1 = Ro (1 + V2/V1) [(V1-V1')/V1']$							
Ri1 =	5864582	Ω	Impact Time:	0	Minutes	57	s
$Ri2 = Ro (1 + V1/V2) [(V2-V2')/V2']$							
Ri2 =	135573472	Ω	Impact Time:	1	Minutes	20	s
Ri = The lesser of Ri1 and Ri2							
Ri =	5864582	Ω	Impact Time:	0	Minutes	57	s
Ri/Vb = electrical Isolation Value/Nominal Battery Voltage							
Minimum Electrical Value is 500 Ω/V							
Ri/Vb =	51130	Ω/V	Impact Time:	0	Minutes	57	s

Is the measured Electrical Isolation Value:	Yes, Pass	No, Fail
≥500 Ω/V without electrical isolation monitoring	X	
≥100 Ω/V with electrical isolation monitoring		

**DATA SHEET 4 (CONTINUED)
POST-IMPACT DATA**

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan

NHTSA No. MC0118

ELECTRIC ENERGY STORAGE/CONVERSION DEVICE

	Inside Passenger Compartment	Outside Passenger Compartment
Location of Electric Energy Storage/Conversion Device:	X	

	Yes, Pass	No, Fail
All Components of Electrical Energy Storage/Conversion Device remained attached to the vehicle with at least one mounting location.	X	

Describe Electric Energy Storage/Conversion Device movement within the passenger compartment [Supply photographs as appropriate]:
Not Applicable

	Yes, Fail	No, Pass
Has the Electric Energy Storage/Conversion Device moved within the passenger compartment?		X

Describe intrusion of an outside Electric Energy Storage/Conversion Device into the passenger compartment [Supply photographs as appropriate]:
No Intrusion


	Yes, Fail	No, Pass
Has an outside Electric Energy Storage/Conversion Device intruded into the passenger compartment?		X

	Yes, Fail	No, Pass
Is Electric Energy Storage/Conversion Device electrolyte spillage visible in the passenger compartment?		X

**DATA SHEET 5
STATIC ROLLOVER TEST DATA**

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan

NHTSA No. MC0118



**DETERMINATION OF ELECTRIC ENERGY STORAGE/CONVERSION DEVICE
ELECTROLYTE COLLECTION TIME PERIOD**

Rollover Stage	Rotation Time (spec. 1-3 min)				FMVSS 301 Hold Time		Total Time				Next Whole Minute Interval	
0° - 90°	1	minutes	50	seconds	5	minutes	7	minutes	50	seconds	8	minutes
90° - 180°	1	minutes	49	seconds	5	minutes	7	minutes	49	seconds	8	minutes
180° - 270°	1	minutes	45	seconds	5	minutes	7	minutes	45	seconds	8	minutes
270° - 360°	1	minutes	57	seconds	5	minutes	7	minutes	57	seconds	8	minutes

**ACTUAL TEST VEHICLE ELECTRIC ENERGY STORAGE/CONVERSION DEVICE
ELECTROLYTE SPILLAGE**

Rollover Stage	Electric Energy Storage/Conversion Device Electrolyte Spillage (L)	Spillage Location
0° to 90°	0	Not Applicable
90° to 180°	0	Not Applicable
180° to 270°	0	Not Applicable
270° to 360°	0	Not Applicable

Total Spillage: 0 L

	Yes, Fail	No, Pass
Is the total spillage of Electric Energy Storage/Conversion Device electrolyte greater than 5.0 Liters?		X
Is Electric Energy Storage/Conversion Device electrolyte spillage visible in the passenger compartment?		X

**DATA SHEET 5 (CONTINUED)
STATIC ROLLOVER TEST DATA**

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan

NHTSA No. MC0118

VOLTMETER INFORMATION

Make:	Fluke
Model:	11
Serial Number:	68541895
Internal Impedance Value (MΩ):	> 10 MΩ < 100 pF
Nominal Electric Energy Storage/Conversion Device Voltage (Vb) (V):	114.7
Record V1, V2, V1', V2' voltage measurements at the start of each successive increment of 90°, 180°, 270°, and 360° of the static rollover test.	

ELECTRICAL ISOLATION MEASUREMENT

V1 =	30.9	V	0°	Time:		Minutes		s
V1 =	30.9	V	90°	Time:	2	Minutes	15	s
V1 =	30.9	V	180°	Time:	2	Minutes	14	s
V1 =	30.9	V	270°	Time:	2	Minutes	9	s
V1 =	30.9	V	360°	Time:	2	Minutes	17	s
V2 =	3.1	V	0°	Time:		Minutes		s
V2 =	3.0	V	90°	Time:	2	Minutes	30	s
V2 =	3.0	V	180°	Time:	2	Minutes	31	s
V2 =	2.9	V	270°	Time:	2	Minutes	28	s
V2 =	2.9	V	360°	Time:	2	Minutes	32	s
V1' =	0.9	V	0°	Time:		Minutes		s
V1' =	0.9	V	90°	Time:	2	Minutes	19	s
V1' =	0.9	V	180°	Time:	2	Minutes	19	s
V1' =	0.9	V	270°	Time:	2	Minutes	16	s
V1' =	0.9	V	360°	Time:	2	Minutes	22	s
V2' =	0.1	V	0°	Time:		Minutes		s
V2' =	0.1	V	90°	Time:	2	Minutes	36	s
V2' =	0.1	V	180°	Time:	2	Minutes	35	s
V2' =	0.1	V	270°	Time:	2	Minutes	31	s
V2' =	0.1	V	360°	Time:	2	Minutes	36	s
Vb =	35.4	V	0°	Time:		Minutes		s
Vb =	35.4	V	90°	Time:	2	Minutes	0	s
Vb =	35.4	V	180°	Time:	2	Minutes	4	s
Vb =	35.4	V	270°	Time:	1	Minutes	59	s
Vb =	35.4	V	360°	Time:	2	Minutes	8	s

**DATA SHEET 5 (CONTINUED)
STATIC ROLLOVER TEST DATA**

Test Vehicle: 2012 Buick Regal Premium II Group with eAssist 4-Dr Hybrid Sedan

NHTSA No. MC0118

ELECTRICAL ISOLATION CALCULATION

Note: If measured voltage is zero and results in a division by zero, record "Zero Volts". This "zero voltage" condition is considered as being compliant.

$R_{i1} = R_o (1 + V_2/V_1) [(V_1 - V_1')/V_1']$								
Ri1 =	2769148	Ω	0°	Time:		Minutes		s
Ri1 =	2761003	Ω	90°	Time:	2	Minutes	15	s
Ri1 =	2761003	Ω	180°	Time:	2	Minutes	14	s
Ri1 =	2752859	Ω	270°	Time:	2	Minutes	9	s
Ri1 =	2752859	Ω	360°	Time:	2	Minutes	17	s
$R_{i2} = R_o (1 + V_1/V_2) [(V_2 - V_2')/V_2']$								
Ri2 =	24841935	Ω	0°	Time:		Minutes		s
Ri2 =	24741350	Ω	90°	Time:	2	Minutes	19	s
Ri2 =	24741350	Ω	180°	Time:	2	Minutes	19	s
Ri2 =	24639034	Ω	270°	Time:	2	Minutes	16	s
Ri2 =	24639034	Ω	360°	Time:	2	Minutes	22	s
Ri = The lesser of Ri1 and Ri2								
Ri =	2769148	Ω	0°	Time:		Minutes		s
Ri =	2761003	Ω	90°	Time:	2	Minutes	15	s
Ri =	2761003	Ω	180°	Time:	2	Minutes	14	s
Ri =	2752859	Ω	270°	Time:	2	Minutes	9	s
Ri =	2752859	Ω	360°	Time:	2	Minutes	17	s
Ri/Vb = Electrical Isolation Value/Nominal Battery Voltage Minimum Electrical Isolation Value is 500 Ω/V								
Ri/Vb =	24143	Ω/V	0°	Time:		Minutes		s
Ri/Vb =	24072	Ω/V	90°	Time:	2	Minutes	15	s
Ri/Vb =	24072	Ω/V	180°	Time:	2	Minutes	14	s
Ri/Vb =	24001	Ω/V	270°	Time:	2	Minutes	9	s
Ri/Vb =	24001	Ω/V	360°	Time:	2	Minutes	17	s

Is the measured Electrical Isolation Value:	Yes, Pass	No, Fail
≥500 Ω/V without electrical isolation monitoring	X	
≥100 Ω/V with electrical isolation monitoring		

APPENDIX A
PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

	<u>Page No.</u>
Auxiliary Power Module Warning Label	A-1
Power Inverter Warning Label	A-1
First Responder Warning Label	A-2
First Responder Warning Location	A-2
First Responder Warning Location	A-3
Other Vehicle Label(s) Related to Electrical Propulsion System	A-3
Other Vehicle Label(s) Related to Electrical Propulsion System	A-4
Other Vehicle Label(s) Related to Electrical Propulsion System	A-4
Other Vehicle Label(s) Related to Electrical Propulsion System	A-5
Other Vehicle Label(s) Related to Electrical Propulsion System	A-5
Manual High Voltage Service Disconnect in Place	A-6
Manual High Voltage Service Disconnect Removed	A-6
Manual High Voltage Service Disconnect Removed	A-7
Pre-Impact View of Propulsion Battery	A-7
Post-Impact Front View of Propulsion Battery	A-8
Post-Impact Rear View of Propulsion Battery	A-8
Pre-Impact View of Battery Box(s) or Container(s) Which Holds Individual Battery Modules	A-9
Post-Impact View of Battery Box(s) or Container(s) Which Holds Individual Battery Modules	A-9
Pre-Impact View of Propulsion Battery Module(s)	A-10
Post-Impact View of Propulsion Battery Module(s)	A-10
Pre-Impact View of Electric Propulsion Drive	A-11
Post-Impact View of Electric Propulsion Drive	A-11
Pre-Impact View of High Voltage Interconnect(s)	A-12
Pre-Impact View of Other Visible Electric Propulsion Components	A-12
Pre-Impact View Propulsion Battery Venting System(s)	A-13
Pre-Impact View of Ground Lead Attached	A-13
Pre-Impact View of High Voltage Leads Attached	A-14
Pre-Impact Close-Up View of High Voltage Leads Attached	A-14
Pre-Impact View of Installed Impact Interface Port	A-15
Post-Impact View of Installed Impact Interface Port	A-15
Pre-Impact View of Other Test Devices	A-16
Post-Impact View of Other Test Devices	A-16
FMVSS No. 305 Static Rollover at 90°	A-17
FMVSS No. 305 Static Rollover at 180°	A-17

	<u>Page No.</u>
FMVSS No. 305 Static Rollover at 270°	A-18
FMVSS No. 305 Static Rollover at 360°	A-18
Pre-Impact View of the Vehicle Passenger Compartment Adjacent to Propulsion Battery	A-19
Post-Impact View of the Vehicle Passenger Compartment Adjacent to Propulsion Battery	A-19
Post-Impact Propulsion Battery System Mounting and/or Intrusion Failure(s)	A-20
Post-Impact View of Battery Component Intrusion	A-20
Post-Impact View of Battery Module Movement or Retention Loss	A-21
Post-Impact View of Propulsion Battery Electrolyte Spillage Location	A-21
Post-Test View of Propulsion Battery Electrolyte Spillage Location	A-22
As Delivered Right Front $\frac{3}{4}$ View of Impact Vehicle	A-22
As Delivered Left Rear $\frac{3}{4}$ View of Impact Vehicle	A-23
Vehicle's Certification Label	A-23
Vehicle's Tire Information Placard or Label	A-24
Electric Energy Storage/Conversion Test Points	A-24

PHOTOGRAPH NOT APPLICABLE

No. 001 Auxiliary Power Module Warning Label

PHOTOGRAPH NOT APPLICABLE

No. 002 Power Inverter Warning Label



No. 003 First Responder Warning Label




No. 004 First Responder Warning Location



No. 004a First Responder Warning Location



No. 005 Other Vehicle Label(s) Related To Electrical Propulsion System



No. 005a Other Vehicle Label(S) Related To Electrical Propulsion System



No. 005b Other Vehicle Label(S) Related To Electrical Propulsion System



No. 005c Other Vehicle Label(S) Related To Electrical Propulsion System



No. 005d Other Vehicle Label(S) Related To Electrical Propulsion System



No. 006 Manual High Voltage Service Disconnect In Place



No. 007 Manual High Voltage Service Disconnect Removed

PHOTOGRAPH NOT APPLICABLE

No. 008 Manual High Voltage Service Disconnect Removed



No. 009 Pre-Impact View Of Propulsion Battery



No. 010 Post-Impact Front View Of Propulsion Battery



No. 011 Post-Impact Rear View Of Propulsion Battery



No. 012 Pre-Impact View Of Battery Box(S) Or Container(S) Which Holds Individual Battery Modules



No. 013 Post-Impact View Of Battery Box(S) Or Container(S) Which Holds Individual Battery Modules



No. 014 Pre-Impact View Of Propulsion Battery Module(S)




No. 015 Post-Impact View Of Propulsion Battery Module(S)



No. 016 Pre-Impact View Of Electric Propulsion Drive



No. 017 Post-Impact View Of Electric Propulsion Drive




No. 018 Pre-Impact View of High Voltage Interconnect(s)



No. 019 Pre-Impact View Of Other Visible Electric Propulsion Components




No. 020 Pre-Impact View Propulsion Battery Venting System(S)




No. 021 Pre-Impact View Of Ground Lead Attached




No. 022 Pre-Impact View Of High Voltage Leads Attached



No. 023 Pre-Impact Close-Up View Of High Voltage Leads Attached



No. 024 Pre-Impact View Of Installed Impact Interface Port



No. 025 Post-Impact View Of Installed Impact Interface Port

PHOTOGRAPH NOT APPLICABLE

No. 026 Pre-Impact View Of Other Test Devices

PHOTOGRAPH NOT APPLICABLE


No. 027 Post-Impact View Of Other Test Devices



No. 028 Fmvss No. 305 Static Rollover At 90°



No. 029 Fmvss No. 305 Static Rollover At 180°



No. 030 Fmvss No. 305 Static Rollover At 270°



No. 031 Fmvss No. 305 Static Rollover At 360°



No. 032 Pre-Impact View Of The Vehicle Passenger Compartment Adjacent To Propulsion Battery



No. 033 Post-Impact View Of The Vehicle Passenger Compartment Adjacent To Propulsion Battery

PHOTOGRAPH NOT APPLICABLE

No. 034 Post-Impact Propulsion Battery System Mounting And-Or Intrusion Failure(S)

PHOTOGRAPH NOT APPLICABLE

No. 035 Post-Impact View Of Battery Component Intrusion

PHOTOGRAPH NOT APPLICABLE

No. 036 Post-Impact View Of Battery Module Movement Or Retention Loss

PHOTOGRAPH NOT APPLICABLE

No. 037 Post-Impact View Of Propulsion Battery Electrolyte Spillage Location

PHOTOGRAPH NOT APPLICABLE

No. 038 Post-Test View Of Propulsion Battery Electrolyte Spillage Location




No. 039 As Delivered Right Front $\frac{3}{4}$ View Of Impact Vehicle




No. 040 As Delivered Left Rear ¾ View Of Impact Vehicle



No. 041 Vehicle's Certification Label



No. 042 Vehicle's Tire Information Placard Or Label



No. 043 Electric Energy Storage-Conversion Test Points