

REPORT NUMBER: 208-MGA-2013-003

**VEHICLE SAFETY COMPLIANCE TESTING
FOR
FMVSS 208, OCCUPANT CRASH PROTECTION
FMVSS 212, WINDSHIELD MOUNTING
FMVSS 219, WINDSHIELD INTRUSION (PARTIAL)
FMVSS 301, FUEL SYSTEM INTEGRITY**

**GENERAL MOTORS LLC
2013 CHEVROLET SONIC PASSENGER CAR
NHTSA NO.: C20130100**

**PREPARED BY:
MGA RESEARCH CORPORATION
5000 WARREN ROAD
BURLINGTON, WI 53105**



TEST DATES: JANUARY 18, 2013 – FEBRUARY 25, 2013

FINAL REPORT DATE: MARCH 25, 2013

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
OFFICE OF ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
1200 NEW JERSEY AVENUE, S.E., NVS-220
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, in response to Contract Number DTNH22-08-D-00086.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: Jeff Lewandowski Date: March 25, 2013
Jeff Lewandowski, Project Engineer

Reviewed by: David Winkelbauer Date: March 25, 2013
David Winkelbauer, Facility Director

FINAL REPORT ACCEPTED BY OVSC:

Accepted By:



Acceptance Date: March 25, 2013

Technical Report Documentation Page

1. Report No. 208-MGA-2013-003	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle Final Report of FMVSS 208 Compliance Testing of a 2013 Chevrolet Sonic NHTSA No.: C20130100		5. Report Date March 25, 2013	
		6. Performing Organization Code MGA	
7. Author(s) Jeff Lewandowski, Project Engineer		8. Performing Organization Report No. 208-MGA-2013-003	
9. Performing Organization Name and Address MGA Research Corporation 5000 Warren Road Burlington, WI 53105		10. Work Unit No.	
		11. Contract or Grant No. DTNH22-08-D-00086	
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Enforcement Office of Vehicle Safety Compliance 1200 New Jersey Avenue, S.E., NVS-220 Washington, D.C. 20590		13. Type of Report and Period Covered 1/18/13 – 2/25/13	
		14. Sponsoring Agency Code NVS-220	
15. Supplementary Notes			
16. Abstract Compliance tests were conducted on the subject 2013 Chevrolet Sonic in accordance with the specifications of the Office of Vehicle Safety Compliance Test Procedure No. TP208-14 for the determination of FMVSS 208 compliance. Test failures identified were as follows: TEST FAILURES: None			
17. Key Words Frontal Impact 40 kmph Vehicle Safety Compliance Testing FMVSS 208, "Occupant Crash Protection" FMVSS 212, "Windshield Mounting" FMVSS 219, (partial), "Windshield Zone Intrusion" FMVSS 301, "Fuel System Integrity"		18. Distribution Statement Copies of this report are available from the following: U.S. Department of Transportation National Highway Traffic Safety Administration Technical Information Services (TIS), NPO-411 1200 New Jersey Avenue, S.E. (Room E12-100) Washington, DC 20590	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 320	22. Price

TABLE OF CONTENTS

<u>Section</u>	<u>Page No</u>
1 Purpose of Compliance Tests	1
2 Tests Performed	2
3 Injury Result Summary for FMVSS 208 Tests	4
4 Discussion of Tests (if applicable)	6
5 Test Data Sheets	7
 <u>Data Sheet</u>	
1 COTR Vehicle Work Order	8
2 Report of Vehicle Condition	13
3 Certification Label and Tire Placard Information	15
4 Rear Seating Position Seat Belts	16
5 Air Bag Labels	17
6 FMVSS 208 Readiness Indicator	24
7 Passenger Air Bag Manual Cut-Off Device	25
8 Lap Belt Lockability	28
9 FMVSS 208 Seat Belt Warning System Check	40
10 Belt Contact Force	41
11 Latch Plate Access	47
12 Seat Belt Retraction	50
13 Seat Belt Guides and Hardware	53
16 Air Bag Suppression Telltale	56
17 Suppression Test Using 12-Month CRABI Dummy	57
18 Suppression Test Using Newborn Infant Dummy	67
19 Suppression Test Using 3-YO Dummy and Booster Seats	68
20 Suppression Test Using 3-YO Dummy and Fwd Facing Restraints	70
21 Suppression Test Using an Unbelted 3-YO Dummy	74
22H Suppression Test Using 6-YO Child and Booster Seats	75
23H Suppression Test Using an Unbelted 6-YO Child	77
29 Summary of Low Risk Deployment Using an Unbelted 5 th % Dummy Position 1	78
30 Summary of Low Risk Deployment Using an Unbelted 5 th % Dummy Position 2	79
32 Vehicle Weight, Fuel Tank, and Attitude Data	80
33 Vehicle Accelerometer Locations and Measurements	84
34 Photographic Targets	87
35 Camera Locations	93
36 Dummy Positioning	95
37 Dummy Measurements	111

<u>Data Sheet</u>		<u>Page No</u>
38	Crash Test	114
40	Accident Investigation Measurements	116
41	Windshield Mounting (FMVSS 212)	118
42	Windshield Zone Intrusion (FMVSS 219)	120
43	Fuel System Integrity (FMVSS 301)	122

Appendix

A	Crash Test Data	A-1
B	Low Risk Test Data	B-1
C	Crash Test Photographs	C-1
D	Low Risk Test Data	D-1
E	Suppression Photographs	E-1
F	Instrumentation Calibration	F-1
G	Notice of Test Failure (If Applicable)	G-1

SECTION 1
PURPOSE OF COMPLIANCE TESTS

This Federal Motor Vehicle Safety Standard 208 compliance test is part of a program conducted for the National Highway Traffic Safety Administration (NHTSA) by MGA Research Corporation (MGA) under Contract No.: DTNH22-08-D-00086. The purpose of this test was to determine whether the subject vehicle, a 2013 Chevrolet Sonic, NHTSA No.: C20130100, meets certain performance requirements of FMVSS 208, "Occupant Crash Protection"; FMVSS 212, "Windshield Mounting"; FMVSS 219, "Windshield Zone Intrusion"; and FMVSS 301, "Fuel System Integrity". The compliance test was conducted in accordance with OVSC Laboratory Test Procedure No. TP208-14 dated April 16, 2008.

SECTION 2

TESTS PERFORMED

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance

NHTSA No.: C20130100
 Test Dates: 1/18/13 - 2/25/13

The following checked items indicate the tests that were performed:

X	1.	Rear seating position seat belts
X	2.	Air bag labels (S4.5.1)
X	3.	Readiness indicator (S4.5.2)
X	4.	Passenger air bag manual cut-off device (S4.5.4)
X	5.	Lap belt lockability (S7.1.1.5)
X	6.	Seat belt warning system (S7.3)
X	7.	Seat belt contact force (S7.4.3)
X	8.	Seat belt latch plate access (S7.4.4)
X	9.	Seat belt retraction (S7.4.5)
X	10.	Seat belt guides and hardware (S7.4.6)
X	11.	Air bag suppression telltale (S19.2.2)
X	12.	Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R)
X	13.	Suppression tests with Newborn infant (Part 572, Subpart K)
X	14.	Suppression tests with 3-year-old dummy (Part 572, Subpart P)
X	15.	Suppression tests with a representative 6-year-old child
X	16.	Test of Reactivation of the passenger air bag system with a representative unbelted 5 th percentile female.
	17.	Low risk deployment test with 12-month-old dummy (Part 572, Subpart R)
	18.	Low risk deployment test with 3-year-old dummy (Part 572, Subpart P)
	19.	Low risk deployment test with 6-year-old dummy (Part 572, Subpart N)
X	20.	Low risk deployment test with 5 th female dummy (Part 572, Subpart O)
X	21.	Impact Tests
		Frontal Oblique
		Belted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a))
		Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1))
		Unbelted 50 th male dummy driver and passenger (32 to 40 kmph) (S5.1.2(a)(1) or S5.1.2(b))
X		Frontal 0°
		Belted 50 th male dummy driver (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))
		Belted 50 th male dummy passenger (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))
		Belted 5 th female dummy driver (0 to 48 kmph) (S16.1(a))
		Belted 5 th female dummy passenger (0 to 48 kmph) (S16.1(a))
		Belted 50 th male dummy driver and passenger (0 to 56 kmph) (S5.1.1.(b)(2))
		Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1))
		Unbelted 50 th male dummy driver (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
		Unbelted 50 th male dummy passenger (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
		X Unbelted 5 th female dummy driver (32 to 40 kmph) (S16.1(b))
		X Unbelted 5 th female dummy passenger (32 to 40 kmph) (S16.1(b))
		40% Offset 0° Belted 5 th female dummy driver and passenger (0 to 40 kmph) (S18.1)
	22.	FMVSS 204 Indicant Test
X	23.	FMVSS 212 Test
X	24.	FMVSS 219 Indicant Test
X	25.	FMVSS 301 Frontal Test
	26.	FMVSS 305 Frontal Indicant Test

For the crash tests, the vehicle was instrumented with 8 accelerometers. The data from the vehicle and dummies were sampled at 10,000 samples per second and processed as specified in SAE J211/1 MAR95 and FMVSS 208, S4.13.

The dynamic tests were recorded using high-speed digital video.

The vehicle appears to meet all of the performance requirements to which it was tested.

SECTION 3

INJURY RESULT SUMMARY FOR FMVSS 208 TESTS

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance

NHTSA No.: C20130100
 Test Date: 2/11/13

5th Percentile Female Low Risk Deployments

5th Percentile Female SN 510 Position 1 (Chin On Module) 2/11/13

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	19
Peak Nij (Nte)	1.0	0.3
Time (ms)	NA	121.5
Peak Nij (Ntf)	1.0	0.3
Time (ms)	NA	12.6
Peak Nij (Nce)	1.0	0.4
Time (ms)	NA	170.8
Peak Nij (Ncf)	1.0	0.3
Time (ms)	NA	17.0
Neck Tension	2070 N	379
Neck Compression	2520 N	347
Chest g	60 g	10
Chest Displacement	52 mm	6
Left Femur	6805 N	76
Right Femur	6805 N	86

Second stage fire time of 120 ms; Injuries calculated on 0 ms to 245 ms.

5th Percentile Female SN 510 Position 2 (Chin On Rim) 2/11/13

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	5
Peak Nij (Nte)	1.0	0.4
Time (ms)	NA	13.4
Peak Nij (Ntf)	1.0	0.1
Time (ms)	NA	45.1
Peak Nij (Nce)	1.0	0.1
Time (ms)	NA	189.5
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	58.7
Neck Tension	2070 N	525
Neck Compression	2520 N	132
Chest g	60 g	20
Chest Displacement	52 mm	18
Left Femur	6805 N	23
Right Femur	6805 N	39

Second stage fire time of 120 ms; Injuries calculated on 0 ms to 245 ms.

SECTION 3

INJURY RESULT SUMMARY FOR FMVSS 208 TESTS

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance

NHTSA No.: C20130100
 Test Date: 2/25/13

40 kmph Frontal Crash

Impact Angle:	Zero			
Belted Dummies:		Yes	X	No

Speed Range:		0 to 40 kmph	X	32 to 40 kmph
		0 to 48 kmph		0 to 56 kmph

Test Speed (kmph):	39.6	Test Weight (kg):	1390.3
--------------------	------	-------------------	--------

Driver Dummy:	X	5 th female		50 th male
Passenger Dummy:	X	5 th female		50 th male

5th Percentile Female Frontal Crash Test

Vehicles certified to S16.1 (a) (1), S16.1 (a) (2), S16.1 (b), or S18.1

Injury Criteria	Max. Allowable Injury Assessment Values	Driver	Passenger
HIC15	700	236	182
N _{te}	1.0	0.3	0.2
N _{tf}	1.0	0.4	0.4
N _{ce}	1.0	0.2	0.2
N _{cf}	1.0	0.1	0.5
Neck Tension	2620 N	1509	341
Neck Compression	2520 N	401	354
Chest g	60 g	43	40
Chest Displacement	52 mm	14	6
Left Femur	6805 N	2544	4284
Right Femur	6805 N	4206	4107

SECTION 4
DISCUSSION OF TESTS

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance

NHTSA No.: C20130100
Test Dates: 1/18/13 - 2/25/13

A blanket and visor were not used in the suppression testing because they did not affect the sensing system used on the vehicle.

There was no valid data after 62ms on the Trunk (Z) accelerometer during the frontal impact test.

SECTION 5
TEST DATA SHEETS

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance

NHTSA No.: C20130100
Test Dates: 1/18/13 - 2/25/13

DATA SHEET 1
COTR VEHICLE WORK ORDER

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance

NHTSA No.: C20130100
Test Dates: 1/18/13 - 2/25/13

COTR Signature: Brian Smith

Test to be performed for this vehicle are checked below:

☒	1.	Rear Seating Position Seat Belts
☒	2.	Air Bag Labels (S4.5.1)
☒	3.	Readiness Indicator (S4.5.2)
☒	4.	Passenger Air Bag Manual Cut-off Device (S4.5.4)
☒	5.	Lap Belt Lockability (S7.1.1.5)
☒	6.	Seat Belt Warning System (S7.3)
☒	7.	Seat Belt Contact Force (S7.4.3)
☒	8.	Seat Belt Latch Plate Access (S7.4.4)
☒	9.	Seat Belt Retraction (S7.4.5)
☒	10.	Seat Belt Guides and Hardware (S7.4.6)
☒	11.	Air bag suppression telltale (S19.2.2)
☒	12.	Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R) using the following indicated child restraints (mid-height seat position):
Section B – Rear Facing (unbelted and belted rear facing, unbelted forward facing)		
☐		Century Smart Fit 4543 ☐ Full Rearward ☐ Mid Position ☐ Full Forward
☒		Cosco Arriva 22-013 ☒ Full Rearward ☒ Mid Position ☒ Full Forward
☐		Evenflo Discovery Adjust Right 212 ☐ Full Rearward ☐ Mid Position ☐ Full Forward
☐		Graco Infant 8457 ☐ Full Rearward ☐ Mid Position ☐ Full Forward
☒		Graco Snugride ☒ Full Rearward ☒ Mid Position ☒ Full Forward
☒		Peg Perego Viaggio ☒ Full Rearward ☒ Mid Position ☒ Full Forward
Section C – Convertible (unbelted and belted rear facing, unbelted and belted forward facing)		
☒		Britax Roundabout E9L02 ☒ Full Rearward ☒ Mid Position ☒ Full Forward
☒		Cosco High Back Booster 22-209 ☒ Full Rearward ☒ Mid Position ☒ Full Forward
☐		Cosco Summit Deluxe 22-262 ☐ Full Rearward ☐ Mid Position ☐ Full Forward
☐		Cosco Touriva 02519 ☐ Full Rearward ☐ Mid Position ☐ Full Forward
☒		Evenflo Generations 352 ☒ Full Rearward ☒ Mid Position ☒ Full Forward
☐		Evenflo Medallion 254 ☐ Full Rearward ☐ Mid Position ☐ Full Forward
☐		Evenflo Tribute V 379 ☐ Full Rearward ☐ Mid Position ☐ Full Forward
☒		Graco ComfortSport ☒ Full Rearward ☒ Mid Position ☒ Full Forward
☐		Graco Platinum Cargo ☐ Full Rearward ☐ Mid Position ☐ Full Forward
☐		Graco Safeseat Step 2 ☐ Full Rearward ☐ Mid Position ☐ Full Forward
☒	13.	Suppression tests with newborn infant (Part 572, Subpart K) using the following indicated child restraints (mid-height seat position):
Section A – Car Bed (Belted)		
☒		Angel Guard Angel Ride ☒ Full Rearward ☒ Mid Position ☒ Full Forward

X	14.	Suppression tests with 3-year-old dummy (Part 572, Subpart P) using the following indicated child restraints where a child restraint is required (mid-height seat position):						
		Section C – Convertible (Belted forward-facing)						
X		Britax Roundabout E9L02	X	Full Rearward	X	Mid Position	X	Full Forward
X		Cosco High Back Booster 22-209	X	Full Rearward	X	Mid Position	X	Full Forward
		Cosco Summit Deluxe 22-262		Full Rearward		Mid Position		Full Forward
		Cosco Touriva 02519		Full Rearward		Mid Position		Full Forward
X		Evenflo Generations 352	X	Full Rearward	X	Mid Position	X	Full Forward
		Evenflo Medallion 254		Full Rearward		Mid Position		Full Forward
		Evenflo Tribute V 379		Full Rearward		Mid Position		Full Forward
X		Graco ComfortSport	X	Full Rearward	X	Mid Position	X	Full Forward
		Graco Platinum Cargo		Full Rearward		Mid Position		Full Forward
		Graco Safeseat Step 2		Full Rearward		Mid Position		Full Forward
		Section D – Toddler/Belt Positioning Booster (Belted)						
		Britax Roadster 9004		Full Rearward		Mid Position		Full Forward
		Cosco High Back Booster 22-209		Full Rearward		Mid Position		Full Forward
X		Cosco Summit Deluxe 22-262	X	Full Rearward	X	Mid Position	X	Full Forward
		Evenflo Right Fit 245		Full Rearward		Mid Position		Full Forward
		Evenflo Generations 352		Full Rearward		Mid Position		Full Forward
X		Graco Platinum Cargo	X	Full Rearward	X	Mid Position	X	Full Forward
	15.	Suppression tests with representative 3-year-old child using the following indicated child restraints where a child restraint is required (mid-height position). (Appendix H, Data Sheet 19H and 20H)						
		Section C – Convertible (Belted forward-facing)						
		Britax Roundabout E9L02		Full Rearward		Mid Position		Full Forward
		Cosco High Back Booster 22-209		Full Rearward		Mid Position		Full Forward
		Cosco Summit Deluxe 22-262		Full Rearward		Mid Position		Full Forward
		Cosco Touriva 02519		Full Rearward		Mid Position		Full Forward
		Evenflo Generations 352		Full Rearward		Mid Position		Full Forward
		Evenflo Medallion 254		Full Rearward		Mid Position		Full Forward
		Evenflo Tribute V 379		Full Rearward		Mid Position		Full Forward
		Graco ComfortSport		Full Rearward		Mid Position		Full Forward
		Graco Platinum Cargo		Full Rearward		Mid Position		Full Forward
		Graco Safeseat Step 2		Full Rearward		Mid Position		Full Forward
		Section D – Toddler/Belt Positioning Booster (Belted)						
		Britax Roadster 9004		Full Rearward		Mid Position		Full Forward
		Cosco High Back Booster 22-209		Full Rearward		Mid Position		Full Forward
		Cosco Summit Deluxe 22-262		Full Rearward		Mid Position		Full Forward
		Evenflo Generations 352		Full Rearward		Mid Position		Full Forward
		Evenflo Right Fit 245		Full Rearward		Mid Position		Full Forward
		Graco Platinum Cargo		Full Rearward		Mid Position		Full Forward

☒	16.	Suppression tests with 3-year-old dummy (Part 572, Subpart P) in the following positions (mid-height seat position):			
☒		Sitting on seat with back against seat back (S22.2.2.1)			
☒		☒ Full Rearward	☒ Mid Position	☒ Full Forward	
☒		Sitting on seat with back against reclined seat back (S22.2.2.2)			
☒		☒ Full Rearward	☒ Mid Position	☒ Full Forward	
☒		Sitting on seat with back not against seat back (S22.2.2.3)			
☒		☒ Full Rearward	☒ Mid Position	☒ Full Forward	
☒		Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)			
☒		☒ Full Rearward	☒ Mid Position	☒ Full Forward	
☒		Standing on seat, facing forward (S22.2.2.5)			
☒		☒ Full Rearward	☒ Mid Position	☒ Full Forward	
☒		Kneeling on seat facing forward (S22.2.2.6)			
☒		☒ Full Rearward	☒ Mid Position	☒ Full Forward	
☒		Kneeling on seat facing rearward (S22.2.2.7)			
☒		☒ Full Rearward	☒ Mid Position	☒ Full Forward	
☐		Lying on seat (S22.2.2.8)			
☐		☐ Full Rearward	☐ Mid Position	☐ Full Forward	
☐	17.	Suppression tests with representative 3-year-old child in the following positions (mid-height seat position):			
☐		Sitting on seat with back against seat back (S22.2.2.1)			
☐		☐ Full Rearward	☐ Mid Position	☐ Full Forward	
☐		Sitting on seat with back against reclined seat back (S22.2.2.2)			
☐		☐ Full Rearward	☐ Mid Position	☐ Full Forward	
☐		Sitting on seat with back not against seat back (S22.2.2.3)			
☐		☐ Full Rearward	☐ Mid Position	☐ Full Forward	
☐		Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)			
☐		☐ Full Rearward	☐ Mid Position	☐ Full Forward	
☐		Standing on seat, facing forward (S22.2.2.5)			
☐		☐ Full Rearward	☐ Mid Position	☐ Full Forward	
☐		Kneeling on seat facing forward (S22.2.2.6)			
☐		☐ Full Rearward	☐ Mid Position	☐ Full Forward	
☐		Kneeling on seat facing rearward (S22.2.2.7)			
☐		☐ Full Rearward	☐ Mid Position	☐ Full Forward	
☐		Lying on seat (S22.2.2.8)			
☐		☐ Full Rearward	☐ Mid Position	☐ Full Forward	
☐	18.	Suppression tests with 6-year-old dummy (Part 572, Subpart N) using the following indicated child restraints where a child restraint is required (mid-height seat position):			
		Section D			
☐		Britax Roadster 9004	☐ Full Rearward	☐ Mid Position	☐ Full Forward
☐		Cosco High Back Booster 22-209	☐ Full Rearward	☐ Mid Position	☐ Full Forward
☐		Cosco Summit Deluxe 22-262	☐ Full Rearward	☐ Mid Position	☐ Full Forward
☐		Evenflo Generations 352	☐ Full Rearward	☐ Mid Position	☐ Full Forward
☐		Evenflo Right Fit 245	☐ Full Rearward	☐ Mid Position	☐ Full Forward
☐		Graco Platinum Cargo	☐ Full Rearward	☐ Mid Position	☐ Full Forward

☒	19.	Suppression tests with representative 6-year-old child using the following indicated child restraints where a child restraint is required (mid-height seat position):
		Section D
☐		Britax Roadster 9004
☐		Cosco High Back Booster 22-209
☒		Cosco Summit Deluxe 22-262
☐		Evenflo Generations 352
☐		Evenflo Right Fit 245
☒		Graco Platinum Cargo
		Full Rearward
		Mid Position
		Full Forward
		Full Rearward
		Mid Position
		Full Forward
		Full Rearward
		Mid Position
		Full Forward
☐	20.	Suppression tests with 6-year-old dummy (Part 572, Subpart N) in the following positions (mid-height seat position):
☐		Sitting on seat with back against seat back (S22.2.2.1)
☐		Full Rearward
☐		Mid Position
☐		Full Forward
☐		Sitting on seat with back against reclined seat back (S22.2.2.2)
☐		Full Rearward
☐		Mid Position
☐		Full Forward
☐		Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
☐		Full Rearward
☐		Mid Position
☐		Full Forward
☐		Sitting back in the seat and leaning on the right front passenger door (S24.2.3)
☐		Full Rearward
☐		Mid Position
☐		Full Forward
☒	21.	Suppression tests with representative 6-year-old child in the following positions (mid-height seat position):
☒		Sitting on seat with back against seat back (S22.2.2.1)
☒		Full Rearward
☒		Mid Position
☒		Full Forward
☒		Sitting on seat with back against reclined seat back (S22.2.2.2)
☒		Full Rearward
☒		Mid Position
☒		Full Forward
☒		Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
☒		Full Rearward
☒		Mid Position
☒		Full Forward
☒		Sitting back in the seat and leaning on the right front passenger door (S24.2.3)
☒		Full Rearward
☒		Mid Position
☒		Full Forward
☐	22.	Test of Reactivation of the Passenger Air Bag System with an Unbelted 5 th percentile female dummy (S20.3, 22.3, S24.3) (mid-height seat position). Perform this test after the following suppression tests: <u>After each restraint.</u>
☒	23.	Test of Reactivation of the Passenger Air Bag System with a representative 5 th percentile female (S20.3, 22.3, S24.3) (mid-height seat position). Perform this test after the following suppression tests: <u>After each restraint.</u>
☐	24.	Low risk deployment test with 12-month-old dummy (Part 572, Subpart R) using the following indicated child restraints (full forward, mid-height seat position)(S20.4):
		Section B
☐		Century Smart Fit 4543
☐		Cosco Arriva 22-013
☐		Evenflo Discovery Adjust Right 212
☐		Graco Infant 8457
☐		Graco Snugride 8645
☐		Peg Perego Viaggio
		Section C
☐		Britax Roundabout E9L02
☐		Cosco Touriva 02519
☐		Evenflo Medallion 254
☐		Evenflo Tribute V 379
☐		Graco ComfortSport

☐	25.	Low risk deployment test with 3-year-old dummy (Part 572, Subpart P) in the following positions:
☐		Position 1 (rearmost, lowest seat position)
☐		Position 2 (mid-height seat position)
☐	26.	Low risk deployment test with 6-year-old dummy (Part 572, Subpart N) in the following positions:
☐		Position 1 (rearmost, lowest seat position)
☐		Position 2 (mid-height seat position)
☒	27.	Low risk deployment test with 5 th female dummy (Part 572, Subpart O) in the following positions:
☒		Position 1 (mid-height seat position)
☒		Position 2 (mid-height seat position)
☒	28.	Impact Tests
☐		Frontal Oblique Impact Angle: Test Speed:
☐		Belted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a))
☐		Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1))
☐		Unbelted 50 th male dummy driver and passenger (32 to 40 kmph) (S5.1.2(a)(2) or S5.1.2(b))
☒		Frontal 0° - Test Speed: 39.6 kmph
☐		Belted 50 th male dummy driver (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))
☐		Belted 50 th male dummy passenger (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))
☐		Belted 5 th female dummy driver (0 to 48 kmph) (S16.1(a)(1))
☐		Belted 5 th female dummy passenger (0 to 48 kmph) (S16.1(a)(1))
☐		Belted 5 th female dummy driver and passenger (0 to 56 kmph) (S16.1(a)(2))
☐		Belted 50 th male dummy driver and passenger (0 to 56 kmph) (S5.1.1.(b)(2))
☐		Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a) (1))
☐		Unbelted 50 th male dummy driver (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
☐		Unbelted 50 th male dummy passenger (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
☒		Unbelted 5 th female dummy driver (32 to 40 kmph) (S16.1(b))
☒		Unbelted 5 th female dummy passenger (32 to 40 kmph) (S16.1(b))
☐		40% Offset 0° Belted 5 th female dummy driver and passenger (0 to 40 kmph) (S18.1)
		Test Speed:
☐	29.	FMVSS 204 Indicant Test
☒	30.	FMVSS 212 Test
☒	31.	FMVSS 219 Indicant Test
☒	33.	FMVSS 301 Frontal Test
☐	34.	FMVSS 305 Frontal Indicant Test

DATA SHEET 2
REPORT OF VEHICLE CONDITION

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance

NHTSA No.: C20130100
Test Dates: 1/18/13 – 2/25/13

CONTRACT NO.: DTNH22-08-D-00086

Date: 3/4/13

FROM (Lab and rep name): MGA Research Corporation

TO: NHTSA, OVSC, NVS-220

PURPOSE: (X) Initial Receipt () Received via Transfer (X) Present vehicle condition

MODEL YEAR/MAKE/MODEL/BODY STYLE: 2013 Chevrolet Sonic 4 Door Sedan

MANUFACTURE DATE: 11/12

NHTSA NO. C20130100

GVWR: 1656 kg (3650 lbs)

BODY COLOR: Silver Ice Metallic

GAWR (Fr): 858 kg (1892 lbs)

VIN: 1G1JB5SH3D4147757

GAWR (Rr): 798 kg (1758 lbs)

ODOMETER READINGS: ARRIVAL (miles): 40

DATE: 12/14/12

COMPLETION (miles): 45

DATE: 2/25/13

PURCHASE PRICE: (\$) 14,795

DEALER'S NAME: Boucher Chevrolet, Inc. 1421 E. Moreland Blvd.

Waukesha, WI 53186-3960

- A. All options listed on window sticker are present on the test vehicle:
X Yes ___ No
- B. Tires and wheel rims are new and the same as listed: X Yes ___ No
- C. There are no dents or other interior or exterior flaws: X Yes ___ No
- D. The vehicle has been properly prepared and is in running condition:
X Yes ___ No
- E. Keyless remote is available and working: X Yes ___ No
- F. The glove box contains an owner's manual, warranty document, consumer information, and extra set of keys: X Yes ___ No
- G. Proper fuel filler cap is supplied on the test vehicle: X Yes ___ No
- H. Using permanent marker, identify vehicle with NHTSA number and FMVSS test type(s) on roof line above driver door or for school buses, place a placard with NHTSA number inside the windshield and to the exterior front and rear side of bus:
X Yes ___ No
- I. Place vehicle in storage area: X Yes ___ No
- J. Inspect the vehicle's interior and exterior, including all windows, seats, doors, etc. to confirm that each system is complete and functional per the manufacturer's specifications. Any damage, misadjustment, or other unusual condition that could influence the test program or test results shall be recorded. Report any abnormal condition to the NHTSA COTR before beginning any test:
X Vehicle OK ___ Conditions reported below in comment section

Identify the letter above to which any of the following comments apply.

Comments: _____

REPORT OF VEHICLE CONDITION AT THE COMPLETION OF TESTING

LIST OF FMVSS TESTS PERFORMED BY THIS LAB: FMVSS 208, 212, 219, 301

VEHICLE: 2013 Chevrolet Sonic

NHTSA NO.: C20130100

REMARKS:

Equipment that is no longer on the test vehicle as noted on previous page:

Right Hand Rear Tail Light, Spare Tire, Jack and Tools, Trunk Carpet

Explanation for equipment removal:

Components removed for instrumentation installation and to meet target weight.

Test Vehicle Condition:

25 mph frontal impact damage- front suspension & structure damaged, hood & front quarter panels damaged, radiator damaged, air bags & pretensioners deployed, stoddard in fuel tank

RECORDED BY: Jeff Lewandowski

DATE: 3/4/2013

APPROVED BY: David Winkelbauer

DATE: 3/4/2013

#####

RELEASE OF TEST VEHICLE

The vehicle described above is released from MGA to be delivered to:

Date:

Time:

Odometer:

Lab Rep's Signature:

Title:

Carrier/Customer Rep:

Date:

DATA SHEET 3

CERTIFICATION LABEL AND TIRE PLACARD INFORMATION

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Chad Seebecker

NHTSA No.: C20130100
Test Date: 2/25/13

Certification Label (Part 567)	
Manufacturer:	GENERAL MOTORS LLC
Date of Manufacture:	11/12
VIN:	1G1JB5SH3D4147757
Vehicle Certified As (Pass. Car/MPV/Truck/Bus):	Passenger Car
Front Axle GVWR:	858 kg (1892 lbs)
Rear Axle GVWR:	798 kg (1758 lbs)
Total GVWR:	1656 kg (3650 lbs)

Tire Placard for Motor Vehicles with GVWR of 10,000 lb or Less and Passenger Cars (571.110)	
Vehicle Capacity Weight:	406 kg (895 lbs)
Designated Seating Capacity Front:	2
Designated Seating Capacity Rear:	3
Total Designated Seating Capacity:	5
Recommended Cold Tire Inflation Pressure Front:	260 kpa (38 psi)
Recommended Cold Tire Inflation Pressure Rear:	260 kpa (38 psi)
Recommended Tire Size:	P195/65R15
Tire Size on Vehicle:	P195/65R15

Signature: 

Date: 2/25/13

DATA SHEET 4
REAR SEATING POSITION SEAT BELTS

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C20130100
Test Date: 1/18/13

	Yes	No
Do all rear seating positions have Type 2 seat belts?	X	

If NO, describe the seat belt installed, the seat location, and any other information about the seat that would explain why a Type 2 seat belt was not installed.

REMARKS:

Signature: Wayne Dahlke

Date: 1/18/13

DATA SHEET 5
AIR BAG LABELS (S4.5.1)

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C20130100
Test Date: 1/18/13

- ☒ 1. Air Bag Maintenance Label and Owner's Manual Instructions: (S4.5.1(a))
- ☒ 1.1 Does the manufacturer recommend periodic maintenance or replacement of the air bag?
- ☐ Yes (Go to 1.2)
- ☒ No (Go to 2)
- ☐ 1.2 Does the vehicle have a label specifying air bag maintenance or replacement?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.3 Does the label contain one of the following?
- ☐ Yes – Pass
- ☐ No – Fail
- Check applicable schedule:
- ☐ Schedule on label specifies month and year (Record date_____)
- ☐ Schedule on label specifies vehicle mileage (Record mileage_____)
- ☐ Schedule on label specifies interval measured from date on certification label (Record interval_____)
- ☐ 1.4 Is the label permanently affixed within the passenger compartment such that it cannot be removed without destroying or defacing the label or vehicle part? (3/19/01 legal interpretation to Todd Mitchell)
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.5 Is the label lettered in English?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.6 Is the label in block capitals and numerals?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.7 Are the letters and numerals at least 3/32 inches high?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.8 Does the owner's manual set forth the recommended schedule for maintenance or replacement?
- ☒ 2. Does the owner's manual: (S4.5.1(f))
- ☒ 2.1 Include a description of the vehicle's air bag system in an easily understandable format?
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 2.2 Include a statement that the vehicle is equipped with an air bag and a lap/shoulder belt at the front outboard seating position?
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 2.3 Include a statement that the air bag is a supplemental restraint at the front outboard seating position?
- ☒ Yes – Pass
- ☐ No – Fail

- ☒ 2.4 Emphasize that all occupants, including the driver, should always wear their seat belts whether or not an air bag is also provided at their seating positions to minimize the risk of severe injury or death in the event of a crash?
☒ Yes – Pass
☐ No – Fail
- ☒ 2.5 Provide any necessary precautions regarding the proper positioning of occupants, including children, at seating positions equipped with air bags to ensure maximum safety protection for those occupants?
☒ Yes – Pass
☐ No – Fail
- ☒ 2.6 Explain that no objects should be placed over or near the air bag on the steering wheel or on the instrument panel, because any such objects could cause harm if the vehicle is in a crash severe enough to cause the air bag to inflate?
☒ Yes – Pass
☐ No – Fail
- ☒ 2.7 Is the vehicle certified to meet the requirements of S14.5, S15, S17, S19, S21, S23, and S25? (Obtain answer to this question from the COTR) (S4.5.1(f)(2))
☒ Yes – (Go to 2.7.1)
☐ No – (Go to 3.)
- ☒ 2.7.1 Explain the proper functioning of the advanced air bag system? (S4.5.1(f)(2))
☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.2 Provide a summary of the actions that may affect the proper functioning of the system? (S4.5.1(f)(2))
☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.3 Present and explain the main components of the advanced passenger air bag system? (S4.5.1(f)(2)(i))
☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.4 Explain how the components function together as part of the advanced passenger air bag system? (S4.5.1(f)(2)(ii))
☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.5 Contain the basic requirements for proper operation, including an explanation of the actions that may affect the proper functioning of the system? (S4.5.1(f)(2)(iii))
☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.6 Is the vehicle certified to the requirements of S19.2, S21.2, or 23.2 (automatic suppression)?
☒ Yes, continue with 2.7.6
☐ No, go to 2.7.7
- ☒ 2.7.6.1 Contain a complete description of the passenger air bag suppression system installed in the vehicle, including a discussion of any suppression zone? (S4.5.1(f)(2)(iv))
☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.6.2 Discuss the telltale light, specifying its location in the vehicle and explaining when the light is illuminated?
☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.7 Explain the interaction of the advanced passenger air bag system with other vehicle components, such as seat belts, seats or other components? (S4.5.1(f)(2)(v))
☒ Yes – Pass
☐ No – Fail

- ☒ 2.7.8 Summarize the expected outcomes when child restraint systems, children and small teenagers or adults are both properly and improperly positioned in the passenger seat, including cautionary advice against improper placement of child restraint systems? (S4.5.1(f)(2)(vi))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.9 Provide information on how to contact the vehicle manufacturer concerning modifications for persons with disabilities that may affect the advanced air bag system? (S4.5.1(f)(2)(vii))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 3. Sun Visor Air Bag Warning Label (S4.5.1(b)): Vehicles certified to meet the requirements of S19, S21 and S23. (S4.5.1(b)(3))
- ☒ 3.1 Is the label permanently affixed (including permanent marking on the visor material or molding into the visor material) to either side of the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(b)(3)) (3/19/01 legal interpretation to Todd Mitchell)
- ☒ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☒ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail
- ☒ 3.2 Does the label conform in content to the label shown in Figure 11 at each front outboard seating position? (S4.5.1(b)(2)) **(Vehicles without back seats or the back seat is too small to accommodate a rear-facing child restraint may omit the statement: “Never put a rear-facing child seat in the front.” (S4.5.1(b)(3)(v)))**



Figure 11. Sun Visor Label Visible when Visor is in Down Position.



Figure 6b. Sun Visor Label Visible When Visor is in Down Position.

- ☒ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☒ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail

☒	3.3	Is the label heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(b)(3)(i))
	☒	Driver Side, Yes – Pass
	☐	Driver Side, No – Fail
	☒	Passenger Side, Yes – Pass
	☐	Passenger Side, No – Fail
☒	3.4	Is the message area white with black text? (S4.5.1(b)(3)(ii))
	☒	Driver Side, Yes – Pass
	☐	Driver Side, No – Fail
	☒	Passenger Side, Yes – Pass
	☐	Passenger Side, No – Fail
☒	3.5	Is the message area at least 30 cm ² ? (S4.5.1(b)(3)(ii))
		The message area consists of the total label area minus the yellow heading area and the pictogram. The pictogram is enclosed on the left side and bottom by the edge of the label. The top edge of the pictogram area is defined by a horizontal line midway between the uppermost edge of the pictogram and the lowermost edge of the text. The right side of the pictogram is defined by a vertical line midway between the rightmost edge of the pictogram and the left most edge of the text, including any bullets. (See 5/6/03 interpretation to Gerald Plante on behalf of Subaru)
		Driver Side: Length <u>86</u> mm, Width <u>39</u> mm
		Passenger Side: Length <u>86</u> mm, Width <u>39</u> mm
		Driver actual message area <u>33.5</u> cm ²
		Passenger actual message area <u>33.5</u> cm ²
	☒	Driver Side, Yes – Pass
	☐	Driver Side, No – Fail
	☒	Passenger Side, Yes – Pass
	☐	Passenger Side, No – Fail
☒	3.6	Is the pictogram black on a white background? (S4.5.1(b)(3)(iii))
	☒	Driver Side, Yes – Pass
	☐	Driver Side, No – Fail
	☒	Passenger Side, Yes – Pass
	☐	Passenger Side, No – Fail
☒	3.7	Is the pictogram at least 30 mm in length? (S4.5.1(b)(3)(iii))
		Driver side: Length: <u>32</u> mm
		Passenger side: Length: <u>32</u> mm
	☒	Driver Side, Yes – Pass
	☐	Driver Side, No – Fail
	☒	Passenger Side, Yes – Pass
	☐	Passenger Side, No – Fail
☒	3.8	Is the same side of the sun visor that contains the air bag warning label free of other information with the exception of the air bag maintenance label and/or the rollover-warning label? (S4.5.1(b)(5)(i))
	☒	Driver Side, Yes – Pass
	☐	Driver Side, No – Fail
	☒	Passenger Side, Yes – Pass
	☐	Passenger Side, No – Fail
☒	3.9	Is the sun visor free of other information about air bags or the need to wear seat belts with the exception of the air bag alert label and/or the rollover-warning label? (S4.5.1(b)(5)(ii))
	☒	Driver Side, Yes – Pass
	☐	Driver Side, No – Fail
	☒	Passenger Side, Yes – Pass
	☐	Passenger Side, No – Fail

- ☒ 3.10 Does the driver side visor contain a rollover-warning label on the same side of the visor as the air bag warning label?
 ___ Yes (go to 3.10.1)
☒ No (go to 4., skipping 3.10.1 through 3.10.3)
- ☐ 3.10.1 Are both the rollover-warning label and the air bag warning label surrounded by a continuous solid-lined border?
 ___ Yes (go to 3.10.2 and skip 3.10.3)
 ___ No (go to 3.10.3 and skip 3.10.2)
- ☐ 3.10.2 Is the shortest distance from the border of the rollover label to the border of the air bag warning label at least 1 cm? (575.105 (d)(1)(iv)(B))
 _____ actual distance
 ___ Yes-Pass ___ **No-FAIL**
- ☐ 3.10.3 Is the shortest distance from any of the lettering or graphics on the rollover-warning label to any of the lettering or graphics of the air bag warning label at least 3 cm? (575.105 (d)(1)(iv)(A))
 _____ actual distance
 ___ Yes-Pass ___ **No-FAIL**
- ☒ 4. Air Bag Alert Label (S4.5.1(c) (A "Rollover Warning Label" or "Rollover Alert Label" may be on the same side of the driver's sun visor as the "Air Bag Alert Label." 575.105(d))
- ☒ 4.1 Is the Sun Visor Warning Label visible when the sun visor is in the stowed position?
☒ **If yes for driver and passenger, go to 5.**
☒ Driver Side, Yes
☐ Driver Side, No
☒ Passenger Side, Yes
☐ Passenger Side, No
- ☐ 4.2 Is the air bag alert label permanently affixed (including permanent marking on the visor material or molding into the visor material) to the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(c)) (3/19/01 legal interpretation to Todd Mitchell)
☐ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☐ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail
- ☐ 4.3 Is the air bag alert label visible when the visor is in the stowed position? (S4.5.1(c))
☐ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☐ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail

4.4 Does the label conform in content to the label shown in Figure 6C? (S4.5.1(c))




Figure 6c. Sun Visor Label Visible When Visor is in Up Position.

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

4.5 Is the message area black with yellow text? (S4.5.1(c)(1))

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

4.6 Is the message area at least 20 cm²? (S4.5.1(c)(1)) **The message area consists of the black part of the label.**

Driver Side: Length __mm, Width __mm

Passenger Side: Length __mm, Width __mm

Driver actual message area __cm²

Passenger actual message area __cm²

- ☐ Driver Side, Yes – Pass
 - ☐ Driver Side, No – Fail
 - ☐ Passenger Side, Yes – Pass
 - ☐ Passenger Side, No – Fail
- 4.7 Is the pictogram black with a red circle and slash on a white background? (S4.5.1(c)(2))

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

4.8 Is the pictogram at least 20 mm in diameter? (S4.5.1(c)(2))

Driver Side: Diameter __mm

Passenger Side: Diameter __mm

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

5. Label on the Dashboard: Vehicles certified to meet the requirements of S19, S21 and S23?

5.1 Does the vehicle have a label on the dash or steering wheel hub? (S4.5.1(e)(3))

- ☒ Yes – Pass
- ☐ No – Fail

5.2 Is the label clearly visible from all front seating positions? (S4.5.1(e)(3))

- ☒ Yes – Pass
- ☐ No – Fail

X

- 5.3 Does the label conform in content to the label shown in Figure 12? (S4.5.1(e)(3)) **Vehicles without back seats may omit the statement: "The back seat is the safest place for children." Vehicles without back seats or too small to accommodate a rear-facing child restraint consistent with S4.5.4.1 as determined in DATA SHEET 7 may omit the statement "Never put a rear-facing child seat in the front." (S4.5.1(e)(3)(iii))**

X
No - Fail

Yes - Pass
No - Fail




Figure 12. Removable Label on Dash.

X

- 5.4 Is the heading area yellow with black text? (S4.5.1(e)(3)(i))

X
No - Fail

Yes - Pass
No - Fail

X

- 5.5 Is the message white with black text? (S4.5.1(e)(3)(ii))

X
No - Fail

Yes - Pass
No - Fail

X

- 5.6 Is the message area at least 30 cm²? (S4.5.1(e)(3)(ii)) **The message area consists of the total label area minus the yellow heading area. (See 5/6/03 interpretation to Gerald Plante on behalf of Subaru)**

Length 105 mm, Width 50 mm

Actual message area 52.5 cm²

X
No - Fail

Yes - Pass
No - Fail

I certify that I have read and performed each instruction.

Signature: Wayne Zahle

Date: 1/18/13

DATA SHEET 6
FMVSS 208 READINESS INDICATOR (S4.5.2)

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C20130100
Test Date: 1/18/13

An occupant restraint system that deploys in the event of a crash shall have a monitoring system with a readiness indicator. A totally mechanical system is exempt from this requirement. (11/8/94 legal interpretation to Lawrence F. Hennegerger on behalf of Breed)

- ☒ 1. Is the system totally mechanical? **(If Yes, this Data Sheet is complete).**
☐ Yes
☒ No
- ☒ 2. Describe the location of the readiness indicator: *Lower right area of instrument cluster*
- ☒ 3. Is the readiness indicator clearly visible to the driver?
☒ Yes – Pass
☐ No - Fail
- ☒ 4. Is a list of the elements in the occupant restraint system, being monitored by the readiness indicator, provided on a label or in the owner's manual?
☒ Yes – Pass
☐ No - Fail
- ☒ 5. Does the vehicle have an on-off switch for the passenger air bag?
☐ If Yes (go to 6)
☒ If No (this form is complete)
- ☐ 6. Is the air bag readiness indicator off when the passenger air bag switch is in the off position?
☐ Yes – Pass
☐ No - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Dahlke

Date: 1/18/13

DATA SHEET 7

PASSENGER AIR BAG MANUAL CUT-OFF DEVICE (S4.5.4)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

- ☒ 1. Is the vehicle equipped with an on-off switch that deactivates the air bag installed at the right front outboard seating position?
☐ Yes, go to 2
☒ No, this sheet is complete
- ☐ 2. Does the vehicle have any forward-facing rear designated seating positions? (S4.5.4.1(a))
☐ Yes, go to 3
☐ No, go to 4
- ☐ 3. Verification there is room for a child restraint in the rear seat behind the driver's seat. (S4.5.4.1(b))
- ☐ 3.1 Using all the controls that affect the fore-aft movement of the seat, move the seat to the rearmost position. Mark this position.
☐ N/A – the seat does not have fore-aft adjustment
- ☐ 3.2 Using all the controls that affect the fore-aft movement of the seat, move the seat to the foremost position. Mark this position.
☐ N/A – the seat does not have fore-aft adjustment
- ☐ 3.3 Move the seat to the middle of the foremost and rearmost positions. (S8.1.2)
☐ N/A – the seat does not have a fore-aft adjustment
- ☐ 3.4 If the driver's seat height is adjustable, use all the controls that affect height to put it in the lowest position while maintaining the middle fore-aft position. (S8.1.2)
☐ N/A – No seat height adjustment
- ☐ 3.5 Position the driver's seat adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)
☐ N/A – No lumbar adjustment
- ☐ 3.6 The driver's seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1(b) and S8.1.3)
☐ N/A – No seat back angle adjustment
☐ Manufacturer's design driver's seat back angle _____
☐ Tested driver's seat back angle _____
- ☐ 3.7 Is the driver seat a bucket seat?
☐ Yes, go to 3.7.1 and skip 3.7.2.
☐ No, go to 3.7.2 and skip 3.7.1.
- ☐ 3.7.1 Bucket seats:
- ☐ 3.7.1.1 Locate and mark a vertical Plane B through the longitudinal centerline of the driver's seat cushion. The longitudinal centerline of a bucket seat cushion is determined at SgRP. (S16.3.1.10) (S4.5.4.1(b)(1))
- ☐ 3.7.1.2 Locate the longitudinal horizontal line in plane B that is tangent to the highest point of the rear seat cushion behind the driver's seat. Measure along this line from the front of the seat back of the rear seat to the rear of the seat back of the driver's seat.
 _____ mm distance ___less than 720 mm – Pass ___more than 720 mm – **FAIL**
 Go to 4
- ☐ 3.7.2 Bench seats (including split bench seats):
- ☐ 3.7.2.1 Locate and mark a vertical Plane B through the center of the steering wheel parallel to the vehicle longitudinal centerline. (S4.5.4.1(b)(2))

- ☐ 3.7.2.2 Locate the longitudinal horizontal line in plane B that is tangent to the highest point of the rear seat cushion. Measure along this line from the front of the seat back of the rear seat to the rear of the seat back of the front seat.
 ____ mm distance ____ less than 720 mm – Pass ____ more than 720 mm - **FAIL**
 Go to 4
- ☐ 4. Does the device turn the air bag on and off using the vehicle's ignition key? (S4.5.4.2)
☐ Yes – Pass
☐ No – Fail
- ☐ 5. Is the on-off device separate from the ignition switch? (S4.5.4.2)
☐ Yes – Pass
☐ No – Fail
- ☐ 6. Is there a telltale light that comes on when the passenger air bag is turned off? (S4.5.4.2)
☐ Yes – Pass
☐ No – Fail
- ☐ 7. Telltale light (S4.5.4.3)
- ☐ 7.1 Is the light yellow? (S4.5.4.3(a))
☐ Yes – Pass
☐ No – Fail
- ☐ 7.2 Are the words "PASSENGER AIR BAG OFF" or "PASS AIR BAG OFF" (S4.5.4.3(b))
☐ 7.2.1 on the telltale?
☐ Yes – Pass, go to 7.3
☐ No – go to 7.2.2
- ☐ 7.2.2 within 25 mm of the telltale?
☐ Measurement from the edge of the telltale light (mm):
☐ Yes – Pass
☐ No – Fail
- ☐ 7.3 Does the telltale remain illuminated while the air bag is turned off? (S4.5.4.3(c)) (Leave the air bag off for 5 minutes.)
☐ Yes – Pass
☐ No – Fail
- ☐ 7.4 Is the telltale illuminated while the air bag is turned on? (S4.5.4.3(d))
☐ Yes – Fail
☐ No – Pass
- ☐ 7.5 Is the telltale combined with the air bag readiness indicator? (S4.5.4.3(e))
☐ Yes – Fail
☐ No – Pass
- ☐ 8. Owner's Manual
- ☐ 8.1 Does the owner's manual contain complete instructions on the operation of the on-off switch? (S4.5.4.4(a))
☐ Yes – Pass
☐ No – Fail

☐ 8.2 Does the owner's manual contain a statement that the on-off switch should only be used when a member of one of the following risk groups is occupying the right front passenger seating position? (S4.5.4.4(b))

Infants:	there is no back seat the rear seat is too small to accommodate a child restraint there is a medical condition that must be monitored constantly
Children aged 1 to 12:	there is no back seat space is not always available in the rear seat there is a medical condition that must be monitored constantly
Medical condition:	medical risk causes special risk for passenger greater risk for harm than with the air bag on

☐ Yes – Pass

☐ No – Fail

☐ 8.3 Does the owner's manual contain a warning about the safety consequences of using the on-off switch at other times?

☐ Yes – Pass

☐ No – Fail

REMARKS:

Signature: Wayne Zuhl

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C20130100
Test Date: 1/18/13

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5 (a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Front Passenger
------------------------------	------------------------

- | | | |
|-------------------------------------|-----|---|
| ☐ | | N/A – No retractor is at this position |
| ☐ | | N/A – The retractor is an automatic locking retractor ONLY |
| ☒ | 1. | Record test fore-aft seat position: REAR
(S7.1.1.5(c)(1)) (Any position is acceptable) |
| ☒ | 2. | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5(a)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 3. | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5(a)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 4. | Place any adjustable seat belt anchorage in the lowest adjustment position. |
| | | ☐ N/A The anchorage is not adjustable. |
| ☒ | 5. | Buckle the seat belt. (S7.1.1.5(c)(1)) |
| ☒ | 6. | Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2)) |
| ☒ | 7. | Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2)) |
| ☒ | 8. | Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing? |
| | | ☒ Yes (go to 8.1) |
| | | ☐ No (go to 9) |
| ☒ | 8.1 | Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system? (S7.1.1.5(b)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 9. | Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1)) |

- ☒ 10. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
Measured distance between A and B (inches): 69 1/4
- ☒ 11. Readjust the belt system so that the webbing between points A and B is at 1/2 the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 12. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle: 10° (spec. 5 - 15 degrees)
- ☒ 13. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B: 44 3/4 inches
- ☒ 14. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate: 15 lb/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
Measured distance between A and B: 45 inches (S7.1.1.5(c)(6))
- ☒ 15. Let the seat belt webbing retract to its minimum length with the seat belt still buckled.
- ☒ 16. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle: 10° (spec. 5 - 15 degrees)
- ☒ 17. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B: 20 3/4 inches
- ☒ 18. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate: 15 lb/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
Measured distance between A and B: 21 1/4 inches (S7.1.1.5(c)(6))
- ☒ 19. Subtract the measurement in 13 from the measurement in 14 and the measurement in 17 from the measurement in 18. Is the difference 2 inches or less for both? (S7.1.1.5(c)(7))
14 - 13 = 45 - 44 3/4 = 1/4 inch;
18 - 17 = 21 1/4 - 20 3/4 = 1/2 inch
- ☒ Yes - Pass
☐ No - Fail

- ☒ 20. Subtract the measurement in 14 from the measurement in 10 and the measurement in 18 from the measurement in 10. Is the difference 3 inches or more for both?
(S7.1.1.5(c)(8))
- ☒ 10-14 = $69 \frac{1}{4} - 45 = 24 \frac{1}{4}$ inches;
☒ 10-18 = $69 \frac{1}{4} - 21 \frac{1}{4} = 48$ inches
- ☒ Yes – Pass
☐ No – Fail

REMARKS:

Signature: Wayne Zuhl

Date: 1/18/13

I certify that I have read and performed each instruction.




Figure 5. - Webbing Tension Pull Device

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C20130100
Test Date: 1/18/13

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5 (a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

- | | | |
|-------------------------------------|-----|---|
| ☐ | | N/A – No retractor is at this position |
| ☐ | | N/A – The retractor is an automatic locking retractor ONLY |
| ☒ | 1. | Record test fore-aft seat position: FIXED
(S7.1.1.5(c)(1)) (Any position is acceptable) |
| ☒ | 2. | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle.
(S7.1.1.5(a)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 3. | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5(a)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 4. | Place any adjustable seat belt anchorage in the lowest adjustment position. |
| | | ☒ N/A The anchorage is not adjustable. |
| ☒ | 5. | Buckle the seat belt. (S7.1.1.5(c)(1)) |
| ☒ | 6. | Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2)) |
| ☒ | 7. | Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2)) |
| ☒ | 8. | Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing? |
| | | ☒ Yes (go to 8.1) |
| | | ☐ No (go to 9) |
| ☒ | 8.1 | Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system? (S7.1.1.5(b)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 9. | Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1)) |

- ☒ 10. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
Measured distance between A and B (inches): 76 1/4
- ☒ 11. Readjust the belt system so that the webbing between points A and B is at 1/2 the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 12. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle: 10° (spec. 5 - 15 degrees)
- ☒ 13. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B: 43 inches
- ☒ 14. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate: 15 lb/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
Measured distance between A and B: 43 inches (S7.1.1.5(c)(6))
- ☒ 15. Let the seat belt webbing retract to its minimum length with the seat belt still buckled.
- ☒ 16. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle: 10° (spec. 5 - 15 degrees)
- ☒ 17. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B: 13 inches
- ☒ 18. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate: 15 lb/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
Measured distance between A and B: 14 inches (S7.1.1.5(c)(6))
- ☒ 19. Subtract the measurement in 13 from the measurement in 14 and the measurement in 17 from the measurement in 18. Is the difference 2 inches or less for both? (S7.1.1.5(c)(7))
14 - 13 = 43 - 43 = 0 inch;
18 - 17 = 14 - 13 = 1 inch
- ☒ Yes - Pass
☐ No - Fail

- ☒ 20. Subtract the measurement in 14 from the measurement in 10 and the measurement in 18 from the measurement in 10. Is the difference 3 inches or more for both?
(S7.1.1.5(c)(8))
- ☒ $10-14 = 76 \frac{1}{4} - 43 = 33 \frac{1}{4}$ inches;
- ☒ $10-18 = 76 \frac{1}{4} - 14 = 62 \frac{1}{4}$ inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS:

Signature: Wayne Zuhl

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C20130100
Test Date: 1/18/13

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5 (a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

- | | | |
|-------------------------------------|-----|---|
| ☐ | | N/A – No retractor is at this position |
| ☐ | | N/A – The retractor is an automatic locking retractor ONLY |
| ☒ | 1. | Record test fore-aft seat position: FIXED
(S7.1.1.5(c)(1)) (Any position is acceptable) |
| ☒ | 2. | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle.
(S7.1.1.5(a)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 3. | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5(a)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 4. | Place any adjustable seat belt anchorage in the lowest adjustment position. |
| | | ☒ N/A The anchorage is not adjustable. |
| ☒ | 5. | Buckle the seat belt. (S7.1.1.5(c)(1)) |
| ☒ | 6. | Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2)) |
| ☒ | 7. | Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2)) |
| ☒ | 8. | Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing? |
| | | ☒ Yes (go to 8.1) |
| | | ☐ No (go to 9) |
| ☒ | 8.1 | Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system? (S7.1.1.5(b)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 9. | Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1)) |

- ☒ 10. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
- ☒ Measured distance between A and B (inches): 77 1/4
- ☒ 11. Readjust the belt system so that the webbing between points A and B is at 1/2 the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 12. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- ☒ Measured force application angle: 10° (spec. 5 - 15 degrees)
- ☒ 13. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- ☒ Measured distance between A and B: 40 inches
- ☒ 14. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- Record onset rate: 15 lb/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
- Measured distance between A and B: 41 1/2 inches (S7.1.1.5(c)(6))
- ☒ 15. Let the seat belt webbing retract to its minimum length with the seat belt still buckled.
- ☒ 16. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- Measured force application angle: 10° (spec. 5 - 15 degrees)
- ☒ 17. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- Measured distance between A and B: 11 3/4 inches
- ☒ 18. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- Record onset rate: 15 lb/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
- Measured distance between A and B: 12 1/4 inches (S7.1.1.5(c)(6))
- ☒ 19. Subtract the measurement in 13 from the measurement in 14 and the measurement in 17 from the measurement in 18. Is the difference 2 inches or less for both? (S7.1.1.5(c)(7))
- ☒ $14 - 13 = 41 \frac{1}{2} - 40 = 1 \frac{1}{2}$ inches;
- ☒ $18 - 17 = 12 \frac{1}{4} - 11 \frac{3}{4} = \frac{1}{2}$ inch
- ☒ Yes – Pass
- ☐ No – Fail

- ☒ 20. Subtract the measurement in 14 from the measurement in 10 and the measurement in 18 from the measurement in 10. Is the difference 3 inches or more for both?
(S7.1.1.5(c)(8))
- ☒ $10-14 = 77 \frac{1}{4} - 41 \frac{1}{2} = 35 \frac{3}{4}$ inches;
- ☒ $10-18 = 77 \frac{1}{4} - 12 \frac{1}{4} = 65$ inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS:

Signature: Wayne Zuhl Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C20130100
Test Date: 1/18/13

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5 (a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	-----------------------------

- | | | |
|-------------------------------------|-----|---|
| ☐ | | N/A – No retractor is at this position |
| ☐ | | N/A – The retractor is an automatic locking retractor ONLY |
| ☒ | 1. | Record test fore-aft seat position: FIXED
(S7.1.1.5(c)(1)) (Any position is acceptable) |
| ☒ | 2. | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5(a)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 3. | Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5(a)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 4. | Place any adjustable seat belt anchorage in the lowest adjustment position. |
| | | ☒ N/A The anchorage is not adjustable. |
| ☒ | 5. | Buckle the seat belt. (S7.1.1.5(c)(1)) |
| ☒ | 6. | Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2)) |
| ☒ | 7. | Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2)) |
| ☒ | 8. | Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing? |
| | | ☒ Yes (go to 8.1) |
| | | ☐ No (go to 9) |
| ☒ | 8.1 | Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system? (S7.1.1.5(b)) |
| | | ☒ Yes – Pass |
| | | ☐ No – Fail |
| ☒ | 9. | Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1)) |

- ☒ 10. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
Measured distance between A and B (inches): 74 ½
- ☒ 11. Readjust the belt system so that the webbing between points A and B is at ½ the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 12. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle: 10° (spec. 5 - 15 degrees)
- ☒ 13. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B: 43 ¼ inches
- ☒ 14. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate: 15 lb/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
Measured distance between A and B: 43 ¾ inches (S7.1.1.5(c)(6))
- ☒ 15. Let the seat belt webbing retract to its minimum length with the seat belt still buckled.
- ☒ 16. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle: 10° (spec. 5 - 15 degrees)
- ☒ 17. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B: 13 ½ inches
- ☒ 18. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate: 15 lb/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
Measured distance between A and B: 15 inches (S7.1.1.5(c)(6))
- ☒ 19. Subtract the measurement in 13 from the measurement in 14 and the measurement in 17 from the measurement in 18. Is the difference 2 inches or less for both? (S7.1.1.5(c)(7))
14 – 13 = 43 ¾ - 43 ¼ = ½ inch;
18 – 17 = 15 - 13 ½ = 1 ½ inch
- ☒ Yes – Pass
☐ No – Fail

- ☒ 20. Subtract the measurement in 14 from the measurement in 10 and the measurement in 18 from the measurement in 10. Is the difference 3 inches or more for both?
(S7.1.1.5(c)(8))
- ☒ $10-14 = 74 \frac{1}{2} - 43 \frac{3}{4} = 30 \frac{3}{4}$ inches;
- ☒ $10-18 = 74 \frac{1}{2} - 15 = 59 \frac{1}{2}$ inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS:

Signature: Wayne Zuhl

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 9

FMVSS 208 SEAT BELT WARNING SYSTEM CHECK (S7.3)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

- ☒ 1. The occupant is in the driver's seat.
- ☒ 2. The seat belt is in the stowed position.
- ☒ 3. The key is in the "on" or "start" position.
- ☒ 4. The time duration of the audible signal beginning with key "on" or "start" is 6 seconds.
- ☒ 5. The occupant is in the driver's seat.
- ☒ 6. The seat belt is in the stowed position.
- ☒ 7. The key is in the "on" or "start" position.
- ☒ 8. The time duration of the warning light beginning with key "on" or "start" is Stays On seconds.
- ☒ 9. The occupant is in the driver's seat.
- ☒ 10. The seat belt is in the latched position and with at least 4 inches of belt webbing extended.
- ☒ 11. The key is in the "on" or "start" position.
- ☒ 12. The time duration of the warning light beginning with key "on" or "start" is 0 seconds.
- ☒ 13. Complete the following table with the data from 4, 8, and 12 to determine which option is used.

		Warning light	Warning light specification	Audible signal	Audible signal specification*
S7.3 (a)(1)	Belt stowed & key on or start	Item 8: <u>Stays On</u>	60 seconds minimum	Item 4: <u>6</u>	4 to 8 seconds
S7.3 (a)(2)	Belt latched & key on or start	Item 12: <u>0</u>	4 to 8 seconds		
	Belt stowed & key on or start	Item 8: <u>Stays On</u>	4 to 8 seconds	Item 4: <u>6</u>	4 to 8 seconds

* 49 USCS @ 30124 does NOT allow an audible signal to operate for more than 8 seconds.

A voluntary audible signal after the 4 to 8 second required signal may be provided. It must be differentiated from the required signal (5/25/2001 legal interpretation to Longacre and Associates).

- ☒ 14. The seat belt warning system meets the requirements of (manufacturers may comply with either section).
 - ☒ S7.3 (a)(1)
 - ☐ S7.3 (a)(2)
 - ☐ FAIL – Does NOT meet the requirements of either option.
- ☒ 15. Note wording of visual warning: (S7.3(a)(1) and S7.3(a)(2))
 - ☐ Fasten Seat Belts
 - ☐ Fasten Belts
 - ☒ Symbol 101 - 
 - ☐ FAIL – Does not use any of the above wording or symbol.

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Dahlke

Date: 1/18/13

DATA SHEET 10
BELT CONTACT FORCE (S7.4.3)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

- | | | |
|-------------------------------------|-----|---|
| ☒ | 1. | Does the vehicle incorporate a webbing tension-relieving device? |
| | | ☐ Yes (this form is complete) |
| | | ☒ No (continue with this check sheet) |
| ☒ | 2. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3) |
| | | ☒ N/A – No lumbar adjustment |
| ☒ | 3. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2) |
| | | ☒ N/A – No additional support adjustment |
| ☒ | 4. | Is the fore-aft position of the seat adjustable? |
| | | ☒ No – go to 5 |
| | | ☐ Yes – go to 4.1 |
| ☐ | 4.1 | Use all the seat controls that have any affect on the fore-aft movement of the seat to move the seat cushion to the rearmost position. Mark this position. (8/31/95 legal interpretation to Hogan and Hartson) |
| ☐ | 4.2 | Use all the seat controls that have any affects on the fore-aft movement of the seat to move the seat cushion to the foremost position. Mark this position. (8/31/95 legal interpretation to Hogan and Hartson) |
| ☐ | 4.3 | Mark each fore-aft position so that there is a visual indication when the seat is at a particular position. For manual seats, mark each detent. For power seats, mark only the rearmost, middle and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost. Determine the mid fore-aft seat position based on the foremost and rearmost positions determined in items 4.1 and 4.2. (8/31/95 legal interpretation to Hogan and Hartson) |
| ☐ | 4.4 | Move the seat to the mid position. |
| ☐ | 4.5 | While maintaining the mid position, move the seat to its lowest position. For seats with adjustable seat cushions, use the manufacturer's recommended seat cushion angle for determining the lowest height position. |
| ☒ | 5. | Is the seat back angle adjustable? |
| | | ☒ No- go to 6 |
| | | ☐ Yes- go to 5.1 |
| ☐ | 5.1 | Set and mark seat back angle, if adjustable, at the manufacturer's nominal design riding position for a 50 th percentile adult male in the manner specified by the manufacturer. |
| | | ☐ N/A – No seat back angle adjustment |
| | | ☐ Manufacturer's design seat back angle: _____ |
| | | ☐ Tested seat back angle: _____ |

☒	6.	Is the seat a bucket seat?
		☐ Yes, go to 6.1 and skip 6.2
		☒ No, go to 6.2 and skip 6.1
☐	6.1	Bucket seats: Locate and mark the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S10.4.1.2 and S16.3.1.10)
☒	6.2	Bench seats (complete ONLY the one that is applicable to the seat being tested):
☐	6.2.1	Driver Seat Locate and mark the longitudinal line on the seat cushion that marks the intersection of the vertical longitudinal plane through the centerline of the steering wheel and the seat cushion upper surface. (S10.4.1.1)
☐	6.2.2	Front Outboard Passenger Seat Locate and mark the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S10.4.1.1)
		☐ Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel. _____
		☐ Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. _____
☒	6.2.3	Rear designated seating positions Locate and mark the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline.
☒	7.	Position the test dummies according to dummy position placement instructions in Appendix F. Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure.
☒	8.	Fasten the seat belt latch.
☒	9.	Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest.
☒	10.	Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing.
☒		Contact Force (lb): 0.3
		☒ 0.0 to 0.7 pounds – Pass
		☐ Greater than 0.7 pounds – FAIL

REMARKS:

Signature: Wayne J. Fahl

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 10
BELT CONTACT FORCE (S7.4.3)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

- | | | |
|-------------------------------------|-----|---|
| ☒ | 1. | Does the vehicle incorporate a webbing tension-relieving device? |
| | | ☐ Yes (this form is complete) |
| | | ☒ No (continue with this check sheet) |
| ☒ | 2. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3) |
| | | ☒ N/A – No lumbar adjustment |
| ☒ | 3. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2) |
| | | ☒ N/A – No additional support adjustment |
| ☒ | 4. | Is the fore-aft position of the seat adjustable? |
| | | ☒ No – go to 5 |
| | | ☐ Yes – go to 4.1 |
| ☐ | 4.1 | Use all the seat controls that have any affect on the fore-aft movement of the seat to move the seat cushion to the rearmost position. Mark this position. (8/31/95 legal interpretation to Hogan and Hartson) |
| ☐ | 4.2 | Use all the seat controls that have any affects on the fore-aft movement of the seat to move the seat cushion to the foremost position. Mark this position. (8/31/95 legal interpretation to Hogan and Hartson) |
| ☐ | 4.3 | Mark each fore-aft position so that there is a visual indication when the seat is at a particular position. For manual seats, mark each detent. For power seats, mark only the rearmost, middle and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost. Determine the mid fore-aft seat position based on the foremost and rearmost positions determined in items 4.1 and 4.2. (8/31/95 legal interpretation to Hogan and Hartson) |
| ☐ | 4.4 | Move the seat to the mid position. |
| ☐ | 4.5 | While maintaining the mid position, move the seat to its lowest position. For seats with adjustable seat cushions, use the manufacturer's recommended seat cushion angle for determining the lowest height position. |
| ☒ | 5. | Is the seat back angle adjustable? |
| | | ☒ No- go to 6 |
| | | ☐ Yes- go to 5.1 |
| ☐ | 5.1 | Set and mark seat back angle, if adjustable, at the manufacturer's nominal design riding position for a 50 th percentile adult male in the manner specified by the manufacturer. |
| | | ☐ N/A – No seat back angle adjustment |
| | | ☐ Manufacturer's design seat back angle: _____ |
| | | ☐ Tested seat back angle: _____ |

- ☒ 6. Is the seat a bucket seat?
☐ Yes, go to 6.1 and skip 6.2
☒ No, go to 6.2 and skip 6.1
- ☐ 6.1 Bucket seats:
 Locate and mark the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S10.4.1.2 and S16.3.1.10)
- ☒ 6.2 Bench seats (complete ONLY the one that is applicable to the seat being tested):
- ☐ 6.2.1 Driver Seat
 Locate and **mark** the longitudinal line on the seat cushion that marks the intersection of the vertical longitudinal plane through the centerline of the steering wheel and the seat cushion upper surface. (S10.4.1.1)
- ☐ 6.2.2 Front Outboard Passenger Seat
 Locate and **mark** the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S10.4.1.1)
☐ Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel. _____
☐ Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. _____
- ☒ 6.2.3 Rear designated seating positions
 Locate and **mark** the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline.
- ☒ 7. Position the test dummies according to dummy position placement instructions in Appendix F. **Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure.**
- ☒ 8. Fasten the seat belt latch.
- ☒ 9. Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest.
- ☒ 10. Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing.
- ☒ Contact Force (lb): **0.3**
☒ 0.0 to 0.7 pounds – Pass
☐ Greater than 0.7 pounds - FAIL

REMARKS:

Signature: Wayne Zuhl

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 10
BELT CONTACT FORCE (S7.4.3)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	----------------------

- | | | |
|---|-----|--|
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">X</div> | 1. | Does the vehicle incorporate a webbing tension-relieving device?
<div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px;"></div> <div>Yes (this form is complete)</div> </div> <div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px; text-align: center; line-height: 15px;">X</div> <div>No (continue with this check sheet)</div> </div> |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">X</div> | 2. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)
<div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px; text-align: center; line-height: 15px;">X</div> <div>N/A – No lumbar adjustment</div> </div> |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">X</div> | 3. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
<div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px; text-align: center; line-height: 15px;">X</div> <div>N/A – No additional support adjustment</div> </div> |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">X</div> | 4. | Is the fore-aft position of the seat adjustable?
<div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px; text-align: center; line-height: 15px;">X</div> <div>No – go to 5</div> </div> <div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px;"></div> <div>Yes – go to 4.1</div> </div> |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;"></div> | 4.1 | Use all the seat controls that have any affect on the fore-aft movement of the seat to move the seat cushion to the rearmost position. Mark this position. (8/31/95 legal interpretation to Hogan and Hartson) |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;"></div> | 4.2 | Use all the seat controls that have any affects on the fore-aft movement of the seat to move the seat cushion to the foremost position. Mark this position. (8/31/95 legal interpretation to Hogan and Hartson) |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;"></div> | 4.3 | Mark each fore-aft position so that there is a visual indication when the seat is at a particular position. For manual seats, mark each detent. For power seats, mark only the rearmost, middle and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost. Determine the mid fore-aft seat position based on the foremost and rearmost positions determined in items 4.1 and 4.2. (8/31/95 legal interpretation to Hogan and Hartson) |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;"></div> | 4.4 | Move the seat to the mid position. |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;"></div> | 4.5 | While maintaining the mid position, move the seat to its lowest position. For seats with adjustable seat cushions, use the manufacturer's recommended seat cushion angle for determining the lowest height position. |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;">X</div> | 5. | Is the seat back angle adjustable?
<div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px; text-align: center; line-height: 15px;">X</div> <div>No- go to 6</div> </div> <div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px;"></div> <div>Yes- go to 5.1</div> </div> |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; margin: 0 auto; text-align: center; line-height: 20px;"></div> | 5.1 | Set and mark seat back angle, if adjustable, at the manufacturer's nominal design riding position for a 50 th percentile adult male in the manner specified by the manufacturer.
<div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px;"></div> <div>N/A – No seat back angle adjustment</div> </div> <div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px;"></div> <div>Manufacturer's design seat back angle: _____</div> </div> <div style="display: flex; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: yellow; border: 1px solid black; margin-right: 5px;"></div> <div>Tested seat back angle: _____</div> </div> |

☒	6.	Is the seat a bucket seat?
		☐ Yes, go to 6.1 and skip 6.2
		☒ No, go to 6.2 and skip 6.1
☐	6.1	Bucket seats: Locate and mark the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S10.4.1.2 and S16.3.1.10)
☒	6.2	Bench seats (complete ONLY the one that is applicable to the seat being tested):
☐	6.2.1	Driver Seat Locate and mark the longitudinal line on the seat cushion that marks the intersection of the vertical longitudinal plane through the centerline of the steering wheel and the seat cushion upper surface. (S10.4.1.1)
☐	6.2.2	Front Outboard Passenger Seat Locate and mark the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S10.4.1.1)
		☐ Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel. _____
		☐ Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. _____
☒	6.2.3	Rear designated seating positions Locate and mark the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline.
☒	7.	Position the test dummies according to dummy position placement instructions in Appendix F. Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure.
☒	8.	Fasten the seat belt latch.
☒	9.	Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest.
☒	10.	Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing.
☒		Contact Force (lb): 0.3
		☒ 0.0 to 0.7 pounds – Pass
		☐ Greater than 0.7 pounds - FAIL

REMARKS:

Signature: Wayne Zuhl

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 11
LATCH PLATE ACCESS (S7.4.4)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

Test all front outboard seat belts **other than those in** walk-in van-type vehicles and those at front outboard designated seating positions in **passenger cars**. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Not Applicable For Any Position - Passenger Car
------------------------------	---

- ☐ 1. Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)
 - ☐ N/A – No lumbar adjustment
- ☐ 2. Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
 - ☐ N/A – No additional support adjustment
- ☐ 3. Is the fore-aft position of the seat adjustable?
 - ☐ No – go to 4
 - ☐ Yes – go to 3.1
- ☐ 3.1 Use all the seat controls that have any affect on the fore-aft movement of the seat to move the seat cushion to the rearmost position. **Mark** this position. (8/31/95 legal interpretation to Hogan and Hartson)
- ☐ 3.2 While maintaining the forward most position, move the seat to its lowest position. For seats with adjustable seat cushions, use the manufacturer's recommended seat cushion angle for determining the lowest height position.
- ☐ 4. Is the seat back angle adjustable?
 - ☐ No- go to 5
 - ☐ Yes- go to 4.1
- ☐ 4.1 Set and mark seat back angle, if adjustable, at the manufacturer's nominal design riding position for a **50th percentile adult male** in the manner specified by the manufacturer.
 - ☐ N/A – No seat back angle adjustment
 - ☐ Manufacturer's design seat back angle: _____
 - ☐ Tested seat back angle: _____
- ☐ 5. Is the seat a bucket seat?
 - ☐ Yes, go to 5.1 and skip 5.2
 - ☐ No, go to 5.2 and skip 5.1
- ☐ 5.1 Bucket seats:

Locate and **mark** the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S10.4.1.2 and S16.3.1.10)
- ☐ 5.2 Bench seats (complete ONLY the one that is applicable to the seat being tested):
 - ☐ 5.2.1 Driver Seat

Locate and **mark** the longitudinal line on the seat cushion that marks the intersection of the vertical longitudinal plane through the centerline of the steering wheel and the seat cushion upper surface. (S10.4.1.1)

- ☐ 5.2.2 Front Outboard Passenger Seat
- Locate and **mark** the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S10.4.1.1)
- ☐ Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel. _____
- ☐ Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. _____
- ☐ 6. Position the test dummy using the procedures in Appendix F. (Some modifications to the positioning procedure may need to be made because the seat is in the forward most position. Note on the Appendix F positioning check sheet any deviations necessary to position the Part 572, Subpart E dummy). **Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure.**
- ☐ 7. Position the adjustable seat belt anchorage in the manufacturer's nominal design position for a 50th percentile adult male occupant.
- ☐ 8. Attach the inboard reach string to the base of the head following the instructions on Figure 3.
- ☐ 9. Attach the outboard reach string to the torso sheath following the instructions on Figure 3.
- ☐ 10. Place the latch plate in the stowed position.
- ☐ 11. Extend the inboard reach string in front of the dummy and then backward and outboard to the latch plate to generate arcs of the reach envelope of the test dummy's arms. Is the latch plate within the reach envelope?
- ☐ Yes – Pass
- ☐ No
- ☐ 12. Extend the outboard reach string in front of the dummy and then backward and outboard to the latch plate to generate arcs of the reach envelope of the test dummy's arms. Is the latch plate within the reach envelope?
- ☐ Yes – Pass
- ☐ No
- ☐ 13. Is the latch plate within the inboard (item 11) or outboard (item 12) reach envelope?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 14. Using the clearance test block, specified in Figure 4, is there sufficient clearance between the vehicle seat and the side of vehicle interior to allow the test block to move unhindered to the latch plate or buckle?
- ☐ Yes – Pass
- ☐ No – Fail

REMARKS:

Signature: Wayne Zuhl Date: 1/18/13

I certify that I have read and performed each instruction.




Figure 3. Location of Anchoring Points for Latchplate Reach Limiting Chains or Strings to Test for Latchplate Accessibility Using Subpart E Test Device




Figure 4—USE OF CLEARANCE TEST BLOCK TO DETERMINE HAND/ARM ACCESS

DATA SHEET 12

SEAT BELT RETRACTION (S7.4.5)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

Test all front outboard seat belts, except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Not Applicable For Any Position – Passenger Car
------------------------------	---

- ☒ 1. Is the vehicle a passenger car or walk-in van-type vehicle?
 - ☒ Yes, this form is complete
 - ☐ No
- ☐ 2. Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)
 - ☐ N/A – No lumbar adjustment
- ☐ 3. Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
 - ☐ N/A – No additional support adjustment
- ☐ 4. Is the fore-aft position of the seat adjustable?
 - ☐ No – go to 5
 - ☐ Yes – go to 4.1
- ☐ 4.1 Use all the seat controls that have any affect on the fore-aft movement of the seat to move the seat cushion to the rearmost position. **Mark** this position. (8/31/95 legal interpretation to Hogan and Hartson)
- ☐ 4.2 Use all the seat controls that have any affects on the fore-aft movement of the seat to move the seat cushion to the foremost position. **Mark** this position. (8/31/95 legal interpretation to Hogan and Hartson)
- ☐ 4.3 **Mark** each fore-aft position so that there is a visual indication when the seat is at a particular position. For manual seats, **mark** each detent. For power seats, mark only the rearmost, middle and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost. Determine the mid fore-aft seat position based on the foremost and rearmost positions determined in items 4.1 and 4.2. (8/31/95 legal interpretation to Hogan and Hartson)
- ☐ 4.4 Move the seat to the mid position.
- ☐ 4.5 While maintaining the mid position, move the seat to its lowest position. For seats with adjustable seat cushions, use the manufacturer's recommended seat cushion angle for determining the lowest height position.
- ☐ 5. Is the seat back angle adjustable?
 - ☐ No- go to 6
 - ☐ Yes- go to 5.1
- ☐ 5.1 Set and mark seat back angle, if adjustable, at the manufacturer's nominal design riding position for a **50th percentile adult male** in the manner specified by the manufacturer.
 - ☐ N/A – No seat back angle adjustment
 - ☐ Manufacturer's design seat back angle: _____
 - ☐ Tested seat back angle: _____
- ☐ 6. Is the seat a bucket seat?
 - ☐ Yes, go to 6.1 and skip 6.2
 - ☐ No, go to 6.2 and skip 6.1

- ☐ 6.1 Bucket Seats:
Locate and **mark** the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S10.4.1.2 and S16.3.1.10)
- ☐ 6.2 Bench seats (complete ONLY the one that is applicable to the seat being tested):
- ☐ 6.2.1 Driver Seat
Locate and **mark** the longitudinal line on the seat cushion that marks the intersection of the vertical longitudinal plane through the centerline of the steering wheel and the seat cushion upper surface. (S10.4.1.1)
- ☐ 6.2.2 Front Outboard Passenger Seat
Locate and **mark** the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S10.4.1.1)
- ☐ Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel. _____
- ☐ Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. _____
- ☐ 7. Position the Part 572 Subpart E test dummy according to dummy position placement instructions in Appendix F. **Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure.**
- ☐ 8. Fasten the seat belt around the dummy.
- ☐ 9. Remove all slack from the lap belt portion. (S10.9)
- ☐ N/A, the seat does not have a fore-aft adjustment
- ☐ 10. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this four times. (S10.9)
- ☐ 11. Apply a 2 to 4 pound tension load to the lap belt. (S10.9)
- Pound load applied:**
- ☐ 12. Is the belt system equipped with a tension relieving device?
- ☐ Yes, continue
- ☐ No, go to 14
- ☐ 13. Introduce the maximum amount of slack into the upper torso belt that is recommended by the vehicle manufacturer in the vehicle owner's manual. (S10.9).
- ☐ 14. Check the statement that applies to this test vehicle:
- ☐ 14.1 The torso and lap belt webbing of the seat belt system automatically retracts to a stowed position when the adjacent vehicle door is in an open position and the seat belt latch plate is released.
- ☐ Yes – Pass go to 16
- ☐ No – go to 14.2
- ☐ 14.2 The torso and lap belt webbing of the seat belt system automatically retracts when the seat belt latch plate is released.
- ☐ Yes – Pass go to 15
- ☐ No – go to 14.3
- ☐ 14.3 Neither 14.1 nor 14.2 apply.
- ☐ Fail
- ☐ 15. With the webbing and hardware in the stowed position are the webbing and hardware prevented from being pinched when the door is closed?
- ☐ Yes – Pass
- ☐ No – Fail

- ☐ 16. If this test vehicle has an open body (without doors) and has a belt system with a tension relieving device, does the belt system fully retract when the tension-relieving device is deactivated?

- ☐ N/A – Not an open body vehicle
☐ Yes – Pass
☐ No – Fail

REMARKS:

Signature: Wayne Zahler

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 13

SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION: Left Rear Passenger

- | | | | | |
|-------------------------------------|-----|--|---|--|
| ☒ | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1(b)) | ☐ Yes, this form is complete | ☒ No, go to 2 |
| ☒ | 2. | Is the seat removable? (S7.4.6.1(b)) | ☐ Yes, this form is complete | ☒ No, go to 3 |
| ☒ | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b)) | ☐ Yes, this form is complete | ☒ No, go to 4 |
| ☒ | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a)) | ☒ Yes, go to 5 | ☐ No, this form is complete |
| ☒ | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a)) | ☒ Yes – Pass | ☐ No – Fail |
| | | Identify the part(s) on top or above the seat. | ☒ Seat belt latch plate | ☒ Buckle |
| ☒ | 6. | Are the remaining two seat belt parts accessible under normal conditions? | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2) | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 8. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2) | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 9. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2) | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 10. | Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2) | ☐ Yes – Pass | ☒ No – Fail |
| | | | ☒ N/A – Rear seat | |

REMARKS:

Signature: Wayne Dahlke

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 13

SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION: Center Rear Passenger

- | | | | | |
|-------------------------------------|-----|--|---|---|
| ☒ | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1(b)) | ☐ Yes, this form is complete | ☒ No, go to 2 |
| ☒ | 2. | Is the seat removable? (S7.4.6.1(b)) | ☐ Yes, this form is complete | ☒ No, go to 3 |
| ☒ | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b)) | ☐ Yes, this form is complete | ☒ No, go to 4 |
| ☒ | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a)) | ☒ Yes, go to 5 | ☐ No, this form is complete |
| ☒ | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a)) | ☒ Yes – Pass | ☐ No – Fail |
| | | Identify the part(s) on top or above the seat. | ☒ Seat belt latch plate | ☒ Buckle |
| ☒ | 6. | Are the remaining two seat belt parts accessible under normal conditions? | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2) | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 8. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2) | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 9. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2) | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 10. | Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2) | ☐ Yes – Pass | ☒ N/A – Rear seat |

REMARKS:

Signature: Wayne Dahlke

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 13

SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C20130100
 Test Date: 1/18/13

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION: Right Rear Passenger

- | | | | | |
|-------------------------------------|-----|--|---|--|
| ☒ | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1(b)) | ☐ Yes, this form is complete | ☒ No, go to 2 |
| ☒ | 2. | Is the seat removable? (S7.4.6.1(b)) | ☐ Yes, this form is complete | ☒ No, go to 3 |
| ☒ | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b)) | ☐ Yes, this form is complete | ☒ No, go to 4 |
| ☒ | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a)) | ☒ Yes, go to 5 | ☐ No, this form is complete |
| ☒ | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a)) | ☒ Yes – Pass | ☐ No – Fail |
| | | Identify the part(s) on top or above the seat. | ☒ Seat belt latch plate | ☒ Buckle |
| ☒ | 6. | Are the remaining two seat belt parts accessible under normal conditions? | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2) | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 8. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2) | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 9. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2) | ☒ Yes – Pass | ☐ No – Fail |
| ☒ | 10. | Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2) | ☐ Yes – Pass | ☐ No – Fail |
| | | | ☒ N/A – Rear seat | |

REMARKS:

Signature: Wayne Dahlke

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 16

AIR BAG SUPPRESSION TELLTALE (S19.2.2)

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C20130100
Test Date: 1/18/13

- X1. Is the vehicle certified to any suppression performance standards of FMVSS 208?
X Yes - go to 2
___ No - this form is complete
- X2. Does telltale emit yellow light when the air bag is suppressed? (S19.2.2 (a))
X Yes - Pass ___ **NO - FAIL**
- X3. Are the words "PASSENGER AIR BAG OFF" or "PASS AIR BAG OFF" (S19.2.2 (b))
X3.1 on the telltale? (S19.2.2 (b))
___ Yes - Pass, go to 4
X No - go to 3.2
- X3.2 Within 25 mm of the telltale? (S19.2.2 (b)) 5 mm from the edge of the telltale light
X Yes - Pass ___ **NO - FAIL**
- X4. Is the telltale separate from the air bag readiness indicator? (S19.2.2(c))
X Yes - Pass ___ **NO - FAIL**
- X5. Is the telltale within the interior of the vehicle? (S19.2.2 (d))
X Yes - Pass ___ **NO - FAIL**
- X6. Is the telltale forward of and above the design H-point of both the driver's and the front outboard passenger's seat when the seats are in their forwardmost seating positions? (S19.2.2 (d))
X Yes - Pass ___ **NO - FAIL**
- X7. Is the telltale away from surfaces that can be used for temporary or permanent storage of objects that could obscure the telltale from either the driver's or front outboard passenger's view? (S19.2.2 (d))
X Yes - Pass ___ **NO - FAIL**
- X8. Is the telltale located so that it is not obscured from the driver or front outboard passenger by a rear-facing child restraint in Appendix A installed in the front outboard passenger seat? (S19.2.2 (d))
X Yes - Pass ___ **NO - FAIL**
- X9. Is the telltale visible or recognizable during the night? (S19.2.2 (e))
X Yes - Pass ___ **NO - FAIL**
- X10. Is the telltale visible or recognizable during the day? (S19.2.2 (e))
X Yes - Pass ___ **NO - FAIL**
- X11. If there is a visibility adjustment, do all the adjustment levels make the telltale visible and recognizable? (S19.2.2 (g))
X N/A-No visibility adjustment
___ Yes - Pass ___ **NO - FAIL**
- X12. Does the telltale remain illuminated while the air bag is suppressed? (S19.2.2 (h)) (Leave the air bag suppressed for 5 minutes.)
X Yes - Pass ___ **NO - FAIL**
- X13. Is the telltale off while the air bag is activated? (S19.2.2 (h)) (Leave the air bag activated for 5 minutes.)
X Yes - Pass ___ **NO - FAIL**

Signature: Wayne Dahlke

Date: 1/18/13

I certify that I have read and performed each instruction.

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Cosco
CHILD RESTRAINT MODEL:	Arriva 22-049 (same as model 22-013)
DATE OF MANUFACTURE:	8-20-2008

Base: ☒ On ☐ Off ☐ N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
 Tested seat back angle: 5.8° on Headrest Post
 Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
 Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward	128	Suppressed
	Middle	128	Suppressed
	Rearward	129	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward 4*	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

* The CRS would not fit in this forward seat slide position. If there is a number in the seat slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 55 = Full Rearward; 55 total Seat Slide detents)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Cosco
CHILD RESTRAINT MODEL:	Arriva 22-049 (same as model 22-013)
DATE OF MANUFACTURE:	8-20-2008

Base: __On XOff __N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
Tested seat back angle: 5.8° on Headrest Post
Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward	127	Suppressed
	Middle	128	Suppressed
	Rearward	128	Suppressed
Unbelted Rear Facing	Forward 1*	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

* The CRS would not fit in this forward seat slide position. If there is a number in the seat slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 55 = Full Rearward; 55 total Seat Slide detents)

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Rearward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	Snugride
DATE OF MANUFACTURE:	5-24-2007

Base: X On Off N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
 Tested seat back angle: 5.8° on Headrest Post
 Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
 Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward	131	Suppressed
	Middle	128	Suppressed
	Rearward	128	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward 3*	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

* The CRS would not fit in this forward seat slide position. If there is a number in the seat slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 55 = Full Rearward; 55 total Seat Slide detents)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	Snugride
DATE OF MANUFACTURE:	5-24-2007

Base: __ On X Off __ N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
Tested seat back angle: 5.8° on Headrest Post
Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward	129	Suppressed
	Middle	130	Suppressed
	Rearward	128	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Middle position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Peg Perego
CHILD RESTRAINT MODEL:	Viaggio
DATE OF MANUFACTURE:	8-27-2007

Base: ☒ On ☐ Off ☐ N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
Tested seat back angle: 5.8° on Headrest Post
Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward	129	Suppressed
	Middle	129	Suppressed
	Rearward	131	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Peg Perego
CHILD RESTRAINT MODEL:	Viaggio
DATE OF MANUFACTURE:	8-27-2007

Base: __On __X__Off __N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
Tested seat back angle: 5.8° on Headrest Post
Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward	131	Suppressed
	Middle	128	Suppressed
	Rearward	128	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Forward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section C Forward Facing Convertible CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Roundabout E9L02
DATE OF MANUFACTURE:	7-2-2008

Base: __On __Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
Tested seat back angle: 5.8° on Headrest Post
Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing	Forward	132	Suppressed
	Middle	129	Suppressed
	Rearward	129	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward	132	Suppressed
	Middle	132	Suppressed
	Rearward	130	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Rearward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section C Forward Facing Convertible CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Cosco
CHILD RESTRAINT MODEL:	High Back Booster 22-209
DATE OF MANUFACTURE:	10-7-2008

Base: __On __Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
Tested seat back angle: 5.8° on Headrest Post
Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing	Forward	128	Suppressed
	Middle	128	Suppressed
	Rearward	128	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Middle position. (Human Identification Code 054; 46.7 kg 149.8 cm)

The Cosco High Back Booster 22-209 does not have a rear facing belt path.

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section C Forward Facing Convertible CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	Generations 352
DATE OF MANUFACTURE:	10-5-2006

Base: __On __Off X N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
Tested seat back angle: 5.8° on Headrest Post
Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing	Forward	128	Suppressed
	Middle	130	Suppressed
	Rearward	128	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Forward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

The Evenflo Generations 352 does not have a rear facing belt path.

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section C Forward Facing Convertible CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	ComfortSport
DATE OF MANUFACTURE:	6-15-2009

Base: ☐ On ☐ Off ☒ N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 6.6° on Headrest Post
 Tested seat back angle: 5.8° on Headrest Post
 Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
 Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing	Forward	131	Suppressed
	Middle	130	Suppressed
	Rearward	130	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward	132	Suppressed
	Middle	128	Suppressed
	Rearward	127	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Rearward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 18 SUMMARY

Suppression Test Using Newborn Infant Dummy (Part 572, Subpart K) Section A Car Bed

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	Newborn Infant	DUMMY SERIAL NO.:	003

CAR BED NAME:	Angel Guard
CAR BED MODEL:	Angel Ride
DATE OF MANUFACTURE:	4-15-2008

Base: __On __Off X N/A-Constraint does not have a removable base
(A car bed with a removable base shall be treated as two separate models, i.e. this form and test procedure will be completed with the base on and then repeated on a new form with the base off.

Manufacturer's design seat back angle: 6.6° on Headrest Post
Tested seat back angle: 5.8° on Headrest Post
Manufacturer's specified anchorage position: 0 of 5; Upper-most defined as 0
Tested anchorage position: 0 of 5; Upper-most defined as 0

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Result
Belted	Forward	Suppressed
	Middle	Suppressed
	Rearward	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Rearward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 19 SUMMARY

Suppression Test Using 3 Year Old Dummy And Booster Seats (Part 572, Subpart P) Section D Forward Facing Belt Positioning Booster

NHTSA NO.:	C20130100	TEST DATE:	1/23/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

BOOSTER SEAT NAME:	Cosco
BOOSTER SEAT MODEL:	Summit Deluxe High Back Booster 22-262
DATE OF MANUFACTURE:	8-9-2007

Manufacturer's design seat back angle:	<u>6.6° on Headrest Post</u>
Tested seat back angle:	<u>5.8° on Headrest Post</u>
Manufacturer's specified anchorage position:	<u>0 of 5; Upper-most defined as 0</u>
Tested anchorage position:	<u>0 of 5; Upper-most defined as 0</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing Without Harness	Forward	15	Suppressed
	Middle	10	Suppressed
	Rearward	14	Suppressed
Belted Forward Facing Cinched With Harness	Forward	127	Suppressed
	Middle	128	Suppressed
	Rearward	128	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Rearward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 19 SUMMARY

Suppression Test Using 3 Year Old Dummy And Booster Seats (Part 572, Subpart P) Section D Forward Facing Belt Positioning Booster

NHTSA NO.:	C20130100	TEST DATE:	1/23/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

BOOSTER SEAT NAME:	Graco
BOOSTER SEAT MODEL:	Platinum Cargo
DATE OF MANUFACTURE:	6-24-2008

Manufacturer's design seat back angle:	<u>6.6° on Headrest Post</u>
Tested seat back angle:	<u>5.8° on Headrest Post</u>
Manufacturer's specified anchorage position:	<u>0 of 5; Upper-most defined as 0</u>
Tested anchorage position:	<u>0 of 5; Upper-most defined as 0</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing Without Harness	Forward	15	Suppressed
	Middle	18	Suppressed
	Rearward	18	Suppressed
Belted Forward Facing Cinched With Harness	Forward	131	Suppressed
	Middle	128	Suppressed
	Rearward	129	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Forward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 20 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Roundabout E9L02
DATE OF MANUFACTURE:	7-2-2008

Manufacturer's design seat back angle:	<u>6.6° on Headrest Post</u>
Tested seat back angle:	<u>5.8° on Headrest Post</u>
Manufacturer's specified anchorage position:	<u>0 of 5; Upper-most defined as 0</u>
Tested anchorage position:	<u>0 of 5; Upper-most defined as 0</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward	128	Suppressed
	Middle	129	Suppressed
	Rearward	128	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Rearward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 20 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Cosco
CHILD RESTRAINT MODEL:	High Back Booster 22-209
DATE OF MANUFACTURE:	10-7-2008

Manufacturer's design seat back angle:	<u>6.6° on Headrest Post</u>
Tested seat back angle:	<u>5.8° on Headrest Post</u>
Manufacturer's specified anchorage position:	<u>0 of 5; Upper-most defined as 0</u>
Tested anchorage position:	<u>0 of 5; Upper-most defined as 0</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing Without Harness	Forward	9	Suppressed
	Middle	12	Suppressed
	Rearward	10	Suppressed
Belted Forward Facing Cinched With Harness	Forward	128	Suppressed
	Middle	127	Suppressed
	Rearward	128	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Middle position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 20 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	Generations 352
DATE OF MANUFACTURE:	10-5-2006

Manufacturer's design seat back angle:	<u>6.6° on Headrest Post</u>
Tested seat back angle:	<u>5.8° on Headrest Post</u>
Manufacturer's specified anchorage position:	<u>0 of 5; Upper-most defined as 0</u>
Tested anchorage position:	<u>0 of 5; Upper-most defined as 0</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing Without Harness	Forward	10	Suppressed
	Middle	9	Suppressed
	Rearward	15	Suppressed
Belted Forward Facing Cinched With Harness	Forward	128	Suppressed
	Middle	127	Suppressed
	Rearward	127	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Forward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 20 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA NO.:	C20130100	TEST DATE:	1/21/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	ComfortSport
DATE OF MANUFACTURE:	6-15-2009

Manufacturer's design seat back angle:	<u>6.6° on Headrest Post</u>
Tested seat back angle:	<u>5.8° on Headrest Post</u>
Manufacturer's specified anchorage position:	<u>0 of 5; Upper-most defined as 0</u>
Tested anchorage position:	<u>0 of 5; Upper-most defined as 0</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward	130	Suppressed
	Middle	128	Suppressed
	Rearward	129	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Rearward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 21 SUMMARY

Suppression Test Using An Unbelted 3 Year Old Dummy (Part 572, Subpart P)
No CRS

NHTSA NO.:	C20130100	TEST DATE:	1/23/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

Test Summary

Position	Seat Slide	Seat Back Angle *	Result
Position 1 Sitting on seat with back against seat back	Forward	5.8° on HRP	Suppressed
	Middle	5.8° on HRP	Suppressed
	Rearward	5.8° on HRP	Suppressed
Position 2 Sitting on seat with back against reclined seat back	Forward	30.2° on HRP	Suppressed
	Middle	30.2° on HRP	Suppressed
	Rearward	30.2° on HRP	Suppressed
Position 3 Sitting on seat with back not against seat back	Forward	5.8° on HRP	Suppressed
	Middle	5.8° on HRP	Suppressed
	Rearward	5.8° on HRP	Suppressed
Position 4 Sitting on seat edge, spine vertical, hands at subject's sides	Forward	5.8° on HRP	Suppressed
	Middle	5.8° on HRP	Suppressed
	Rearward	5.8° on HRP	Suppressed
Position 5 Standing on seat, facing forward	Forward	5.8° on HRP	Suppressed
	Middle	5.8° on HRP	Suppressed
	Rearward	5.8° on HRP	Suppressed
Position 6 Kneeling on seat, facing forward	Forward	5.8° on HRP	Suppressed
	Middle	5.8° on HRP	Suppressed
	Rearward	5.8° on HRP	Suppressed
Position 7 Kneeling on seat, facing rearward	Forward	5.8° on HRP	Suppressed
	Middle	5.8° on HRP	Suppressed
	Rearward	5.8° on HRP	Suppressed
Position 8 Lying on seat. (Three designated seating positions only)	Forward	N/A	N/A
	Middle	N/A	N/A
	Rearward	N/A	N/A

*The manufacturer's design seat back angle was 6.6° on the headrest post (HRP). When the vehicle passenger seat was reclined 25° the seat back angle on the headrest post was 30.2°.

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Forward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 22H SUMMARY

Suppression Test Using 6 Year Old Human Subject and Booster Seats
Section D Forward Facing Toddler

NHTSA NO.:	C20130100	TEST DATE:	1/23/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
SUBJECT TYPE:	6 Year Old	CHILD IDENTIFICATION CODE:	068

(Child Identification Code 068; 22.8 kg, 119.7 cm)

CHILD RESTRAINT NAME:	Cosco
CHILD RESTRAINT MODEL:	Summit Deluxe High Back Booster 22-260
DATE OF MANUFACTURE:	8-9-2007

Manufacturer's design seat back angle:	<u>6.6° on Headrest Post</u>
Tested seat back angle:	<u>5.8° on Headrest Post</u>
Manufacturer's specified anchorage position:	<u>0 of 5; Upper-most defined as 0</u>
Tested anchorage position:	<u>0 of 5; Upper-most defined as 0</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward	18	Suppressed
	Middle	12	Suppressed
	Rearward	10	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Middle position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 22H SUMMARY

Suppression Test Using 6 Year Old Human Subject and Booster Seats Section D Forward Facing Toddler

NHTSA NO.:	C20130100	TEST DATE:	1/23/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
SUBJECT TYPE:	6 Year Old	CHILD IDENTIFICATION CODE:	068

(Child Identification Code 068; 22.8 kg, 119.7 cm)

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	Platinum Cargo
DATE OF MANUFACTURE:	6-24-2008

Manufacturer's design seat back angle:	<u>6.6° on Headrest Post</u>
Tested seat back angle:	<u>5.8° on Headrest Post</u>
Manufacturer's specified anchorage position:	<u>0 of 5; Upper-most defined as 0</u>
Tested anchorage position:	<u>0 of 5; Upper-most defined as 0</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward	15	Suppressed
	Middle	17	Suppressed
	Rearward	10	Suppressed

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Forward position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 23H SUMMARY

Suppression Test Using an Unbelted 6 Year Old Human Subject
No CRS

NHTSA NO.:	C20130100	TEST DATE:	1/23/13
LABORATORY:	MGA	TECHNICIAN(S):	WD
SUBJECT TYPE:	6 Year Old	CHILD IDENTIFICATION CODE:	068

(Child Identification Code 068; 22.8 kg, 119.7 cm)

Test Summary

Position	Seat Slide	Seat Back Angle *	Result
Position 1 Sitting on seat with back against seat back	Forward	5.8° on HRP	Suppressed
	Middle	5.8° on HRP	Suppressed
	Rearward	5.8° on HRP	Suppressed
Position 2 Sitting on seat with back against reclined seat back	Forward	30.2° on HRP	Suppressed
	Middle	30.2° on HRP	Suppressed
	Rearward	30.2° on HRP	Suppressed
Position 3 Sitting on seat edge, spine vertical, hands at subject's sides	Forward	5.8° on HRP	Suppressed
	Middle	5.8° on HRP	Suppressed
	Rearward	5.8° on HRP	Suppressed
Position 4 Sitting on seat with back against seat back then leaning on the door	Forward	5.8° on HRP	Suppressed
	Middle	5.8° on HRP	Suppressed
	Rearward	5.8° on HRP	Suppressed

* The manufacturer's design seat back angle was 6.6° on the head rest post (HRP). When the vehicle passenger seat was reclined 25° the seat back angle on the head rest post was 30.2°.

Successful unbelted representative 5th percentile female reactivation was performed with the seat in the Middle position. (Human Identification Code 054; 46.7 kg 149.8 cm)

DATA SHEET 29 SUMMARY

Low Risk Deployment Tests Using an Unbelted 5th Percentile Female
Dummy (Part 572, Subpart O) (S26) Position 1 - Chin On Module (S26.2)

NHTSA NO.:	C20130100	TEST DATE:	2/11/13
LABORATORY:	MGA	TECHNICIAN(S):	BR / WD
DUMMY TYPE:	5 th Percentile Female	DUMMY SERIAL NO.:	510

Manufacturer's design seat back angle: 6.6° on Headrest Post
Tested seat back angle: 6.6° on Headrest Post
Tested seat position: Full Aft

Tested steering wheel angle: 23.7°
Thorax cavity angle: 29.2°
Bottom of chin height: 0 mm - At Plane F Module Height

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.0
2	120.0	120.0

5th Percentile Female SN 510 Position 1 (Chin On Module) 2/11/13

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	19
Peak Nij (Nte)	1.0	0.3
Time (ms)	NA	121.5
Peak Nij (Ntf)	1.0	0.3
Time (ms)	NA	12.6
Peak Nij (Nce)	1.0	0.4
Time (ms)	NA	170.8
Peak Nij (Ncf)	1.0	0.3
Time (ms)	NA	17.0
Neck Tension	2070 N	379
Neck Compression	2520 N	347
Chest g	60 g	10
Chest Displacement	52 mm	6
Left Femur	6805 N	76
Right Femur	6805 N	86

Calculated on data recorded for 125 ms after the initiation of the final stage of air bag deployment designed to deploy in any full frontal rigid barrier crash up to 26 km/h. (S4.11(d))
Second stage fire time of 120 ms; Injuries calculated on 0 ms to 245 ms.

The original equipment parts were used for this deployment.

DATA SHEET 30 SUMMARY

Low Risk Deployment Tests Using an Unbelted 5th Percentile Female Dummy (Part 572, Subpart O) (S26) Position 2 - Chin On Rim (S26.3)

NHTSA NO.:	C20130100	TEST DATE:	2/11/13
LABORATORY:	MGA	TECHNICIAN(S):	BR / WD
DUMMY TYPE:	5 th Percentile Female	DUMMY SERIAL NO.:	510

Manufacturer's design seat back angle: 6.6° on Headrest Post

Tested seat back angle: 6.6° on Headrest Post

Tested seat position: Full Aft

Tested steering wheel angle: 23.7°

Thorax cavity angle: 29.9°

Chin Point height: 0 mm - At Steering Wheel Target

Note: The chin on rim steering wheel target is 10 mm below the highest point on the steering wheel

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.0
2	120.0	120.0

5th Percentile Female SN 510 Position 2 (Chin On Rim) 2/11/13

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	5
Peak Nij (Nte)	1.0	0.4
Time (ms)	NA	13.4
Peak Nij (Ntf)	1.0	0.1
Time (ms)	NA	45.1
Peak Nij (Nce)	1.0	0.1
Time (ms)	NA	189.5
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	58.7
Neck Tension	2070 N	525
Neck Compression	2520 N	132
Chest g	60 g	20
Chest Displacement	52 mm	18
Left Femur	6805 N	23
Right Femur	6805 N	39

Calculated on data recorded for 125 ms after the initiation of the final stage of air bag deployment designed to deploy in any full frontal rigid barrier crash up to 26 km/h. (S4.11(d))
Second stage fire time of 120 ms; Injuries calculated on 0 ms to 245 ms.

A new air bag was used for this deployment.

DATA SHEET 32

VEHICLE WEIGHT, FUEL TANK, AND ATTITUDE DATA

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Chad Seebecker

NHTSA No.: C20130100
 Test Date: 2/25/13

IMPACT ANGLE:	Zero				
BELTED DUMMIES (YES/NO):	No				
TEST SPEED:	X	32 to 40 kmph		0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	X		5 th female		50 th male
PASSENGER DUMMY:	X		5 th female		50 th male

- | | | |
|---|-----|---|
| X | 1. | Fill the transmission with transmission fluid to the satisfactory range. |
| X | 2. | Drain fuel from vehicle. |
| X | 3. | Run the engine until fuel remaining in the fuel delivery system is used and the engine stops. |
| X | 4. | Record the useable fuel tank capacity supplied by the COTR. |
| X | | Useable Fuel Tank Capacity supplied by COTR: 46.2 liters (12.2 gallons) |
| X | 5. | Record the fuel tank capacity supplied in the owner's manual. |
| X | | Useable Fuel Tank Capacity in owner's manual: 46.2 liters (12.2 gallons) |
| X | 6. | Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," or gasoline, fill the fuel tank. |
| X | | Amount Added: 46.2 liters (12.2 gallons) |
| X | 7. | Fill the coolant system to capacity. |
| X | 8. | Fill the engine with motor oil to the Max. mark on the dip stick. |
| X | 9. | Fill the brake reservoir with brake fluid to its normal level. |
| X | 10. | Fill the windshield washer reservoir to capacity. |
| X | 11. | Inflate the tires to the tire pressure on the tire placard. If no tire placard is available, inflate the tires to the recommended pressure in the owner's manual. |

Tire placard pressure:	RF:	38 psi	LF:	38 psi	RR:	38 psi	LR:	38 psi
Owner's manual pressure:	RF:	38 psi	LF:	38 psi	RR:	38 psi	LR:	38 psi
Actual inflated pressure:	RF:	38 psi	LF:	38 psi	RR:	38 psi	LR:	38 psi

- | | | |
|---|-----|--|
| X | 12. | Record the vehicle weight at each wheel to determine the unloaded vehicle weight (UVW), i.e. "as delivered" weight). |
|---|-----|--|

Right Front (kg):	377.8	Right Rear (kg):	234.1
Left Front (kg):	366.1	Left Rear (kg):	254.9
Total Front (kg):	743.9	Total Rear (kg):	489.0
% Total Weight:	60.3	% Total Weight:	39.7
UVW = TOTAL FRONT PLUS TOTAL REAR (KG):		1232.9	

- | | | |
|---|------|--|
| X | 13. | UVW Test Vehicle Attitude: (All dimensions in millimeters) |
| X | 13.1 | Mark a point on the vehicle above the center of each wheel. |
| X | 13.2 | Place the vehicle on a level surface. |
| X | 13.3 | Measure perpendicular to the level surface to the 4 points marked on the body and record the measurements. |

RF:	680	LF:	681	RR:	690	LR:	686
-----	-----	-----	-----	-----	-----	-----	-----

- ☒ 14. Calculate the Rated Cargo and Luggage Weight (RCLW): 66 kg
- ☒ 14.1 Does the vehicle have the vehicle capacity weight (VCW) on the certification label or tire placard?
- ☒ Yes, go to 14.3
- ☐ No, go to 14.2
- ☐ 14.2 VCW = Gross Vehicle Weight - UVW

$$VCW = \underline{\hspace{2cm}} - \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

- ☒ 14.3 VCW = 406 kg (895 lbs)
- ☒ 14.4 Does the certification or tire placard contain the Designated Seating Capacity (DSC)?
- ☒ Yes, go to 14.6
- ☐ No, go to 14.5 and skip 14.6
- ☐ 14.5 DSC = Total number of seat belt assemblies =
- ☒ 14.6 DSC = 5
- ☒ 14.7 RCLW = VCW - (68 kg x DSC) = 406 kg - (68 kg x 5) = 66 kg
- ☒ 14.8 Is the vehicle certified as a truck, MPV or bus (see the certification label on the door jamb)?
- ☐ Yes, if the calculated RCLW is greater than 136 kg, use 136 kg as the RCLW. (S8.1.1)
- ☒ No, use the RCLW calculated in 14.7
- ☒ 15. Fully Loaded Weight (100% fuel fill): 1396.6 kg
- ☒ 15.1 Place the appropriate test dummy in both front outboard seating positions.

Driver: X 5th female 50th male
 Passenger: X 5th female 50th male

- ☒ 15.2 Load the vehicle with the RCLW from 14.7 or 14.8 whichever is applicable.
- ☒ 15.3 Place the RCLW in the cargo area. Center the load over the longitudinal centerline of the vehicle. (S8.1.1 (d))
- ☒ 15.4 Record the vehicle weight at each wheel to determine the Fully Loaded Weight.

Right Front (kg):	398.7	Right Rear (kg):	294.8
Left Front (kg):	387.4	Left Rear (kg):	315.7
Total Front (kg):	786.1	Total Rear (kg):	610.5
% Total Weight:	56.3	% Total Weight:	43.7
% GVW	51.8	% GVW	48.2
(% GVW = Axle GVW divided by Vehicle GVW)			
Fully Loaded Weight = Total Front Plus Total Rear (kg):			1396.6

- ☒ 16. Fully Loaded Test Vehicle Attitude: (All dimensions in millimeters)
- ☒ 16.1 Place the vehicle on a level surface.
- ☒ 16.2 Measure perpendicular to the level surface to the 4 points marked on the body (see 13.1 above) and record the measurements.

RF:	675	LF:	674	RR:	658	LR:	656
-----	-----	-----	-----	-----	-----	-----	-----

- ☒ 17. Drain the fuel system.

☒ 18. Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," fill the fuel tank to 92 - 94 percent of useable capacity.

☒ Fuel tank capacity x .94 = 46.2 liters (12.2 gallons) x .94 = 43.4 liters (11.5 gallons)

☒ Amount added: 43.0 liters (11.35 gallons) 93%

☒ 19. Crank the engine to fill the fuel delivery system with Stoddard solvent.

☒ 20. Calculate the test weight range.

☒ 20.1 Calculated Weight =
UVW (see 12 above) + RCLW (see 14 above) + 2x(dummy weight)

1396.9 kg = 1232.9 kg + 66.0 kg + 98.0 kg

☒ 20.2 Test Weight Range = Calculated Weight (- 4.5 kg, - 9 kg.)
Max. Test Weight = Calculated Test Weight - 4.5 kg = 1392.4 kg
Min. Test Weight = Calculated Test Weight - 9 kg = 1387.9 kg

☒ 21. Remove the RCLW from the cargo area.

☒ 22. Drain transmission fluid, engine coolant, motor oil, and windshield washer fluid from the test vehicle so that Stoddard solvent leakage from the fuel system will be evident.

☒ 23. Vehicle Components Removed For Weight Reduction:
Right Hand Rear Tail Light, Spare Tire, Jack and Tools, Trunk Carpet

☒ 24. Secure the equipment and ballast in the load carrying area and distribute it, as nearly as possible, to obtain the proportion of axle weight indicated by the gross axle weight ratings and center it over the longitudinal centerline of the vehicle.

☒ 25. If necessary, add ballast to achieve the actual test weight.

☐ N/A

☒ Weight of Ballast: 40.8 kg in cargo area

☒ 26. Ballast, including test equipment, must be contained so that it will not shift during the impact event or interfere with data collection or interfere with high-speed film recordings or affect the structural integrity of the vehicle or do anything else to affect test results. Care must be taken to assure that any attachment hardware added to the vehicle is not in the vicinity of the fuel tank or lines.

☒ 27. Record the vehicle weight at each wheel to determine the actual test weight.

Right Front (kg):	398.3	Right Rear (kg):	294.4
Left Front (kg):	397.8	Left Rear (kg):	299.8
Total Front (kg):	796.1	Total Rear (kg):	594.2
% Total Weight:	57.3	% Total Weight:	42.7
% GVW	51.8	% GVW	48.2
(% GVW = Axle GVW divided by Vehicle GVW)			
TOTAL FRONT PLUS TOTAL REAR (kg):			1390.3

☒ 28. Is the test weight between the Max. Weight and the Min. Weight (See 20.2)?

☒ Yes

☐ No, explain why not.

☒ 29. Test Weight Vehicle Attitude: (all dimensions in millimeters)

☒ 29.1 Place the vehicle on a level surface.

☒ 29.2 Measure perpendicular to the level surface to the 4 points marked on the body (see 13 above) and record the measurements.

RF:	680	LF:	680	RR:	682	LR:	683
-----	-----	-----	-----	-----	-----	-----	-----

- ☒ 30. Summary of test attitude
☒ 30.1 AS DELIVERED:

RF:	680	LF:	681	RR:	690	LR:	686
-----	-----	-----	-----	-----	-----	-----	-----

AS TESTED:

RF:	680	LF:	680	RR:	682	LR:	683
-----	-----	-----	-----	-----	-----	-----	-----


FULLY LOADED:

RF:	675	LF:	674	RR:	658	LR:	656
-----	-----	-----	-----	-----	-----	-----	-----

- ☒ 30.2 Is the "as tested" test attitude equal to or between the "fully loaded" and "as delivered" attitude?

- ☒ Yes
☐ No, explain why not.

REMARKS:

Signature: 

Date: 2/25/13

I certify that I have read and performed each instruction.

DATA SHEET 33

VEHICLE ACCELEROMETER LOCATION AND MEASUREMENT

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Chad Seebecker


NHTSA No.: C20130100
 Test Date: 2/25/13

IMPACT ANGLE:	Zero				
BELTED DUMMIES (YES/NO):	No				
TEST SPEED:	X	32 to 40 kmph		0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	X		5 th female		50 th male
PASSENGER DUMMY:	X		5 th female		50 th male

- ☒ 1. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the left front outboard seating position intersects the left rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- ☒ 2. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the right front outboard seating position intersects the right rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- ☒ 3. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect at the top of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- ☒ 4. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect the bottom of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- ☒ 5. Install an accelerometer on the right front brake caliper to record x-direction accelerations. Record the location on the following chart.
- ☒ 6. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the top of the instrument panel. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- ☒ 7. Install an accelerometer on the left front brake caliper to record x-direction accelerations. Record the location on the following chart.
- ☒ 8. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the floor of the trunk. Install an accelerometer on the trunk floor at this intersection to record z-direction accelerations. Record the location on the following chart.

REMARKS:


I certify that I have read and performed each instruction.

Signature: 

Date: 2/25/13


VEHICLE ACCELEROMETER LOCATION AND DATA SUMMARY

CENTERLINE OF
FRONT WHEELS



ACCELEROMETER
COORDINATE SYSTEM
(POSITIVE DIRECTION SHOWN)

REAR SEAT CUSHION
ASSY. FRONT ATTACHMENT
BRACKET SUPPORT



Dimensions Corresponding To The Letters "A" Through "K" (Excluding "I") Are Recorded In The Table On The Following Page.

Accelerometers Corresponding To The Numbers 1 Through 8 Are Specified On The Preceding Page.

VEHICLE ACCELEROMETER LOCATION AND MEASUREMENTS

<u>DIMENSION</u>	<u>LENGTH (mm)</u>	
<u>PRETEST VALUES</u>		
<u>A</u> (LH Rear Seat Xmbr)	375	
<u>B</u> (RH Rear Seat Xmbr)	375	
<u>C</u> (Engine Top)	3659	
<u>D</u> (Engine Bottom)	3649	
<u>E</u> (Caliper)	Right Side: 3610	Left Side: 3610
<u>F</u> (Left Caliper)	652	
<u>G</u> (IP)	3028	
<u>H</u> (Seat)	1857	
<u>J</u> (Right Caliper)	652	
<u>K</u> (Trunk)	168	
<u>POST TEST VALUES</u>		
<u>A</u> (LH Rear Seat Xmbr)	375	
<u>B</u> (RH Rear Seat Xmbr)	375	
<u>C</u> (Engine Top)	3631	
<u>D</u> (Engine Bottom)	3640	
<u>E</u> (Caliper)	Right Side: 3589	Left Side: 3602
<u>F</u> (Left Caliper)	649	
<u>G</u> (IP)	3028	
<u>H</u> (Seat)	1857	
<u>J</u> (Right Caliper)	646	
<u>K</u> (Trunk)	168	

DATA SHEET 34 **PHOTOGRAPHIC TARGETS**

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Chad Seebecker

NHTSA No.: C20130100
Test Date: 2/25/13

IMPACT ANGLE:	Zero				
BELTED DUMMIES (YES/NO):	No				
TEST SPEED:	X	32 to 40 kmph		0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	X		5 th female		50 th male
PASSENGER DUMMY:	X		5 th female		50 th male

- | | | |
|-------------------------------------|------|--|
| ☒ | 1. | FMVSS 208 vehicle targeting requirements (See Figures 28A and 28B) |
| ☒ | 1.1 | Targets A1 and A2 are on flat rectangular panels. |
| ☒ | 1.2 | Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the front on the outboard sides of A1 and A2. The center of each circular target is 100 mm from the one next to it. |
| ☒ | | Distance between targets (mm): <u>100 mm</u> |
| ☒ | 1.3 | Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the back on the outboard sides of on A1 and A2. The center of each circular target is 100 mm from the one next to it. |
| ☒ | | Distance between targets (mm): <u>100 mm</u> |
| ☒ | 1.4 | The distance between the first circular target at the front of A1 and A2 and the last circular target at the back of A1 and A2 is at least 915 mm. |
| ☒ | | Distance between the first and last circular targets (mm): <u>915 mm</u> |
| ☒ | 1.5 | Firmly fix target A1 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy. |
| ☒ | 1.6 | Firmly fix target A2 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy. |
| ☒ | 1.7 | Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the driver door. The centers of each circular target are at least 610 mm apart. |
| ☒ | | Distance between targets (mm): <u>610 mm</u> |
| ☒ | 1.8 | Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the passenger door. The centers of each circular target are at least 610 mm apart. |
| ☒ | | Distance between targets (mm): <u>610 mm</u> |
| ☒ | 1.9 | Place tape with squares having alternating colors on the top portion of the steering wheel. |
| ☒ | 1.10 | Chalk the bottom portion of the steering wheel. |
| ☒ | 1.11 | Is this an offset test? |
| ☐ | | Yes, continue with this section |
| ☒ | | No, go to 2. |
| ☐ | 1.12 | Measure the width of the vehicle. |
| ☐ | | Vehicle width (mm): _____ |
| ☐ | 1.13 | Find the centerline of the vehicle. ($\frac{1}{2}$ of the vehicle width) |
| ☐ | 1.14 | Find the line parallel to the centerline of the vehicle and 0.1 x vehicle width from the centerline of the vehicle. |

☐	1.15	Apply 25 mm wide tape with alternating black and yellow squares parallel to and on each side of the line found in 1.14. The edge of each tape shall be 50 mm from the line found in 1.14. The tape shall extend from the bottom of the bumper to the front edge of the windshield. (Figure 28D)
☒	2.	Barrier Targeting
☒	2.1	Fix two stationary targets D1 and D2 to the barrier as shown in the Figure 28A. One target is in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy. The other is in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy.
☒	2.2	Targets D1 and D2 are on a rectangular panel.
☒	2.3	Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted on the sides of the rectangular panel away from the longitudinal centerline of the vehicle. The center of each circular target is 100 mm from the one next to it.
☒		Distance between circular targets on D1 (mm): <u>100 mm</u>
☒		Distance between circular targets on D2 (mm): <u>100 mm</u>
☒	3.	FMVSS 208 Dummy Targeting Requirements
☒	3.1	Place a circular target with black and yellow quadrants on both sides of the driver dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
☒	3.2	Place a circular target with black and yellow quadrants on both sides of the passenger dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
☒	3.3	Place a circular target with black and yellow quadrants on the outboard shoulder of the driver dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
☒	3.4	Place a circular target with black and yellow quadrants on the outboard shoulder of the passenger dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
☒	4.	FMVSS 204 Targeting Requirements
☒	4.1	Is an FMVSS 204 indicant test ordered on the "COTR Vehicle Work Order?"
☐		Yes, continue with this form.
☒		No, this form is complete.
☐	4.2	Resection panel (Figure 28C)
☐	4.2.1	The panel deviates no more than 6 mm from perfect flatness when suspended vertically
☐	4.2.2	The 8 targets on the panel are circular targets at least 90 mm in diameter and with black and yellow quadrants.
☐	4.2.3	The center of each of the 4 outer targets are placed within 1 mm of the corners of a square measuring 914 mm on each side.
☐	4.2.4	Locate another square with 228 mm sides and with the center of this square coincident with the center of the 914 mm square.
☐	4.2.5	The center of the 4 inner targets are placed at the midpoints of each of the 228 mm sides.
☐	4.3	Place a circular target at least 90 mm in diameter and with black and yellow quadrants on a material (cardboard, metal, etc.) that can be taped to the top of the steering column.



- 4.4 Tape the target from 4.3 to the top of the steering column in a manner that does not interfere with the movement of the steering column in a crash.


REMARKS:

Signature: 


Date: 2/25/13

I certify that I have read and performed each instruction.


REFERENCE PHOTO TARGETS




RESECTION PANEL TARGETING ALIGNMENT



TEST RUN STEERING COLUMN CAMERA VIEW OF TYPICAL TIME ZERO VEHICLE POSITION



PRE-RUN STEERING COLUMN HIGH SPEED CAMERA VIEW



LEFT SIDE VIEW

DATA SHEET 35
CAMERA LOCATIONS

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance


NHTSA No.: C20130100
Test Date: 2/25/13
Time: 11:06 am

CAMERA NO.	VIEW	CAMERA POSITIONS (mm) *			LENS (mm)	SPEED (fps)
		X	Y	Z		
1	Real Time Left Side View				13	24
2	Left Side View (Barrier face to front seat backs)	1150	-4690	1410	24	1000
3	Left Side View (Driver)	1320	-6580	1990	35	1000
4	Left Side View (B-post aimed toward center of steering wheel)	5540	-5050	2010	50	1000
5	Left Side View (Steering Column)	580	-4910	1240	24	1000
6	Left Side View (Steering Column)	560	-4860	830	24	1000
7	Right Side View (Overall)	2100	6120	1420	20	1000
8	Right Side View (Passenger)	1280	4720	1390	24	1000
9	Right Side View (Angle)	5750	4770	2030	50	1000
10	Right Side View (Front door)	1510	6690	1990	35	1000
11	Front View Windshield	-50	0	2810	20	1000
12	Front View Driver	240	-450	2030	8.5	1000
13	Front View Passenger	240	450	2030	8.5	1000
14	Overhead Barrier Impact View	1900	0	4910	14	1000
15	Pit Camera Engine View	1270	0	-3150	24	1000
16	Pit Camera Fuel Tank View	3120	0	-3150	24	1000

***COORDINATES:**

- +X - forward of impact plane
- +Y - right of monorail centerline
- +Z - above ground level

CAMERA POSITIONS FOR FMVSS 208



DATA SHEET 36 - APPENDIX G
DUMMY POSITIONING PROCEDURES
FOR 5th PERCENTILE FEMALE DRIVER TEST DUMMY
CONFORMING TO SUBPART O OF PART 572

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Alexander Vanderheyden

NHTSA No.: C20130100
 Test Date: 2/25/13

IMPACT ANGLE:	Zero				
BELTED DUMMIES (YES/NO):	No				
TEST SPEED:	X	32 to 40 kmph		0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	X		5 th female		50 th male
PASSENGER DUMMY:	X		5 th female		50 th male

Seating Procedure 5th Percentile Female Driver Dummy (Part 572, Subpart O) (S16.2-S16.3)

1. Seat Position

- X 1.1 Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions. (S16.2.10.1, S20.1.9.1, S20.4.1, S22.1.7.1)
X N/A – No lumbar adjustment
- X 1.2 Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2, S20.1.9.2, S20.4.1, S22.1.7.1, S22.4.2.1, S22.4.3.1, S24.4.2.1, S26.2.3, S26.3.1)
X N/A – No additional support adjustment
- X 1.3 Position an adjustable leg support system in its rearmost position. (8/27/04 interpretation to Toyota)
X N/A – No adjustable leg support system
- X 1.4 **Mark** a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion. (S16.3.1.12)
- X 1.5 Draw a line (seat cushion reference line) through the seat cushion reference point. (S16.3.1.13)
- X 1.6 Use only the controls that primarily move the seat in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S22.1.7.3)
- X 1.7 If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S20.1.9.3)
X N/A – No independent fore-aft seat cushion adjustment
- X 1.8 Use any part of any control, other than the parts just used for fore-aft positioning, to determine the range of angles of the seat cushion reference line and to set the seat cushion reference line at the mid-angle. (S16.2.10.3.1)
 Maximum angle: 0.6° Nose Up
 Minimum angle: 4.8 ° Nose Down
 Mid-angle: 2.1° Nose Down

- ☒ 1.9 If the seat and/or seat cushion height is adjustable, use any part of any control other than the parts which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-angle found in 1.8. (S16.2.10.3.1)
☐ N/A – No seat height adjustment
- ☒ 1.10 Use only the controls that primarily move the seat in the fore-aft direction to verify the seat is in the rearmost position.
- ☒ 1.11 Use only the controls that primarily move the seat in the fore-aft direction to **mark** the fore-aft seat positions. **Mark** each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and **mark** each detent. For power seats, **mark** only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost.
- ☒ 1.12 Use only the controls that primarily move the seat in the fore-aft direction to place the seat in the rearmost position.
- ☒ 1.13 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S22.4.3.1, S24.1.2, S24.3.1, S24.4.3.1, S26.2.3, S26.3.1)
☐ N/A – No seat height adjustment. Go to 1.18
- ☒ 1.14 Use only the controls that primarily move the seat and/or seat cushion in the fore-aft direction to place the seat in the mid-fore-aft position.
- ☒ 1.15 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- ☒ 1.16 Use only the control that change the seat in the fore-aft direction to place the seat in the foremost position. (S16.2.10.3.2)
- ☒ 1.17 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S16.2.10.3.3, S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- ☒ 1.18. Is the seat a bucket seat?
☒ Yes, go to 1.19 and skip 1.20
☐ No, go to 1.20 and skip 1.19
- ☒ 1.19 Bucket seats:
Locate and **mark** for future reference the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S16.3.1.10 & S20.1.10)

- ☐ 1.20 Bench seats (complete ONLY the one that is applicable to the seat being marked):
Locate and **mark** for future reference the longitudinal line on the seat cushion that marks the intersection of the vertical longitudinal plane through the centerline of the steering wheel and the seat cushion upper surface.

2. Head Restraint Position

- ☐ N/A Vehicle contains automatic head restraints.
☐ N/A, there is no head restraint adjustment Go to 3
- ☒ 2.1 Adjust the head restraint to its lowest position. (S16.2.10.2, S20.1.9.6, S20.4.1, S22.1.7.6, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)
- ☒ 2.2 All adjustments of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible.
Mark the foremost position. (S16.2.10.2 & S16.3.4.4 & S20.1.9.6, S20.4.1, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)
- ☒ 2.3 Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and **mark** a horizontal plane through the midpoint of this distance. (S16.3.4.3)
Vertical height of head restraint: 210 mm
Mid-point height: 105 mm
- ☒ 3. Is the **steering wheel** adjustable up and down and/or in and out?
☒ Yes – go to 3.1
☐ No – Go to 4
- ☒ 3.1. Find and **mark** for future reference each up and down position. Label three of the positions with the following: H for highest, M for mid-position (if there is no mid-position, label the next lowest adjustment position), and L for lowest.
☐ N/A – steering wheel is not adjustable up and down
- ☒ 3.2. Find and **mark** for future references each in and out position. Label three of the Positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the next rearmost adjustment position), and R for rearmost.
☐ N/A – steering wheel is not adjustable in and out.
- ☒ 3.3. Use the markings to position the steering controls in the mid-position or if applicable next lowest detent position. (S16.2.9)
- ☒ 4. Place the SCRP in the full rearward, mid-height position, and mid-seat cushion angle, determined in Item 1. (S16.3.2.1.1)
- ☒ 5. If the vehicle has an adjustable accelerator pedal, place it in the full forward position. (S16.3.2.2.1)
☒ N/A accelerator pedal not adjustable
- ☒ 6. Fully recline the seat back. (S16.3.2.1.2)
☐ N/A seat back not adjustable.
- ☒ 7. Place the dummy in the seat with the legs at an angle of 120 degrees to the thighs. The calves should not be touching the seat cushion. (S16.3.2.1.2)
- ☒ 8. Position the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion markings as determined in Item 1.19 or 1.20. (S16.3.2.1.3 and S16.3.2.1.4)

- ☒ 9. Hold down the dummy's thighs and push rearward on the upper torso to maximize the pelvic angle. (S16.3.2.1.5)
- ☒ 10. Set the angle between the legs and the thighs to 120 degrees. (S16.3.2.1.6)
- ☒ 11. Set the transverse distance between the centers of the front of the knees at 160 to 170 mm. (6.3 to 6.7 inches) Center the knee separation with respect to the longitudinal seat cushion marking as determined in Item 1.19 or 1.20. (S16.3.2.1.6)
Record Knee Separation: 165 mm
- ☒ 12. Push rearward on the dummy's knees until the pelvis contacts the seat back, or the backs of the calves contact the seat cushion, whichever occurs first. (S16.3.2.1.6)
☒ Pelvis contacted seat back.
☐ Calves contacted seat cushion.
- ☒ 13. Gently rock the upper torso ± 5 degrees (approximately 51 mm (2 inches)) side-to-side three time. (S16.3.2.1.7)
- ☒ 14. If needed, extend the legs until the feet do not contact the floor pan. The thighs should be resting on the seat cushion. (S16.3.2.1.8)
- ☒ 15. Position the right foot until the foot is in line with a longitudinal vertical plane passing through the center of the accelerator pedal. Maintain the leg and thigh in a vertical plane. (S16.3.2.1.8)
- ☒ 16. Rotate the left leg and thigh laterally to equalize the distance between each knee and the longitudinal seat cushion marking as determined in Item 1.19 or 1.20. (S16.3.2.1.8)
- ☒ 17. Attempt to return the seat to the foremost fore-aft position, mid-height, and seat cushion mid-angle as determined in Item 1. The foot may contact and depress the accelerator and/or change the angle of the foot with respect to the leg. (S16.3.2.1.8)
☒ Foremost position achieved. Proceed to step 22.
☐ Foremost not achieved because of foot interference. Proceed to step 19.
☐ Foremost not achieved because of steering wheel contact.
- ☐ 18. If either of the dummy's legs contact the steering wheel, move the steering wheel up the minimum amount required to avoid contact. If the steering wheel is not adjustable separate the knees the minimum required to avoid contact. (S16.3.2.1.8)
☐ N/A- there was no leg contact
☐ Steering wheel repositioned
☐ Knees separated
- ☐ 19. If the left foot interferes with the clutch or brake pedals, rotate the left foot about the leg to provide clearance. If this is not sufficient, rotate the thigh outboard at the hip the minimum amount required for clearance. (S16.3.2.1.8)
☐ N/A, No foot interference with pedals.
☐ Foot adjusted to provide clearance.
☐ Foot and Thigh adjusted to provide clearance.

- ☐ 20. Continue to move the seat. Use seat controls to line up the seat markings determined during item 1 to set the foremost fore-aft position, mid-height position and the seat cushion mid-angle. If the dummy contacts the interior move the seat rearward until a maximum clearance of 5 mm (0.2 inches) is achieved or the seat is in the closest detent position that does not cause dummy contact. (S16.3.2.1.8)
☐ Foremost, mid-height position and the seat cushion mid-angle reached
☐ Dummy Contact. Clearance set at maximum of 5 mm
Measured Clearance: _____
☐ Dummy Contact. Seat set at nearest detent position.
Seat position _____ detent positions rearward of foremost
(foremost is position zero)
- ☐ 21. If the steering wheel was repositioned in step 18, return the steering wheel to the original position. If the steering wheel contacts the dummy before reaching the original position, position the wheel until a maximum clearance of 5 mm (.2 inches) is achieved, or the steering wheel is in the closest detent position that does not cause dummy contact. (S16.3.2.1.8)
☐ N/A Steering wheel was not repositioned.
☐ Original position achieved.
☐ Dummy Contact. Clearance set at maximum of 5 mm
Measured Clearance: _____
☐ Dummy Contact. Steering wheel set at nearest detent position.
Steering wheel position _____ detent positions upward of original position.
(Original position is position zero)
- ☒ 22. If the seat back is adjustable, rotate the seat back forward while holding the thighs in place. Continue rotating the seat back forward until the transverse instrument platform of the dummy head is level ± 0.5 degrees. If the head cannot be leveled using the seat back adjustment, or the seat back is not adjustable, use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, minimize the angle. (S16.3.2.1.9)
☒ Head Level Achieved. (Check all that apply)
☒ Head leveled using the adjustable seat back
☐ Head leveled using the neck bracket.
Head Angle: 0.2 degrees
☐ Head Level NOT Achieved. (Check all that apply)
☐ Head adjusted using the adjustable seat back
☐ Head adjusted using the neck bracket.
Head Angle: _____ degrees
- ☒ 23. Verify the pelvis is not interfering with the seat bight. (S16.3.2.1.9)
☒ No interference
☐ Pelvis moved forward the minimum amount so that it is not caught in the seat bight.
- ☒ 24. Verify the dummy abdomen is properly installed. (S16.3.2.1.9)
☒ Abdomen still seated properly into dummy
☐ Abdomen was adjusted because it was not seated properly into dummy

☒ 25. Head Angle

☒ N/A, neither the pelvis nor the abdomen were adjusted.

☒ 25.1 Head still level (Go to 26)

☐ 25.2 Head level adjusted

☐ Head Level Achieved. (Check all that apply)

☐ Head leveled using the adjustable seat back

☐ Head leveled using the neck bracket.

Head Angle: _____ degrees

☐ Head Level NOT Achieved. (Check all that apply)

☐ Head level adjusted using the adjustable seat back

☐ Head level adjusted using the neck bracket.

Head Angle: _____ degrees

☒ 26. If the dummy torso contacts the steering wheel while performing step 22, reposition the steering wheel in the following order to eliminate contact. (S16.3.2.1.9)

☒ N/A, No dummy torso contact with the steering wheel.

☐ 26.1 Adjust telescoping mechanism.

☐ N/A No telescoping adjustment.

☐ Adjustment performed (fill in appropriate change)

Steering wheel moved _____ detent positions in the forward direction.

Steering wheel moved _____ mm in the forward direction.

☐ 26.2 Adjust tilt mechanism.

☐ N/A No tilt adjustment.

☐ No adjustment performed.

☐ Adjustment performed. (circle one)

Steering wheel moved _____ detent positions Upward/Downward.

Steering wheel moved _____ degrees Upward/Downward

☐ 26.3 Adjust Seat in the aft direction.

☐ No Adjustment performed.

☐ Seat moved aft _____ mm from original position.

☐ Seat moved aft _____ detent positions from the original position.

☒ 27. Measure and set the pelvic angle using the pelvic angle gage TE-2504. The pelvic angle should be 20.0 degrees $\pm$ 2.5 degrees. If the pelvic angle cannot be set to the specified range because the head will not be level or because the dummy will have need major repositioning, adjust the pelvis as closely as possible to the angle range, but keep the head level. (S16.3.2.1.11)

☒ Pelvic angle set to 20.0 degrees $\pm$ 2.5 degrees.

☐ Pelvic angle of 20.0 degrees not achieved, the angular difference was minimized.

☒ Record the pelvic angle: 20.6 degrees

☒ 28. Check the dummy for contact with the interior after completing adjustments. (S16.3.2.1.12)

☒ No contact.

☐ Dummy in contact with interior.

☐ Seat moved aft _____ mm from the previous position.

☐ Seat moved aft _____ detent positions from the previous position.

- ☒ 29. Check the dummy to see if additional interior clearance is obtained, allowing the seat to be moved forward. (S16.3.2.1.12)
- ☒ N/A, Seat already at foremost position.
- ☐ Clearance unchanged. No adjustments required.
- ☐ Additional clearance available
- ☐ Seat moved Forward _____ mm from the previous position.
- ☐ Seat moved Forward _____ detent positions from the previous position.
- ☒ 30. Driver's foot positioning, right foot. Place the foot perpendicular to the leg and determine if the heel contacts the floor pan at any leg position. If the heel contacts the floor pan proceed to step 31 otherwise, proceed to step 32. (S16.3.2.2.1)
- ☒ 31. Perform the following steps until either all steps are completed, or the foot contacts the accelerator pedal. Step 31.6 shall be completed in all cases. (S16.3.2.2.1 (a))
- ☒ 31.1 With the rear of the heel contacting the floor pan, move the foot forward until pedal contact occurs or the foot is at the full forward position.
- ☐ 31.2 If the vehicle has an adjustable accelerator pedal, move the pedals rearward until pedal contact occurs or the pedals reach the full rearward position.
- ☐ 31.3 Extend the leg, allowing the heel to lose contact with the floor until the foot contacts the pedal. Do not raise the toe of the foot higher than the top of the accelerator pedal. If the foot does not contact the pedal, proceed to the next step. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)
- ☐ 31.4 Angle the foot to achieve contact between the foot and the pedal. If the foot does not contact the pedal, return the foot to the perpendicular orientation. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)
- ☐ 31.5 Align the centerline of the foot with the vertical-longitudinal plane passing through the center of the accelerator pedal. Place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)
- ☒ 31.6 Record foot position
- ☒ Pedal Contact achieved. Contact occurred at step 31.1.
- ☒ Heel contacts floor pan
- ☐ Heel set _____ mm from floor pan.
- ☐ Pedal Contact not achieved. Heel set _____ mm from the floor pan.




FIGURE G1

- ___ 32. Perform the following steps until either all steps are completed, or the foot contacts the accelerator pedal. Step 32.5 shall be completed in all cases.
- ___ 32.1 Extend the leg until the foot contacts the pedal. Do not raise the toe of the foot higher than the top of the accelerator pedal. If the foot does not contact the pedal, proceed to the next step. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.1 (b) & S16.3.2.2.3)
- ___ 32.2 If the vehicle has an adjustable accelerator pedal, move the pedals rearward until pedal contact occurs or the pedals reach the full rearward position. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.1 (b) & S16.3.2.2.3)
- ___ N/A No pedal adjustment
- ___ 32.3 Angle the foot to achieve contact between the foot and the pedal. If the foot does not contact the pedal, return the foot to the perpendicular orientation. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.2 & S16.3.2.2.3)
- ___ 32.4 Align the centerline of the foot in the same horizontal plane as the centerline of the accelerator pedal. Place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)
- ___ 32.5 Record foot position
- ___ Pedal Contact achieved. Contact occurred at step _____.
 ___ Heel set _____ mm from floor pan.
 ___ Pedal Contact not achieved. Heel set _____ mm from the floor pan.

X 33. Driver's foot positioning, left foot.

X 33.1 Place the foot perpendicular to the leg and determine if the heel contacts the floor pan at any leg position. If the heel contacts the floor pan proceed to step 33.2, otherwise position the leg as perpendicular to the thigh as possible with the foot parallel to the floor pan. (S16.2.2.6)

X 33.2 Place the foot on the toe board with the heel resting on the floor pan as close to the intersection of the floor pan and the toe board as possible. Adjust the angle of the foot if necessary to contact the toe board. If the foot will not contact the toe board, set the foot perpendicular to the leg, and set the heel on the floor pan as far forward as possible. Avoid contact with the brake pedal, clutch pedal, wheel well projection, and footrest. To avoid this contact use the following three manipulations in the order listed, with each subsequent option incorporating the previous, until contact is avoided: rotate the foot about the lower leg (abduction/adduction), plantar flex the foot, rotate the leg outboard about the hip. Movement should be the minimum amount necessary. If it is not possible to avoid all foot contact, give priority to avoiding brake or clutch pedal contact. (S16.2.2.4 & S16.2.2.5 & S16.2.2.7)

☐ No contact

☐ Foot rotated about the leg (abduction/adduction)

☒ Foot rotated about the leg, and foot plantar flexed

☐ Foot rotated about the leg, foot plantar flexed, and the leg rotated about the hip.

X 33.3 Record foot position.

☐ Heel does not contact floor pan.

☐ Heel on floor pan and foot on toe board.

☒ Heel on floor pan and foot not on toe board.

X 34. Driver arm/hand positioning.

X 34.1 Place the dummy's upper arms adjacent to the torso with the arm centerlines as close to a vertical longitudinal plane as possible. (S16.3.2.3.1)

X 34.2 Place the palms of the dummy in contact with the outer part of the steering wheel rim at its horizontal centerline with the thumbs over the steering wheel rim. (S16.3.2.3.2)

X 34.3 If it is not possible to position the thumbs inside the steering wheel rim at its horizontal centerline, then position them above and as close to the horizontal centerline of the steering wheel rim as possible. (S16.3.2.3.3)

X 34.4 Lightly tape the hands to the steering wheel rim so that if the hand of the test dummy is pushed upward by a force of not less than 9 N (2 lb) and not more than 22 N (5 lb), the tape releases the hand from the steering wheel rim. S16.3.2.3.4

X 35. Adjustable head restraints

☐ N/A, there is no head restraint adjustment

☐ 35.1 If the head restraint has an automatic adjustment, leave it where the system positions the restraint after the dummy is placed in the seat. (S16.3.4.1) Go to 36.

☐ 35.2 Adjust each head restraint vertically so that the mid-horizontal plane determined in Item 2 is aligned with the center of gravity (CG) of the dummy head. (S16.3.4.3)

☒ 35.3 If the above position is not attainable, move the vertical center of the head restraint to the closest detent below the center of the head CG. (S16.3.4.3)

☐ N/A midpoint position attained in previous step

☒ Headrest set at nearest detent below the head CG

☐ 35.4 If the head restraint has a fore and aft adjustment, place the restraint in the foremost position or until contact with the head is made, whichever occurs first. (S16.3.4.4)

☒ 36. Driver and passenger manual belt adjustment (for tests conducted with a belted dummy). (S16.3.5)

☒ N/A Dummies are unbelted for this test.

☐ 36.1 If an adjustable seat belt D-ring anchorage exists, place it in the manufacturer's design position for a 5th percentile adult female. (S16.3.5.1) **This information will be supplied by the COTR.**

Manufacturer's specified position: _____


Actual Position: _____

☐ 36.2 Place the Type 2 manual belt around the test dummy and fasten the latch. (S16.3.5.2)

☐ 36.3 Ensure that the dummy's head remains as level as possible. (S16.3.5.3)

☐ 36.4 Remove all slack from the lap belt. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this operation four times. Apply a 9 N (2 lbf) to 18 N (4 lbf) tension load to the lap belt. If the belt system is equipped with a tension-relieving device, introduce the maximum amount of slack into the upper torso belt that is recommended by the manufacturer. If the belt system is not equipped with a tension-relieving device, allow the excess webbing in the shoulder belt to be retracted by the retractive force of the retractor. (S16.3.5.4)

I certify that I have read and performed each instruction.

Signature: 

Date: 2/25/13

DATA SHEET 36 - APPENDIX G
DUMMY POSITIONING PROCEDURES
FOR 5th PERCENTILE FEMALE PASSENGER TEST DUMMY
CONFORMING TO SUBPART O OF PART 572

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Tim Bratz

NHTSA No.: C20130100
 Test Date: 2/25/13

IMPACT ANGLE:	Zero				
BELTED DUMMIES (YES/NO):	No				
TEST SPEED:	X	32 to 40 kmph		0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	X		5 th female		50 th male
PASSENGER DUMMY:	X		5 th female		50 th male

(Check this item ONLY if it applies to this vehicle.)

 The passenger seat adjustments are controlled by the adjustments made to the driver's seat. Therefore, positioning of the passenger dummy is made simultaneously with the driver dummy. Adjustments made to the seat to position the driver will over ride any adjustments that would normally be made to position the passenger. (S16.2.10.3)

1. Seat Position

X 1.1 Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions. (S16.2.10.1, S20.1.9.1, S20.4.1, S22.1.7.1)

X N/A – No lumbar adjustment

X 1.2 Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2, S20.1.9.2, S20.4.1, S22.1.7.1, S22.4.2.1, S22.4.3.1, S24.4.2.1, S26.2.3, S26.3.1)

X N/A – No additional support adjustment

X 1.3 Position an adjustable leg support system in its rearmost position. (8/27/04 interpretation to Toyota)

X N/A – No adjustable leg support system

X 1.4 **Mark** a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion. (S16.3.1.12)

X 1.5 Draw a line (seat cushion reference line) through the seat cushion reference point. (S16.3.1.13)

X 1.6 Use only the controls that primarily move the seat in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S22.1.7.3)

X 1.7 If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S20.1.9.3)

X N/A – No independent fore-aft seat cushion adjustment

- ☒ 1.8 Use any part of any control, other than the parts just used for fore-aft positioning, to determine the range of angles of the seat cushion reference line and to set the seat cushion reference line at the mid-angle. (S16.2.10.3.1)
Maximum angle: Fixed
Minimum angle: Fixed
Mid-angle: Fixed
- ☒ 1.9 If the seat and/or seat cushion height is adjustable, use any part of any control other than the parts which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-angle found in 1.8. (S16.2.10.3.1)
☒ N/A – No seat height adjustment
- ☒ 1.10 Use only the controls that primarily move the seat in the fore-aft direction to verify the seat is in the rearmost position.
- ☒ 1.11 Use only the controls that primarily move the seat in the fore-aft direction to **mark** the fore-aft seat positions. **Mark** each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and **mark** each detent. For power seats, **mark** only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost.
- ☒ 1.12 Use only the controls that primarily move the seat in the fore-aft direction to place the seat in the rearmost position.
- ☒ 1.13 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S22.4.3.1, S24.1.2, S24.3.1, S24.4.3.1, S26.2.3, S26.3.1)
☒ N/A – No seat height adjustment. Go to 1.18
- ☐ 1.14 Use only the controls that primarily move the seat and/or seat cushion in the fore-aft direction to place the seat in the mid-fore-aft position.
- ☐ 1.15 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- ☐ 1.16 Use only the controls that change the seat in the fore-aft direction to place the seat in the foremost position. (S16.2.10.3.2)
- ☐ 1.17 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S16.2.10.3.3, S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- ☒ 1.18. Is the seat a bucket seat?
☒ Yes, go to 1.19 and skip 1.20
☐ No, go to 1.20 and skip 1.19

X 1.19 Bucket seats:

Locate and **mark** for future reference the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S16.3.1.10 & S20.1.10)

 1.20 Bench seats:

Locate and **mark** the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S20.2.1.4, S22.2.1.3, S24.2.3, S20.4.4, S22.2.2.1 (b), S22.2.2.3 (b), S22.2.2.4 (a), S22.2.2.5 (a), S22.2.2.6 (a), S22.2.2.7 (a), S24.2.3 (a))

Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel. _____

Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. (The vertical plane through this longitudinal centerline is Plane B for suppression.) _____

2. Head Restraint Position

 N/A Vehicle contains automatic head restraints.

 N/A, there is no head restraint adjustment Go to 3

X 2.1 Adjust the head restraint to its lowest position. (S16.2.10.2, S20.1.9.6, S20.4.1, S22.1.7.6, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)

X 2.2 All adjustments of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. **Mark** the foremost position. (S16.2.10.2 & S16.3.4.4 & S20.1.9.6, S20.4.1, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)

X 2.3 Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and **mark** a horizontal plane through the midpoint of this distance. (S16.3.4.3)

Vertical height of head restraint: 210 mm

Mid-point height: 105 mm

X 3. Place the SCRIP in the full rearward, mid-height position, and mid-seat cushion angle. (S16.3.3.1.1)

X 4. Fully recline the seat back. (S16.3.3.1.2)

 N/A seat back not adjustable.

X 5. Place the dummy in the seat with the legs at an angle of 120 degrees to the thighs. The calves should not be touching the seat cushion. (S16.3.3.1.2)

X 6. Position the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion marking that was determined in item 1.19 or 1.20. (S16.3.3.1.3 and S16.3.3.1.4)

X 7. Hold down the dummy's thighs and push rearward on the upper torso to maximize the pelvic angle. (S16.3.3.1.5)

X 8. Set the angle between the legs and the thighs to 120 degrees. (S16.3.3.1.6)

- ☒ 9. Set the transverse distance between the centers of the front of the knees at 160 to 170 mm. (6.3 to 6.7 inches). Center the knee separation with respect to the longitudinal seat cushion marking that was determined in item 1.19 or 1.20. (S16.3.3.1.6)
Record Knee Separation: 167 mm
- ☒ 10. Push rearward on the dummy's knees until the pelvis contacts the seat back, or the backs of the calves contact the seat cushion, whichever occurs first. (S16.3.3.1.6)
☒ Pelvis contacted seat back.
☐ Calves contacted seat cushion.
- ☒ 11. Gently rock the upper torso ± 5 degrees (approximately 51 mm (2 inches)) side-to-side three times. (S16.3.3.1.7)
- ☒ 12. If needed, extend the legs until the feet do not contact the floor pan. The thighs should be resting on the seat cushion. (S16.3.3.1.8)
- ☒ 13. Use seat controls to line up the seat markings determined during the completion of item 1 to set the foremost fore-aft position, mid-height position and the seat cushion mid-angle. If the dummy contacts the interior move the seat rearward until a maximum clearance of 5 mm (0.2 inches) is achieved or the seat is in the closest detent position that does not cause dummy contact. (S16.3.3.1.8)
☒ Foremost, mid-height position and the seat cushion mid-angle reached
☐ Dummy Contact. Clearance set at maximum of 5 mm
Measured Clearance: _____
☐ Dummy Contact. Seat set at nearest detent position.
Seat position _____ detent positions rearward of foremost
(foremost is position zero)
- ☒ 14. If the seat back is adjustable, rotate the seat back forward while holding the thighs in place. Continue rotating the seat back forward until the transverse instrument platform of the dummy head is level ± 0.5 degrees. If head cannot be leveled using the seat back adjustment, or the seat back is not adjustable, use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, adjust the head as closely as possible to the ± 0.5 degree range. (S16.3.3.1.9 and S16.3.3.1.10)
(Check All That Apply)
☐ Seat back not adjustable
☐ Seat back not independent of driver side seat back
☒ Head Level Achieved. (Check all that apply)
☒ Head leveled using the adjustable seat back
☐ Head leveled using the neck bracket.
Head Angle: 0.1 degrees
☐ Head Level NOT Achieved. (Check all that apply)
☐ Head adjusted using the adjustable seat back
☐ Head adjusted using the neck bracket.
Head Angle: _____ degrees
- ☒ 15. Verify the pelvis is not interfering with the seat bight. (S16.3.3.1.9)
☒ No interference
☐ Pelvis moved forward the minimum amount so that it is not caught in the seat bight.
- ☒ 16. Verify the dummy abdomen is properly installed. (S16.3.3.1.9)
☒ Abdomen still seated properly into dummy
☐ Abdomen was adjusted because it was not seated properly into dummy

X 17. Head Angle

X N/A, neither the pelvis nor the abdomen were adjusted.

X 17.1 Head still level (Go to 18)

 17.2 Head level adjusted

 Head Level Achieved. (Check all that apply)

 Head leveled using the adjustable seat back

 Head leveled using the neck bracket.

Head Angle: degrees

 Head Level NOT Achieved. (Check all that apply)

 Head adjusted using the adjustable seat back

 Head adjusted using the neck bracket.

Head Angle: degrees

X 18. Measure and set the pelvic angle using the pelvic angle gage TE-2504. The pelvic angle should be 20.0 degrees $\pm$ 2.5 degrees. If the pelvic angle cannot be set to the specified range because the head will not be level or because the dummy will have need major repositioning, adjust the pelvis as closely as possible to the angle range, but keep the head level.

X Pelvic angle set to 20.0 degrees $\pm$ 2.5 degrees.

 Pelvic angle of 20.0 degrees not achieved, the angular difference was minimized.

X Record the pelvic angle: 19.9 degrees

X 19. Check the dummy for contact with the interior after completing adjustments.

X No contact.

 Dummy in contact with interior.

 Seat moved aft mm from the previous position.

 Seat moved aft detent positions from the previous position.

X 20. Verify the transverse instrument platform of the dummy head is level $\pm$ 0.5 degrees. Use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, minimize the angle. (S16.3.3.1.9, S16.3.3.1.10, and S16.3.3.1.11)

X Head Level Achieved

Head Angle: 0.1 degrees

 Head Level NOT Achieved.

Head Angle: degrees

X 21. Check the dummy to see if additional interior clearance is obtained, allowing the seat to be moved forward. (S16.3.3.1.12)

 N/A Bench Seat

X N/A Seat already at full forward position.

 Clearance unchanged. No adjustments required.

 Additional clearance available

 Seat moved Forward mm from the previous position.

 Seat moved Forward detent positions from the previous position.

 Seat moved Forward, Full Forward position reached.

X 22. Passenger foot positioning. (Indicate final position achieved) (S16.3.3.2)

 22.1 Place feet flat on the toe board; OR (S16.3.3.2.1)

X 22.2 If the feet cannot be placed flat on the toe board, set the feet perpendicular to the lower leg, and rest the heel as far forward on the floor pan as possible; OR (S16.3.3.2.2)

☐ 22.3 If the heels do not touch the floor pan, set the legs as perpendicular to the thighs as possible and set the feet parallel to the floor pan. (S16.3.3.2.2)

☒ 23. Passenger arm/hand positioning. (S16.3.3.3)

☒ 23.1 Place the dummy's upper arms adjacent to the torso with the arm centerlines as close to a vertical longitudinal plane as possible. (S16.3.3.3.1)

☒ 23.2 Place the palms of the dummy in contact with the outer part of the thighs (S16.3.3.3.2)

☒ 23.3 Place the little fingers in contact with the seat cushion. (S16.3.3.3.3)

☒ 24. Adjustable head restraints (S16.3.4)
☐ N/A, there is no head restraint adjustment

☐ 24.1 If the head restraint has an automatic adjustment, leave it where the system positions the restraint after the dummy is placed in the seat. (S16.3.4.1) Go to 25.

☐ 24.2 Adjust each head restraint vertically so that the horizontal plane determined in Item 2 is aligned with the center of gravity (CG) of the dummy head. (S16.3.4.3)

☒ 24.3 If the above position is not attainable, move the vertical center of the head restraint to the closest detent below the center of the head CG. (S16.3.4.3)

☐ N/A midpoint position attained in previous step

☒ Headrest set at nearest detent below the head CG

☐ 24.4 If the head restraint has a fore and aft adjustment, place the restraint in the foremost position or until contact with the head is made, whichever occurs first. (S16.3.4.4)

☒ 25. Manual belt adjustment (for tests conducted with a belted dummy) S16.3.5
☒ N/A, Unbelted test

☐ 25.1 If an adjustable seat belt D-ring anchorage exists, place it in the manufacturer's design position for a 5th percentile adult female. **This information will be supplied by the COTR.** (S16.3.5.1)

Manufacturer's specified position: _____

Actual Position: _____

☐ 25.2 Place the Type 2 manual belt around the test dummy and fasten the latch. (S16.3.5.2)

☐ 25.3 Ensure that the dummy's head remains as level as possible. (S16.3.5.3)

☐ 25.4 Remove all slack from the lap belt. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this operation four times. Apply a 9 N (2 lbf) to 18 N (4 lbf) tension load to the lap belt. If the belt system is equipped with a tension-relieving device, introduce the maximum amount of slack into the upper torso belt that is recommended by the manufacturer. If the belt system is not equipped with a tension-relieving device, allow the excess webbing in the shoulder belt to be retracted by the retractive force of the retractor. (S16.3.5.4)

I certify that I have read and performed each instruction.

Signature: Tim Brady


Date: 2/25/13

DATA SHEET 37 **DUMMY MEASUREMENTS**

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Tim Bratz

NHTSA No.: C20130100
 Test Date: 2/25/13


DUMMY MEASUREMENTS FOR FRONT SEAT OCCUPANTS



TEST DUMMY POSITION MEASUREMENTS

Code	Measurement Description	Driver SN 511		Passenger SN 507	
		Length (mm)	Angle (°)	Length (mm)	Angle (°)
WA	Windshield Angle		23.6		
SWA	Steering Wheel Angle		65.7		
SCA	Steering Column Angle		24.3		
SA	Seat Back Angle (On Headrest Post)		2.0		3.0
HZ	Head to Roof (Z)	263		230	
HH	Head to Header	347	31.5	341	39.0
HW	Head to Windshield	809	0	741	0
HR	Head to Side Header (Y)	266		245	
NR	Nose to Rim	293	6.6		
CD	Chest to Dash	465		468	
CS	Chest to Steering Hub	245	14.5		
RA	Rim to Abdomen	130	0		
KDL	Left Knee to Dash	155	18.3	124	
KDR	Right Knee to Dash	135		137	28.8
PA	Pelvic Angle		20.6		19.9
TA	Tibia Angle		44.4		48.6
KK	Knee to Knee (Y)	275		220	
SK	Striker to Knee	608	98.7	625	98.3
ST	Striker to Head	419	20.4	451	21.4
SH	Striker to H-Point	340	117.3	351	114.7
SHY	Striker to H-Point (Y)	285		275	
HS	Head to Side Window	355		352	
HD	H-Point to Door (Y)	192		178	
AD	Arm to Door (Y)	73		103	
AA	Ankle to Ankle	278		168	

SEAT BELT POSITIONING DATA



FRONT VIEW OF DUMMY

SEAT BELT POSITIONING MEASUREMENTS

Measurement Description	Units	Driver	Passenger
PBU - Top surface of reference to belt upper edge	mm	N/A	N/A
PBL - Top surface of reference to belt lower edge	mm	N/A	N/A

DATA SHEET 38

CRASH TEST

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Tim Bratz

NHTSA No.: C20130100
 Test Date: 2/25/13

IMPACT ANGLE:	Zero				
BELTED DUMMIES (YES/NO):	No				
TEST SPEED:	X	32 to 40 kmph		0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	X		5 th female		50 th male
PASSENGER DUMMY:	X		5 th female		50 th male

- ☒ 1. Vehicle underbody painted.
- ☒ 2. The speed measuring devices are in place and functioning.
- ☒ 3. The speed measuring devices are 1.0 m from the barrier (spec. 1.5 m) and 30 cm from the barrier (spec. is 30 cm).
- ☒ 4. Convertible top is in the closed position.
☒ N/A, not a convertible.
- ☒ 5. Instrumentation and wires are placed so motion of dummies during impact is not affected.
- ☒ 6. Tires inflated to pressure on tire placard or if it does not have a tire placard because it is not a passenger car, then inflated to the tire pressure specified in the owner information.

260 kpa front left tire 260 kpa specified on tire placard or in owner information
260 kpa front right tire 260 kpa specified on tire placard or in owner information
260 kpa rear left tire 260 kpa specified on tire placard or in owner information
260 kpa rear right tire 260 kpa specified on tire placard or in owner information

- ☒ 7. Time zero contacts on barrier in place.
- ☒ 8. Pre test zero and shunt calibration adjustments performed and recorded.
- ☒ 9. Dummy temperature meets requirements of section 12.2 of the test procedure.
- ☒ 10. Vehicle hood closed and latched.
- ☒ 11. Transmission placed in neutral.
- ☒ 12. Parking brake off.
- ☒ 13. Are the heads still level?
☒ Yes, go to 14
☐ No, Adjust dummy so that head is at the angle recorded in the Appendix F or G data sheets and then continue.
- ☒ 14. Ignition in the ON position.
- ☒ 15. Doors closed and latched but not locked.
- ☒ 16. Post test zero and shunt calibration checks performed and recorded.
- ☒ 17. Actual test speed 39.6 kmph
- ☒ 18. Vehicle rebound from the barrier 78 cm
- ☒ 19. Describe whether the doors open after the test and what method is used to open the doors.
☒ Left Front Door: Door remained closed and latched; Door opened without tools.
☒ Right Front Door: Door remained closed and latched; Door opened without tools.
☒ Left Rear Door: Door remained closed and latched; Door opened without tools.
☒ Right Rear Door: Door remained closed and latched; Door opened without tools.

- ☒ 20. Describe the contact points of the dummy with the interior of the vehicle.
- ☒ Driver Dummy: Head to Air Bag, Head to Head Rest, Chest to Air Bag; Knees to Knee Restraint.
- ☒ Passenger Dummy: Head to Air Bag, Head to Curtain Air Bag; Chest to Air Bag; Knees to Knee Restraint.

REMARKS:

Signature: Tim Bray

Date: 2/25/13

I certify that I have read and performed each instruction.

DATA SHEET 40

ACCIDENT INVESTIGATION MEASUREMENTS

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Chad Seebecker

NHTSA No.: C20130100
 Test Date: 2/25/13

IMPACT ANGLE:	Zero					
BELTED DUMMIES (YES/NO):	No					
TEST SPEED:	X	32 to 40 kmph		0 to 48 kmph		0 to 56 kmph
DRIVER DUMMY:	X		5 th female		50 th male	
PASSENGER DUMMY:	X		5 th female		50 th male	

Vehicle Year/Make/Model/Body Style:	2013 Chevrolet Sonic Passenger Car
VIN:	1G1JB5SH3D4147757
Wheelbase:	2530 mm
Build Date:	11/12
Vehicle Size Category:	2
Test Weight:	1390.3 kg
Front Overhang:	915 mm
Overall Width:	1690 mm
Overall Length Center:	4391 mm


Accelerometer Data	
Location:	As per measurements on Data Sheet 33
Linearity:	>99.9%

Integration Algorithm:	Trapezoidal
Vehicle Impact Speed:	39.6 kmph
Time of Separation:	100.1 ms
Velocity Change:	43.3 kmph

CRUSH PROFILE

Collision Deformation Classification: 12FDEW2
 Midpoint of Damage: Vehicle Longitudinal Centerline
 Damage Region Length (mm): 1120
 Impact Mode: Frontal Barrier

No.	Measurement Description	Units	Pre-Test	Post-Test	Difference
C1	Crush zone 1 at left side	mm	4245	4158	87
C2	Crush zone 2 at left side	mm	4336	4208	128
C3	Crush zone 3 at left side	mm	4370	4227	143
C4	Crush zone 4 at right side	mm	4370	4209	161
C5	Crush zone 5 at right side	mm	4336	4184	152
C6	Crush zone 6 at right side	mm	4245	4149	96



REMARKS:

Signature: 

Date: 2/25/13

I certify that I have read and performed each instruction.

DATA SHEET 41
WINDSHIELD MOUNTING (FMVSS 212)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Chad Seebecker

NHTSA No.: C20130100
 Test Date: 2/25/13

IMPACT ANGLE:	Zero				
BELTED DUMMIES (YES/NO):	No				
TEST SPEED:	☒	32 to 40 kmph	☐	0 to 48 kmph	☐ 0 to 56 kmph
DRIVER DUMMY:	☒ X		5 th female		50 th male
PASSENGER DUMMY:	☒ X		5 th female		50 th male

1. Pre-Crash
 - ☒ 1.1 Describe from visual inspection how the windshield is mounted and describe any trim material.


 Retained with glue
 Rubber and plastic trim
 - ☒ 1.2 Mark the longitudinal centerline of the windshield.
 - ☒ 1.3 Measure pre-crash A, B, and C for the left side and record in the chart below.
 - ☒ 1.4 Measure pre-crash C, D, and E for the right side and record in the chart below.
 - ☒ 1.5 Measure from the edge of the retainer or molding to the edge of the windshield.
 Dimension G (mm): 17 mm
2. Post Crash
 - ☒ 2.1 Can a single thickness of copier type paper (as small a piece as necessary) slide between the windshield and the vehicle body?
 - ☒ No - Pass. Skip to the table of measurements, complete it by repeating the pre-crash measurements in the post crash column, and calculate the retention percentage, which will be 100%.
 - ☐ Yes, go to 2.2
 - ☐ 2.2 Visibly mark the beginning and end of the portions of the periphery where the paper slides between the windshield and the vehicle body.
 - ☐ 2.3 Measure and record post-crash A, B, C, D, E, and F such that the measurements do not include any of the parts of the windshield where the paper slides between the windshield and the vehicle body.
 - ☐ 2.4 Calculate and record the percent retention for the right and left side of the windshield.
 - ☐ 2.5 Is total right side percent retention less than 75%?
 - ☐ Yes, Fail
 - ☐ No, Pass
 - ☐ 2.6 Is total left side percent retention less than 75%?
 - ☐ Yes, Fail
 - ☐ No, Pass

WINDSHIELD RETENTION MEASUREMENTS

	Dimension	Pre-Crash (mm)	Post-Crash (mm)	Percent Retention (Post-Test ÷ Pre-Crash)
Left Side	A	548	548	100%
	B	842	842	100%
	C	694	694	100%
	Total	2084	2084	100%
Right Side	D	548	548	100%
	E	842	842	100%
	F	694	694	100%
	Total	2084	2084	100%

Indicate area of mounting failure: NONE

FRONT VIEW OF WINDSHIELD



REMARKS:

Signature: 

Date: 2/25/13

I certify that I have read and performed each instruction.

DATA SHEET 42
WINDSHIELD ZONE INTRUSION (FMVSS 219)

Test Vehicle: 2013 Chevrolet Sonic
 Test Program: FMVSS 208 Compliance
 Test Technician: Chad Seebecker


NHTSA No.: C20130100
 Test Date: 2/25/13

IMPACT ANGLE:	Zero					
BELTED DUMMIES (YES/NO):	No					
TEST SPEED:	X	32 to 40 kmph		0 to 48 kmph		0 to 56 kmph
DRIVER DUMMY:	X		5 th female		50 th male	
PASSENGER DUMMY:	X		5 th female		50 th male	

This standard specifies limits for the displacement of vehicle components into the windshield area during a frontal barrier impact test at any speed up to and including 48 kmph.

- ☒ 1. Place a 165 mm diameter rigid sphere, with a mass of 6.8 kg on the instrument panel so that it is simultaneously touching the instrument panel and the windshield. (571.219 S6.1(a))
- ☒ 2. Roll the sphere from one side of the windshield to the other while marking on the windshield where the sphere contacts the windshield. (571.219 S6.1(b))
- ☒ 3. From the outermost contactable points on the windshield draw a horizontal line to the edges of the windshield. (571.219 S6.1(b))
- ☒ 4. Draw a line on the inner surface of the windshield that is 13 mm below the line determined in items 2 and 3.
- ☒ 5. After the crash test, record any points where a part of the exterior of the vehicle has marked, penetrated, or broken the windshield.

Provide all dimensions necessary to reproduce the protected area.



WINDSHIELD DIMENSIONS

Item	Units	Value
A	mm	1096
B	mm	524
C	mm	1388
D	mm	842
E	mm	532
F	mm	517

AREA OF PROTECTED ZONE FAILURES:

- B. Provide coordinates of the area that the protected zone was penetrated more than 0.25 inches by a vehicle component other than one which is normally in contact with the windshield.

X	Y
NONE	

- C. Provide coordinates of the area beneath the protected zone template that the inner surface of the windshield was penetrated by a vehicle component.

X	Y
NONE	

REMARKS:

I certify that I have read and performed each instruction.

Signature: 

Date: 2/25/13

DATA SHEET 43
FUEL SYSTEM INTEGRITY (FMVSS 301)

Test Vehicle: 2013 Chevrolet Sonic
Test Program: FMVSS 208 Compliance
Test Technician: Chad Seebecker

NHTSA No.: C20130100
Test Date: 2/25/13


TYPE OF IMPACT:	25 mph Unbelted
-----------------	-----------------

Stoddard Solvent Spillage Measurements

- A. From impact until vehicle motion ceases: 0.0 grams
(Maximum Allowable = 28 grams)
- B. For the 5 minute period after motion ceases: 0.0 grams
(Maximum Allowable = 142 grams)
- C. For the following 25 minutes: 0.0 grams
(Maximum Allowable = 28 grams/minute)
- D. Spillage: NONE

REMARKS: NO SPILLAGE

FMVSS 301 STATIC ROLLOVER DATA



1. The specified fixture rollover rate for each 90° of rotation is 60 to 180 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. Details of Stoddard Solvent spillage locations: **None**

Test Phase	Rotation Time (sec.)	Hold Time (sec.)	Spillage (grams)
0° to 90°	110	300	0.0
90° to 180°	111	300	0.0
180° to 270°	107	300	0.0
270° to 360°	152	300	0.0

APPENDIX A





CRASH TEST DATA




TABLE OF DATA PLOTS




		<u>Page No.</u>
Figure No. 1.	Driver Head X Acceleration vs. Time	A-1
Figure No. 2.	Driver Head Y Acceleration vs. Time	A-1
Figure No. 3.	Driver Head Z Acceleration vs. Time	A-1
Figure No. 4.	Driver Head Resultant Acceleration vs. Time	A-1
Figure No. 5.	Driver Head X Velocity vs. Time	A-2
Figure No. 6.	Driver Head Y Velocity vs. Time	A-2
Figure No. 7.	Driver Head Z Velocity vs. Time	A-2
Figure No. 8.	Driver Neck Force X vs. Time	A-3
Figure No. 9.	Driver Neck Force Y vs. Time	A-3
Figure No. 10.	Driver Neck Force Z vs. Time	A-3
Figure No. 11.	Driver Neck Force Resultant vs. Time	A-3
Figure No. 12.	Driver Neck Moment X vs. Time	A-4
Figure No. 13.	Driver Neck Moment Y vs. Time	A-4
Figure No. 14.	Driver Neck Moment Z vs. Time	A-4
Figure No. 15.	Driver Neck Moment Resultant vs. Time	A-4
Figure No. 16.	Driver Chest X Acceleration vs. Time	A-5
Figure No. 17.	Driver Chest Y Acceleration vs. Time	A-5
Figure No. 18.	Driver Chest Z Acceleration vs. Time	A-5
Figure No. 19.	Driver Chest Resultant Acceleration vs. Time	A-5
Figure No. 20.	Driver Chest X Velocity vs. Time	A-6
Figure No. 21.	Driver Chest Y Velocity vs. Time	A-6
Figure No. 22.	Driver Chest Z Velocity vs. Time	A-6
Figure No. 23.	Driver Chest Displacement vs. Time	A-6
Figure No. 24.	Driver Left Femur Force vs. Time	A-7
Figure No. 25.	Driver Right Femur Force vs. Time	A-7
Figure No. 26.	Passenger Head X Acceleration vs. Time	A-8
Figure No. 27.	Passenger Head Y Acceleration vs. Time	A-8
Figure No. 28.	Passenger Head Z Acceleration vs. Time	A-8
Figure No. 29.	Passenger Head Resultant Acceleration vs. Time	A-8
Figure No. 30.	Passenger Head X Velocity vs. Time	A-9





	<u>Page No.</u>
Figure No. 31. Passenger Head Y Velocity vs. Time	A-9
Figure No. 32. Passenger Head Z Velocity vs. Time	A-9
Figure No. 33. Passenger Neck Force X vs. Time	A-10
Figure No. 34. Passenger Neck Force Y vs. Time	A-10
Figure No. 35. Passenger Neck Force Z vs. Time	A-10
Figure No. 36. Passenger Neck Force Resultant vs. Time	A-10
Figure No. 37. Passenger Neck Moment X vs. Time	A-11
Figure No. 38. Passenger Neck Moment Y vs. Time	A-11
Figure No. 39. Passenger Neck Moment Z vs. Time	A-11
Figure No. 40. Passenger Neck Moment Resultant vs. Time	A-11
Figure No. 41. Passenger Chest X Acceleration vs. Time	A-12
Figure No. 42. Passenger Chest Y Acceleration vs. Time	A-12
Figure No. 43. Passenger Chest Z Acceleration vs. Time	A-12
Figure No. 44. Passenger Chest Resultant Acceleration vs. Time	A-12
Figure No. 45. Passenger Chest X Velocity vs. Time	A-13
Figure No. 46. Passenger Chest Y Velocity vs. Time	A-13
Figure No. 47. Passenger Chest Z Velocity vs. Time	A-13
Figure No. 48. Passenger Chest Displacement vs. Time	A-13
Figure No. 49. Passenger Left Femur Force vs. Time	A-14
Figure No. 50. Passenger Right Femur Force vs. Time	A-14
Figure No. 51. Driver Nij (N_{TF}) vs. Time	A-15
Figure No. 52. Driver Nij (N_{TE}) vs. Time	A-15
Figure No. 53. Driver Nij (N_{CF}) vs. Time	A-15
Figure No. 54. Driver Nij (N_{CE}) vs. Time	A-15
Figure No. 55. Passenger Nij (N_{TF}) vs. Time	A-16
Figure No. 56. Passenger Nij (N_{TE}) vs. Time	A-16
Figure No. 57. Passenger Nij (N_{CF}) vs. Time	A-16
Figure No. 58. Passenger Nij (N_{CE}) vs. Time	A-16
Figure No. 59. Driver Occipital Condyle Moment vs. Time	A-17
Figure No. 60. Passenger Occipital Condyle Moment vs. Time	A-17
Figure No. 61. Left Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 62. Left Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 63. Right Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 64. Right Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 65. Top of Engine X Acceleration vs. Time	A-19





		<u>Page No.</u>
Figure No. 66.	Top of Engine X Velocity vs. Time	A-19
Figure No. 67.	Bottom of Engine X Acceleration vs. Time	A-19
Figure No. 68.	Bottom of Engine X Velocity vs. Time	A-19
Figure No. 69.	Left Brake Caliper X Acceleration vs. Time	A-20
Figure No. 70.	Left Brake Caliper X Velocity vs. Time	A-20
Figure No. 71.	Right Brake Caliper X Acceleration vs. Time	A-20
Figure No. 72.	Right Brake Caliper X Velocity vs. Time	A-20
Figure No. 73.	Instrument Panel X Acceleration vs. Time	A-21
Figure No. 74.	Instrument Panel X Velocity vs. Time	A-21
Figure No. 75.	Trunk Z Acceleration vs. Time	A-21
Figure No. 76.	Trunk Z Velocity vs. Time	A-21


























PASSENGER HEAD X (G's) vs TIME (ms)




PASSENGER HEAD Y (G's) vs TIME (ms)










PASSENGER HEAD Z (G's) vs TIME (ms)










PASSENGER HEAD Resultant (G's) vs TIME (ms)


























































APPENDIX B

LOW RISK TEST DATA





TABLE OF DATA PLOTS

	<u>Page No.</u>
Figure No. 1. 5 th Fem. P1 Driver Head X Acceleration vs. Time	B-1
Figure No. 2. 5 th Fem. P1 Driver Head Y Acceleration vs. Time	B-1
Figure No. 3. 5 th Fem. P1 Driver Head Z Acceleration vs. Time	B-1
Figure No. 4. 5 th Fem. P1 Driver Head Resultant Acceleration vs. Time	B-1
Figure No. 5. 5 th Fem. P1 Driver Head X Velocity vs. Time	B-2
Figure No. 6. 5 th Fem. P1 Driver Head Y Velocity vs. Time	B-2
Figure No. 7. 5 th Fem. P1 Driver Head Z Velocity vs. Time	B-2
Figure No. 8. 5 th Fem. P1 Driver Neck Force X vs. Time	B-3
Figure No. 9. 5 th Fem. P1 Driver Neck Force Y vs. Time	B-3
Figure No. 10. 5 th Fem. P1 Driver Neck Force Z vs. Time	B-3
Figure No. 11. 5 th Fem. P1 Driver Neck Force Resultant vs. Time	B-3
Figure No. 12. 5 th Fem. P1 Driver Neck Moment X vs. Time	B-4
Figure No. 13. 5 th Fem. P1 Driver Neck Moment Y vs. Time	B-4
Figure No. 14. 5 th Fem. P1 Driver Neck Moment Z vs. Time	B-4
Figure No. 15. 5 th Fem. P1 Driver Occipital Condyle Moment vs. Time	B-4
Figure No. 16. 5 th Fem. P1 Driver Chest X Acceleration vs. Time	B-5
Figure No. 17. 5 th Fem. P1 Driver Chest Y Acceleration vs. Time	B-5
Figure No. 18. 5 th Fem. P1 Driver Chest Z Acceleration vs. Time	B-5
Figure No. 19. 5 th Fem. P1 Driver Chest Resultant Acceleration vs. Time	B-5
Figure No. 20. 5 th Fem. P1 Driver Chest X Velocity vs. Time	B-6
Figure No. 21. 5 th Fem. P1 Driver Chest Y Velocity vs. Time	B-6
Figure No. 22. 5 th Fem. P1 Driver Chest Z Velocity vs. Time	B-6
Figure No. 23. 5 th Fem. P1 Driver Chest Displacement vs. Time	B-6
Figure No. 24. 5 th Fem. P1 Driver Left Femur Force vs. Time	B-7
Figure No. 25. 5 th Fem. P1 Driver Right Femur Force vs. Time	B-7
Figure No. 26. Fire Voltage #1 vs. Time	B-8
Figure No. 27. Fire Current #1 vs. Time	B-8
Figure No. 28. Fire Voltage #2 vs. Time	B-8
Figure No. 29. Fire Current #2 vs. Time	B-8
Figure No. 30. 5 th Fem. P1 Driver Nij (N_{TF}) vs. Time	B-9
Figure No. 31. 5 th Fem. P1 Driver Nij (N_{TE}) vs. Time	B-9

Figure No. 32.	5 th Fem. P1 Driver Nij (N_{CF}) vs. Time	B-9
Figure No. 33.	5 th Fem. P1 Driver Nij (N_{CE}) vs. Time	B-9
Figure No. 34.	5 th Fem. P2 Driver Head X Acceleration vs. Time	B-10
Figure No. 35.	5 th Fem. P2 Driver Head Y Acceleration vs. Time	B-10
Figure No. 36.	5 th Fem. P2 Driver Head Z Acceleration vs. Time	B-10
Figure No. 37.	5 th Fem. P2 Driver Head Resultant Acceleration vs. Time	B-10
Figure No. 38.	5 th Fem. P2 Driver Head X Velocity vs. Time	B-11
Figure No. 39.	5 th Fem. P2 Driver Head Y Velocity vs. Time	B-11
Figure No. 40.	5 th Fem. P2 Driver Head Z Velocity vs. Time	B-11
Figure No. 41.	5 th Fem. P2 Driver Neck Force X vs. Time	B-12
Figure No. 42.	5 th Fem. P2 Driver Neck Force Y vs. Time	B-12
Figure No. 43.	5 th Fem. P2 Driver Neck Force Z vs. Time	B-12
Figure No. 44.	5 th Fem. P2 Driver Neck Force Resultant vs. Time	B-12
Figure No. 45.	5 th Fem. P2 Driver Neck Moment X vs. Time	B-13
Figure No. 46.	5 th Fem. P2 Driver Neck Moment Y vs. Time	B-13
Figure No. 47.	5 th Fem. P2 Driver Neck Moment Z vs. Time	B-13
Figure No. 48.	5 th Fem. P2 Driver Occipital Condyle Moment vs. Time	B-13
Figure No. 49.	5 th Fem. P2 Driver Chest X Acceleration vs. Time	B-14
Figure No. 50.	5 th Fem. P2 Driver Chest Y Acceleration vs. Time	B-14
Figure No. 51.	5 th Fem. P2 Driver Chest Z Acceleration vs. Time	B-14
Figure No. 52.	5 th Fem. P2 Driver Chest Resultant Acceleration vs. Time	B-14
Figure No. 53.	5 th Fem. P2 Driver Chest X Velocity vs. Time	B-15
Figure No. 54.	5 th Fem. P2 Driver Chest Y Velocity vs. Time	B-15
Figure No. 55.	5 th Fem. P2 Driver Chest Z Velocity vs. Time	B-15
Figure No. 56.	5 th Fem. P2 Driver Chest Displacement vs. Time	B-15
Figure No. 57.	5 th Fem. P2 Driver Left Femur Force vs. Time	B-16
Figure No. 58.	5 th Fem. P2 Driver Right Femur Force vs. Time	B-16
Figure No. 59.	Fire Voltage #1 vs. Time	B-17
Figure No. 60.	Fire Current #1 vs. Time	B-17
Figure No. 61.	Fire Voltage #2 vs. Time	B-17
Figure No. 62.	Fire Current #2 vs. Time	B-17
Figure No. 63.	5 th Fem. P2 Driver Nij (N_{TF}) vs. Time	B-18
Figure No. 64.	5 th Fem. P2 Driver Nij (N_{TE}) vs. Time	B-18
Figure No. 65.	5 th Fem. P2 Driver Nij (N_{CF}) vs. Time	B-18
Figure No. 66.	5 th Fem. P2 Driver Nij (N_{CE}) vs. Time	B-18






Injury Values Calculated between 0ms and 245ms









Injury Values Calculated between 0ms and 245ms






Injury Values Calculated between 0ms and 245ms






Injury Values Calculated between 0ms and 245ms


5TH FEM. DRIVER NECK MX (Nm) vs TIME (ms)




5TH FEM. DRIVER NECK MY (Nm) vs TIME (ms)



5TH FEM. DRIVER NECK MZ (Nm) vs TIME (ms)







Drv. Occipital Condyle Moment (Nm) vs TIME (ms)









Injury Values Calculated between 0ms and 245ms







Injury Values Calculated between 0ms and 245ms






Injury Values Calculated between 0ms and 245ms






Injury Values Calculated between 0ms and 245ms


FIRE VOLTAGE #1 (Volts) vs TIME (ms)




FIRE CURRENT #1 (Amps) vs TIME (ms)







FIRE VOLTAGE #2 (Volts) vs TIME (ms)



FIRE CURRENT #2 (Amps) vs TIME (ms)









Injury Values Calculated between 0ms and 245ms


5TH FEM. DRIVER HEAD X (G's) vs TIME (ms)




5TH FEM. DRIVER HEAD Y (G's) vs TIME (ms)



5TH FEM. DRIVER HEAD Z (G's) vs TIME (ms)






5TH FEM. DRIVER HEAD Resultant (G's) vs TIME (ms)









Injury Values Calculated between 0ms and 245ms






Injury Values Calculated between 0ms and 245ms






Injury Values Calculated between 0ms and 245ms

5TH FEM. DRIVER NECK MX (Nm) vs TIME (ms)




Max: 3.1 Nm
Tmax: 19.9 ms
Min: -1.1 Nm
Tmin: 80.8 ms
CFC 600

5TH FEM. DRIVER NECK MY (Nm) vs TIME (ms)




Max: 20.0 Nm
Tmax: 60.1 ms
Min: -23.3 Nm
Tmin: 17.2 ms
CFC 600

5TH FEM. DRIVER NECK MZ (Nm) vs TIME (ms)



Max: 0.3 Nm
Tmax: 5.0 ms
Min: -2.5 Nm
Tmin: 103.5 ms
CFC 600





Drv. Occipital Condyle Moment (Nm) vs TIME (ms)



Max: 22.8 Nm
Tmax: 59.5 ms
Min: -17.8 Nm
Tmin: 17.2 ms
CFC 600







Injury Values Calculated between 0ms and 245ms






Injury Values Calculated between 0ms and 245ms






Injury Values Calculated between 0ms and 245ms

5TH FEM. DRIVER LEFT FEMUR (N) vs TIME (ms)











5TH FEM. DRIVER RIGHT FEMUR (N) vs TIME (ms)





Injury Values Calculated between 0ms and 245ms





APPENDIX C
CRASH TEST PHOTOGRAPHS
TABLE OF PHOTOGRAPHS

	<u>Page No.</u>
Photo No. 1. Vehicle Certification Label	C-1
Photo No. 2. Tire Placard	C-2
Photo No. 3. Pre-Test Front View of Test Vehicle	C-3
Photo No. 4. Post-Test Front View of Test Vehicle	C-4
Photo No. 5. Pre-Test Left Side View of Test Vehicle	C-5
Photo No. 6. Post-Test Left Side View of Test Vehicle	C-6
Photo No. 7. Pre-Test Right Side View of Test Vehicle	C-7
Photo No. 8. Post-Test Right Side View of Test Vehicle	C-8
Photo No. 9. Pre-Test Left Front Three-Quarter View of Test Vehicle	C-9
Photo No. 10. Post-Test Left Front Three-Quarter View of Test Vehicle	C-10
Photo No. 11. Pre-Test Right Front Three-Quarter View of Test Vehicle	C-11
Photo No. 12. Post-Test Right Front Three-Quarter View of Test Vehicle	C-12
Photo No. 13. Pre-Test Right Rear Three-Quarter View of Test Vehicle	C-13
Photo No. 14. Post-Test Right Rear Three-Quarter View of Test Vehicle	C-14
Photo No. 15. Pre-Test Left Rear Three-Quarter View of Test Vehicle	C-15
Photo No. 16. Post-Test Left Rear Three-Quarter View of Test Vehicle	C-16
Photo No. 17. Pre-Test Rear View of Test Vehicle	C-17
Photo No. 18. Post-Test Rear View of Test Vehicle	C-18
Photo No. 19. Pre-Test Windshield View	C-19
Photo No. 20. Post-Test Windshield View	C-20
Photo No. 21. Pre-Test Engine Compartment View	C-21
Photo No. 22. Post-Test Engine Compartment View	C-22
Photo No. 23. Pre-Test Fuel Filler Cap View	C-23
Photo No. 24. Post-Test Fuel Filler Cap View	C-24
Photo No. 25. Pre-Test Front Underbody View	C-25
Photo No. 26. Post-Test Front Underbody View	C-26
Photo No. 27. Pre-Test Mid Underbody View	C-27
Photo No. 28. Post-Test Mid Underbody View	C-28
Photo No. 29. Pre-Test Mid Rear Underbody View	C-29
Photo No. 30. Post-Test Mid Rear Underbody View	C-30
Photo No. 31. Pre-Test Rear Underbody View	C-31
Photo No. 32. Post-Test Rear Underbody View	C-32

Page No.

Photo No. 33.	Pre-Test Driver Dummy Front View (head position)	C-33
Photo No. 34.	Post-Test Driver Dummy Front View (head position)	C-34
Photo No. 35.	Pre-Test Driver Dummy Position Left Side View	C-35
Photo No. 36.	Post-Test Driver Dummy Position Left Side View	C-36
Photo No. 37.	Pre-Test Driver Dummy Position Left Side View (door open)	C-37
Photo No. 38.	Post-Test Driver Dummy Position Left Side View (door open)	C-38
Photo No. 39.	Pre-Test Driver Dummy Seat Position	C-39
Photo No. 40.	Post-Test Driver Dummy Seat Position	C-40
Photo No. 41.	Pre-Test Driver Dummy Feet Position	C-41
Photo No. 42.	Post-Test Driver Dummy Feet Position	C-42
Photo No. 43.	Pre-Test Driver Side Knee Bolster View	C-43
Photo No. 44.	Post-Test Driver Side Knee Bolster View	C-44
Photo No. 45.	Post-Test Driver Dummy Airbag Contact	C-45
Photo No. 46.	Post-Test Driver Dummy Head Contact (headrest)	C-46
Photo No. 47.	Post-Test Driver Dummy Head Contact (headliner)	C-47
Photo No. 48.	Post-Test Driver Dummy Knee Contact (knee restraint)	C-48
Photo No. 49.	Post-Test Driver Dummy Knee Contact (knee bolster)	C-49
Photo No. 50.	Pre-Test Passenger Dummy Front View (head position)	C-50
Photo No. 51.	Post-Test Passenger Dummy Front View (head position)	C-51
Photo No. 52.	Pre-Test Passenger Dummy Position Right Side View	C-52
Photo No. 53.	Post-Test Passenger Dummy Position Right Side View	C-53
Photo No. 54.	Pre-Test Passenger Dummy Position Right Side View (door open)	C-54
Photo No. 55.	Post-Test Passenger Dummy Position Right Side View (door open)	C-55
Photo No. 56.	Pre-Test Passenger Dummy Seat Position	C-56
Photo No. 57.	Post-Test Passenger Dummy Seat Position	C-57
Photo No. 58.	Pre-Test Passenger Dummy Feet Position	C-58
Photo No. 59.	Post-Test Passenger Dummy Feet Position	C-59
Photo No. 60.	Pre-Test Passenger Side Knee Bolster View	C-60
Photo No. 61.	Post-Test Passenger Side Knee Bolster View	C-61
Photo No. 62.	Post-Test Passenger Dummy Airbag Contact	C-62
Photo No. 63.	Post-Test Passenger Dummy Head Contact (visor)	C-63
Photo No. 64.	Post-Test Passenger Dummy Head Contact (curtain airbag)	C-64
Photo No. 65.	Post-Test Passenger Dummy Head Contact (headliner)	C-65
Photo No. 66.	Post-Test Passenger Dummy Knee Contact (knee restraint)	C-66
Photo No. 67.	Rollover 90 Degrees	C-67
Photo No. 68.	Rollover 180 Degrees	C-68

Page No.

Photo No. 69. Rollover 270 Degrees
Photo No. 70. Rollover 360 Degrees
Photo No. 71. Temperature Plot

C-69

C-70

C-71



Vehicle Certification Label

 **TIRE AND LOADING INFORMATION**

SEATING CAPACITY TOTAL 5 FRONT 2 REAR 3

The combined weight of occupants and cargo should never exceed 406 kg or 895 lbs.

TIRE	ORIGINAL SIZE		COLD TIRE PRESSURE
FRONT	P195/65R15	H	260 kPa, 38 PSI
REAR	P195/65R15	H	260 kPa, 38 PSI
SPARE	T115/70R16	M	420 kPa, 60 PSI

SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION

1G1JB5SH3D4147757

C20130100

Tire Placard



Pre-Test Front View of Test Vehicle



Post-Test Front View of Test Vehicle



Pre-Test Left Side View of Test Vehicle



Post-Test Left Side View of Test Vehicle



Pre-Test Right Side View of Test Vehicle



Post-Test Right Side View of Test Vehicle



Pre-Test Left Front Three-Quarter View of Test Vehicle



Post-Test Left Front Three-Quarter View of Test Vehicle



Pre-Test Right Front Three-Quarter View of Test Vehicle



Post-Test Right Front Three-Quarter View of Test Vehicle



Pre-Test Right Rear Three-Quarter View of Test Vehicle



Post-Test Right Rear Three-Quarter View of Test Vehicle



Pre-Test Left Rear Three-Quarter View of Test Vehicle



Post-Test Left Rear Three-Quarter View of Test Vehicle



Pre-Test Rear View of Test Vehicle



Post-Test Rear View of Test Vehicle



Pre-Test Windshield View



Post-Test Windshield View



Pre-Test Engine Compartment View




Post-Test Engine Compartment View




Pre-Test Fuel Filler Cap View




Post-Test Fuel Filler Cap View



Pre-Test Front Underbody View




Post-Test Front Underbody View




Pre-Test Mid Underbody View



Post-Test Mid Underbody View




Pre-Test Mid Rear Underbody View



Post-Test Mid Rear Underbody View



Pre-Test Rear Underbody View



Post-Test Rear Underbody View



Pre-Test Driver Dummy Front View (head position)



Post-Test Driver Dummy Front View (head position)



Pre-Test Driver Dummy Position Left Side View



Post-Test Driver Dummy Position Left Side View



Pre-Test Driver Dummy Position Left Side View (door open)



Post-Test Driver Dummy Position Left Side View (door open)



Pre-Test Driver Dummy Seat Position



Post-Test Driver Dummy Seat Position



Pre-Test Driver Dummy Feet Position



Post-Test Driver Dummy Feet Position



Pre-Test Driver Side Knee Bolster View



Post-Test Driver Side Knee Bolster View



Post-Test Driver Dummy Airbag Contact



Post-Test Driver Dummy Head Contact (headrest)



Post-Test Driver Dummy Head Contact (headliner)



Post-Test Driver Dummy Knee Contact (knee restraint)



Post-Test Driver Dummy Knee Contact (knee bolster)



Pre-Test Passenger Dummy Front View (head position)



Post-Test Passenger Dummy Front View (head position)



Pre-Test Passenger Dummy Position Right Side View



Post-Test Passenger Dummy Position Right Side View



Pre-Test Passenger Dummy Position Right Side View (door open)



Post-Test Passenger Dummy Position Right Side View (door open)



Pre-Test Passenger Dummy Seat Position



Post-Test Passenger Dummy Seat Position



Pre-Test Passenger Dummy Feet Position



Post-Test Passenger Dummy Feet Position



Pre-Test Passenger Side Knee Bolster View



Post-Test Passenger Side Knee Bolster View



Post-Test Passenger Dummy Airbag Contact



Post-Test Passenger Dummy Head Contact (visor)



Post-Test Passenger Dummy Head Contact (curtain airbag)



Post-Test Passenger Dummy Head Contact (headliner)



Post-Test Passenger Dummy Knee Contact (knee restraint)



Rollover 90 Degrees



Rollover 180 Degrees




Rollover 270 Degrees



Rollover 360 Degrees

C-71



Temperature Plot

APPENDIX D

LOW RISK PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

		<u>Page No.</u>
Photo No. 1.	Pre-Test 5 th Fem. P1 Driver Dummy Left Side View	D-1
Photo No. 2.	Post-Test 5 th Fem. P1 Driver Dummy Left Side View	D-2
Photo No. 3.	Pre-Test 5 th Fem. P1 Driver Dummy Right Side View	D-3
Photo No. 4.	Post-Test 5 th Fem. P1 Driver Dummy Right Side View	D-4
Photo No. 5.	Post-Test 5 th Fem. P1 Driver Dummy Airbag Left Side View	D-5
Photo No. 6.	Post-Test 5 th Fem. P1 Driver Dummy Airbag Right Side View	D-6
Photo No. 7.	Post-Test 5 th Fem. P1 Driver Dummy Head Contact (headrest)	D-7
Photo No. 8.	Pre-Test 5 th Fem. P2 Driver Dummy Left Side View	D-8
Photo No. 9.	Post-Test 5 th Fem. P2 Driver Dummy Left Side View	D-9
Photo No. 10.	Pre-Test 5 th Fem. P2 Driver Dummy Right Side View	D-10
Photo No. 11.	Post-Test 5 th Fem. P2 Driver Dummy Right Side View	D-11
Photo No. 12.	Post-Test 5 th Fem. P2 Driver Dummy Airbag Left Side View	D-12
Photo No. 13.	Post-Test 5 th Fem. P2 Driver Dummy Head Contact (visor)	D-13



Pre-Test 5th Fem. P1 Driver Dummy Left Side View



Post-Test 5th Fem. P1 Driver Dummy Left Side View



Pre-Test 5th Fem. P1 Driver Dummy Right Side View

Post-Test 5th Fem. P1 Driver Dummy Right Side View



Post-Test 5th Fem. P1 Driver Dummy Airbag Left Side View



Post-Test 5th Fem. P1 Driver Dummy Airbag Right Side View



Post-Test 5th Fem. P1 Driver Dummy Head Contact (headrest)



Pre-Test 5th Fem. P2 Driver Dummy Left Side View



Post-Test 5th Fem. P2 Driver Dummy Left Side View



Pre-Test 5th Fem. P2 Driver Dummy Right Side View



Post-Test 5th Fem. P2 Driver Dummy Right Side View



Post-Test 5th Fem. P2 Driver Dummy Airbag Left Side View



Post-Test 5th Fem. P2 Driver Dummy Head Contact (visor)

APPENDIX E

SUPPRESSION PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

		<u>Page #</u>
Photo No. 1.	Angel Guard Angel Ride Car Bed Belted, Forward Seat Track	E-1
Photo No. 2.	Angel Guard Angel Ride Car Bed Belted, Middle Seat Track	E-1
Photo No. 3.	Angel Guard Angel Ride Car Bed Belted, Rearward Seat Track	E-1
Photo No. 4.	Unbelted 5 th Percentile Female Representative Reactivation, Rearward Seat Track	E-1
Photo No. 5.	Cosco Arriva W/Base, Belted, Rear Facing, Forward Seat Track	E-2
Photo No. 6.	Cosco Arriva W/Base, Belted, Rear Facing, Middle Seat Track	E-2
Photo No. 7.	Cosco Arriva W/Base, Belted, Rear Facing, Rearward Seat Track	E-2
Photo No. 8.	Cosco Arriva W/Base, Unbelted, Rear Facing, Forward Seat Track	E-2
Photo No. 9.	Cosco Arriva W/Base, Unbelted, Rear Facing, Middle Seat Track	E-3
Photo No. 10.	Cosco Arriva W/Base, Unbelted, Rear Facing, Rearward Seat Track	E-3
Photo No. 11.	Cosco Arriva W/Base, Unbelted, Forward Facing, Forward Seat Track	E-3
Photo No. 12.	Cosco Arriva W/Base, Unbelted, Forward Facing, Middle Seat Track	E-3
Photo No. 13.	Cosco Arriva W/Base, Unbelted, Forward Facing, Rearward Seat Track	E-4
Photo No. 14.	Cosco Arriva W/Out Base, Belted, Rear Facing, Forward Seat Track	E-4
Photo No. 15.	Cosco Arriva W/Out Base, Belted, Rear Facing, Middle Seat Track	E-4
Photo No. 16.	Cosco Arriva W/Out Base, Belted, Rear Facing, Rearward Seat Track	E-4
Photo No. 17.	Cosco Arriva W/Out Base, Unbelted, Rear Facing, Forward Seat Track	E-5
Photo No. 18.	Cosco Arriva W/Out Base, Unbelted, Rear Facing, Middle Seat Track	E-5
Photo No. 19.	Cosco Arriva W/Out Base, Unbelted, Rear Facing, Rearward Seat Track	E-5
Photo No. 20.	Cosco Arriva W/Out Base, Unbelted, Forward Facing, Forward Seat Track	E-5
Photo No. 21.	Cosco Arriva W/Out Base, Unbelted, Forward Facing, Middle Seat Track	E-6
Photo No. 22.	Cosco Arriva W/Out Base, Unbelted, Forward Facing, Rearward Seat Track	E-6
Photo No. 23.	Unbelted 5 th Percentile Female Representative Reactivation, Rearward Seat Track	E-6
Photo No. 24.	Graco Snugride W/Base, Belted, Rear Facing, Forward Seat Track	E-7
Photo No. 25.	Graco Snugride W/Base, Belted, Rear Facing, Middle Seat Track	E-7
Photo No. 26.	Graco Snugride W/Base, Belted, Rear Facing, Rearward Seat Track	E-7
Photo No. 27.	Graco Snugride W/Base, Unbelted, Rear Facing, Forward Seat Track	E-7
Photo No. 28.	Graco Snugride W/Base, Unbelted, Rear Facing, Middle Seat Track	E-8
Photo No. 29.	Graco Snugride W/Base, Unbelted, Rear Facing, Rearward Seat Track	E-8
Photo No. 30.	Graco Snugride W/Base, Unbelted, Forward Facing, Forward Seat Track	E-8
Photo No. 31.	Graco Snugride W/Base, Unbelted, Forward Facing, Middle Seat Track	E-8
Photo No. 32.	Graco Snugride W/Base, Unbelted, Forward Facing, Rearward Seat Track	E-9

		<u>Page #</u>
Photo No. 33.	Graco Snugride W/Out Base, Belted, Rear Facing, Forward Seat Track	E-9
Photo No. 34.	Graco Snugride W/Out Base, Belted, Rear Facing, Middle Seat Track	E-9
Photo No. 35.	Graco Snugride W/Out Base, Belted, Rear Facing, Rearward Seat Track	E-9
Photo No. 36.	Graco Snugride W/Out Base, Unbelted, Rear Facing, Forward Seat Track	E-10
Photo No. 37.	Graco Snugride W/Out Base, Unbelted, Rear Facing, Middle Seat Track	E-10
Photo No. 38.	Graco Snugride W/Out Base, Unbelted, Rear Facing, Rearward Seat Track	E-10
Photo No. 39.	Graco Snugride W/Out Base, Unbelted, Forward Facing, Forward Seat Track	E-10
Photo No. 40.	Graco Snugride W/Out Base, Unbelted, Forward Facing, Middle Seat Track	E-11
Photo No. 41.	Graco Snugride W/Out Base, Unbelted, Forward Facing, Rearward Seat Track	E-11
Photo No. 42.	Unbelted 5 th Percentile Female Representative Reactivation, Middle Seat Track	E-11
Photo No. 43.	Peg Perego Viaggio W/Base, Belted, Rear Facing, Forward Seat Track	E-12
Photo No. 44.	Peg Perego Viaggio W/Base, Belted, Rear Facing, Middle Seat Track	E-12
Photo No. 45.	Peg Perego Viaggio W/Base, Belted, Rear Facing, Rearward Seat Track	E-12
Photo No. 46.	Peg Perego Viaggio W/Base, Unbelted, Rear Facing, Forward Seat Track	E-12
Photo No. 47.	Peg Perego Viaggio W/Base, Unbelted, Rear Facing, Middle Seat Track	E-13
Photo No. 48.	Peg Perego Viaggio W/Base, Unbelted, Rear Facing, Rearward Seat Track	E-13
Photo No. 49.	Peg Perego Viaggio W/Base, Unbelted, Forward Facing, Forward Seat Track	E-13
Photo No. 50.	Peg Perego Viaggio W/Base, Unbelted, Forward Facing, Middle Seat Track	E-13
Photo No. 51.	Peg Perego Viaggio W/Base, Unbelted, Forward Facing, Rearward Seat Track	E-14
Photo No. 52.	Peg Perego Viaggio W/Out Base, Belted, Rear Facing, Forward Seat Track	E-14
Photo No. 53.	Peg Perego Viaggio W/Out Base, Belted, Rear Facing, Middle Seat Track	E-14
Photo No. 54.	Peg Perego Viaggio W/Out Base, Belted, Rear Facing, Rearward Seat Track	E-14
Photo No. 55.	Peg Perego Viaggio W/Out Base, Unbelted, Rear Facing, Forward Seat Track	E-15
Photo No. 56.	Peg Perego Viaggio W/Out Base, Unbelted, Rear Facing, Middle Seat Track	E-15
Photo No. 57.	Peg Perego Viaggio W/Out Base, Unbelted, Rear Facing, Rearward Seat Track	E-15
Photo No. 58.	Peg Perego Viaggio W/Out Base, Unbelted, Forward Facing, Forward Seat Track	E-15
Photo No. 59.	Peg Perego Viaggio W/Out Base, Unbelted, Forward Facing, Middle Seat Track	E-16
Photo No. 60.	Peg Perego Viaggio W/Out Base, Unbelted, Forward Facing, Rearward Seat Track	E-16
Photo No. 61.	Unbelted 5 th Percentile Female Representative Reactivation, Forward Seat Track	E-16
Photo No. 62.	Britax Roundabout Forward Facing Belted, Forward Seat Track	E-17
Photo No. 63.	Britax Roundabout Forward Facing Belted, Middle Seat Track	E-17
Photo No. 64.	Britax Roundabout Forward Facing Belted, Rearward Seat Track	E-17
Photo No. 65.	Britax Roundabout Forward Facing Unbelted, Forward Seat Track	E-17
Photo No. 66.	Britax Roundabout Forward Facing Unbelted, Middle Seat Track	E-18
Photo No. 67.	Britax Roundabout Forward Facing Unbelted, Rearward Seat Track	E-18
Photo No. 68.	Britax Roundabout Rear Facing Belted, Forward Seat Track	E-18
Photo No. 69.	Britax Roundabout Rear Facing Belted, Middle Seat Track	E-18

		<u>Page #</u>
Photo No. 70.	Britax Roundabout Rear Facing Belted, Rearward Seat Track	E-19
Photo No. 71.	Britax Roundabout Rear Facing Unbelted, Forward Seat Track	E-19
Photo No. 72.	Britax Roundabout Rear Facing Unbelted, Middle Seat Track	E-19
Photo No. 73.	Britax Roundabout Rear Facing Unbelted, Rearward Seat Track	E-19
Photo No. 74.	Unbelted 5 th Percentile Female Representative Reactivation, Rearward Seat Track	E-20
Photo No. 75.	Cosco High Back Booster Forward Facing Belted, Forward Seat Track	E-21
Photo No. 76.	Cosco High Back Booster Forward Facing Belted, Middle Seat Track	E-21
Photo No. 77.	Cosco High Back Booster Forward Facing Belted, Rearward Seat Track	E-21
Photo No. 78.	Cosco High Back Booster Forward Facing Unbelted, Forward Seat Track	E-21
Photo No. 79.	Cosco High Back Booster Forward Facing Unbelted, Middle Seat Track	E-22
Photo No. 80.	Cosco High Back Booster Forward Facing Unbelted, Rearward Seat Track	E-22
Photo No. 81.	Cosco High Back Booster Rear Facing Unbelted, Forward Seat Track	E-22
Photo No. 82.	Cosco High Back Booster Rear Facing Unbelted, Middle Seat Track	E-22
Photo No. 83.	Cosco High Back Booster Rear Facing Unbelted, Rearward Seat Track	E-23
Photo No. 84.	Unbelted 5 th Percentile Female Representative Reactivation, Middle Seat Track	E-23
Photo No. 85.	Evenflo Generations Forward Facing Belted, Forward Seat Track	E-24
Photo No. 86.	Evenflo Generations Forward Facing Belted, Middle Seat Track	E-24
Photo No. 87.	Evenflo Generations Forward Facing Belted, Rearward Seat Track	E-24
Photo No. 88.	Evenflo Generations Forward Facing Unbelted, Forward Seat Track	E-24
Photo No. 89.	Evenflo Generations Forward Facing Unbelted, Middle Seat Track	E-25
Photo No. 90.	Evenflo Generations Forward Facing Unbelted, Rearward Seat Track	E-25
Photo No. 91.	Evenflo Generations Rear Facing Unbelted, Forward Seat Track	E-25
Photo No. 92.	Evenflo Generations Rear Facing Unbelted, Middle Seat Track	E-25
Photo No. 93.	Evenflo Generations Rear Facing Unbelted, Rearward Seat Track	E-26
Photo No. 94.	Unbelted 5 th Percentile Female Representative Reactivation, Forward Seat Track	E-26
Photo No. 95.	Graco Comfortsport Forward Facing Belted, Forward Seat Track	E-27
Photo No. 96.	Graco Comfortsport Forward Facing Belted, Middle Seat Track	E-27
Photo No. 97.	Graco Comfortsport Forward Facing Belted, Rearward Seat Track	E-27
Photo No. 98.	Graco Comfortsport Forward Facing Unbelted, Forward Seat Track	E-27
Photo No. 99.	Graco Comfortsport Forward Facing Unbelted, Middle Seat Track	E-28
Photo No. 100.	Graco Comfortsport Forward Facing Unbelted, Rearward Seat Track	E-28
Photo No. 101.	Graco Comfortsport Rear Facing Belted, Forward Seat Track	E-28
Photo No. 102.	Graco Comfortsport Rear Facing Belted, Middle Seat Track	E-28
Photo No. 103.	Graco Comfortsport Rear Facing Belted, Rearward Seat Track	E-29
Photo No. 104.	Graco Comfortsport Rear Facing Unbelted, Forward Seat Track	E-29
Photo No. 105.	Graco Comfortsport Rear Facing Unbelted, Middle Seat Track	E-29
Photo No. 106.	Graco Comfortsport Rear Facing Unbelted, Rearward Seat Track	E-29

	<u>Page #</u>
Photo No. 107. Unbelted 5 th Percentile Female Representative Reactivation, Rearward Seat Track	E-30
Photo No. 108. 3-Year-Old Forward Facing Britax Roundabout Belted, Forward Seat Track	E-31
Photo No. 109. 3-Year-Old Forward Facing Britax Roundabout Belted, Middle Seat Track	E-31
Photo No. 110. 3-Year-Old Forward Facing Britax Roundabout Belted, Rearward Seat Track	E-31
Photo No. 111. Unbelted 5 th Percentile Female Representative Reactivation, Rearward Seat Track	E-31
Photo No. 112. 3-Year-Old Forward Facing Cosco High Back Booster Belted, Forward Seat Track	E-32
Photo No. 113. 3-Year-Old Forward Facing Cosco High Back Booster Belted, Middle Seat Track	E-32
Photo No. 114. 3-Year-Old Forward Facing Cosco High Back Booster Belted, Rearward Seat Track	E-32
Photo No. 115. 3-Year-Old Forward Facing Cosco High Back Booster Cinched With Harness, Forward Seat Track	E-32
Photo No. 116. 3-Year-Old Forward Facing Cosco High Back Booster Cinched With Harness, Middle Seat Track	E-33
Photo No. 117. 3-Year-Old Forward Facing Cosco High Back Booster Cinched With Harness, Rearward Seat Track	E-33
Photo No. 118. Unbelted 5 th Percentile Female Representative Reactivation, Middle Seat Track	E-33
Photo No. 119. 3-Year-Old Forward Facing Evenflo Generations Belted, Forward Seat Track	E-34
Photo No. 120. 3-Year-Old Forward Facing Evenflo Generations Belted, Middle Seat Track	E-34
Photo No. 121. 3-Year-Old Forward Facing Evenflo Generations Belted, Rearward Seat Track	E-34
Photo No. 122. 3-Year-Old Forward Facing Evenflo Generations Cinched With Harness, Forward Seat Track	E-34
Photo No. 123. 3-Year-Old Forward Facing Evenflo Generations Cinched With Harness, Middle Seat Track	E-35
Photo No. 124. 3-Year-Old Forward Facing Evenflo Generations Cinched With Harness, Rearward Seat Track	E-35
Photo No. 125. Unbelted 5 th Percentile Female Representative Reactivation, Forward Seat Track	E-35
Photo No. 126. 3-Year-Old Forward Facing Graco Comfortsport Belted, Forward Seat Track	E-36
Photo No. 127. 3-Year-Old Forward Facing Graco Comfortsport Belted, Middle Seat Track	E-36
Photo No. 128. 3-Year-Old Forward Facing Graco Comfortsport Belted, Rearward Seat Track	E-36
Photo No. 129. Unbelted 5 th Percentile Female Representative Reactivation, Rearward Seat Track	E-36
Photo No. 130. 3-Year-Old Cosco Summit Deluxe Belted, Forward Seat Track	E-37
Photo No. 131. 3-Year-Old Cosco Summit Deluxe Belted, Middle Seat Track	E-37
Photo No. 132. 3-Year-Old Cosco Summit Deluxe Belted, Rearward Seat Track	E-37
Photo No. 133. 3-Year-Old Cosco Summit Deluxe Cinched With Harness, Forward Seat Track	E-37
Photo No. 134. 3-Year-Old Cosco Summit Deluxe Cinched With Harness, Middle Seat Track	E-38
Photo No. 135. 3-Year-Old Cosco Summit Deluxe Cinched With Harness, Rearward Seat Track	E-38
Photo No. 136. Unbelted 5 th Percentile Female Representative Reactivation, Rearward Seat Track	E-38
Photo No. 137. 3-Year-Old Graco Platinum Cargo Belted, Forward Seat Track	E-39
Photo No. 138. 3-Year-Old Graco Platinum Cargo Belted, Middle Seat Track	E-39
Photo No. 139. 3-Year-Old Graco Platinum Cargo Belted, Rearward Seat Track	E-39
Photo No. 140. 3-Year-Old Graco Platinum Cargo Cinched With Harness, Forward Seat Track	E-39
Photo No. 141. 3-Year-Old Graco Platinum Cargo Cinched With Harness, Middle Seat Track	E-40
Photo No. 142. 3-Year-Old Graco Platinum Cargo Cinched With Harness, Rearward Seat Track	E-40
Photo No. 143. Unbelted 5 th Percentile Female Representative Reactivation, Forward Seat Track	E-40

		Page #
Photo No. 144.	6-Year-Old Cosco Summit Deluxe Belted, Forward Seat Track	E-41
Photo No. 145.	6-Year-Old Cosco Summit Deluxe Belted, Middle Seat Track	E-41
Photo No. 146.	6-Year-Old Cosco Summit Deluxe Belted, Rearward Seat Track	E-41
Photo No. 147.	Unbelted 5 th Percentile Female Representative Reactivation, Middle Seat Track	E-41
Photo No. 148.	6-Year-Old Graco Platinum Cargo Belted, Forward Seat Track	E-42
Photo No. 149.	6-Year-Old Graco Platinum Cargo Belted, Middle Seat Track	E-42
Photo No. 150.	6-Year-Old Graco Platinum Cargo Belted, Rearward Seat Track	E-42
Photo No. 151.	Unbelted 5 th Percentile Female Representative Reactivation, Forward Seat Track	E-42
Photo No. 152.	3-Year-Old Unbelted, Forward Seat Track, Position 1	E-43
Photo No. 153.	3-Year-Old Unbelted, Forward Seat Track, Position 2	E-43
Photo No. 154.	3-Year-Old Unbelted, Forward Seat Track, Position 3	E-43
Photo No. 155.	3-Year-Old Unbelted, Forward Seat Track, Position 4	E-43
Photo No. 156.	3-Year-Old Unbelted, Forward Seat Track, Position 5	E-44
Photo No. 157.	3-Year-Old Unbelted, Forward Seat Track, Position 6	E-44
Photo No. 158.	3-Year-Old Unbelted, Forward Seat Track, Position 7	E-44
Photo No. 159.	3-Year-Old Unbelted, Middle Seat Track, Position 1	E-44
Photo No. 160.	3-Year-Old Unbelted, Middle Seat Track, Position 2	E-45
Photo No. 161.	3-Year-Old Unbelted, Middle Seat Track, Position 3	E-45
Photo No. 162.	3-Year-Old Unbelted, Middle Seat Track, Position 4	E-45
Photo No. 163.	3-Year-Old Unbelted, Middle Seat Track, Position 5	E-45
Photo No. 164.	3-Year-Old Unbelted, Middle Seat Track, Position 6	E-46
Photo No. 165.	3-Year-Old Unbelted, Middle Seat Track, Position 7	E-46
Photo No. 166.	3-Year-Old Unbelted, Rearward Seat Track, Position 1	E-46
Photo No. 167.	3-Year-Old Unbelted, Rearward Seat Track, Position 2	E-46
Photo No. 168.	3-Year-Old Unbelted, Rearward Seat Track, Position 3	E-47
Photo No. 169.	3-Year-Old Unbelted, Rearward Seat Track, Position 4	E-47
Photo No. 170.	3-Year-Old Unbelted, Rearward Seat Track, Position 5	E-47
Photo No. 171.	3-Year-Old Unbelted, Rearward Seat Track, Position 6	E-47
Photo No. 172.	3-Year-Old Unbelted, Rearward Seat Track, Position 7	E-48
Photo No. 173.	Unbelted 5 th Percentile Female Representative Reactivation, Forward Seat Track	E-48
Photo No. 174.	6-Year-Old Unbelted, Forward Seat Track, Position 1	E-49
Photo No. 175.	6-Year-Old Unbelted, Forward Seat Track, Position 2	E-49
Photo No. 176.	6-Year-Old Unbelted, Forward Seat Track, Position 3	E-49
Photo No. 177.	6-Year-Old Unbelted, Forward Seat Track, Position 4	E-49
Photo No. 178.	6-Year-Old Unbelted, Middle Seat Track, Position 1	E-50
Photo No. 179.	6-Year-Old Unbelted, Middle Seat Track, Position 2	E-50
Photo No. 180.	6-Year-Old Unbelted, Middle Seat Track, Position 3	E-50

		<u>Page #</u>
Photo No. 181.	6-Year-Old Unbelted, Middle Seat Track, Position 4	E-50
Photo No. 182.	6-Year-Old Unbelted, Rearward Seat Track, Position 1	E-51
Photo No. 183.	6-Year-Old Unbelted, Rearward Seat Track, Position 2	E-51
Photo No. 184.	6-Year-Old Unbelted, Rearward Seat Track, Position 3	E-51
Photo No. 185.	6-Year-Old Unbelted, Rearward Seat Track, Position 4	E-51
Photo No. 186.	Unbelted 5 th Percentile Female Representative Reactivation, Middle Seat Track	E-52

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
Newborn

Car Bed



Angel Guard Angel Ride Car Bed Belted, Forward Seat Track



Angel Guard Angel Ride Car Bed Belted, Middle Seat Track



Angel Guard Angel Ride Car Bed Belted, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Rearward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section B

Rear Facing CRS



Cosco Arriva WBase, Belted, Rear Facing, Forward Seat Track



Cosco Arriva WBase, Belted, Rear Facing, Middle Seat Track



Cosco Arriva WBase, Belted, Rear Facing, Rearward Seat Track



Cosco Arriva WBase, Unbelted, Rear Facing, Forward Seat Track



Cosco Arriva WBase, Unbelted, Rear Facing, Middle Seat Track



Cosco Arriva WBase, Unbelted, Rear Facing, Rearward Seat Track



Cosco Arriva WBase, Unbelted, Forward Facing, Forward Seat Track



Cosco Arriva WBase, Unbelted, Forward Facing, Middle Seat Track



Cosco Arriva WBase, Unbelted, Forward Facing, Rearward Seat Track



Cosco Arriva WOut Base, Belted, Rear Facing, Forward Seat Track



Cosco Arriva WOut Base, Belted, Rear Facing, Middle Seat Track



Cosco Arriva WOut Base, Belted, Rear Facing, Rearward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section B

Rear Facing CRS



Cosco Arriva WOut Base, Unbelted, Rear Facing, Forward Seat Track



Cosco Arriva WOut Base, Unbelted, Rear Facing, Middle Seat Track



Cosco Arriva WOut Base, Unbelted, Rear Facing, Rearward Seat Track



Cosco Arriva WOut Base, Unbelted, Forward Facing, Forward Seat Track



Cosco Arriva WOut Base, Unbelted, Forward Facing, Middle Seat Track



Cosco Arriva WOut Base, Unbelted, Forward Facing, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Rearward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section B

Rear Facing CRS



Graco Snugride WBase, Belted, Rear Facing, Forward Seat Track



Graco Snugride WBase, Belted, Rear Facing, Middle Seat Track



Graco Snugride WBase, Belted, Rear Facing, Rearward Seat Track



Graco Snugride WBase, Unbelted, Rear Facing, Forward Seat Track



Graco Snugride WBase, Unbelted, Rear Facing, Middle Seat Track



Graco Snugride WBase, Unbelted, Rear Facing, Rearward Seat Track



Graco Snugride WBase, Unbelted, Forward Facing, Forward Seat Track



Graco Snugride WBase, Unbelted, Forward Facing, Middle Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section B

Rear Facing CRS



Graco Snugride WBase, Unbelted, Forward Facing, Rearward Seat Track



Graco Snugride WOut Base, Belted, Rear Facing, Forward Seat Track



Graco Snugride WOut Base, Belted, Rear Facing, Middle Seat Track



Graco Snugride WOut Base, Belted, Rear Facing, Rearward Seat Track



Graco Snugride WOut Base, Unbelted, Rear Facing, Forward Seat Track



Graco Snugride WOut Base, Unbelted, Rear Facing, Middle Seat Track



Graco Snugride WOut Base, Unbelted, Rear Facing, Rearward Seat Track



Graco Snugride WOut Base, Unbelted, Forward Facing, Forward Seat Track



Graco Snugride WOut Base, Unbelted, Forward Facing, Middle Seat Track



Graco Snugride WOut Base, Unbelted, Forward Facing, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Middle Seat Track



Peg Perego Viaggio WBase, Belted, Rear Facing, Forward Seat Track



Peg Perego Viaggio WBase, Belted, Rear Facing, Middle Seat Track



Peg Perego Viaggio WBase, Belted, Rear Facing, Rearward Seat Track



Peg Perego Viaggio WBase, Unbelted, Rear Facing, Forward Seat Track



Peg Perego Viaggio WBase, Unbelted, Rear Facing, Middle Seat Track



Peg Perego Viaggio WBase, Unbelted, Rear Facing, Rearward Seat Track



Peg Perego Viaggio WBase, Unbelted, Forward Facing, Forward Seat Track



Peg Perego Viaggio WBase, Unbelted, Forward Facing, Middle Seat Track



Peg Perego Viaggio WBase, Unbelted, Forward Facing, Rearward Seat Track



Peg Perego Viaggio WOut Base, Belted, Rear Facing, Forward Seat Track



Peg Perego Viaggio WOut Base, Belted, Rear Facing, Middle Seat Track



Peg Perego Viaggio WOut Base, Belted, Rear Facing, Rearward Seat Track



Peg Perego Viaggio WOut Base, Unbelted, Rear Facing, Forward Seat Track



Peg Perego Viaggio WOut Base, Unbelted, Rear Facing, Middle Seat Track



Peg Perego Viaggio WOut Base, Unbelted, Rear Facing, Rearward Seat Track



Peg Perego Viaggio WOut Base, Unbelted, Forward Facing, Forward Seat Track



Peg Perego Viaggio WOut Base, Unbelted, Forward Facing, Middle Seat Track



Peg Perego Viaggio WOut Base, Unbelted, Forward Facing, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Britax Roundabout Forward Facing Belted, Forward Seat Track



Britax Roundabout Forward Facing Belted, Middle Seat Track



Britax Roundabout Forward Facing Belted, Rearward Seat Track



Britax Roundabout Forward Facing Unbelted, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Britax Roundabout Forward Facing Unbelted, Middle Seat Track



Britax Roundabout Forward Facing Unbelted, Rearward Seat Track



Britax Roundabout Rear Facing Belted, Forward Seat Track



Britax Roundabout Rear Facing Belted, Middle Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Britax Roundabout Rear Facing Belted, Rearward Seat Track



Britax Roundabout Rear Facing Unbelted, Forward Seat Track



Britax Roundabout Rear Facing Unbelted, Middle Seat Track



Britax Roundabout Rear Facing Unbelted, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Rearward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Cosco High Back Booster Forward Facing Belted, Forward Seat Track



Cosco High Back Booster Forward Facing Belted, Middle Seat Track



Cosco High Back Booster Forward Facing Belted, Rearward Seat Track



Cosco High Back Booster Forward Facing Unbelted, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Cosco High Back Booster Forward Facing Unbelted, Middle Seat Track



Cosco High Back Booster Forward Facing Unbelted, Rearward Seat Track



Cosco High Back Booster Rear Facing Unbelted, Forward Seat Track



Cosco High Back Booster Rear Facing Unbelted, Middle Seat Track



Cosco High Back Booster Rear Facing Unbelted, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Middle Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Evenflo Generations Forward Facing Belted, Forward Seat Track



Evenflo Generations Forward Facing Belted, Middle Seat Track



Evenflo Generations Forward Facing Belted, Rearward Seat Track



Evenflo Generations Forward Facing Unbelted, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Evenflo Generations Forward Facing Unbelted, Middle Seat Track



Evenflo Generations Forward Facing Unbelted, Rearward Seat Track



Evenflo Generations Rear Facing Unbelted, Forward Seat Track



Evenflo Generations Rear Facing Unbelted, Middle Seat Track



Evenflo Generations Rear Facing Unbelted, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Graco Comfortsport Forward Facing Belted, Forward Seat Track



Graco Comfortsport Forward Facing Belted, Middle Seat Track



Graco Comfortsport Forward Facing Belted, Rearward Seat Track



Graco Comfortsport Forward Facing Unbelted, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Graco Comfortsport Forward Facing Unbelted, Middle Seat Track



Graco Comfortsport Forward Facing Unbelted, Rearward Seat Track



Graco Comfortsport Rear Facing Belted, Forward Seat Track



Graco Comfortsport Rear Facing Belted, Middle Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
12 Month
Section C

Forward Facing Convertible CRS



Graco Comfortsport Rear Facing Belted, Rearward Seat Track



Graco Comfortsport Rear Facing Unbelted, Forward Seat Track



Graco Comfortsport Rear Facing Unbelted, Middle Seat Track



Graco Comfortsport Rear Facing Unbelted, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Rearward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
Section C

Forward Facing Convertible CRS



3-Year-Old Forward Facing Britax Roundabout Belted, Forward Seat Track



3-Year-Old Forward Facing Britax Roundabout Belted, Middle Seat Track



3-Year-Old Forward Facing Britax Roundabout Belted, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Rearward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
Section C

Forward Facing Convertible CRS



3-Year-Old Forward Facing Cosco High Back Booster Belted, Forward Seat Track



3-Year-Old Forward Facing Cosco High Back Booster Belted, Middle Seat Track



3-Year-Old Forward Facing Cosco High Back Booster Belted, Rearward Seat Track



3-Year-Old Forward Facing Cosco High Back Booster Cinched With Harness, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old

Section C

Forward Facing Convertible CRS



3-Year-Old Forward Facing Cosco High Back Booster Cinched With Harness, Middle Seat Track



3-Year-Old Forward Facing Cosco High Back Booster Cinched With Harness, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Middle Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
Section C

Forward Facing Convertible CRS



3-Year-Old Forward Facing Evenflo Generations Belted, Forward Seat Track



3-Year-Old Forward Facing Evenflo Generations Belted, Middle Seat Track



3-Year-Old Forward Facing Evenflo Generations Belted, Rearward Seat Track



3-Year-Old Forward Facing Evenflo Generations Cinched With Harness, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
Section C

Forward Facing Convertible CRS



3-Year-Old Forward Facing Evenflo Generations Cinched With Harness, Middle Seat Track



3-Year-Old Forward Facing Evenflo Generations Cinched With Harness, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
Section C

Forward Facing Convertible CRS



3-Year-Old Forward Facing Graco Comfortsport Belted, Forward Seat Track



3-Year-Old Forward Facing Graco Comfortsport Belted, Middle Seat Track



3-Year-Old Forward Facing Graco Comfortsport Belted, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Rearward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Cosco Summit Deluxe Belted, Forward Seat Track



3-Year-Old Cosco Summit Deluxe Belted, Middle Seat Track



3-Year-Old Cosco Summit Deluxe Belted, Rearward Seat Track



3-Year-Old Cosco Summit Deluxe Cinched With Harness, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Cosco Summit Deluxe Cinched With Harness, Middle Seat Track



3-Year-Old Cosco Summit Deluxe Cinched With Harness, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Rearward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Graco Platinum Cargo Belted, Forward Seat Track



3-Year-Old Graco Platinum Cargo Belted, Middle Seat Track



3-Year-Old Graco Platinum Cargo Belted, Rearward Seat Track



3-Year-Old Graco Platinum Cargo Cinched With Harness, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Graco Platinum Cargo Cinched With Harness, Middle Seat Track



3-Year-Old Graco Platinum Cargo Cinched With Harness, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)

6 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



6-Year-Old Cosco Summit Deluxe Belted, Forward Seat Track



6-Year-Old Cosco Summit Deluxe Belted, Middle Seat Track



6-Year-Old Cosco Summit Deluxe Belted, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Middle Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)

6 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



6-Year-Old Graco Platinum Cargo Belted, Forward Seat Track



6-Year-Old Graco Platinum Cargo Belted, Middle Seat Track



6-Year-Old Graco Platinum Cargo Belted, Rearward Seat Track



Unbelted 5th Percentile Female Representative Reactivation, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
No CRS



3-Year-Old Unbelted, Forward Seat Track, Position 1



3-Year-Old Unbelted, Forward Seat Track, Position 2



3-Year-Old Unbelted, Forward Seat Track, Position 3



3-Year-Old Unbelted, Forward Seat Track, Position 4

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
No CRS



3-Year-Old Unbelted, Forward Seat Track, Position 5



3-Year-Old Unbelted, Forward Seat Track, Position 6



3-Year-Old Unbelted, Forward Seat Track, Position 7



3-Year-Old Unbelted, Middle Seat Track, Position 1

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
No CRS



3-Year-Old Unbelted, Middle Seat Track, Position 2



3-Year-Old Unbelted, Middle Seat Track, Position 3



3-Year-Old Unbelted, Middle Seat Track, Position 4



3-Year-Old Unbelted, Middle Seat Track, Position 5

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
No CRS



3-Year-Old Unbelted, Middle Seat Track, Position 6



3-Year-Old Unbelted, Middle Seat Track, Position 7



3-Year-Old Unbelted, Rearward Seat Track, Position 1



3-Year-Old Unbelted, Rearward Seat Track, Position 2

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
No CRS



3-Year-Old Unbelted, Rearward Seat Track, Position 3



3-Year-Old Unbelted, Rearward Seat Track, Position 4



3-Year-Old Unbelted, Rearward Seat Track, Position 5



3-Year-Old Unbelted, Rearward Seat Track, Position 6

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
3 Year Old
No CRS



3-Year-Old Unbelted, Rearward Seat Track, Position 7



Unbelted 5th Percentile Female Representative Reactivation, Forward Seat Track

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
6 Year Old
No CRS



6-Year-Old Unbelted, Forward Seat Track, Position 1



6-Year-Old Unbelted, Forward Seat Track, Position 2



6-Year-Old Unbelted, Forward Seat Track, Position 3



6-Year-Old Unbelted, Forward Seat Track, Position 4

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
6 Year Old
No CRS



6-Year-Old Unbelted, Middle Seat Track, Position 1



6-Year-Old Unbelted, Middle Seat Track, Position 2



6-Year-Old Unbelted, Middle Seat Track, Position 3



6-Year-Old Unbelted, Middle Seat Track, Position 4

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
6 Year Old
No CRS



6-Year-Old Unbelted, Rearward Seat Track, Position 1



6-Year-Old Unbelted, Rearward Seat Track, Position 2



6-Year-Old Unbelted, Rearward Seat Track, Position 3



6-Year-Old Unbelted, Rearward Seat Track, Position 4

DOT/NHTSA 208 Suppression Test - 2013 Chevrolet Sonic (C20130100)
6 Year Old No CRS



Unbelted 5th Percentile Female Representative Reactivation, Middle Seat Track

APPENDIX F

INSTRUMENTATION CALIBRATION

INSTRUMENTS FOR DRIVER DUMMY NO.: 511

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	P73720	Endevco	09/18/12
Head Y	P73721	Endevco	09/18/12
Head Z	P73722	Endevco	09/18/12
Neck Load Cell	N1673	Denton	10/22/12
Chest X	P73732	Endevco	09/18/12
Chest Y	P73733	Endevco	09/18/12
Chest Z	P73734	Endevco	09/18/12
Chest Displacement	511	Servo	09/24/12
Left Femur Load Cell	F9426	GSE	01/28/13
Right Femur Load Cell	F186	GSE	01/28/13

INSTRUMENTS FOR PASSENGER DUMMY NO.: 507

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	P77594	Endevco	02/19/13
Head Y	P77597	Endevco	02/19/13
Head Z	P77603	Endevco	02/19/13
Neck Load Cell	N1561	Denton	01/18/13
Chest X	P78282	Endevco	02/19/13
Chest Y	P78283	Endevco	02/19/13
Chest Z	P78284	Endevco	02/19/13
Chest Displacement	507	Servo	02/20/13
Left Femur Load Cell	F8154	Denton	09/26/12
Right Femur Load Cell	F8153	Denton	09/26/12

INSTRUMENTS FOR LOW RISK 5TH FEMALE DUMMY NO.: 510 (P1 & P2)

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	P77617	Endevco	01/24/13
Head Y	P77618	Endevco	01/24/13
Head Z	P77620	Endevco	01/24/13
Neck Load Cell	N1703	Denton	10/22/12
Chest X	P77634	Endevco	01/24/13
Chest Y	P77635	Endevco	01/24/13
Chest Z	P77636	Endevco	01/24/13
Chest Displacement	510	Servo	01/28/13
Left Femur Load Cell	F995	Denton	01/29/13
Right Femur Load Cell	F991	Denton	01/29/13

VEHICLE INSTRUMENTS

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Left Rear Seat Crossmember X	P63902	Endevco	01/04/13
Right Rear Seat Crossmember X	P66656	Endevco	12/26/12
Top of Engine X	P66573	Endevco	10/18/12
Bottom of Engine X	P63530	Endevco	10/06/12
Left Brake Caliper X	P66522	Endevco	01/29/13
Right Brake Caliper X	P66651	Endevco	12/27/12
Instrument Panel X	P66664	Endevco	10/31/12
Trunk Z	P67439	Endevco	10/30/12