

FINAL REPORT NUMBER: SINCAP-TRC-14-004

**NEW CAR ASSESSMENT PROGRAM (NCAP)
MOVING DEFORMABLE BARRIER SIDE IMPACT TEST**

**Mazda Motor Company
2014 Mazda 6 I Sport 4- Door Sedan
NHTSA NUMBER: M20145402**

**PREPARED BY:
Transportation Research Center Inc.
10820 State Route 347
P. O. Box B-67
East Liberty, OH 43319**



Report Date: March 12, 2014

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
National Highway Traffic Safety Administration
Office of Crashworthiness Standards
Mail Code: NVS-111
1200 New Jersey Ave, SE, Room W43-410
Washington, D.C. 20590**

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings, and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof.

If trade or manufacturers' names or products are mentioned, it is only because they are considered essential to the object of the publication and should not be construed as an endorsement.

Report Prepared By: ILO Project Operations Group

Report Approved By: 

Jeffery W. Sankey, Manager, Project Operations

Approval Date: March 12, 2014

FINAL REPORT ACCEPTANCE BY OCWS:

Division Chief, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

COTR, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

Technical Report Documentation Page

1. Report No. SINCAP-TRC-14-004	2. Government Accession No.	3. Recipient's Catalog No.																									
4. Title and Subtitle Final Report of New Car Assessment Program Side Impact MDB Testing of a 2014 Mazda 6 I Sport 4-door Sedan NHTSA No.: M20145402		5. Report Date March 12, 2014																									
		6. Performing Organization Code TRC Inc.																									
7. Author(s) Jeffery W. Sankey, Manager, Project Operations		8. Performing Organization Report Number 140114																									
9. Performing Organization Name and Address Transportation Research Center Inc. 10820 State Route 347 East Liberty, OH 43319		10. Work Unit No.																									
		11. Contract or Grant No. DTNH22-09-D-00125																									
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Crashworthiness Standards (NVS-111) 1200 New Jersey Ave, SE, Room W43-410 Washington, DC 20590		13. Type of Report and Period Covered Final Test Report January 14 2014 – March 12, 2014																									
		14. Sponsoring Agency Code NVS-111																									
15. Supplemental Notes																											
16. Abstract This 55/28 km/h 90° Moving Deformable Barrier NCAP Side Impact Test was conducted on the subject 2014 Mazda 6 I Sport 4-door Sedan in accordance with the specifications of the Office of Crashworthiness Standards Test Procedure for the generation of consumer information on vehicle side crash protection. This test was conducted by Transportation Research Center Inc. in East Liberty, Ohio, on January 14, 2014. The impact velocity of the Moving Deformable Barrier (MDB) was 62.00 km/h, and the ambient temperature at the struck (left) side of the target vehicle at the time of impact was 22° C. The target vehicle post-test maximum crush was 221 mm at Level 2. The test vehicle's performance was as follows:																											
Driver ATD (ES-2re)																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Measurement Description</th> <th style="text-align: center;">Units</th> <th style="text-align: center;">IARV</th> <th style="text-align: center;">Result</th> </tr> </thead> <tbody> <tr> <td>Head Injury Criteria (HIC₃₆)</td> <td style="text-align: center;">N/A</td> <td style="text-align: center;">1000</td> <td style="text-align: center;">154¹</td> </tr> <tr> <td>Maximum Thoracic Rib Deflection</td> <td style="text-align: center;">mm</td> <td style="text-align: center;">44</td> <td style="text-align: center;">27.1</td> </tr> <tr> <td>Total Abdominal Force</td> <td style="text-align: center;">N</td> <td style="text-align: center;">2500</td> <td style="text-align: center;">1140.4</td> </tr> <tr> <td>Pubic Symphysis Force</td> <td style="text-align: center;">N</td> <td style="text-align: center;">6000</td> <td style="text-align: center;">1943.0</td> </tr> </tbody> </table>				Measurement Description	Units	IARV	Result	Head Injury Criteria (HIC ₃₆)	N/A	1000	154 ¹	Maximum Thoracic Rib Deflection	mm	44	27.1	Total Abdominal Force	N	2500	1140.4	Pubic Symphysis Force	N	6000	1943.0				
Measurement Description	Units	IARV	Result																								
Head Injury Criteria (HIC ₃₆)	N/A	1000	154 ¹																								
Maximum Thoracic Rib Deflection	mm	44	27.1																								
Total Abdominal Force	N	2500	1140.4																								
Pubic Symphysis Force	N	6000	1943.0																								
Passenger ATD (SID-IIs)																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Measurement Description</th> <th style="text-align: center;">Units</th> <th style="text-align: center;">IARV</th> <th style="text-align: center;">Result</th> </tr> </thead> <tbody> <tr> <td>Head Injury Criteria (HIC₃₆)</td> <td style="text-align: center;">N/A</td> <td style="text-align: center;">1000</td> <td style="text-align: center;">356</td> </tr> <tr> <td>Lower Spine Resultant Acceleration</td> <td style="text-align: center;">g's</td> <td style="text-align: center;">82</td> <td style="text-align: center;">64.4</td> </tr> <tr> <td>Total Pelvic Force (sum of acetabular and iliac forces)</td> <td style="text-align: center;">N</td> <td style="text-align: center;">5525</td> <td style="text-align: center;">1691.9</td> </tr> <tr> <td>Maximum Thoracic Rib Deflection</td> <td style="text-align: center;">mm</td> <td style="text-align: center;">38*</td> <td style="text-align: center;">32.0</td> </tr> <tr> <td>Maximum Abdominal Rib Deflection</td> <td style="text-align: center;">mm</td> <td style="text-align: center;">45*</td> <td style="text-align: center;">33.4</td> </tr> </tbody> </table>				Measurement Description	Units	IARV	Result	Head Injury Criteria (HIC ₃₆)	N/A	1000	356	Lower Spine Resultant Acceleration	g's	82	64.4	Total Pelvic Force (sum of acetabular and iliac forces)	N	5525	1691.9	Maximum Thoracic Rib Deflection	mm	38*	32.0	Maximum Abdominal Rib Deflection	mm	45*	33.4
Measurement Description	Units	IARV	Result																								
Head Injury Criteria (HIC ₃₆)	N/A	1000	356																								
Lower Spine Resultant Acceleration	g's	82	64.4																								
Total Pelvic Force (sum of acetabular and iliac forces)	N	5525	1691.9																								
Maximum Thoracic Rib Deflection	mm	38*	32.0																								
Maximum Abdominal Rib Deflection	mm	45*	33.4																								
* Proposed IARV																											
The doors on the struck side of the vehicle did not separate from the body at the hinges or latches and the opposite doors did not open during the side impact event.																											
¹ The HIC was calculated using the redundant Y-axis.																											
17. Key Words New Car Assessment Program (NCAP) Side Impact MDB ES-2re SID-IIs		18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Administration Technical Information Services Division, NPO-411 1200 New Jersey Ave, SE Washington, DC 20590 e-mail: tis@nhtsa.dot.gov FAX: 202-493-2833																									
19. Security Classification (of this report) Unclassified	20. Security Classification (of this page) Unclassified	21. Number of Pages 210	22. Price																								

TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1	Test Purpose and Procedure	1
2	Summary of Test Results	2
3	Occupant and Vehicle Information	4
<u>Appendix</u>		
A	Photographs	A-1
B	Vehicle and Dummy Response Data Plots	B-1
C	Dummy Performance Calibration Test Data	C-1
D	Test Equipment and Instrumentation Calibration Data	D-1
<u>Data Sheet No.</u>		<u>Page No.</u>
1	General Test and Vehicle Parameter Data	5
2	Seat, Seat Belt, Steering Wheel Adjustment and Fuel Systems Data	8
3	Dummy Longitudinal Clearance Dimensions	11
4	Dummy Lateral Clearance Dimensions	12
5	Camera and Instrumentation Data	13
6	Test Vehicle Accelerometer Locations	14
7	MDB Accelerometer Locations	15
8	Post-Test Observations	16
9	MDB Summary of Results	18
10	Test Vehicle Profile Measurements	19
11	Test Vehicle Exterior Crush Measurements	20
12	MDB Exterior Static Crush Measurements	23
13	FMVSS No. 301 Static Rollover Results	24
14	Dummy/Vehicle Temperature and Humidity Stabilization	25

SECTION 1
TEST PURPOSE AND PROCEDURE

TEST PURPOSE AND PROCEDURE

This moving deformable barrier side impact test was conducted as part of the MY 2014 New Car Assessment Program Side Impact Test Program, sponsored by the National Highway Traffic Safety Administration (NHTSA), under Contract No. DTNH22-09-D-00125. The purpose of this test is to generate comparative side impact performance in a 2014 Mazda 6 I Sport 4-door Sedan. The side impact test was conducted in accordance with the Office of Crashworthiness Standard's Laboratory Test Procedure dated September 2013.

SECTION 2

SUMMARY OF TEST RESULTS

A 2014 Mazda 6 I Sport 4-door Sedan was impacted on the left (driver's) side by a Moving Deformable Barrier (MDB) which was moving forward in a 27° crabbed position to the tow road guidance system at a velocity of 62.00 km/h (38.53 mph). The target vehicle was stationary and was positioned at an angle of 63° to the line of forward motion. The side impact test was conducted by the Transportation Research Center Inc. in East Liberty, Ohio, on January 14, 2014. Pre-test and post-test photographs of the test vehicle and the MDB and the dummies (ES-2-re and SID-IIs) are included in this report.

Dummies were placed in the driver and left rear designated seating positions according to instructions specified in the OCWS Side Impact Laboratory Test Procedure, dated September 2013. The side impact event was documented by 11 cameras. Camera locations are included in this report.

The dummies were instrumented in the following manner:

DRIVER ATD (ES-2re)

- Primary and redundant head CG tri-axial accelerometers
- Chest upper rib, middle rib, and lower rib y-axis displacement potentiometers
- Abdomen forward, middle, and rear y-axis load cells
- Lower spine (T12) tri-axial accelerometers
- Pubic symphysis y-axis load cell

PASSENGER ATD (SID-IIs)

- Primary and redundant head CG triaxial accelerometers
- Chest upper rib, middle rib, and lower rib y-axis displacement potentiometers
- Abdomen upper rib and lower rib y-axis displacement potentiometers
- Lower spine (T12) tri-axial accelerometers
- Acetabulum and iliac wing y-axis load cells

APPENDIX B contains the vehicle and dummy response data. Dummy configuration and performance verification data can be found in APPENDIX C of this report.

Dummy injury readings were recorded as follows:

Measurement Description	Driver ATD (ES-2-re)		
	Units	Threshold	Result
Head Injury Criteria (HIC ₃₆)	N/A	1000	154 ¹
Maximum Thoracic Rib Deflection	mm	44	27.1
Combined Abdominal Force	N	2500	1140.4
Pubic Symphysis Force	N	6000	1943.0

¹The HIC was calculated using the redundant Y-axis.

Measurement Description	Passenger ATD (SID-IIs)		
	Units	Threshold	Result
Head Injury Criteria (HIC ₃₆)	N/A	1000	356
Lower Spine (T12) Resultant Acceleration	G	82	64.4
Total Pelvic Force (sum of acetabular and iliac forces)	N	5525	1691.9
Maximum Thoracic Rib Deflection	mm	38*	32.0
Maximum Abdominal Rib Deflection	mm	45*	33.4

* Proposed IARV

Supplemental Restraint Information is given below:

Restraint Type	Left Front (Driver) Occupant Location 1		Left Rear (Passenger) Occupant Location 4	
	Mounted	Deployed	Mounted	Deployed
Frontal Airbag	Yes	No		
Side Curtain Airbag	Yes	Yes	Yes	Yes
Side Torso/Pelvis Airbag	Yes	Yes	No	N/A
Knee Airbag	No	NA	No	N/A
Seat Belt Pretensioner	Yes	Yes	No	N/A
Seat Belt Load Limiter	Yes	No	No	N/A
Other	N/A	N/A	N/A	N/A

GENERAL COMMENTS

All doors remained closed throughout the test. No fuel spillage occurred during the impact or the static rollover test which followed. Injury values for both ATDs were within the established performance thresholds. The restraint system performed as expected. The vehicle had secondary impact with the cart on the left front bumper and fender.

SECTION 3
OCCUPANT AND VEHICLE INFORMATION

**DATA SHEET NO. 1
GENERAL TEST AND VEHICLE PARAMETER DATA**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
Test Program: NCAP Side Impact

NHTSA No.: M20145402
Test Date: 1/14/14

TEST VEHICLE INFORMATION AND OPTIONS

NHTSA No.	M20145402
Model Year	2014
Make	Mazda
Model	6 I Sport
Body Style	Sedan
VIN	JM1GJ1U68E1143182
Body Color	Silver
Odometer Reading (km/mi)	100 mi
Engine Displacement (L)	2.5
Type/No. Cylinders	4
Engine Placement	Front/Transverse
Transmission Type	Automatic
Transmission Speeds	6
Overdrive	Yes
Final Drive	FWD
Roof Rack	No
Sunroof/T-Top	No
Running Boards	No
Tilt Steering Wheel	Yes
Power Seats	No
Anti-Lock Brakes (ABS)	Yes

Traction Control System (TCS)	Yes
Auto-Leveling System	No
Automatic Door Locks (ADL)	Yes
Power Window Auto-Reverse	Yes
Other Optional Feature	N/A
Driver Front Airbag	Yes
Driver Curtain Airbag	Yes
Driver Head/Torso Airbag	No
Driver Torso Airbag	No
Driver Torso/Pelvis Airbag	Yes
Driver Pelvis Airbag	No
Driver Knee Airbag	No
Rear Pass. Curtain Airbag	Yes
Rear Pass. Head/Torso Airbag	No
Rear Pass. Torso Airbag	No
Rear Pass. Torso/Pelvis Airbag	No
Rear Passenger Pelvis Airbag	No
Driver Seat Belt Pretensioner	Yes
Rear Pass. Seat Belt Pretensioner	No
Driver Load Limiter	Yes
Rear Passenger Load Limiter	No
Other Safety Restraint	N/A

Does owner's manual provide instructions to turn off automatic door locks? Yes

DATA FROM CERTIFICATION LABEL

Manufactured By	Mazda Motor Company
Date of Manufacture	09/13
Vehicle Type	Passenger Car

GVWR (kg)	1945
GAWR Front (kg)	1029
GAWR Rear (kg)	921

VEHICLE SEATING AND CAPACITY WEIGHT INFORMATION

Measured Parameter	Front	Rear	Third	Total
Designated Seating Capacity (DSC)	2	3	N/A	5
Capacity Weight (VCW) (kg)				385
DSC x 68.04 (kg)				340.2
Cargo Weight (RCLW) (kg)				44.8


VEHICLE SEAT TYPE

Seating Location	Type of Seat Pan				Type of Seat Back		
	Bucket	Bench	Split Bench	Contoured	Fixed	Adjustable	
						w/ Lever	w/ Knob
Front Seat	Yes	N/A	N/A		N/A	Yes	N/A
Rear or Second Row Seat	N/A	N/A	Yes	N/A	Yes	N/A	N/A
Third Row Seat	N/A	N/A	N/A	N/A	N/A	N/A	N/A

DATA SHEET NO. 1 (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14



DATA FROM TIRE PLACARD

Measured Parameter	Front	Rear
Maximum Tire Pressure (kPa)	350	350
Cold Pressure (kPa)	250	250
Recommended Tire Size	P225/55R17	P225/55R17
Tire Size on Vehicle	P225/55R17	P225/55R17
Tire Manufacturer	Yokohama	Yokohama
Tire Model	ADVAN A83	ADVAN A83
Treadwear	280	280
Traction	A	A
Temperature Grades	A	A
Tire Plies Sidewall	1	1
Tire Plies Body	4	4
Load Index/Speed Symbol	95 V	95 V
Tire Material	Polyester, Steel, Nylon	Polyester, Steel, Nylon
DOT Safety Code Left	FDUP-PFW3413	FDUP-PFW3413
DOT Safety Code Right	FDUP-PFW3413	FDUP-PFW3413

DATA SHEET NO. 1 (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14

TIRE PRESSURES

	Units	LF	RF	LR	RR
As Delivered	kPa	276	276	276	276
Tire Placard	kPa	250	250	250	250
Owner's Manual	kPa	250	250	250	250
As Tested	kPa	250	250	250	250

MDB TIRE SPECIFICATIONS

	Units	Requirement	LF	RF	LR	RR
Tire Size		P205/75R15	P205/75R15	P205/75R15	P205/75R15	P205/75R15
Tire Pressure	kPa	207	207	207	207	207

TEST VEHICLE AXLE WEIGHTS

	Units	As Delivered (UVW)			As Tested (ATW)			Fully Loaded		
		Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total
Left	kg	430.6	305.0		477.8	351.0		480.0	392.6	
Right	kg	425.4	286.4		448.8	332.8		433.8	342.8	
Ratio	%	59.1	40.9		57.5	42.5		55.4	44.6	
Totals	kg	856.0	591.4	1447.4	926.6	683.8	1610.4	913.8	735.4	1649.2

TARGET TEST WEIGHT CALCULATION

Measured Parameter	Units	Value	
Total As Delivered Weight (UVW)	kg	1447.4	(A)
Actual Weight of 1 P572V ATD (SID-II)s Dummy Used	kg	125.0	(B)
Rated Cargo/Luggage Weight (RCLW)	kg	44.8	(C)
Calculated Vehicle Target Weight (TVTW)	kg	1617.2	(A+B+C)

Does the measured As Tested Vehicle Weight lie within the required weight range (i.e. Calculated Test Vehicle Target Weight – 4.5 kg to 9 kg)? YES NO

TEST VEHICLE ATTITUDES AND CG

Measurement Description	Units	Fully Loaded	As Tested	Meets Requirement
LF	mm	704	706	Yes
RF	mm	718	705	No
RR	mm	713	715	Yes
LR	mm	695	708	No
Vehicle CG (Aft of Front Axle)	mm	1262	1202	
Vehicle CG (Left+)/Right(-) from Longitudinal Centerline)	mm	+45	+23	

***The "As Tested" vehicle attitude measurements must be equal to or within ± 10 mm of the "Fully Loaded" vehicle attitude measurements at each wheel well. Indicate "Yes" or "No" for "Meets Requirement".

WEIGHT OF BALLAST AND VEHICLE COMPONENTS REMOVED TO MEET TVTW

Component Description	Weight (kg)
Ballast : None	None
Removed: Rear fascia, muffler, and tail lights.	24.4

DATA SHEET NO. 2

SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT AND FUEL SYSTEM DATA

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan

NHTSA No.: M20145402

Test Program: NCAP Side Impact

Test Date: 1/14/14

SEAT POSITIONING

The driver seat, front center seat (if applicable), and right front passenger's seat should be set to the mid-track, lowest, mid-angle position. The struck-side rear passenger's seat, rear center seat, and non-struck side rear passenger's seats should be set to the rear-most, lowest, mid-angle position.

SCRL ANGLE RANGE

Seat	SCRL(°)		
	Max.	Min.	Mid
Driver Seat	18.7	13.8	16.3
Front Passenger Seat	N/A	N/A	15.8
Front Center Seat*	N/A	N/A	N/A
Struck Side Rear Seat	Fixed	N/A	16.3
Non-Struck Side Rear Seat	Fixed	N/A	15.8
Rear Center Seat*	Fixed	N/A	7.8

* If applicable.

SEAT HEIGHT AND ANGLE

Seat	As Tested SCRL Angle (Mid) (°)	As Tested SCRP Height (mm)	SCRP Height Position	SCRP Height (mm)		
				Rearmost	Mid-Fore/Aft	Forward-Most
Driver Seat	16.3	136	Max	N/A	N/A	N/A
			Mid	121	136	148
			Min	N/A	N/A	N/A
Front Passenger Seat	15.8	139	Max	N/A	N/A	N/A
			Mid	124	139	152
			Min	N/A	N/A	N/A
Front Center Seat*	N/A	N/A	Max	N/A	N/A	N/A
			Mid	N/A	N/A	N/A
			Min	N/A	N/A	N/A
Struck Side Rear Seat	16.3	Fixed	Max	N/A	N/A	N/A
			Mid	N/A	N/A	N/A
			Min	N/A	N/A	N/A
Non-Struck Side Rear Seat	15.8	Fixed	Max	N/A	N/A	N/A
			Mid	N/A	N/A	N/A
			Min	N/A	N/A	N/A
Rear Center Seat*	7.8	Fixed	Max	N/A	N/A	N/A
			Mid	N/A	N/A	N/A
			Min	N/A	N/A	N/A

* If applicable.

DATA SHEET NO. 2 (CONTINUED)

SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT AND FUEL SYSTEM DATA

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan

NHTSA No.: M20145402

Test Program: NCAP Side Impact


Test Date: 1/14/14

SEAT FORE/AFT POSITION

Seat	Total Fore/Aft Travel		Test Position from Forwardmost Position	
	mm	Detents	mm	Detent
Driver Seat	260	27	130	13
Front Passenger Seat	260	27	130	13
Front Center Seat*	N/A	N/A	N/A	N/A
Struck Side Rear Seat	Fixed	N/A	Fixed	N/A
Non-Struck Side Rear Seat	Fixed	N/A	Fixed	N/A
Rear Center Seat*	Fixed	N/A	Fixed	N/A

SEAT BACK ANGLE ADJUSTMENT

The driver's seat back is positioned to the manufacturer's designated seat back angle. The front center and front passenger's seat backs are positioned in a similar manner as the driver's seat back. The struck side rear seat back is positioned such that the dummy's head is level. The rear center and non-struck side rear outboard seat backs are positioned in a similar manner as the struck-side rear seat back.



Seat	Total Seat Back Angle Range		Test Position from Most Upright	
	Degrees	Detents	Degrees	Detent
Driver Seat w/ Seated Dummy	66.6	40	9.6	8
Front Passenger Seat	65.1	40	10.8	8
Front Center Seat*	N/A	N/A	N/A	N/A
Struck Side Rear Seat w/ Seated Dummy	Fixed	N/A	23.2	Fixed
Non-Struck Side Rear Seat	Fixed	N/A	23.3	Fixed
Rear Center Seat*	Fixed	N/A	25.6	Fixed

SEAT BELT ANCHORAGE ADJUSTMENT

Seat belt anchorages are adjusted in accordance with the information provided by the manufacturer on Form No. 1.

	Total # of Positions	Placed in Position #
Driver Seat	3, Numbered from 0 to 2	0, Uppermost
Rear Seat	1	1, Fixed

HEAD RESTRAINT ADJUSTMENT

The driver's head restraint is adjusted to the highest and most full forward in-use position. The struck-side rear passenger's head restraint is adjusted to the lowest and most full forward in-use position.

	Total # of Positions	Placed in Position #
Driver Seat	4, Numbered from 0 to 3	0, Uppermost
Rear Seat	4, Numbered from 0 to 3	3, Lowermost

DATA SHEET NO. 2 (CONTINUED)


SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT AND FUEL SYSTEMS DATA

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14

STEERING COLUMN ADJUSTMENT


Steering wheel and column adjustments are made so that the steering wheel hub is at the center of its geometric locus it describes when it moves through its full range of motion.



	Degrees	Fore/Aft Position (mm)
Lowermost, Position No. 1	20.7	50
Geometric Center, Position No. 2	22.9	50
Uppermost, Position No. 3	25.0	50
Telescoping Steering Wheel Travel		50
Test Position	22.9	25

FUEL PUMP

Pump operates a few seconds after ignition switch is turned ON. After that, pump operates only while engine is running.



FUEL TANK CAPACITY


	Liters
Usable Capacity of "Standard Tank" (see Form No. 1)	62.0
Usable Capacity of "Optional Tank" (see Form No. 1)	N/A
Usable Capacity of Standard Tank (see Owner's Manual)	62.0
Usable Capacity of Optional Tank (see Owner's Manual)	N/A
93% of Usable Capacity	57.7
Actual Amount of Solvent Used in Test	57.7
1/3 of Usable Capacity	19.2

Is the Actual Amount of Solvent Used in the test equal to 93% ± 1% of the Usable Capacity stated in on Form No. 1? YES NO

**DATA SHEET NO. 3
DUMMY LONGITUDINAL CLEARANCE DIMENSIONS**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
Test Program: NCAP Side Impact

NHTSA No.: M20145402
Test Date: 1/14/14



LEFT SIDE VIEW

NOTE: 2-DOOR VEHICLE SHOWN.
REAR DUMMY PHX & PHZ
MEASUREMENTS FOR A 4-DOOR
VEHICLE WOULD USE THE C-POST
STRIKER AS A REFERENCE POINT


DUMMY LONGITUDINAL CLEARANCE DIMENSION INFORMATION

Driver Code	Pass. Code	Measurement Description	Driver		Passenger	
			Length (mm)	Angle	Length (mm)	Angle
HH		Header to Header	364			
HW		Header to Windshield	637			
HZ	HZ	Head to Roof Liner	172		251	
NR	NB	Nose to Rim/Seat Back	478		536	
CD	CB	Chest to Dash/Seat Back	573		529	
CS		Chest to Steering Wheel	308			
KD(L)/KDA(L) ^o	KB(L)/KBA(L) ^o	Left Knee to Dash/Seat Back	137	30	284	11
KD(R)/KDA(R) ^o	KB(R)/KBA(R) ^o	Right Knee to Dash/Seat Back	135	30	290	11
PAX ^o	PAX ^o	Pelvic Tilt Angle X		1.0		1.0
	PAY ^o	Pelvic Tilt Angle Y				20.8
PHX	PHX	Hip Point to Striker (X-Axis)	205		282	
PHZ	PHZ	Hip Point to Striker (Z-Axis)	198		338	

**DATA SHEET NO. 4
DUMMY LATERAL CLEARANCE DIMENSIONS**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14




FRONT VIEW OF DUMMY

Code	Description	Units	Driver	Passenger
HR	Head to Side Header	mm	215	251
HS	Head to Side Window	mm	348	293
AD	Arm to Door	mm	112	130
HD	H-Point to Door	mm	164	193

**DATA SHEET NO. 5
CAMERA AND INSTRUMENTATION DATA**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14



CAMERA LOCATIONS AND DATA

No.	Camera View	Coordinates (mm)			Lens Length (mm)	Operating Frame Rate (fps)
		X	Y	Z		
1	Overhead Overall	0	385	-5724	8.5	1000
2	Overhead Close-up	0	840	-5724	25	1000
3	Left Impact Point (MDB)	-1791	-853	-821	25	1000
4	Side Overall (MDB)	-2458	0	-1438	8.5	1000
5	Rear	-1050	-6891	-1321	Zoom	1000
6	Left Front	-2639	-4551	-1312	Zoom	1000
7	Driver Front (OB)				8.5	1000
8	Driver Side (OB)				8.5	1000
9	Passenger Side (OB)				8.5	1000
10	Real-time Left Rear				Zoom	30
11	Real-time Inrun				zoom	30

Reference: Impact Point projected to Ground; +X = To Front of MDB +Y = To Right of MDB; +Z = Down

*All measurements accurate to ± 6 mm.

If applicable, explain why camera(s) did not operate as intended:


INSTRUMENTATION

Driver Dummy Channels	16
Passenger Dummy Channels	16
Vehicle Structure Accelerometers	23
MBD Accelerometers	7
TOTAL	62

**DATA SHEET NO. 6
TEST VEHICLE ACCELEROMETER LOCATIONS**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14



TEST VEHICLE ACCELEROMETER LOCATIONS


Loc. No.	Accelerometer Location	Coordinates (mm)		
		X	Y	Z
1	Vehicle CG	2825	115	290
2	Right Sill at Front Seat	2650	660	280
3	Right Sill at Rear Seat	1720	670	290
4	Left Sill at Front Door	2650	-660	285
5	Left Sill at Rear Door	1720	-670	290
6	A-Post Lower	3085	-825	465
7	A-Post Middle	3080	-825	833
8	B-Post Lower	2020	-825	542
9	B-Post Middle	1963	-808	897
10	Front Seat Track	2555	-585	330
11	Rear Seat Structure	1440	-505	395
12	Right Rear Occ. Compartment	1680	455	260
13	Engine Block	3690	0	832
14	Rear Above Axle	980	0	565

Reference: X - Rear surface of vehicle (+ forward)
 Y - Vehicle Centerline (+ to right)
 Z - Ground Plane (+ down)

**DATA SHEET NO. 7
MDB ACCELEROMETER LOCATIONS**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14



MDB ACCELEROMETER LOCATIONS

Loc. No.	Accelerometer Location	Coordinates (mm)		
		X	Y	Z
1	MDB CG	-2179	0	-505
2	MDB Rear	-3648	-650	-618

Reference : X - Face of MDB (+ forward)
 Y - MDB Centerline (+ to right)
 Z - Ground Plane (+ down)

**DATA SHEET NO. 8
POST-TEST OBSERVATIONS**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
Test Program: NCAP Side Impact

NHTSA No.: M20145402
Test Date: 1/14/14

TEST DUMMY INFORMATION AND CONTACT POINTS

Dummy Body Part	Front Seat Dummy (ES2-re)	Rear Seat Dummy (SID-IIs)
Face	SCAB	SCAB, Headliner
Top of Head	SCAB, Headliner	SCAB, Headliner
Left Side of Head	SCAB	SCAB
Back of Head	SCAB, Headliner	None
Left Shoulder	Torso/Pelvis Bag	Door Panel
Upper Torso	Seat Side Bolster	Seat Side Bolster
Lower Torso	Seat Side Bolster	Seat Side Bolster
Left Hip	Torso Bag	Seat Bolster, Door Panel
Left Knee	None	Door Panel

POST TEST DOOR PERFORMANCE

Description	Struck Side		Non-Struck Side		Trunk Lid
	Front	Rear	Front	Rear	
Remained Closed and Operational	No	No	Yes	Yes	Yes
Total Separation from Vehicle at Hinges or Latches	No	No	No	No	No
Latch or Hinge Systems Pulled Out of Their Anchorages	No	No	No	No	No
Disengaged from Latched Position	No	No	No	No	No
Latch Separated from Striker	No	No	No	No	No
Jammed Shut	Yes	Yes	No	No	No
If Door Opened at Striker, Record Width of Opening at Striker (mm)	N/A	N/A	N/A	N/A	N/A

POST TEST SEAT PERFORMANCE

Description	Struck Side		Non-Struck Side	
	Front	Rear	Front	Rear
Seat Movement Along Seat Track	No	No	No	No
Seat Disengagement from Floor pan	No	No	No	No
Seat Back Movement from Initial Position	No	No	No	No
Seat Back Collapse	No	No	No	No

POST TEST STRUCTURAL OBSERVATIONS

Critical Areas of Performance	Observations and Conclusions
Pillar Performance	Major Deformation
Sill Separation	None
Windshield Damage	None
Side Window Damage	Left front and left rear Shattered
Other Notable Effects	N/A

**DATA SHEET NO. 8 (CONTINUED)
POST TEST OBSERVATIONS**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
Test Program: NCAP Side Impact

NHTSA No.: M20145402
Test Date: 1/14/14

SUPPLEMENTAL RESTRAINT SYSTEM INFORMATION

Restraint Type	Struck Side Driver		Struck Side Rear Passenger	
	Mounted	Deployed	Mounted	Deployed
Frontal Airbag	Yes	No		
Knee Airbag	No	N/A		
Side Curtain Airbag	Yes	Yes	Yes	Yes
Side Torso/Pelvis Airbag	Yes	Yes	No	N/A
Seat Belt Pretensioner	Yes	Yes	No	N/A
Seat Belt Load Limiter	Yes	No	No	N/A
Other	No	N/A	No	N/A

IMPACT POINT LOCATION DATA

Measured Parameter	Units	Tolerance	Value
Vehicle Wheel Base	mm		2830
Vertical Impact Reference Line (Aft of Front Axle) (Intended Impact Point)	mm		480
Actual Impact Point (Aft of Front Axle)	mm		478
Horizontal Offset (+ forward / - rearward)	mm	+/- 50 of Intended Impact point	+2
Vertical Offset (+ down / - up)	mm	+/- 20 of Intended Impact point	-5

**DATA SHEET NO. 9
MDB SUMMARY OF RESULTS**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
Test Program: NCAP Side Impact

NHTSA No.: M20145402
Test Date: 1/14/14

MDB SPECIFICATIONS

Measurement Description	Length (mm)
Overall Width of Framework Carriage	1252
Overall Length Including Honeycomb Face	4115
Wheel Base of Framework Carriage	2591
C.G. Location aft of Front Axle	1115

MDB WEIGHTS

	Units	Front Axle	Rear Axle	Total
Left	kg	386.4	295.2	681.6
Right	kg	392.6	293.6	686.2
Ratio	%	57.0	43.0	100.0
Totals	kg	779.0	588.8	1367.8

SPEED AND IMPACT ANGLE DATA

Measured Parameter	Units	Requirement	Value
Trap No. 1 Velocity (Primary)	km/h	61.1 to 62.7	62.00
Trap No. 2 Velocity (Redundant)	km/h	61.1 to 62.7	61.99
MDB CL to Target Vehicle CL	degrees	88.5 to 91.5	90.0
MDB Forward Line of Motion to Target Vehicle CL	degrees	62.5 to 63.5	63.0
MDB Crabbed Angle to MDB Forward Line of Motion	degrees	26 to 28	27.0


MAXIMUM STATIC CRUSH OF HONEYCOMB IMPACT FACE

Vertical Location			From Centerline		Maximum Crush
Row	Description	Height	Distance	Direction	
A	Center of Bumper	432	800	Right	-204
B	Top of Bumper	533	200	Right	-373
C	Mid-Level	686	800	Left	-110
D	Top of Stack	813	800	Left	-140

**DATA SHEET NO. 10
TEST VEHICLE PROFILE MEASUREMENTS**

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
Test Program: NCAP Side Impact

NHTSA No.: M20145402
Test Date: 1/14/14



LEFT SIDE VIEW

All MEASUREMENTS IN (mm) WITH TOLERANCE OF ± 3 mm

VEHICLE PRE- AND POST-TEST MEASUREMENT INFORMATION


Code	Measurement Description	Pre-Test	Post-Test	Difference
A	Wheelbase	2830	2835	-5
B	Front Axle to Front Surface of Vehicle	965	973	-8
C	Rear Axle to Rear Surface of Vehicle	1090	1093	-3
D	Total Length at Centerline	4885	4895	-10
E	Front Bumper Thickness	145	145	0
F	Front Bumper Bottom to Ground	385	403	-18
G	Sill Height at Front Wheel Well	250	267	-17
H	Sill Height at Front Door Leading Edge	255	263	-8
I	Sill Height at B-Pillar	255	330	-75
J1	Sill Height at Rear Wheel Well	268	319	-51
J2	Pinch Weld Height at Rear Wheel Well	155	194	-39
K	Sill Height Aft of Rear Wheel Well	325	366	-41
L	Rear Bumper Thickness	160	160	0
M	Rear Bumper Bottom to Ground	516	554	-38
N	Sill Height to Window Bottom Sill	705	615	90
O	Front Door Leading Edge to Impact CL	796	742	54
P	Rear Door Trailing Edge to Impact CL	1355	1120	235
Q	Front Window Opening	340	305	35
R	Right Side Length	4660	4620	40
S	Left Side Length	4640	4595	45
T	Vehicle Width at B Pillar	1820	1820	0

DATA SHEET NO. 11

TEST VEHICLE EXTERIOR CRUSH MEASUREMENTS

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14



LEFT SIDE VIEW

MAXIMUM EXTERIOR CRUSH MEASUREMENTS

Level	Measurement Description	Height Above Ground	Maximum Exterior Static Crush	Distance From Impact
1	Sill Top	347	136	750
2	Driver Hip Point	529	221	450
3	Mid-Door	635	202	1350
4	Window Sill	930	202	1800
5	Window Top	1377	6	1350

NOTE: The above measurements were taken along the vertical impact reference line. Vehicle measurements forward of the vertical impact reference line are negative.

DATA SHEET NO. 11 (CONTINUED)

TEST VEHICLE EXTERIOR CRUSH MEASUREMENTS

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14

EXTERIOR CRUSH MEASUREMENTS AT EACH LEVEL

	Pre-Test					Post-Test					Difference				
	1	2	3	4	5	1	2	3	4	5	1	2	3	4	5
-900	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-750	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-600	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-450	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-300	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-150	0	0	917	792	0	0	0	921	793	0	0	0	-4	-1	0
0	893	909	910	807	0	905	908	900	799	0	-12	1	10	8	0
150	888	903	906	816	0	796	716	762	807	0	92	187	144	9	0
300	888	901	904	822	0	764	684	704	785	0	124	217	200	37	0
450	890	901	904	832	0	760	680	715	775	0	130	221	189	57	0
600	892	902	906	840	0	757	684	723	773	0	135	218	183	67	0
750	894	903	907	848	0	758	695	706	768	0	136	208	201	80	0
900	893	903	908	855	611	758	711	714	758	618	135	192	194	97	-7
1050	891	903	908	859	624	760	693	711	774	627	131	210	197	85	-3
1200	889	902	907	863	625	773	695	718	765	621	116	207	189	98	4
1350	887	902	907	865	621	783	690	705	725	615	104	212	202	140	6
1500	885	902	907	866	617	792	697	708	697	612	93	205	199	169	5
1650	886	902	906	865	610	817	708	710	665	607	69	194	196	200	3
1800	888	904	906	864	597	878	739	720	662	598	10	165	186	202	-1
1950	900	914	911	857	570	912	890	834	753	571	-12	24	77	104	-1
2100	0	0	917	859	0	0	0	901	830	0	0	0	16	29	0
2250	0	0	0	855	0	0	0	0	838	0	0	0	0	17	0
2400	0	0	0	848	0	0	0	0	837	0	0	0	0	11	0
2550	0	0	0	837	0	0	0	0	834	0	0	0	0	3	0
2700	0	0	0	824	0	0	0	0	824	0	0	0	0	0	0
2850	0	0	0	807	0	0	0	0	809	0	0	0	0	-2	0


NOTE: Pre-test measurements are taken when the vehicle is in the "As Tested" weight condition.

Vehicle measurements forward of the vertical impact reference line are negative. The crush profile grid is established prior to the test based on an estimated impact point.

DATA SHEET NO. 11 (CONTINUED)
TEST VEHICLE EXTERIOR CRUSH MEASUREMENTS

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
Test Program: NCAP Side Impact


NHTSA No.: M20145402
Test Date: 1/14/14



DATA SHEET NO. 12
MDB EXTERIOR STATIC CRUSH MEASUREMENTS

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14



NOTE: Dimensions are shown in millimeters, mm

DEFORMABLE BARRIER STATIC CRUSH

Stack Level	Distance Right of Center									C/L	Distance Left of Center								
	800	700	600	500	400	300	200	100	0		100	200	300	400	500	600	700	800	
1	4	0	-11	-25	-45	-86	-101	-98	-74	-37	-44	-53	-62	-70	-89	-118	-140		
2	-20	-19	-22	-27	-34	-63	-72	-66	-40	-27	-23	-23	-33	-48	-66	-77	-110		
3	-94	-92	-90	-89	N/A ¹	N/A ¹	N/A ¹	N/A ¹	-80	-77	-77	-73	-70	-68	-67	-71	-91		
4	-204	-193	-184	-183	-181	-182	-182	-178	-174	-169	-166	-164	-161	-158	-157	-170	-181		

¹ Measurement point missing post-test

DATA SHEET NO. 13
FMVSS NO. 301 STATIC ROLLOVER RESULTS


Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
 Test Program: NCAP Side Impact

NHTSA No.: M20145402
 Test Date: 1/14/14

Test Time: 13:44 Temperature: 21.6°C

- A. From impact until vehicle motion ceases: 0 oz.
 (Maximum allowable is 1 ounce)
- B. For the 5 minute period after motion ceases: 0 oz.
 (Maximum allowable is 5 ounces)
- C. For the following 25 minutes: 0 oz.
 (Maximum allowable is 1 ounce/minute)
- D. Spillage Details: None

FMVSS 301 STATIC ROLLOVER DATA



ROLLOVER SOLVENT COLLECTION TIME TABLE IN SECONDS

Test Phase	Rotation Time	Hold Time	Total Time
0 to 90	90	330	420
90 to 180	90	330	840
180 to 270	90	330	1260
270 to 360	90	330	1680

FMVSS NO. 301 ROLLOVER SPILLAGE TABLE

Test Phase	First 5 Minutes	Sixth Minute	Seventh Minute	Eighth Minute
0 to 90	0	0	0	N/A
90 to 180	0	0	0	N/A
180 to 270	0	0	0	N/A
270 to 360	0	0	0	N/A

ROLLOVER SOLVENT SPILLAGE LOCATION TABLE


Test Phase	Spillage Location
0 to 90	None
90 to 180	None
180 to 270	None
270 to 360	None

DATA SHEET NO. 14

DUMMY/VEHICLE TEMPERATURE AND HUMIDITY STABILIZATION DATA

Test Vehicle: 2014 Mazda 6 I Sport 4-door Sedan
Test Program: NCAP Side Impact

NHTSA No.: M20145402
Test Date: 1/14/14



**APPENDIX A
PHOTOGRAPHS**

TABLE OF PHOTOGRAPHS

No.	Description	Page
001	As-Delivered Right Front $\frac{3}{4}$ View of Test Vehicle	A-6
002	As-Delivered Left Rear $\frac{3}{4}$ View of Test Vehicle	A-6
003	Pre-Test Front View of Test Vehicle	A-7
004	Post-Test Front View of Test Vehicle	A-7
005	Pre-Test Left Front $\frac{3}{4}$ View of Test Vehicle	A-8
006	Post-Test Left Front $\frac{3}{4}$ View of Test Vehicle	A-8
007	Pre-Test Left Side View of Test Vehicle	A-9
008	Post-Test Left Side View of Test Vehicle	A-9
009	Pre-Test Left Rear $\frac{3}{4}$ View of Test Vehicle	A-10
010	Post-Test Left Rear $\frac{3}{4}$ View of Test Vehicle	A-10
011	Pre-Test Rear View of Test Vehicle	A-11
012	Post-Test Rear View of Test Vehicle	A-11
013	Pre-Test Right Side View of Test Vehicle	A-12
014	Post-Test Right Side View of Test Vehicle	A-12
015	Pre-Test Overhead View of Test Area	A-13
016	Post-Test Overhead View of Test Area	A-13
017	Pre-Test Left Side View of MDB Positioned Against Side of Test Vehicle	A-14
018	Pre-Test Right Side View of MDB Positioned Against Side of Test Vehicle	A-14
019	Pre-Test Close-up View of Impact Point Target	A-15
020	Post-Test Close-up View of Impact Point Target	A-15
021	Pre-Test Left Front Door Latch Close-up	A-16
022	Post-Test Left Front Door Latch Close-up	A-16
023	Pre-Test Left Rear Door Latch Close-up	A-17
024	Post-Test Left Rear Door Latch Close-up	A-17
025	Pre-Test Front Close-up View of Driver Dummy	A-18
026	Post-Test Front Close-up View of Driver Dummy	A-18
027	Pre-Test Left Side View of Driver Dummy Showing Belt and Chalking	A-19
028	Pre-Test Left Side View of Driver Dummy Shoulder and Door Top	A-19
029	Post-Test Left Side View of Driver Dummy Shoulder and Door Top	A-20
030	Pre-Test Frontal View of Driver Seat Back Prior to Dummy Positioning	A-20
031	Pre-Test Frontal View of Driver Dummy Head and Shoulders in Relation to Head Restraint	A-21
032	Pre-Test Frontal View of Driver Seat Pan Prior to Dummy Positioning	A-21
033	Pre-Test Overhead View of Driver Dummy Thighs on Seat Pan	A-22
034	Pre-Test Placement of Driver Dummy's Feet	A-22
035	Pre-Test View of Belt Anchorage for Driver Dummy	A-23
036	Pre-Test Left Side View of Steering Wheel	A-23

TABLE OF PHOTOGRAPHS (CONTINUED)

No.	Description	Page
037	View of Disengaged Parking Brake	A-24
038	Pre-Test View of Parking Brake	A-24
039	Pre-Test Close-Up Left Side View of Driver Seat Track	A-25
040	Pre-Test Close-Up Left Side View of Driver Seat Back	A-25
041	Pre-Test Close-Up View of Driver Seat Back or Head Restraint	A-26
042	Pre-Test Driver Dummy and Door Clearance View	A-26
043	Post-Test Driver Dummy and Door Clearance View	A-27
044	Pre-Test Right Side View of Driver Dummy and Front Seat of Occupant Compartment	A-27
045	Post-Test Right Side View of Driver Dummy and Front Seat of Occupant Compartment	A-28
046	Pre-Test Driver Inner Door Panel View	A-28
047	Post-Test Driver Inner Door Panel View	A-29
048	Post-Test Driver Dummy Close-Up Head Contact with Vehicle View	A-29
049	Post-Test Driver Dummy Close-Up Head Contact with Side Airbag View	A-30
050	Post-Test Driver Dummy Close-Up Torso Contact with Vehicle Interior View	A-30
051	Post-Test Driver Dummy Close-Up Torso Contact with Side Airbag View	A-31
052	Post-Test Driver Dummy Close-Up Pelvis Contact View	A-31
053	Post-Test Driver Dummy Close-Up Pelvis Contact with Side Airbag View	A-32
054	Post-Test Driver Dummy Close-Up Knee Contact View	A-32
055	Pre-Test Left Side View of Passenger Dummy Showing Belt and Chalking	A-33
056	Pre-Test Left Side View of Passenger Dummy Shoulder and Door Top View	A-33
057	Post-Test Left Side View of Passenger Dummy Shoulder and Door Top View	A-34
058	Pre-Test Frontal View of Rear Passenger Seat Back Prior to Dummy Positioning	A-34
059	Pre-Test Frontal View of Rear Passenger Dummy Head and Shoulders in Relation to Head Restraint	A-35
060	Pre-Test Overhead View of Rear Passenger Seat Pan Prior to Dummy Positioning	A-35
061	Pre-Test Overhead View of Rear Passenger Dummy Thighs on Seat Pan	A-36
062	Pre-Test View of Rear Passenger Dummy's Neck Showing Position of Adjustable Neck Bracket	A-36
063	Pre-Test View of Rear Passenger Dummy's Head Showing Dummy's Head is Level	A-37
064	Pre-Test Placement of Rear Passenger Dummy's Feet	A-37
065	Pre-Test View of Belt Anchorage for Rear Passenger Dummy	A-38
066	Pre-Test Close-Up Left Side View of Rear Passenger Seat Track	A-38
067	Pre-test Close-Up Left Side View of Rear Passenger Seat Back	A-39

TABLE OF PHOTOGRAPHS (CONTINUED)

No.	Description	Page
068	Pre-Test Close-Up View of Rear Passenger Seat Back or Head Restraint	A-39
069	Pre-Test Passenger Dummy and Door Clearance View	A-40
070	Post-Test Passenger Dummy and Door Clearance View	A-40
071	Pre-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment	A-41
072	Post-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment	A-41
073	Pre-Test Passenger Inner Door Panel View	A-42
074	Post-Test Passenger Inner Door Panel View	A-42
075	Post-Test Rear Passenger Dummy Close-Up Head Contact with Vehicle View	A-43
076	Post-Test Rear Passenger Dummy Close-Up Head Contact with Side Airbag View	A-43
077	Post-Test Rear Passenger Dummy Close-Up Torso Contact with Vehicle Interior View	A-44
078	Post-Test Rear Passenger Dummy Close-Up Torso Contact with Side Airbag View	A-44
079	Post-Test Rear Passenger Dummy Close-Up Pelvis Contact View	A-45
080	Post-Test Rear Passenger Dummy Close-Up Pelvis Contact with Side Airbag View	A-45
081	Post-Test Rear Passenger Dummy Close-Up Knee Contact View	A-46
082	Pre-Test View of Fuel Filler Cap or Fuel Filler Neck	A-46
083	Post-Test View of Fuel Filler Cap or Fuel Filler Neck	A-47
084	Pre-Test Front View of MDB Impactor Face	A-47
085	Post-Test Front View of MDB Impactor Face	A-48
086	Pre-Test Top View of MDB Impactor Face	A-48
087	Post-Test Top View of MDB Impactor Face	A-49
088	Pre-Test Left Side View of MDB Impactor Face	A-49
089	Post-Test Left Side View of MDB Impactor Face	A-50
090	Pre-Test Right Side View of MDB Impactor Face	A-50
091	Post-Test Right Side View of MDB Impactor Face	A-51
092	Close-Up View of Vehicle's Certification Label	A-51
093	Close-Up View of Vehicle's Tire Information Placard or Label	A-52
094	Pre-Test Ballast View	A-52
095	Post-Test Primary and Redundant Speed Trap Read-Out	A-53

TABLE OF PHOTOGRAPHS (CONTINUED)

No.	Description	Page
096	FMVSS No. 301 Static Rollover 0 Degrees	A-53
097	FMVSS No. 301 Static Rollover 90 Degrees	A-54
098	FMVSS No. 301 Static Rollover 180 Degrees	A-54
099	FMVSS No. 301 Static Rollover 270 Degrees	A-55
100	FMVSS No. 301 Static Rollover 360 Degrees	A-55
101	Impact Event	A-56
102	Monroney Label	A-56
103	Driver Head Restraint Use and Adjustment Information from Vehicle Owner's Manual	A-57
104	Left Rear Passenger Head Restraint Use and Adjustment Information from Vehicle Owner's Manual	A-57



001 As-Delivered Right Front $\frac{3}{4}$ View of Test Vehicle



002 As-Delivered Left Rear $\frac{3}{4}$ View of Test Vehicle



003 Pre-Test Front View of Test Vehicle



004 Post-Test Front View of Test Vehicle



005 Pre-Test Left Front $\frac{3}{4}$ View of Test Vehicle



006 Post-Test Left Front $\frac{3}{4}$ View of Test Vehicle



007 Pre-Test Left Side View of Test Vehicle



008 Post-Test Left Side View of Test Vehicle



009 Pre-Test Left Rear $\frac{3}{4}$ View of Test Vehicle



010 Post-Test Left Rear $\frac{3}{4}$ View of Test Vehicle



011 Pre-Test Rear View of Test Vehicle




012 Post-Test Rear View of Test Vehicle




013 Pre-Test Right Side View of Test Vehicle



014 Post-Test Right Side View of Test Vehicle



015 Pre-Test Overhead View of Test Area



016 Post-Test Overhead View of Test Area



017 Pre-Test Left Side View of MDB Positioned Against Side of Test Vehicle



018 Pre-Test Right Side View of MDB Positioned Against Side of Test Vehicle



019 Pre-Test Close-up View of Impact Point Target



020 Post-Test Close-up View of Impact Point Target



021 Pre-Test Left Front Door Latch Close-up



022 Post-Test Left Front Door Latch Close-up



023 Pre-Test Left Rear Door Latch Close-up



024 Post-Test Left Rear Door Latch Close-up



025 Pre-Test Front Close-up View of Driver Dummy



026 Post-Test Front Close-up View of Driver Dummy




027 Pre-Test Left Side View of Driver Dummy Showing Belt and Chalking



028 Pre-Test Left Side View of Driver Dummy Shoulder and Door Top



029 Post-Test Left Side View of Driver Dummy Shoulder and Door Top



030 Pre-Test Frontal View of Driver Seat Back Prior to Dummy Positioning



031 Pre-Test Frontal View of Driver Dummy Head and Shoulders in Relation to Head Restraint



032 Pre-Test Frontal View of Driver Seat Pan Prior to Dummy Positioning



033 Pre-Test Overhead View of Driver Dummy Thighs on Seat Pan



034 Pre-Test Placement of Driver Dummy Feet



035 Pre-Test View of Belt Anchorage for Driver Dummy



036 Pre-Test Left Side View of Steering Wheel




037 View of Disengaged Parking Brake



038 Pre-Test View of Parking Brake



039 Pre-Test Close-Up Left Side View of Driver Seat Track



040 Pre-Test Close-Up Left Side View of Driver Seat Back



041 Pre-Test Close-Up View of Driver Seat Back or Head Restraint




042 Pre-Test Driver Dummy and Door Clearance View



043 Post-Test Driver Dummy and Door Clearance View




044 Pre-Test Right Side View of Driver Dummy and Front Seat of Occupant Compartment




045 Post-Test Right Side View of Driver Dummy and Front Seat of Occupant Compartment



046 Pre-Test Driver Inner Door Panel View




047 Post-Test Driver Inner Door Panel View



048 Post-Test Driver Dummy Close-Up Head Contact with Vehicle View



049 Post-Test Driver Dummy Close-Up Head Contact with Side Airbag View



050 Post-Test Driver Dummy Close-Up Torso Contact with Vehicle Interior View



051 Post-Test Driver Dummy Close-Up Torso Contact with Side Airbag View



052 Post-Test Driver Dummy Close-Up Pelvis Contact View



053 Post-Test Driver Dummy Close-Up Pelvis Contact with Side Airbag View



054 Post-Test Driver Dummy Close-Up Knee Contact View



055 Pre-Test Left Side View of Passenger Dummy Showing Belt and Chalking



056 Pre-Test Left Side View of Passenger Dummy Shoulder and Door Top View



057 Post-Test Left Side View of Passenger Dummy Shoulder and Door Top View




058 Pre-Test Frontal View of Rear Passenger Seat Back Prior to Dummy Positioning



059 Pre-Test Frontal View of Rear Passenger Dummy Head and Shoulders in Relation to Head Restraint



060 Pre-Test Overhead View of Rear Passenger Seat Pan Prior to Dummy Positioning




061 Pre-Test Overhead View of Rear Passenger Dummy Thighs on Seat Pan



062 Pre-Test View of Rear Passenger Dummy Neck Showing Position of Adjustable Neck Bracket



063 Pre-Test View of Rear Passenger Dummy Head Showing Dummy Head is Level



064 Pre-Test Placement of Rear Passenger Dummy Feet



065 Pre-Test View of Belt Anchorage for Rear Passenger Dummy



066 Pre-Test Close-Up Left Side View of Rear Passenger Seat Track



067 Pre-test Close-Up Left Side View of Rear Passenger Seat Back



068 Pre-Test Close-Up View of Rear Passenger Seat Back or Head Restraint



069 Pre-Test Passenger Dummy and Door Clearance View



070 Post-Test Passenger Dummy and Door Clearance View



071 Pre-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment




072 Post-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment



073 Pre-Test Passenger Inner Door Panel View



074 Post-Test Passenger Inner Door Panel View




075 Post-Test Rear Passenger Dummy Close-Up Head Contact with Vehicle View



076 Post-Test Rear Passenger Dummy Close-Up Head Contact with Side Airbag View




077 Post-Test Rear Passenger Dummy Close-Up Torso Contact with Vehicle Interior View



078 Post-Test Rear Passenger Dummy Close-Up Torso Contact with Side Airbag View



079 Post-Test Rear Passenger Dummy Close-Up Pelvis Contact View



080 Post-Test Rear Passenger Dummy Close-Up Pelvis Contact with Side Airbag View



081 Post-Test Rear Passenger Dummy Close-Up Knee Contact View



082 Pre-Test View of Fuel Filler Cap or Fuel Filler Neck



083 Post-Test View of Fuel Filler Cap or Fuel Filler Neck



084 Pre-Test Front View of MDB Impactor Face



085 Post-Test Front View of MDB Impactor Face



086 Pre-Test Top View of MDB Impactor Face



087 Post-Test Top View of MDB Impactor Face



088 Pre-Test Left Side View of MDB Impactor Face



089 Post-Test Left Side View of MDB Impactor Face




090 Pre-Test Right Side View of MDB Impactor Face




091 Post-Test Right Side View of MDB Impactor Face




092 Close-Up View of Vehicle Certification Label



093 Close-Up View of Vehicle Tire Information Placard or Label



094 Pre-Test Ballast View



095 Post-Test Primary Speed Trap Read-Out




096 FMVSS No. 301 Static Rollover 0 Degrees



097 FMVSS No. 301 Static Rollover 90 Degrees



098 FMVSS No. 301 Static Rollover 180 Degrees



099 FMVSS No. 301 Static Rollover 270 Degrees



100 FMVSS No. 301 Static Rollover 360 Degrees



101 Impact Event

Fuel Economy and Environment

30 MPG combined city/hwy
26 city / 38 highway
3.3 gallons per 100 miles

You save \$2,750 in fuel costs over 5 years compared to the average new vehicle.

Annual fuel cost \$1,750

Fuel Economy & Greenhouse Gas Rating (EPA-est.) Smog Rating (EPA-est.)

1 8 10 1 5 10

fuel economy.gov

Scan for Vehicle Info and offers

PARTS CONTENT INFORMATION:

FOR VEHICLES IN THIS CARLINE: U.S./CANADIAN PARTS CONTENT: 95%

MAJOR SOURCES OF FOREIGN PARTS CONTENT: JAPAN 90%

NOTE: PARTS CONTENT DOES NOT INCLUDE FINAL ASSEMBLY, DISTRIBUTION, OR OTHER NON-PARTS COSTS.

FOR THIS VEHICLE: FINAL ASSEMBLY POINT: HONJU, JAPAN; COUNTRY OF ORIGIN: ENGINE: JAPAN; TRANSMISSION: JAPAN

The local is offered pursuant to the Federal Automobile Dealers' Use Act. Gasoline, License and Title fees, State and Local taxes, and Dealer Installed Options are not included.

2014 Mazda6

Model: **2014 MAZDA6 I SPORT**
Exterior Color: **LIQUID SILVER**
Interior Color: **BLACK**

STANDARD EQUIPMENT

ENGINE/MECHANICAL FEATURES

- SKYACTIV-G 2.5L DOHC 4-CYL. ENGINE
- SKYACTIV-DRIVE 6-SPEED SPORT AT
- 184 HP/SEPOWER: 185 LB-FT TORQUE
- FRONT-WHEEL DRIVE

EXTERIOR FEATURES

- 17-INCH ALLOY WHEELS
- P225S5 R17 ALL-SEASON TIRES
- VARIABLE-INTERMITTENT WIPERS
- POWER SIDE MIRRORS W/TURN LAMPS
- DUAL EXHAUST W/RIGHT OUTLETS

INTERIOR FEATURES

- CLOTH-TRIMMED SPORT SEATS
- 6-WAY MANUAL DRIVER'S SEAT
- TILT & TELESCOPIC STEERING COLUMN
- 5.8" COLOR TOUCH-SCREEN DISPLAY
- REARVIEW CAMERA
- AM/FM/CD/MP3/AUX & SPEAKER AUDIO
- USB AUDIO INPUT & HD RADIO
- BLUETOOTH HANDS-FREE PHONE/AUDIO
- STEERING WHEEL MOUNTED CONTROLS
- LEATHER WRAPPED STEERING WHEEL
- CRUISE CONTROL

SAFETY AND SECURITY FEATURES

- 30-MONTH/50,000-MILE BUMPER-TO-BUMPER WARRANTY
- 60-MONTH/100,000-MILE POWERTRAIN WARRANTY
- 24-HOUR ROADSIDE ASSISTANCE
- 5-PASSENGER 3-POINT SAFETY BELTS
- LATCH CHILD SAFETY SEAT ANCHORS
- ANTI-THEFT ENGINE IMMOBILIZER
- TIRE PRESSURE MONITORING SYSTEM

EXTERIOR FEATURES (continued)

- HALOGEN HEADLIGHTS W/AUTO OFF
- HALOGEN DAYTIME RUNNING LIGHTS
- LED COMBINATION TAILLIGHTS
- IN-GLASS ANTENNA
- REAR WINDOW DEFROSTER

INTERIOR FEATURES (continued)

- MID WTRIP COMPUTER
- POWER AUTOMATIC DOOR LOCKS
- POWER WINDOWS W/DRIVER ONE-TOUCH
- REMOTE KEYLESS ENTRY
- PUSH BUTTON ENGINE START
- AIR CONDITIONING W/POLLEN FILTER
- DUAL VANITY MIRRORS
- CENTER ARMREST W/COVERED STORAGE
- 60/40 SPLIT FOLD-DOWN REAR SEAT
- REAR SEAT AIRBAGS W/CHILD SAFETY SEAT ANCHORS

SAFETY AND SECURITY FEATURES (continued)

- ANTI-LOCK BRAKE SYSTEM (ABS WITH EBD & BRAKE ASSIST)
- DYNAMIC STABILITY CONTROL (DSC)
- TRACTION CONTROL SYSTEM (TCS)
- HILL LAUNCH ASSIST
- ADVANCED DUAL FRONT AIR BAGS
- FRONT SIDE-IMPACT AIR BAGS
- FRONT & REAR SIDE AIR CURTAINS
- SKYACTIV-BODY RING STRUCTURE

MSRP \$22,695

Total Vehicle and Options \$22,698
Delivery, Processing and Handling Fee \$795

Total MSRP \$23,490

GOVERNMENT 5-STAR SAFETY RATINGS

Overall Vehicle Score Not Rated
Based on the combined ratings of frontal, side and rollover. Should ONLY be compared to other vehicles of similar size and weight.

Frontal Crash	Driver Passenger	Not Rated
Based on the risk of injury in a frontal impact. Should ONLY be compared to other vehicles of similar size and weight.		
Side Crash	Front seat Rear seat	Not Rated
Based on the risk of injury in a side impact.		
Rollover		Not Rated
Based on the risk of rollover in a single vehicle crash.		

Star ratings range from 1 to 5 stars (★ ★ ★ ★ ★) with 5 being the highest. Source: National Highway Traffic Safety Administration (NHTSA) www.safercar.gov or 1-888-327-4236

SOLD TO: 61420 HOLIDAY MAZDA 390 N. ROLLING MEADOWS RD. FOND DU LAC, WI 54937

SHIP TO: 61420 DY HOLIDAY MAZDA 390 N. ROLLING MEADOWS RD. FOND DU LAC, WI 54937

JM1GJ1U68E1143182

MazdaUSA.COM

102 Monroney Label

Head Restraints


Your vehicle is equipped with head restraints on all outboard seats and the rear center seat. The head restraints are intended to help protect you and the passengers from neck injury.

⚠ WARNING
Always drive with the head restraints installed when seats are being used and make sure they are properly adjusted.


Driving with the head restraints adjusted too low or removed is dangerous. With no support behind your head, your neck could be seriously injured in a collision.

Height adjustment


To raise a head restraint, pull it up to the desired position.
To lower the head restraint, press the stop-catch release, then push the head restraint down.
Adjust the head restraint so that the center is even with the top of the passenger's ears.




Front outboard seat



Rear outboard seat



Rear center seat



Removal/Installation

To remove the head restraint, pull it up while pressing the stop-catch.
To install the head restraint, insert the legs into the holes while pressing the stop-catch.

⚠ WARNING

Always drive with the head restraints installed when seats are being used and make sure they are properly installed.

Driving with the head restraints not installed is dangerous. With no support behind your head, your neck could be seriously injured in a collision.

103 Driver Head Restraint Use and Adjustment Information from Vehicle Owner Manual

Head Restraints


Your vehicle is equipped with head restraints on all outboard seats and the rear center seat. The head restraints are intended to help protect you and the passengers from neck injury.

⚠ WARNING
Always drive with the head restraints installed when seats are being used and make sure they are properly adjusted.


Driving with the head restraints adjusted too low or removed is dangerous. With no support behind your head, your neck could be seriously injured in a collision.

Height adjustment


To raise a head restraint, pull it up to the desired position.
To lower the head restraint, press the stop-catch release, then push the head restraint down.
Adjust the head restraint so that the center is even with the top of the passenger's ears.




Front outboard seat



Rear outboard seat



Rear center seat



Removal/Installation

To remove the head restraint, pull it up while pressing the stop-catch.
To install the head restraint, insert the legs into the holes while pressing the stop-catch.

⚠ WARNING

Always drive with the head restraints installed when seats are being used and make sure they are properly installed.

Driving with the head restraints not installed is dangerous. With no support behind your head, your neck could be seriously injured in a collision.

104 Left Rear Passenger Head Restraint Use and Adjustment Information from Vehicle Owner Manual

APPENDIX B
VEHICLE AND DUMMY RESPONSE DATA PLOTS

TABLE OF DATA PLOTS

Driver & Passenger Dummy Instrumentation Plots

No.	Description	Page
1	Driver Head Acceleration (X) Primary vs. Time	B-5
2	Driver Head Acceleration (Y) Secondary vs. Time	B-5
3	Driver Head Acceleration (Z) Primary vs. Time	B-5
4	Driver Head Resultant Acceleration Primary vs. Time	B-5
5	Driver Upper Thorax Rib Deflection (Y) vs. Time	B-6
6	Driver Middle Thorax Rib Deflection (Y) vs. Time	B-6
7	Driver Lower Thorax Rib Deflection (Y) vs. Time	B-6
8	Driver Thorax Rib Deflection Maximum vs. Time	B-6
9	Driver Anterior Abdominal Force (Y) vs. Time	B-7
10	Driver Middle Abdominal Force (Y) vs. Time	B-7
11	Driver Posterior Abdominal Force (Y) vs. Time	B-7
12	Driver Total Abdominal Force (Y) vs. Time	B-7
13	Driver Pubic Symphysis Force (Y) vs. Time	B-8
14	Passenger Head Acceleration (X) Primary vs. Time	B-8
15	Passenger Head Acceleration (Y) Primary vs. Time	B-8
16	Passenger Head Acceleration (Z) Primary vs. Time	B-8
17	Passenger Head Resultant Acceleration Primary vs. Time	B-9
18	Passenger Lower Spine T12 Acceleration (X) vs. Time	B-9
19	Passenger Lower Spine T12 Acceleration (Y) vs. Time	B-9
20	Passenger Lower Spine T12 Acceleration (Z) vs. Time	B-9
21	Passenger Lower Spine T12 Resultant Acceleration vs. Time	B-10
22	Passenger Iliac Force on Impact Side (Y) vs. Time	B-10
23	Passenger Acetabulum Force on Impact Side (Y) vs. Time	B-10
24	Passenger Total Pelvic Force on Impact Side (Y) vs. Time	B-10

The following additional data can be obtained from the Research and Development section of the NHTSA website (<http://www.nhtsa.dot.gov>)

Additional Driver & Passenger Dummy Instrumentation Data

Driver Lower Spine T12 Acceleration (X)
Driver Lower Spine T12 Acceleration (Y)
Driver Lower Spine T12 Acceleration (Z)
Passenger Upper Thorax Rib Deflection (Y)
Passenger Middle Thorax Rib Deflection (Y)
Passenger Lower Thorax Rib Deflection (Y)
Passenger Upper Abdomen Rib Deflection (Y)
Passenger Lower Abdomen Rib Deflection (Y)
Driver Head Acceleration Redundant (X)
Driver Head Acceleration Redundant (Y)
Driver Head Acceleration Redundant (Z)
Passenger Head Acceleration Redundant (X)
Passenger Head Acceleration Redundant (Y)
Passenger Head Acceleration Redundant (Z)

Vehicle Instrumentation Data

Vehicle Center of Gravity Acceleration (X)
Vehicle Center of Gravity Acceleration (Y)
Vehicle Center of Gravity Acceleration (Z)
Right Side Sill at Front Seat Acceleration (X)
Right Side Sill at Front Seat Acceleration (Y)
Right Side Sill at Front Seat Acceleration (Z)
Right Side Sill at Rear Seat Acceleration (X)
Right Side Sill at Rear Seat Acceleration (Y)
Right Side Sill at Rear Seat Acceleration (Z)
Left Side Sill at Front Seat Acceleration (Y)
Left Side Sill at Rear Seat Acceleration (Y)
Lower A-Post Acceleration (Y)
Middle A-Post Acceleration (Y)
Lower B-Post Acceleration (Y)
Middle B-Post Acceleration (Y)
Front Seat Track Acceleration (Y)
Rear Seat Structure Acceleration (Y)
Right Rear Occupant Compartment Acceleration (Y)
Engine Block (X)
Engine Block (Y)
Rear Floorpan Above Axle Acceleration (X)
Rear Floorpan Above Axle Acceleration (Y)
Rear Floorpan Above Axle Acceleration (Z)

MDB Instrumentation Data

MDB Center of Gravity Acceleration (X)
MDB Center of Gravity Acceleration (Y)
MDB Center of Gravity Acceleration (Z)
MDB Rear Acceleration (X)
MDB Rear Acceleration (Y)
Left MDB Contact Switch
Right MDB Contact Switch

NHTSA


Test Lab: CTF

Test Number: 140114 (M20145402)

Test Date: 01/14/2014

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)




<Max>

2.08 g at 122.00 ms

<Min>

-17.45 g at 53.44 ms

CFC 1000




<Max>

31.47 g at 54.40 ms

<Min>

-6.11 g at 148.16 ms

CFC 1000




<Max>

9.42 g at 35.84 ms

<Min>

-10.55 g at 60.16 ms

CFC 1000



<Max>

37.46 g at 47.20 ms

<Min>

0.14 g at 7.60 ms

CFC 1000



NHTSA

Test Lab: CTF


Test Number: 140114 (M20145402)

Test Date: 01/14/2014

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)

Driver Upper Thorax Rib Deflection (Y) vs. Time (mm) vs. Time [ms]



<Max>


26.58 mm at 38.88 ms

<Min>

-1.56 mm at 16.00 ms

CFC_180

Driver Middle Thorax Rib Deflection (Y) vs. Time (mm) vs. Time [ms]



<Max>


24.15 mm at 38.72 ms

<Min>

0.00 mm at 1.20 ms

CFC_180

Driver Lower Thorax Rib Deflection (Y) vs. Time (mm) vs. Time [ms]



<Max>


27.11 mm at 38.88 ms

<Min>

0.00 mm at 2.88 ms

CFC_180

Driver Thorax Rib Deflection Maximum vs. Time (mm) vs. Time [ms]



<Max>

27.11 mm at 38.88 ms

<Min>

0.00 mm at 2.88 ms

CFC_180



NHTSA

Test Lab: CTF


Test Number: 140114 (M20145402)

Test Date: 01/14/2014

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)

Driver Anterior Abdominal Force (Y) vs. Time (N) vs. Time [ms]



<Max>


225.40 N at 47.20 ms

<Min>

-13.61 N at 10.72 ms

CFC_600

Driver Middle Abdominal Force (Y) vs. Time (N) vs. Time [ms]



<Max>


393.42 N at 34.96 ms

<Min>

-7.95 N at 214.32 ms

CFC_600

Driver Posterior Abdominal Force (Y) vs. Time (N) vs. Time [ms]



<Max>


581.22 N at 34.00 ms

<Min>

-6.73 N at 215.68 ms

CFC_600

Driver Total Abdominal Force (Y) vs. Time (N) vs. Time [ms]



<Max>

1,140.35 N at 35.28 ms

<Min>

-18.88 N at 10.88 ms

CFC_600



NHTSA


Test Lab: CTF

Test Number: 140114 (M20145402)

Test Date: 01/14/2014

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)




<Max>

122.47 N at 107.04 ms

<Min>

-1,942.96 N at 35.76 ms

CFC_600




<Max>

13.91 g at 157.60 ms

<Min>

-14.06 g at 48.72 ms

CFC_1000




<Max>

54.63 g at 58.96 ms

<Min>

-27.33 g at 154.96 ms

CFC_1000



<Max>

7.11 g at 82.48 ms

<Min>

-2.64 g at 16.48 ms

CFC_1000



NHTSA

Test Lab: CTF


Test Number: 140114 (M20145402)

Test Date: 01/14/2014

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)

Passenger Head Resultant Acceleration Primary vs. Time (g) vs. Time [ms]



<Max>


55.51 g at 58.96 ms

<Min>

0.03 g at -19.84 ms

CFC_1000

Passenger Lower Spine T12 Acceleration (X) vs. Time (g) vs. Time [ms]



<Max>


4.45 g at 176.08 ms

<Min>

-9.07 g at 47.52 ms

CFC_180

Passenger Lower Spine T12 Acceleration (Y) vs. Time (g) vs. Time [ms]



<Max>


62.85 g at 47.36 ms

<Min>

-6.22 g at 175.84 ms

CFC_180

Passenger Lower Spine T12 Acceleration (Z) vs. Time (g) vs. Time [ms]



<Max>

7.90 g at 70.80 ms

<Min>

-10.97 g at 47.68 ms

CFC_180



NHTSA

Test Lab: CTF


Test Number: 140114 (M20145402)

Test Date: 01/14/2014

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)

Passenger Lower Spine T12 Resultant Acceleration vs. Time (g) vs. Time [ms]



<Max>


64.37 g at 47.44 ms

<Min>

0.00 g at -17.28 ms

CFC_180

Passenger Iliac Force on Impact Side (Y) vs. Time (N) vs. Time [ms]



<Max>


554.84 N at 49.84 ms

<Min>

-61.79 N at 67.68 ms

CFC_600

Passenger Acetabulum Force on Impact Side (Y) vs. Time (N) vs. Time [ms]



<Max>


1,357.40 N at 44.88 ms

<Min>

-70.86 N at 58.48 ms

CFC_600

Passenger Total Pelvic Force on Impact Side (Y) vs. Time (N) vs. Time [ms]



<Max>

1,691.93 N at 45.52 ms

<Min>

-83.45 N at 65.84 ms

CFC_600



APPENDIX C
DUMMY PERFORMANCE CALIBRATION TEST DATA

TABLE OF CALIBRATION MEASUREMENTS AND PLOTS

ES-2re (Driver) Dummy

Description

Table 1. External Measurements

Table 2. Head Drop Test

- Resultant Head Acceleration (G's) vs. Time (ms)
- Head (X) Acceleration (G's) vs. Time (ms)
- Head (Y) Acceleration (G's) vs. Time (ms)
- Head (Z) Acceleration (G's) vs. Time (ms)

Table 3 Neck Pendulum Test

- Pendulum Velocity (m/s) vs. Time (ms)
- Flexion Angle (°) vs. Time (ms)
- Potentiometer A (°) vs. Time (ms)
- Potentiometer B (°) vs. Time (ms)
- Potentiometer C (°) vs. Time (ms)

Table 4. Shoulder Impact Test

- Impactor Acceleration (G's) vs. Time (ms)

Table 5. Thorax – Upper Rib Drop Test

- Upper Rib Displacement @ 459 mm Drop Height (mm) vs. Time (ms)
- Upper Rib Displacement @ 815 mm Drop Height (mm) vs. Time (ms)

Table 6. Thorax – Middle Rib Drop Test

- Middle Rib Displacement @ 459 mm Drop Height (mm) vs. Time (ms)
- Middle Rib Displacement @ 815 mm Drop Height (mm) vs. Time (ms)

Table 7. Thorax – Lower Rib Drop Test

- Lower Rib Displacement @ 459 mm Drop Height (mm) vs. Time (ms)
- Lower Rib Displacement @ 815 mm Drop Height (mm) vs. Time (ms)

Table 8. Thorax – Full Body Impact Test

- Pendulum Acceleration (G's) vs. Time (ms)
- Impactor Force (kN) vs. Time (ms)
- Upper Rib Displacement (mm) vs. Time (ms)
- Middle Rib Displacement (mm) vs. Time (ms)
- Lower Rib Displacement (mm) vs. Time (ms)

Table 9. Abdomen Impact Test

- Impactor Force (kN) vs. Time (ms)
- Total Abdomen Force (kN) vs. Time (ms)
- Front Abdomen Force (kN) vs. Time (ms)
- Middle Abdomen Force (kN) vs. Time (ms)
- Rear Abdomen Force (kN) vs. Time (ms)

Table 10. Lumbar Spine Flexion Test

- Pendulum Velocity (m/s) vs. Time (ms)
- Spine Flexion Angle (°) vs. Time (ms)
- Potentiometer A (°) vs. Time (ms)
- Potentiometer B (°) vs. Time (ms)
- Potentiometer C (°) vs. Time (ms)

Table 11. Pelvis Impact Test

- Pendulum Acceleration (G's) vs. Time (ms)
- Impactor Force (kN) vs. Time (ms)
- Pubic Symphysis (Y) Force (kN) vs. Time (ms)

TABLE OF CALIBRATION MEASUREMENTS AND PLOTS

SID-IIs (Rear Passenger) Dummy

Description

Table 1. External Measurements

Table 2. Head Drop Test

Resultant Head Acceleration (G's) vs. Time (ms)

Head (X) Acceleration (G's) vs. Time (ms)

Head (Y) Acceleration (G's) vs. Time (ms)

Head (Z) Acceleration (G's) vs. Time (ms)

Table 3. Lateral Neck Pendulum Test

Pendulum Velocity (m/s) vs. Time (ms)

Flexion Angle (°) vs. Time (ms)

Moment About Occipital Condyle (Nm) vs. Time (ms)

Table 4. Shoulder Impact Test

Impactor Acceleration (G's) vs. Time (ms)

Shoulder Displacement (mm) vs. Time (ms)

Upper Spine Acceleration (G's) vs. Time (ms)

Table 5. Thorax (With Arm) Impact Test

Impactor Acceleration (G's) vs. Time (ms)

Shoulder Displacement (mm) vs. Time (ms)

Upper Rib Displacement (mm) vs. Time (ms)

Middle Rib Displacement (mm) vs. Time (ms)

Lower Rib Displacement (mm) vs. Time (ms)

Upper Spine Acceleration (G's) vs. Time (ms)

Lower Spine Acceleration (G's) vs. Time (ms)

Table 6. Thorax (Without Arm) Impact Test

Impactor Acceleration (G's) vs. Time (ms)

Upper Rib Displacement (mm) vs. Time (ms)

Middle Rib Displacement (mm) vs. Time (ms)

Lower Rib Displacement (mm) vs. Time (ms)

Upper Spine Acceleration (G's) vs. Time (ms)

Lower Spine Acceleration (G's) vs. Time (ms)

Table 7. Abdomen Impact Test

Impactor Acceleration (G's) vs. Time (ms)

Upper Abdominal Rib Displacement (mm) vs. Time (ms)

Lower Abdominal Rib Displacement (mm) vs. Time (ms)

Lower Spine Acceleration (G's) vs. Time (ms)

Table 8. Pelvis Plug Quasi-Static Test (Optional*)

Table 9. Pelvis Acetabulum Impact Test

Impactor Acceleration (G's) vs. Time (ms)

Pelvis (Y) Acceleration (G's) vs. Time (ms)

Acetabulum Force (N) vs. Time (ms)

Table 10. Pelvis Iliac Impact Test

Impactor Acceleration (G's) vs. Time (ms)

Pelvis (Y) Acceleration (G's) vs. Time (ms)


Iliac Force (N) vs. Time (ms)

**Pre-Test Calibration Sheets
Driver S/N F030**

Transportation Research Center Inc.
572U ES-2re Dummy
External Dimensions
Serial No. F030 Calibration No. 19
01/13/14

Symbol	Description	Specification	Results	Pass
		mm	mm	
1	Sitting Height	900.0 - 918.0	910	Yes
2	Seat to Shoulder Joint	558.0 - 572.0	560	Yes
3	Seat to Lower Face of Thoracic Spine Box	346.0 - 356.0	350	Yes
4	Seat to Hip Joint (center of bolt)	97.0 - 103.0	98	Yes
5	Sole to Seat, Sitting	433.0 - 451.0	447	Yes
6	Head Width	152.0 - 158.0	155	Yes
7	Shoulder/Arm Width	461.0 - 479.0	470	Yes
8	Thorax Width	322.0 - 332.0	326	Yes
9	Abdomen Width	273.0 - 287.0	282	Yes
10	Pelvis Lap Width	359.0 - 373.0	367	Yes
11	Head Depth	196.0 - 206.0	200	Yes
12	Thorax Depth	262.0 - 272.0	267	Yes
13	Abdomen Depth	194.0 - 204.0	200	Yes
14	Pelvis Depth	235.0 - 245.0	240	Yes
15	Back of Buttocks to Hip Joint (center of bolt)	150.0 - 160.0	159	Yes
16	Back of Buttocks to Front of Knee	597.0 - 615.0	606	Yes

Technician



Approved




Baseline 10/07/05


Transportation Research Center Inc.

Left Lateral Head Drop
ES-2re Serial No. F030 Certification No. 19-2
Test Date: 1/13/2014


Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	34 %	Yes
Peak Resultant Acceleration	125 - 155 g	146.9 g	Yes
Peak Longitudinal Acceleration	(-15) - 15 g	6.1 g	Yes
Is Resultant Acceleration Curve Unimodal within 15% of Main Pulse?	Yes	Yes	Yes

Test meets specifications.

Comments:

Technician 

Specification Source: NHTSA Final Rule 8/15/2008

Approved 

01.13.2014 14:14:51 360




Transportation Research Center Inc.


Left Lateral Head Drop

ES-2re Serial No. F030 Certification No. 19-2


Test Date: 1/13/2014




Filter Class: CFC_1000
Max: 6.1 g at 4.3 ms
Min: -1.3 g at 9.9 ms



Filter Class: CFC_1000
Max: 122.8 g at 2.2 ms
Min: -5.0 g at 5.7 ms



Filter Class: CFC_1000
Max: 80.6 g at 2.2 ms
Min: -2.0 g at 9.2 ms



Filter Class: CFC_1000
Max: 146.9 g at 2.2 ms
Min: 0.1 g at -0.5 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 14:15:01 360



Transportation Research Center Inc.

Left Lateral Neck

ES-2re Serial No. F030 Certification No. 19-1


Test Date: 1/13/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.1 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Pendulum Integrated Velocity Change within Corridor	Yes	Yes	Yes
Pendulum Velocity	(-3.3) - (-3.5) m/s	-3.36 m/s	Yes
Maximum Headform Flexion			
Peak	(-49) - (-59) deg	-52.7 deg	Yes
Time of Peak	54 - 66 ms	56.3 ms	Yes
Headform Flexion Decay			
- Peak to Zero	53 - 88 ms	66.5 ms	Yes


Test meets specifications.

Comments:

Technician



Approved



Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 14:01:19 1310




Transportation Research Center Inc.


Left Lateral Neck

ES-2re Serial No. F030 Certification No. 19-1

Test Date: 1/13/2014



Filter Class: CFC_60
Max: 34.3 g at 10.1 ms
Min: -6.3 g at 45.7 ms



Filter Class: CFC_60
Max: 3.6 m/s at 37.0 ms
Min: 0.0 m/s at 0.0 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 14:01:29 1310




Transportation Research Center Inc.


Left Lateral Neck

ES-2re Serial No. F030 Certification No. 19-1


Test Date: 1/13/2014




Filter Class: CFC_180
Max: 16.2 ° at 169.9 ms
Min: -35.4 ° at 61.8 ms



Filter Class: CFC_180
Max: 17.3 ° at 168.9 ms
Min: -31.4 ° at 57.9 ms



Filter Class: CFC_180
Max: 11.4 ° at 163.0 ms
Min: -17.8 ° at 56.2 ms



Filter Class: CFC_180
Max: 27.5 ° at 168.9 ms
Min: -52.7 ° at 56.3 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 14:01:30 1310



Transportation Research Center Inc.

Left Lateral Shoulder

ES-2re Serial No. F030 Certification No. 19-1


Test Date: 1/13/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.8 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Test Probe Velocity	4.2 - 4.4 m/s	4.34 m/s	Yes
Test Probe Acceleration	(-7.5) - (-10.5) g	-10.01 g	Yes


Test meets specifications.

Comments:

Technician



Approved




Specification Source: NHTSA final rule 8/15/2008

01.13.2014 17:40:12 597



Transportation Research Center Inc.

Left Lateral Shoulder
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014



Filter Class: CFC_180
Max: 0.6 g at 54.6 ms
Min: -10.0 g at 11.5 ms

Specification Source: NHTSA final rule 8/15/2008

01.13.2014 17:40:26 597



Transportation Research Center Inc.

4.0 m/s Upper Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	22.0 °C	Yes
Relative Humidity	10 - 70 %	35 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	47.8 mm	Yes

Test meets specifications.

Comments:

Drop Height: 816

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 14:59:43 745



Transportation Research Center Inc.

4.0 m/s Upper Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014



Filter Class: CFC_180
Max: 47.8 mm at 27.0 ms
Min: -4.3 mm at 59.4 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 14:59:55 745



Transportation Research Center Inc.

3.0 m/s Upper Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014


Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	35 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	36.7 mm	Yes

Test meets specifications.

Comments:


Drop Height: 462

Technician



Specification Source: NHTSA Final Rule 8/15/2008

Approved




01.13.2014 15:06:01 939



Transportation Research Center Inc.

3.0 m/s Upper Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014



Filter Class: CFC_180
Max: 36.7 mm at 29.0 ms
Min: -3.7 mm at 62.1 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 15:06:20 939



Transportation Research Center Inc.

4.0 m/s Center Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014


Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	48.7 mm	Yes

Test meets specifications.

Comments:


Drop Height: 816

Technician



Specification Source: NHTSA Final Rule 8/15/2008

Approved




01.13.2014 15:21:51 748



Transportation Research Center Inc.

4.0 m/s Center Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014



Filter Class: CFC_180
Max: 48.7 mm at 26.9 ms
Min: -4.5 mm at 59.4 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 15:22:02 748



Transportation Research Center Inc.

3.0 m/s Center Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014


Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	22.0 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	37.1 mm	Yes

Test meets specifications.


Comments:

Drop Height: 462

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 15:31:47 946



Transportation Research Center Inc.

3.0 m/s Center Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014



Filter Class: CFC_180
Max: 37.1 mm at 28.2 ms
Min: -4.0 mm at 61.9 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 15:32:12 946



Transportation Research Center Inc.

4.0 m/s Lower Full Rib Module

ES-2re Serial No. F030 Certification No. 19-1

Test Date: 1/13/2014


Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	20.9 °C	Yes
Relative Humidity	10 - 70 %	40 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	47.9 mm	Yes

Test meets specifications.

Comments:

Drop Height: 816

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 15:39:23 732



Transportation Research Center Inc.

4.0 m/s Lower Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014



Filter Class: CFC_180
Max: 47.9 mm at 27.4 ms
Min: -4.0 mm at 60.0 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 15:39:36 732



Transportation Research Center Inc.

3.0 m/s Lower Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014


Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.8 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	36.9 mm	Yes

Test meets specifications.


Comments:

Drop Height: 462

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 15:47:23 929



Transportation Research Center Inc.

3.0 m/s Lower Full Rib Module
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014



Filter Class: CFC_180
Max: 36.9 mm at 29.0 ms
Min: -3.3 mm at 62.6 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 15:47:35 929



Transportation Research Center Inc.


Left Lateral Thorax
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
Impactor Velocity	5.4 - 5.60 m/s	5.464 m/s	Yes
Peak Impactor Force after 6 ms	(-5,100) - (-6,200) N	-5,590.8 N	Yes
Upper Rib Displacement	34 - 41 mm	36.0 mm	Yes
Center Rib Displacement	37 - 45 mm	39.2 mm	Yes
Lower Rib Displacement	37 - 44 mm	40.3 mm	Yes

Test meets specifications.

Comments:

Technician



Approved




Specification Source: Procedures based on Final Rule dated 8/15/2008.
Polarity in accordance with SAE J211.

01.13.2014 17:47:20 453



Transportation Research Center Inc.

Left Lateral Thorax
ES-2re Serial No. F030 Certification No. 19-1
Test Date: 1/13/2014



Filter Class: CFC_180
Max: 28.1 N at 63.4 ms
Min: -8,983.8 N at 4.0 ms

Specification Source: Procedures based on Final Rule dated 8/15/2008.
Polarity in accordance with SAE J211.

01.13.2014 17:47:56 453






Transportation Research Center Inc.

Left Lateral Thorax

ES-2re Serial No. F030 Certification No. 19-1

Test Date: 1/13/2014



Specification Source: Procedures based on Final Rule dated 8/15/2008.
Polarity in accordance with SAE J211.

01.13.2014 17:47:56 453



Transportation Research Center Inc.


Left Lateral Abdomen
ES-2re Serial No. F030 Certification No. 19-2
Test Date: 1/13/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.8 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Test Probe Velocity	3.9 - 4.1 m/s	3.94 m/s	Yes
Test Probe Force			
Peak	4,000 - 4,800 N	4,137.2 N	Yes
Time of Peak	10.6 - 13.0 ms	10.96 ms	Yes
Total Abdominal Force			
Peak	2,200 - 2,700 N	2,647.2 N	Yes
Time of Peak	10.0 - 12.3 ms	10.56 ms	Yes

Test meets specifications.

Comments:

Technician



Approved



Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 18:06:37 590




Transportation Research Center Inc.


Left Lateral Abdomen

ES-2re Serial No. F030 Certification No. 19-2

Test Date: 1/13/2014



Filter Class: CFC_180
Max: 18.1 g at 11.0 ms
Min: -0.3 g at -0.6 ms



Filter Class: CFC_180
Max: 4,137.2 N at 11.0 ms
Min: -73.8 N at -0.6 ms


Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 18:06:52 590




Transportation Research Center Inc.


Left Lateral Abdomen
ES-2re Serial No. F030 Certification No. 19-2
Test Date: 1/13/2014




Filter Class: CFC_600
Max: 699.6 N at 11.1 ms
Min: -9.3 N at 98.9 ms



Filter Class: CFC_600
Max: 1,051.6 N at 10.8 ms
Min: -1.8 N at 1.4 ms



Filter Class: CFC_600
Max: 907.3 N at 9.8 ms
Min: -13.1 N at 2.5 ms



Filter Class: CFC_600
Max: 2,647.2 N at 10.6 ms
Min: -9.5 N at 98.9 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 18:06:52 590




Transportation Research Center Inc.

Left Lateral Lumbar
ES-2re Serial No. F030 Certification No. 19-2
Test Date: 1/13/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	20.8 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Pendulum Integrated Velocity Change within Corridor	Yes	Yes	Yes
Pendulum Velocity	(-5.95) - (-6.15) m/s	-6.017 m/s	Yes
Maximum Headform Flexion			
Peak	(-45) - (-55) deg	-46.9 deg	Yes
Time of Peak	39 - 53 ms	43.0 ms	Yes
Headform Flexion Decay			
- Peak to Zero	37 - 57 ms	38.9 ms	Yes

Test meets specifications.

Comments:

Technician


Approved



Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 12:56:01 580




Transportation Research Center Inc.

Left Lateral Lumbar
ES-2re Serial No. F030 Certification No. 19-2
Test Date: 1/13/2014



Filter Class: CFC_60
Max: 30.5 g at 10.8 ms
Min: -4.1 g at 35.4 ms



Filter Class: CFC_60
Max: 6.2 m/s at 29.5 ms
Min: 0.0 m/s at 0.0 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 12:56:12 580




Transportation Research Center Inc.


Left Lateral Lumbar

ES-2re Serial No. F030 Certification No. 19-2


Test Date: 1/13/2014




Filter Class: CFC_180
Max: 14.8 ° at 106.5 ms
Min: -31.9 ° at 46.2 ms



Filter Class: CFC_180
Max: 15.2 ° at 106.2 ms
Min: -28.8 ° at 45.5 ms



Filter Class: CFC_180
Max: 9.1 ° at 105.2 ms
Min: -15.2 ° at 42.7 ms



Filter Class: CFC_180
Max: 23.9 ° at 106.1 ms
Min: -46.9 ° at 43.0 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.13.2014 12:56:13 580



Transportation Research Center Inc.

Left Lateral Pelvis
ES-2re Serial No. F030 Certification No. 21-1
Test Date: 1/23/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.2 °C	Yes
Relative Humidity	10 - 70 %	30 %	Yes
Test Probe Velocity	4.2 - 4.4 m/s	4.28 m/s	Yes
Test Probe Force			
Peak	4,700 - 5,400 N	5,087.5 N	Yes
Time of Peak	11.8 - 16.1 ms	12.64 ms	Yes
Pubic Symphysis Force			
Peak	(-1,230) - (-1,590) N	-1,280.1 N	Yes
Time of Peak	12.2 - 17.0 ms	12.80 ms	Yes

Test meets specifications.

Comments:

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.23.2014 15:14:28 567




Transportation Research Center Inc.


Left Lateral Pelvis
ES-2re Serial No. F030 Certification No. 21-1
Test Date: 1/23/2014



Filter Class: CFC_180
Max: 22.2 g at 12.6 ms
Min: -0.1 g at -0.6 ms



Filter Class: CFC_180
Max: 5,087.5 N at 12.6 ms
Min: -20.6 N at -0.6 ms



Filter Class: CFC_600
Max: 69.8 N at 34.9 ms
Min: -1,280.1 N at 12.8 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.23.2014 15:14:35 567



Driver S/N F030

Post-Test Calibration Sheets

Transportation Research Center Inc.
572U ES-2re Dummy
External Dimensions
Serial No. F030 Calibration No. 20
01/21/14

Symbol	Description	Specification	Results	Pass
		mm	mm	
1	Sitting Height	900.0 - 918.0	910	Yes
2	Seat to Shoulder Joint	558.0 - 572.0	560	Yes
3	Seat to Lower Face of Thoracic Spine Box	346.0 - 356.0	350	Yes
4	Seat to Hip Joint (center of bolt)	97.0 - 103.0	98	Yes
5	Sole to Seat, Sitting	433.0 - 451.0	446	Yes
6	Head Width	152.0 - 158.0	155	Yes
7	Shoulder/Arm Width	461.0 - 479.0	471	Yes
8	Thorax Width	322.0 - 332.0	326	Yes
9	Abdomen Width	273.0 - 287.0	282	Yes
10	Pelvis Lap Width	359.0 - 373.0	367	Yes
11	Head Depth	196.0 - 206.0	200	Yes
12	Thorax Depth	262.0 - 272.0	267	Yes
13	Abdomen Depth	194.0 - 204.0	200	Yes
14	Pelvis Depth	235.0 - 245.0	240	Yes
15	Back of Buttocks to Hip Joint (center of bolt)	150.0 - 160.0	159	Yes
16	Back of Buttocks to Front of Knee	597.0 - 615.0	606	Yes

Technician



Approved



Baseline 10/07/05



Transportation Research Center Inc.

Left Lateral Head Drop

ES-2re Serial No. F030 Certification No. 20-1

Test Date: 1/20/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
Peak Resultant Acceleration	125 - 155 g	144.7 g	Yes
Peak Longitudinal Acceleration	(-15) - 15 g	6.1 g	Yes
Is Resultant Acceleration Curve Unimodal within 15% of Main Pulse?	Yes	Yes	Yes

Test meets specifications.

Comments:

Technician



Approved



Specification Source: NHTSA Final Rule 8/15/2008

01.20.2014 13:56:27 360




Transportation Research Center Inc.


Left Lateral Head Drop

ES-2re Serial No. F030 Certification No. 20-1


Test Date: 1/20/2014




Filter Class: CFC_1000
Max: 6.1 g at 4.3 ms
Min: -0.9 g at 9.6 ms



Filter Class: CFC_1000
Max: 98.7 g at 2.2 ms
Min: -4.0 g at 5.4 ms



Filter Class: CFC_1000
Max: 105.7 g at 2.2 ms
Min: -2.0 g at 10.0 ms



Filter Class: CFC_1000
Max: 144.7 g at 2.2 ms
Min: 0.0 g at -0.4 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.20.2014 13:56:37 360



Transportation Research Center Inc.

Left Lateral Neck

ES-2re Serial No. F030 Certification No. 20-1

Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	36 %	Yes
Pendulum Integrated Velocity Change within Corridor	Yes	Yes	Yes
Pendulum Velocity	(-3.3) - (-3.5) m/s	-3.37 m/s	Yes
Maximum Headform Flexion			
Peak	(-49) - (-59) deg	-53.2 deg	Yes
Time of Peak	54 - 66 ms	55.7 ms	Yes
Headform Flexion Decay			
- Peak to Zero	53 - 88 ms	67.0 ms	Yes

Test meets specifications.

Comments:

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 09:17:39 1306




Transportation Research Center Inc.

Left Lateral Neck
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014



Filter Class: CFC_60
Max: 33.6 g at 9.7 ms
Min: -6.4 g at 45.4 ms



Filter Class: CFC_60
Max: 3.6 m/s at 36.6 ms
Min: 0.0 m/s at 0.0 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 09:17:48 1306




Transportation Research Center Inc.


Left Lateral Neck

ES-2re Serial No. F030 Certification No. 20-1


Test Date: 1/21/2014




Filter Class: CFC_180
Max: 15.9 ° at 168.8 ms
Min: -35.6 ° at 61.0 ms



Filter Class: CFC_180
Max: 17.2 ° at 169.3 ms
Min: -31.5 ° at 63.0 ms



Filter Class: CFC_180
Max: 11.2 ° at 163.0 ms
Min: -18.0 ° at 55.8 ms



Filter Class: CFC_180
Max: 27.0 ° at 166.8 ms
Min: -53.2 ° at 55.7 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 09:17:49 1306



Transportation Research Center Inc.

Left Lateral Shoulder

ES-2re Serial No. F030 Certification No. 20-1

Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.1 °C	Yes
Relative Humidity	10 - 70 %	35 %	Yes
Test Probe Velocity	4.2 - 4.4 m/s	4.34 m/s	Yes
Test Probe Acceleration	(-7.5) - (-10.5) g	-9.84 g	Yes

Test meets specifications.

Comments:

Technician



Approved




Specification Source: NHTSA final rule 8/15/2008

01.21.2014 13:02:12 533



Transportation Research Center Inc.

Left Lateral Shoulder
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 0.6 g at 56.1 ms
Min: -9.8 g at 11.5 ms

Specification Source: NHTSA final rule 8/15/2008

01.21.2014 13:02:18 533



Transportation Research Center Inc.

4.0 m/s Upper Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014


Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	47.8 mm	Yes

Test meets specifications.

Comments:

Drop Height: 816

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 10:52:02 742



Transportation Research Center Inc.

4.0 m/s Upper Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 47.8 mm at 27.3 ms
Min: -4.2 mm at 59.6 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 10:52:10 742



Transportation Research Center Inc.

3.0 m/s Upper Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	36.7 mm	Yes

Test meets specifications.

Comments:

Drop Height: 462

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 10:58:11 923



Transportation Research Center Inc.

3.0 m/s Upper Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 36.7 mm at 28.9 ms
Min: -3.7 mm at 62.0 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 10:58:21 923



Transportation Research Center Inc.

4.0 m/s Center Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.1 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	48.2 mm	Yes

Test meets specifications.

Comments:

Drop Height: 816

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 11:02:14 740



Transportation Research Center Inc.

4.0 m/s Center Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 48.2 mm at 26.9 ms
Min: -4.5 mm at 59.4 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 11:02:21 740



Transportation Research Center Inc.

3.0 m/s Center Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.0 °C	Yes
Relative Humidity	10 - 70 %	36 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	37.2 mm	Yes

Test meets specifications.

Comments:

Drop Height: 462

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 11:08:06 930



Transportation Research Center Inc.

3.0 m/s Center Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 37.2 mm at 28.6 ms
Min: -4.0 mm at 62.4 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 11:08:20 930



Transportation Research Center Inc.

4.0 m/s Lower Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.2 °C	Yes
Relative Humidity	10 - 70 %	35 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	47.6 mm	Yes

Test meets specifications.

Comments:

Drop Height: 816

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 11:12:24 744



Transportation Research Center Inc.

4.0 m/s Lower Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 47.6 mm at 27.0 ms
Min: -3.9 mm at 59.7 ms



Transportation Research Center Inc.

3.0 m/s Lower Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.6 °C	Yes
Relative Humidity	10 - 70 %	33 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	36.8 mm	Yes

Test meets specifications.

Comments:

Drop Height: 462

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 11:17:54 936



Transportation Research Center Inc.

3.0 m/s Lower Full Rib Module
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 36.8 mm at 28.7 ms
Min: -3.3 mm at 62.2 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 11:18:05 936



Transportation Research Center Inc.

Left Lateral Thorax
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.1 °C	Yes
Relative Humidity	10 - 70 %	34 %	Yes
Impactor Velocity	5.4 - 5.60 m/s	5.456 m/s	Yes
Peak Impactor Force after 6 ms	(-5,100) - (-6,200) N	-5,485.6 N	Yes
Upper Rib Displacement	34 - 41 mm	37.2 mm	Yes
Center Rib Displacement	37 - 45 mm	40.7 mm	Yes
Lower Rib Displacement	37 - 44 mm	41.0 mm	Yes

Test meets specifications.

Comments:

Technician



Approved




Specification Source: Procedures based on Final Rule dated 8/15/2008.
Polarity in accordance with SAE J211.

01.21.2014 13:08:12 435



Transportation Research Center Inc.

Left Lateral Thorax
ES-2re Serial No. F030 Certification No. 20-1
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 34.6 N at 57.5 ms
Min: -8,988.2 N at 3.8 ms

Specification Source: Procedures based on Final Rule dated 8/15/2008.
Polarity in accordance with SAE J211.

01.21.2014 13:08:20 435




Transportation Research Center Inc.


Left Lateral Thorax

ES-2re Serial No. F030 Certification No. 20-1


Test Date: 1/21/2014



Filter Class: CFC_180
Max: 37.2 mm at 17.9 ms
Min: -4.3 mm at 41.2 ms



Filter Class: CFC_180
Max: 40.7 mm at 18.8 ms
Min: -4.5 mm at 44.7 ms



Filter Class: CFC_180
Max: 41.0 mm at 19.1 ms
Min: -2.8 mm at 48.6 ms

Specification Source: Procedures based on Final Rule dated 8/15/2008.
Polarity in accordance with SAE J211.

01.21.2014 13:08:20 435



Transportation Research Center Inc.

Left Lateral Abdomen
ES-2re Serial No. F030 Certification No. 20-2
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	34 %	Yes
Test Probe Velocity	3.9 - 4.1 m/s	3.93 m/s	Yes
Test Probe Force			
Peak	4,000 - 4,800 N	4,110.2 N	Yes
Time of Peak	10.6 - 13.0 ms	11.28 ms	Yes
Total Abdominal Force			
Peak	2,200 - 2,700 N	2,687.3 N	Yes
Time of Peak	10.0 - 12.3 ms	10.40 ms	Yes

Test meets specifications.

Comments:

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 13:57:04 626




Transportation Research Center Inc.

Left Lateral Abdomen
ES-2re Serial No. F030 Certification No. 20-2
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 17.9 g at 11.3 ms
Min: -0.3 g at -0.5 ms



Filter Class: CFC_180
Max: 4,110.2 N at 11.3 ms
Min: -67.5 N at -0.5 ms


Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 13:57:11 626




Transportation Research Center Inc.


Left Lateral Abdomen
ES-2re Serial No. F030 Certification No. 20-2
Test Date: 1/21/2014




Filter Class: CFC_600
Max: 636.9 N at 10.7 ms
Min: -23.1 N at 99.6 ms



Filter Class: CFC_600
Max: 1,099.5 N at 10.9 ms
Min: -3.6 N at 99.5 ms



Filter Class: CFC_600
Max: 968.1 N at 10.0 ms
Min: -2.4 N at 82.6 ms



Filter Class: CFC_600
Max: 2,687.3 N at 10.4 ms
Min: -28.6 N at 99.5 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 13:57:12 626



Transportation Research Center Inc.


Left Lateral Lumbar
ES-2re Serial No. F030 Certification No. 20-3
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.6 °C	Yes
Relative Humidity	10 - 70 %	40 %	Yes
Pendulum Integrated Velocity Change within Corridor	Yes	Yes	Yes
Pendulum Velocity	(-5.95) - (-6.15) m/s	-6.017 m/s	Yes
Maximum Headform Flexion Peak	(-45) - (-55) deg	-46.6 deg	Yes
Time of Peak	39 - 53 ms	44.6 ms	Yes
Headform Flexion Decay - Peak to Zero	37 - 57 ms	38.3 ms	Yes

Test meets specifications.

Comments:

Technician



Approved




Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 08:54:44 580




Transportation Research Center Inc.

Left Lateral Lumbar
ES-2re Serial No. F030 Certification No. 20-3
Test Date: 1/21/2014



Filter Class: CFC_60
Max: 29.8 g at 10.7 ms
Min: -4.7 g at 35.7 ms



Filter Class: CFC_60
Max: 6.2 m/s at 30.7 ms
Min: 0.0 m/s at 0.0 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 08:54:51 580




Transportation Research Center Inc.


Left Lateral Lumbar

ES-2re Serial No. F030 Certification No. 20-3


Test Date: 1/21/2014




Filter Class: CFC_180
Max: 14.5 ° at 107.6 ms
Min: -31.6 ° at 44.8 ms



Filter Class: CFC_180
Max: 15.3 ° at 109.3 ms
Min: -28.6 ° at 45.8 ms



Filter Class: CFC_180
Max: 8.9 ° at 106.7 ms
Min: -15.0 ° at 41.4 ms



Filter Class: CFC_180
Max: 23.4 ° at 107.0 ms
Min: -46.6 ° at 44.6 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 08:54:52 580



Transportation Research Center Inc.

Left Lateral Pelvis

ES-2re Serial No. F030 Certification No. 20-1

Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.1 °C	Yes
Relative Humidity	10 - 70 %	30 %	Yes
Test Probe Velocity	4.2 - 4.4 m/s	4.28 m/s	Yes
Test Probe Force			
Peak	4,700 - 5,400 N	5,030.8 N	Yes
Time of Peak	11.8 - 16.1 ms	12.56 ms	Yes
Pubic Symphysis Force			
Peak	(-1,230) - (-1,590) N	-1,268.6 N	Yes
Time of Peak	12.2 - 17.0 ms	12.56 ms	Yes

Test meets specifications.

Comments:

Technician



Approved



Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 13:32:03 597




Transportation Research Center Inc.


Left Lateral Pelvis

ES-2re Serial No. F030 Certification No. 20-1


Test Date: 1/21/2014



Filter Class: CFC_180
Max: 22.0 g at 12.6 ms
Min: -0.1 g at 67.4 ms



Filter Class: CFC_180
Max: 5,030.8 N at 12.6 ms
Min: -18.9 N at 67.4 ms



Filter Class: CFC_600
Max: 104.0 N at 36.0 ms
Min: -1,268.6 N at 12.6 ms

Specification Source: NHTSA Final Rule 8/15/2008

01.21.2014 13:32:10 597



**Pre-Test Calibration Sheets
Passenger S/N 305**


Transportation Research Center Inc.
SIDIIs Dummy - Level D
External Dimensions
Serial No. 305 Calibration No.024

Symbol	Description	Specification	Results	Pass
		mm	mm	
A	Sitting Height	772.0 - 788.0	780	Yes
B	Shoulder Pivot Height	437.0 - 453.0	444	Yes
C	H-Point Height	79.0 - 89.0	84	Yes
D	H-Point from Seat Back	141.0 - 151.0	145	Yes
E	Shoulder Pivot from Backline	97.0 - 107.0	102	Yes
F	Thigh Clearance	119.0 - 135.0	129	Yes
G	Head Breadth	140.0 - 148.0	145	Yes
H	Head Back from Backline	40.0 - 46.0	45	Yes
I	Head Depth	178.0 - 188.0	183	Yes
J	Head Circumference	541.0 - 551.0	544	Yes
K	Buttock to Knee Length	514.0 - 540.0	528	Yes
L	Popliteal Height	343.0 - 369.0	355	Yes
M	Knee Pivot to Floor Height	393.0 - 409.0	402	Yes
N	Buttock Popliteal Length	416.0 - 442.0	428	Yes
O	Chest Depth without Jacket	195.0 - 211.0	201	Yes
P	Foot Length (right)	216.0 - 232.0	220	Yes
P	Foot Length (left)	216.0 - 232.0	220	Yes
Q	Hip Breadth	313.0 - 323.0	317	Yes
R	Arm Length	249.0 - 259.0	253	Yes
S	Knee Joint to seat Back	478.0 - 493.0	484	Yes
V	Shoulder Width (only one arm installed)	341.0 - 357.0	348	Yes
W	Foot Width (right)	78.0 - 94.0	84	Yes
W	Foot Width (left)	78.0 - 94.0	84	Yes
Y	Chest Circumference with Jacket	851.0 - 881.0	867	Yes
Z	Waist Circumference	761.0 - 791.0	779	Yes

Technician



Approved




Revised 9/29/2005

Transportation Research Center Inc.

Left Lateral Head Drop
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014

Test Parameter	Specification	Test Results	Pass
Temperature	18.9 - 25.6 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Peak Head Resultant Acceleration	115 - 137 g	119.5 g	Yes
Peak Head Longitudinal Acceleration	(-15) - 15 g	-2.6 g	Yes
Is Head Resultant Acceleration Curve Unimodal within 15% of Peak?	Yes	Yes	Yes


Test meets specifications.

Comments:

Technician



Approved



Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 11:08:19 232




Transportation Research Center Inc.

Left Lateral Head Drop

SID IIs Serial No. 305 Certification No. 24-1


Test Date: 1/10/2014



Filter Class: CFC_1000

Max: 1.4 g at 2.8 ms


Min: -2.6 g at 5.6 ms



Filter Class: CFC_1000

Max: 97.8 g at 2.8 ms


Min: -1.3 g at 7.2 ms



Filter Class: CFC_1000

Max: 69.0 g at 2.9 ms

Min: -0.9 g at 8.4 ms



Filter Class: CFC_1000

Max: 119.5 g at 2.8 ms

Min: 0.0 g at -1.0 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 11:08:29 232




Transportation Research Center Inc.


Left Lateral Neck
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Pendulum Velocity	(-5.51) - (-5.63) m/s	-5.604 m/s	Yes
Pendulum Integrated Velocity			
Change at 10 ms	2.20 - 2.80 m/s	2.486 m/s	Yes
Change at 15 ms	3.30 - 4.10 m/s	3.614 m/s	Yes
Change at 20 ms	4.40 - 5.40 m/s	4.850 m/s	Yes
Change at 25 ms	5.40 - 6.10 m/s	5.783 m/s	Yes
Change at 25 to 100 ms	5.50 - 6.20 m/s	5.800 m/s	Yes
Maximum Headform Flexion occurring between 50ms and 70ms.			
Peak	(-71) - (-81) deg	-75.0 deg	Yes
Time of Peak	50 - 70 ms	66.1 ms	Yes
Total Neck Occipital Condyles Moment	36 - 44 N·m	41.1 N·m	Yes
Total Neck Occipital Condyles Moment			
Decay Time to 0 N·m	102 - 126 ms	115.8 ms	Yes

Test meets specifications.

Comments:

Technician 

Approved 

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 12:05:03 641




Transportation Research Center Inc.

Left Lateral Neck

SID II_s Serial No. 305 Certification No. 24-1


Test Date: 1/10/2014



Filter Class: CFC_180

Max: 33.4 g at 2.0 ms

Min: -6.5 g at 33.2 ms



Filter Class: CFC_180

Max: 6.6 m/s at 200.0 ms

Min: 0.0 m/s at 0.0 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 12:06:55 641




Transportation Research Center Inc.


Left Lateral Neck

SID IIs Serial No. 305 Certification No. 24-1


Test Date: 1/10/2014




Filter Class: CFC_60
Max: 18.5 ° at 189.8 ms
Min: -65.9 ° at 70.9 ms



Filter Class: CFC_60
Max: 20.1 ° at 184.4 ms
Min: -48.6 ° at 61.8 ms



Filter Class: CFC_60
Max: 13.3 ° at 179.4 ms
Min: -13.2 ° at 44.0 ms



Filter Class: CFC_60
Max: 31.5 ° at 188.1 ms
Min: -75.0 ° at 66.1 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 12:06:56 641




Transportation Research Center Inc.


Left Lateral Neck

SID IIs Serial No. 305 Certification No. 24-1


Test Date: 1/10/2014




Filter Class: CFC_1000
Max: 463.7 N at 49.3 ms
Min: -148.2 N at 172.2 ms



Filter Class: CFC_600
Max: 463.4 N at 49.4 ms
Min: -148.1 N at 172.2 ms



Filter Class: CFC_600
Max: 33.7 Nm at 52.8 ms
Min: -26.7 Nm at 11.3 ms



Filter Class: Without_(Consta
Max: 41.1 N·m at 53.0 ms
Min: -21.1 N·m at 11.1 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 12:06:56 641



Transportation Research Center Inc.

Left Lateral Shoulder
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	34 %	Yes
Impactor Velocity	4.2 - 4.4 m/s	4.33 m/s	Yes
Impactor Acceleration	(-13) - (-18) g	-15.8 g	Yes
Shoulder Displacement	28 - 37 mm	31.0 mm	Yes
Upper Spine Lateral Acceleration	17 - 22 g	20.2 g	Yes


Test meets specifications.

Comments:

Technician



Approved



Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 16:21:29 828




Transportation Research Center Inc.


Left Lateral Shoulder

SID IIs Serial No. 305 Certification No. 24-1


Test Date: 1/10/2014



Filter Class: CFC_180
Max: 0.1 g at 51.0 ms
Min: -15.8 g at 13.8 ms



Filter Class: CFC_600
Max: 31.0 mm at 18.2 ms
Min: -0.0 mm at 1.0 ms



Filter Class: CFC_180
Max: 20.2 g at 8.2 ms
Min: -7.0 g at 34.9 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 16:21:40 828



Transportation Research Center Inc.

Left Lateral Thorax with Arm
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	36 %	Yes
Impactor Velocity	6.60 - 6.80 m/s	6.707 m/s	Yes
Impactor Acceleration	(-30) - (-36) g	-33.5 g	Yes
Shoulder Displacement	31 - 40 mm	34.3 mm	Yes
Upper Thorax Rib Displacement	25 - 32 mm	26.5 mm	Yes
Center Thorax Rib Displacement	30 - 36 mm	31.4 mm	Yes
Lower Thorax Rib Displacement	32 - 38 mm	33.2 mm	Yes
Upper Spine Lateral Acceleration	34 - 43 g	39.2 g	Yes
Lower Spine Lateral Acceleration	29 - 37 g	33.8 g	Yes


Test meets specifications.

Comments:

Technician



Approved




Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 18:09:42 609




Transportation Research Center Inc.


Left Lateral Thorax with Arm
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014



Filter Class: CFC_180
Max: 0.3 g at 46.7 ms
Min: -33.5 g at 12.8 ms



Filter Class: CFC_180
Max: 39.2 g at 9.8 ms
Min: -9.9 g at 31.1 ms



Filter Class: CFC_180
Max: 33.8 g at 9.1 ms
Min: -9.2 g at 32.6 ms


Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 18:09:54 609




Transportation Research Center Inc.


Left Lateral Thorax with Arm
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014




Filter Class: CFC_600
Max: 34.3 mm at 16.1 ms
Min: -1.0 mm at 33.0 ms



Filter Class: CFC_600
Max: 26.5 mm at 16.1 ms
Min: -0.0 mm at -7.5 ms



Filter Class: CFC_600
Max: 31.4 mm at 16.6 ms
Min: -0.0 mm at -7.3 ms



Filter Class: CFC_600
Max: 33.2 mm at 17.3 ms
Min: -0.0 mm at 2.6 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 18:09:55 609



Transportation Research Center Inc.

Left Lateral Thorax without Arm
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Impactor Velocity	4.20 - 4.40 m/s	4.391 m/s	Yes
Impactor Acceleration	(-14) - (-18) g	-16.4 g	Yes
Upper Thorax Rib Displacement	32 - 40 mm	34.0 mm	Yes
Center Thorax Rib Displacement	39 - 45 mm	40.5 mm	Yes
Lower Thorax Rib Displacement	35 - 43 mm	37.6 mm	Yes
Upper Spine Lateral Acceleration	13 - 17 g	16.0 g	Yes
Lower Spine Lateral Acceleration	7 - 11 g	10.4 g	Yes


Test meets specifications.

Comments:

Technician



Approved




Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 17:21:34 829




Transportation Research Center Inc.


Left Lateral Thorax without Arm
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014



Filter Class: CFC_180
Max: 0.1 g at 57.0 ms
Min: -16.4 g at 18.6 ms



Filter Class: CFC_180
Max: 16.0 g at 16.2 ms
Min: -5.7 g at 48.1 ms



Filter Class: CFC_180
Max: 10.4 g at 14.5 ms
Min: -4.5 g at 45.2 ms


Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 17:21:46 829




Transportation Research Center Inc.


Left Lateral Thorax without Arm
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014



Filter Class: CFC_600
Max: 34.0 mm at 20.3 ms
Min: -0.0 mm at -6.4 ms



Filter Class: CFC_600
Max: 40.5 mm at 20.8 ms
Min: -0.0 mm at -5.0 ms



Filter Class: CFC_600
Max: 37.6 mm at 22.5 ms
Min: -0.0 mm at 1.4 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 17:21:47 829



Transportation Research Center Inc.


Left Lateral Abdomen
SID IIs Serial No. 305 Certification No. 24-1
Test Date: 1/10/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
Impactor Velocity	4.2 - 4.4 m/s	4.27 m/s	Yes
Impactor Acceleration	(-12) - (-16) g	-13.5 g	Yes
Upper Abdominal Rib Displacement	36 - 47 mm	43.1 mm	Yes
Lower Abdominal Rib Displacement	33 - 44 mm	37.5 mm	Yes
Lower Spine Lateral Acceleration	9 - 14.0 g	10.58 g	Yes


Test meets specifications.

Comments:

Technician



Approved



Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 16:38:47 644




Transportation Research Center Inc.


Left Lateral Abdomen

SID IIs Serial No. 305 Certification No. 24-1


Test Date: 1/10/2014



Filter Class: CFC_180
Max: 0.1 g at 78.2 ms
Min: -13.5 g at 16.4 ms



Filter Class: CFC_180
Max: 10.6 g at 12.6 ms
Min: -1.4 g at 36.2 ms



Filter Class: CFC_600
Max: 43.1 mm at 24.4 ms
Min: -0.0 mm at -1.0 ms



Filter Class: CFC_600
Max: 37.5 mm at 23.2 ms
Min: -0.0 mm at 0.8 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 16:38:57 644



Transportation Research Center Inc.


Left Lateral Pelvis
SID IIs Serial No. 305 Certification No. 24-7
Test Date: 1/13/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	20.8 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Pendulum Velocity	6.6 - 6.8 m/s	6.63 m/s	Yes
Impactor Acceleration	(-38.0) - (-47.0) g	-41.95 g	Yes
Peak Pelvis Lateral Acceleration after 6ms	34 - 42 g	37.3 g	Yes
Acetabulum Force	3,600 - 4,300 N	4,274.5 N	Yes

Test meets specifications.

Comments:

Technician



Approved



Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.13.2014 18:16:38 449




Transportation Research Center Inc.


Left Lateral Pelvis

SID IIs Serial No. 305 Certification No. 24-7


Test Date: 1/13/2014



Filter Class: CFC_180
Max: 0.5 g at -0.9 ms
Min: -42.0 g at 8.2 ms



Filter Class: CFC_180
Max: 48.7 g at 1.5 ms
Min: -15.1 g at 25.8 ms



Filter Class: CFC_600
Max: 4,274.5 N at 7.8 ms
Min: -78.0 N at 96.7 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.13.2014 18:16:57 449



Transportation Research Center Inc.

Left Lateral Iliac

SID IIs Serial No. 305 Certification No. 24-1


Test Date: 1/10/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	36 %	Yes
Pendulum Velocity	4.2 - 4.4 m/s	4.27 m/s	Yes
Impactor Acceleration	(-36) - (-45) g	-40.6 g	Yes
Peak Pelvis Lateral Acceleration	28 - 39 g	33.8 g	Yes
Iliac Force	4,100 - 5,100 N	4,922.7 N	Yes

Test meets specifications.

Comments:

Technician



Approved



Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.10.2014 15:14:14 676




Transportation Research Center Inc.


Left Lateral Iliac

SID IIs Serial No. 305 Certification No. 24-1


Test Date: 1/10/2014



Filter Class: CFC_180
Max: 0.3 g at 41.7 ms
Min: -40.6 g at 9.0 ms



Filter Class: CFC_180
Max: 33.8 g at 8.6 ms
Min: -4.0 g at 14.5 ms



Filter Class: CFC_600
Max: 4,922.7 N at 9.0 ms
Min: -0.8 N at -1.8 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.


01.10.2014 15:14:25 676




Post-Test Calibration Sheets
Passenger S/N 305

Transportation Research Center Inc.
SIDI's Dummy - Level D
External Dimensions
Serial No. 305 Calibration No.025

Symbol	Description	Specification	Results	Pass
		mm	mm	
A	Sitting Height	772.0 - 788.0	780	Yes
B	Shoulder Pivot Height	437.0 - 453.0	444	Yes
C	H-Point Height	79.0 - 89.0	84	Yes
D	H-Point from Seat Back	141.0 - 151.0	145	Yes
E	Shoulder Pivot from Backline	97.0 - 107.0	102	Yes
F	Thigh Clearance	119.0 - 135.0	128	Yes
G	Head Breadth	140.0 - 148.0	145	Yes
H	Head Back from Backline	40.0 - 46.0	45	Yes
I	Head Depth	178.0 - 188.0	183	Yes
J	Head Circumference	541.0 - 551.0	544	Yes
K	Buttock to Knee Length	514.0 - 540.0	527	Yes
L	Popliteal Height	343.0 - 369.0	355	Yes
M	Knee Pivot to Floor Height	393.0 - 409.0	402	Yes
N	Buttock Popliteal Length	416.0 - 442.0	428	Yes
O	Chest Depth without Jacket	195.0 - 211.0	201	Yes
P	Foot Length (right)	216.0 - 232.0	220	Yes
P	Foot Length (left)	216.0 - 232.0	220	Yes
Q	Hip Breadth	313.0 - 323.0	318	Yes
R	Arm Length	249.0 - 259.0	253	Yes
S	Knee Joint to seat Back	478.0 - 493.0	484	Yes
V	Shoulder Width (only one arm installed)	341.0 - 357.0	348	Yes
W	Foot Width (right)	78.0 - 94.0	84	Yes
W	Foot Width (left)	78.0 - 94.0	84	Yes
Y	Chest Circumference with Jacket	851.0 - 881.0	866	Yes
Z	Waist Circumference	761.0 - 791.0	778	Yes

Technician


Approved


Revised 9/29/2005



Transportation Research Center Inc.


Left Lateral Head Drop
SID IIs Serial No. 305 Certification No. 25-1
Test Date: 1/16/2014

Test Parameter	Specification	Test Results	Pass
Temperature	18.9 - 25.6 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	33 %	Yes
Peak Head Resultant Acceleration	115 - 137 g	120.6 g	Yes
Peak Head Longitudinal Acceleration	(-15) - 15 g	-2.0 g	Yes
Is Head Resultant Acceleration Curve Unimodal within 15% of Peak?	Yes	Yes	Yes


Test meets specifications.

Comments:

Technician



Approved



Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.16.2014 11:41:42 232




Transportation Research Center Inc.


Left Lateral Head Drop

SID IIs Serial No. 305 Certification No. 25-1


Test Date: 1/16/2014




Filter Class: CFC_1000
Max: 1.9 g at 2.7 ms
Min: -2.0 g at 5.3 ms



Filter Class: CFC_1000
Max: 94.9 g at 2.8 ms
Min: -0.9 g at 7.0 ms



Filter Class: CFC_1000
Max: 74.3 g at 2.9 ms
Min: -0.9 g at 7.6 ms



Filter Class: CFC_1000
Max: 120.6 g at 2.8 ms
Min: 0.0 g at -0.1 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.16.2014 11:41:52 232



Transportation Research Center Inc.

Left Lateral Neck

SID IIs Serial No. 305 Certification No. 25-1


Test Date: 1/16/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Pendulum Velocity	(-5.51) - (-5.63) m/s	-5.609 m/s	Yes
Pendulum Integrated Velocity			
Change at 10 ms	2.20 - 2.80 m/s	2.456 m/s	Yes
Change at 15 ms	3.30 - 4.10 m/s	3.531 m/s	Yes
Change at 20 ms	4.40 - 5.40 m/s	4.718 m/s	Yes
Change at 25 ms	5.40 - 6.10 m/s	5.676 m/s	Yes
Change at 25 to 100 ms	5.50 - 6.20 m/s	5.794 m/s	Yes
Maximum Headform Flexion occurring between 50ms and 70ms.			
Peak	(-71) - (-81) deg	-77.5 deg	Yes
Time of Peak	50 - 70 ms	69.6 ms	Yes
Total Neck Occipital Condyles Moment	36 - 44 N·m	38.1 N·m	Yes
Total Neck Occipital Condyles Moment			
Decay Time to 0 N·m	102 - 126 ms	118.6 ms	Yes


Test meets specifications.

Comments:

Technician



Approved



Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.16.2014 12:28:27 642




Transportation Research Center Inc.


Left Lateral Neck

SID IIs Serial No. 305 Certification No. 25-1

Test Date: 1/16/2014



Filter Class: CFC_180
Max: 32.9 g at 1.8 ms
Min: -6.0 g at 34.0 ms



Filter Class: CFC_180
Max: 6.6 m/s at 200.0 ms
Min: 0.0 m/s at 0.0 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.16.2014 12:28:38 642







Transportation Research Center Inc.

Left Lateral Neck

SID IIs Serial No. 305 Certification No. 25-1

Test Date: 1/16/2014




Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.16.2014 12:28:38 642




Transportation Research Center Inc.


Left Lateral Neck
SID IIs Serial No. 305 Certification No. 25-1
Test Date: 1/16/2014




Filter Class: CFC_1000
Max: 445.9 N at 50.2 ms
Min: -151.4 N at 176.8 ms



Filter Class: CFC_600
Max: 442.2 N at 50.2 ms
Min: -150.8 N at 176.8 ms



Filter Class: CFC_600
Max: 30.9 Nm at 58.6 ms
Min: -20.7 Nm at 10.6 ms



Filter Class: Without_(Consta
Max: 38.1 N·m at 58.6 ms
Min: -15.9 N·m at 10.4 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.16.2014 12:28:39 642



Transportation Research Center Inc.

Left Lateral Shoulder
SID IIs Serial No. 305 Certification No. 25-2
Test Date: 1/17/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.2 °C	Yes
Relative Humidity	10 - 70 %	36 %	Yes
Impactor Velocity	4.2 - 4.4 m/s	4.30 m/s	Yes
Impactor Acceleration	(-13) - (-18) g	-15.5 g	Yes
Shoulder Displacement	28 - 37 mm	29.9 mm	Yes
Upper Spine Lateral Acceleration	17 - 22 g	20.2 g	Yes

Test meets specifications.

Comments:

Technician



Approved




Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.17.2014 12:40:56 833




Transportation Research Center Inc.


Left Lateral Shoulder
SID IIs Serial No. 305 Certification No. 25-2
Test Date: 1/17/2014



Filter Class: CFC_180
Max: 0.1 g at 50.1 ms
Min: -15.5 g at 13.8 ms



Filter Class: CFC_600
Max: 29.9 mm at 18.1 ms
Min: -0.0 mm at -2.3 ms



Filter Class: CFC_180
Max: 20.2 g at 8.2 ms
Min: -7.9 g at 39.4 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.17.2014 12:41:06 833



Transportation Research Center Inc.


Left Lateral Thorax with Arm
SID IIs Serial No. 305 Certification No. 25-4
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	31 %	Yes
Impactor Velocity	6.60 - 6.80 m/s	6.699 m/s	Yes
Impactor Acceleration	(-30) - (-36) g	-33.3 g	Yes
Shoulder Displacement	31 - 40 mm	33.1 mm	Yes
Upper Thorax Rib Displacement	25 - 32 mm	26.2 mm	Yes
Center Thorax Rib Displacement	30 - 36 mm	31.6 mm	Yes
Lower Thorax Rib Displacement	32 - 38 mm	34.2 mm	Yes
Upper Spine Lateral Acceleration	34 - 43 g	38.7 g	Yes
Lower Spine Lateral Acceleration	29 - 37 g	33.4 g	Yes


Test meets specifications.

Comments:

Technician



Approved




Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.21.2014 13:22:22 615




Transportation Research Center Inc.


Left Lateral Thorax with Arm
SID IIs Serial No. 305 Certification No. 25-4
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 0.2 g at -1.0 ms
Min: -33.3 g at 12.6 ms



Filter Class: CFC_180
Max: 38.7 g at 9.5 ms
Min: -9.9 g at 30.7 ms



Filter Class: CFC_180
Max: 33.4 g at 9.0 ms
Min: -9.7 g at 32.0 ms


Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.21.2014 13:22:34 615




Transportation Research Center Inc.


Left Lateral Thorax with Arm
SID IIs Serial No. 305 Certification No. 25-4
Test Date: 1/21/2014




Filter Class: CFC_600
Max: 33.1 mm at 16.1 ms
Min: -1.1 mm at 33.0 ms



Filter Class: CFC_600
Max: 26.2 mm at 15.8 ms
Min: -0.0 mm at -1.6 ms



Filter Class: CFC_600
Max: 31.6 mm at 16.2 ms
Min: -0.0 mm at -5.2 ms



Filter Class: CFC_600
Max: 34.2 mm at 16.2 ms
Min: -0.0 mm at -0.2 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.21.2014 13:22:35 615



Transportation Research Center Inc.


Left Lateral Thorax without Arm
SID IIs Serial No. 305 Certification No. 25-2
Test Date: 1/21/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	40 %	Yes
Impactor Velocity	4.20 - 4.40 m/s	4.378 m/s	Yes
Impactor Acceleration	(-14) - (-18) g	-16.6 g	Yes
Upper Thorax Rib Displacement	32 - 40 mm	35.1 mm	Yes
Center Thorax Rib Displacement	39 - 45 mm	41.4 mm	Yes
Lower Thorax Rib Displacement	35 - 43 mm	38.8 mm	Yes
Upper Spine Lateral Acceleration	13 - 17 g	15.8 g	Yes
Lower Spine Lateral Acceleration	7 - 11 g	10.7 g	Yes


Test meets specifications.

Comments:

Technician



Approved




Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.21.2014 12:45:45 819




Transportation Research Center Inc.


Left Lateral Thorax without Arm
SID IIs Serial No. 305 Certification No. 25-2
Test Date: 1/21/2014



Filter Class: CFC_180
Max: 0.1 g at 65.3 ms
Min: -16.6 g at 19.3 ms



Filter Class: CFC_180
Max: 15.8 g at 15.7 ms
Min: -5.6 g at 48.6 ms



Filter Class: CFC_180
Max: 10.7 g at 15.9 ms
Min: -4.3 g at 45.8 ms


Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.21.2014 12:45:57 819




Transportation Research Center Inc.


Left Lateral Thorax without Arm
SID IIs Serial No. 305 Certification No. 25-2
Test Date: 1/21/2014



Filter Class: CFC_600
Max: 35.1 mm at 21.3 ms
Min: -0.0 mm at -6.1 ms



Filter Class: CFC_600
Max: 41.4 mm at 21.8 ms
Min: -0.0 mm at -7.7 ms



Filter Class: CFC_600
Max: 38.8 mm at 22.8 ms
Min: -0.0 mm at -6.1 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.21.2014 12:45:58 819



Transportation Research Center Inc.

Left Lateral Abdomen

SID IIs Serial No. 305 Certification No. 26-1


Test Date: 1/24/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	20.9 °C	Yes
Relative Humidity	10 - 70 %	40 %	Yes
Impactor Velocity	4.2 - 4.4 m/s	4.27 m/s	Yes
Impactor Acceleration	(-12) - (-16) g	-13.5 g	Yes
Upper Abdominal Rib Displacement	36 - 47 mm	43.3 mm	Yes
Lower Abdominal Rib Displacement	33 - 44 mm	38.4 mm	Yes
Lower Spine Lateral Acceleration	9 - 14.0 g	10.66 g	Yes

Test meets specifications.

Comments:

Technician



Approved




Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.24.2014 10:25:40 683




Transportation Research Center Inc.


Left Lateral Abdomen
SID IIs Serial No. 305 Certification No. 26-1
Test Date: 1/24/2014




Filter Class: CFC_180
Max: 0.3 g at 88.7 ms
Min: -13.5 g at 16.1 ms



Filter Class: CFC_180
Max: 10.7 g at 12.3 ms
Min: -1.7 g at 42.3 ms



Filter Class: CFC_600
Max: 43.3 mm at 24.2 ms
Min: -0.0 mm at -8.2 ms



Filter Class: CFC_600
Max: 38.4 mm at 23.4 ms
Min: -0.0 mm at -2.2 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.24.2014 10:25:50 683




Transportation Research Center Inc.


Left Lateral Pelvis
SID IIs Serial No. 305 Certification No. 25-2
Test Date: 1/20/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.2 °C	Yes
Relative Humidity	10 - 70 %	26 %	Yes
Pendulum Velocity	6.6 - 6.8 m/s	6.62 m/s	Yes
Impactor Acceleration	(-38.0) - (-47.0) g	-41.89 g	Yes
Peak Pelvis Lateral Acceleration after 6ms	34 - 42 g	37.0 g	Yes
Acetabulum Force	3,600 - 4,300 N	4,230.1 N	Yes

Test meets specifications.

Comments:

Technician


Approved


Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.20.2014 10:15:47 425




Transportation Research Center Inc.


Left Lateral Pelvis

SID IIs Serial No. 305 Certification No. 25-2


Test Date: 1/20/2014



Filter Class: CFC_180
Max: 0.5 g at -0.6 ms
Min: -41.9 g at 8.3 ms



Filter Class: CFC_180
Max: 47.1 g at 1.8 ms
Min: -14.6 g at 25.8 ms



Filter Class: CFC_600
Max: 4,230.1 N at 7.8 ms
Min: -46.9 N at 0.4 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.20.2014 10:15:56 425



Transportation Research Center Inc.


Left Lateral Iliac
SID IIs Serial No. 305 Certification No. 25-1
Test Date: 1/16/2014

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.7 °C	Yes
Relative Humidity	10 - 70 %	32 %	Yes
Pendulum Velocity	4.2 - 4.4 m/s	4.27 m/s	Yes
Impactor Acceleration	(-36) - (-45) g	-41.3 g	Yes
Peak Pelvis Lateral Acceleration	28 - 39 g	34.4 g	Yes
Iliac Force	4,100 - 5,100 N	5,082.9 N	Yes

Test meets specifications.

Comments:

Technician



Approved



Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.16.2014 13:56:38 648




Transportation Research Center Inc.


Left Lateral Iliac

SID IIs Serial No. 305 Certification No. 25-1


Test Date: 1/16/2014



Filter Class: CFC_180
Max: 0.2 g at 42.6 ms
Min: -41.3 g at 9.0 ms



Filter Class: CFC_180
Max: 34.4 g at 8.7 ms
Min: -2.9 g at 54.2 ms



Filter Class: CFC_600
Max: 5,082.9 N at 9.0 ms
Min: -0.7 N at -4.6 ms

Specification Source: Procedures based on Final Rule effective 8/24/2009
Polarity in accordance with SAE J211.

01.16.2014 13:56:49 648



APPENDIX D
TEST EQUIPMENT AND INSTRUMENTATION CALIBRATION DATA

TABLE 1 – Dummy Instrumentation (ES-2re)

		ES-2re S/N F030			
		Serial Number	Manufacturer	Calibration Date	
Head Accelerometers		X	P58890	Endevco	9-Dec-13
		Y	P51702	Endevco	9-Dec-13
		Z	P52083	Endevco	9-Dec-13
Thoracic Rib Displacement Potentiometers	Upper	Y	175	FTSS	10-Dec-13
	Middle	Y	174	FTSS	10-Dec-13
	Lower	Y	173	FTSS	10-Dec-13
Abdomen Load Cells	Upper	Y	1441	Denton	21-Oct-13
	Middle	Y	1436	Denton	21-Oct-13
	Lower	Y	1437	Denton	21-Oct-13
Lower Spine Accelerometers (T12)		X	P15954	Endevco	9-Dec-13
		Y	P68599	Endevco	9-Dec-13
		Z	P59005	Endevco	9-Dec-13
Acetabulum Load Cell		Y	N/A	N/A	N/A
Pubic Symphysis Load Cell		Y	457-FY	Denton	21-Oct-13

TABLE 2 – Dummy Instrumentation (SID-IIs)

		SID-IIs S/N 305				
		Serial Number	Manufacturer	Calibration Date		
Head Accelerometers		X	P51719	Endevco	11-Dec-13	
		Y	P51272	Endevco	11-Dec-13	
		Z	P58862	Endevco	11-Dec-13	
Displacement Potentiometers	Shoulder		Y	N/A	N/A	
	Thoracic Rib	Upper	Y	007	Servo	12-Dec-13
		Middle	Y	1161	Servo	12-Dec-13
		Lower	Y	1279	Servo	12-Dec-13
	Abdominal Rib	Upper	Y	1295	Servo	12-Dec-13
		Lower	Y	1136	Servo	12-Dec-13
Lower Spine Accelerometers (T12)		X	P50068	Endevco	12-Dec-13	
		Y	P52051	Endevco	12-Dec-13	
		Z	P51710	Endevco	12-Dec-13	
Acetabulum Load Cell		Y	D14285-FY	FTSS	28-Oct-13	
Iliac Wing Load Cell		Y	287-FY	FTSS	24-Oct-13	
Pelvis Plug (struck side)			63398	FTSS	28-Jan-13	
Pelvis Plug (non-struck side)			36473	FTSS	23-Sep-10	

TABLE 3 – Vehicle Instrumentation

Vehicle Instrumentation			Serial Number	Manufacturer	Calibration Date
1	Vehicle Center of Gravity	X	P80933	Endevco	5-Nov-2013
	Vehicle Center of Gravity	Y	P78143	Endevco	30-Jul-2013
	Vehicle Center of Gravity	Z	P82031	Endevco	5-Nov-2013
2	Right Sill at Front Seat	X	P82062	Endevco	4-Nov-2013
	Right Sill at Front Seat	Y	P81994	Endevco	5-Nov-2013
	Right Sill at Front Seat	Z	P75240	Endevco	14-May-2013
3	Right Sill at Rear Seat	X	P78112	Endevco	15-Oct-2013
	Right Sill at Rear Seat	Y	P82055	Endevco	15-Nov-2013
	Right Sill at Rear Seat	Z	P75515	Endevco	17-Jul-2013
4	Left Sill at Front Door	Y	P81663	Endevco	12-Nov-2013
5	Left Sill at Rear Door	Y	P81665	Endevco	15-Nov-2013
6	Left A-Post Lower	Y	P78114	Endevco	28-Dec-2013
7	Left A-Post Middle	Y	P81657	Endevco	17-Nov-2013
8	Left B-Post Lower	Y	P78102	Endevco	24-Sep-2013
9	B-Post Middle	Y	P80710	Endevco	17-Sep-2013
10	Front Seat Track	Y	P78203	Endevco	24-Sep-2013
11	Rear Seat Track or Structure	Y	P79313	Endevco	24-Sep-2013
12	Right Rear Occupant Compartment	Y	P78111	Endevco	15-May-2013
13	Engine Block	X	P80456	Endevco	23-Sep-2013
	Engine Block	Y	P81030	Endevco	10-Sep-2013
14	Rear Floorpan Above Axle	X	P82287	Endevco	12-Nov-2013
	Rear Floorpan Above Axle	Y	P81642	Endevco	15-Nov-2013
	Rear Floorpan Above Axle	Z	P82043	Endevco	15-Nov-2013

TABLE 4 – MDB Instrumentation

MDB Instrumentation		Serial Number	Manufacturer	Calibration Date
MDB Center of Gravity	X	P80602	Endevco	17-Sep-2013
MDB Center of Gravity	Y	P81025	Endevco	17-Sep-2013
MDB Center of Gravity	Z	P81041	Endevco	17-Sep-2013
Left Frame Rail at Rear Axle Centerline	X	P78221	Endevco	14-Aug-2013
Left Frame Rail at Rear Axle Centerline	Y	P80765	Endevco	17-Sep-2013