

**REPORT NUMBER: SINCAP-KAR-14-013**

**NEW CAR ASSESSMENT PROGRAM (NCAP)  
MOVING DEFORMABLE BARRIER SIDE IMPACT TEST**

**FUJI HEAVY INDUSTRIES LTD.  
2014 SUBARU XV CROSSTREK 5-DOOR MPV**

**NHTSA No: M20145504**

**PREPARED BY:  
KARCO ENGINEERING, LLC.  
9270 HOLLY ROAD  
ADELANTO, CA 92301**




**FEBRUARY 11, 2014**

**FINAL REPORT**

**PREPARED FOR:  
U.S. DEPARTMENT OF TRANSPORTATION  
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION  
OFFICE OF CRASHWORTHINESS STANDARDS  
MAIL CODE: NVS-111  
1200 NEW JERSEY AVE, SE, ROOM W43-410  
WASHINGTON, D.C. 20590**

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned, it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared By:   
Mr. Steven D. Matsusaka, Engineering Dept. Supervisor  
KARCO Engineering, LLC.

Reviewed By:   
Mr. Michael L. Dunlap, Director of Operations  
KARCO Engineering, LLC.

Approved By:   
Mr. Frank D. Richardson, Program Manager  
KARCO Engineering, LLC.

Approval Date: February 11, 2014

FINAL REPORT ACCEPTANCE BY OCWS:

  
Division Chief, New Car Assessment Program  
NHTSA, Office of Crashworthiness Standards

Date: 

  
COTR, New Car Assessment Program  
NHTSA, Office of Crashworthiness Standards

Date: 

# TECHNICAL REPORT DOCUMENTATION PAGE

|                                                                                                                                                                                                                                                            |                                    |                                                                                            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--------------------------------------------------------------------------------------------|
| <b>1. Report No.</b><br>SINCAP-KAR-14-013                                                                                                                                                                                                                  | <b>2. Government Accession No.</b> | <b>3. Recipient's Catalog No.</b>                                                          |
| <b>4. Title and Subtitle</b><br>Final Report of New Car Assessment Program<br>Side Impact MDB Testing of a 2014 Subaru XV Crosstrek 5-Door MPV<br>NHTSA No. M20145504                                                                                      |                                    | <b>5. Report Date</b><br>February 11, 2014                                                 |
| <b>7. Authors</b><br>Mr. Steven D. Matsusaka, Engineering Department Supervisor, KARCO<br>Mr. Frank Richardson, Program Manager, KARCO                                                                                                                     |                                    | <b>6. Performing Organization Code</b><br>KAR                                              |
| <b>9. Performing Organization Name and Address</b><br>KARCO Engineering, LLC.<br>9270 Holly Rd.<br>Adelanto, CA 92301                                                                                                                                      |                                    | <b>8. Performing Organization Report No.</b><br>TR-P33003-05-NC                            |
| <b>12. Sponsoring Agency Name and Address</b><br>U. S. Department of Transportation<br>National Highway Traffic Safety Administration<br>Office of Crashworthiness Standards (NVS-111)<br>1200 New Jersey Ave., SE, Room W43-410<br>Washington, D.C. 20590 |                                    | <b>10. Work Unit No.</b>                                                                   |
|                                                                                                                                                                                                                                                            |                                    | <b>11. Contract or Grant No.</b><br>DTNH22-09-D-00122                                      |
|                                                                                                                                                                                                                                                            |                                    | <b>13. Type of Report and Period Covered</b><br>Final Test Report, Jan. 28 - Feb. 11, 2014 |
|                                                                                                                                                                                                                                                            |                                    | <b>14. Sponsoring Agency Code</b><br>NVS-111                                               |
| <b>15. Supplementary Notes</b>                                                                                                                                                                                                                             |                                    |                                                                                            |

## **16. Abstract**

A 55/28 km/h 90 deg. Moving Deformable Barrier NCAP Side Impact Test was conducted on the subject 2014 Subaru XV Crosstrek 5-door MPV in accordance with the specifications of the Office of Crash Worthiness Standards Test Procedure for the generation of consumer information on vehicle side crash protection. The test was conducted at the KARCO Engineering, LLC. facility in Adelanto, California on January 28, 2014.

The impact velocity of the Moving Deformable Barrier was 61.97 km/h and the outside ambient temperature at the struck (driver's) side of the vehicle was 24.4 deg. C. The target vehicle's maximum post-test static crush was 207 mm located at level 3. The test vehicle's occupant performance data is as follows:

| Measurement Description                   | Driver ATD (ES-2re) |      |        |
|-------------------------------------------|---------------------|------|--------|
|                                           | Units               | IARV | Result |
| Head Injury Criteria (HIC <sub>36</sub> ) |                     | 1000 | 88.2   |
| Maximum Thorax Rib Deflection             | mm                  | 44   | 15     |
| Total Abdominal Force                     | N                   | 2500 | 941    |
| Pubic Symphysis Force                     | N                   | 6000 | 1593   |

| Measurement Description                                 | Passenger ATD (SID-IIs) |      |        |
|---------------------------------------------------------|-------------------------|------|--------|
|                                                         | Units                   | IARV | Result |
| Head Injury Criteria (HIC <sub>36</sub> )               |                         | 1000 | 165.1  |
| Resultant Lower Spine Acceleration                      | g                       | 82   | 51     |
| Total Pelvic Force (Sum of Acetubular and Iliac Forces) | N                       | 5525 | 2890   |
| Maximum Thoracic Rib Deflection                         | mm                      | 38*  | 27     |
| Maximum Abdominal Rib Deflection                        | mm                      | 45*  | 17     |

The two doors on the struck side of the vehicle did not separate from the body at the hinges or latches. The opposite side doors did not open during the side impact event.

\* Proposed IARV

|                                                                                                                                  |                                                                 |                                                                                                                                                                                                                                                                                                                                  |                  |
|----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <b>17. Key Words</b><br>New Car Assessment Program (NCAP)<br>Side Impact<br>Moving Deformable Barrier (MDB)<br>ES-2re<br>SID-IIs |                                                                 | <b>18. Distribution Statement</b><br>Copies of this report are available from:<br>National Highway Traffic Safety Administration<br>Technical Information Services Division, NPO-411<br>1200 New Jersey Ave., SE<br>Washington, DC 20590<br>e-mail: <a href="mailto:tis@nhtsa.dot.gov">tis@nhtsa.dot.gov</a><br>FAX 202-493-2833 |                  |
| <b>19. Security Classification of this report</b><br>UNCLASSIFIED                                                                | <b>20. Security Classification of this page</b><br>UNCLASSIFIED | <b>21. No. of Pages</b><br>160                                                                                                                                                                                                                                                                                                   | <b>22. Price</b> |

## TABLE OF CONTENTS

| <u>Section</u>    |                                                                  | <u>Page</u> |
|-------------------|------------------------------------------------------------------|-------------|
| 1                 | Test Purpose and Procedure                                       | 1           |
| 2                 | Summary of Test Results                                          | 2           |
| 3                 | Occupant and Vehicle Information/Data Sheets                     | 4           |
| <u>Data Sheet</u> |                                                                  | <u>Page</u> |
| 1                 | General Test and Vehicle Parameter Data                          | 5           |
| 2                 | Seat, Seat Belt, Steering Wheel Adjustment, and Fuel System Data | 9           |
| 3                 | Dummy Longitudinal Clearance Dimensions                          | 13          |
| 4                 | Dummy Lateral Clearance Dimensions                               | 14          |
| 5                 | Camera and Instrumentation Data                                  | 15          |
| 6                 | Test Vehicle Accelerometer Locations                             | 16          |
| 7                 | MDB Accelerometer Locations                                      | 17          |
| 8                 | Post-Test Observations                                           | 18          |
| 9                 | MDB Summary of Results                                           | 21          |
| 10                | Test Vehicle Profile Measurements                                | 22          |
| 11                | Test Vehicle Exterior Crush Measurements                         | 23          |
| 12                | MDB Exterior Static Crush Measurements                           | 26          |
| 13                | Vehicle and MDB Damage Profile Distances                         | 27          |
| 14                | FMVSS No. 301 Static Rollover Results                            | 28          |
| 15                | Dummy/Vehicle Temperature and Humidity Stabilization             | 29          |
| <u>Appendix</u>   |                                                                  | <u>Page</u> |
| A                 | Photographs                                                      | A           |
| B                 | Vehicle and Dummy Response Data Plots                            | B           |
| C                 | Dummy Configuration and Performance Verification Data            | C           |
| D                 | Test Equipment and Instrumentation Calibration Data              | D           |

## **SECTION 1**

### **TEST PURPOSE AND PROCEDURE**

This moving deformable barrier side impact test is part of the MY 2014 New Car Assessment Program Side Impact Test Program, sponsored by the National Highway Traffic Safety Administration (NHTSA), under contract number DTNH22-09-D-00122. The purpose of this test is to generate comparative side impact performance in a 2014 Subaru XV Crosstrek 5-door MPV. The side impact test was conducted in accordance with the Office of Crashworthiness Standard's Laboratory Test Procedure dated September 2013.

## **SECTION 2**

### **SUMMARY OF TEST RESULTS**

A 2014 Subaru XV Crosstrek 5-door MPV was impacted on the left (driver's) side by a Moving Deformable Barrier (MDB) which was moving forward in a 27° crabbed position to the tow road guidance system at a velocity of 61.97 km/h (38.51 mph). The target vehicle was stationary and was positioned at an angle of 63° to the line of forward motion. The side impact test was conducted by KARCO Engineering, LLC. in Adelanto, California, on January 28, 2014. Pre- and post-test photographs of the test vehicle, the MDB and the dummies (ES-2re and SID-IIs) are included in Appendix A of this report.

Dummies were placed in the driver and left rear designated seating positions according to instructions specified in the OCWS Side Impact Laboratory Test Procedure, dated September 2013. The side impact event was documented by 11 cameras. Camera locations are included in Data Sheet No. 5 of this report.

The dummy was instrumented in the following manner:

**DRIVER ATD (ES-2re)**

Primary and redundant head CG tri-axial accelerometers

Chest upper rib, middle rib and lower rib y-axis displacement potentiometers

Abdomen forward, middle, and rear y-axis load cells

Lower spine (12) tri-axial accelerometers

Pubic symphysis y-axis load cell

**PASSENGER ATD (SID-IIs)**

Primary and redundant head CG tri-axial accelerometers

Chest upper rib, middle rib and lower rib y-axis displacement potentiometers

Abdomen upper rib and lower rib y-axis displacement potentiometers

Lower spine (12) tri-axial accelerometers

Acetabulum and iliac wing y-axis load cells

Appendix B contains the vehicle and dummy response data. Dummy configuration and performance verification data can be found in Appendix C of this report. Appendix D of this report contains the test equipment and instrumentation calibration data.

Dummy injury readings were recorded as follows:

| Measurement Description                   | Units | Driver ATD (ES-2re) |        |
|-------------------------------------------|-------|---------------------|--------|
|                                           |       | Threshold           | Result |
| Head Injury Criteria (HIC <sub>36</sub> ) |       | 1000                | 88.2   |
| Maximum Thorax Rib Deflection             | mm    | 44                  | 15     |
| Combined Abdominal Force                  | N     | 2500                | 941    |
| Pubic Symphysis Force                     | N     | 6000                | 1593   |

| Measurement Description                                 | Units | Passenger ATD (SID-IIs) |        |
|---------------------------------------------------------|-------|-------------------------|--------|
|                                                         |       | Threshold               | Result |
| Head Injury Criteria (HIC <sub>36</sub> )               |       | 1000                    | 165.1  |
| Lower Spine (T12) Resultant Acceleration                | g     | 82                      | 51     |
| Total Pelvic Force (sum of acetabular and iliac forces) | N     | 5525                    | 2890   |
| Maximum Thoracic Rib Deflection                         | mm    | 38*                     | 27     |
| Maximum Abdominal Rib Deflection                        | mm    | 45*                     | 17     |

\*Proposed IARV

Supplemental restraint information is given below:

| Restraint Type               | Left Front (Driver)<br>Occupant Location 1 |          | Left Rear (Passenger)<br>Occupant Location 4 |          |
|------------------------------|--------------------------------------------|----------|----------------------------------------------|----------|
|                              | Mounted                                    | Deployed | Mounted                                      | Deployed |
| Frontal Airbag               | Yes                                        | No       | No                                           |          |
| Knee Airbag                  | Yes                                        | No       | No                                           |          |
| Side Airbag 1 (Curtain)      | Yes                                        | Yes      | Yes                                          | Yes      |
| Side Airbag 2 (Torso/Pelvis) | Yes                                        | Yes      | No                                           |          |
| Seat Belt Pretensioner       | Yes                                        | No       | No                                           |          |
| Seat Belt Load Limiter       | Yes                                        | No       | No                                           |          |
| Other                        | No                                         |          | No                                           |          |

## GENERAL COMMENTS

The two doors on the struck side of the vehicle remained closed and latched. There was no separation at the hinges or latches. The doors on the non-struck side remained closed and latched. There were no ATD values that exceeded limits.

### SECTION 3

#### OCCUPANT AND VEHICLE INFORMATION/DATA SHEETS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

#### CONVERSION FACTORS

| Quantity           | Typical Application | Std Units           | Metric Unit | Multiply By       |
|--------------------|---------------------|---------------------|-------------|-------------------|
| Mass               | Vehicle Weight      | lb                  | kg          | 0.4536            |
| Linear Velocity    | Impact Velocity     | miles/hr            | km/hr       | 1.609344          |
| Length or Distance | Measurements        | in                  | mm          | 25.4              |
| Volume             | Fuel Systems        | gal                 | liter       | 3.785             |
| Volume             | Small Fluids        | oz                  | mL          | 29.574            |
| Pressure           | Tire Pressures      | lbf/in <sup>2</sup> | kPa         | 6.895             |
| Temperature        | General Use         | °F                  | °C          | $=(T_f - 32)/1.8$ |
| Force              | Dynamic Forces      | lbf                 | N           | 4.448             |
| Moment             | Torque              | lbf-ft              | N•m         | 1.355             |

# DATA SHEET NO. 1

## GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

## TEST VEHICLE INFORMATION AND OPTIONS

|                            |                    |
|----------------------------|--------------------|
| NHTSA Number               | M20145504          |
| Model Year                 | 2014               |
| Make                       | Subaru             |
| Model                      | XV Crosstrek       |
| Body Style                 | 5-Door MPV         |
| VIN                        | JF2GPACC9E9214236  |
| Body Color                 | Dark Gray Metallic |
| Odometer Reading (km / mi) | 171 / 106          |
| Engine Displacement (L)    | 2.0                |
| Type / No. of Cylinders    | H-4                |
| Engine Placement           | Longitudinal       |
| Transmission Type          | Manual             |
| Transmission Speeds        | 6                  |
| Overdrive                  | Yes                |
| Final Drive                | AWD                |
| Roof Rack                  | Yes                |
| Sunroof / T-Top            | No                 |
| Running Boards             | No                 |
| Tilt Steering Wheel        | Yes                |
| Power Seats                | No                 |
| Anti-Lock Brakes (ABS)     | Yes                |

|                                   |     |
|-----------------------------------|-----|
| Traction Control System (TCS)     | Yes |
| Auto-Leveling System              | No  |
| Automatic Door Locks              | No  |
| Power Window Auto-Reverse         | No  |
| Other Optional Feature            | No  |
| Driver Front Airbag               | Yes |
| Driver Curtain Airbag             | Yes |
| Driver Head/Torso Airbag          | No  |
| Driver Torso Airbag               | No  |
| Driver Torso/Pelvis Airbag        | Yes |
| Driver Pelvis Airbag              | No  |
| Driver Knee Airbag                | Yes |
| Rear Pass. Curtain Airbag         | Yes |
| Rear Pass. Head/Torso Airbag      | No  |
| Rear Pass. Torso Airbag           | No  |
| Rear Pass. Torso/Pelvis Airbag    | No  |
| Rear Pass. Pelvis Airbag          | No  |
| Driver Seat Belt Pretensioner     | Yes |
| Rear Pass. Seat Belt Pretensioner | No  |
| Driver Load Limiter               | Yes |
| Rear Pass. Load Limiter           | No  |
| Other Safety Restraint            | No  |

Does Owner's Manual provide instructions to turn off automatic door locks?

N/A

## DATA FROM CERTIFICATION LABEL

|                     |                            |
|---------------------|----------------------------|
| Manufactured By     | Fuji Heavy Industries Ltd. |
| Date of Manufacture | Sep-13                     |
| Vehicle Type        | MPV / VTUM                 |

|                 |      |
|-----------------|------|
| GVWR (kg)       | 1970 |
| GAWR Front (kg) | 1010 |
| GAWR Rear (kg)  | 1000 |

## VEHICLE SEATING AND CAPACITY WEIGHT INFORMATION

| Measured Parameter          | Front | Rear | Third | Total |
|-----------------------------|-------|------|-------|-------|
| Designated Seating Capacity | 2     | 3    |       | 5     |
| Capacity Weight (VCW) (kg)  |       |      |       | 408.0 |
| DSC x 68.04 (kg)            |       |      |       | 340.2 |
| Cargo Weight (RCLW) (kg)    |       |      |       | 67.8  |


## VEHICLE SEAT TYPE

| Seating Location        | Type of Seat Pan |       |             |           | Type of Seat Back |            |         |
|-------------------------|------------------|-------|-------------|-----------|-------------------|------------|---------|
|                         | Bucket           | Bench | Split Bench | Contoured | Fixed             | Adjustable |         |
|                         |                  |       |             |           |                   | w/ Lever   | w/ Knob |
| Front Seat              | Yes              |       |             |           |                   | Yes        |         |
| Rear or Second Row Seat |                  | Yes   |             |           | Yes               |            |         |
| Third Row Seat          |                  |       |             |           |                   |            |         |

## DATA SHEET NO. 1 ... (CONTINUED)

### GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14



| Measured Parameter       | Front                         | Rear                          |
|--------------------------|-------------------------------|-------------------------------|
| Max. Tire Pressure (kpa) | 300                           | 300                           |
| Cold Pressure (kPa)      | 220                           | 210                           |
| Recommended Tire Size    | P225/55R17                    | P225/55R17                    |
| Tire Size on Vehicle     | P225/55R17                    | P225/55R17                    |
| Tire Manufacturer        | Yokohama                      | Yokohama                      |
| Tire Model               | Geolandar G95                 | Geolandar G95                 |
| Treadware                | 320                           | 320                           |
| Traction Grade           | B                             | B                             |
| Temperature Grade        | A                             | A                             |
| Tire Plies Sidewall      | 2 Polyester                   | 2 Polyester                   |
| Tire Plies Body          | 2 Polyester, 2 Steel, 1 Nylon | 2 Polyester, 2 Steel, 1 Nylon |
| Load Index/Speed Symbol  | 95H                           | 95H                           |
| Tire Material            | Polyester, Steel, Nylon       | Polyester, Steel, Nylon       |
| DOT Safety Code Left     | EDUP N2U3613                  | EDUP N2U3613                  |
| DOT Safety Code Right    | EDUP N2U3613                  | EDUP N2U3613                  |

# DATA SHEET NO. 1 ... (CONTINUED)

## GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

### TIRE PRESSURES

|                | Units | LF  | RF  | LR  | RR  |
|----------------|-------|-----|-----|-----|-----|
| As Delivered   | kPa   | 295 | 265 | 290 | 290 |
| Tire Placard   | kPa   | 220 | 220 | 210 | 210 |
| Owner's Manual | kPa   | 220 | 220 | 210 | 210 |
| As Tested      | kPa   | 220 | 220 | 210 | 210 |

### MDB TIRE SPECIFICATIONS

|               | Units | Requirement | LF         | RF         | LR         | RR         |
|---------------|-------|-------------|------------|------------|------------|------------|
| Tire Size     |       | P205/75R15  | P205/75R15 | P205/75R15 | P205/75R15 | P205/75R15 |
| Tire Pressure | kPa   | 200 ± 21    | 200        | 200        | 200        | 200        |

### TEST VEHICLE AXLE WEIGHTS

|       | Units | As Delivered (UVW) |       |        | As Tested (ATW) |       |        | Fully Loaded |       |        |
|-------|-------|--------------------|-------|--------|-----------------|-------|--------|--------------|-------|--------|
|       |       | Front              | Rear  | Total  | Front           | Rear  | Total  | Front        | Rear  | Total  |
| Left  | kg    | 424.5              | 303.0 |        | 463.0           | 388.0 |        | 466.0        | 393.5 |        |
| Right | kg    | 397.0              | 290.0 |        | 397.0           | 354.0 |        | 395.0        | 352.0 |        |
| Ratio | %     | 58.1%              | 41.9% | 100.0% | 53.7%           | 46.3% | 100.0% | 53.6%        | 46.4% | 100.0% |
| Total | kg    | 821.5              | 593.0 | 1414.5 | 860.0           | 742.0 | 1602.0 | 861.0        | 745.5 | 1606.5 |

### TARGET TEST WEIGHT CALCULATION

| Measured Parameter                  | Units | Value  |       |
|-------------------------------------|-------|--------|-------|
| Total Delivered Weight (UVW)        | kg    | 1414.5 | A     |
| Actual Weight of 2 P572 ATDs Used   | kg    | 125.0  | B     |
| Rated Cargo/Luggage Wt (RCLW)       | kg    | 67.8   | C     |
| Calculated Vehicle Target Wt (TVTW) | kg    | 1607.3 | A+B+C |

Does the measured As Tested Vehicle Weight lie within the required weight range (i.e. Calculated Test Vehicle Target Weight -4.5 kg to -9.0 kg)? ☒ Yes ☐ No

### TEST VEHICLE ATTITUDE AND CG

| Measurement Description                                      | Units | Fully Loaded | As Tested | Meets Requirement*** |
|--------------------------------------------------------------|-------|--------------|-----------|----------------------|
| LF                                                           | mm    | 774          | 777       | Yes                  |
| RF                                                           | mm    | 787          | 784       | Yes                  |
| LR                                                           | mm    | 753          | 749       | Yes                  |
| RR                                                           | mm    | 757          | 748       | Yes                  |
| Vehicle CG (Aft of Front Axle)                               | mm    | 1230         | 1227      |                      |
| Vehicle CG (Left (+)/Right (-) from Longitudinal Centerline) | mm    | 54           | 48        |                      |

\*\*\*The "As Tested" vehicle attitude measurements must be equal to or within ±10 mm of the "Fully Loaded" vehicle attitude measurements at each wheel well. Indicate "Yes" or "No" for "Meets Requirement"

**DATA SHEET NO. 1 ... (CONTINUED)**

**GENERAL TEST AND VEHICLE PARAMETER DATA**

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

**WEIGHT OF BALLAST AND VEHICLE COMPONENTS REMOVED TO MEET TVTW**

| Component Description     | Weight (kg) |
|---------------------------|-------------|
| Spare Tire                | 12.5        |
| Tire Tools                | 2.5         |
| Rear Trim                 | 6.0         |
|                           |             |
| Ballast / Equipment Added | 103.0       |

|                                                |  |
|------------------------------------------------|--|
| Test Height Adjustable Setting (If Applicable) |  |
|------------------------------------------------|--|

**DATA SHEET NO. 2****SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT, AND FUEL SYSTEM DATA**Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14**SEAT POSITIONING**

The driver's seat, front center seat (if applicable), and right front passenger's seat should be set to the mid-track, lowest, mid-angle position. The struck side rear passenger's seat, rear center seat, and non-struck side rear passenger's seats should be set to the rear most, lowest, mid-angle position.

**SCRL ANGLE RANGE**

| Seat                      | SCRL (°) |       |       |
|---------------------------|----------|-------|-------|
|                           | Max      | Min   | Mid   |
| Driver Seat               | 4.2      | 0.0   | 2.1   |
| Front Passenger Seat      | Fixed    | Fixed | Fixed |
| Front Center Seat         |          |       |       |
| Struck Side Rear Seat     | Fixed    | Fixed | Fixed |
| Non-Struck Side Rear Seat | Fixed    | Fixed | Fixed |
| Rear Center Seat          | Fixed    | Fixed | Fixed |

**SEAT HEIGHT AND ANGLE**

| Seat                      | As Tested SCRL Angle | As Tested SCRP Height | SCRP Height Position | SCRP Height (mm) |              |             |
|---------------------------|----------------------|-----------------------|----------------------|------------------|--------------|-------------|
|                           |                      |                       |                      | Rearmost         | Mid Fore/Aft | Forwardmost |
| Driver Seat               | 2.1                  | 602                   | Max                  | 590              | 602          | 613         |
|                           |                      |                       | Mid                  | 590              | 602          | 613         |
|                           |                      |                       | Min                  | 590              | 602          | 613         |
| Front Passenger Seat      | Fixed                | 599                   | Max                  | 587              | 599          | 610         |
|                           |                      |                       | Mid                  | 587              | 599          | 610         |
|                           |                      |                       | Min                  | 587              | 599          | 610         |
| Front Center Seat         |                      |                       | Max                  |                  |              |             |
|                           |                      |                       | Mid                  |                  |              |             |
|                           |                      |                       | Min                  |                  |              |             |
| Struck Side Rear Seat     | Fixed                | Fixed                 | Max                  | Fixed            | Fixed        | Fixed       |
|                           |                      |                       | Mid                  | Fixed            | Fixed        | Fixed       |
|                           |                      |                       | Min                  | Fixed            | Fixed        | Fixed       |
| Non-Struck Side Rear Seat | Fixed                | Fixed                 | Max                  | Fixed            | Fixed        | Fixed       |
|                           |                      |                       | Mid                  | Fixed            | Fixed        | Fixed       |
|                           |                      |                       | Min                  | Fixed            | Fixed        | Fixed       |
| Rear Center Seat          | Fixed                | Fixed                 | Max                  | Fixed            | Fixed        | Fixed       |
|                           |                      |                       | Mid                  | Fixed            | Fixed        | Fixed       |
|                           |                      |                       | Min                  | Fixed            | Fixed        | Fixed       |

## DATA SHEET NO. 2 ... (CONTINUED)

### SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT, AND FUEL SYSTEM DATA


Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

#### SEAT FORE/AFT POSITION

| Seat                      | Total Fore/Aft Travel |         | Test Position From Forwardmost Position |        |
|---------------------------|-----------------------|---------|-----------------------------------------|--------|
|                           | mm                    | Detents | mm                                      | Detent |
| Driver Seat               | 240                   | 25      | 120                                     | 12     |
| Front Passenger Seat      | 240                   | 25      | 120                                     | 12     |
| Front Center Seat         |                       |         |                                         |        |
| Struck Side Rear Seat     | Fixed                 | Fixed   | Fixed                                   | Fixed  |
| Non-Struck Side Rear Seat | Fixed                 | Fixed   | Fixed                                   | Fixed  |
| Rear Center Seat          | Fixed                 | Fixed   | Fixed                                   | Fixed  |

#### SEAT BACK ADJUSTMENT

The driver's seat back is positioned to the manufacturer's designated design angle. The right front passenger's seat back is positioned in a similar manner as the driver's seat back. The struck side rear seat back is positioned such that the dummy's head is level. The rear center and non-struck side rear outboard seat backs are positioned in a similar manner as the struck side rear seat back. Seat back angle is measured at the headrest post.



#### SEAT BACK POSITION

| Seat                                 | Total Seat Back Angle Range |         | Test Position from Most Upright |        |
|--------------------------------------|-----------------------------|---------|---------------------------------|--------|
|                                      | Degrees                     | Detents | Degree                          | Detent |
| Driver Seat w/Seated Dummy           | 64.5                        | 33      | 2.1                             | 5      |
| Front Passenger Seat                 | 64.2                        | 33      | 1.1                             | 5      |
| Front Center Seat                    |                             |         |                                 |        |
| Struck Side Rear Seat w/Seated Dummy | Fixed                       | Fixed   | Fixed                           | Fixed  |
| Non-Struck Side Rear Seat            | Fixed                       | Fixed   | Fixed                           | Fixed  |
| Rear Center Seat                     | Fixed                       | Fixed   | Fixed                           | Fixed  |

**DATA SHEET NO. 2 ... (CONTINUED)****SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT, AND FUEL SYSTEM DATA**

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

**SEAT BELT ANCHORAGE ADJUSTMENT**

Seat belt anchorages are adjusted in accordance with the information provided by the manufacturer on Form No. 1. The positions are marked H, M1,..., L from top to bottom.

|             | Total No. of Positions | Placed in Position |
|-------------|------------------------|--------------------|
| Driver Seat | 4                      | M1                 |
| Rear Seat   | Fixed                  | Fixed              |

**HEAD RESTRAINT ADJUSTMENT**


The driver's head restraint is adjusted to the highest and most full forward in-use position. The struck-side rear passenger's head restraint is adjusted to the lowest and most full forward in-use position.

|             | Total No. of Positions   | Placed in Position    |
|-------------|--------------------------|-----------------------|
| Driver Seat | 3 Vertical, 5 Horizontal | Full Up, Full Forward |
| Rear Seat   | Fixed                    | Fixed                 |

**STEERING COLUMN ADJUSTMENT**

Steering wheel and column adjustments are made so that the steering wheel hub is at the center of the geometric locus it describes when it moves through its full range of motion.

|                                   | Degrees | Fore-Aft Position (mm) |
|-----------------------------------|---------|------------------------|
| Lowermost - Position 1            | 21.9    | 121                    |
| Geometric Center - Position 2     | 23.3    | 141                    |
| Uppermost - Position 3            | 24.7    | 160                    |
| Telescoping Steering Wheel Travel |         | 39                     |
| Test Position                     | 23.3    | 141                    |




## DATA SHEET NO. 2 ... (CONTINUED)

### SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT, AND FUEL SYSTEM DATA

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

#### FUEL PUMP

The vehicle is equipped with an electric fuel pump. The fuel pump operates for a few seconds after the ignition is turned "ON" and then only operates when the engine is running.



#### FUEL TANK CAPACITY


| Description                                             | Liters |
|---------------------------------------------------------|--------|
| Usable Capacity of "Standard Tank" (see Form No. 1)     | 60.18  |
| Usable Capacity of "Optional Tank" (see Form No. 1)     |        |
| Usable Capacity of "Standard Tank" (see Owner's Manual) |        |
| Usable Capacity of "Optional Tank" (see Owner's Manual) |        |
| 93% of Usable Capacity                                  | 55.98  |
| Actual amount of Solvent Used in Test                   | 55.98  |
| 1/3 of Usable Capacity                                  | 20.06  |

Is the Actual Amount of Solvent Used in the test equal to  $93\% \pm 1\%$  of the Usable Capacity stated in the Form No. 1? ☒ Yes ☐ No

### DATA SHEET NO. 3

#### DUMMY LONGITUDINAL CLEARANCE DIMENSIONS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14



**LEFT SIDE VIEW**

NOTE: 2-DOOR VEHICLE SHOWN.  
 REAR DUMMY PHX & PHZ  
 MEASUREMENTS FOR A 4-DOOR  
 VEHICLE WOULD USE THE C-POST  
 STRIKER AS A REFERENCE POINT


#### DUMMY LONGITUDINAL CLEARANCE DIMENSION INFORMATION

| Driver Code   | Pass. Code    | Description                   | Driver      |           | Passenger   |           |
|---------------|---------------|-------------------------------|-------------|-----------|-------------|-----------|
|               |               |                               | Length (mm) | Angle (°) | Length (mm) | Angle (°) |
| HH            |               | Head to Header                | 366         |           |             |           |
| HW            |               | Head to Windshield            | 690         |           |             |           |
| HZ            | HZ            | Head to Roof                  | 200         |           | 261         |           |
| NR            | NB            | Nose to Rim/Seat Back         | 422         |           | 565         |           |
| CD            | CB            | Chest to Dash/Seat Back       | 554         |           | 548         |           |
| CS            |               | Chest to Steering Wheel       | 297         |           |             |           |
| KD(L)/KDA(L)° | KB(L)/KBA(L)° | Left Knee to Dash/Seat Back   | 163         | 30.4      | 272         | 40.9      |
| KD(R)/KDA(R)° | KB(R)/KBA(R)° | Right Knee to Dash/Seat Back  | 154         | 34.4      | 281         | 38.9      |
| PAX°          | PAX°          | Pelvic Tilt Angle X           |             | 19.1      |             | 22.0      |
|               | PAY°          | Pelvic Tilt Angle Y           |             | 0.2       |             | 0.4       |
| PHX           | PHX           | Hip Point to Striker (x-axis) | 226         |           | 297         |           |
| PHZ           | PHZ           | Hip Point to Striker (z-axis) | 218         |           | 293         |           |

## DATA SHEET NO. 4

### DUMMY LATERAL CLEARANCE DIMENSIONS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14




### DUMMY LATERAL CLEARANCE DIMENSION INFORMATION

| Code | Measurement Description | Units | Driver | Passenger |
|------|-------------------------|-------|--------|-----------|
| HR   | Head to Side Header     | mm    | 226    | 247       |
| HS   | Head to Side Window     | mm    | 342    | 353       |
| AD   | Arm to Door             | mm    | 101    | 139       |
| HD   | H-Point to Door         | mm    | 142    | 159       |

## DATA SHEET NO. 5

### CAMERA AND INSTRUMENTATION DATA

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14



### CAMERA LOCATIONS AND DATA

| No. | View                      | Coordinates (mm) |       |       | Lens Length (mm) | Operating Frame Rate (fps) |
|-----|---------------------------|------------------|-------|-------|------------------|----------------------------|
|     |                           | X                | Y     | Z     |                  |                            |
| 1   | Overhead Overall          | 1220             | 2287  | -5486 | 14               | 1000                       |
| 2   | Overhead Close-Up         | 609              | 2287  | -5102 | 35               | 1000                       |
| 3   | Left Impact Point (MDB)   | -2134            | 0     | -1143 | 25               | 1000                       |
| 4   | Side Overall (MDB)        | -3912            | 838   | -1829 | 12.5             | 1000                       |
| 5   | Rear                      | -64              | 2485  | -1348 | 85               | 1000                       |
| 6   | Left Front                | -2266            | -3564 | -1475 | 24               | 1000                       |
| 7   | Driver Front (On-Board)   | 462              | -978  | -718  | 24               | 1000                       |
| 8   | Driver Side (On-Board)    | 1668             | 855   | -396  | 12               | 1000                       |
| 9   | Passenger Side (On-Board) | 1701             | 1704  | -381  | 12               | 1000                       |
| 10  | Real Time Overall         |                  |       |       | Zoom             | 30                         |
| 11  | Real Time Inrun           |                  |       |       | Zoom             | 30                         |

Reference: Impact Point Projected to Ground; +X = To Front of MDB, +Y = To Right of MDB, +Z = Down

\*All measurements accurate to  $\pm 6$  mm


### INSTRUMENTATION

|                                  |    |
|----------------------------------|----|
| Driver Dummy Channels            | 16 |
| Passenger Dummy Channels         | 16 |
| Vehicle Structure Accelerometers | 22 |
| MDB Accelerometers               | 5  |
| Total                            | 59 |

## DATA SHEET NO. 6

### TEST VEHICLE ACCELEROMETER LOCATIONS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV      NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test      Test Date: 01/28/14



### VEHICLE ACCELEROMETER PRE-TEST LOCATIONS


| Loc. No. | Sensor Description              | Coordinates (mm) |      |      |
|----------|---------------------------------|------------------|------|------|
|          |                                 | X                | Y    | Z    |
| 1        | Vehicle CG                      | 1690             | 0    | -448 |
| 2        | Right Sill at Front Seat        | 2573             | 715  | -432 |
| 3        | Right Sill at Rear Seat         | 1720             | 715  | -432 |
| 4        | Left Sill at Front Door         | 2462             | -744 | -253 |
| 5        | Left Sill at Rear Door          | 1560             | -744 | -253 |
| 6        | A-Pillar Lower                  | 2946             | -814 | -662 |
| 7        | A-Pillar Middle                 | 2946             | -814 | -947 |
| 8        | B-Pillar Lower                  | 1933             | -725 | -590 |
| 9        | B-Pillar Middle                 | 1933             | -725 | -876 |
| 10       | Front Seat Track                | 2188             | -190 | -409 |
| 11       | Rear Seat Structure             |                  |      |      |
| 12       | Right Rear Occupant Compartment | 1700             | 340  | -282 |
| 13       | Engine Block                    | 3773             | 0    | -692 |
| 14       | Rear Floorpan Above Axle        | 988              | 0    | -656 |

Reference:      X – Rear surface of vehicle (+ forward)  
                      Y – Vehicle centerline (+ to right)  
                      Z – Ground plane (+ down)

## DATA SHEET NO. 7

### MDB ACCELEROMETER LOCATIONS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14



### MDB ACCELEROMETER LOCATIONS

| Loc. No. | Accelerometer Location | Measurement |      |      |
|----------|------------------------|-------------|------|------|
|          |                        | X           | Y    | Z    |
| 1        | MDB CG                 | -1195       | 0    | -430 |
| 2        | MDB Rear               | -2642       | -593 | -608 |

Reference: X – Face of MDB (+ forward)  
Y – MDB centerline (+ to right)  
Z – Ground plane (+ down)

**DATA SHEET NO. 8**  
**POST-TEST OBSERVATIONS**

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

**TEST DUMMY INFORMATION AND CONTACT POINTS**

| Dummy Body Part   | Front Seat Dummy (ES-2re)             | Rear Seat Dummy (SID-IIs)                                   |
|-------------------|---------------------------------------|-------------------------------------------------------------|
| Face              | Curtain Airbag                        | Curtain Airbag                                              |
| Top of Head       | Side Header                           | Curtain Airbag, Side Header, Center Seat Headrest           |
| Left Side of Head | Curtain Airbag                        | Curtain Airbag                                              |
| Back of Head      | Curtain Airbag, Side Header, Headrest | Curtain Airbag, Side Header, Headrest, Center Seat Headrest |
| Left Shoulder     | Curtain Airbag                        | Door Panel                                                  |
| Upper Torso       | Seat, Torso/Pelvis Airbag             | Door Panel                                                  |
| Lower Torso       | Seat, Torso/Pelvis Airbag             | Seat, Door Panel                                            |
| Left Hip          | Torso/Pelvis Airbag, Door Panel       | Seat, Door Panel                                            |
| Left Knee         | Door Panel, Right Knee                | Door Panel, Right Knee                                      |

**POST-TEST DOOR PERFORMANCE**

| Description                                                        | Struck Side |      | Non-Struck Side |      | Rear Hatch/Other |
|--------------------------------------------------------------------|-------------|------|-----------------|------|------------------|
|                                                                    | Front       | Rear | Front           | Rear |                  |
| Remained Closed and Operational                                    | No          | No   | Yes             | Yes  | Yes              |
| Total Separation from Vehicle at Hinges or Latches                 | No          | No   | No              | No   | No               |
| Latch or Hinge System Pulled Out of Their Anchorages               | No          | No   | No              | No   | No               |
| Disengaged from Latched Position                                   | No          | No   | No              | No   | No               |
| Latch Separated from Striker                                       | No          | No   | No              | No   | No               |
| Jammed Shut                                                        | Yes         | Yes  | No              | No   | No               |
| If Door Opened at Striker, Record Width of Opening at Striker (mm) | N/A         | N/A  | N/A             | N/A  | N/A              |

**DATA SHEET NO. 8 ... (CONTINUED)****POST-TEST OBSERVATIONS**

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

**POST-TEST SEAT PERFORMANCE**

| Description                              | Struck Side |      | Non-Struck Side |      |
|------------------------------------------|-------------|------|-----------------|------|
|                                          | Front       | Rear | Front           | Rear |
| Seat Movement Along Seat Track           | No          | No   | No              | No   |
| Seat Disengagement from Floor Pan        | No          | No   | No              | No   |
| Seat Back Movement from Initial Position | No          | No   | No              | No   |
| Seat Back Collapse                       | No          | No   | No              | No   |

**POST-TEST STRUCTURAL OBSERVATIONS**

| Critical Areas of Performance | Observations and Conclusions |
|-------------------------------|------------------------------|
| Pillar Performance            | No separation                |
| Sill Separation               | No separation                |
| Windshield Damage             | None                         |
| Side Window Damage            | Left front window broken     |
| Other Notable Effects         | None                         |

**DATA SHEET NO. 8 ... (CONTINUED)****POST-TEST OBSERVATIONS**

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

**SUPPLEMENTAL RESTRAINT SYSTEM INFORMATION**

| Restraint Type               | Struck Side Driver |          | Struck Side Rear Passenger |          |
|------------------------------|--------------------|----------|----------------------------|----------|
|                              | Mounted            | Deployed | Mounted                    | Deployed |
| Frontal Airbag               | Yes                | No       | No                         |          |
| Knee Airbag                  | Yes                | No       | No                         |          |
| Side Airbag 1 (Curtain)      | Yes                | Yes      | Yes                        | Yes      |
| Side Airbag 2 (Torso/Pelvis) | Yes                | Yes      | No                         |          |
| Seat Belt Pretensioner       | Yes                | No       | No                         |          |
| Seat Belt Load Limiter       | Yes                | No       | No                         |          |
| Other                        | No                 |          | No                         |          |

**IMPACT POINT LOCATION DATA**

| Measured Parameter                                                        | Units | Tolerance                     | Value |
|---------------------------------------------------------------------------|-------|-------------------------------|-------|
| Vehicle Wheel Base                                                        | mm    |                               | 2650  |
| Vertical Impact Reference Line (Aft of Front Axle)(Intended Impact Point) | mm    |                               | 385   |
| Actual Impact Point (Aft of Front Axle)                                   | mm    |                               | 385   |
| Horizontal Offset (+ forward / - rearward)                                | mm    | ± 50 of Intended Impact Point | 0     |
| Vertical Offset (+ down / - up)                                           | mm    | ± 20 of Intended Impact Point | 7     |

**DATA SHEET NO. 9****MDB SUMMARY OF RESULTS**

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

**MDB SPECIFICATIONS**

| Measurement Description                 | Length (mm) |
|-----------------------------------------|-------------|
| Overall Width of Framework Carriage     | 1251        |
| Overall Length including Honeycomb Face | 4023        |
| Wheel Base of Framework Carriage        | 2595        |
| CG location aft of Front Axle           | 1118        |

**MDB WEIGHTS**

|        | Units | Front Axle | Rear Axle | Total  |
|--------|-------|------------|-----------|--------|
| Left   | kg    | 401.8      | 298.0     | 699.8  |
| Right  | kg    | 376.9      | 291.6     | 668.5  |
| Ratio  | %     | 56.9%      | 43.1%     | 100.0% |
| Totals | kg    | 778.7      | 589.6     | 1368.3 |

**SPEED AND IMPACT DATA**

| Measured Parameter                              | Units   | Requirement  | Value |
|-------------------------------------------------|---------|--------------|-------|
| Trap No. 1 Velocity (Primary)                   | km/h    | 61.1 to 62.7 | 61.97 |
| Trap No. 2 Velocity (Redundant)                 | km/h    | 61.1 to 62.7 | 61.99 |
| MDB CL to Target Vehicle CL                     | degrees | 88.5 to 91.5 | 90.5  |
| MDB Forward Line of Motion to Target Vehicle CL | degrees | 62.5 to 63.5 | 62.7  |
| MDB Crabbed Angle to MDB Forward Line of Motion | degrees | 26.0 to 28.0 | 27.8  |


**MAXIMUM STATIC CRUSH OF HONEYCOMB FACE**

| Vertical Location |                  |             | From Centerline |           | Max. Crush (mm) |
|-------------------|------------------|-------------|-----------------|-----------|-----------------|
| Row               | Description      | Height (mm) | Distance (mm)   | Direction |                 |
| A                 | Center of Bumper | 432         | 800             | Right     | 259             |
| B                 | Top of Bumper    | 533         | 800             | Right     | 167             |
| C                 | Mid Level        | 686         | 800             | Left      | 168             |
| D                 | Top of Stack     | 813         | 800             | Left      | 227             |

## DATA SHEET NO. 10

### TEST VEHICLE PROFILE MEASUREMENTS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14



**LEFT SIDE VIEW**

### VEHICLE PRE- AND POST-TEST MEASUREMENT INFORMATION

| Code | Description                                | Pre-Test | Post-Test | Difference |
|------|--------------------------------------------|----------|-----------|------------|
| A    | Wheelbase                                  | 2650     | 2640      | -10        |
| B    | Front Axle to FSOV                         | 958      | 961       | 3          |
| C    | Rear Axle to RSOV                          | 837      | 842       | 5          |
| D    | Total Length at Centerline                 | 4445     | 4443      | -2         |
| E    | Front Bumper Thickness                     | 112      | 113       | 1          |
| F    | Front Bumper Bottom to Ground              | 499      | 501       | 2          |
| G    | Sill Height at Front Wheel Well            | 316      | 330       | 14         |
| H    | Sill Height at Front Door Leading Edge     | 339      | 353       | 14         |
| I    | Sill Height at B-Pillar                    | 344      | 364       | 20         |
| J1   | Sill Height at Rear Wheel Well             | 258      | 301       | 43         |
| J2   | Pinch Weld Height at Rear Wheel Well       | 235      | 262       | 27         |
| K    | Sill Height Aft of Rear Wheel Well         | 300      | 327       | 27         |
| L    | Rear Bumper Thickness                      | 161      | 163       | 2          |
| M    | Rear Bumper Bottom to Ground               | 488      | 513       | 25         |
| N    | Sill Height to Bottom of Front Window Sill | 658      | 610       | -48        |
| O    | Front Door Leading Edge to Impact CL       | 752      | 725       | -27        |
| P    | Rear Door Trailing Edge to Impact CL       | 1416     | 1385      | -31        |
| Q    | Front Window Opening                       | 424      | 440       | 16         |
| R    | Right Side Length                          | 3310     | 3312      | 2          |
| S    | Left Side Length                           | 3311     | 3299      | -12        |
| T    | Vehicle Width at B-Pillar                  | 1735     | 1644      | -91        |


All measurements in mm with tolerance of  $\pm 3$ mm

## DATA SHEET NO. 11

### TEST VEHICLE EXTERIOR CRUSH MEASUREMENTS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504

Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14



LEFT SIDE VIEW

### MAXIMUM EXTERIOR CRUSH MEASUREMENTS

| Level | Description      | Height Above Ground (mm) | Maximum Exterior Static Crush | Distance from Impact |
|-------|------------------|--------------------------|-------------------------------|----------------------|
| 1     | Sill Top         | 296                      | 37                            | 1500                 |
| 2     | Occupant H-Point | 608                      | 174                           | 1650                 |
| 3     | Mid-Door         | 729                      | 207                           | 1650                 |
| 4     | Window Sill      | 972                      | 94                            | 1350                 |
| 5     | Window Top       | 1486                     | 16                            | 900                  |

# DATA SHEET NO. 11 ... (CONTINUED)

## TEST VEHICLE EXTERIOR CRUSH MEASUREMENTS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504

Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14

### EXTERIOR CRUSH MEASUREMENTS AT EACH LEVEL

|      | Pre-Test (mm) |     |     |     |     | Post-Test (mm) |     |     |     |     | Difference (mm) |     |     |    |    |
|------|---------------|-----|-----|-----|-----|----------------|-----|-----|-----|-----|-----------------|-----|-----|----|----|
|      | 1             | 2   | 3   | 4   | 5   | 1              | 2   | 3   | 4   | 5   | 1               | 2   | 3   | 4  | 5  |
| -900 |               |     |     |     |     |                |     |     |     |     |                 |     |     |    |    |
| -750 |               |     |     |     |     |                |     |     |     |     |                 |     |     |    |    |
| -600 |               |     |     |     |     |                |     |     |     |     |                 |     |     |    |    |
| -450 |               |     |     | 731 |     |                |     |     | 740 |     |                 |     |     | 9  |    |
| -300 |               |     |     | 706 |     |                |     |     | 715 |     |                 |     |     | 9  |    |
| -150 |               |     | 611 | 697 |     |                |     | 630 | 709 |     |                 |     | 19  | 12 |    |
| 0    | 621           | 621 | 630 | 694 |     | 645            | 651 | 659 | 710 |     | 24              | 30  | 29  | 16 |    |
| 150  | 665           | 634 | 633 | 690 |     | 681            | 731 | 730 | 685 |     | 16              | 97  | 97  | -5 |    |
| 300  | 665           | 634 | 632 | 663 |     | 685            | 759 | 770 | 675 |     | 20              | 125 | 138 | 12 |    |
| 450  | 665           | 633 | 630 | 680 |     | 689            | 761 | 796 | 718 |     | 24              | 128 | 166 | 38 |    |
| 600  | 664           | 632 | 628 | 673 |     | 691            | 763 | 806 | 721 |     | 27              | 131 | 178 | 48 |    |
| 750  | 664           | 632 | 627 | 669 | 880 | 695            | 769 | 808 | 724 | 896 | 31              | 137 | 181 | 55 | 16 |
| 900  | 664           | 631 | 627 | 664 | 879 | 696            | 775 | 804 | 729 | 895 | 32              | 144 | 177 | 65 | 16 |
| 1050 | 665           | 632 | 627 | 661 | 883 | 699            | 779 | 770 | 716 | 898 | 34              | 147 | 143 | 55 | 15 |
| 1200 | 665           | 634 | 629 | 660 | 888 | 700            | 764 | 768 | 702 | 903 | 35              | 130 | 139 | 42 | 15 |
| 1350 | 665           | 635 | 630 | 661 | 892 | 700            | 787 | 817 | 755 | 907 | 35              | 152 | 187 | 94 | 15 |
| 1500 | 664           | 636 | 631 | 662 | 893 | 701            | 790 | 834 | 733 | 908 | 37              | 154 | 203 | 71 | 15 |
| 1650 | 665           | 636 | 633 | 666 | 896 | 698            | 810 | 840 | 722 | 910 | 33              | 174 | 207 | 56 | 14 |
| 1800 | 658           | 633 | 634 | 668 | 896 | 688            | 787 | 833 | 716 | 910 | 30              | 154 | 199 | 48 | 14 |
| 1950 |               | 615 | 631 | 673 | 898 |                | 645 | 740 | 705 | 911 |                 | 30  | 109 | 32 | 13 |
| 2100 |               |     | 612 | 674 | 900 |                |     | 638 | 669 | 912 |                 |     | 26  | -5 | 12 |
| 2250 |               |     |     | 683 | 906 |                |     |     | 708 | 917 |                 |     |     | 25 | 11 |
| 2400 |               |     |     | 688 | 914 |                |     |     | 705 | 924 |                 |     |     | 17 | 10 |
| 2550 |               |     |     | 695 | 925 |                |     |     | 705 | 937 |                 |     |     | 10 | 12 |
| 2700 |               |     |     |     |     |                |     |     |     |     |                 |     |     |    |    |
| 2850 |               |     |     |     |     |                |     |     |     |     |                 |     |     |    |    |

# DATA SHEET NO. 11 ... (CONTINUED)


## TEST VEHICLE EXTERIOR CRUSH MEASUREMENTS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV

NHTSA No. M20145504

Test Program: NCAP MDB Side Impact Test


Test Date: 01/28/14



## DATA SHEET NO. 12

### MDB EXTERIOR STATIC CRUSH MEASUREMENTS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV      NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test      Test Date: 01/28/14



NOTE: Dimensions are shown in millimeters, mm

### DEFORMABLE BARRIER STATIC CRUSH


| Stack Level | Distance Right of Center |     |     |     |     |     |     |     | C/L | Distance Left of Center |     |     |     |     |     |     |     |
|-------------|--------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-------------------------|-----|-----|-----|-----|-----|-----|-----|
|             | 800                      | 700 | 600 | 500 | 400 | 300 | 200 | 100 |     | 100                     | 200 | 300 | 400 | 500 | 600 | 700 | 800 |
| 1           | 259                      | 239 | 234 | 232 | 234 | 229 | 231 | 232 | 224 | 231                     | 232 | 232 | 231 | 235 | 233 | 235 | 256 |
| 2           | 167                      | 157 | 158 | 152 | 137 | 140 | 135 | 130 | 132 | 140                     | 147 | 151 | 155 | 157 | 157 | 157 | 164 |
| 3           | 75                       | 79  | 83  | 95  | 107 | 112 | 126 | 102 | 82  | 79                      | 77  | 77  | 82  | 92  | 102 | 127 | 168 |
| 4           | 81                       | 72  | 72  | 76  | 104 | 138 | 145 | 108 | 84  | 75                      | 77  | 82  | 102 | 117 | 152 | 192 | 227 |

All dimensions in millimeters.

## DATA SHEET NO. 13

### VEHICLE AND MDB DAMAGE PROFILE DISTANCES

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14



### VEHICLE DAMAGE PROFILE DISTANCES

| DPD | Distance From Impact Point (mm) | Level | Pre-Test (mm) | Post-Test (mm) | Crush (mm) |
|-----|---------------------------------|-------|---------------|----------------|------------|
| 1   | 2550                            | 5     | 925           | 937            | 12         |
| 2   | 1950                            | 3     | 631           | 740            | 109        |
| 3   | 1350                            | 3     | 630           | 817            | 187        |
| 4   | 750                             | 3     | 627           | 808            | 181        |
| 5   | 150                             | 3     | 633           | 730            | 97         |
| 6   | -450                            | 4     | 731           | 740            | 9          |

### MDB DAMAGE PROFILE DISTANCES


| DPD | From MDB Centerline |           | Level | Crush (mm) |
|-----|---------------------|-----------|-------|------------|
|     | Distance (mm)       | Direction |       |            |
| 1   | 800                 | Left      | 1     | 256        |
| 2   | 500                 | Left      | 1     | 235        |
| 3   | 200                 | Left      | 1     | 232        |
| 4   | 200                 | Right     | 1     | 231        |
| 5   | 500                 | Right     | 1     | 232        |
| 6   | 800                 | Right     | 1     | 259        |

## DATA SHEET NO. 14

### FMVSS NO. 301 STATIC ROLLOVER RESULTS

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
 Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14  
 Temperature at Time of Impact: 24.4° C Test Time: 11:47 AM

- A. From impact until vehicle motion ceases: 0 oz.  
 (Maximum allowable = 1 oz.)
- B. For the 5 minute period after motion ceases: 0 oz.  
 (Maximum allowable = 5 oz.)
- C. For the following 25 minutes: 0 oz.  
 (Maximum allowable = 1 oz./minute)
- D. Spillage Details: There was no Stoddard solvent spillage.



### SOLVENT COLLECTION TIME TABLE IN SECONDS

| Test Phase   | Rotation Time | Hold Time | Total Time |
|--------------|---------------|-----------|------------|
| 0° To 90°    | 83            | 300       | 383        |
| 90° To 180°  | 82            | 300       | 382        |
| 180° To 270° | 80            | 300       | 380        |
| 270° To 360° | 86            | 300       | 386        |

### FMVSS 301 SPILLAGE TABLE

| Test Phase   | First 5 Minutes | Sixth Minute | Seventh Minute | Eighth Minute |
|--------------|-----------------|--------------|----------------|---------------|
| 0° To 90°    | 0               |              |                |               |
| 90° To 180°  | 0               |              |                |               |
| 180° To 270° | 0               |              |                |               |
| 270° To 360° | 0               |              |                |               |


### SOLVENT SPILLAGE LOCATION TABLE

| Test Phase   | Spillage Location |
|--------------|-------------------|
| 0° To 90°    | N/A               |
| 90° To 180°  | N/A               |
| 180° To 270° | N/A               |
| 270° To 360° | N/A               |

## DATA SHEET NO. 15

### DUMMY/VEHICLE TEMPERATURE AND HUMIDITY STABILIZATION

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV NHTSA No. M20145504  
Test Program: NCAP MDB Side Impact Test Test Date: 01/28/14



**APPENDIX A**  
**PHOTOGRAPHS**

## TABLE OF PHOTOGRAPHS

| Figure |                                                                                        | Page |
|--------|----------------------------------------------------------------------------------------|------|
| 1      | As-Delivered Right Front $\frac{3}{4}$ View of Test Vehicle                            | A-1  |
| 2      | As-Delivered Left Rear $\frac{3}{4}$ View of Test Vehicle                              | A-1  |
| 3      | Pre-Test Frontal View of Test Vehicle                                                  | A-2  |
| 4      | Post-Test Frontal View of Test Vehicle                                                 | A-2  |
| 5      | Pre-Test Left Front $\frac{3}{4}$ View of Test Vehicle                                 | A-3  |
| 6      | Post-Test Left Front $\frac{3}{4}$ View of Test Vehicle                                | A-3  |
| 7      | Pre-Test Left Side View of Test Vehicle                                                | A-4  |
| 8      | Post-Test Left Side View of Test Vehicle                                               | A-4  |
| 9      | Pre-Test Left Rear $\frac{3}{4}$ View of Test Vehicle                                  | A-5  |
| 10     | Post-Test Left Rear $\frac{3}{4}$ View of Test Vehicle                                 | A-5  |
| 11     | Pre-Test Rear View of Test Vehicle                                                     | A-6  |
| 12     | Post-Test Rear View of Test Vehicle                                                    | A-6  |
| 13     | Pre-Test Right Side View of Test Vehicle                                               | A-7  |
| 14     | Post-Test Right Side View of Test Vehicle                                              | A-7  |
| 15     | Pre-Test Overhead View of Test Area                                                    | A-8  |
| 16     | Post-Test Overhead View of Test Area                                                   | A-8  |
| 17     | Pre-Test Left Side View of MDB Positioned Against Side of Test Vehicle                 | A-9  |
| 18     | Pre-Test Right Side View of MDB Positioned Against Side of Test Vehicle                | A-9  |
| 19     | Pre-Test Close-Up View of Impact Point Target                                          | A-10 |
| 20     | Post-Test Close-Up View of Impact Point Target                                         | A-10 |
| 21     | Pre-Test Left Front Door Latch Close-Up                                                | A-11 |
| 22     | Post-Test Left Front Door Latch Close-Up                                               | A-11 |
| 23     | Pre-Test Left Rear Door Latch Close-Up                                                 | A-12 |
| 24     | Post-Test Left Rear Door Latch Close-Up                                                | A-12 |
| 25     | Pre-Test Front Close-Up View of Driver Dummy                                           | A-13 |
| 26     | Post-Test Front Close-Up View of Driver Dummy                                          | A-13 |
| 27     | Pre-Test Left Side View of Driver Dummy Showing Belt and Chalking                      | A-14 |
| 28     | Pre-Test Left Side View of Driver Dummy Shoulder and Door Top View                     | A-14 |
| 29     | Post-Test Left Side View of Driver Dummy Shoulder and Door Top View                    | A-15 |
| 30     | Pre-Test Frontal View of Driver Seat Back Prior to Dummy Positioning                   | A-15 |
| 31     | Pre-Test Frontal View of Driver Dummy Head and Shoulders in Relation to Head Restraint | A-16 |
| 32     | Pre-Test Overhead View of Driver Seat Pan Prior to Dummy Positioning                   | A-16 |
| 33     | Pre-Test Overhead View of Driver Dummy Thighs on Seat Pan                              | A-17 |
| 34     | Pre-Test Placement of Driver Dummy's Feet                                              | A-17 |
| 35     | Pre-Test View of Belt Anchorage for Driver Dummy                                       | A-18 |

## TABLE OF PHOTOGRAPHS ... (CONTINUED)

| Figure |                                                                                                | Page |
|--------|------------------------------------------------------------------------------------------------|------|
| 36     | Pre-Test Left Side View of Steering Wheel                                                      | A-18 |
| 37     | View of Disengaged Parking Brake                                                               | A-19 |
| 38     | Pre-Test View of Parking Brake                                                                 | A-19 |
| 39     | Pre-Test Close-Up Left Side View of Driver Seat Track                                          | A-20 |
| 40     | Pre-Test Close-Up Left Side View of Driver Seat Back                                           | A-20 |
| 41     | Pre-Test Close-Up View of Driver Seat Back or Head Restraint                                   | A-21 |
| 42     | Pre-Test Driver Dummy and Door Clearance View                                                  | A-21 |
| 43     | Post-Test Driver Dummy and Door Clearance View                                                 | A-22 |
| 44     | Pre-Test Right Side View of Driver Dummy and Front Seat Occupant Compartment                   | A-22 |
| 45     | Post-Test Right Side View of Driver Dummy and Front Seat Occupant Compartment                  | A-23 |
| 46     | Pre-Test Driver Inner Door Panel View                                                          | A-23 |
| 47     | Post-Test Driver Inner Door Panel View Showing Driver Dummy Contact Locations                  | A-24 |
| 48     | Post-Test Driver Dummy Close-Up Head Contact with Vehicle Interior View                        | A-24 |
| 49     | Post-Test Driver Dummy Close-Up Head Contact with Side Airbag View                             | A-25 |
| 50     | Post-Test Driver Dummy Close-Up Torso Contact with Vehicle Interior View                       | A-25 |
| 51     | Post-Test Driver Dummy Close-Up Torso Contact with Side Airbag View                            | A-26 |
| 52     | Post-Test Driver Dummy Close-Up Pelvis Contact View                                            | A-26 |
| 53     | Post-Test Driver Dummy Close-Up Pelvis Contact with Side Airbag View                           | A-27 |
| 54     | Post-Test Driver Dummy Close-Up Knee Contact View                                              | A-27 |
| 55     | Pre-Test Left Side View of Rear Passenger Dummy Showing Belt and Chalking                      | A-28 |
| 56     | Pre-Test Left Side View of Rear Passenger Dummy Shoulder and Door Top View                     | A-28 |
| 57     | Post-Test Left Side View of Rear Passenger Dummy Shoulder and Door Top View                    | A-29 |
| 58     | Pre-Test Frontal View of Rear Passenger Seat Back Prior to Dummy Positioning                   | A-29 |
| 59     | Pre-Test Frontal View of Rear Passenger Dummy Head and Shoulders in Relation to Head Restraint | A-30 |
| 60     | Pre-Test Overhead View of Rear Passenger Seat Pan Prior to Dummy Positioning                   | A-30 |
| 61     | Pre-Test Overhead View of Rear Passenger Dummy Thighs on Seat Pan                              | A-31 |
| 62     | Pre-Test View of Rear Passenger Dummy's Neck Showing Position of Adjustable Neck Bracket       | A-31 |
| 63     | Pre-Test View of Rear Passenger Dummy's Head Showing Dummy's Head is Level                     | A-32 |
| 64     | Pre-Test Placement of Rear Passenger Dummy's Feet                                              | A-32 |
| 65     | Pre-Test View of Belt Anchorage for Rear Passenger Dummy                                       | A-33 |
| 66     | Pre-Test Close-Up Left Side View of Rear Passenger Seat Track                                  | A-33 |
| 67     | Pre-Test Close-Up Left Side View of Rear Passenger Seat Back                                   | A-34 |
| 68     | Pre-Test Close-Up View of Rear Passenger Seat Back or Head Restraint                           | A-34 |
| 69     | Pre-Test Rear Passenger Dummy and Door Clearance View                                          | A-35 |
| 70     | Post-Test Rear Passenger Dummy and Door Clearance View                                         | A-35 |

## TABLE OF PHOTOGRAPHS ... (CONTINUED)

| Figure |                                                                                               | Page |
|--------|-----------------------------------------------------------------------------------------------|------|
| 71     | Pre-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment           | A-36 |
| 72     | Post-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment          | A-36 |
| 73     | Pre-Test Rear Passenger Inner Door Panel View                                                 | A-37 |
| 74     | Post-Test Rear Passenger Inner Door Panel View Showing Rear Passenger Dummy Contact Locations | A-37 |
| 75     | Post-Test Rear Passenger Dummy Close-Up Head Contact with Vehicle Interior View               | A-38 |
| 76     | Post-Test Rear Passenger Dummy Close-Up Head Contact with Side Airbag View                    | A-38 |
| 77     | Post-Test Rear Passenger Dummy Close-Up Torso Contact with Vehicle Interior View              | A-39 |
| 78     | Post-Test Rear Passenger Dummy Close-Up Torso Contact with Side Airbag View                   | A-39 |
| 79     | Post-Test Rear Passenger Dummy Close-Up Pelvis Contact with Vehicle Interior View             | A-40 |
| 80     | Post-Test Rear Passenger Dummy Close-Up Pelvis Contact with Side Airbag View                  | A-40 |
| 81     | Post-Test Rear Passenger Dummy Close-Up Knee Contact View                                     | A-41 |
| 82     | Pre-Test View of Fuel Filler Cap or Fuel Filler Neck                                          | A-41 |
| 83     | Post-Test View of Fuel Filler Cap or Fuel Filler Neck                                         | A-42 |
| 84     | Pre-Test Front View of MDB Impactor Face                                                      | A-42 |
| 85     | Post-Test Front View of MDB Impactor Face                                                     | A-43 |
| 86     | Pre-Test Top View of MDB Impactor Face                                                        | A-43 |
| 87     | Post-Test Top View of MDB Impactor Face                                                       | A-44 |
| 88     | Pre-Test Left Side View of MDB Impactor Face                                                  | A-44 |
| 89     | Post-Test Left Side View of MDB Impactor Face                                                 | A-45 |
| 90     | Pre-Test Right Side View of MDB Impactor Face                                                 | A-45 |
| 91     | Post-Test Right Side View of MDB Impactor Face                                                | A-46 |
| 92     | Close-Up View of Vehicle's Certification Label                                                | A-46 |
| 93     | Close-Up View of Vehicle's Tire Information Placard or Label                                  | A-47 |
| 94     | Pre-Test Ballast View                                                                         | A-47 |
| 95     | Post-Test Primary and Redundant Speed Trap Read-Out                                           | A-48 |
| 96     | FMVSS No. 301 Static Rollover 0 Degrees                                                       | A-48 |
| 97     | FMVSS No. 301 Static Rollover 90 Degrees                                                      | A-49 |
| 98     | FMVSS No. 301 Static Rollover 180 Degrees                                                     | A-49 |
| 99     | FMVSS No. 301 Static Rollover 270 Degrees                                                     | A-50 |
| 100    | FMVSS No. 301 Static Rollover 360 Degrees                                                     | A-50 |
| 101    | Impact Event                                                                                  | A-51 |
| 102    | Monroney Label                                                                                | A-51 |
| 103    | Driver Head Restraint Use and Adjustment Information from Vehicle Owner's Manual              | A-52 |
| 104    | Left Rear Passenger Head Restraint Use and Adjustment Information from Vehicle Owner's Manual | A-52 |



FIGURE 1. As-Delivered Right Front  $\frac{3}{4}$  View of Test Vehicle



FIGURE 2. As-Delivered Left Rear  $\frac{3}{4}$  View of Test Vehicle




FIGURE 3. Pre-Test Frontal View of Test Vehicle




FIGURE 4. Post-Test Frontal View of Test Vehicle



FIGURE 5. Pre-Test Left Front  $\frac{3}{4}$  View of Test Vehicle



FIGURE 6. Post-Test Left Front  $\frac{3}{4}$  View of Test Vehicle



FIGURE 7. Pre-Test Left Side View of Test Vehicle



FIGURE 8. Post-Test Left Side View of Test Vehicle



FIGURE 9. Pre-Test Left Rear  $\frac{3}{4}$  View of Test Vehicle



FIGURE 10. Post-Test Left Rear  $\frac{3}{4}$  View of Test Vehicle



FIGURE 11. Pre-Test Rear View of Test Vehicle



FIGURE 12. Post-Test Rear View of Test Vehicle



FIGURE 13. Pre-Test Right Side View of Test Vehicle



FIGURE 14. Post-Test Right Side View of Test Vehicle



FIGURE 15. Pre-Test Overhead View of Test Area




FIGURE 16. Post-Test Overhead View of Test Area



FIGURE 17. Pre-Test Left Side View of MDB Positioned  
Against Side of Test Vehicle



FIGURE 18. Pre-Test Right Side View of MDB Positioned  
Against Side of Test Vehicle



FIGURE 19. Pre-Test Close-Up View of Impact Point Target



FIGURE 20. Post-Test Close-Up View of Impact Point Target



FIGURE 21. Pre-Test Left Front Door Latch Close-Up



FIGURE 22. Post-Test Left Front Door Latch Close-Up



FIGURE 23. Pre-Test Left Rear Door Latch Close-Up



FIGURE 24. Post-Test Left Rear Door Latch Close-Up



FIGURE 25. Pre-Test Front Close-Up View of Driver Dummy



FIGURE 26. Post-Test Front Close-Up View of Driver Dummy



FIGURE 27. Pre-Test Left Side View of Driver Dummy  
Showing Belt and Chalking



FIGURE 28. Pre-Test Left Side View of Driver Dummy Shoulder and Door Top View



FIGURE 29. Post-Test Left Side View of Driver Dummy Shoulder and Door Top View



FIGURE 30. Pre-Test Frontal View of Driver Seat Back Prior to Dummy Positioning



FIGURE 31. Pre-Test Frontal View of Driver Dummy Head and Shoulders in Relation to Head Restraint



FIGURE 32. Pre-Test Overhead View of Driver Seat Pan Prior to Dummy Positioning



FIGURE 33. Pre-Test Overhead View of Driver Dummy Thighs on Seat Pan



FIGURE 34. Pre-Test Placement of Driver Dummy's Feet




FIGURE 35. Pre-Test View of Belt Anchorage for Driver Dummy



FIGURE 36. Pre-Test Left Side View of Steering Wheel



FIGURE 37. View of Disengaged Parking Brake




FIGURE 38. Pre-Test View of Parking Brake



FIGURE 39. Pre-Test Close-Up Left Side View of Driver Seat Track



FIGURE 40. Pre-Test Close-Up Left Side View of Driver Seat Back



FIGURE 41. Pre-Test Close-Up View of Driver Seat Back or Head Restraint



FIGURE 42. Pre-Test Driver Dummy and Door Clearance View



FIGURE 43. Post-Test Driver Dummy and Door Clearance View



FIGURE 44. Pre-Test Right Side View of Driver Dummy  
and Front Seat Occupant Compartment



FIGURE 45. Post-Test Right Side View of Driver Dummy and Front Seat Occupant Compartment



FIGURE 46. Pre-Test Driver Inner Door Panel View



FIGURE 47. Post-Test Driver Inner Door Panel View  
Showing Driver Dummy Contact Locations



FIGURE 48. Post-Test Driver Dummy Close-Up Head Contact with Vehicle Interior View



FIGURE 49. Post-Test Driver Dummy Close-Up Head Contact with Side Airbag View



FIGURE 50. Post-Test Driver Dummy Close-Up Torso Contact with Vehicle Interior View



FIGURE 51. Post-Test Driver Dummy Close-Up Torso Contact with Side Airbag View




FIGURE 52. Post-Test Driver Dummy Close-Up Pelvis Contact with Vehicle Interior View



FIGURE 53. Post-Test Driver Dummy Close-Up Pelvis Contact with Side Airbag View




FIGURE 54. Post-Test Driver Dummy Close-Up Knee Contact View



FIGURE 55. Pre-Test Left Side View of Rear Passenger Dummy  
Showing Belt and Chalking



FIGURE 56. Pre-Test Left Side View of Rear Passenger Dummy  
Shoulder and Door Top View



FIGURE 57. Post-Test Left Side View of Rear Passenger Dummy  
Shoulder and Door Top View



FIGURE 58. Pre-Test Frontal View of Rear Passenger Seat Back  
Prior to Dummy Positioning



FIGURE 59. Pre-Test Frontal View of Rear Passenger Dummy  
Head and Shoulders in Relation to Head Restraint



FIGURE 60. Pre-Test Overhead View of Rear Passenger  
Seat Pan Prior to Dummy Positioning



FIGURE 61. Pre-Test Overhead View of Rear Passenger Dummy Thighs on Seat Pan




FIGURE 62. Pre-Test View of Rear Passenger Dummy's Neck  
Showing Position of Adjustable Neck Bracket



FIGURE 63. Pre-Test View of Rear Passenger Dummy's Head  
Showing Dummy's Head is Level



FIGURE 64. Pre-Test Placement of Rear Passenger Dummy's Feet



FIGURE 65. Pre-Test View of Belt Anchorage for Rear Passenger Dummy



FIGURE 66. Pre-Test Close-Up Left Side View of Rear Passenger Seat Track



FIGURE 67. Pre-Test Close-Up Left Side View of Rear Passenger Seat Back



FIGURE 68. Pre-Test Close-Up View of Rear Passenger Seat Back or Head Restraint



FIGURE 69. Pre-Test Rear Passenger Dummy and Door Clearance View



FIGURE 70. Post-Test Rear Passenger Dummy and Door Clearance View



FIGURE 71. Pre-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment



FIGURE 72. Post-Test Right Side View of Rear Passenger Dummy and Rear Seat of Occupant Compartment



FIGURE 73. Pre-Test Rear Passenger Inner Door Panel View



FIGURE 74. Post-Test Rear Passenger Inner Door Panel View  
Showing Rear Passenger Dummy Contact Locations



FIGURE 75. Post-Test Rear Passenger Dummy Close-Up  
Head Contact with Vehicle Interior View




FIGURE 76. Post-Test Rear Passenger Dummy Close-Up  
Head Contact with Side Airbag View



FIGURE 77. Post-Test Rear Passenger Dummy Close-Up  
Torso Contact with Vehicle Interior View

Photograph Not Applicable

Vehicle Not Equipped with  
Rear Passenger Side Airbag

FIGURE 78. Post-Test Rear Passenger Dummy Close-Up  
Torso Contact with Side Airbag View




FIGURE 79. Post-Test Rear Passenger Dummy Close-Up  
Pelvis Contact with Vehicle Interior View

Photograph Not Applicable

Vehicle Not Equipped with  
Rear Passenger Side Airbag

FIGURE 80. Post-Test Rear Passenger Dummy Close-Up  
Pelvis Contact with Side Airbag View



FIGURE 81. Post-Test Rear Passenger Dummy Close-Up Knee Contact View



FIGURE 82. Pre-Test View of Fuel Filler Cap or Fuel Filler Neck



FIGURE 83. Post-Test View of Fuel Filler Cap or Fuel Filler Neck



FIGURE 84. Pre-Test Front View of MDB Impactor Face



FIGURE 85. Post-Test Front View of MDB Impactor Face



FIGURE 86. Pre-Test Top View of MDB Impactor Face



FIGURE 87. Post-Test Top View of MDB Impactor Face



FIGURE 88. Pre-Test Left Side View of MDB Impactor Face



FIGURE 89. Post-Test Left Side View of MDB Impactor Face



FIGURE 90. Pre-Test Right Side View of MDB Impactor Face



FIGURE 91. Post-Test Right Side View of MDB Impactor Face



FIGURE 92. Close-Up View of Vehicle's Certification Label



FIGURE 93. Close-Up View of Vehicle's Tire Information Placard or Label




FIGURE 94. Pre-Test Ballast View



FIGURE 95. Post-Test Primary and Redundant Speed Trap Read-Out




FIGURE 96. FMVSS No. 301 Static Rollover 0 Degrees



FIGURE 97. FMVSS No. 301 Static Rollover 90 Degrees



FIGURE 98. FMVSS No. 301 Static Rollover 180 Degrees



FIGURE 99. FMVSS No. 301 Static Rollover 270 Degrees




FIGURE 100. FMVSS No. 301 Static Rollover 360 Degrees



FIGURE 101. Impact Event

VIN: JF2GPACCE9214236

Model/Code: 2014 Subaru XV Crosstrek 2.0i

Exterior Color: Premium / EPA

Port / Assembly: Denim Gray Metallic

Deliver by / Center: Truck / 433

SHIP TO: 090796

SUBARU OF GLENDALE

1235 S BRAND BLVD

GLENDALE, CA 91204

SOLD TO: 090796

SUBARU OF GLENDALE

1235 S BRAND BLVD

GLENDALE, CA 91204

Confidence in Motion

**STANDARD EQUIPMENT**

**SAFETY**

- Symmetrical All-Wheel Drive (AWD)
- Vehicle Dynamics Control (VDC)
- Subaru Advanced Frontal Air Bag System
- Front Seat Side-Impact Airbags
- Side-Curtain Airbags w/ Roll-over Sensor
- Driver's Side Knee Airbag
- 4-Wheel Disc Brakes w/ Brake Assist
- Anti-Lock Braking System (ABS)
- Electronic Brake-Force Distribution
- Tire Pressure Monitoring System (TPMS)
- Air-Thief Alarm & Immobilizer System
- Daytime Running Lights (DRL)

**PERFORMANCE AND EXTERIOR**

- 2.0L Horizontally-Opposed DOHC Engine
- Fully Independent Raised Suspension
- Roof Rails & Front Fog Lights
- Wheels: 17-inch Aluminum-Alloy
- Privacy Glass
- Intermittent Front/Rear Wipers

**COMFORT, CONVENIENCE AND INTERIOR**

- Air Conditioning w/ Air Filtration System
- AM/FM/CD Audio System w/ Aux Input Jack
- Steering Wheel Mounted Audio Controls

**Bluetooth Hands-Free Phone Connectivity**

- USB Port with iPod Connectivity
- Cruise Control, Tilt/Telescopic Steering
- Power Door Locks & Dual Power Mirrors
- Remote Keyless Entry System
- Power Windows w/ Driver's Auto Up/Down
- Height Adjustable Driver's Seat
- Tilt-Adjustable Front Seat Headrests
- Multi-Function Trip Computer
- 60/40 Split Fold-Down Rear Seatback
- All-Weather Package w/ Heated Front Seats

**LIMITED WARRANTY/ROADSIDE ASSISTANCE**

- 3 Years / 36,000 Miles Basic
- 5 Years / 60,000 Miles Powertrain
- 5 Yrs/Unlimited Mileage Rust Perforation
- 3 Yrs / 36,000 24/7 Roadside Assistance

See Owner Info X38/Warranty For Details

**OPTIONAL EQUIPMENT AND OTHER ITEMS**

Manufacturer's Suggested Retail Price \$21,995.00

Option Package: 01 - STANDARD PACKAGE

- Full Tank of Gas
- Popular Package #2
- Seat Back Protector
- Auto-Den Mirror/Compass/Map
- All Weather Floor Mats
- Rear Bumper Cover
- Speech Guard

INCLD \$887.00

**GOVERNMENT 5-STAR SAFETY RATINGS**

**Overall Vehicle Score** Not Rated

Based on the combined ratings of frontal, side and rollover. (Smaller ONLY, if compared to other vehicles of similar size and weight.)

|               |                  |           |
|---------------|------------------|-----------|
| Frontal Crash | Driver Passenger | Not Rated |
| Side Crash    | Front seat       | Not Rated |
| Rear seat     | Not Rated        |           |
| Rollover      | Not Rated        |           |

Star ratings range from 1 to 5 stars (★★★★★) with 5 being the highest. Source: National Highway Traffic Safety Administration (NHTSA) www.safercar.gov or 1-888-327-4236

**Fuel Economy and Environment** Gasoline Vehicle

**Fuel Economy** **26** MPG combined city/hwy

23 city 30 highway

3.8 gallons per 100 miles

**Annual fuel cost** **\$ 2,000**

**You save \$ 1,500** in fuel costs over 5 years compared to the average new vehicle.

**Fuel Economy & Greenhouse Gas Rating** (Smaller only) Smog Rating (Smaller only)

Actual results will vary for many reasons, including driving conditions and how you drive and maintain your vehicle. The average new vehicle gets 23 MPG and costs \$11,500 to fuel over 5 years. Cost estimates are based on 15,000 miles per year at \$3.50 per gallon. MPGe is miles per gallon equivalent. Vehicle emissions are a significant cause of climate change and smog.

**fuel economy.gov** Calculate estimated annual fuel costs and compare vehicles

**Destination and Delivery** \$625.00

**Total Suggested Retail Price** **\$23,487.00**

**Additional protection is available on this vehicle from Subaru**

**Always insist on Genuine Subaru Products**

- Added Security\* protects your investment
- Mechanical and Maintenance plans available
- Coverage up to 100,000 miles
- Genuine Subaru replacement parts
- Design & Rental car benefits
- Trip Interruption and Tire Hazard benefits available
- Theodorakis

**THE ONLY EXTENDED SERVICE PLAN BACKED AND ENDORSED BY SUBARU FOR OVER 30 YEARS!**

**PART CONTENTS INFORMATION FOR VEHICLES IN THIS COUNTRY:**

U.S./CANADIAN PARTS CONTENT: 0%

MAJOR SOURCES OF FOREIGN PARTS CONTENT: JAPAN 90%

FOR THIS VEHICLE:

FINAL ASSEMBLY POINT: OTA, GUNMA, JAPAN

COUNTRY OF ORIGIN: ENGINE: JAPAN TRANSMISSION: JAPAN

FIGURE 102. Monroney Label




FIGURE 103. Driver Head Restraint Use and Adjustment  
Information from Vehicle Owner's Manual




FIGURE 104. Left Rear Passenger Head Restraint  
Use and Adjustment Information from Vehicle Owner's Manual

**APPENDIX B**  
**DUMMY RESPONSE DATA**

## TABLE OF DATA PLOTS

| Plot |                                                           | Page |
|------|-----------------------------------------------------------|------|
| 1    | Driver Head Acceleration (X) Primary vs. Time             | B-1  |
| 2    | Driver Head Acceleration (Y) Primary vs. Time             | B-1  |
| 3    | Driver Head Acceleration (Z) Primary vs. Time             | B-1  |
| 4    | Driver Head Resultant Acceleration Primary vs. Time       | B-1  |
| 5    | Driver Upper Thorax Rib Deflection (Y) vs. Time           | B-2  |
| 6    | Driver Middle Thorax Rib Deflection (Y) vs. Time          | B-2  |
| 7    | Driver Lower Thorax Rib Deflection (Y) vs. Time           | B-2  |
| 8    | Driver Thorax Rib Deflection Maximum vs. Time             | B-2  |
| 9    | Driver Anterior Abdominal Force (Y) vs. Time              | B-3  |
| 10   | Driver Middle Abdominal Force (Y) vs. Time                | B-3  |
| 11   | Driver Posterior Abdominal Force (Y) vs. Time             | B-3  |
| 12   | Driver Total Abdominal Force (Y) vs. Time                 | B-3  |
| 13   | Driver Pubic Symphysis Force (Y) vs. Time                 | B-4  |
| 14   | Passenger Head Acceleration (X) vs. Time Primary          | B-5  |
| 15   | Passenger Head Acceleration (Y) vs. Time Primary          | B-5  |
| 16   | Passenger Head Acceleration (Z) vs. Time Primary          | B-5  |
| 17   | Passenger Head Resultant Acceleration Primary vs. Time    | B-5  |
| 18   | Passenger Lower Spine T12 Acceleration (X) vs. Time       | B-6  |
| 19   | Passenger Lower Spine T12 Acceleration (Y) vs. Time       | B-6  |
| 20   | Passenger Lower Spine T12 Acceleration (Z) vs. Time       | B-6  |
| 21   | Passenger Lower Spine T12 Resultant Acceleration vs. Time | B-6  |
| 22   | Passenger Iliac Force on Impact Side (Y) vs. Time         | B-7  |
| 23   | Passenger Acetabulum Force on Impact Side (Y) vs. Time    | B-7  |
| 24   | Passenger Total Pelvic Force on Impact Side (Y) vs. Time  | B-7  |

**The following additional data for this test can be obtained from the Research and Development section of the NHTSA website ([www.NHTSA.dot.gov](http://www.NHTSA.dot.gov))**

### Additional Driver & Passenger Dummy Instrumentation Data

Driver Lower Spine T12 Acceleration (X)

Driver Lower Spine T12 Acceleration (Y)

Driver Lower Spine T12 Acceleration (Z)

Passenger Upper Thorax Rib Deflection (Y)

Passenger Middle Thorax Rib Deflection (Y)

Passenger Lower Thorax Rib Deflection (Y)

Passenger Upper Abdomen Rib Deflection (Y)  
Passenger Lower Abdomen Rib Deflection (Y)  
Driver Head Acceleration Redundant (X)  
Driver Head Acceleration Redundant (Y)  
Driver Head Acceleration Redundant (Z)  
Passenger Head Acceleration Redundant (X)  
Passenger Head Acceleration Redundant (Y)  
Passenger Head Acceleration Redundant (Z)

### **Vehicle Instrumentation Data**

Vehicle Center of Gravity Acceleration (X)  
Vehicle Center of Gravity Acceleration (Y)  
Vehicle Center of Gravity Acceleration (Z)  
Right Side Sill at Front Seat Acceleration (X)  
Right Side Sill at Front Seat Acceleration (Y)  
Right Side Sill at Front Seat Acceleration (Z)  
Right Side Sill at Rear Seat Acceleration (X)  
Right Side Sill at Rear Seat Acceleration (Y)  
Right Side Sill at Rear Seat Acceleration (Z)  
Left Side Sill at Front Seat Acceleration (Y)  
Left Side Sill at Rear Seat Acceleration (Y)  
Lower A-Post Acceleration (Y)  
Middle A-Post Acceleration (Y)  
Lower B-Post Acceleration (Y)  
Middle B-Post Acceleration (Y)  
Front Seat Track Acceleration (Y)  
Rear Seat Structure Acceleration (Y)  
Right Rear Occupant Compartment Acceleration (Y)  
Engine Block (X)  
Engine Block (Y)  
Rear Floorpan Above Axle Acceleration (X)  
Rear Floorpan Above Axle Acceleration (Y)  
Rear Floorpan Above Axle Acceleration (Z)

### **MDB Instrumentation Data**

MDB Center of Gravity Acceleration (X)

MDB Center of Gravity Acceleration (Y)

MDB Center of Gravity Acceleration (Z)

MDB Rear Acceleration (X)


MDB Rear Acceleration (Y)

Left MDB Contact Switch


Right MDB Contact Switch

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV  
 Test Program: 61 km/h (38 mph) Side Impact NCAP 27° Moving Deformable Barrier Test


NHTSA No.: M20145504  
 Test Date: 1/28/14




| Curve Description                  |       |           |       |
|------------------------------------|-------|-----------|-------|
| Driver Head Acceleration X Primary |       |           |       |
| Plot No.                           | Type  | SAE Class | Units |
| 001                                | FIL   | 1000      | G's   |
| Max                                | Time  | Min       | Time  |
| 5.0                                | 153.9 | -20.6     | 69.2  |



| Curve Description                  |      |           |       |
|------------------------------------|------|-----------|-------|
| Driver Head Acceleration Y Primary |      |           |       |
| Plot No.                           | Type | SAE Class | Units |
| 002                                | FIL  | 1000      | G's   |
| Max                                | Time | Min       | Time  |
| 21.8                               | 63.8 | -7.6      | 137.1 |




| Curve Description                  |      |           |       |
|------------------------------------|------|-----------|-------|
| Driver Head Acceleration Z Primary |      |           |       |
| Plot No.                           | Type | SAE Class | Units |
| 003                                | FIL  | 1000      | G's   |
| Max                                | Time | Min       | Time  |
| 6.9                                | 57.7 | -11.2     | 71.6  |




| Curve Description                          |      |           |       |
|--------------------------------------------|------|-----------|-------|
| Driver Head Resultant Acceleration Primary |      |           |       |
| Plot No.                                   | Type | SAE Class | Units |
| 004                                        | RES  | 1000      | G's   |
| Max                                        | Time | Min       | Time  |
| 29.8                                       | 66.6 | 0.1       | 1.2   |

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV  
 Test Program: 61 km/h (38 mph) Side Impact NCAP 27° Moving Deformable Barrier Test


NHTSA No.: M20145504  
 Test Date: 1/28/14




| Curve Description                    |      |           |       |
|--------------------------------------|------|-----------|-------|
| Driver Upper Thorax Rib Deflection Y |      |           |       |
| Plot No.                             | Type | SAE Class | Units |
| 005                                  | FIL  | 180       | MM    |
| Max                                  | Time | Min       | Time  |
| 13.7                                 | 34.2 | -2.7      | 55.0  |



| Curve Description                     |      |           |       |
|---------------------------------------|------|-----------|-------|
| Driver Middle Thorax Rib Deflection Y |      |           |       |
| Plot No.                              | Type | SAE Class | Units |
| 006                                   | FIL  | 180       | MM    |
| Max                                   | Time | Min       | Time  |
| 12.9                                  | 33.3 | -3.0      | 53.1  |




| Curve Description                    |      |           |       |
|--------------------------------------|------|-----------|-------|
| Driver Lower Thorax Rib Deflection Y |      |           |       |
| Plot No.                             | Type | SAE Class | Units |
| 007                                  | FIL  | 180       | MM    |
| Max                                  | Time | Min       | Time  |
| 15.2                                 | 34.8 | -1.4      | 148.5 |




| Curve Description                    |      |           |       |
|--------------------------------------|------|-----------|-------|
| Driver Thorax Rib Deflection Maximum |      |           |       |
| Plot No.                             | Type | SAE Class | Units |
| 010                                  | FIL  | 180       | MM    |
| Max                                  | Time | Min       | Time  |
| 15.2                                 | 34.8 | -1.4      | 148.5 |

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV  
 Test Program: 61 km/h (38 mph) Side Impact NCAP 27° Moving Deformable Barrier Test


NHTSA No.: M20145504  
 Test Date: 1/28/14




| Curve Description                 |      |           |         |
|-----------------------------------|------|-----------|---------|
| Driver Anterior Abdominal Force Y |      |           |         |
| Plot No.                          | Type | SAE Class | Units   |
| 008                               | FIL  | 600       | Newtons |
| Max                               | Time | Min       | Time    |
| 268.0                             | 59.0 | -11.8     | 23.5    |



| Curve Description               |      |           |         |
|---------------------------------|------|-----------|---------|
| Driver Middle Abdominal Force Y |      |           |         |
| Plot No.                        | Type | SAE Class | Units   |
| 009                             | FIL  | 600       | Newtons |
| Max                             | Time | Min       | Time    |
| 329.9                           | 54.6 | -3.7      | 146.5   |




| Curve Description                  |      |           |         |
|------------------------------------|------|-----------|---------|
| Driver Posterior Abdominal Force Y |      |           |         |
| Plot No.                           | Type | SAE Class | Units   |
| 011                                | FIL  | 600       | Newtons |
| Max                                | Time | Min       | Time    |
| 358.4                              | 55.4 | -3.5      | 131.8   |



| Curve Description            |      |           |         |
|------------------------------|------|-----------|---------|
| Driver Total Abdominal Force |      |           |         |
| Plot No.                     | Type | SAE Class | Units   |
| 012                          | SUM  | 600       | Newtons |
| Max                          | Time | Min       | Time    |
| 940.5                        | 55.2 | -9.7      | 161.0   |

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV  
 Test Program: 61 km/h (38 mph) Side Impact NCAP 27° Moving Deformable Barrier Test


NHTSA No.: M20145504  
 Test Date: 1/28/14




| Curve Description              |       |           |         |
|--------------------------------|-------|-----------|---------|
| Driver Pubic Symphysis Force Y |       |           |         |
| Plot No.                       | Type  | SAE Class | Units   |
| 013                            | FIL   | 600       | Newtons |
| Max                            | Time  | Min       | Time    |
| 61.6                           | 182.7 | -1592.8   | 33.9    |

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV  
 Test Program: 61 km/h (38 mph) Side Impact NCAP 27° Moving Deformable Barrier Test


NHTSA No.: M20145504  
 Test Date: 1/28/14




| Curve Description                     |       |           |       |
|---------------------------------------|-------|-----------|-------|
| Passenger Head Acceleration X Primary |       |           |       |
| Plot No.                              | Type  | SAE Class | Units |
| 014                                   | FIL   | 1000      | G's   |
| Max                                   | Time  | Min       | Time  |
| 2.0                                   | 116.4 | -23.3     | 72.0  |



| Curve Description                     |      |           |       |
|---------------------------------------|------|-----------|-------|
| Passenger Head Acceleration Y Primary |      |           |       |
| Plot No.                              | Type | SAE Class | Units |
| 015                                   | FIL  | 1000      | G's   |
| Max                                   | Time | Min       | Time  |
| 25.3                                  | 60.0 | -2.2      | 30.3  |




| Curve Description                     |      |           |       |
|---------------------------------------|------|-----------|-------|
| Passenger Head Acceleration Z Primary |      |           |       |
| Plot No.                              | Type | SAE Class | Units |
| 016                                   | FIL  | 1000      | G's   |
| Max                                   | Time | Min       | Time  |
| 5.9                                   | 49.4 | -30.9     | 66.5  |




| Curve Description                             |      |           |       |
|-----------------------------------------------|------|-----------|-------|
| Passenger Head Acceleration Resultant Primary |      |           |       |
| Plot No.                                      | Type | SAE Class | Units |
| 017                                           | RES  | 1000      | G's   |
| Max                                           | Time | Min       | Time  |
| 43.3                                          | 67.9 | 0.1       | 10.2  |

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV  
 Test Program: 61 km/h (38 mph) Side Impact NCAP 27° Moving Deformable Barrier Test


NHTSA No.: M20145504  
 Test Date: 1/28/14




| Curve Description                        |       |           |       |
|------------------------------------------|-------|-----------|-------|
| Passenger Lower Spine T12 Acceleration X |       |           |       |
| Plot No.                                 | Type  | SAE Class | Units |
| 019                                      | FIL   | 180       | G's   |
| Max                                      | Time  | Min       | Time  |
| 3.8                                      | 164.4 | -12.6     | 64.7  |



| Curve Description                        |      |           |       |
|------------------------------------------|------|-----------|-------|
| Passenger Lower Spine T12 Acceleration Y |      |           |       |
| Plot No.                                 | Type | SAE Class | Units |
| 020                                      | FIL  | 180       | G's   |
| Max                                      | Time | Min       | Time  |
| 50.1                                     | 52.2 | -3.8      | 165.0 |




| Curve Description                        |      |           |       |
|------------------------------------------|------|-----------|-------|
| Passenger Lower Spine T12 Acceleration Z |      |           |       |
| Plot No.                                 | Type | SAE Class | Units |
| 021                                      | FIL  | 180       | G's   |
| Max                                      | Time | Min       | Time  |
| 21.9                                     | 67.6 | -14.4     | 45.6  |




| Curve Description                                |      |           |       |
|--------------------------------------------------|------|-----------|-------|
| Passenger Lower Spine T12 Acceleration Resultant |      |           |       |
| Plot No.                                         | Type | SAE Class | Units |
| 022                                              | RES  | 180       | G's   |
| Max                                              | Time | Min       | Time  |
| 51.5                                             | 52.3 | 0.1       | 0.6   |

Test Vehicle: 2014 Subaru XV Crosstrek 5-Door MPV  
 Test Program: 61 km/h (38 mph) Side Impact NCAP 27° Moving Deformable Barrier Test


NHTSA No.: M20145504  
 Test Date: 1/28/14



| Curve Description                           |      |           |         |
|---------------------------------------------|------|-----------|---------|
| Passenger Iliac Wing Force on Impact Side Y |      |           |         |
| Plot No.                                    | Type | SAE Class | Units   |
| 023                                         | FIL  | 600       | Newtons |
| Max                                         | Time | Min       | Time    |
| 698.5                                       | 53.0 | -80.1     | 156.4   |



| Curve Description                           |      |           |         |
|---------------------------------------------|------|-----------|---------|
| Passenger Acetabulum Force on Impact Side Y |      |           |         |
| Plot No.                                    | Type | SAE Class | Units   |
| 024                                         | FIL  | 600       | Newtons |
| Max                                         | Time | Min       | Time    |
| 2469.7                                      | 44.8 | -37.1     | 26.9    |



| Curve Description            |      |           |         |
|------------------------------|------|-----------|---------|
| Passenger Total Pelvic Force |      |           |         |
| Plot No.                     | Type | SAE Class | Units   |
| 018                          | SUM  | 600       | Newtons |
| Max                          | Time | Min       | Time    |
| 2889.6                       | 46.7 | -75.1     | 156.1   |

**APPENDIX C**  
**DUMMY CONFIGURATION AND PERFORMANCE VERIFICATION DATA**

**APPENDIX C**  
**PRE-TEST / ATD CONFIGURATION AND PERFORMANCE VERIFICATION DATA**

Test Program: ES2re External Measurements  
 ATD Serial No.: F037

Test Date: 1/17/14  
 Test I.D.: N/A




| Tested Parameter             |                                                | Units | Specification | Result | Pass/Fail |
|------------------------------|------------------------------------------------|-------|---------------|--------|-----------|
| Laboratory Temperature       |                                                | °C    | 20.6 to 22.2  | 21.2   | Pass      |
| Laboratory Relative Humidity |                                                | %     | 10 to 70      | 30.0   | Pass      |
| 1                            | Sitting Height                                 | mm    | 900 - 918     | 909    | Pass      |
| 2                            | Seat to Shoulder Joint                         | mm    | 558 - 572     | 564    | Pass      |
| 3                            | Seat to Lower Face of Thoracic Spine Box       | mm    | 346 - 356     | 350    | Pass      |
| 4                            | Seat to Hip Joint (Center of Bolt)             | mm    | 97 - 103      | 99     | Pass      |
| 5                            | Sole to Seat, Sitting                          | mm    | 333 - 451     | 395    | Pass      |
| 6                            | Head Width                                     | mm    | 152 - 158     | 156    | Pass      |
| 7                            | Shoulder / Arm Width                           | mm    | 461 - 479     | 470    | Pass      |
| 8                            | Thorax Width                                   | mm    | 322 - 332     | 326    | Pass      |
| 9                            | Abdomen Width                                  | mm    | 273 - 287     | 280    | Pass      |
| 10                           | Pelvis Lap Width                               | mm    | 359 - 373     | 363    | Pass      |
| 11                           | Head Depth                                     | mm    | 196 - 206     | 201    | Pass      |
| 12                           | Thorax Depth                                   | mm    | 262 - 272     | 270    | Pass      |
| 13                           | Abdomen Width                                  | mm    | 194 - 204     | 199    | Pass      |
| 14                           | Pelvis Depth                                   | mm    | 235 - 245     | 240    | Pass      |
| 15                           | Back of Buttocks to Hip Joint (Center of Bolt) | mm    | 150 - 160     | 155    | Pass      |
| 16                           | Back of Buttocks to Front Knee                 | mm    | 597 - 615     | 608    | Pass      |
| Overall Test Results         |                                                |       |               |        | Pass      |

Test Program: ES2re Head Drop Test  
 ATD Serial No.: F037


Test Date: 1/17/14  
 Test I.D.: F037HD054




| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Head Assembly Soak Time            | Minutes | ≥240          | 253    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.6   | Pass      |
|                                    | Min     |               | 21.4   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 19.4   | Pass      |
|                                    | Min     |               | 18.5   | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2  | 21.5   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 18.5   | Pass      |
| Peak Head Resultant Acceleration   | G's     | 125 to 155    | 143.7  | Pass      |
| Peak Head X Acceleration           | G's     | ≤15           | 5.6    | Pass      |
| Is Acceleration Unimodal?          | Yes/No  | Yes           | Yes    | Pass      |
| Oscillations After Main Pulse      | %       | <15           | 4.8    | Pass      |
| Overall Test Results               |         |               |        | Pass      |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Resultant    |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 001               | RES  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 143.7             | 2.4  | 0.1       | 0.1   |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head X            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 5.6               | 3.6  | -2.0      | 2.0   |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Y            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 003               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 119.3             | 2.4  | -5.4      | 5.3   |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Z            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 004               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 80.1              | 2.4  | -1.3      | 6.5   |

Test Program: ES2re Neck Flexion Test  
 ATD Serial No.: F037


Test Date: 1/17/14  
 Test I.D.: F037NB054




| Tested Parameter                      | Units   | Specification | Result | Pass/Fail |
|---------------------------------------|---------|---------------|--------|-----------|
| Neck Assembly Soak Time               | Minutes | ≥240          | 288    | Pass      |
| Temperature During Soak               | Max     | 20.6 to 22.2  | 21.6   | Pass      |
|                                       | Min     |               | 21.4   | Pass      |
| Humidity During Soak                  | Max     | 10.0 to 70.0  | 19.4   | Pass      |
|                                       | Min     |               | 18.5   | Pass      |
| Laboratory Temperature During Test    | °C      | 20.6 to 22.2  | 21.5   | Pass      |
| Laboratory Humidity During Test       | %       | 10.0 to 70.0  | 18.5   | Pass      |
| Pendulum Velocity                     | m/s     | 3.3 to 3.5    | 3.48   | Pass      |
| Headform Flexion                      | Max     | 49 to 59      | 56.5   | Pass      |
|                                       | Time    | 54 to 66      | 57.0   | Pass      |
| Headform Flexion Decay (Peak to Zero) | msec    | 53 to 88      | 61.8   | Pass      |
| Overall Test Results                  |         |               |        | Pass      |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Pendulum Deceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 001                   | FIL  | 60        | G's   |
| Max                   | Time | Min       | Time  |
| 6.5                   | 48.1 | -31.7     | 5.6   |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Pendulum Velocity |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 60        | m/s   |
| Max               | Time | Min       | Time  |
| 0.0               | -0.8 | -4.6      | 199.9 |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Pendulum Velocity |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 60        | m/s   |
| Max               | Time | Min       | Time  |
| 0.0               | -0.8 | -4.6      | 199.9 |

#### Velocity Corridors


| Upper Boundary |                | Lower Boundary |                |
|----------------|----------------|----------------|----------------|
| Time (msec)    | Velocity (m/s) | Time (msec)    | Velocity (m/s) |
| 1.0            | 0.00           | 0.0            | -0.05          |
| 3.0            | -0.03          | 2.5            | -0.375         |
| 14.0           | -3.20          | 13.5           | -3.70          |
|                |                | 17.0           | -3.70          |

Test Program: ES2re Neck Flexion Test  
 ATD Serial No.: F037


Test Date: 1/17/14  
 Test I.D.: F037NB054




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Headform Rotation |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 003               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 56.5              | 57.0 | -28.9     | 160.4   |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer A   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 004               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 37.1              | 51.9 | -17.8     | 162.1   |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer B   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 005               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 32.9              | 54.8 | -20.3     | 163.6   |




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer C   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 006               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 19.7              | 59.0 | -11.2     | 158.5   |

Test Program: ES2re Shoulder Impact Test  
 ATD Serial No.: F037

Test Date: 1/17/14  
 Test I.D.: F037SH054



| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                    | Minutes | ≥240          | 353    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.6   | Pass      |
|                                    | Min     |               | 21.4   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 19.4   | Pass      |
|                                    | Min     |               | 18.5   | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2  | 21.5   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 18.6   | Pass      |
| Pendulum Speed                     | m/s     | 4.2 to 4.4    | 4.40   | Pass      |
| Peak Impactor Acceleration         | G's     | 7.5 to 10.5   | 10.2   | Pass      |
| Overall Test Results               |         |               |        | Pass      |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 001                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 10.2                  | 17.2 | 0.0       | 92.4  |

Test Program: ES2re Thorax - Rib Drop Test  
 ATD Serial No.: F037 Rib # 1


Test Date: 1/17/14  
 Test I.D.: F037RB1054



| Tested Parameter                                | Units   | Specification | Result | Pass/Fail |
|-------------------------------------------------|---------|---------------|--------|-----------|
| Rib Module Soak Time                            | Minutes | ≥240          | 408    | Pass      |
| Temperature During Soak                         | Max     | 20.6 to 22.2  | 21.6   | Pass      |
|                                                 | Min     |               | 21.4   | Pass      |
| Humidity During Soak                            | Max     | 10.0 to 70.0  | 19.4   | Pass      |
|                                                 | Min     |               | 18.5   | Pass      |
| Laboratory Temperature During Test              | °C      | 20.6 to 22.2  | 21.5   | Pass      |
| Laboratory Humidity During Test                 | %       | 10.0 to 70.0  | 18.6   | Pass      |
| Peak Rib Deflection at 459 +/- 5 mm Drop Height | mm      | 36 to 40      | 38.2   | Pass      |
| Peak Rib Deflection at 815 +/- 8 mm Drop Height | mm      | 46 to 51      | 47.6   | Pass      |
| Overall Test Results                            |         |               |        | Pass      |



| Curve Description                         |      |           |       |
|-------------------------------------------|------|-----------|-------|
| Upper Rib Deflection (459 mm Drop Height) |      |           |       |
| Plot No.                                  | Type | SAE Class | Units |
| 001                                       | FIL  | 180       | MM    |
| Max                                       | Time | Min       | Time  |
| 38.2                                      | 32.4 | -4.8      | 66.9  |




| Curve Description                         |      |           |       |
|-------------------------------------------|------|-----------|-------|
| Upper Rib Deflection (815 mm Drop Height) |      |           |       |
| Plot No.                                  | Type | SAE Class | Units |
| 002                                       | FIL  | 180       | MM    |
| Max                                       | Time | Min       | Time  |
| 47.6                                      | 34.0 | -4.7      | 68.0  |

Test Program: ES2re Thorax - Rib Drop Test  
 ATD Serial No.: F037 Rib # 2


Test Date: 1/17/14  
 Test I.D.: F037RB2054



| Tested Parameter                                | Units   | Specification | Result | Pass/Fail |
|-------------------------------------------------|---------|---------------|--------|-----------|
| Rib Module Soak Time                            | Minutes | ≥240          | 453    | Pass      |
| Temperature During Soak                         | Max     | 20.6 to 22.2  | 21.6   | Pass      |
|                                                 | Min     |               | 21.4   | Pass      |
| Humidity During Soak                            | Max     | 10.0 to 70.0  | 19.4   | Pass      |
|                                                 | Min     |               | 18.5   | Pass      |
| Laboratory Temperature During Test              | °C      | 20.6 to 22.2  | 21.5   | Pass      |
| Laboratory Humidity During Test                 | %       | 10.0 to 70.0  | 18.8   | Pass      |
| Peak Rib Deflection at 459 +/- 5 mm Drop Height | mm      | 36 to 40      | 38.7   | Pass      |
| Peak Rib Deflection at 815 +/- 8 mm Drop Height | mm      | 46 to 51      | 47.9   | Pass      |
| Overall Test Results                            |         |               |        | Pass      |



| Curve Description                          |      |           |       |
|--------------------------------------------|------|-----------|-------|
| Middle Rib Deflection (459 mm Drop Height) |      |           |       |
| Plot No.                                   | Type | SAE Class | Units |
| 001                                        | FIL  | 180       | MM    |
| Max                                        | Time | Min       | Time  |
| 38.7                                       | 32.2 | -4.5      | 66.7  |




| Curve Description                          |      |           |       |
|--------------------------------------------|------|-----------|-------|
| Middle Rib Deflection (815 mm Drop Height) |      |           |       |
| Plot No.                                   | Type | SAE Class | Units |
| 002                                        | FIL  | 180       | MM    |
| Max                                        | Time | Min       | Time  |
| 47.9                                       | 33.9 | -4.6      | 68.0  |

Test Program: ES2re Thorax - Rib Drop Test  
 ATD Serial No.: F037 Rib # 3


Test Date: 1/17/14  
 Test I.D.: F037RB3054



| Tested Parameter                                | Units   | Specification | Result | Pass/Fail |
|-------------------------------------------------|---------|---------------|--------|-----------|
| Rib Module Soak Time                            | Minutes | ≥240          | 498    | Pass      |
| Temperature During Soak                         | Max     | 20.6 to 22.2  | 21.6   | Pass      |
|                                                 | Min     |               | 21.4   | Pass      |
| Humidity During Soak                            | Max     | 10.0 to 70.0  | 19.4   | Pass      |
|                                                 | Min     |               | 18.5   | Pass      |
| Laboratory Temperature During Test              | °C      | 20.6 to 22.2  | 21.5   | Pass      |
| Laboratory Humidity During Test                 | %       | 10.0 to 70.0  | 18.9   | Pass      |
| Peak Rib Deflection at 459 +/- 5 mm Drop Height | mm      | 36 to 40      | 37.9   | Pass      |
| Peak Rib Deflection at 815 +/- 8 mm Drop Height | mm      | 46 to 51      | 49.6   | Pass      |
| Overall Test Results                            |         |               |        | Pass      |



| Curve Description                         |      |           |       |
|-------------------------------------------|------|-----------|-------|
| Lower Rib Deflection (459 mm Drop Height) |      |           |       |
| Plot No.                                  | Type | SAE Class | Units |
| 001                                       | FIL  | 180       | MM    |
| Max                                       | Time | Min       | Time  |
| 37.9                                      | 34.0 | -4.6      | 67.7  |




| Curve Description                         |      |           |       |
|-------------------------------------------|------|-----------|-------|
| Lower Rib Deflection (815 mm Drop Height) |      |           |       |
| Plot No.                                  | Type | SAE Class | Units |
| 002                                       | FIL  | 180       | MM    |
| Max                                       | Time | Min       | Time  |
| 49.6                                      | 36.0 | -5.3      | 69.3  |

Test Program: ES2re Thorax - Full Body Impact Test  
 ATD Serial No.: F037


Test Date: 1/17/14  
 Test I.D.: F037TH054




| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                    | Minutes | ≥240          | 543    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.6   | Pass      |
|                                    | Min     |               | 21.4   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 19.4   | Pass      |
|                                    | Min     |               | 18.5   | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2  | 21.6   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 19.0   | Pass      |
| Peak Impactor Velocity             | m/s     | 5.4 to 5.6    | 5.50   | Pass      |
| Peak Impactor Force                | N       | 5100 to 6200  | 5961.4 | Pass      |
|                                    | msec    | > 6.0 msec    | 9.8    | Pass      |
| Peak Upper Rib Deflection          | mm      | 34 to 41      | 36.4   | Pass      |
| Peak Middle Rib Deflection         | mm      | 37 to 45      | 40.9   | Pass      |
| Peak Lower Rib Deflection          | mm      | 37 to 44      | 38.1   | Pass      |
| Overall Test Results               |         |               |        | Pass      |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Impactor Force    |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 001               | FIL  | 180       | Newtons |
| Max               | Time | Min       | Time    |
| 10853.6           | 2.6  | -54.0     | -0.5    |



| Curve Description                    |      |              |       |
|--------------------------------------|------|--------------|-------|
| Upper, Middle, Lower Rib Deflections |      |              |       |
| Plot No.                             | Type | SAE Class    | Units |
| 002                                  | FIL  | 180          | MM    |
| Max (Upper)                          | Time | Min (Upper)  | Time  |
| 36.4                                 | 15.9 | -4.0         | 40.4  |
| Max (Middle)                         | Time | Min (Middle) | Time  |
| 40.9                                 | 16.8 | -3.6         | 45.3  |
| Max (Lower)                          | Time | Min (Lower)  | Time  |
| 38.1                                 | 17.2 | -3.2         | 50.1  |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 003                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 47.4                  | 2.6  | -0.2      | -0.5  |

Test Program: ES2re Abdomen Impact Test  
 ATD Serial No.: F037


Test Date: 1/17/14  
 Test I.D.: F037ABD054



| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                    | Minutes | ≥240          | 613    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.6   | Pass      |
|                                    | Min     |               | 21.4   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 19.4   | Pass      |
|                                    | Min     |               | 18.5   | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2  | 21.6   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 19.2   | Pass      |
| Probe Velocity                     | m/s     | 3.9 to 4.1    | 4.00   | Pass      |
| Peak Impactor Force                | N       | 4000 to 4800  | 4405.5 | Pass      |
|                                    | msec    | 10.6 to 13.0  | 11.4   | Pass      |
| Sum of Abdominal Forces            | N       | 2200 to 2700  | 2627.0 | Pass      |
|                                    | msec    | 10.0 to 12.3  | 10.9   | Pass      |
| Overall Test Results               |         |               |        | Pass      |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 001                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 19.2                  | 11.4 | -0.1      | -0.4  |




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Impactor Force    |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 002               | FIL  | 180       | Newtons |
| Max               | Time | Min       | Time    |
| 4405.5            | 11.4 | -25.6     | -0.4    |

Test Program: ES2re Abdomen Impact Test  
 ATD Serial No.: F037


Test Date: 1/17/14  
 Test I.D.: F037ABD054




| Curve Description   |      |           |            |
|---------------------|------|-----------|------------|
| Front Abdomen Force |      |           |            |
| Plot No.            | Type | SAE Class | Units      |
| 003                 | FIL  | 600       | Newtontons |
| Max                 | Time | Min       | Time       |
| 573.4               | 11.1 | -6.7      | 75.8       |



| Curve Description    |      |           |            |
|----------------------|------|-----------|------------|
| Middle Abdomen Force |      |           |            |
| Plot No.             | Type | SAE Class | Units      |
| 004                  | FIL  | 600       | Newtontons |
| Max                  | Time | Min       | Time       |
| 1080.0               | 11.0 | -4.4      | 114.3      |



| Curve Description  |      |           |            |
|--------------------|------|-----------|------------|
| Rear Abdomen Force |      |           |            |
| Plot No.           | Type | SAE Class | Units      |
| 005                | FIL  | 600       | Newtontons |
| Max                | Time | Min       | Time       |
| 984.6              | 10.5 | -2.6      | 72.7       |




| Curve Description     |      |           |            |
|-----------------------|------|-----------|------------|
| Abdomen Sum Resultant |      |           |            |
| Plot No.              | Type | SAE Class | Units      |
| 006                   | RES  | 600       | Newtontons |
| Max                   | Time | Min       | Time       |
| 2627.0                | 10.9 | -10.6     | 72.7       |

Test Program: ES2re Lumbar Flexion Test  
 ATD Serial No.: F037


Test Date: 1/17/14  
 Test I.D.: F037LB054




| Tested Parameter                      | Units   | Specification | Result | Pass/Fail |
|---------------------------------------|---------|---------------|--------|-----------|
| Lumbar Spine Assembly Soak Time       | Minutes | ≥240          | 688    | Pass      |
| Temperature During Soak               | Max     | 20.6 to 22.2  | 21.6   | Pass      |
|                                       | Min     |               | 21.4   | Pass      |
| Humidity During Soak                  | Max     | 10.0 to 70.0  | 19.4   | Pass      |
|                                       | Min     |               | 18.5   | Pass      |
| Laboratory Temperature During Test    | °C      | 20.6 to 22.2  | 21.6   | Pass      |
| Laboratory Humidity During Test       | %       | 10.0 to 70.0  | 19.3   | Pass      |
| Pendulum Velocity                     | m/s     | 5.95 to 6.15  | 6.01   | Pass      |
| Headform Rotation                     | Max     | 45 to 55      | 49.4   | Pass      |
|                                       | Time    | 39 to 53      | 44.6   | Pass      |
| Time of Decay to Zero Angle from Peak | msec    | 37 to 57      | 41.7   | Pass      |
| Overall Test Results                  |         |               |        | Pass      |



| Curve Description     |       |           |       |
|-----------------------|-------|-----------|-------|
| Pendulum Deceleration |       |           |       |
| Plot No.              | Type  | SAE Class | Units |
| 001                   | FIL   | 60        | G's   |
| Max                   | Time  | Min       | Time  |
| 3.2                   | 140.5 | -26.7     | 9.3   |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Pendulum Velocity |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 60        | m/s   |
| Max               | Time | Min       | Time  |
| 0.0               | -1.3 | -7.1      | 122.9 |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Pendulum Velocity |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 60        | m/s   |
| Max               | Time | Min       | Time  |
| 0.0               | -1.3 | -7.1      | 122.9 |

#### Velocity Corridors


| Upper Boundary |                | Lower Boundary |                |
|----------------|----------------|----------------|----------------|
| Time (msec)    | Velocity (m/s) | Time (msec)    | Velocity (m/s) |
| 1.0            | 0.00           | 0.0            | -0.05          |
| 3.7            | -0.24          | 2.7            | -0.425         |
| 27.0           | -5.80          | 24.5           | -6.50          |
|                |                | 30.0           | -6.50          |

Test Program: ES2re Lumbar Flexion Test  
 ATD Serial No.: F037


Test Date: 1/17/14  
 Test I.D.: F037LB054




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Headform Rotation |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 003               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 49.4              | 44.6 | -18.8     | 100.8   |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer A   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 004               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 30.4              | 44.4 | -11.1     | 100.4   |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer B   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 005               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 28.3              | 42.9 | -12.6     | 100.6   |




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer C   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 006               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 19.0              | 45.0 | -7.8      | 104.2   |

Test Program: ES2re Pelvis Impact Test  
 ATD Serial No.: F037


Test Date: 1/17/14  
 Test I.D.: F037PL054




| Tested Parameter                   | Units   | Specification  | Result  | Pass/Fail |
|------------------------------------|---------|----------------|---------|-----------|
| Dummy Soak Time                    | Minutes | ≥240           | 743     | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2   | 21.6    | Pass      |
|                                    | Min     |                | 21.4    | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0   | 19.4    | Pass      |
|                                    | Min     |                | 18.5    | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2   | 21.6    | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0   | 19.4    | Pass      |
| Pendulum Velocity                  | m/s     | 4.2 to 4.4     | 4.29    | Pass      |
| Peak Impactor Force                | N       | 4700 to 5400   | 5179.1  | Pass      |
|                                    | msec    | 11.8 to 16.1   | 13.4    | Pass      |
| Peak Pubic Symphysis Load          | N       | -1230 to -1590 | -1346.8 | Pass      |
|                                    | msec    | 12.2 to 17.0   | 14.5    | Pass      |
| Overall Test Results               |         |                |         | Pass      |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Impactor Force    |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 001               | FIL  | 180       | Newtons |
| Max               | Time | Min       | Time    |
| 5179.1            | 13.4 | -31.2     | -0.6    |



| Curve Description       |      |           |         |
|-------------------------|------|-----------|---------|
| Pubic Symphysis Force Y |      |           |         |
| Plot No.                | Type | SAE Class | Units   |
| 002                     | FIL  | 600       | Newtons |
| Max                     | Time | Min       | Time    |
| 166.1                   | 40.1 | -1346.8   | 14.5    |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 003                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 22.6                  | 13.4 | -0.1      | -0.6  |

Test Program: SID IIs External Measurements  
 ATD Serial No.: 307

Test Date: 1/20/14  
 Test I.D.: N/A




| Tested Parameter             |                                 | Units | Specification | Result | Pass/Fail |
|------------------------------|---------------------------------|-------|---------------|--------|-----------|
| Laboratory Temperature       |                                 | °C    | 20.6 to 22.2  | 21.7   | Pass      |
| Laboratory Relative Humidity |                                 | %     | 10 to 70      | 21     | Pass      |
| A                            | Sitting Height                  | mm    | 772 - 788     | 778    | Pass      |
| B                            | Shoulder Pivot Height           | mm    | 437 - 453     | 443    | Pass      |
| C                            | H-Point Height                  | mm    | 79 - 89       | 85     | Pass      |
| D                            | H-Point from Seatback           | mm    | 141 - 151     | 144    | Pass      |
| E                            | Shoulder Pivot from Backline    | mm    | 97 - 107      | 102    | Pass      |
| F                            | Thigh Clearance                 | mm    | 119 - 135     | 128    | Pass      |
| G                            | Head Breadth                    | mm    | 140 - 148     | 145    | Pass      |
| H                            | Head Back from Backline         | mm    | 40 - 46       | 43     | Pass      |
| I                            | Head Depth                      | mm    | 178 - 188     | 185    | Pass      |
| J                            | Head Circumference              | mm    | 541 - 551     | 546    | Pass      |
| K                            | Buttock to Knee Length          | mm    | 514 - 540     | 525    | Pass      |
| L                            | Popliteal Height                | mm    | 343 - 369     | 351    | Pass      |
| M                            | Knee Pivot to Floor Height      | mm    | 392 - 409     | 400    | Pass      |
| N                            | Buttock Popliteal Length        | mm    | 416 - 442     | 432    | Pass      |
| O                            | Chest Depth w/o Jacket          | mm    | 195 - 211     | 205    | Pass      |
| P                            | Foot Length                     | mm    | 216 - 232     | 223    | Pass      |
| Q                            | Hip Breadth with Pelvic Plug    | mm    | 313 - 323     | 319    | Pass      |
| R                            | Arm Length                      | mm    | 249 - 259     | 254    | Pass      |
| S                            | Knee Joint to Seatback          | mm    | 477 - 493     | 483    | Pass      |
| V                            | Shoulder Width                  | mm    | 341 - 357     | 351    | Pass      |
| W                            | Foot Width                      | mm    | 78 - 94       | 89     | Pass      |
| Y                            | Chest Circumference with Jacket | mm    | 851 - 881     | 872    | Pass      |
| Z                            | Waist Circumference             | mm    | 760 - 791     | 774    | Pass      |
| Overall Test Results         |                                 |       |               |        | Pass      |

Test Program: SID IIs Head Drop Test  
 ATD Serial No.: 307

Test Date: 1/20/14  
 Test I.D.: 307HD062




| Tested Parameter                   |     | Units   | Specification | Result | Pass/Fail |
|------------------------------------|-----|---------|---------------|--------|-----------|
| Head Assembly Soak Time            |     | Minutes | ≥240          | 267    | Pass      |
| Temperature During Soak            | Max | °C      | 18.9 to 25.6  | 21.7   | Pass      |
|                                    | Min | °C      |               | 21.6   | Pass      |
| Humidity During Soak               | Max | %       | 10.0 to 70.0  | 21.3   | Pass      |
|                                    | Min | %       |               | 20.6   | Pass      |
| Laboratory Temperature During Test |     | °C      | 18.9 to 25.6  | 21.7   | Pass      |
| Laboratory Humidity During Test    |     | %       | 10.0 to 70.0  | 20.6   | Pass      |
| Peak Head Resultant Acceleration   |     | G's     | 115 to 137    | 132.2  | Pass      |
| Peak Head X Acceleration           |     | G's     | <15           | 4.8    | Pass      |
| Is Acceleration Unimodal?          |     | Yes/No  | Yes           | Yes    | Pass      |
| Oscillations After Main Pulse      |     | %       | <15           | 1.9    | Pass      |
| Overall Test Results               |     |         |               | Pass   |           |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Resultant    |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 001               | RES  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 132.2             | 2.8  | 0.1       | -0.7  |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head X            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 4.8               | 2.9  | -0.1      | -0.8  |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Y            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 003               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 109.9             | 2.7  | -0.8      | 7.0   |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Z            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 004               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 73.4              | 2.8  | -1.0      | 12.0  |

Test Program: SID IIs Neck Flexion Test  
 ATD Serial No.: 307


Test Date: 1/20/14  
 Test I.D.: 307NB062




| Tested Parameter                   | Units       | Specification  | Result | Pass/Fail |
|------------------------------------|-------------|----------------|--------|-----------|
| Neck Assembly Soak Time            | Minutes     | ≥240           | 342    | Pass      |
| Temperature During Soak            | Max         | 20.6 to 22.2   | 21.7   | Pass      |
|                                    | Min         |                | 21.6   | Pass      |
| Humidity During Soak               | Max         | 10.0 to 70.0   | 21.3   | Pass      |
|                                    | Min         |                | 20.6   | Pass      |
| Laboratory Temperature During Test | °C          | 20.6 to 22.2   | 21.6   | Pass      |
| Laboratory Humidity During Test    | %           | 10.0 to 70.0   | 20.9   | Pass      |
| Pendulum Velocity                  | m/s         | 5.51 to 5.63   | 5.55   | Pass      |
| Pendulum Deceleration              | 10 msec     | -2.20 to -2.80 | -2.59  | Pass      |
|                                    | 15 msec     | -3.30 to -4.10 | -3.78  | Pass      |
|                                    | 20 msec     | -4.40 to -5.40 | -5.01  | Pass      |
|                                    | 25 msec     | -5.40 to -6.10 | -6.01  | Pass      |
|                                    | 25-100 msec | -5.50 to -6.20 | -6.10  | Pass      |
| D-Plane Rotation                   | Max         | 71 to 81       | 77.5   | Pass      |
|                                    | Time        | 50 to 70       | 58.8   | Pass      |
| Peak Occipital Condyle Moment      | Nm          | -36 to -44     | -42.1  | Pass      |
| Decaying Moment Time to Cross 0 Nm | msec        | 102 to 126     | 105.5  | Pass      |
| Overall Test Results               |             |                | Pass   |           |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Pendulum Deceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 001                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 4.2                   | 0.0  | -33.2     | 0.0   |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Pendulum Velocity |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 180       | m/s   |
| Max               | Time | Min       | Time  |
| 0.0               | -0.9 | -6.9      | 199.9 |




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| D-Plane Rotation  |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 003               | FIL  | 60        | Degress |
| Max               | Time | Min       | Time    |
| 77.5              | 58.8 | -29.8     | 171.6   |

Test Program: SID IIs Neck Flexion Test  
 ATD Serial No.: 307


Test Date: 1/20/14  
 Test I.D.: 307NB062



| Curve Description |       |           |         |
|-------------------|-------|-----------|---------|
| Neck Force Y      |       |           |         |
| Plot No.          | Type  | SAE Class | Units   |
| 004               | FIL   | 1000      | Newtons |
| Max               | Time  | Min       | Time    |
| 145.5             | 162.6 | -538.9    | 50.4    |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Neck Moment X     |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 005               | FIL  | 600       | Nm    |
| Max               | Time | Min       | Time  |
| 18.6              | 6.3  | -33.3     | 54.7  |




| Curve Description              |      |           |       |
|--------------------------------|------|-----------|-------|
| Moment About Occipital Condyle |      |           |       |
| Plot No.                       | Type | SAE Class | Units |
| 006                            | FIL  | 600       | Nm    |
| Max                            | Time | Min       | Time  |
| 14.2                           | 5.7  | -42.1     | 47.2  |

Test Program: SID IIs Shoulder Impact Test  
 ATD Serial No.: 307


Test Date: 1/20/14  
 Test I.D.: 307SH062




| Tested Parameter                   |     | Units   | Specification | Result | Pass/Fail |
|------------------------------------|-----|---------|---------------|--------|-----------|
| Dummy Soak Time                    |     | Minutes | ≥180          | 397    | Pass      |
| Temperature During Soak            | Max | °C      | 20.6 to 22.2  | 21.7   | Pass      |
|                                    | Min | °C      |               | 21.6   | Pass      |
| Humidity During Soak               | Max | %       | 10.0 to 70.0  | 21.3   | Pass      |
|                                    | Min | %       |               | 20.6   | Pass      |
| Laboratory Temperature During Test |     | °C      | 20.6 to 22.2  | 21.6   | Pass      |
| Laboratory Humidity During Test    |     | %       | 10.0 to 70.0  | 21.0   | Pass      |
| Impactor Velocity                  |     | m/s     | 4.20 to 4.40  | 4.33   | Pass      |
| Peak Shoulder Deflection           |     | mm      | 28 to 37      | 32.4   | Pass      |
| Peak Lateral Spine Acceleration Y  |     | G's     | 17 to 22      | 18.3   | Pass      |
| Peak Impactor Acceleration         |     | G's     | 13 to 18      | 15.9   | Pass      |
| Overall Test Results               |     |         |               | Pass   |           |



| Curve Description   |      |           |       |
|---------------------|------|-----------|-------|
| Shoulder Deflection |      |           |       |
| Plot No.            | Type | SAE Class | Units |
| 001                 | FIL  | 600       | MM    |
| Max                 | Time | Min       | Time  |
| 32.4                | 19.2 | 0.0       | 1.5   |



| Curve Description          |      |           |       |
|----------------------------|------|-----------|-------|
| Upper Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 002                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 18.3                       | 17.5 | -8.2      | 38.0  |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 003                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 15.9                  | 15.3 | -0.1      | -20.0 |

Test Program: SID IIs Thorax with Arm Impact Test  
 ATD Serial No.: 307


Test Date: 1/20/14  
 Test I.D.: 307TWA062




| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                    | Minutes | ≥180          | 442    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.7   | Pass      |
|                                    | Min     |               | 21.6   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 21.3   | Pass      |
|                                    | Min     |               | 20.6   | Pass      |
| Laboratory Temperature During Test | °C      | 18.9 to 25.6  | 21.6   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 21.3   | Pass      |
| Impactor Velocity                  | m/s     | 6.6 to 6.8    | 6.73   | Pass      |
| Peak Shoulder Deflection           | mm      | 31 to 40      | 38.7   | Pass      |
| Peak Upper Thorax Rib Deflection   | mm      | 25 to 32      | 28.5   | Pass      |
| Peak Middle Thorax Rib Deflection  | mm      | 30 to 36      | 32.2   | Pass      |
| Peak Lower Thorax Rib Deflection   | mm      | 32 to 38      | 33.1   | Pass      |
| Peak Upper Spine Y Acceleration    | G's     | 34 to 43      | 37.7   | Pass      |
| Peak Lower Spine Y Acceleration    | G's     | 29 to 37      | 34.6   | Pass      |
| Peak Impactor Acceleration         | G's     | 30 to 36      | 34.6   | Pass      |
| Overall Test Results               |         |               | Pass   |           |



| Curve Description        |      |           |       |
|--------------------------|------|-----------|-------|
| Upper Thorax Deflection  |      |           |       |
| Plot No.                 | Type | SAE Class | Units |
| 001                      | FIL  | 600       | MM    |
| Max                      | Time | Min       | Time  |
| 28.5                     | 17.0 | 0.0       | -1.5  |
| Middle Thorax Deflection |      |           |       |
| Max                      | Time | Min       | Time  |
| 32.2                     | 17.1 | 0.0       | -19.4 |
| Lower Thorax Deflection  |      |           |       |
| Max                      | Time | Min       | Time  |
| 33.1                     | 16.8 | 0.0       | -18.6 |




| Curve Description          |      |           |       |
|----------------------------|------|-----------|-------|
| Upper Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 004                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 37.7                       | 11.0 | -12.2     | 32.9  |
| Lower Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 005                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 34.6                       | 9.5  | -8.2      | 37.2  |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 006                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 34.6                  | 13.5 | -0.6      | 46.0  |

Test Program: SID IIs Thorax with Arm Impact Test  
 ATD Serial No.: 307

Test Date: 1/20/14  
 Test I.D.: 307TWA062




| Curve Description   |      |           |       |
|---------------------|------|-----------|-------|
| Shoulder Deflection |      |           |       |
| Plot No.            | Type | SAE Class | Units |
| 007                 | FIL  | 600       | MM    |
| Max                 | Time | Min       | Time  |
| 38.7                | 16.5 | -2.7      | 34.5  |

Test Program: SID IIs Thorax without Arm Impact Test  
 ATD Serial No.: 307


Test Date: 1/20/14  
 Test I.D.: 307TWOA062




| Tested Parameter                   |     | Units   | Specification | Result | Pass/Fail |
|------------------------------------|-----|---------|---------------|--------|-----------|
| Dummy Soak Time                    |     | Minutes | ≥180          | 492    | Pass      |
| Temperature During Soak            | Max | °C      | 18.9 to 25.6  | 21.7   | Pass      |
|                                    | Min | °C      |               | 21.6   | Pass      |
| Humidity During Soak               | Max | %       | 10.0 to 70.0  | 21.3   | Pass      |
|                                    | Min | %       |               | 20.6   | Pass      |
| Laboratory Temperature During Test |     | °C      | 18.9 to 25.6  | 21.7   | Pass      |
| Laboratory Humidity During Test    |     | %       | 10.0 to 70.0  | 21.2   | Pass      |
| Impactor Velocity                  |     | m/s     | 4.2 to 4.4    | 4.27   | Pass      |
| Peak Upper Thorax Rib Deflection   |     | mm      | 32 to 40      | 36.1   | Pass      |
| Peak Middle Thorax Rib Deflection  |     | mm      | 39 to 45      | 39.3   | Pass      |
| Peak Lower Thorax Rib Deflection   |     | mm      | 35 to 43      | 37.2   | Pass      |
| Peak Upper Spine Y Acceleration    |     | G's     | 13 to 17      | 15.7   | Pass      |
| Peak Lower Spine Y Acceleration    |     | G's     | 7 to 11       | 8.8    | Pass      |
| Peak Impactor Acceleration         |     | G's     | 14 to 18      | 16.0   | Pass      |
| Overall Test Results               |     |         |               | Pass   |           |



| Curve Description        |      |           |       |
|--------------------------|------|-----------|-------|
| Upper Thorax Deflection  |      |           |       |
| Plot No.                 | Type | SAE Class | Units |
| 001                      | FIL  | 600       | MM    |
| Max                      | Time | Min       | Time  |
| 36.1                     | 21.0 | 0.0       | -17.4 |
| Middle Thorax Deflection |      |           |       |
| Max                      | Time | Min       | Time  |
| 39.3                     | 21.6 | 0.0       | -15.6 |
| Lower Thorax Deflection  |      |           |       |
| Max                      | Time | Min       | Time  |
| 37.2                     | 22.6 | 0.0       | -19.5 |



| Curve Description          |      |           |       |
|----------------------------|------|-----------|-------|
| Upper Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 004                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 15.7                       | 16.8 | -6.1      | 49.8  |
| Lower Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 005                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 8.8                        | 15.6 | -4.0      | 45.1  |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 006                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 16.0                  | 19.3 | -0.2      | -20.0 |

Test Program: SID IIs Abdomen Impact Test  
 ATD Serial No.: 307


Test Date: 1/20/14  
 Test I.D.: 307ABD062




| Tested Parameter                    | Units   | Specification | Result | Pass/Fail |
|-------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                     | Minutes | ≥180          | 527    | Pass      |
| Temperature During Soak             | Max     | 20.6 to 22.2  | 21.7   | Pass      |
|                                     | Min     |               | 21.6   | Pass      |
| Humidity During Soak                | Max     | 10.0 to 70.0  | 21.3   | Pass      |
|                                     | Min     |               | 20.6   | Pass      |
| Laboratory Temperature During Test  | °C      | 18.9 to 25.6  | 21.7   | Pass      |
| Laboratory Humidity During Test     | %       | 10.0 to 70.0  | 21.0   | Pass      |
| Impactor Velocity                   | m/s     | 4.2 to 4.4    | 4.29   | Pass      |
| Peak Upper Abdominal Rib Deflection | mm      | 36 to 47      | 37.1   | Pass      |
| Peak Lower Abdominal Rib Deflection | mm      | 33 to 44      | 36.1   | Pass      |
| Peak Lower Spine Y Acceleration     | G's     | 9 to 14       | 12.0   | Pass      |
| Peak Impactor Acceleration          | G's     | 12 to 16      | 14.8   | Pass      |
| Overall Test Results                |         |               |        | Pass      |



| Curve Description              |      |           |       |
|--------------------------------|------|-----------|-------|
| Upper Abdominal Rib Deflection |      |           |       |
| Plot No.                       | Type | SAE Class | Units |
| 001                            | FIL  | 600       | MM    |
| Max                            | Time | Min       | Time  |
| 37.1                           | 22.8 | 0.0       | -12.0 |
| Curve Description              |      |           |       |
| Lower Abdominal Rib Deflection |      |           |       |
| Plot No.                       | Type | SAE Class | Units |
| 002                            | FIL  | 600       | MM    |
| Max                            | Time | Min       | Time  |
| 36.1                           | 22.0 | 0.0       | -12.8 |




| Curve Description          |      |           |       |
|----------------------------|------|-----------|-------|
| Lower Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 003                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 12.0                       | 11.8 | -6.5      | 34.5  |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 004                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 14.8                  | 17.7 | -0.1      | 97.3  |

# Resultant Data - SIDIIs Plug Compression



ATD Calibration Lab

Test ID

Part Serial Number

Test Date

Test Time

46107

9/21/2011

1:00 AM

Cert ID

ATD Serial Number

ATD Type

N/A

SIDIIs

**M20145504 PRE-TEST**

Current Date : 9/21/2011


Current Time : 01:00:51

Test Program: SID IIs Pelvis Acetabulum Impact Test  
 ATD Serial No.: 307


Test Date: 1/20/14  
 Test I.D.: 307ACET062




| Tested Parameter                         | Units   | Specification | Result | Pass/Fail |
|------------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                          | Minutes | ≥180          | 572    | Pass      |
| Temperature During Soak                  | Max     | 20.6 to 22.2  | 21.7   | Pass      |
|                                          | Min     |               | 21.6   | Pass      |
| Humidity During Soak                     | Max     | 10.0 to 70.0  | 21.3   | Pass      |
|                                          | Min     |               | 20.6   | Pass      |
| Laboratory Temperature During Test       | °C      | 18.9 to 25.6  | 21.7   | Pass      |
| Laboratory Humidity During Test          | %       | 10.0 to 70.0  | 21.2   | Pass      |
| Impactor Velocity                        | m/s     | 6.6 to 6.8    | 6.69   | Pass      |
| Peak Acetabulum Force Y                  | Newtons | 3600 to 4300  | 3872.7 | Pass      |
| Peak Pelvis Y Acceleration After 6 msec. | G's     | 34 to 42      | 36.5   | Pass      |
| Peak Impactor Acceleration               | G's     | 38 to 47      | 47.0   | Pass      |
| Overall Test Results                     |         |               | Pass   |           |



| Curve Description       |      |           |         |
|-------------------------|------|-----------|---------|
| Pelvis Acetabulum Force |      |           |         |
| Plot No.                | Type | SAE Class | Units   |
| 001                     | FIL  | 600       | Newtons |
| Max                     | Time | Min       | Time    |
| 3872.7                  | 7.3  | -41.2     | 0.3     |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Pelvis Y Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 002                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 48.0                  | 1.8  | -11.6     | 24.0  |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 003                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 47.0                  | 7.9  | -0.5      | -0.7  |

Test Program: SID IIs Pelvis Iliac Calibration  
 ATD Serial No.: 307

Test Date: 1/20/14  
 Test I.D.: 307PL062




| Tested Parameter                   |     | Units   | Specification | Result | Pass/Fail |
|------------------------------------|-----|---------|---------------|--------|-----------|
| Dummy Soak Time                    |     | Minutes | ≥180          | 642    | Pass      |
| Temperature During Soak            | Max | °C      | 20.6 to 22.2  | 21.7   | Pass      |
|                                    | Min | °C      |               | 21.6   | Pass      |
| Humidity During Soak               | Max | %       | 10.0 to 70.0  | 21.3   | Pass      |
|                                    | Min | %       |               | 20.6   | Pass      |
| Laboratory Temperature During Test |     | °C      | 18.9 to 25.6  | 21.6   | Pass      |
| Laboratory Humidity During Test    |     | %       | 10.0 to 70.0  | 21.2   | Pass      |
| Impactor Velocity                  |     | m/s     | 4.2 to 4.4    | 4.29   | Pass      |
| Peak Iliac Force                   |     | Newtons | 4100 to 5100  | 4505.9 | Pass      |
| Peak Pelvis Y Acceleration         |     | G's     | 28 to 39      | 32.0   | Pass      |
| Peak Impactor Acceleration         |     | G's     | 36 to 45      | 41.3   | Pass      |
| Overall Test Results               |     |         |               | Pass   |           |



#### Curve Description

##### Pelvis Iliac Force


| Plot No. | Type | SAE Class | Units   |
|----------|------|-----------|---------|
| 001      | FIL  | 600       | Newtons |
| Max      | Time | Min       | Time    |
| 4505.9   | 10.0 | -1.5      | -6.1    |



#### Curve Description

##### Pelvis Y Acceleration

| Plot No. | Type | SAE Class | Units |
|----------|------|-----------|-------|
| 002      | FIL  | 180       | G's   |
| Max      | Time | Min       | Time  |
| 32.0     | 9.6  | -4.1      | 15.7  |



#### Curve Description

##### Impactor Acceleration

| Plot No. | Type | SAE Class | Units |
|----------|------|-----------|-------|
| 003      | FIL  | 180       | G's   |
| Max      | Time | Min       | Time  |
| 41.3     | 10.0 | 0.0       | 38.0  |

**APPENDIX C**  
**POST-TEST / ATD CONFIGURATION AND PERFORMANCE VERIFICATION DATA**

Test Program: ES2re External Measurements  
 ATD Serial No.: F037

Test Date: 1/30/14  
 Test I.D.: N/A




| Tested Parameter             |                                                | Units | Specification | Result | Pass/Fail |
|------------------------------|------------------------------------------------|-------|---------------|--------|-----------|
| Laboratory Temperature       |                                                | °C    | 20.6 to 22.2  | 21.2   | Pass      |
| Laboratory Relative Humidity |                                                | %     | 10 to 70      | 30.0   | Pass      |
| 1                            | Sitting Height                                 | mm    | 900 - 918     | 909    | Pass      |
| 2                            | Seat to Shoulder Joint                         | mm    | 558 - 572     | 564    | Pass      |
| 3                            | Seat to Lower Face of Thoracic Spine Box       | mm    | 346 - 356     | 350    | Pass      |
| 4                            | Seat to Hip Joint (Center of Bolt)             | mm    | 97 - 103      | 99     | Pass      |
| 5                            | Sole to Seat, Sitting                          | mm    | 333 - 451     | 395    | Pass      |
| 6                            | Head Width                                     | mm    | 152 - 158     | 156    | Pass      |
| 7                            | Shoulder / Arm Width                           | mm    | 461 - 479     | 470    | Pass      |
| 8                            | Thorax Width                                   | mm    | 322 - 332     | 326    | Pass      |
| 9                            | Abdomen Width                                  | mm    | 273 - 287     | 280    | Pass      |
| 10                           | Pelvis Lap Width                               | mm    | 359 - 373     | 363    | Pass      |
| 11                           | Head Depth                                     | mm    | 196 - 206     | 201    | Pass      |
| 12                           | Thorax Depth                                   | mm    | 262 - 272     | 270    | Pass      |
| 13                           | Abdomen Width                                  | mm    | 194 - 204     | 199    | Pass      |
| 14                           | Pelvis Depth                                   | mm    | 235 - 245     | 240    | Pass      |
| 15                           | Back of Buttocks to Hip Joint (Center of Bolt) | mm    | 150 - 160     | 155    | Pass      |
| 16                           | Back of Buttocks to Front Knee                 | mm    | 597 - 615     | 608    | Pass      |
| Overall Test Results         |                                                |       |               |        | Pass      |

Test Program: ES2re Head Drop Test  
 ATD Serial No.: F037


Test Date: 1/30/14  
 Test I.D.: F037HD055




| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Head Assembly Soak Time            | Minutes | ≥240          | 450    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.4   | Pass      |
|                                    | Min     |               | 21.2   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                    | Min     |               | 16.8   | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2  | 21.3   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 16.8   | Pass      |
| Peak Head Resultant Acceleration   | G's     | 125 to 155    | 137.8  | Pass      |
| Peak Head X Acceleration           | G's     | ≤15           | 5.8    | Pass      |
| Is Acceleration Unimodal?          | Yes/No  | Yes           | Yes    | Pass      |
| Oscillations After Main Pulse      | %       | <15           | 6.5    | Pass      |
| Overall Test Results               |         |               |        | Pass      |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Resultant    |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 001               | RES  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 137.8             | 2.6  | 0.1       | -2.0  |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head X            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 5.8               | 5.3  | -3.3      | 2.0   |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Y            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 003               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 112.1             | 2.6  | -6.2      | 6.0   |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Z            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 004               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 80.2              | 2.6  | -0.2      | -0.5  |

Test Program: ES2re Neck Flexion Test  
 ATD Serial No.: F037


Test Date: 1/30/14  
 Test I.D.: F037NB055




| Tested Parameter                      | Units   | Specification | Result | Pass/Fail |
|---------------------------------------|---------|---------------|--------|-----------|
| Neck Assembly Soak Time               | Minutes | ≥240          | 485    | Pass      |
| Temperature During Soak               | Max     | 20.6 to 22.2  | 21.4   | Pass      |
|                                       | Min     |               | 21.2   | Pass      |
| Humidity During Soak                  | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                       | Min     |               | 16.8   | Pass      |
| Laboratory Temperature During Test    | °C      | 20.6 to 22.2  | 21.3   | Pass      |
| Laboratory Humidity During Test       | %       | 10.0 to 70.0  | 16.8   | Pass      |
| Pendulum Velocity                     | m/s     | 3.3 to 3.5    | 3.45   | Pass      |
| Headform Flexion                      | Max     | 49 to 59      | 54.3   | Pass      |
|                                       | Time    | 54 to 66      | 60.0   | Pass      |
| Headform Flexion Decay (Peak to Zero) | msec    | 53 to 88      | 61.0   | Pass      |
| Overall Test Results                  |         |               |        | Pass      |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Pendulum Deceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 001                   | FIL  | 60        | G's   |
| Max                   | Time | Min       | Time  |
| 4.4                   | 47.4 | -32.2     | 10.0  |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Pendulum Velocity |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 60        | m/s   |
| Max               | Time | Min       | Time  |
| 0.0               | -0.9 | -4.2      | 199.9 |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Pendulum Velocity |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 60        | m/s   |
| Max               | Time | Min       | Time  |
| 0.0               | -0.9 | -4.2      | 199.9 |

#### Velocity Corridors


| Upper Boundary |                | Lower Boundary |                |
|----------------|----------------|----------------|----------------|
| Time (msec)    | Velocity (m/s) | Time (msec)    | Velocity (m/s) |
| 1.0            | 0.00           | 0.0            | -0.05          |
| 3.0            | -0.03          | 2.5            | -0.375         |
| 14.0           | -3.20          | 13.5           | -3.70          |
|                |                | 17.0           | -3.70          |

Test Program: ES2re Neck Flexion Test  
 ATD Serial No.: F037


Test Date: 1/30/14  
 Test I.D.: F037NB055




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Headform Rotation |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 003               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 54.3              | 60.0 | -28.6     | 162.3   |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer A   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 004               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 35.9              | 54.0 | -17.9     | 162.7   |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer B   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 005               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 31.8              | 52.7 | -20.0     | 164.1   |




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer C   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 006               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 18.6              | 60.4 | -10.7     | 160.0   |

Test Program: ES2re Shoulder Impact Test  
 ATD Serial No.: F037

Test Date: 1/30/14  
 Test I.D.: F037SH055



| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                    | Minutes | ≥240          | 550    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.4   | Pass      |
|                                    | Min     |               | 21.2   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                    | Min     |               | 16.8   | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2  | 21.4   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 17.1   | Pass      |
| Pendulum Speed                     | m/s     | 4.2 to 4.4    | 4.33   | Pass      |
| Peak Impactor Acceleration         | G's     | 7.5 to 10.5   | 9.3    | Pass      |
| Overall Test Results               |         |               |        | Pass      |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 001                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 9.3                   | 17.2 | 0.0       | 89.4  |

Test Program: ES2re Thorax - Rib Drop Test  
 ATD Serial No.: F037 Rib # 1


Test Date: 1/30/14  
 Test I.D.: F037RB1055



| Tested Parameter                                | Units   | Specification | Result | Pass/Fail |
|-------------------------------------------------|---------|---------------|--------|-----------|
| Rib Module Soak Time                            | Minutes | ≥240          | 605    | Pass      |
| Temperature During Soak                         | Max     | 20.6 to 22.2  | 21.4   | Pass      |
|                                                 | Min     |               | 21.2   | Pass      |
| Humidity During Soak                            | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                                 | Min     |               | 16.8   | Pass      |
| Laboratory Temperature During Test              | °C      | 20.6 to 22.2  | 21.4   | Pass      |
| Laboratory Humidity During Test                 | %       | 10.0 to 70.0  | 17.0   | Pass      |
| Peak Rib Deflection at 459 +/- 5 mm Drop Height | mm      | 36 to 40      | 38.5   | Pass      |
| Peak Rib Deflection at 815 +/- 8 mm Drop Height | mm      | 46 to 51      | 49.5   | Pass      |
| Overall Test Results                            |         |               |        | Pass      |



| Curve Description                         |      |           |       |
|-------------------------------------------|------|-----------|-------|
| Upper Rib Deflection (459 mm Drop Height) |      |           |       |
| Plot No.                                  | Type | SAE Class | Units |
| 001                                       | FIL  | 180       | MM    |
| Max                                       | Time | Min       | Time  |
| 38.5                                      | 31.6 | -4.2      | 66.3  |




| Curve Description                         |      |           |       |
|-------------------------------------------|------|-----------|-------|
| Upper Rib Deflection (815 mm Drop Height) |      |           |       |
| Plot No.                                  | Type | SAE Class | Units |
| 002                                       | FIL  | 180       | MM    |
| Max                                       | Time | Min       | Time  |
| 49.5                                      | 31.3 | -4.6      | 64.7  |

Test Program: ES2re Thorax - Rib Drop Test  
 ATD Serial No.: F037 Rib # 2


Test Date: 1/30/14  
 Test I.D.: F037RB2055



| Tested Parameter                                | Units   | Specification | Result | Pass/Fail |
|-------------------------------------------------|---------|---------------|--------|-----------|
| Rib Module Soak Time                            | Minutes | ≥240          | 650    | Pass      |
| Temperature During Soak                         | Max     | 20.6 to 22.2  | 21.4   | Pass      |
|                                                 | Min     |               | 21.2   | Pass      |
| Humidity During Soak                            | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                                 | Min     |               | 16.8   | Pass      |
| Laboratory Temperature During Test              | °C      | 20.6 to 22.2  | 21.4   | Pass      |
| Laboratory Humidity During Test                 | %       | 10.0 to 70.0  | 16.9   | Pass      |
| Peak Rib Deflection at 459 +/- 5 mm Drop Height | mm      | 36 to 40      | 38.7   | Pass      |
| Peak Rib Deflection at 815 +/- 8 mm Drop Height | mm      | 46 to 51      | 50.5   | Pass      |
| Overall Test Results                            |         |               |        | Pass      |



| Curve Description                          |      |           |       |
|--------------------------------------------|------|-----------|-------|
| Middle Rib Deflection (459 mm Drop Height) |      |           |       |
| Plot No.                                   | Type | SAE Class | Units |
| 001                                        | FIL  | 180       | MM    |
| Max                                        | Time | Min       | Time  |
| 38.7                                       | 31.9 | -3.8      | 66.6  |




| Curve Description                          |      |           |       |
|--------------------------------------------|------|-----------|-------|
| Middle Rib Deflection (815 mm Drop Height) |      |           |       |
| Plot No.                                   | Type | SAE Class | Units |
| 002                                        | FIL  | 180       | MM    |
| Max                                        | Time | Min       | Time  |
| 50.5                                       | 31.4 | -4.5      | 64.6  |

Test Program: ES2re Thorax - Rib Drop Test  
 ATD Serial No.: F037 Rib # 3


Test Date: 1/30/14  
 Test I.D.: F037RB3055



| Tested Parameter                                | Units   | Specification | Result | Pass/Fail |
|-------------------------------------------------|---------|---------------|--------|-----------|
| Rib Module Soak Time                            | Minutes | ≥240          | 695    | Pass      |
| Temperature During Soak                         | Max     | 20.6 to 22.2  | 21.4   | Pass      |
|                                                 | Min     |               | 21.2   | Pass      |
| Humidity During Soak                            | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                                 | Min     |               | 16.8   | Pass      |
| Laboratory Temperature During Test              | °C      | 20.6 to 22.2  | 21.3   | Pass      |
| Laboratory Humidity During Test                 | %       | 10.0 to 70.0  | 16.9   | Pass      |
| Peak Rib Deflection at 459 +/- 5 mm Drop Height | mm      | 36 to 40      | 39.0   | Pass      |
| Peak Rib Deflection at 815 +/- 8 mm Drop Height | mm      | 46 to 51      | 49.3   | Pass      |
| Overall Test Results                            |         |               |        | Pass      |



| Curve Description                         |      |           |       |
|-------------------------------------------|------|-----------|-------|
| Lower Rib Deflection (459 mm Drop Height) |      |           |       |
| Plot No.                                  | Type | SAE Class | Units |
| 001                                       | FIL  | 180       | MM    |
| Max                                       | Time | Min       | Time  |
| 39.0                                      | 31.7 | -3.4      | 66.7  |




| Curve Description                         |      |           |       |
|-------------------------------------------|------|-----------|-------|
| Lower Rib Deflection (815 mm Drop Height) |      |           |       |
| Plot No.                                  | Type | SAE Class | Units |
| 002                                       | FIL  | 180       | MM    |
| Max                                       | Time | Min       | Time  |
| 49.3                                      | 30.6 | -4.2      | 63.9  |

Test Program: ES2re Thorax - Full Body Impact Test  
 ATD Serial No.: F037


Test Date: 1/30/14  
 Test I.D.: F037TH055




| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                    | Minutes | ≥240          | 740    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.4   | Pass      |
|                                    | Min     |               | 21.2   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                    | Min     |               | 16.8   | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2  | 21.2   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 16.9   | Pass      |
| Peak Impactor Velocity             | m/s     | 5.4 to 5.6    | 5.56   | Pass      |
| Peak Impactor Force                | N       | 5100 to 6200  | 5788.3 | Pass      |
|                                    | msec    | > 6.0 msec    | 9.5    | Pass      |
| Peak Upper Rib Deflection          | mm      | 34 to 41      | 36.5   | Pass      |
| Peak Middle Rib Deflection         | mm      | 37 to 45      | 40.8   | Pass      |
| Peak Lower Rib Deflection          | mm      | 37 to 44      | 38.2   | Pass      |
| Overall Test Results               |         |               |        | Pass      |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Impactor Force    |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 001               | FIL  | 180       | Newtons |
| Max               | Time | Min       | Time    |
| 10050.5           | 2.4  | -58.7     | -0.7    |



| Curve Description                    |      |              |       |
|--------------------------------------|------|--------------|-------|
| Upper, Middle, Lower Rib Deflections |      |              |       |
| Plot No.                             | Type | SAE Class    | Units |
| 002                                  | FIL  | 180          | MM    |
| Max (Upper)                          | Time | Min (Upper)  | Time  |
| 36.5                                 | 16.1 | -3.9         | 40.2  |
| Max (Middle)                         | Time | Min (Middle) | Time  |
| 40.8                                 | 16.7 | -3.6         | 45.0  |
| Max (Lower)                          | Time | Min (Lower)  | Time  |
| 38.2                                 | 17.2 | -3.2         | 49.9  |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 003                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 43.9                  | 2.4  | -0.3      | -0.7  |

Test Program: ES2re Abdomen Impact Test  
 ATD Serial No.: F037


Test Date: 1/30/14  
 Test I.D.: F037ABD055



| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                    | Minutes | ≥240          | 810    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.4   | Pass      |
|                                    | Min     |               | 21.2   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                    | Min     |               | 16.8   | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2  | 21.2   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 16.9   | Pass      |
| Probe Velocity                     | m/s     | 3.9 to 4.1    | 4.01   | Pass      |
| Peak Impactor Force                | N       | 4000 to 4800  | 4685.6 | Pass      |
|                                    | msec    | 10.6 to 13.0  | 11.4   | Pass      |
| Sum of Abdominal Forces            | N       | 2200 to 2700  | 2613.8 | Pass      |
|                                    | msec    | 10.0 to 12.3  | 10.8   | Pass      |
| Overall Test Results               |         |               |        | Pass      |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 001                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 20.5                  | 11.4 | -0.2      | -0.5  |




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Impactor Force    |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 002               | FIL  | 180       | Newtons |
| Max               | Time | Min       | Time    |
| 4685.6            | 11.4 | -39.7     | -0.5    |

Test Program: ES2re Abdomen Impact Test  
 ATD Serial No.: F037


Test Date: 1/30/14  
 Test I.D.: F037ABD055




| Curve Description   |      |           |         |
|---------------------|------|-----------|---------|
| Front Abdomen Force |      |           |         |
| Plot No.            | Type | SAE Class | Units   |
| 003                 | FIL  | 600       | Newtons |
| Max                 | Time | Min       | Time    |
| 606.6               | 11.0 | -8.1      | 75.7    |



| Curve Description    |      |           |         |
|----------------------|------|-----------|---------|
| Middle Abdomen Force |      |           |         |
| Plot No.             | Type | SAE Class | Units   |
| 004                  | FIL  | 600       | Newtons |
| Max                  | Time | Min       | Time    |
| 1040.5               | 10.8 | -4.5      | 115.9   |



| Curve Description  |      |           |         |
|--------------------|------|-----------|---------|
| Rear Abdomen Force |      |           |         |
| Plot No.           | Type | SAE Class | Units   |
| 005                | FIL  | 600       | Newtons |
| Max                | Time | Min       | Time    |
| 976.3              | 10.1 | -1.9      | 71.3    |




| Curve Description     |      |           |         |
|-----------------------|------|-----------|---------|
| Abdomen Sum Resultant |      |           |         |
| Plot No.              | Type | SAE Class | Units   |
| 006                   | RES  | 600       | Newtons |
| Max                   | Time | Min       | Time    |
| 2613.8                | 10.8 | -12.0     | 71.5    |

Test Program: ES2re Lumbar Flexion Test  
 ATD Serial No.: F037


Test Date: 1/30/14  
 Test I.D.: F037LB055




| Tested Parameter                      | Units   | Specification | Result | Pass/Fail |
|---------------------------------------|---------|---------------|--------|-----------|
| Lumbar Spine Assembly Soak Time       | Minutes | ≥240          | 885    | Pass      |
| Temperature During Soak               | Max     | 20.6 to 22.2  | 21.4   | Pass      |
|                                       | Min     |               | 21.2   | Pass      |
| Humidity During Soak                  | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                       | Min     |               | 16.8   | Pass      |
| Laboratory Temperature During Test    | °C      | 20.6 to 22.2  | 21.2   | Pass      |
| Laboratory Humidity During Test       | %       | 10.0 to 70.0  | 16.9   | Pass      |
| Pendulum Velocity                     | m/s     | 5.95 to 6.15  | 6.02   | Pass      |
| Headform Rotation                     | Max     | 45 to 55      | 51.0   | Pass      |
|                                       | Time    | 39 to 53      | 44.7   | Pass      |
| Time of Decay to Zero Angle from Peak | msec    | 37 to 57      | 41.6   | Pass      |
| Overall Test Results                  |         |               |        | Pass      |



| Curve Description     |       |           |       |
|-----------------------|-------|-----------|-------|
| Pendulum Deceleration |       |           |       |
| Plot No.              | Type  | SAE Class | Units |
| 001                   | FIL   | 60        | G's   |
| Max                   | Time  | Min       | Time  |
| 3.4                   | 140.5 | -28.4     | 9.3   |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Pendulum Velocity |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 60        | m/s   |
| Max               | Time | Min       | Time  |
| 0.0               | -1.3 | -7.1      | 122.9 |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Pendulum Velocity |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 60        | m/s   |
| Max               | Time | Min       | Time  |
| 0.0               | -1.3 | -7.1      | 122.9 |

#### Velocity Corridors


| Upper Boundary |                | Lower Boundary |                |
|----------------|----------------|----------------|----------------|
| Time (msec)    | Velocity (m/s) | Time (msec)    | Velocity (m/s) |
| 1.0            | 0.00           | 0.0            | -0.05          |
| 3.7            | -0.24          | 2.7            | -0.425         |
| 27.0           | -5.80          | 24.5           | -6.50          |
|                |                | 30.0           | -6.50          |

Test Program: ES2re Lumbar Flexion Test  
 ATD Serial No.: F037


Test Date: 1/30/14  
 Test I.D.: F037LB055




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Headform Rotation |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 003               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 51.0              | 44.7 | -20.0     | 101.0   |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer A   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 004               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 31.5              | 45.0 | -12.9     | 104.3   |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer B   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 005               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 28.0              | 42.8 | -12.4     | 100.6   |




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Potentiometer C   |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 006               | FIL  | 180       | Degrees |
| Max               | Time | Min       | Time    |
| 19.5              | 44.4 | -7.1      | 100.4   |

Test Program: ES2re Pelvis Impact Test  
 ATD Serial No.: F037


Test Date: 1/30/14  
 Test I.D.: F037PL055




| Tested Parameter                   | Units   | Specification  | Result  | Pass/Fail |
|------------------------------------|---------|----------------|---------|-----------|
| Dummy Soak Time                    | Minutes | ≥240           | 940     | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2   | 21.4    | Pass      |
|                                    | Min     |                | 21.2    | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0   | 17.1    | Pass      |
|                                    | Min     |                | 16.8    | Pass      |
| Laboratory Temperature During Test | °C      | 20.6 to 22.2   | 21.2    | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0   | 17.0    | Pass      |
| Pendulum Velocity                  | m/s     | 4.2 to 4.4     | 4.33    | Pass      |
| Peak Impactor Force                | N       | 4700 to 5400   | 5023.4  | Pass      |
|                                    | msec    | 11.8 to 16.1   | 12.9    | Pass      |
| Peak Pubic Symphysis Load          | N       | -1230 to -1590 | -1371.5 | Pass      |
|                                    | msec    | 12.2 to 17.0   | 15.9    | Pass      |
| Overall Test Results               |         |                |         | Pass      |



| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| Impactor Force    |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 001               | FIL  | 180       | Newtons |
| Max               | Time | Min       | Time    |
| 5023.4            | 12.9 | -72.7     | 39.8    |



| Curve Description       |      |           |         |
|-------------------------|------|-----------|---------|
| Pubic Symphysis Force Y |      |           |         |
| Plot No.                | Type | SAE Class | Units   |
| 002                     | FIL  | 600       | Newtons |
| Max                     | Time | Min       | Time    |
| 177.9                   | 40.3 | -1371.5   | 15.9    |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 003                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 21.9                  | 12.9 | -0.3      | 39.8  |

Test Program: SID IIs External Measurements  
 ATD Serial No.: 307

Test Date: 1/31/14  
 Test I.D.: N/A




| Tested Parameter             |                                 | Units | Specification | Result | Pass/Fail |
|------------------------------|---------------------------------|-------|---------------|--------|-----------|
| Laboratory Temperature       |                                 | °C    | 20.6 to 22.2  | 21.2   | Pass      |
| Laboratory Relative Humidity |                                 | %     | 10 to 70      | 17     | Pass      |
| A                            | Sitting Height                  | mm    | 772 - 788     | 778    | Pass      |
| B                            | Shoulder Pivot Height           | mm    | 437 - 453     | 443    | Pass      |
| C                            | H-Point Height                  | mm    | 79 - 89       | 85     | Pass      |
| D                            | H-Point from Seatback           | mm    | 141 - 151     | 144    | Pass      |
| E                            | Shoulder Pivot from Backline    | mm    | 97 - 107      | 102    | Pass      |
| F                            | Thigh Clearance                 | mm    | 119 - 135     | 128    | Pass      |
| G                            | Head Breadth                    | mm    | 140 - 148     | 145    | Pass      |
| H                            | Head Back from Backline         | mm    | 40 - 46       | 43     | Pass      |
| I                            | Head Depth                      | mm    | 178 - 188     | 185    | Pass      |
| J                            | Head Circumference              | mm    | 541 - 551     | 546    | Pass      |
| K                            | Buttock to Knee Length          | mm    | 514 - 540     | 525    | Pass      |
| L                            | Popliteal Height                | mm    | 343 - 369     | 351    | Pass      |
| M                            | Knee Pivot to Floor Height      | mm    | 392 - 409     | 400    | Pass      |
| N                            | Buttock Popliteal Length        | mm    | 416 - 442     | 432    | Pass      |
| O                            | Chest Depth w/o Jacket          | mm    | 195 - 211     | 205    | Pass      |
| P                            | Foot Length                     | mm    | 216 - 232     | 223    | Pass      |
| Q                            | Hip Breadth with Pelvic Plug    | mm    | 313 - 323     | 319    | Pass      |
| R                            | Arm Length                      | mm    | 249 - 259     | 254    | Pass      |
| S                            | Knee Joint to Seatback          | mm    | 477 - 493     | 483    | Pass      |
| V                            | Shoulder Width                  | mm    | 341 - 357     | 351    | Pass      |
| W                            | Foot Width                      | mm    | 78 - 94       | 89     | Pass      |
| Y                            | Chest Circumference with Jacket | mm    | 851 - 881     | 872    | Pass      |
| Z                            | Waist Circumference             | mm    | 760 - 791     | 774    | Pass      |
| Overall Test Results         |                                 |       |               |        | Pass      |

Test Program: SID IIs Head Drop Test  
 ATD Serial No.: 307


Test Date: 1/31/14  
 Test I.D.: 307HD063




| Tested Parameter                   |     | Units   | Specification | Result | Pass/Fail |
|------------------------------------|-----|---------|---------------|--------|-----------|
| Head Assembly Soak Time            |     | Minutes | ≥240          | 500    | Pass      |
| Temperature During Soak            | Max | °C      | 18.9 to 25.6  | 21.2   | Pass      |
|                                    | Min | °C      |               | 21.2   | Pass      |
| Humidity During Soak               | Max | %       | 10.0 to 70.0  | 17.1   | Pass      |
|                                    | Min | %       |               | 16.9   | Pass      |
| Laboratory Temperature During Test |     | °C      | 18.9 to 25.6  | 21.2   | Pass      |
| Laboratory Humidity During Test    |     | %       | 10.0 to 70.0  | 17.1   | Pass      |
| Peak Head Resultant Acceleration   |     | G's     | 115 to 137    | 130.7  | Pass      |
| Peak Head X Acceleration           |     | G's     | <15           | 5.1    | Pass      |
| Is Acceleration Unimodal?          |     | Yes/No  | Yes           | Yes    | Pass      |
| Oscillations After Main Pulse      |     | %       | <15           | 2.4    | Pass      |
| Overall Test Results               |     |         |               | Pass   |           |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Resultant    |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 001               | RES  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 130.7             | 4.9  | 0.6       | 2.2   |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head X            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 002               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 5.1               | 6.5  | -0.4      | 0.4   |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Y            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 003               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 105.1             | 4.9  | -2.5      | 8.0   |




| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Head Z            |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 004               | FIL  | 1000      | G's   |
| Max               | Time | Min       | Time  |
| 77.8              | 5.0  | -0.8      | 10.6  |

Test Program: SID IIs Neck Flexion Test  
 ATD Serial No.: 307


Test Date: 1/31/14  
 Test I.D.: 307NB063




| Tested Parameter                   |             | Units   | Specification  | Result | Pass/Fail |
|------------------------------------|-------------|---------|----------------|--------|-----------|
| Neck Assembly Soak Time            |             | Minutes | ≥240           | 575    | Pass      |
| Temperature During Soak            | Max         | °C      | 20.6 to 22.2   | 21.2   | Pass      |
|                                    | Min         | °C      |                | 21.2   | Pass      |
| Humidity During Soak               | Max         | %       | 10.0 to 70.0   | 17.1   | Pass      |
|                                    | Min         | %       |                | 16.9   | Pass      |
| Laboratory Temperature During Test |             | °C      | 20.6 to 22.2   | 21.2   | Pass      |
| Laboratory Humidity During Test    |             | %       | 10.0 to 70.0   | 17.0   | Pass      |
| Pendulum Velocity                  |             | m/s     | 5.51 to 5.63   | 5.58   | Pass      |
| Pendulum Deceleration              | 10 msec     | m/s     | -2.20 to -2.80 | -2.26  | Pass      |
|                                    | 15 msec     | m/s     | -3.30 to -4.10 | -3.42  | Pass      |
|                                    | 20 msec     | m/s     | -4.40 to -5.40 | -4.54  | Pass      |
|                                    | 25 msec     | m/s     | -5.40 to -6.10 | -5.47  | Pass      |
|                                    | 25-100 msec | m/s     | -5.50 to -6.20 | -5.72  | Pass      |
| D-Plane Rotation                   | Max         | Degrees | 71 to 81       | 73.3   | Pass      |
|                                    | Time        | msec    | 50 to 70       | 65.2   | Pass      |
| Peak Occipital Condyle Moment      |             | Nm      | -36 to -44     | -42.3  | Pass      |
| Decaying Moment Time to Cross 0 Nm |             | msec    | 102 to 126     | 113.4  | Pass      |
| Overall Test Results               |             |         |                | Pass   |           |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Pendulum Deceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 001                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 3.1                   | 0.0  | -27.0     | 0.0   |




| Curve Description |       |           |       |
|-------------------|-------|-----------|-------|
| Pendulum Velocity |       |           |       |
| Plot No.          | Type  | SAE Class | Units |
| 002               | FIL   | 180       | m/s   |
| Max               | Time  | Min       | Time  |
| 0.0               | -20.0 | -5.7      | 40.8  |




| Curve Description |      |           |         |
|-------------------|------|-----------|---------|
| D-Plane Rotation  |      |           |         |
| Plot No.          | Type | SAE Class | Units   |
| 003               | FIL  | 60        | Degress |
| Max               | Time | Min       | Time    |
| 73.3              | 65.2 | -35.5     | 184.2   |

Test Program: SID IIs Neck Flexion Test  
 ATD Serial No.: 307


Test Date: 1/31/14  
 Test I.D.: 307NB063



| Curve Description |       |           |         |
|-------------------|-------|-----------|---------|
| Neck Force Y      |       |           |         |
| Plot No.          | Type  | SAE Class | Units   |
| 004               | FIL   | 1000      | Newtons |
| Max               | Time  | Min       | Time    |
| 160.9             | 172.7 | -451.3    | 59.1    |



| Curve Description |      |           |       |
|-------------------|------|-----------|-------|
| Neck Moment X     |      |           |       |
| Plot No.          | Type | SAE Class | Units |
| 005               | FIL  | 600       | Nm    |
| Max               | Time | Min       | Time  |
| 16.2              | 9.5  | -34.9     | 63.7  |




| Curve Description              |       |           |       |
|--------------------------------|-------|-----------|-------|
| Moment About Occipital Condyle |       |           |       |
| Plot No.                       | Type  | SAE Class | Units |
| 006                            | FIL   | 600       | Nm    |
| Max                            | Time  | Min       | Time  |
| 17.6                           | 167.3 | -42.3     | 62.5  |

Test Program: SID IIs Shoulder Impact Test  
 ATD Serial No.: 307


Test Date: 1/31/14  
 Test I.D.: 307SH063




| Tested Parameter                   |     | Units   | Specification | Result | Pass/Fail |
|------------------------------------|-----|---------|---------------|--------|-----------|
| Dummy Soak Time                    |     | Minutes | ≥180          | 630    | Pass      |
| Temperature During Soak            | Max | °C      | 20.6 to 22.2  | 21.2   | Pass      |
|                                    | Min | °C      |               | 21.2   | Pass      |
| Humidity During Soak               | Max | %       | 10.0 to 70.0  | 17.1   | Pass      |
|                                    | Min | %       |               | 16.9   | Pass      |
| Laboratory Temperature During Test |     | °C      | 20.6 to 22.2  | 21.2   | Pass      |
| Laboratory Humidity During Test    |     | %       | 10.0 to 70.0  | 16.9   | Pass      |
| Impactor Velocity                  |     | m/s     | 4.20 to 4.40  | 4.34   | Pass      |
| Peak Shoulder Deflection           |     | mm      | 28 to 37      | 31.0   | Pass      |
| Peak Lateral Spine Acceleration Y  |     | G's     | 17 to 22      | 18.9   | Pass      |
| Peak Impactor Acceleration         |     | G's     | 13 to 18      | 16.2   | Pass      |
| Overall Test Results               |     |         |               | Pass   |           |



| Curve Description   |      |           |       |
|---------------------|------|-----------|-------|
| Shoulder Deflection |      |           |       |
| Plot No.            | Type | SAE Class | Units |
| 001                 | FIL  | 600       | MM    |
| Max                 | Time | Min       | Time  |
| 31.0                | 18.9 | 0.0       | -18.6 |



| Curve Description          |      |           |       |
|----------------------------|------|-----------|-------|
| Upper Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 002                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 18.9                       | 10.9 | -7.6      | 39.5  |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 003                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 16.2                  | 14.8 | -0.2      | 54.5  |

Test Program: SID IIs Thorax with Arm Impact Test  
 ATD Serial No.: 307


Test Date: 1/31/14  
 Test I.D.: 307TWA063




| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                    | Minutes | ≥180          | 675    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.2   | Pass      |
|                                    | Min     |               | 21.2   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                    | Min     |               | 16.9   | Pass      |
| Laboratory Temperature During Test | °C      | 18.9 to 25.6  | 21.2   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 16.9   | Pass      |
| Impactor Velocity                  | m/s     | 6.6 to 6.8    | 6.75   | Pass      |
| Peak Shoulder Deflection           | mm      | 31 to 40      | 34.8   | Pass      |
| Peak Upper Thorax Rib Deflection   | mm      | 25 to 32      | 28.6   | Pass      |
| Peak Middle Thorax Rib Deflection  | mm      | 30 to 36      | 31.8   | Pass      |
| Peak Lower Thorax Rib Deflection   | mm      | 32 to 38      | 33.0   | Pass      |
| Peak Upper Spine Y Acceleration    | G's     | 34 to 43      | 37.7   | Pass      |
| Peak Lower Spine Y Acceleration    | G's     | 29 to 37      | 32.5   | Pass      |
| Peak Impactor Acceleration         | G's     | 30 to 36      | 34.7   | Pass      |
| Overall Test Results               |         |               | Pass   |           |



| Curve Description        |      |           |       |
|--------------------------|------|-----------|-------|
| Upper Thorax Deflection  |      |           |       |
| Plot No.                 | Type | SAE Class | Units |
| 001                      | FIL  | 600       | MM    |
| Max                      | Time | Min       | Time  |
| 28.6                     | 16.6 | 0.0       | -4.5  |
| Middle Thorax Deflection |      |           |       |
| Max                      | Time | Min       | Time  |
| 31.8                     | 16.7 | 0.0       | -2.7  |
| Lower Thorax Deflection  |      |           |       |
| Max                      | Time | Min       | Time  |
| 33.0                     | 16.9 | 0.0       | -3.0  |




| Curve Description          |      |           |       |
|----------------------------|------|-----------|-------|
| Upper Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 004                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 37.7                       | 11.4 | -11.4     | 29.7  |
| Lower Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 005                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 32.5                       | 10.1 | -7.5      | 36.5  |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 006                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 34.7                  | 13.8 | -0.3      | 72.0  |

Test Program: SID IIs Thorax with Arm Impact Test  
 ATD Serial No.: 307

Test Date: 1/31/14  
 Test I.D.: 307TWA063




| Curve Description   |      |           |       |
|---------------------|------|-----------|-------|
| Shoulder Deflection |      |           |       |
| Plot No.            | Type | SAE Class | Units |
| 007                 | FIL  | 600       | MM    |
| Max                 | Time | Min       | Time  |
| 34.8                | 16.3 | -0.5      | 34.0  |

Test Program: SID IIs Thorax without Arm Impact Test  
 ATD Serial No.: 307


Test Date: 1/31/14  
 Test I.D.: 307TWOA063




| Tested Parameter                   |     | Units   | Specification | Result | Pass/Fail |
|------------------------------------|-----|---------|---------------|--------|-----------|
| Dummy Soak Time                    |     | Minutes | ≥180          | 725    | Pass      |
| Temperature During Soak            | Max | °C      | 18.9 to 25.6  | 21.2   | Pass      |
|                                    | Min | °C      |               | 21.2   | Pass      |
| Humidity During Soak               | Max | %       | 10.0 to 70.0  | 17.1   | Pass      |
|                                    | Min | %       |               | 16.9   | Pass      |
| Laboratory Temperature During Test |     | °C      | 18.9 to 25.6  | 21.2   | Pass      |
| Laboratory Humidity During Test    |     | %       | 10.0 to 70.0  | 16.9   | Pass      |
| Impactor Velocity                  |     | m/s     | 4.2 to 4.4    | 4.32   | Pass      |
| Peak Upper Thorax Rib Deflection   |     | mm      | 32 to 40      | 36.3   | Pass      |
| Peak Middle Thorax Rib Deflection  |     | mm      | 39 to 45      | 39.6   | Pass      |
| Peak Lower Thorax Rib Deflection   |     | mm      | 35 to 43      | 36.6   | Pass      |
| Peak Upper Spine Y Acceleration    |     | G's     | 13 to 17      | 15.0   | Pass      |
| Peak Lower Spine Y Acceleration    |     | G's     | 7 to 11       | 8.7    | Pass      |
| Peak Impactor Acceleration         |     | G's     | 14 to 18      | 15.8   | Pass      |
| Overall Test Results               |     |         |               | Pass   |           |



| Curve Description        |      |           |       |
|--------------------------|------|-----------|-------|
| Upper Thorax Deflection  |      |           |       |
| Plot No.                 | Type | SAE Class | Units |
| 001                      | FIL  | 600       | MM    |
| Max                      | Time | Min       | Time  |
| 36.3                     | 21.9 | 0.0       | -10.4 |
| Middle Thorax Deflection |      |           |       |
| Max                      | Time | Min       | Time  |
| 39.6                     | 22.6 | 0.0       | -8.0  |
| Lower Thorax Deflection  |      |           |       |
| Max                      | Time | Min       | Time  |
| 36.6                     | 23.3 | 0.0       | -10.7 |



| Curve Description          |      |           |       |
|----------------------------|------|-----------|-------|
| Upper Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 004                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 15.0                       | 17.5 | -5.4      | 52.5  |
| Lower Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 005                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 8.7                        | 8.9  | -3.6      | 46.4  |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 006                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 15.8                  | 20.4 | -0.2      | 60.8  |

Test Program: SID IIs Abdomen Impact Test  
 ATD Serial No.: 307


Test Date: 1/31/14  
 Test I.D.: 307ABD063




| Tested Parameter                    | Units   | Specification | Result | Pass/Fail |
|-------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                     | Minutes | ≥180          | 760    | Pass      |
| Temperature During Soak             | Max     | 20.6 to 22.2  | 21.2   | Pass      |
|                                     | Min     |               | 21.2   | Pass      |
| Humidity During Soak                | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                     | Min     |               | 16.9   | Pass      |
| Laboratory Temperature During Test  | °C      | 18.9 to 25.6  | 21.2   | Pass      |
| Laboratory Humidity During Test     | %       | 10.0 to 70.0  | 17.0   | Pass      |
| Impactor Velocity                   | m/s     | 4.2 to 4.4    | 4.33   | Pass      |
| Peak Upper Abdominal Rib Deflection | mm      | 36 to 47      | 37.8   | Pass      |
| Peak Lower Abdominal Rib Deflection | mm      | 33 to 44      | 34.0   | Pass      |
| Peak Lower Spine Y Acceleration     | G's     | 9 to 14       | 12.0   | Pass      |
| Peak Impactor Acceleration          | G's     | 12 to 16      | 15.1   | Pass      |
| Overall Test Results                |         |               | Pass   |           |



| Curve Description              |      |           |       |
|--------------------------------|------|-----------|-------|
| Upper Abdominal Rib Deflection |      |           |       |
| Plot No.                       | Type | SAE Class | Units |
| 001                            | FIL  | 600       | MM    |
| Max                            | Time | Min       | Time  |
| 37.8                           | 24.3 | 0.0       | -7.4  |
| Curve Description              |      |           |       |
| Lower Abdominal Rib Deflection |      |           |       |
| Plot No.                       | Type | SAE Class | Units |
| 002                            | FIL  | 600       | MM    |
| Max                            | Time | Min       | Time  |
| 34.0                           | 23.4 | 0.0       | -4.0  |



| Curve Description          |      |           |       |
|----------------------------|------|-----------|-------|
| Lower Spine Y Acceleration |      |           |       |
| Plot No.                   | Type | SAE Class | Units |
| 003                        | FIL  | 180       | G's   |
| Max                        | Time | Min       | Time  |
| 12.0                       | 13.5 | -3.8      | 40.2  |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 004                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 15.1                  | 18.7 | -0.2      | 83.8  |

Resultant Data - SIDIIs Plug Compression

1980.0

1700.0

1500.0

1300.0

1100.0

900.0

700.0

500.0

300.0

100.0

-90.0

-0.500

0.000

0.500

1.000

1.500

2.000

2.500

3.000

3.500

Displacement(mm)

M20145504 POST-TEST

Loading Curve

Boundary Limit Upper

Boundary Limit Lower

Peak Load Upper

Peak Load Lower

Peak Defl Upper

Peak Defl Lower

ATD Calibration Lab

Test ID

Part Serial Number

Test Date

Test Time

48956

12/6/2011

8:49 PM

Cert ID

ATD Serial Number

ATD Type

N/A

SIDIIs

Current Date : 12/6/2011


Current Time : 20:50:14

Test Program: SID IIs Pelvis Acetabulum Impact Test  
 ATD Serial No.: 307


Test Date: 1/31/14  
 Test I.D.: 307ACET063




| Tested Parameter                         | Units   | Specification | Result | Pass/Fail |
|------------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                          | Minutes | ≥180          | 805    | Pass      |
| Temperature During Soak                  | Max     | 20.6 to 22.2  | 21.2   | Pass      |
|                                          | Min     |               | 21.2   | Pass      |
| Humidity During Soak                     | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                          | Min     |               | 16.9   | Pass      |
| Laboratory Temperature During Test       | °C      | 18.9 to 25.6  | 21.2   | Pass      |
| Laboratory Humidity During Test          | %       | 10.0 to 70.0  | 17.0   | Pass      |
| Impactor Velocity                        | m/s     | 6.6 to 6.8    | 6.75   | Pass      |
| Peak Acetabulum Force Y                  | Newtons | 3600 to 4300  | 3943.2 | Pass      |
| Peak Pelvis Y Acceleration After 6 msec. | G's     | 34 to 42      | 35.9   | Pass      |
| Peak Impactor Acceleration               | G's     | 38 to 47      | 45.3   | Pass      |
| Overall Test Results                     |         |               | Pass   |           |



| Curve Description       |      |           |         |
|-------------------------|------|-----------|---------|
| Pelvis Acetabulum Force |      |           |         |
| Plot No.                | Type | SAE Class | Units   |
| 001                     | FIL  | 600       | Newtons |
| Max                     | Time | Min       | Time    |
| 3943.2                  | 7.9  | -48.0     | 0.3     |



| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Pelvis Y Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 002                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 38.4                  | 1.9  | -10.9     | 23.8  |




| Curve Description     |      |           |       |
|-----------------------|------|-----------|-------|
| Impactor Acceleration |      |           |       |
| Plot No.              | Type | SAE Class | Units |
| 003                   | FIL  | 180       | G's   |
| Max                   | Time | Min       | Time  |
| 45.3                  | 8.5  | -0.4      | -0.7  |

Test Program: SID IIs Pelvis Iliac Calibration  
 ATD Serial No.: 307

Test Date: 1/31/14  
 Test I.D.: 307PL063




| Tested Parameter                   | Units   | Specification | Result | Pass/Fail |
|------------------------------------|---------|---------------|--------|-----------|
| Dummy Soak Time                    | Minutes | ≥180          | 875    | Pass      |
| Temperature During Soak            | Max     | 20.6 to 22.2  | 21.2   | Pass      |
|                                    | Min     |               | 21.2   | Pass      |
| Humidity During Soak               | Max     | 10.0 to 70.0  | 17.1   | Pass      |
|                                    | Min     |               | 16.9   | Pass      |
| Laboratory Temperature During Test | °C      | 18.9 to 25.6  | 21.2   | Pass      |
| Laboratory Humidity During Test    | %       | 10.0 to 70.0  | 17.0   | Pass      |
| Impactor Velocity                  | m/s     | 4.2 to 4.4    | 4.32   | Pass      |
| Peak Iliac Force                   | Newtons | 4100 to 5100  | 4229.5 | Pass      |
| Peak Pelvis Y Acceleration         | G's     | 28 to 39      | 30.6   | Pass      |
| Peak Impactor Acceleration         | G's     | 36 to 45      | 40.8   | Pass      |
| Overall Test Results               |         |               | Pass   |           |



#### Curve Description

##### Pelvis Iliac Force


| Plot No. | Type | SAE Class | Units   |
|----------|------|-----------|---------|
| 001      | FIL  | 600       | Newtons |
| Max      | Time | Min       | Time    |
| 4229.5   | 10.3 | -1.4      | -13.3   |



#### Curve Description

##### Pelvis Y Acceleration

| Plot No. | Type | SAE Class | Units |
|----------|------|-----------|-------|
| 002      | FIL  | 180       | G's   |
| Max      | Time | Min       | Time  |
| 30.6     | 10.2 | -1.9      | 15.8  |



#### Curve Description

##### Impactor Acceleration

| Plot No. | Type | SAE Class | Units |
|----------|------|-----------|-------|
| 003      | FIL  | 180       | G's   |
| Max      | Time | Min       | Time  |
| 40.8     | 10.3 | -0.1      | 45.2  |

**APPENDIX D**  
**TEST EQUIPMENT AND INSTRUMENTATION CALIBRATION DATA**

**APPENDIX D**  
**TEST EQUIPMENT AND INSTRUMENTATION CALIBRATION DATA**

**TABLE 1 – Dummy Instrumentation (ES-2re)**

|                                        |           |   | ES-2re S/N F037 |              |             |
|----------------------------------------|-----------|---|-----------------|--------------|-------------|
|                                        |           |   | Serial Number   | Manufacturer | Calibration |
| Head Accelerometers                    | Primary   | X | P58858          | Endevco      | 10/9/13     |
|                                        |           | Y | P58865          | Endevco      | 10/9/13     |
|                                        |           | Z | P58867          | Endevco      | 10/9/13     |
|                                        | Redundant | X | P58859          | Endevco      | 10/9/13     |
|                                        |           | Y | P58866          | Endevco      | 10/9/13     |
|                                        |           | Z | P58873          | Endevco      | 10/9/13     |
| Thorax Rib Displacement Potentiometers | Upper     | Y | 209             | FTSS         | 10/9/13     |
|                                        | Middle    | Y | 210             | FTSS         | 10/9/13     |
|                                        | Lower     | Y | 207             | FTSS         | 10/9/13     |
| Abdomen Load Cells                     | Forward   | Y | 1504            | Denton       | 5/9/13      |
|                                        | Middle    | Y | 1505            | Denton       | 5/9/13      |
|                                        | Rear      | Y | 1506            | Denton       | 5/9/13      |
| Lower Spine Accelerometers (T12)       |           | X | P16336          | Endevco      | 10/9/13     |
|                                        |           | Y | P58876          | Endevco      | 10/9/13     |
|                                        |           | Z | P58877          | Endevco      | 10/9/13     |
| Pubic Symphysis Load Cell              |           | Y | DG6834          | Denton       | 5/9/13      |

**TABLE 2 – Dummy Instrumentation (SID-IIs)**

|                                  |               |           |   | SID-IIs S/N 307 |              |             |
|----------------------------------|---------------|-----------|---|-----------------|--------------|-------------|
|                                  |               |           |   | Serial Number   | Manufacturer | Calibration |
| Head Accelerometers              |               | Primary   | X | P58900          | Endevco      | 8/27/13     |
|                                  |               |           | Y | P58902          | Endevco      | 8/27/13     |
|                                  |               |           | Z | P58983          | Endevco      | 8/27/13     |
|                                  |               | Redundant | X | P58901          | Endevco      | 8/27/13     |
|                                  |               |           | Y | P58906          | Endevco      | 8/27/13     |
|                                  |               |           | Z | P58989          | Endevco      | 8/27/13     |
| Displacement Potentiometers      | Thoracic Rib  | Upper     | Y | 1249            | FTSS         | 8/28/13     |
|                                  |               | Middle    | Y | 1265            | FTSS         | 8/28/13     |
|                                  |               | Lower     | Y | 1277            | FTSS         | 8/28/13     |
|                                  | Abdominal Rib | Upper     | Y | 1286            | FTSS         | 8/28/13     |
|                                  |               | Lower     | Y | 1290            | FTSS         | 8/28/13     |
| Lower Spine Accelerometers (T12) |               |           | X | P59007          | Endevco      | 8/28/13     |
|                                  |               |           | Y | P59015          | Endevco      | 8/28/13     |
|                                  |               |           | Z | P58995          | Endevco      | 8/28/13     |
| Acetabulum Load Cell             |               |           | Y | 277             | Denton       | 4/19/13     |
| Iliac Wing Load Cell             |               |           | Y | 289             | Denton       | 4/19/13     |
| Pelvis Plug (Struck Side)        |               |           |   | 46574           | FTSS         | 9/26/11     |
| Pelvis Plug (Non-Struck Side)    |               |           |   | 49032           | FTSS         | 12/7/11     |

**TABLE 3 – Vehicle Instrumentation**

| Vehicle Instrumentation |                             |   | Serial Number | Manufacturer | Calibration Date |
|-------------------------|-----------------------------|---|---------------|--------------|------------------|
| 1                       | Vehicle Center of Gravity   | X | Keva202x      | ICSensor     | 7/2/13           |
|                         | Vehicle Center of Gravity   | Y | Keva202y      | ICSensor     | 7/2/13           |
|                         | Vehicle Center of Gravity   | Z | Keva202z      | ICSensor     | 7/1/13           |
| 2                       | Right Sill at Front Seat    | X | 13735         | Endevco      | 10/22/13         |
|                         | Right Sill at Front Seat    | Y | 12499         | Endevco      | 10/28/13         |
|                         | Right Sill at Front Seat    | Z | 13657         | Endevco      | 5/7/13           |
| 3                       | Right Sill at Rear Seat     | X | 12489         | Endevco      | 6/25/13          |
|                         | Right Sill at Rear Seat     | Y | 13322         | Endevco      | 6/25/13          |
|                         | Right Sill at Rear Seat     | Z | 13501         | Endevco      | 6/26/13          |
| 4                       | Left Sill at Front Door     | Y | 12493         | Endevco      | 7/1/13           |
| 5                       | Left Sill at Rear Door      | Y | 13375         | Endevco      | 6/25/13          |
| 6                       | Left A-Post Lower           | Y | 13723         | Endevco      | 6/18/13          |
| 7                       | Left A-Post Middle          | Y | 13496         | Endevco      | 11/15/13         |
| 8                       | Left B-Post Lower           | Y | 13649         | Endevco      | 11/4/13          |
| 9                       | Left B-Post Middle          | Y | 13468         | Endevco      | 6/26/13          |
| 10                      | Front Seat Track            | Y | 13479         | Endevco      | 6/19/13          |
| 11                      | Rear Seat Structure         | Y | N/A           | N/A          | N/A              |
| 12                      | Right Rear Occ. Compartment | Y | 13742         | Endevco      | 10/22/13         |
| 13                      | Engine Block                | X | 13697         | Endevco      | 12/6/13          |
|                         | Engine Block                | Y | 13696         | Endevco      | 12/6/13          |
| 14                      | Rear Floorpan Above Axle    | X | 13660         | Endevco      | 6/18/13          |
|                         | Rear Floorpan Above Axle    | Y | 13381         | Endevco      | 6/25/13          |
|                         | Rear Floorpan Above Axle    | Z | 13463         | Endevco      | 6/18/13          |

**TABLE 4 – MDB Instrumentation**

|                                    |   | Serial Number | Manufacturer | Calibration Date |
|------------------------------------|---|---------------|--------------|------------------|
| MDB Center of Gravity              | X | 13682         | Endevco      | 6/24/13          |
| MDB Center of Gravity              | Y | 13706         | Endevco      | 6/24/13          |
| MDB Center of Gravity              | Z | 13715         | Endevco      | 6/24/13          |
| Left Frame at Rear Axle Centerline | X | 13705         | Endevco      | 6/24/13          |
| Left Frame at Rear Axle Centerline | Y | 13711         | Endevco      | 6/24/13          |