

REPORT NUMBER: 305-MGA-2011-001

**SAFETY COMPLIANCE TESTING FOR FMVSS 305
Electric Powered Vehicles: Electrolyte Spillage and Electrical Shock Protection**

**HONDA MOTOR CO., LTD
2011 HONDA CR-Z 3-DR HATCHBACK
NHTSA NUMBER: CB5302**

**PREPARED BY:
MGA RESEARCH CORPORATION
5000 WARREN ROAD
BURLINGTON, WI 53105**



Test Date: March 23, 2011

Report Date: March 28, 2011

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
1200 NEW JERSEY AVENUE, SE
WEST BUILDING (NVS-220)
WASHINGTON, DC 20590**

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: 
Donna Janovicz, Project Manager

Approved by: 
Joe Fleck, Project Engineer

Approval Date: March 28, 2011

FINAL REPORT ACCEPTANCE BY OVSC:

Accepted by: Edward E. Chan  Digitally signed by Edward E. Chan
DN: cn=Edward E. Chan, o=National Highway Traffic Safety
Administration, ou=Office of Vehicle Safety Compliance,
email=ed.chan@dot.gov, c=US
Date: 2011.03.31 14:14:46 -04'00'

Acceptance Date: _____

Technical Report Documentation Page

1. Report No. 305-MGA-2011-001		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle Final Report of FMVSS 305 Compliance Testing of 2011 Honda CR-Z 3-Dr Hatchback; NHTSA No.: CB5302				5. Report Date March 28, 2011	
				6. Performing Organization Code MGA	
7. Author(s) Donna Janovicz, Project Manager Joe Fleck, Project Engineer				8. Performing Organization Report No. 305-MGA-2011-001	
9. Performing Organization Name and Address MGA Research Corporation 5000 Warren Road Burlington, WI 53105				10. Work Unit No.	
				11. Contract or Grant No. DTNH22-07-D-00062	
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Vehicle Safety Compliance (NVS-220) 1200 New Jersey Ave, SE Washington, DC 20590				13. Type of Report and Period Covered: Final Test Report 3/23/2011 to 3/28/2011	
				14. Sponsoring Agency Code NVS-220	
15. Supplementary Notes					
16. Abstract A post-test evaluation on the subject 2011 Honda CR-Z 3-Dr Hatchback in accordance with the specifications of the Office of Vehicle Safety Compliance Test Procedure No. TP-305-01 was performed.					
17. Key Words Compliance Testing Safety Engineering FMVSS 305				18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Administration Technical Information Services (TIS) Room E12-100 East Building 1200 New Jersey Ave. Washington, D.C. 20590 e-mail: tis@nhtsa.dot.gov Fax: 202-493-2833	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 22	22. Price		

TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1	Purpose of Compliance Test	1
2	Data Sheets	2
<u>Data Sheet</u>		<u>Page No.</u>
1	Test Vehicle Information and Options	3
2	General Test and Vehicle Parameter Data	4
3	Pre-Impact Electric Isolation Measurements and Calculations	6
4	Post-Impact Data	8
5	Static Rollover Test Data	10
<u>Appendix</u>		
A	Photographs	A-1

SECTION 1

PURPOSE OF COMPLIANCE TEST

This hybrid vehicle, a 2011 Honda CR-Z 3-Dr Hatchback (NHTSA No. CB5302), in conjunction with the FMVSS 214P impact, was tested to FMVSS 305.

The test was performed in accordance with the specifications of the Office of Vehicle Safety Compliance (OVSC) Test Procedure TF-305-01 to determine compliance to the requirements of Federal Motor Vehicle Safety Standard (FMVSS) 305, "Electric Powered Vehicles: Electrolyte Spillage and Electrical Shock Protection".

Based on the test results, the 2011 Honda CR-Z 3-Dr Hatchback appears to meet the post-test requirements of FMVSS 305 testing.

This program is sponsored by the National Highway Traffic Safety Administration (NHTSA), under Contract No. DTNH22-07-D-00062.

The following data sheets document the results of the FMVSS 305 test.

TEST NOTES

The manufacturer's details for FMVSS 305 were not received until after the impact test. All documentation was performed after the post-test roll.

MGA does not endorse or certify products. The manufacturer's name appears solely for identification purposes.

SECTION 2
DATA SHEETS

DATA SHEET NO. 1
TEST VEHICLE SPECIFICATIONS

Test Vehicle: 2011 Honda CR-Z 3-Dr Hatchback

NHTSA No. CB5302

TEST VEHICLE INFORMATION

Year/Make/Model/Body Style	2011 Honda CR-Z 3-Dr Hatchback
NHTSA No.	CB5302
Color	North Shore Blue
Date Received	3/03/2011
Odometer Reading	44 miles
Selling Dealer	Rosen Honda

DATA FROM CERTIFICATION LABEL

Manufactured By	Honda Motor Co., Ltd.	GVWR (kg)	1435
Date of Manufacture	09/'10	GAWR Front (kg)	815
VIN:	JHMZF1D44BS005488	GAWR Rear (kg)	625

DATA FROM VEHICLE'S TIRE PLACARD & SIDEWALL

Measured Parameter	Front	Rear
Location of Placard of Vehicle	Left Side B-Post	
Recommended Tire Size	P195/55R16	P195/55R16
Recommended Cold Tire Pressure	210 kPa	210 kPa
Size of Tires on Test Vehicle	P195/55R16	P195/55R16
Type of Spare Tire	T135/80D15	

VEHICLE CAPACITY DATA

Measured Parameter	Front	Rear	Third	Total
Type of Front Seats	Bucket			
Number of Occupants	2			2
Capacity Weight (VCW) (kg)				181
Number of Occupants x 68 kg				136
Cargo Weight (RCLW) (kg)				45

ELECTRIC VEHICLE PROPULSION SYSTEM

Type of Electric Vehicle (Electric/Hybrid):	Gas-Electric Hybrid
Propulsion Battery Type:	Ni-MH
Nominal Voltage (V):	100.8 V
Physical Location of Automatic Propulsion Battery Disconnect:	IPU (Intelligent power unit) is located in cargo area.
Auxiliary Battery Type:	Lead-Acid

DATA SHEET 2
PRE-TEST DATA

Test Vehicle: 2011 Honda CR-Z 3-Dr Hatchback

NHTSA No. CB5302

CALCULATION OF TARGET TEST WEIGHT (TTW)

Measured Parameter	Units	Value
Unloaded Vehicle Weight (UVW)	kg	1213.8
Rated Cargo & Luggage Weight (RCLW)	kg	45
Weight of 1 P572U ATD (ES-2re) Dummy	kg	77.1
TARGET TEST WEIGHT	kg	1335.9

Note: The target weight is calculated including tolerances as specified in each vehicle crash test procedure.

TEST VEHICLE WEIGHTS

	Units	As Delivered			Fully Loaded			As Tested		
		Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total
Left	kg	366.1	253.1		394.2	303.4		395.5	299.8	
Right	kg	358.3	236.3		368.8	269.9		364.7	269.9	
Ratio	%	59.7	40.3		57.1	42.9		57.2	42.8	
Totals	kg	724.4	489.4	1213.8	763.0	573.3	1336.3	760.2	569.7	1329.9

TIRE PRESSURES

	Units	LF	RF	RR	LR
As Delivered	kPa	210	210	210	210
As Tested	kPa	210	210	210	210

PROPULSION BATTERY SYSTEM DATA (COTR SUPPLIED DATA)

Electrolyte Fluid Type:	KOH	
Electrolyte Fluid Specific Gravity:	1.29 g/cm ²	
Electrolyte Kinematic Viscosity (centistokes):	1.8 mPa·s	
Electrolyte Fluid Color:	Clear	
Propulsion Battery Coolant Type, Color, Specific Gravity (if applicable):	Air	
Location of Battery Modules:		Inside Passenger Compartment
	X	Outside Passenger Compartment

DATA SHEET 2 (CONTINUED)

PRE-TEST DATA

MEASURE AND RECORD BATTERY STATE OF CHARGE

	Maximum State of Charge recommended by manufacturer:	
	Test Voltage ($\geq 95\%$ of Maximum State of Charge):	
X	Test Voltage (Within Normal Operating Voltage Range):	See note below

Note: Normal operating range is 4 or 5 segments of IMA battery level gauge on the instrument panel.

VEHICLE CHASSIS GROUND POINT(S) LOCATION(S)

Details of Vehicle Chassis Ground Point(s) & Locations(s)	Body ground located on left side of floor extension lead wire. 10 mm bolt.
---	--

PROPULSION BATTERY SYSTEM

Details of Propulsion Battery Components	Connector terminal 31 pin Motor ECU Side. Pin 31: VHB0 Battery (+) Pin 1: VHB8 Battery (-)
--	--

DATA SHEET 3

PRE-IMPACT ELECTRIC ISOLATION MEASUREMENTS & CALCULATIONS

Test Vehicle: 2011 Honda CR-Z 3-Dr Hatchback

NHTSA No. CB5302

VOLTMETER INFORMATION

Make:	
Model:	
Serial Number:	
Internal Impedance Value (M Ω):	
Resolution (V):	
Last Calibration Date:	

PROPULSION BATTERY VOLTAGE

Measurement shall be made with propulsion battery connected to the vehicle propulsion system, and the vehicle in the "ready-to-drive" (Propulsion motor(s) activated) position.

If voltage measurement is not at the voltage or within the normal operating voltage range specified by the manufacturer, the battery must be charged.

Vb (V):	
---------	--

PROPULSION BATTERY TO VEHICLE CHASSIS

Vehicle chassis point(s) determined and supplied to contractor by COTR.

V1 (V):	
V2 (V):	

PROPULSION BATTERY TO VEHICLE CHASSIS ACROSS RESISTOR

The known resistance Ro (in ohms) should be approximately 500 times the normal operating voltage of the vehicle (in volts) per SAE J1766.

Ro (Ω):	157900 Ω
------------------	-----------------

DATA SHEET 3 (CONTINUED)

PRE-IMPACT ELECTRICAL ISOLATION MEASUREMENTS & CALCULATIONS

ELECTRICAL ISOLATION MEASUREMENT

Note: If measured voltage is zero and results in a division by zero, record "Zero Volts". This "zero voltage" condition is considered as being compliant.

V1' (V):	
$R_{i1} = R_o (1 + V_2/V_1) [(V_1 - V_1')/V_1']$	
Ri1 (Ω):	
V2' (V):	
$R_{i2} = R_o (1 + V_1/V_2) [(V_2 - V_2')/V_2']$	
Ri2 (Ω):	
$R_i = \text{The lesser of } R_{i1} \text{ and } R_{i2}$	
Ri Pre-Test (Ω):	
Ri/Vb (Ω/V):	
Minimum Electrical Isolation Value is 500 Ω/V	

Note: Measured 6 minutes 24 seconds before impact.

	Yes	No, Fail
Is the measured Electrical Isolation Value $\geq$ 500 Ω/V ?		

DATA SHEET 4
POST-IMPACT DATA

Test Vehicle: 2011 Honda CR-Z 3-Dr Hatchback

NHTSA No. CB5302

VOLTMETER INFORMATION

Make:	Fluke
Model:	11
Serial Number:	68541895
Internal Impedance Value (MΩ):	> 10 MΩ < 100 pF
Nominal Propulsion Battery Voltage (Vb) (V):	100.8

PROPULSION BATTERY VOLTAGE

NOTE: Record V1, V2, V1', V2' voltage measurements after post-test roll.

V1 =	1.5	V
V2 =	1.4	V
V1' =	0.2	V
V2' =	0.6	V

ELECTRICAL ISOLATION MEASUREMENT

Note: If measured voltage is zero and results in a division by zero, record "Zero Volts". This "zero voltage" condition is considered as being compliant.

$R_{i1} = R_o (1 + V_2/V_1) [(V_1 - V_1')/V_1']$		
Ri1 =	1984 K	Ω
$R_{i2} = R_o (1 + V_1/V_2) [(V_2 - V_2')/V_2']$		
Ri2 =	436 K	Ω
Ri = The lesser of Ri1 and Ri2		
Ri =	436 K	Ω
Ri/Vb = electrical Isolation Value/Nominal Battery Voltage		
Minimum Electrical Value is 500 Ω/V		
Ri/Vb =	3856	Ω/V

	Yes	No, Fail
Is the measured Electrical Isolation Value $\geq$ 500 Ω/V?	X	

DATA SHEET 4 (CONTINUED)

POST-IMPACT DATA

PROPULSION BATTERY SYSTEM COMPONENTS

Describe Propulsion Battery Module movement within the passenger compartment [Supply photographs as appropriate]:
No Movement

	Yes	No
Has the Propulsion Battery Module moved within the passenger compartment?		X

Describe intrusion of an outside Propulsion Battery Component into the passenger compartment [Supply photographs as appropriate]:
Not Applicable


	Yes	No
Has an outside Propulsion Battery Component intruded into the passenger compartment?		X

	Yes	No
Is propulsion battery electrolyte spillage visible in the passenger compartment?		X


DATA SHEET 5
STATIC ROLLOVER TEST DATA

Test Vehicle: 2011 Honda CR-Z 3-Dr Hatchback


NHTSA No. CB5302




0/360



90



180



270

REAR VIEW

DETERMINATION OF PROPULSION BATTERY ELECTROLYTE COLLECTION TIME PERIOD

Rollover Stage	Rotation Time (spec. 1-3 min)				FMVSS 301 Hold Time		Total Time				Next Whole Minute Interval	
0° - 90°	2	minutes	02	seconds	5	minutes	7	minutes	02	seconds	8	minutes
90° - 180°	2	minutes	00	seconds	5	minutes	7	minutes	00	seconds	8	minutes
180° - 270°	1	minutes	44	seconds	5	minutes	6	minutes	44	seconds	7	minutes
270° - 360°	1	minutes	56	seconds	5	minutes	6	minutes	56	seconds	7	minutes

ACTUFMVSS 305 ELECTROLYTE SPILLAGE LOCATION TABLE

Rollover Stage	Propulsion Battery Electrolyte Spillage (L)	Spillage Location
0° to 90°	0	
90° to 180°	0	
180° to 270°	0	
270° to 360°	0	

Total Spillage: 0 L

	Yes	No
Is the total spillage of propulsion battery electrolyte greater than 5.0 Liters?		X
Is propulsion battery electrolyte spillage visible in the passenger compartment?		X

APPENDIX A
PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

		<u>Page No.</u>
Photo No. 1.	As Delivered Right Front $\frac{3}{4}$ View of Test Vehicle	A-1
Photo No. 2.	As Delivered Left Rear $\frac{3}{4}$ View of Test Vehicle	A-1
Photo No. 3.	Vehicle's Certification Label	A-2
Photo No. 4.	Vehicle's Tire Information Placard or Label	A-2
Photo No. 5.	Post-Test View of Propulsion Battery	A-3
Photo No. 6.	Post-Test View of Electric Propulsion Drive	A-3
Photo No. 7.	Post-Test View of Vehicle's Passenger Compartment Adjacent to Propulsion Battery	A-4
Photo No. 8.	Labels and Markings	A-4
Photo No. 9.	Labels and Markings	A-5
Photo No. 10.	Labels and Markings	A-5
Photo No. 11.	Ground Location/Close-up of Leads Attached	A-6



As Delivered Right Front $\frac{3}{4}$ View of Test Vehicle



As Delivered Left Rear $\frac{3}{4}$ View of Test Vehicle

MFD. IN JAPAN BY HONDA MOTOR CO., LTD; 09/'10
GVWR 3164LBS GAWR F 1797LBS R 1378LBS
GVWR 1435KG GAWR F 815 KG R 625 KG
THIS VEHICLE CONFORMS TO ALL APPLICABLE
FEDERAL MOTOR VEHICLE SAFETY, BUMPER,
AND THEFT PREVENTION STANDARDS IN EFFECT
ON THE DATE OF MANUFACTURE SHOWN ABOVE.
V.I.N.: JHMZF1D44BS005488 TYPE: PASSENGER CAR



SZT B AA5 - BG57P - A - S

Vehicle's Certification Label



TIRE AND LOADING INFORMATION

SEATING CAPACITY : TOTAL 2 : FRONT 2 : REAR 0

The combined weight of occupants and cargo should never exceed 181kg or 400lbs.

TIRE	SIZE	COLD TIRE PRESSURE
FRONT	P195/55R16 86V	210KPA, 30PSI
REAR		210KPA, 30PSI
SPARE	T135/80D15 99M	420KPA, 60PSI

SEE OWNER'S
MANUAL FOR
ADDITIONAL
INFORMATION

XA

Vehicle's Tire Information Placard or Label



Post-Test View of Propulsion Battery



Post-Test View of Electric Propulsion Drive



Post-Test View of Vehicle's Passenger Compartment Adjacent to Propulsion Battery



Labels and Markings



Labels and Markings



Labels and Markings



Ground Location/Close-up of Leads Attached