REPORT NUMBER: NCAP-CAL-24-007

NEW CAR ASSESSMENT PROGRAM (NCAP)
FRONTAL BARRIER IMPACT TEST

General Motors LLC
2024 Chevrolet Traverse
5 Door SUV

NHTSA No: M20240106

PREPARED BY:
CALSPAN CORPORATION
P.O. BOX 400
BUFFALO, NEW YORK 14225

January 7, 2025

FINAL REPORT

PREPARED FOR:
U. S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
OFFICE OF CRASHWORTHINESS STANDARDS
1200 NEW JERSEY AVE SE
WASHINGTON, D.C. 20590

This final test report was prepared for the U.S. Department of Transportation, National Highway Safety Traffic Administration, in response to Contract Number 693JJ919D000005.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof.

If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: Alexander Rudniski Date: January 7, 2025
Alexander Rudniski, Test Engineer

Approved by: Vanessa Hansen Date: January 7, 2025
Vanessa Hansen, Operations Manager

FINAL REPORT ACCEPTANCE BY OCWS:

_____
Division Chief, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

_____
COTR, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

TECHNICAL REPORT DOCUMENTATION PAGE

1. *Report No.* NCAP-CAL-24-007	***2. Government Accession No.***	***3. Recipient's Catalog No.***
4. Title and Subtitle Final Report of New Car Assessment Program Frontal Impact Testing of a 2024 Chevrolet Traverse 5 Door SUV NHTSA No.: M20240106		***5. Report Date*** January 7, 2025 ***6. Performing Organization Code*** CAL
7. Author(s) Alexander Rudniski, Test Engineer Vanessa Hansen, Operations Manager		***8. Performing Organization Report No.*** CAL-DOT-2024-007
9. Performing Organization Name and Address Calspan Corporation Transportation Test Operations P.O. Box 400 Buffalo, New York 14225		***10. Work Unit No.*** ***11. Contract or Grant No.*** 693JJ919D000005
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Crashworthiness Standards 1200 New Jersey Ave., SE Washington, D.C. 20590		***13. Type of Report and Period Covered:*** Final Test Report September 18, 2024 - January 7, 2025 ***14. Sponsoring Agency Code*** NRM-100
15. Supplementary Notes		

16. Abstract

A 56.30 km/h (35 mph), NCAP frontal rigid barrier impact test was conducted on a 2024 Chevrolet Traverse 5 Door SUV in accordance with the specifications of the Office of Crashworthiness Standards Laboratory Procedure for NCAP Full Frontal Rigid Barrier Impact Testing. The test was conducted at Calspan Corporation's Transportation Test Operations facility in Buffalo, New York on September 18, 2024.

The impact velocity of the vehicle was 56.33 km/h, and the ambient temperature at the barrier face at the time of impact was 21°C. The target vehicle post-test maximum crush was 378 mm at crush zone 2. The test vehicle's occupant performance data is as follows:

Measurement Description	Units	Driver ATD (Serial No. 065)		Passenger ATD (Serial No. 137)	
		Threshold	Result	Threshold	Result
Head Injury Criteria (HIC15)		700	164.988	700	234.078
Maximum Chest Compression	mm	63	-22.592	52	-18.694
Nij		1	0.201	1	0.359
Neck Tension	N	4170	793.855	2620	706.878
Neck Compression	N	4000	-7.858	2520	-215.168
Left Femur Force	N	10008	-141.867	6805	-710.084
Right Femur Force	N	10008	-56.017	6805	-1184.506

17. Key Words 56.3 km/h (35 mph) Full Frontal Rigid Barrier Impact Test New Car Assessment Program (NCAP)	***18. Distribution Statement*** Copies of this report are available from: National Highway Traffic Safety Administration Technical Information Services Division 1200 New Jersey Ave, SE Washington, DC 20590

19. Security Class. (of this report)	***20. Security Class. (of this page)***	***21. No. of Pages***	***22. Price***
UNCLASSIFIED	UNCLASSIFIED	169	

Form DOT F1700.7 (8-69)

TABLE OF CONTENTS

Section		Page
1	Purpose and Summary of Test	1-1
2	Occupant and Vehicle Information / Data Sheets	2-1

Data Sheet		Page
1	General Test and Vehicle Parameter Data	2-2
2	Seat Adjustment, Fuel System, and Steering Wheel Data	2-6
3	Dummy Longitudinal Clearance Dimensions	2-8
4	Dummy Lateral Clearance Dimensions	2-9
5	Seat Belt Positioning Data	2-10
6	High-Speed Camera Locations and Data	2-11
7	Vehicle Accelerometer Locations	2-13
8	Photographic Reference Target Locations	2-14
9	Load Cell Locations on Fixed Barrier	2-15
10	Test Vehicle Summary of Results	2-16
11	Post-Test Observations	2-17
12	Vehicle Profile Measurements	2-19
13	Accident Investigation Division Data	2-21
14	Vehicle Intrusion Measurements	2-22
15	Summary of FMVSS No.212, 219 (Partial), and 301 Data	2-24
16	FMVSS 301 Static Rollover Results	2-26
17	Dummy/Vehicle Temperature Stabilization Chart	2-27

Appendix		Page
A	Photographs	A-1
B	Vehicle and Dummy Response Data Traces	B-1
C	Dummy Calibration and Performance Verification Data	C-1
D	Test Equipment and Instrumentation Calibration	D-1

SECTION 1

PURPOSE AND SUMMARY OF TEST

PURPOSE

This 56.3 km/h frontal barrier impact test is part of the Vehicle Barrier Impact Testing Program sponsored by the National Highway Traffic Safety Administration (NHTSA) under Contract No. 693JJ919D000005. The purpose of this test was to obtain vehicle crashworthiness and occupant restraint system performance data for consumer information purposes.

The 56.3 km/h frontal barrier impact test was conducted in accordance with the Office of Crashworthiness Standards Laboratory Procedure for NCAP Full Frontal Rigid Barrier Impact Testing, dated May 2018.

SUMMARY

A load cell barrier consisting of 128 load cells was impacted by a 2024 Chevrolet Traverse 5 Door SUV at a velocity of 56.33 km/h. The test was performed at Calspan Corporation's Transportation Test Operations facility in Buffalo, New York on September 18, 2024. Pre- and post-test photographs of the vehicle and dummies to document the test can be found in Appendix A. One real-time camera and 16 high-speed cameras were used to document the frontal barrier impact event. Camera locations and other pertinent camera information can be found in Data Sheet 6 of this report.

One Part 572E, 50th percentile male anthropomorphic test device (ATD), was placed in the driver seating position and one Part 572O 5th percentile female ATD was placed in the right-front passenger seating position according to dummy placement instructions specified in the Laboratory Procedure for NCAP Full Frontal Rigid Barrier Impact Testing. Both ATDs were fully instrumented with head, chest and pelvis tri-axial accelerometers, chest displacement potentiometers, upper neck transducers, femur load cells, and lower leg instrumentation. Seat belt load cells were installed on the driver's and passenger's lap and shoulder belts to measure dummy torso and pelvic section loading. The driver (position 1) ATD (Serial No. 065) and the right-front passenger (position 2) ATD (Serial No. 137) were qualified prior to this test. Certification details, along with instrumentation calibration data, can be found in Appendix C of this report.

The 230 channels of data were recorded on an on-board data acquisition system. Appendix B contains the vehicle, load cell barrier and dummy response data traces.

There was 100 percent windshield retention and no intrusion into the protected zone of the windshield during the event. There was a total of 0.0 grams of Stoddard solvent leakage after the event or during any phase of the static rollover. The maximum static crush of the vehicle was 378 mm and both driver and passenger side doors remained closed during the impact event and were operable after the impact.

The driver's visible contact points were as follows: The driver's head contacted the frontal airbag and the head restraint. The upper torso contacted the frontal airbag.

The passenger's visible contact points were as follows: The passenger's head contacted the frontal airbag, curtain airbag and the head restraint. The upper torso contacted the frontal airbag. Both knees contacted the knee airbag.

The occupant data is summarized below.

ATD Position	HIC_{15}	Nij	Neck Tension (N)	Neck Comp. (N)	3ms Chest Clip (Gs)	Chest Disp. (mm)	Left Femur (N)	Right Femur (N)
Driver (50th)	164.988	0.201	793.855	-7.858	37.169	-22.592	-141.867	-56.017
Passenger (5th)	234.078	0.359	706.878	-215.168	39.967	-18.694	-710.084	-1184.506

GENERAL COMMENTS:

1. P1 (Driver) serial number - 065
2. P2 (Passenger) serial number - 137

Data Anomalies:

- No Questionable Channels

SECTION 2

OCCUPANT AND VEHICLE INFORMATION / DATA SHEETS

This section contains information reporting for the following Data Sheets:

Data Sheet No. 1 – General Test and Vehicle Parameter Data

Data Sheet No. 2 – Seat Adjustment, Fuel System, and Steering Wheel Data

Data Sheet No. 3 – Dummy Longitudinal Clearance Dimensions

Data Sheet No. 4 – Dummy Lateral Clearance Dimensions

Data Sheet No. 5 – Seat Belt Positioning Data

Data Sheet No. 6 – High-Speed Camera Locations and Data

Data Sheet No. 7 – Vehicle Accelerometer Locations

Data Sheet No. 8 – Photographic Reference Target Locations

Data Sheet No. 9 – Load Cell Locations on Fixed Barrier

Data Sheet No. 10 – Test Vehicle Summary of Results

Data Sheet No. 11 – Post-Test Observations

Data Sheet No. 12 – Vehicle Profile Measurements

Data Sheet No. 13 – Accident Investigation Division Data

Data Sheet No. 14 – Vehicle Intrusion Measurements

Data Sheet No. 15 – Summary of FMVSS No.212, 219 (Partial), and 301 Data

Data Sheet No. 16 – FMVSS 301 Static Rollover Results

Data Sheet No. 17 – Dummy/Vehicle Temperature Stabilization Chart

DATA SHEET NO. 1
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

TEST VEHICLE INFORMATION AND OPTIONS

NHTSA No.	M20240106	Traction Control System (TCS)	Yes
Model Year	2024	Power Steering	Yes
Make	Chevrolet	Power Window Auto-Reverse	Yes
Model	Traverse	Driver Frontal Airbag	Yes
Body Style	SUV	Driver Curtain Airbag	Yes
VIN	1GNEVGKS1RJ162720	Driver Head/Torso Airbag	No
Body Color	Mosaic Black Metallic	Driver Torso Airbag	No
Odometer Reading (km /mi)	187	Driver Torso/Pelvis Airbag	Yes
Engine Displacement (L)	2.5	Driver Pelvis Airbag	No
Type / No. Cylinders	I4	Driver Knee Airbag	No
Engine Placement	Transverse	Front Pass. Frontal Airbag	Yes
Transmission Type	Automatic	Front Pass. Curtain Airbag	Yes
Transmission Speeds	8-Speed	Front Pass. Head/Torso Airbag	No
Overdrive	Yes	Front Pass. Torso Airbag	No
Final Drive	All Wheel Drive	Front Pass. Torso/Pelvis Airbag	Yes
Roof Rack	No	Front Pass. Pelvis Airbag	No
Sunroof / T-Top	No	Front Pass. Knee Airbag	No
Running Boards	No	Driver Pretensioner	Yes
Tilt Steering Wheel	Yes	Driver Load Limiter	Yes
Power Seats	Yes	Front Pass. Pretensioner	Yes
Anti-Lock Brakes (ABS)	Yes	Front Pass. Load Limiter	Yes
Automatic Door Locks (ADLs)	Yes	Other – Driver Center Airbag	Yes

Does owner's manual provide instructions to turn off automatic door locks?	No

DATA FROM CERTIFICATION LABEL

Manufactured By	General Motors LLC	GVWR (KG)	2900
Date of Manufacture	04/24	GVWR Front (KG)	1450
		GVWR Rear (KG)	1600

VEHICLE SEATING AND WEIGHT CAPACITY DATA

Measured Parameter	Front	Rear	Third	Total
Type of Seats	Bucket	Bucket	Split Bench	
Number of Occupants	2	2	3	7
Capacity Wt. (VCW) (kg)				761
Cargo Wt. (RCLW) (kg)				136

DATA SHEET NO. 1 … (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

Collect items circled in red, tire manufacturer, and tire name.



VEHICLE TIRE INFORMATION

Measured Parameter	Front	Rear
Maximum Tire Pressure (kPa)	350	350
Cold Pressure (kPa)	240	240
Recommended Tire Size	255/55R20	255/55R20
Tire Size on Vehicle	255/55R20	255/55R20
Tire Manufacturer	Continental	Continental
Tire Model	Cross Contact LX20	Cross Contact LX20
Treadwear	680	680
Traction	A	A
Temperature Grades	A	A
Tire Plies Sidewall	2 Polyester	2 Polyester
Tire Plies Body	2 Polyester, 2 Steel, 1 Polyamide	2 Polyester, 2 Steel, 1 Polyamide
Load Index / Speed Symbol	107H	107H
Tire Material	Rubber	Rubber
DOT Safety Code Left	1A30FBAXX0424	1A30FBAXX0424
DOT Safety Code Right	1A30FBAXX0424	1A30FBAXX0424

DATA SHEET NO. 1 … (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2024 Chevrolet Traverse 5 Door SUV
NHTSA No.: M20240106
Test Program: NCAP Frontal Barrier Impact Test
Test Date: 09/18/2024

TEST VEHICLE WEIGHTS

	Units	As Delivered Weights (UVW)			As Tested Weights (ATW)		
		Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total
Left	kg	612	467		647	562	
Right	kg	598	455		627	566	
Ratio	%	56.8	43.2		53.0	47.0	
Total	kg	1210	922	2132	1274	1128	2402

TARGET TEST WEIGHT CALCULATION

Measured Parameter	Units	Value	
Total Delivered Weight (UVW)	kg	2132	(A)
Weight of 1 P572E ATD & 1 P572O ATD	kg	142	(B)
Rated Cargo / Luggage Weight (RCLW)	kg	136	(C)
Calculated Vehicle Target Weight (TVTW)	kg	2410	(A+B+C)

TEST VEHICLE ATTITUDES AND CG

Condition	Units	LF	RF	LR	RR	CG (aft of front axle)
As Delivered	mm	956	962	988	1000	1327
As Tested	mm	952	956	953	961	1441
Post-Test	mm	980	996	943	965	

GENERAL TEST VEHICLE DATA

Measurement Description	Units	Value
Total Vehicle Wheel Base	mm	3068
Total Vehicle Length at Left Side	mm	5079
Total Vehicle Length at Centerline	mm	5186
Total Vehicle Length at Right Side	mm	5079
Weight of Ballast in Cargo Area	kg	124.7
Weight of Vehicle Components Removed	kg	31
Amount of Stoddard Solvent in Fuel Tank	L	76.35

LIST OF COMPONENTS REMOVED TO MEET TEST WEIGHT:

Trunk carpeting and spare tire.

DATA SHEET NO.1 … (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

TARGET VEHICLE STRUCTURAL MEASUREMENT

No.	Description	Pre-Test
1	Total Length	5186
2	Total Width	1969
3*	Bumper Top Height	603
4*	Bumper Bottom Height	506
5*	Longitudinal Member Top Height	640
6	Distance Between Longitudinal Members	1048
7	Longitudinal Member Width	73
8*	Engine Top Height	1058
9*	Engine Bottom Height	220
10	Engine and Gearbox Width	480
11	Front Bumper-Engine Distance	557
12*	Front Shock Absorber Fixing Height	1050
13*	Bonnet Leading Edge Height	1060
14	Front Shock Absorber Fixing Width	1281
15	Front Bumper – Front Axle Distance	1022
16	Front Axle – A Pillar Distance	528
17	A-Pillar – B-Pillar Distance	1108
18	B-Pillar – Rear Axle Distance	1433
19	B-Pillar – C-Pillar Distance	1065
20*	Roof Sill Bottom Height	1679
21*	Roof Sill Top Height	1739
22*	Floor Sill Bottom Height	446
23*	Floor Sill Top Height	478

*Height Measurements are taken from the ground
Note: All measurements are in millimeters

DATA SHEET NO. 2
SEAT ADJUSTMENT, FUEL SYSTEM, AND STEERING WHEEL DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

NOMINAL DESIGN RIDING POSITION

The driver's seat back was set to the manufacturer's designated angle. The passenger's seat back was positioned in a similar manner as the driver's seat back. Seat back angles are measured at the headrest post bezel using a digital inclinometer.

Seating Position	Degrees
Driver Seat Back Angle	12.8
Passenger Seat Back Angle	20.0



FRONT SEAT ASSEMBLY

SEAT FORE / AFT POSITIONS

The driver's seat was positioned at the mid-point of fore/aft travel at its lowest position. The passenger's seat was positioned at the most forward position of fore/aft travel. Zero is defined as the forward most position.

Seating Position	Total Fore / Aft Travel	Placed in Position #
Driver Seat	316	158
Passenger Seat	260	0

SEAT BELT UPPER ANCHORAGE

The driver's seat belt anchorage was positioned according to the manufacturer's designated positioning for a 50th percentile adult male ATD. The passenger's seat belt anchorage was positioned according to the manufacturer's designated positioning for a 5th percentile adult female ATD. For this test zero is defined as the uppermost position.

Seating Position	Total # of Positions	Placed in Position #
Driver Seat	4 (0-3)	0
Passenger Seat	4 (0-3)	0



DATA SHEET NO. 2 … (CONTINUED)
SEAT ADJUSTMENT, FUEL SYSTEM, AND STEERING WHEEL DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

FUEL TANK CAPACITY

Description	Liters
Usable Capacity of "Standard Tank"	82.1
Usable Capacity of "Optional Tank"	N/A
92%-94% of Usable Capacity	75.5 - 77.2
Actual Amount of Solvent Used	76.35
1/3 of Usable Capacity	27.36

FUEL PUMP

The vehicle is equipped with an electric fuel pump. The fuel filler neck is on the left side of the vehicle. The pump creates positive pressure in the fuel lines, pushing the gasoline to the engine. See form 1 for more information.



VEHICLE FUEL TANK ASSEMBLY

STEERING COLUMN ADJUSTMENT

Steering wheel and column adjustments are made so that the steering wheel hub is at the geometric center of the locus it describes when moved through its full range of motion. For angular measurements, a digital inclinometer was used to measure a plate which was placed across the steering wheel rim. A tape measure was used to measure the telescoping steering wheel travel.



STEERING COLUMN ASSEMBLY

STEERING COLUMN POSITIONS

Description	Degrees	Fore / Aft Position (mm)
Lowermost position No. 1	20.2	
Geometric center position No. 2	22.5	
Uppermost position No. 3	24.7	
Telescoping Steering Wheel Travel		64
Test Position	22.5	32

DATA SHEET NO. 3
DUMMY LONGITUDINAL CLEARANCE DIMENSIONS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024



Left Side View

Code	Measurement Description	Driver (SN: 065)		Passenger (SN: 137)	
		Length (mm)	Angle (°)	Length (mm)	Angle (°)
WA°	Windshield Angle		30.3		
SWA°	Steering Wheel Angle		22.5		
SCA°	Steering Column Angle		67.5		
SA°	Seat Back Angle (on headrest post)		12.8		20.0
HZ	Head to Roof (Z)	284	90	271	90
HH	Head to Header	508	26.2	396	42.6
HW	Head to Windshield	835	0.0	741	0.2
NR	Nose to Rim / Dash	415	8.2	442	37.2
CD	Chest to Dash	625		352	
CS	Chest to Steering Hub	350	4.0		
RA	Rim to Abdomen	215	18.6		
KDL	Left Knee to Dash	184	32.3	92	30.5
KDR	Right Knee to Dash	174	32.4	93	37.7
PA°	Pelvic Angle		24.6		20.4
TA°	Tibia Angle		30.6		45.4
SK	Striker to Knee	575	3.5	693	2.3
ST	Striker to Head	562	83.0	603	64.9
SH	Striker to H-Point	210	23.9	384	10.8

DATA SHEET NO. 4
DUMMY LATERAL CLEARANCE DIMENSIONS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024



Front View

Code	Description	Driver (mm)	Passenger (mm)
AD	Arm to Door	55	100
HD	H-Point to Door	161	195
HR	Head to Side Header	279	303
HS	Head to Side Window	395	404
KK	Knee to Knee	350	214
SHY	Striker to H-Point (Y Direction)	260	310
AA	Ankle to Ankle	380	166

DATA SHEET NO. 5
SEAT BELT POSITIONING DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024



SEAT BELT POSITIONING MEASUREMENTS

Measurement Description	Units	Driver	Passenger
PBU — Top surface of reference to belt upper edge	mm	345	300
PBL — Top surface of reference to belt lower edge	mm	255	208

BELT LENGTH DATA

Measurement Description	Units	Driver	Passenger
Shoulder belt length as measured on ATD	mm	850	962
Lap Belt Length as measured on ATD	mm	520	660
Remainder of belt on reel	mm	830	578
Total belt length for continuous webbing systems	mm	2200	2200

DATA SHEET NO. 6
HIGH-SPEED CAMERA LOCATIONS AND DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

CAMERA POSITIONS FOR FRONTAL IMPACTS



DATA SHEET NO. 6 … (CONTINUED)
HIGH-SPEED CAMERA LOCATIONS AND DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

CAMERA LOCATIONS

No.	Camera View	Location (mm)			Lens (mm)	Speed (fps)
		X	Y	Z		
1	Real-Time Left Overall				Zoom	60
2	Left Overall	-2511	-7778	-1475	24	1000
3	Driver Close-Up	-1819	-6373	-1395	50	1000
4	Left Front Half	-978	-6192	-1523	28	1000
5	Left Angle	-4165	-3886	-2610	50	1000
6	Steering Column	-2011	-7192	-2492	75	1000
7	Right Overall	-2252	7359	-1454	24	1000
8	Passenger Close-Up	-1427	6329	-1544	50	1000
9	Right Front Half	-920	5951	-1517	28	1000
10	Right Angle	-3818	4041	-2586	50	1000
11	Windshield	1221	0	-2915	12.5	1000
12	Driver Windshield	1192	-481	-2113	25	1000
13	Passenger Windshield	1192	481	-2113	25	1000
14	Pit Front	-1103	0	2089	12.5	1000
15	Pit Rear	-3026	0	2071	12.5	1000
16	Onboard Driver Airbag (Optional)				8	1000
17	Onboard Passenger Airbag (Optional)				8	1000

** COORDINATES:* *+X = forward of impact plane*
+Y = right of monorail center
+Z = into ground

DATA SHEET NO. 7
VEHICLE ACCELEROMETER LOCATIONS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024





VEHICLE ACCELEROMETER PRE-TEST LOCATIONS

No.	Accelerometer Location	Measurements (mm)		
		X	Y	Z
1	Left Rear Accelerometer – X Direction	2116	-467	32
2	Right Rear Accelerometer – X Direction	2117	446	31
3	Engine Top X	4403	202	-493
4	Engine Bottom X	4069	53	310
5	Left Rear Accelerometer – Z Direction	2116	-467	32
6	Right Rear Accelerometer – Z Direction	2117	446	31
7	Left Rear Accelerometer – X Direction Redundant	2117	-478	33
8	Right Rear Accelerometer – X Direction Redundant	2109	449	31

Reference Points: *X – Rear Surface of Vehicle (+ forward)*
Y – Vehicle Centerline (+ to right)
Z – Ground Plane (+ down)

DATA SHEET NO. 8
PHOTOGRAPHIC REFERENCE TARGET LOCATIONS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

Item	Value
A	414
B	985
C	3134
D	607
E	1445
F	318
G	1852
H	1413
I	1531
J	1029
K	1025
L	1601
M	1411
N	1597
O	1031
P	1028
Q	1530

All units in millimeters



DATA SHEET NO. 9
LOAD CELL LOCATIONS ON FIXED BARRIER

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024



Figure 1 - Load Cell Locations on a 128-Load Cell Barrier with Plywood Height Extension*
Please note above diagram is not actual representation of load cell barrier used.

DATA SHEET NO. 10
TEST VEHICLE SUMMARY OF RESULTS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

INSTRUMENTATION

Instrumentation	Number of Channels Collected
Driver Dummy Accelerometers	47
Passenger Dummy Accelerometers	47
Vehicle Structure Accelerometers	8
Load Cell Barrier	128
Total	230

CAMERA COVERAGE

Type of Camera	Number Used in this Test
High-Speed Vehicle Onboard	2
High-Speed Offboard	14
Real-Time Panning	1
Total	17

DATA SHEET NO. 11
POST-TEST OBSERVATIONS

Test Vehicle: 2024 Chevrolet Traverse 5 Door SUV
NHTSA No.: M20240106
Test Program: NCAP Frontal Barrier Impact Test
Test Date: 09/18/2024

TEST DUMMY INFORMATION AND CONTACT LOCATIONS

Description	Driver	Passenger
Dummy Type / Serial No.	Hybrid 50th / 065	Hybrid 5th / 137
Head Contact	Frontal Airbag & Headrest	Frontal Airbag, Curtain Airbag & Headrest
Upper Torso Contact	Frontal Airbag	Frontal Airbag
Lower Torso Contact	None	None
Left Knee Contact	None	Glovebox
Right Knee Contact	Knee Bolster	Glovebox

DOOR OPENING AND SEAT TRACK INFORMATION

Description	Driver	Passenger	Other
Locked / Unlocked Doors	Unlocked	Unlocked	
Front Door Opening	Closed & Operational	Closed & Operational	
Rear Door Opening	Closed & Operational	Closed & Operational	
Trunk/Hatch/Tailgate Opening			Closed and Operational
Seat Track Shift (mm)	0	0	
Seat Back Movement from Initial Position	None	None	

POST-TEST STRUCTURAL OBSERVATIONS

Critical Areas of Performance	Observations and Conclusions
Windshield Damage	None
Window Damage	None
Other	None

VEHICLE REBOUND FROM BARRIER

Measured Parameter	Units	Value
Left Side	mm	915
Center	mm	894
Right Side	mm	910
Average	mm	906

DATA SHEET NO. 11 … (CONTINUED)
POST-TEST OBSERVATIONS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

SUPPLEMENTAL RESTRAINT SYSTEM INFORMATION

Restraint Type	Driver		Passenger	
	Installed	Deployed	Installed	Deployed
Front Airbag	Yes	Yes	Yes	Yes
Side Airbag 1 - Curtain	Yes	Yes	Yes	Yes
Side Airbag 2 - Torso/Pelvis	Yes	No	Yes	No
Knee Airbag	No	N/A	No	N/A
Seat Belt Pretensioner	Yes	Yes	Yes	Yes
Seat Belt Load Limiter	Yes	Yes	Yes	Yes
Center Airbag	Yes	Disabled	No	N/A

DATA SHEET NO. 12
VEHICLE PROFILE MEASUREMENTS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024





DATA SHEET NO. 12 … (CONTINUED)
VEHICLE PROFILE MEASUREMENTS

Test Vehicle: 2024 Chevrolet Traverse 5 Door SUV NHTSA No.: M20240106
Test Program: NCAP Frontal Barrier Impact Test Test Date: 09/18/2024

No.	Measurement Description	Pre-Test	Post-Test	Change
1	Total Length of Vehicle at Centerline	5186	4810	-376
2	Rear Surface of Vehicle (RSOV) to Front of Engine	4629	4356	-273
3	RSOV to Firewall	4148	4123	-25
4	RSOV to Upper Leading Edge of Right Door	3626	3629	3
5	RSOV to Upper Leading Edge of Left Door	3626	3627	1
6	RSOV to Lower Leading Edge of Right Door	3586	3588	2
7	RSOV to Lower Leading Edge of Left Door	3581	3581	0
8	RSOV to Upper Trailing Edge of Right Door	2535	2536	1
9	RSOV to Upper Trailing Edge of Left Door	2535	2534	-1
10	RSOV to Lower Trailing Edge of Right Door	2558	2558	0
11	RSOV to Lower Trailing Edge of Left Door	2556	2555	-1
12	RSOV to Bottom of “A” Post of Right Side	3622	3631	9
13	RSOV to Bottom of “A” Post of Left Side	3622	3643	21
14	RSOV to Firewall, Right Side	4149	4145	-4
15	RSOV to Firewall, Left Side	4182	4179	-3
16	RSOV to Steering Column	3170	3247	77
17	Center of Steering Column to “A” Post	309	303	-6
18	Center of Steering Column to Headliner	456	472	16
19	RSOV to Right Side of Front Bumper	5118	4796	-322
20	RSOV to Left Side of Front Bumper	5119	4757	-362
21	Length of Engine Block	435	435	0
RD	RSOV to Right Side of Dash Panel	3353	3355	2
CD	RSOV to Center of Dash Panel	3333	3337	4
LD	RSOV to Left Side of Dash Panel	3353	3353	0

All Dimensions in mm

DATA SHEET NO. 13
ACCIDENT INVESTIGATION DIVISION DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

VEHICLE INFORMATION

VIN:	1GNEVGKS1RJ162720	Wheelbase (mm):	3068
Vehicle Size Category:	MPV	Test Weight (kg):	2402

ACCELEROMETER DATA

Accelerometer Locations:	Please See Data Sheet No. 7
Cal. Procedure / Interval:	Calspan Procedure / 6 month
Integration Algorithm:	Trapezoidal
Linearity:	> 99%
Impact Velocity (km/h):	56.33
Velocity Change (km/h):	67.01
Time of Separation (ms):	114



CRUSH PROFILE

Collision Deformation Classification:	12FDEW2
Midpoint of Damage:	C3
Damage Region Length (mm):	1536
Impact Mode:	Frontal

No.	Measurement Description	Units	Pre-Test	Post-Test	Crush
C1	Crush Zone 1 at Left Side	mm	4965	4658	307
C2	Crush Zone 2 at Left Side	mm	5130	4752	378
C3	Crush Zone 3 at Left Side	mm	5174	4796	378
C4	Crush Zone 4 at Right Side	mm	5173	4819	354
C5	Crush Zone 5 at Right Side	mm	5129	4816	313
C6	Crush Zone 6 at Right Side	mm	4971	4729	242
L	C1 to C6	mm	1470	1536	-66

DATA SHEET NO. 14
VEHICLE INTRUSION MEASUREMENTS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

DOOR OPENING WIDTH

Item	Description	Units	Pre-Test	Post-Test	Change
A	Left Side Upper	mm	974	973	-1
B	Left Side Lower	mm	886	885	-1
D	Right Side Upper	mm	973	974	1
E	Right Side Lower	mm	889	888	-1

WHEELBASE MEASUREMENTS

Item	Description	Units	Pre-Test	Post-Test	Change
C	Left Side Wheelbase	mm	3068	3003	-65
F	Right Side Wheelbase	mm	3068	2997	-71



Left & Right Side Views

DATA SHEET NO.14 … (CONTINUED)
VEHICLE INTRUSION MEASUREMENTS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

DRIVER COMPARTMENT INTRUSION

Item	Description	Units	Pre-Test	Post-Test	Change
AB	Door Opening (Inside Window Jam)	mm	789	792	3
CX	Left Knee Bolster to X	mm	330	334	4
DX	Right Knee Bolster to X	mm	330	334	4
EX	Brake Pedal to X	mm	565	519	-46
FX	Foot Rest to X	mm	561	560	-1
GX	Center of Steering Column Wheel Hub to X	mm	85	164	79

X = Front of Seat Track (Stationary)



DATA SHEET NO. 15
SUMMARY OF FMVSS 212, 219 (PARTIAL), AND 301 DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

Windshield Mounting Details: A trim surrounds the top and side of windshield while a plastic shroud is on the bottom.

The standard requires that the post-test retention measurement be a minimum of 75% of the pre-test total periphery measurement for vehicles not equipped with occupant passive restraints and 50% for each side of the windshield for vehicles which are equipped with occupant passive restraints.

Temperature of windshield molding during test: 21 °C

WINDSHIELD PERIPHERY MEASUREMENTS

Measurement	Pre-Test (mm)	Post-Test (mm)	% Retention
Left Side	2310	2310	100%
Right Side	2310	2310	100%
Total	4620	4620	100%



FRONT VIEW OF WINDSHIELD

Item	Units	Value
A	mm	1360
B	mm	522
C	mm	1480
D	mm	890
E	mm	554
F	mm	395

AREAS OF PROTECTED ZONE FAILURES

A. *Provide coordinates of the area that the protected zone was penetrated more than .25 inches by a vehicle component other than one that is normally in contact with the windshield.*
   - No Penetration

B. *Provide coordinates of the area beneath the protected zone that the inner surface of the windshield was penetrated by a vehicle component.*
   - No Penetration

X	Y

X	Y

DATA SHEET NO. 15 … (CONTINUED)
SUMMARY OF FMVSS 212, 219 (PARTIAL), AND 301 DATA

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024

FMVSS 301 FUEL SYSTEM INTEGRITY POST IMPACT DATA

Temperature at Time of Impact: 21°C Test Time: 11:45 AM

STODDARD SOLVENT SPILLAGE MEASUREMENTS

A. From impact until vehicle motion ceases (Maximum allowable is 1 oz.)	0	oz
B. For the 5-minute period after motion ceases (Maximum allowable is 5 oz.)	0	oz
C. For the following 25 minutes: (Maximum allowable is 1 oz.)	0	oz
D. Spillage:	No Spillage	

DATA SHEET NO. 16
FMVSS 301 STATIC ROLLOVER RESULTS

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024



1. The specified fixture rollover rate for each 90°of rotation is 60 to 180 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. Details of Stoddard Solvent Spillage: No Spillage

SOLVENT COLLECTION TIME TABLE IN SECONDS

Test Phase	Rotation Time	Hold Time	Total Time
0° to 90°	66	300	366
90° to 180°	66	300	366
180° to 270°	66	300	366
270° to 360°	65	300	365

FMVSS 301 SPILLAGE TABLE

Test Phase	First 5 Minutes	Sixth Minute	Seventh Minute	Eighth Minute
0° to 90°	0	0	0	
90° to 180°	0	0	0	
180° to 270°	0	0	0	
270° to 360°	0	0	0	

SOLVENT SPILLAGE LOCATION TABLE

Test Phase	Spillage Location
0° to 90°	None
90° to 180°	None
180° to 270°	None
270° to 360°	None

DATA SHEET NO. 17
DUMMY / VEHICLE TEMPERATURE STABILIZATION CHART

Test Vehicle:	2024 Chevrolet Traverse 5 Door SUV	NHTSA No.:	M20240106
Test Program:	NCAP Frontal Barrier Impact Test	Test Date:	09/18/2024



Temperature and Humidity Stabilization Chart/Data for Dummies and Test Vehicle

APPENDIX A

PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

Fig.	Description	Page
1	Load Cell Location	A-5
2	Pre-Test Load Cell Wall	A-5
3	Post-Test Load Cell Wall	A-6
4	Manufacturer's Label	A-6
5	Tire Placard	A-7
6	2024 Chevrolet Traverse Frontal As Delivered	A-7
7	Left Rear 3-4 View, as Received	A-8
8	Pre-Test Front View of Test Vehicle	A-8
9	Post-Test Front View of Test Vehicle	A-9
10	Pre-Test Left View of Test Vehicle	A-9
11	Post-Test Left View of Test Vehicle	A-10
12	Pre-Test Right View of Test Vehicle	A-10
13	Post-Test Right View of Test Vehicle	A-11
14	Pre-Test Right Front 3-4 View	A-11
15	Post-Test Right Front 3-4 View	A-12
16	Pre-Test Left Rear 3-4 View	A-12
17	Post-Test Left Rear 3-4 View	A-13
18	Pre-Test Windshield View	A-13
19	Post-Test Windshield View	A-14
20	Pre-Test Engine Compartment View	A-14
21	Post-Test Engine Compartment View	A-15
22	Pre-Test Fuel Filler Cap View	A-15
23	Post-Test Fuel Filler Cap View	A-16
24	Pre-Test Front Underbody View[1]	A-16
25	Post-Test Front Underbody View[1]	A-17
26	Pre-Test Rear Underbody View[1]	A-17
27	Post-Test Rear Underbody View[1]	A-18
28	Pre-Test Dummy Cable Routing	A-18
29	Post-Test Dummy Cable Routing	A-19
30	Pre-Test Driver Dummy Front View	A-19
31	Post-Test Driver Dummy Front View	A-20
32	Pre-Test Driver Dummy Window View	A-20
33	Post-Test Driver Dummy Window View	A-21
34	Pre-Test Driver Dummy and Vehicle Interior View	A-21
35	Post-Test Driver Dummy and Vehicle Interior View	A-22

Fig.	Description	Page
36	Pre-Test Driver's Seat Fore-Aft Markings	A-22
37	Post-Test Driver's Seat Fore-Aft Markings	A-23
38	Pre-Test View of Belt Anchorage for Driver Dummy	A-23
39	Post-Test View of Belt Anchorage for Driver Dummy	A-24
40	Pre-Test View of Belt Buckle and Latch Plate for Driver Dummy	A-24
41	Post-Test View of Belt Buckle and Latch Plate for Driver Dummy	A-25
42	Pre-Test Driver Dummy Feet	A-25
43	Post-Test Driver Dummy Feet	A-26
44	Pre-Test Driver's Side Knee Bolster	A-26
45	Post-Test Driver's Side Knee Bolster	A-27
46	Pre-Test Driver's Side Floorpan	A-27
47	Post-Test Driver's Side Floorpan	A-28
48	Post-Test Driver Dummy Face	A-28
49	Post-Test Driver Dummy Contact With Airbag	A-29
50	Post-Test Driver Dummy Contact With Headrest	A-29
51	Pre-Test View of the Steering Wheel	A-30
52	Post-Test View of the Steering Wheel	A-30
53	Pre-Test Passenger Dummy Front View	A-31
54	Post-Test Passenger Dummy Front View	A-31
55	Pre-Test Passenger Dummy Window View	A-32
56	Post-Test Passenger Dummy Window View	A-32
57	Pre-Test Passenger Dummy and Vehicle Interior View	A-33
58	Post-Test Passenger Dummy and Vehicle Interior View	A-33
59	Pre-Test Passenger's Seat Fore-Aft Markings	A-34
60	Post-Test Passenger's Seat Fore-Aft Markings	A-34
61	Pre-Test View of Belt Anchorage for Passenger Dummy	A-35
62	Post-Test View of Belt Anchorage for Passenger Dummy	A-35
63	Pre-Test View of Belt Buckle and Latch Plate for Passenger Dummy	A-36
64	Post-Test View of Belt Buckle and Latch Plate for Passenger Dummy	A-36
65	Pre-Test Passenger Dummy Feet	A-37
66	Post-Test Passenger Dummy Feet	A-37
67	Pre-Test Passenger's Side Knee Bolster	A-38
68	Post-Test Passenger's Side Knee Bolster	A-38
69	Pre-Test Passenger's Side Floorpan	A-39
70	Post-Test Passenger's Side Floorpan	A-39
71	Post-Test Passenger Dummy Face	A-40

Fig.	Description	Page
72	Post-Test Passenger Dummy Contact With Airbag	A-40
73	Post-Test Passenger Dummy Contact With Headrest	A-41
74	Photograph of Ballast Installed in Vehicle	A-41
75	Post-Test Stoddard Solvent Spillage Location View, if Required	A-42
76	Post-Test Speed Trap Read-Out	A-42
77	Vehicle at 0º on Static Rollover Device	A-43
78	Vehicle at 90º on Static Rollover Device	A-43
79	Vehicle at 180º on Static Rollover Device	A-44
80	Vehicle at 270º on Static Rollover Device	A-44
81	Vehicle at 360º on Static Rollover Device	A-45
82	2024 Chevrolet Traverse Frontal Impact Event	A-45
83	Monroney Label Photograph	A-46

[1]**NOTE**: *The underbody views should include the following vehicle components: fuel pump, fuel lines, sender unit, fuel tank filler pipe and any other visible system components.*



Figure A-1: Load Cell Location



Figure A-2: Pre-Test Load Cell Wall



Figure A-3: Post-Test Load Cell Wall



Figure A-4: Manufacturer's Label



Figure A-5: Tire Placard



Figure A-6: 2024 Chevrolet Traverse Frontal As Delivered



Figure A-7: Left Rear 3-4 View, As Received



Figure A-8: Pre-Test Front View of Test Vehicle



Figure A-9: Post-Test Front View of Test Vehicle



Figure A-10: Pre-Test Left View of Test Vehicle



Figure A-11: Post-Test Left View of Test Vehicle



Figure A-12: Pre-Test Right View of Test Vehicle



Figure A-13: Post-Test Right View of Test Vehicle



Figure A-14: Pre-Test Right Front 3-4 View



Figure A-15: Post-Test Right Front 3-4 View



Figure A-16: Pre-Test Left Rear 3-4 View



Figure A-17: Post-Test Left Rear 3-4 View



Figure A-18: Pre-Test Windshield View



Figure A-19: Post-Test Windshield View



Figure A-20: Pre-Test Engine Compartment View



Figure A-21: Post-Test Engine Compartment View



Figure A-22: Pre-Test Fuel Filler Cap View



Figure A-23: Post-Test Fuel Filler Cap View



Figure A-24: Pre-Test Front Underbody View



Figure A-25: Post-Test Front Underbody View



Figure A-26: Pre-Test Rear Underbody View



Figure A-27: Post-Test Rear Underbody View



Figure A-28: Pre-Test Dummy Cable Routing



Figure A-29: Post-Test Dummy Cable Routing



Figure A-30: Pre-Test Driver Dummy Front View



Figure A-31: Post-Test Driver Dummy Front View



Figure A-32: Pre-Test Driver Dummy Window View



Figure A-33: Post-Test Driver Dummy Window View



Figure A-34: Pre-Test Driver Dummy and Vehicle Interior View



Figure A-35: Post-Test Driver Dummy and Vehicle Interior View



Figure A-36: Pre-Test Driver's Seat Fore-Aft Markings



Figure A-37: Post-Test Driver's Seat Fore-Aft Markings



Figure A-38: Pre-Test View of Belt Anchorage for Driver Dummy



Figure A-39: Post-Test View of Belt Anchorage for Driver Dummy



Figure A-40: Pre-Test View of Belt Buckle and Latch Plate for Driver Dummy



Figure A-41: Post-Test View of Belt Buckle and Latch Plate for Driver Dummy



Figure A-42: Pre-Test Driver Dummy Feet



Figure A-43: Post-Test Driver Dummy Feet



Figure A-44: Pre-Test Driver's Side Knee Bolster



Figure A-45: Post-Test Driver's Side Knee Bolster



Figure A-46: Pre-Test Driver's Side Floorpan



Figure A-47: Post-Test Driver's Side Floorpan



Figure A-48: Post-Test Driver Dummy Face



Figure A-49: Post-Test Driver Dummy Contact With Airbag



Figure A-50: Post-Test Driver Dummy Contact With Headrest



Figure A-51: Pre-Test View of the Steering Wheel



Figure A-52: Post-Test View of the Steering Wheel



Figure A-53: Pre-Test Passenger Dummy Front View



Figure A-54: Post-Test Passenger Dummy Front View



Figure A-55: Pre-Test Passenger Dummy Window View



Figure A-56: Post-Test Passenger Dummy Window View



Figure A-57: Pre-Test Passenger Dummy and Vehicle Interior View



Figure A-58: Post-Test Passenger Dummy and Vehicle Interior View



Figure A-59: Pre-Test Passenger's Seat Fore-Aft Markings



Figure A-60: Post-Test Passenger's Seat Fore-Aft Markings



Figure A-61: Pre-Test View of Belt Anchorage for Passenger Dummy



Figure A-62: Post-Test View of Belt Anchorage for Passenger Dummy



Figure A-63: Pre-Test View of Belt Buckle and Latch Plate for Passenger Dummy



Figure A-64: Post-Test View of Belt Buckle and Latch Plate for Passenger Dummy



Figure A-65: Pre-Test Passenger Dummy Feet



Figure A-66: Post-Test Passenger Dummy Feet



Figure A-67: Pre-Test Passenger's Side Knee Bolster



Figure A-68: Post-Test Passenger's Side Knee Bolster



Figure A-69: Pre-Test Passenger's Side Floorpan



Figure A-70: Post-Test Passenger's Side Floorpan



Figure A-71: Post-Test Passenger Dummy Face



Figure A-72: Post-Test Passenger Dummy Contact With Airbag



Figure A-73: Post-Test Passenger Dummy Contact With Headrest



Figure A-74: Photograph of Ballast Installed in Vehicle

Photo Not Applicable

Figure A-75: Post-Test Stoddard Solvent Spillage Location View, If Required



Figure A-76: Post-Test Speed Trap Read-Out



Figure A-77: Vehicle at 0º on Static Rollover Device



Figure A-78: Vehicle at 90º on Static Rollover Device



Figure A-79: Vehicle at 180º on Static Rollover Device



Figure A-80: Vehicle at 270º on Static Rollover Device



Figure A-81: Vehicle at 360º on Static Rollover Device



Figure A-82: 2024 Chevrolet Traverse Frontal Impact Event



Figure A-83: Monroney Label Photograph

APPENDIX B
VEHICLE AND DUMMY RESPONSE DATA TRACES

Table of Data Plots

Fig.	Description	Page
Plot 1	Driver Head X Acceleration vs. Time Primary	B-5
Plot 2	Driver Head Y Acceleration vs. Time Primary	B-5
Plot 3	Driver Head Z Acceleration vs. Time Primary	B-5
Plot 4	Driver Head Resultant Acceleration vs. Time Primary	B-5
Plot 5	Driver Chest X Deflection vs. Time	B-6
Plot 6	Driver Chest X Acceleration vs. Time Primary	B-6
Plot 7	Driver Chest Y Acceleration vs. Time Primary	B-6
Plot 8	Driver Chest Z Acceleration vs. Time Primary	B-6
Plot 9	Driver Chest Resultant Acceleration vs. Time Primary	B-7
Plot 10	Driver Upper Neck Force X vs. Time Primary	B-7
Plot 11	Driver Upper Neck Force Z vs. Time Primary	B-7
Plot 12	Driver Upper Neck Moment Y vs. Time Primary	B-7
Plot 13	Driver Nij vs. Time Primary	B-8
Plot 14	Driver Left Femur Force vs. Time	B-8
Plot 15	Driver Right Femur Force vs. Time	B-8
Plot 16	Passenger Head X Acceleration vs. Time Primary	B-8
Plot 17	Passenger Head Y Acceleration vs. Time Primary	B-9
Plot 18	Passenger Head Z Acceleration vs. Time Primary	B-9
Plot 19	Passenger Head Resultant Acceleration vs. Time Primary	B-9
Plot 20	Passenger Chest X Deflection vs. Time	B-9
Plot 21	Passenger Chest X Acceleration vs. Time Primary	B-10
Plot 22	Passenger Chest Y Acceleration vs. Time Primary	B-10
Plot 23	Passenger Chest Z Acceleration vs. Time Primary	B-10
Plot 24	Passenger Chest Resultant Acceleration vs. Time Primary	B-10
Plot 25	Passenger Upper Neck Force X vs. Time Primary	B-11
Plot 26	Passenger Upper Neck Force Z vs. Time Primary	B-11
Plot 27	Passenger Upper Neck Moment Y vs. Time Primary	B-11
Plot 28	Passenger Nij vs. Time Primary	B-11
Plot 29	Passenger Left Femur Force vs. Time	B-12
Plot 30	Passenger Right Femur Force vs. Time	B-12

The following additional dummy and vehicle response data can be found in the R&D section of the NHTSA website at www.NHTSA.gov

Driver Head X Acceleration Redundan
Driver Head Y Acceleration Redundant
Driver Head Z Acceleration Redundant
Driver Upper Neck Force Y
Driver Upper Neck Moment X
Driver Upper Neck Moment Z
Driver Chest X Acceleration Redundant
Driver Chest Y Acceleration Redundant
Driver Chest Z Acceleration Redundant
Driver Pelvis X
Driver Pelvis Y
Driver Pelvis Z
Driver Left Femur Redundant
Driver Right Femur Redundant
Driver Left Upper Tibia Moment X
Driver Left Upper Tibia Moment Y

Driver Left Upper Tibia Force Z
Driver Left Lower Tibia Moment X
Driver Left Lower Tibia Moment Y
Driver Left Lower Tibia Force Z
Driver Right Upper Tibia Moment X
Driver Right Upper Tibia Moment Y
Driver Right Upper Tibia Force Z
Driver Right Lower Tibia Moment X
Driver Right Lower Tibia Moment Y
Driver Right Lower Tibia Force Z
Driver Left Foot Fore Z
Driver Left Foot Aft X
Driver Left Foot Aft Z
Driver Right Foot Fore Z
Driver Right Foot Aft X
Driver Right Foot Aft Z
Driver Shoulder Belt Force
Driver Lap Belt Force
Driver Head Angular Velocity X
Driver Head Angular Velocity Y
Driver Head Angular Velocity Z
Passenger Head X Acceleration Redundant
Passenger Head Y Acceleration Redundant
Passenger Head Z Acceleration Redundant
Passenger Upper Neck Force X
Passenger Upper Neck Force Z
Passenger Upper Neck Moment Y
Passenger Chest X Acceleration Redundant
Passenger Chest Y Acceleration Redundant
Passenger Chest Z Acceleration Redundant
Passenger Pelvis X
Passenger Pelvis Y
Passenger Pelvis Z
Passenger Left Femur Redundant
Passenger Right Femur Redundant
Passenger Left Upper Tibia Moment X
Passenger Left Upper Tibia Moment Y
Passenger Left Upper Tibia Force Z
Passenger Left Lower Tibia Moment X
Passenger Left Lower Tibia Moment Y
Passenger Left Lower Tibia Force Z
Passenger Right Upper Tibia Moment X
Passenger Right Upper Tibia Moment Y
Passenger Right Upper Tibia Force Z
Passenger Right Lower Tibia Moment X
Passenger Right Lower Tibia Moment Y
Passenger Right Lower Tibia Force Z
Passenger Left Foot Fore Z
Passenger Left Foot Aft X
Passenger Left Foot Aft Z

Passenger Right Food Fore Z
Passenger Right Foot Aft X
Passenger Right Foot Aft Z
Passenger Shoulder Belt Force
Passenger Lap Belt Force
Passenger Head Angular Velocity X
Passenger Head Angular Velocity Y
Passenger Head Angular Velocity Z
Left Rear Seat Crossmember X
Left Rear Seat Crossmember Z
Right Rear Seat Crossmember X
Right Rear Seat Crossmember Z
Left Rear Seat Crossmember X Redundant
Right Rear Seat Crossmember X Redundant
Vehicle Engine Top X
Vehicle Engine Bottom X
Load Cell Barrier Forces and Moments

Driver Head X Acceleration vs. Time Primary



Driver Head Y Acceleration vs. Time Primary



Driver Head Z Acceleration vs. Time Primary



Driver Head Resultant Acceleration vs. Time Primary



Driver Chest X Deflection vs. Time



Driver Chest X Acceleration vs. Time Primary



Driver Chest Y Acceleration vs. Time Primary



Driver Chest Z Acceleration vs. Time Primary



Driver Chest Resultant Acceleration vs. Time Primary



Driver Upper Neck Force X vs. Time Primary



Driver Upper Neck Force Z vs. Time Primary



Driver Upper Neck Moment Y vs. Time Primary



Driver Nij vs. Time Primary



Driver Left Femur Force vs. Time



Driver Right Femur Force vs. Time



Passenger Head X Acceleration vs. Time Primary



Passenger Head Y Acceleration vs. Time Primary



Passenger Head Z Acceleration vs. Time Primary



Passenger Head Resultant Acceleration vs. Time Primary



Passenger Chest X Deflection vs. Time



Passenger Chest X Acceleration vs. Time Primary



Passenger Chest Y Acceleration vs. Time Primary



Passenger Chest Z Acceleration vs. Time Primary



Passenger Chest Resultant Acceleration vs. Time Primary



Passenger Upper Neck Force X vs. Time Primary



Passenger Upper Neck Force Z vs. Time Primary



Passenger Upper Neck Moment Y vs. Time Primary



Passenger Nij vs. Time Primary




Passenger Left Femur Force vs. Time
FORCE [N]
750
500
250
0
-250
-500
-750
-50
0
50
100
150
200
250
300
Time axis [ms]
Max: 716.09 [N]
TMax: 29.3 [ms]
Min: -710.08 [N]
TMin: 58.1 [ms]
Filter: CFC 600


Passenger Right Femur Force vs. Time
FORCE [N]
1000
500
0
-500
-1000
-1500
-50
0
50
100
150
200
250
300
Time axis [ms]
Max: 825.22 [N]
TMax: 36.85 [ms]
Min: -1184.51 [N]
TMin: 53.7 [ms]
Filter: CFC 600

APPENDIX C

DUMMY CALIBRATION AND PERFORMANCE VERIFICATION DATA

CALIBRATION TEST RESULTS

PRE-TEST

HYBRID III 50TH PERCENTILE MALE - DRIVER ATD

SERIAL NO: 065

External Measurements - Hybrid 3 - 50th Male

Technician: J. Rios Date: 09/12/2024

Dummy Serial Number: 065



Symbol	Description	Specification (in)		Result (in)	Pass/Fail
A	Sitting Height	34.6	35.0	34.8	Pass
B	Shoulder Pivot Height	19.9	20.5	20.2	Pass
C	H-Point Height	3.3	3.5	3.4	Pass
D	H-Point from Backline	5.3	5.5	5.5	Pass
E	Shoulder Pivot from Backline	3.3	3.7	3.6	Pass
F	Thigh Clearance	5.5	6.1	5.9	Pass
G	Back of Elbow to Wrist Pivot	11.4	12.0	11.8	Pass
H	Head Back to Backline	1.6	1.8	1.7	Pass
I	Shoulder to Elbow Length	13.0	13.6	13.3	Pass
J	Elbow Rest Height	7.5	8.3	7.8	Pass
K	Buttock to Knee Length	22.8	23.8	23.4	Pass
L	Popliteal Height	16.9	17.9	17.4	Pass
M	Knee Pivot Height	19.1	19.7	19.3	Pass
N	Buttock Popliteal Length	17.8	18.8	18.3	Pass
O	Chest Depth without Jacket	8.4	9.0	8.7	Pass
P	Foot Length (right)	9.9	10.5	10.2	Pass
V	Shoulder Breadth	16.3	17.2	16.8	Pass
W	Foot Breadth	3.6	4.2	3.8	Pass
Y	Chest Circumference with Jacket	38.2	39.4	39.0	Pass
Z	Waist Circumference	32.9	34.1	33.5	Pass
AA	Reference Location (Chest Circumference)	16.9	17.1	17.0	Pass
BB	Reference Location (Waist Circumference)	8.9	9.1	9.0	Pass

ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.8	Pass
Humidity	10	70	%	48.1	Pass
Resultant Acceleration	225	275	g's	249.4	Pass
Oscillation	0	10	%	4.4	Pass
Lateral Acceleration	-15	15	g's	12.5	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
X Accelerometer	Endevco	P52383	9/9/2024	3/8/2025
Y Accelerometer	Measurement Specialties	A341256	9/9/2024	3/8/2025
Z Accelerometer	Endevco	P71303	9/9/2024	3/8/2025




Head CG X Acceleration
Acceleration (g's)
250
200
150
100
50
0
-50
0
2.5
5
7.5
10
Time [ms]
Max: 221.4 g's
Min: 0.4 g's
Filter: CFC 1000


Head CG Y Acceleration
Acceleration (g's)
15
10
5
0
-5
-10
-15
0
2.5
5
7.5
10
Time [ms]
Max: 12.5 g's
Min: -1.5 g's
Filter: CFC 1000


Head CG Z Acceleration
Acceleration (g's)
25
0
-25
-50
-75
-100
-125
0
2.5
5
7.5
Time [ms]
Max: 1.5 g's
Min: -115.0 g's
Filter: CFC 1000

ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	21.8	Pass
Humidity	10	70	%	48.1	Pass
Velocity	6.89	7.13	m/s	7.016	Pass
Pendulum Deceleration at 10ms	22.5	27.5	g's	25.53	Pass
Pendulum Deceleration at 20ms	17.6	22.6	g's	22.24	Pass
Pendulum Deceleration at 30ms	12.5	18.5	g's	16.93	Pass
Max. Pendulum Deceleration After 30ms	0	29	g's	25.9	Pass
Pendulum Deceleration Time to 5 g's	34	42	ms	38.2	Pass
Maximum D Plane Rotation	64	78	deg	72.0	Pass
Time to Maximum Rotation	57	64	ms	58.1	Pass
Rotation Decay to Zero	113	127	ms	119.9	Pass
Moment About Occipital Condyle	88.1	108.4	Nm	97.19	Pass
Time to Maximum Moment	47	58	ms	50.8	Pass
Moment Decay to Zero	97	107	ms	97.1	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	C16678	8/29/2024	2/25/2025
Pendulum Potentiometer	ETI	1412	12/18/2023	12/17/2024
Condyle Potentiometer	ETI	1911	12/18/2023	12/17/2024
Upper Neck Load Cell	Denton	1629-FX	12/8/2023	12/7/2024


D-Plane Rotation
Rotation (Deg)
100
75
50
25
0
-25
-50
0
25
50
75
100
125
150
Time [ms]
Max: 72.0 deg
Min: -35.8 deg
Filter: CFC 60


Moment About Occipital Condyle
Moment (Nm)
125
100
75
50
25
0
-25
-50
0
25
50
75
100
125
150
Time [ms]
Max: 97.2 Nm
Min: -28.2 Nm
Filter: CFC 600


Pendulum Deceleration
Max: 25.9 g's
Min: -2.8 g's
Filter: CFC 60
Acceleration (g's)
Time [ms]


Upper Neck Y Moment
Max: 84.3 Nm
Min: -39.8 Nm
Filter: CFC 600
Moment (Nm)
Time [ms]


Upper Neck X Force
Max: 91.5 N
Min: -848.5 N
Filter: CFC 600
Force (N)
Time [ms]

ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	21.8	Pass
Humidity	10	70	%	48.1	Pass
Velocity	5.94	6.19	m/s	6.132	Pass
Pendulum Deceleration at 10ms	17.2	21.2	g's	18.83	Pass
Pendulum Deceleration at 20ms	14	19	g's	18.3	Pass
Pendulum Deceleration at 30ms	11	16	g's	14.4	Pass
Max. Pendulum Deceleration After 30ms	0	22	g's	19.1	Pass
Pendulum Deceleration Time to 5 g's	38	46	ms	41.5	Pass
Maximum D Plane Rotation	81	106	deg	99.8	Pass
Time to Maximum Rotation	72	82	ms	76.9	Pass
Rotation Decay to Zero	147	174	ms	169.5	Pass
Minimum Moment About OC	-80	-52.9	Nm	-71.53	Pass
Time to Minimum Moment	65	79	ms	72.5	Pass
Moment Decay to Zero	120	148	ms	123.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	C16678	8/29/2024	2/25/2025
Pendulum Potentiometer	ETI	SP22G_1412	12/18/2023	12/17/2024
Condyle Potentiometer	ETI	SP22G_1911	12/18/2023	12/17/2024
Upper Neck Load Cell	Denton	1629-FX	12/8/2023	12/7/2024


D-Plane Rotation
Rotation (deg)
125
100
75
50
25
0
-25
-50
0
25
50
75
100
125
150
Time [ms]
Max: 99.8 deg
Min: 0.1 deg
Filter: CFC 60


Moment About Occipital Condyle
Moment (Nm)
50
25
0
-25
-50
-75
-100
0
25
50
75
100
125
150
Time [ms]
Max: 21.7 Nm
Min: -71.5 Nm
Filter: CFC 600


Pendulum Deceleration
Max: 19.1 g's
Min: -3.3 g's
Filter: CFC 60
Acceleration (g's)
25
20
15
10
5
0
-5
-10
0
10
20
30
40
50
Time [ms]


Upper Neck Y Moment
Max: 26.6 Nm
Min: -63.0 Nm
Filter: CFC 600
Moment (Nm)
40
20
0
-20
-40
-60
-80
0
25
50
75
100
125
150
Time [ms]


Upper Neck X Force
Max: 552.2 N
Min: -95.9 N
Filter: CFC 600
Force (N)
600
500
400
300
200
100
0
-100
-200
-300
0
25
50
75
100
125
150
Time [ms]

ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	22.1	Pass
Humidity	10	70	%	42.8	Pass
Velocity	6.59	6.83	m/s	6.713	Pass
Chest Displacement	-72.6	-63.5	mm	-67.32	Pass
Resistive Force	5160	5894	N	5815.9	Pass
Hysteresis	69	85	%	71.7	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	T31053	8/21/2023	2/17/2024
Chest Potentiometer	Servo	1046	4/30/2024	10/29/2024




Resistive Force
Force (N)
6000
5000
4000
3000
2000
1000
0
-1000
0
25
50
75
100
Time [ms]
Max: 5815.9 N
Min: -33.1 N
Filter: CFC 180


Sternum Displacement
Displacement (mm)
20
0
-20
-40
-60
-80
0
25
50
75
100
Time [ms]
Max: 0.04 mm
Min: -67.32 mm
Filter: CFC 180


Probe Acceleration
Acceleration (g's)
30
25
20
15
10
5
0
-5
0
25
50
75
100
Time [ms]
Max: 25.4 g's
Min: -0.1 g's
Filter: CFC 180


Change in Velocity (Integrated Acceleration)
Velocity (m/s)
8
7
6
5
4
3
2
1
0
0
25
50
75
100
Time [ms]
Max: 7.1 m/s
Min: 0.0 m/s
Filter: CFC 180

ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.7	Pass
Humidity	10	70	%	44.2	Pass
Average Velocity	5	10	deg/s	7.0	Pass
Angle at 203Nm	40	50	deg	41.0	Pass
Moment at 30 degrees	0	94.9	Nm	82.3	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	Servo 14CB1-3615	3203	11/16/2023	11/15/2024
Load Cell	PCB 2301-02A	111	2023-09-21	2024-09-20



ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.7	Pass
Humidity	10	70	%	44.2	Pass
Average Velocity	5	10	deg/s	6.8	Pass
Angle at 203Nm	40	50	deg	40.1	Pass
Moment at 30 degrees	0	94.9	Nm	86.7	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	Servo 14CB1-3615	3203	11/16/2023	11/15/2024
Load Cell	PCB 2301-02A	111	2023-09-21	2024-09-20



ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.7	Pass
Humidity	10	70	%	44.2	Pass
Velocity	2.07	2.13	m/s	2.115	Pass
Maximum Resistive Force	4720	5780	N	5723.2	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	T29720	6/12/2024	12/9/2024




Pendulum Acceleration
Max: 118.3 g's
Min: -0.5 g's
Filter: CFC 600
Acceleration (g's)
125
100
75
50
25
0
-25
0
2
4
6
8
Time [ms]


Change in Pendulum Velocity (Integrated Acceleration)
Max: 2.8 m/s
Filter: CFC 180
Velocity (m/s)
3
2.5
2
1.5
1
0.5
0
0
2
4
6
8
Time [ms]

ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.7	Pass
Humidity	10	70	%	44.2	Pass
Velocity	2.07	2.13	m/s	2.123	Pass
Maximum Resistive Force	4720	5780	N	5747.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	T29720	6/12/2024	12/9/2024




Pendulum Acceleration
Max: 118.8 g's
Min: -0.5 g's
Filter: CFC 600
Acceleration (g's)
125
100
75
50
25
0
-25
0
2
4
6
8
Time [ms]


Change in Pendulum Velocity (Integrated Acceleration)
Max: 2.9 m/s
Filter: CFC 180
Velocity (m/s)
3
2.5
2
1.5
1
0.5
0
0
2
4
6
8
Time [ms]

CALIBRATION TEST RESULTS

PRE-TEST

HYBRID III 5TH PERCENTILE - PASSENGER ATD

SERIAL NO: 137

External Measurements - Hybrid 3 - 5th Female

Technician: J. Rios Date: 09/10/2024

Dummy Serial Number: 137





Symbol	Description	Specification (mm)		Result (mm)	Pass/Fail
A	Sitting Height	775	800	788	Pass
B	Shoulder Pivot Height	432	457	431	Pass
C	H-Point Height	81	86	83	Pass
D	H-Point from Backline	145	150	147	Pass
E	Shoulder Pivot from Backline	69	84	74	Pass
F	Thigh Clearance	119	135	127	Pass
G	Back of Elbow to Wrist Pivot	244	259	251	Pass
H	Head Back to Backline	43	48	46	Pass
I	Shoulder to Elbow Length	277	297	285	Pass
J	Elbow Rest Height	183	203	195	Pass
K	Buttock to Knee Length	521	546	527	Pass
L	Popliteal Height	356	376	369	Pass
M	Knee Pivot Height	394	419	410	Pass
N	Buttock Popliteal Length	414	439	425	Pass
O	Chest Depth without Jacket	175	191	185	Pass
P	Foot Length (right)	219	234	230	Pass
R	Buttock To Knee Pivot Length	457	483	467	Pass
S	Head Breadth	137	147	145	Pass
T	Head Depth	178	188	184	Pass
U	Hip Breadth	300	315	311	Pass
V	Shoulder Breadth	351	366	360	Pass
W	Foot Breadth	79	94	85	Pass
X	Head Circumference	528	549	537	Pass
Y	Chest Circumference with Jacket	851	881	857	Pass
Z	Waist Circumference	460	790	617	Pass
AA	Reference Location (Chest Circumference)	333	358	340	Pass
BB	Reference Location (Waist Circumference)	160	170	165	Pass

ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	20.9	Pass
Humidity	10	70	%	57	Pass
Resultant Acceleration	250	300	g's	265.2	Pass
Oscillation	0	10	%	2.0	Pass
Lateral Acceleration	-15	15	g's	14.1	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
X Accelerometer	Endevco	P79417	8/19/2024	2/15/2025
Y Accelerometer	Endevco	P83335	8/19/2024	2/15/2025
Z Accelerometer	Endevco	P64149	8/19/2024	2/15/2025




Head CG X Acceleration
Acceleration (g's)
50
0
-50
-100
-150
-200
-250
0
2.5
5
7.5
10
Time [ms]
Max: 3.0 g's
Min: -227.4 g's
Filter: CFC 1000


Head CG Y Acceleration
Acceleration (g's)
15
10
5
0
-5
-10
-15
0
2.5
5
7.5
10
Time [ms]
Max: 14.1 g's
Min: -1.3 g's
Filter: CFC 1000


Head CG Z Acceleration
Acceleration (g's)
150
125
100
75
50
25
0
-25
0
2.5
5
7.5
10
Time [ms]
Max: 136.0 g's
Min: -1.7 g's
Filter: CFC 1000

ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	20.6	Pass
Humidity	10	70	%	55	Pass
Velocity	6.89	7.13	m/s	7.034	Pass
Pendulum Impulse at 10ms	2.1	2.5	m/s	2.29	Pass
Pendulum Impulse at 20ms	4.0	5.0	m/s	4.73	Pass
Pendulum Impulse at 30ms	5.8	7.0	m/s	6.85	Pass
Max D Plane Rotation	77	91	deg	78.9	Pass
Max Moment During Rotation Interval	69	83	Nm	71.5	Pass
Moment Decay to 10.0 Nm	80	100	ms	84.2	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	C16503	4/29/2024	10/26/2024
Pendulum Potentiometer	ETI	SP22G_LABPOT1	5/7/2024	5/7/2025
Condyle Potentiometer	ETI	SP22G_LABPOT2	5/7/2024	5/7/2025
Upper Neck Load Cell	Denton	2184-FX	7/10/2024	7/10/2025

Pendulum Pulse




D-Plane Rotation
Max: 78.9 deg
Min: -52.2 deg
Filter: CFC 60
Rotation (Deg)
Time [ms]
100
75
50
25
0
-25
-50
-75
0
25
50
75
100
125
150


Moment About Occipital Condyle
Max: 71.5 Nm
Min: -24.0 Nm
Filter: CFC 600
Moment (Nm)
Time [ms]
100
75
50
25
0
-25
-50
0
25
50
75
100
125
150

Pendulum Deceleration



Upper Neck Y Moment



Upper Neck X Force



ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	20.6	Pass
Humidity	10	70	%	55	Pass
Velocity	5.95	6.19	m/s	6.009	Pass
Pendulum Impulse at 10ms	1.5	1.9	m/s	1.61	Pass
Pendulum Impulse at 20ms	3.1	3.9	m/s	3.41	Pass
Pendulum Impulse at 30ms	4.6	5.6	m/s	5.24	Pass
D Plane Rotation	99	114	deg	108.5	Pass
Moment During Rotation Interval	-65	-53	Nm	-57.9	Pass
Moment Decay to -10Nm	94	114	ms	103.5	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	C16503	4/29/2024	10/26/2024
Pendulum Potentiometer	ETI	SP22G_LABPOT1	5/7/2024	5/7/2025
Condyle Potentiometer	ETI	SP22G_LABPOT2	5/7/2024	5/7/2025
Upper Neck Load Cell	Denton	2184-FX	7/10/2024	7/10/2025




D-Plane Rotation
Rotation (deg)
125
100
75
50
25
0
-25
-50
0
25
50
75
100
125
150
Time [ms]
Max: 108.5 deg
Min: -12.9 deg
Filter: CFC 60


Moment About Occipital Condyle
Moment (Nm)
50
25
0
-25
-50
-75
0
25
50
75
100
125
150
Time [ms]
Max: 15.7 Nm
Min: -57.9 N
Filter: CFC 600


Pendulum Deceleration
Max: 20.3 g's
Min: -3.5 g's
Filter: CFC 60
Acceleration (g's)
25
20
15
10
5
0
-5
-10
0
10
20
30
40
50
Time [ms]


Upper Neck Y Moment
Max: 19.7 Nm
Min: -49.8 Nm
Filter: CFC 600
Moment (Nm)
30
20
10
0
-10
-20
-30
-40
-50
0
25
50
75
100
125
150
Time [ms]


Upper Neck X Force
Max: 466.7 N
Min: -164.3 N
Filter: CFC 600
Force (N)
500
400
300
200
100
0
-100
-200
0
25
50
75
100
125
150
Time [ms]

ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	20.9	Pass
Humidity	10	70	%	57	Pass
Velocity	6.59	6.83	m/s	6.615	Pass
Chest Deflection	-58	-50	mm	-52.6	Pass
Maximum Resistive Force (50 to 58mm)	3900	4400	N	4389.8	Pass
Maximum Resistive Force (18 to 50mm)	0	4600	N	4398.6	Pass
Hysteresis	69	85	%	74.2	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	18587	11/20/2023	11/19/2024
Chest Potentiometer	Servo	0720	8/19/2024	2/17/2025




Resistive Force
Max: 4398.6 N
Min: -23.0 N
Filter: CFC 180
Force (N)
5000
4000
3000
2000
1000
0
-1000
0
10
20
30
40
50
Time [ms]


Chest Displacement
Max: 0.0 mm
Min: -52.6 mm
Filter: CFC 180
Displacement (mm)
10
0
-10
-20
-30
-40
-50
-60
0
10
20
30
40
50
Time [ms]


Probe Acceleration
Max: 32.30 g's
Min: -0.01 g's
Filter: CFC 180
Acceleration (g's)
35
30
25
20
15
10
5
0
-5
0
10
20
30
40
50
Time [ms]


Change in Velocity (Integrated Acceleration)
Max: 7.39 m/s
Filter: CFC 180
Velocity (m/s)
8
7
6
5
4
3
2
1
0
0
10
20
30
40
50
Time [ms]

ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.6	25.6	ºC	20.9	Pass
Humidity	10	70	%	58	Pass
Initial Angle	0	20	deg	12.5	Pass
Force at 45 Degrees	320	390	N	388.3	Pass
Return Angle Relative to Initial	0	8	deg	5.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	Rieker	DS-1905226	2023-11-14	2024-11-13
Load Cell	Interface	1134516	2023-11-30	2024-11-29



ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	20.8	Pass
Humidity	10	70	%	57	Pass
Velocity	2.07	2.13	m/s	2.081	Pass
Resistive Force	3450	4060	N	4027.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	18587	11/20/2023	11/19/2024




Pendulum Acceleration
Max: 138.2 g's
Min: -1.6 g's
Filter: CFC 600
Acceleration (g's)
150
125
100
75
50
25
0
-25
0
2
4
6
8
Time [ms]


Change in Pendulum Velocity (Integrated Acceleration)
Velocity (m/s)
3
2.5
2
1.5
1
0.5
0
0
2
4
6
8
Time [ms]
Max: 2.7 m/s
Filter: CFC 180

ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	20.8	Pass
Humidity	10	70	%	57	Pass
Velocity	2.07	2.13	m/s	2.082	Pass
Resistive Force	3450	4060	N	3939.5	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	18587	11/20/2023	11/19/2024




Pendulum Acceleration
Max: 135.2 g's
Min: -3.0 g's
Filter: CFC 600
Acceleration (g's)
Time [ms]
150
125
100
75
50
25
0
-25
0
2
4
6
8


Change in Pendulum Velocity (Integrated Acceleration)
Max: 2.7 m/s
Filter: CFC 180
Velocity (m/s)
Time [ms]
3
2.5
2
1.5
1
0.5
0
0
2
4
6
8

CALIBRATION TEST RESULTS

POST-TEST

HYBRID III 50TH PERCENTILE MALE - DRIVER ATD

SERIAL NO: 065

External Measurements - Hybrid 3 - 50th Male

Technician: J. Rios Date: 09/20/2024

Dummy Serial Number: 065



HYBRID III Exterior Body Dimensions - Front View



HYBRID III Exterior Body Dimensions - Side View

Symbol	Description	Specification (in)		Result (in)	Pass/Fail
A	Sitting Height	34.6	35.0	34.7	Pass
B	Shoulder Pivot Height	19.9	20.5	20.2	Pass
C	H-Point Height	3.3	3.5	3.3	Pass
D	H-Point from Backline	5.3	5.5	5.5	Pass
E	Shoulder Pivot from Backline	3.3	3.7	3.5	Pass
F	Thigh Clearance	5.5	6.1	5.9	Pass
G	Back of Elbow to Wrist Pivot	11.4	12.0	11.7	Pass
H	Head Back to Backline	1.6	1.8	1.6	Pass
I	Shoulder to Elbow Length	13.0	13.6	13.3	Pass
J	Elbow Rest Height	7.5	8.3	7.7	Pass
K	Buttock to Knee Length	22.8	23.8	23.4	Pass
L	Popliteal Height	16.9	17.9	17.3	Pass
M	Knee Pivot Height	19.1	19.7	19.3	Pass
N	Buttock Popliteal Length	17.8	18.8	18.2	Pass
O	Chest Depth without Jacket	8.4	9.0	8.7	Pass
P	Foot Length (right)	9.9	10.5	10.3	Pass
V	Shoulder Breadth	16.3	17.2	16.8	Pass
W	Foot Breadth	3.6	4.2	3.9	Pass
Y	Chest Circumference with Jacket	38.2	39.4	38.8	Pass
Z	Waist Circumference	32.9	34.1	33.5	Pass
AA	Reference Location (Chest Circumference)	16.9	17.1	17.0	Pass
BB	Reference Location (Waist Circumference)	8.9	9.1	9.1	Pass

ATD Manufacturer	Humanetics	Test Technician	ZP
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.8	Pass
Humidity	10	70	%	48.1	Pass
Resultant Acceleration	225	275	g's	258.7	Pass
Oscillation	0	10	%	5.1	Pass
Lateral Acceleration	-15	15	g's	11.5	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
X Accelerometer	Endevco	P52383	9/9/2024	3/8/2025
Y Accelerometer	Measurement Specialties	A341256	9/9/2024	3/8/2025
Z Accelerometer	Endevco	P71303	9/9/2024	3/8/2025




Head CG X Acceleration
Acceleration (g's)
250
200
150
100
50
0
-50
0
2.5
5
7.5
10
Time [ms]
Max: 218.2 g's
Min: -6.7 g's
Filter: CFC 1000


Head CG Y Acceleration
Acceleration (g's)
15
10
5
0
-5
-10
-15
0
2.5
5
7.5
10
Time [ms]
Max: 11.5 g's
Min: -1.4 g's
Filter: CFC 1000


Head CG Z Acceleration
Acceleration (g's)
25
0
-25
-50
-75
-100
-125
-150
0
2.5
5
7.5
Time [ms]
Max: 5.6 g's
Min: -138.5 g's
Filter: CFC 1000

ATD Manufacturer	Humaetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	21.2	Pass
Humidity	10	70	%	40.7	Pass
Velocity	6.89	7.13	m/s	7.051	Pass
Pendulum Deceleration at 10ms	22.5	27.5	g's	24.56	Pass
Pendulum Deceleration at 20ms	17.6	22.6	g's	22.24	Pass
Pendulum Deceleration at 30ms	12.5	18.5	g's	16.35	Pass
Max. Pendulum Deceleration After 30ms	0	29	g's	24.8	Pass
Pendulum Deceleration Time to 5 g's	34	42	ms	39.8	Pass
Maximum D Plane Rotation	64	78	deg	73.7	Pass
Time to Maximum Rotation	57	64	ms	60.8	Pass
Rotation Decay to Zero	113	127	ms	123.1	Pass
Moment About Occipital Condyle	88.1	108.4	Nm	95.84	Pass
Time to Maximum Moment	47	58	ms	52.8	Pass
Moment Decay to Zero	97	107	ms	98.7	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	C16678	8/29/2024	2/25/2025
Pendulum Potentiometer	ETI	1412	12/18/2023	12/17/2024
Condyle Potentiometer	ETI	1911	12/18/2023	12/17/2024
Upper Neck Load Cell	Denton	1629-FX	12/8/2023	12/7/2024


D-Plane Rotation
Rotation (Deg)
100
75
50
25
0
-25
-50
0
25
50
75
100
125
150
Time [ms]
Max: 73.7 deg
Min: -33.5 deg
Filter: CFC 60


Moment About Occipital Condyle
Moment (Nm)
125
100
75
50
25
0
-25
-50
0
25
50
75
100
125
150
Time [ms]
Max: 95.8 Nm
Min: -26.6 Nm
Filter: CFC 600


Pendulum Deceleration
Max: 24.8 g's
Min: -2.5 g's
Filter: CFC 60
Acceleration (g's)
Time [ms]


Upper Neck Y Moment
Max: 82.3 Nm
Min: -37.3 Nm
Filter: CFC 600
Moment (Nm)
Time [ms]


Upper Neck X Force
Max: 84.7 N
Min: -839.9 N
Filter: CFC 600
Force (N)
Time [ms]

ATD Manufacturer	Humaetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	21.2	Pass
Humidity	10	70	%	40.7	Pass
Velocity	5.94	6.19	m/s	6.109	Pass
Pendulum Deceleration at 10ms	17.2	21.2	g's	19.27	Pass
Pendulum Deceleration at 20ms	14	19	g's	18.9	Pass
Pendulum Deceleration at 30ms	11	16	g's	14.8	Pass
Max. Pendulum Deceleration After 30ms	0	22	g's	19.4	Pass
Pendulum Deceleration Time to 5 g's	38	46	ms	41.0	Pass
Maximum D Plane Rotation	81	106	deg	101.4	Pass
Time to Maximum Rotation	72	82	ms	76.8	Pass
Rotation Decay to Zero	147	174	ms	166.6	Pass
Minimum Moment About OC	-80	-52.9	Nm	-67.94	Pass
Time to Minimum Moment	65	79	ms	73.6	Pass
Moment Decay to Zero	120	148	ms	146.2	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	C16678	8/29/2024	2/25/2025
Pendulum Potentiometer	ETI	SP22G_1412	12/18/2023	12/17/2024
Condyle Potentiometer	ETI	SP22G_1911	12/18/2023	12/17/2024
Upper Neck Load Cell	Denton	1629-FX	12/8/2023	12/7/2024


D-Plane Rotation
Rotation (deg)
125
100
75
50
25
0
-25
-50
0
25
50
75
100
125
150
Time [ms]
Max: 101.4 deg
Min: 0.0 deg
Filter: CFC 60


Moment About Occipital Condyle
Moment (Nm)
50
25
0
-25
-50
-75
-100
0
25
50
75
100
125
150
Time [ms]
Max: 21.8 Nm
Min: -67.9 Nm
Filter: CFC 600


Pendulum Deceleration
Max: 19.4 g's
Min: -3.2 g's
Filter: CFC 60
Acceleration (g's)
Time [ms]


Upper Neck Y Moment
Max: 26.7 Nm
Min: -60.0 Nm
Filter: CFC 600
Moment (Nm)
Time [ms]


Upper Neck X Force
Max: 527.1 N
Min: -92.7 N
Filter: CFC 600
Force (N)
Time [ms]

ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	22.1	Pass
Humidity	10	70	%	42.8	Pass
Velocity	6.59	6.83	m/s	6.823	Pass
Chest Displacement	-72.6	-63.5	mm	-69.86	Pass
Resistive Force	5160	5894	N	5830.1	Pass
Hysteresis	69	85	%	71.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	T31053	8/21/2023	2/17/2024
Chest Potentiometer	Servo	1046	4/30/2024	10/29/2024




Resistive Force
Force (N)
6000
5000
4000
3000
2000
1000
0
-1000
0
25
50
75
100
Time [ms]
Max: 5830.1 N
Min: -19.0 N
Filter: CFC 180


Sternum Displacement
Displacement (mm)
20
0
-20
-40
-60
-80
0
25
50
75
100
Time [ms]
Max: 0.02 mm
Min: -69.86 mm
Filter: CFC 180


Probe Acceleration
Acceleration (g's)
30
25
20
15
10
5
0
-5
0
25
50
75
100
Time [ms]
Max: 25.4 g's
Min: -0.1 g's
Filter: CFC 180


Change in Velocity (Integrated Acceleration)
Velocity (m/s)
8
7
6
5
4
3
2
1
0
0
25
50
75
100
Time [ms]
Max: 7.4 m/s
Min: 0.0 m/s
Filter: CFC 180

ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.7	Pass
Humidity	10	70	%	44.2	Pass
Average Velocity	5	10	deg/s	7.1	Pass
Angle at 203Nm	40	50	deg	41.5	Pass
Moment at 30 degrees	0	94.9	Nm	79.5	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	Servo 14CB1-3615	3203	11/16/2023	11/15/2024
Load Cell	PCB 2301-02A	111	2023-09-21	2024-09-20



ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.7	Pass
Humidity	10	70	%	44.2	Pass
Average Velocity	5	10	deg/s	7.1	Pass
Angle at 203Nm	40	50	deg	41.6	Pass
Moment at 30 degrees	0	94.9	Nm	85.1	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	Servo 14CB1-3615	3203	11/16/2023	11/15/2024
Load Cell	PCB 2301-02A	111	2023-09-21	2024-09-20



ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.7	Pass
Humidity	10	70	%	44.2	Pass
Velocity	2.07	2.13	m/s	2.127	Pass
Maximum Resistive Force	4720	5780	N	5630.6	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	T29720	6/12/2024	12/9/2024




Pendulum Acceleration
Max: 116.4 g's
Min: -0.3 g's
Filter: CFC 600
Acceleration (g's)
125
100
75
50
25
0
-25
0
2
4
6
8
Time [ms]


Change in Pendulum Velocity (Integrated Acceleration)
Max: 2.8 m/s
Filter: CFC 180
Velocity (m/s)
3
2.5
2
1.5
1
0.5
0
0
2
4
6
8
Time [ms]

ATD Manufacturer	Humanetics	Test Technician	AG
ATD Serial Number	065	Laboratory Supervisor	ZP

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21.7	Pass
Humidity	10	70	%	44.2	Pass
Velocity	2.07	2.13	m/s	2.110	Pass
Maximum Resistive Force	4720	5780	N	5740.5	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	T29720	6/12/2024	12/9/2024




Pendulum Acceleration
Max: 118.6 g's
Min: -0.5 g's
Filter: CFC 600
Acceleration (g's)
125
100
75
50
25
0
-25
0
2
4
6
8
Time [ms]


Change in Pendulum Velocity (Integrated Acceleration)
Max: 2.9 m/s
Filter: CFC 180
Velocity (m/s)
3
2.5
2
1.5
1
0.5
0
0
2
4
6
8
Time [ms]

CALIBRATION TEST RESULTS

POST-TEST

HYBRID III 5TH PERCENTILE FEMALE - PASSENGER ATD

SERIAL NO: 137

External Measurements - Hybrid 3 - 5th Female

Technician: J. Rios Date: 09/24/2024

Dummy Serial Number: 137





Symbol	Description	Specification (mm)		Result (mm)	Pass/Fail
A	Sitting Height	775	800	789	Pass
B	Shoulder Pivot Height	432	457	431	Pass
C	H-Point Height	81	86	85	Pass
D	H-Point from Backline	145	150	148	Pass
E	Shoulder Pivot from Backline	69	84	74	Pass
F	Thigh Clearance	119	135	120	Pass
G	Back of Elbow to Wrist Pivot	244	259	251	Pass
H	Head Back to Backline	43	48	45	Pass
I	Shoulder to Elbow Length	277	297	282	Pass
J	Elbow Rest Height	183	203	195	Pass
K	Buttock to Knee Length	521	546	532	Pass
L	Popliteal Height	356	376	369	Pass
M	Knee Pivot Height	394	419	409	Pass
N	Buttock Popliteal Length	414	439	425	Pass
O	Chest Depth without Jacket	175	191	184	Pass
P	Foot Length (right)	219	234	225	Pass
R	Buttock To Knee Pivot Length	457	483	467	Pass
S	Head Breadth	137	147	144	Pass
T	Head Depth	178	188	184	Pass
U	Hip Breadth	300	315	309	Pass
V	Shoulder Breadth	351	366	360	Pass
W	Foot Breadth	79	94	86	Pass
X	Head Circumference	528	549	537	Pass
Y	Chest Circumference with Jacket	851	881	862	Pass
Z	Waist Circumference	460	790	607	Pass
AA	Reference Location (Chest Circumference)	333	358	339	Pass
BB	Reference Location (Waist Circumference)	160	170	167	Pass

ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	20.9	Pass
Humidity	10	70	%	57	Pass
Resultant Acceleration	250	300	g's	250.8	Pass
Oscillation	0	10	%	1.7	Pass
Lateral Acceleration	-15	15	g's	15.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
X Accelerometer	Endevco	P79417	8/19/2024	2/15/2025
Y Accelerometer	Endevco	P83335	8/19/2024	2/15/2025
Z Accelerometer	Endevco	P64149	8/19/2024	2/15/2025




Head CG X Acceleration
Acceleration (g's)
50
0
-50
-100
-150
-200
-250
0
2.5
5
7.5
10
Time [ms]
Max: 1.3 g's
Min: -203.7 g's
Filter: CFC 1000


Head CG Y Acceleration
Acceleration (g's)
15
10
5
0
-5
-10
-15
0
2.5
5
7.5
10
Time [ms]
Max: 15.0 g's
Min: -1.9 g's
Filter: CFC 1000


Head CG Z Acceleration
Acceleration (g's)
150
125
100
75
50
25
0
-25
0
2.5
5
7.5
10
Time [ms]
Max: 146.9 g's
Min: -1.3 g's
Filter: CFC 1000

ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	20.6	Pass
Humidity	10	70	%	63	Pass
Velocity	6.89	7.13	m/s	7.092	Pass
Pendulum Impulse at 10ms	2.1	2.5	m/s	2.32	Pass
Pendulum Impulse at 20ms	4.0	5.0	m/s	4.74	Pass
Pendulum Impulse at 30ms	5.8	7.0	m/s	6.89	Pass
Max D Plane Rotation	77	91	deg	77.3	Pass
Max Moment During Rotation Interval	69	83	Nm	83.0	Pass
Moment Decay to 10.0 Nm	80	100	ms	86.7	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	C16650	10/31/2023	10/30/2024
Pendulum Potentiometer	ETI	SP22G_LABPOT1	5/7/2024	5/7/2025
Condyle Potentiometer	ETI	SP22G_LABPOT2	5/7/2024	5/7/2025
Upper Neck Load Cell	Denton	2184-FX	7/10/2024	7/10/2025




D-Plane Rotation
Rotation (Deg)
100
75
50
25
0
-25
-50
-75
0
25
50
75
100
125
150
Time [ms]
Max: 77.3 deg
Min: -52.4 deg
Filter: CFC 60


Moment About Occipital Condyle
Moment (Nm)
100
75
50
25
0
-25
0
25
50
75
100
125
150
Time [ms]
Max: 83.0 Nm
Min: -23.8 Nm
Filter: CFC 600


Pendulum Deceleration
Acceleration (g's)
Time [ms]
Max: 29.6 g's
Min: -4.9 g's
Filter: CFC 60


Upper Neck Y Moment
Moment (Nm)
Time [ms]
Max: 78.3 Nm
Min: -34.3 Nm
Filter: CFC 600


Upper Neck X Force
Force (N)
Time [ms]
Max: 31.6 N
Min: -722.0 N
Filter: CFC 600

ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	20.6	Pass
Humidity	10	70	%	63	Pass
Velocity	5.95	6.19	m/s	6.144	Pass
Pendulum Impulse at 10ms	1.5	1.9	m/s	1.78	Pass
Pendulum Impulse at 20ms	3.1	3.9	m/s	3.72	Pass
Pendulum Impulse at 30ms	4.6	5.6	m/s	5.48	Pass
D Plane Rotation	99	114	deg	103.6	Pass
Moment During Rotation Interval	-65	-53	Nm	-62.3	Pass
Moment Decay to -10Nm	94	114	ms	101.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	C16650	10/31/2023	10/30/2024
Pendulum Potentiometer	ETI	SP22G_LABPOT1	5/7/2024	5/7/2025
Condyle Potentiometer	ETI	SP22G_LABPOT2	5/7/2024	5/7/2025
Upper Neck Load Cell	Denton	2184-FX	7/10/2024	7/10/2025




D-Plane Rotation
Rotation (deg)
125
100
75
50
25
0
-25
-50
0
25
50
75
100
125
150
Time [ms]
Max: 103.6 deg
Min: -17.1 deg
Filter: CFC 60


Moment About Occipital Condyle
Moment (Nm)
50
25
0
-25
-50
-75
-100
0
25
50
75
100
125
150
Time [ms]
Max: 16.7 Nm
Min: -62.3 N
Filter: CFC 600


Pendulum Deceleration
Max: 22.7 g's
Min: -3.2 g's
Filter: CFC 60
Acceleration (g's)
25
20
15
10
5
0
-5
-10
0
10
20
30
40
50
Time [ms]


Upper Neck Y Moment
Max: 20.8 Nm
Min: -53.4 Nm
Filter: CFC 600
Moment (Nm)
30
20
10
0
-10
-20
-30
-40
-50
-60
0
25
50
75
100
125
150
Time [ms]


Upper Neck X Force
Max: 505.8 N
Min: -160.8 N
Filter: CFC 600
Force (N)
600
500
400
300
200
100
0
-100
-200
0
25
50
75
100
125
150
Time [ms]

ATD Manufacturer	Humanetics	Test Technician	C. Mantell
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	ºC	21.0	Pass
Humidity	10	70	%	60	Pass
Velocity	6.59	6.83	m/s	6.719	Pass
Chest Deflection	-58	-50	mm	-53.3	Pass
Maximum Resistive Force (50 to 58mm)	3900	4400	N	4349.0	Pass
Maximum Resistive Force (18 to 50mm)	0	4600	N	4348.5	Pass
Hysteresis	69	85	%	74.3	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	18599	9/13/2024	3/12/2025
Chest Potentiometer	Servo	0720	8/19/2024	2/17/2025




Resistive Force
Max: 4349.0 N
Min: -1.9 N
Filter: CFC 180
Force (N)
5000
4000
3000
2000
1000
0
-1000
0
10
20
30
40
50
Time [ms]


Chest Displacement
Max: 0.1 mm
Min: -53.3 mm
Filter: CFC 180
Displacement (mm)
10
0
-10
-20
-30
-40
-50
-60
0
10
20
30
40
50
Time [ms]


Probe Acceleration
Max: 31.93 g's
Min: 0.01 g's
Filter: CFC 180
Acceleration (g's)
35
30
25
20
15
10
5
0
-5
0
10
20
30
40
50
Time [ms]


Change in Velocity (Integrated Acceleration)
Max: 7.32 m/s
Filter: CFC 180
Velocity (m/s)
8
7
6
5
4
3
2
1
0
0
10
20
30
40
50
Time [ms]

ATD Manufacturer	Humanetics	Test Technician	K. Konieczny
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.6	25.6	ºC	20.9	Pass
Humidity	10	70	%	64	Pass
Initial Angle	0	20	deg	10.9	Pass
Force at 45 Degrees	320	390	N	388.4	Pass
Return Angle Relative to Initial	0	8	deg	6.7	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	Rieker	DS-1905226	2023-11-14	2024-11-13
Load Cell	Interface	1134516	2023-11-30	2024-11-29



ATD Manufacturer	Humanetics	Test Technician	C. Hinkley
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21	Pass
Humidity	10	70	%	66	Pass
Velocity	2.07	2.13	m/s	2.079	Pass
Resistive Force	3450	4060	N	3883.4	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	18599	9/13/2024	3/12/2025




Pendulum Acceleration
Max: 133.2 g's
Min: -0.9 g's
Filter: CFC 600
Acceleration (g's)
150
125
100
75
50
25
0
-25
0
2
4
6
8
Time [ms]


Change in Pendulum Velocity (Integrated Acceleration)
Velocity (m/s)
3
2.5
2
1.5
1
0.5
0
0
2
4
6
8
Time [ms]
Max: 2.7 m/s
Filter: CFC 180

ATD Manufacturer	Humanetics	Test Technician	C. Hinkley
ATD Serial Number	137	Laboratory Supervisor	C. Mantell

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	ºC	21	Pass
Humidity	10	70	%	66	Pass
Velocity	2.07	2.13	m/s	2.082	Pass
Resistive Force	3450	4060	N	3854.5	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	18599	9/13/2024	3/12/2025




Pendulum Acceleration
Max: 132.3 g's
Min: -1.3 g's
Filter: CFC 600
Acceleration (g's)
Time [ms]
150
125
100
75
50
25
0
-25
0
2
4
6
8


Change in Pendulum Velocity (Integrated Acceleration)
Max: 2.7 m/s
Filter: CFC 180
Velocity (m/s)
Time [ms]
3
2.5
2
1.5
1
0.5
0
0
2
4
6
8

APPENDIX D

TEST EQUIPMENT AND INSTRUMENTATION CALIBRATION

Table 1 – Driver Dummy Instrumentation

Instrumentation		Axis/Location	Hybrid III 50th S/N: 065		
			Serial Number	Manufacturer	Calibration Date
Head Accelerometers	Primary	X	P52152	Endevco	04/30/2024
		Y	P58888	Endevco	04/30/2024
		Z	P58911	Endevco	04/30/2024
	Redundant	X	P52012	Endevco	05/17/2024
		Y	P51979	Endevco	04/30/2024
		Z	P49204	Endevco	04/30/2024
Head Angular Rate Sensors		X	15212	DTS ARS	11/15/2023
		Y	15695	DTS ARS	11/17/2023
		Z	7603	DTS ARS	11/15/2023
Upper Neck Load Cell		FX, Fy, Fz MX,MY, MZ	851-FX	Humanetics	05/22/2024
Chest Accelerometers	Primary	X	P58887	Endevco	04/30/2024
		Y	P66917	Endevco	04/30/2024
		Z	P49197	Endevco	04/30/2024
	Redundant	X	P49213	Endevco	04/30/2024
		Y	P63840	Endevco	04/30/2024
		Z	P83313	Endevco	04/30/2024
Chest Potentiometer		X	1046	Servo	04/30/2024
Pelvis Accelerometer		X	P51699	Endevco	04/30/2024
		Y	P94090	Endevco	04/30/2024
		Z	P83437	Endevco	04/30/2024
Femur Load Cells - Left	Primary	Z	117-FZ1	Denton	05/22/2024
	Redundant	Z	117-FZ2	Denton	05/22/2024
Femur Load Cells - Right	Primary	Z	109-FZ1	Denton	05/22/2024
	Redundant	Z	109-FZ2	Denton	05/22/2024
Tibia Load Cells - Left	Upper	MX, MY, FZ	652-FZ	Denton	05/20/2024
	Lower	MX, MY, FZ	360-FZ	Denton	05/20/2024
Tibia Load Cells – Right	Upper	MX, MY, FZ	371-FZ	Denton	05/20/2024
	Lower	MX, MY, FZ	360-FZ	Denton	05/20/2024
Foot Accelerometers - Left	Rear	X	P69797	Endevco	04/30/2024
	Front	Z	P51729	Endevco	04/30/2024
Foot Accelerometers - Right	Rear	X	T20878	Endevco	05/14/2024
	Front	Z	P51685	Endevco	04/30/2024
Seat belt Load Cells	Lap		174	GFE	02/08/2024
	Shoulder		168	Denton	06/21/2024

Table 2 – Front Passenger Dummy Instrumentation

Instrumentation		Axis/Location	Hybrid III 5th S/N: 137		
			Serial Number	Manufacturer	Calibration Date
Head Accelerometers	Primary	X	P79417	Endevco	08/19/2024
		Y	P83335	Endevco	08/19/2024
		Z	P64149	Endevco	08/19/2024
	Redundant	X	P52008	Endevco	08/19/2024
		Y	P52045	Endevco	08/19/2024
		Z	P74774	Endevco	08/19/2024
Head Angular Rate Sensors		X	7589	DTS ARS	11/15/2023
		Y	13095	DTS ARS	11/15/2023
		Z	4718	DTS ARS	11/15/2023
Upper Neck Load Cell		FX, Fy, Fz MX,MY, MZ	2184-FX	Denton	07/10/2024
Chest Accelerometers	Primary	X	P58780	Endevco	08/19/2024
		Y	P83346	Endevco	08/19/2024
		Z	P49190	Endevco	08/19/2024
	Redundant	X	P58794	Endevco	08/19/2024
		Y	P69791	Endevco	08/19/2024
		Z	T11253	Endevco	08/19/2024
Chest Potentiometer		X	0720	Servo	08/19/2024
Pelvis Accelerometer		X	P58735	Endevco	08/19/2024
		Y	P77587	Endevco	08/19/2024
		Z	P51285	Endevco	08/19/2024
Femur Load Cells - Left	Primary	Z	DT0998-FZ1	Denton	05/22/2024
	Redundant	Z	DT0998-FZ2	Denton	05/22/2024
Femur Load Cells - Right	Primary	Z	DH3271-FZ1	Denton	05/22/2024
	Redundant	Z	DH3271-FZ2	Denton	05/22/2024
Tibia Load Cells - Left	Upper	MX, MY, FZ	476-FZ	Denton	05/20/2024
	Lower	MX, MY, FZ	363-FZ	Denton	05/20/2024
Tibia Load Cells – Right	Upper	MX, MY, FZ	361-FZ	Denton	05/20/2024
	Lower	MX, MY, FZ	359-FZ	Denton	05/20/2024
Foot Accelerometers - Left	Rear	X	P78959	Endevco	08/19/2024
	Front	Z	P83418	Endevco	08/19/2024
Foot Accelerometers - Right	Rear	X	P63998	Endevco	08/19/2024
	Front	Z	P80265	Endevco	08/19/2024
Seat belt Load Cells	Lap		292	GFE	02/08/2024
	Shoulder		295	GFE	02/08/2024

Table 3 – Vehicle Instrumentation

Instrumentation			Axis	Serial Number	Manufacturer	Calibration Date
Crossmember/Rear Seat Accelerometers	Left	Primary	X	G25551	Endevco	04/27/2024
			Z	G25569	Endevco	05/08/2024
		Redundant	X	G25864	Endevco	06/03/2024
	Right	Primary	X	A431232	Measurement Specialties	03/27/2024
			Z	A431233	Measurement Specialties	03/27/2024
		Redundant	X	A431240	Measurement Specialties	03/27/2024
Engine Accelerometers	Top		X	A428009	Measurement Specialties	04/09/2024
	Bottom		X	G22432	Endevco	05/07/2024