

REPORT NUMBER: NCAP-MGA-25-017

**NEW CAR ASSESSMENT PROGRAM (NCAP)
Frontal Barrier Impact Test**

**FCA US LLC
2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
NHTSA No.: M20250301**

**MGA RESEARCH CORPORATION
5000 Warren Road
Burlington, WI 53105**



Test Date: March 10, 2025


Final Report Date: April 29, 2025


FINAL REPORT

**U.S. DEPARTMENT OF TRANSPORTATION
National Highway Traffic Safety Administration
Office of Crashworthiness Standards
Mail Code: NRM-110
1200 New Jersey Ave, SE
Washington, DC 20590**

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof.

If trade or manufacturers' names or products are mentioned, it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: 
Ben Fischer, Program Manager

Approved by: 
Robert Schnorenberg, Project Engineer

Approval Date: April 29, 2025

FINAL REPORT ACCEPTANCE BY OCWS:

Division Chief, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

COTR, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

TECHNICAL REPORT DOCUMENTATION PAGE

1. Report No. NCAP-MGA-25-017	2. Government Accession No.	3. Recipient's Catalog No.																																																							
4. Title and Subtitle Final Report of New Car Assessment Program Frontal Impact Testing of a 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck, NHTSA No.: M20250301		5. Report Date April 29, 2025																																																							
		6. Performing Organization Code MGA																																																							
7. Author(s) Ben Fischer, Program Manager		8. Performing Organization Report No. NCAP-MGA-25-017																																																							
9. Performing Organization Name and Address MGA Research Corporation 5000 Warren Road Burlington, WI 53105		10. Work Unit No.																																																							
		11. Contract or Grant No. 693JJ919D000006																																																							
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Crashworthiness Standards (NRM-110) 1200 New Jersey Ave, SE Washington, D.C. 20590		13. Type of Report and Period Covered Final Test Report March 10, 2025 to April 29, 2025																																																							
		14. Sponsoring Agency Code NRM-110																																																							
15. Supplementary Notes																																																									
16. Abstract A 56.3 km/h NCAP Frontal Rigid Barrier Impact Test was conducted on a 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck in accordance with the specifications of the Office of Crashworthiness Standards Laboratory Procedure for NCAP Full Frontal Rigid Barrier Impact Testing. The test was conducted at MGA Research Corporation in Burlington, Wisconsin on March 10, 2025. The impact velocity of the vehicle was 56.43 km/h and the ambient temperature at the barrier face at the time of impact was 21.0°C. The target vehicle post-test maximum crush was 434 mm located to the left of the vehicle centerline. The test vehicle's performance was as follows:																																																									
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Measurement Description</th><th rowspan="2">Units</th><th colspan="2">Driver ATD</th><th colspan="2">Passenger ATD</th></tr> <tr> <th>Threshold</th><th>Result</th><th>Threshold</th><th>Result</th></tr> </thead> <tbody> <tr> <td>Head Injury Criteria (HIC₁₅)</td><td></td><td>700</td><td>150.605</td><td>700</td><td>278.725</td></tr> <tr> <td>Maximum Chest Compression</td><td>mm</td><td>63</td><td>31.670</td><td>52</td><td>15.101</td></tr> <tr> <td>Nij</td><td></td><td>1</td><td>0.326</td><td>1</td><td>0.329</td></tr> <tr> <td>Neck Tension</td><td>N</td><td>4170</td><td>1531.785</td><td>2620</td><td>938.928</td></tr> <tr> <td>Neck Compression</td><td>N</td><td>4000</td><td>132.466</td><td>2520</td><td>449.449</td></tr> <tr> <td>Left Femur Force</td><td>N</td><td>10008</td><td>2964.144</td><td>6805</td><td>1161.285</td></tr> <tr> <td>Right Femur Force</td><td>N</td><td>10008</td><td>2783.118</td><td>6805</td><td>2187.574</td></tr> </tbody> </table>						Measurement Description	Units	Driver ATD		Passenger ATD		Threshold	Result	Threshold	Result	Head Injury Criteria (HIC ₁₅)		700	150.605	700	278.725	Maximum Chest Compression	mm	63	31.670	52	15.101	Nij		1	0.326	1	0.329	Neck Tension	N	4170	1531.785	2620	938.928	Neck Compression	N	4000	132.466	2520	449.449	Left Femur Force	N	10008	2964.144	6805	1161.285	Right Femur Force	N	10008	2783.118	6805	2187.574
Measurement Description	Units	Driver ATD		Passenger ATD																																																					
		Threshold	Result	Threshold	Result																																																				
Head Injury Criteria (HIC ₁₅)		700	150.605	700	278.725																																																				
Maximum Chest Compression	mm	63	31.670	52	15.101																																																				
Nij		1	0.326	1	0.329																																																				
Neck Tension	N	4170	1531.785	2620	938.928																																																				
Neck Compression	N	4000	132.466	2520	449.449																																																				
Left Femur Force	N	10008	2964.144	6805	1161.285																																																				
Right Femur Force	N	10008	2783.118	6805	2187.574																																																				
17. Key Words 35 mph Frontal Barrier Impact Test New Car Assessment Program (NCAP)			18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Administration Technical Information Services Division 1200 New Jersey Ave, SE Washington, DC 20590																																																						
19. Security Classification of Report Unclassified	20. Security Classification of Page Unclassified	21. No. of Pages 168	22. Price																																																						

TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1	Purpose and Summary of Test	1
2	Occupant and Vehicle Information / Data Sheets	3
<u>Data Sheet No.</u>		<u>Page No.</u>
1	General Test and Vehicle Parameter Data	4
2	Seat Adjustment, Fuel System, and Steering Wheel Data	8
3	Dummy Longitudinal Clearance Dimensions	10
4	Dummy Lateral Clearance Dimensions	11
5	Seat Belt Positioning Data	12
6	High-Speed Camera Locations and Data	13
7	Vehicle Accelerometer Locations	15
8	Photographic Reference Target Locations	16
9	Load Cell Locations on Fixed Barrier	17
10	Test Vehicle Summary of Results	18
11	Post-Test Observations	19
12	Vehicle Profile Measurements	20
13	Accident Investigation Division Data	22
14	Vehicle Intrusion Measurements	23
15	Summary of Indicant FMVSS No. 212 and FMVSS No. 219 (Partial) Data	25
16	FMVSS No. 301 Barrier Impact and Static Rollover Results	26
17	Dummy/Vehicle Temperature Stabilization Data	28
<u>Appendix</u>		
A	Photographs	A
B	Dummy Response Data Traces	B
C	Dummy Qualification and Performance Verification	C
D	Test Equipment and Instrumentation Calibration	D

SECTION 1 PURPOSE AND SUMMARY OF TEST

PURPOSE

This 56.3 km/h frontal barrier impact test is part of the Vehicle Barrier Impact Testing Program sponsored by the National Highway Traffic Safety Administration (NHTSA) under contract number 693JJ919D000006. The purpose of this test was to obtain vehicle crashworthiness and occupant restraint system performance data for consumer information purposes.

The 56.3 km/h frontal barrier impact was conducted in accordance with the Office of Crashworthiness Standards Laboratory Procedure for NCAP Full Frontal Rigid Barrier Impact Testing.

SUMMARY

A load cell barrier consisting of 176 load cells was impacted by a 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck at a velocity of 56.43 km/h. The test was performed at MGA Research Corporation on March 10, 2025. Pre-test and post-test photographs of the vehicle and dummies can be found in Appendix A.

Two (2) real-time cameras and sixteen (16) high-speed cameras were used to document the frontal barrier impact event. Camera locations and other pertinent camera information can be found in this report.

One Part 572E 50th percentile male anthropomorphic test device (ATD), was placed in the driver seating position and one Part 572O 5th percentile female test device (ATD) was placed in the right-front passenger seating position according to dummy placement instructions specified in the Laboratory Procedure for NCAP Full Frontal Rigid Barrier Impact Testing.

Both ATDs were fully instrumented with head, chest and pelvis tri-axial accelerometers, chest displacement potentiometers, upper neck transducers, right/left femur load cells, and lower leg instrumentation. Seat belt load cells were installed on the driver's and passenger's lap and shoulder belts to measure dummy torso and pelvic section loading.

The driver (position 1) ATD (Serial No. 064) and the right-front passenger (position 2) ATD (Serial No. 142) were qualified previous to this test. Certification details, along with instrumentation calibration data, are found in Appendix C of this report.

The 106 channels of data were recorded on a data acquisition system. Appendix B contains the dummy response data traces.

There was 100 percent windshield retention and no intrusion into the protected zone of the windshield during the event. There was no Stoddard Solvent leakage after the event or during any phase of the static rollover.

The maximum static crush of the vehicle was 434 mm located to the left of the vehicle centerline and both the driver and passenger side doors remained closed during the impact event and were operable after the impact.

The driver's visible contact points were as follows: The driver's head contacted the airbag. The driver's head also contacted the headrest. The driver's knees contacted the knee bolster.

The passenger's visible contact points were as follows: The passenger's head contacted the airbag. The passenger's head also contacted the headrest. The passenger's knees contacted the glove box.

The occupant data is summarized below:

ATD position	HIC₁₅	Nij	Neck Tension (N)	Neck Comp. (N)	3ms Chest Clip (g)	Chest Disp. (mm)	Left Femur (N)	Right Femur (N)
Driver (50 th)	150.605	0.326	1531.785	132.466	44.068	31.670	2964.144	2783.118
Passenger (5 th)	278.725	0.329	938.928	449.449	46.811	15.101	1161.285	2187.574

The test data can be found on the NHTSA website at www.nhtsa.gov

TEST NOTES

None.

MGA does not endorse or certify products. The manufacturer's name appears solely for identification purposes.

SECTION 2
OCCUPANT AND VEHICLE INFORMATION / DATA SHEETS

DATA SHEET NO. 1
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

TEST VEHICLE INFORMATION AND OPTIONS

NHTSA No.	M20250301	Traction Control System (TCS)	Yes
Model Year	2025	Power Steering	Yes
Make	Jeep	Power Window Auto-Reverse	Yes
Model	Gladiator Sport 4x4	Driver Frontal Airbag	Yes
Body Style	4-Door Pickup Truck	Driver Curtain Airbag	Yes
VIN	1C6PJTAG3SL502583	Driver Head/Torso Airbag	No
Body Color	Anvil Clear Coat	Driver Torso Airbag	No
Odometer (km/mi)	85 km / 53 mi	Driver Torso/Pelvis Airbag	Yes
Engine Displacement (L)	3.6	Driver Pelvis Airbag	No
Type/No. Cylinders	V6	Driver Knee Airbag	No
Engine Placement	Longitudinal	Front Pass. Frontal Airbag	Yes
Transmission Type	Automatic	Front Pass. Curtain Airbag	Yes
Transmission Speeds	8	Front Pass. Head/Torso Airbag	No
Overdrive	Yes	Front Pass. Torso Airbag	No
Final Drive	AWD	Front Pass. Torso/Pelvis Airbag	Yes
Roof Rack	No	Front Pass. Pelvis Airbag	No
Sunroof/T-Top	No	Front Pass. Knee Airbag	No
Running Boards	No	Driver Pretensioner	Yes
Tilt Steering Wheel	Yes	Driver Load Limiter	Yes
Power Seats	No	Front Pass. Pretensioner	Yes
Anti-Lock Brakes (ABS)	Yes	Front Pass. Load Limiter	Yes
Automatic Door Locks (ADLs)	Yes	Other	N/A

Does owner's manual provide instructions to turn off automatic door locks?	Yes
--	-----

DATA FROM CERTIFICATION LABEL

Manufactured By	FCA US LLC	GVWR (kg)	2631
Date of Manufacture	11-24	GAWR Front (kg)	1407
		GAWR Rear (kg)	1701

VEHICLE SEATING AND WEIGHT CAPACITY DATA


Measured Parameter	Front	Rear	Third	Total
Type of Seats	Bucket	Split Bench		
Designated Seating Capacity (DSC)	2	3		5
Capacity Weight (VCW) (kg)				419
Cargo Weight (RCLW) (kg)				79

DATA SHEET NO. 1 (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

VEHICLE TIRE INFORMATION



Measured Parameter	Front	Rear
Max. Tire Pressure (kPa)	300	300
Cold Pressure (kPa)	250	250
Recommended Tire Size	275/55R20	275/55R20
Tire Size on Vehicle	275/55R20	275/55R20
Tire Manufacturer	General	General
Tire Model	Grabber A/T	Grabber A/T
Treadwear	500	500
Traction	A	A
Temperature Grade	B	B
Tire Plies Sidewall	2 Polyester	2 Polyester
Tire Plies Body	2 Polyester, 2 Steel, 1 Polyamide	2 Polyester, 2 Steel, 1 Polyamide
Load Index/Speed Symbol	113T	113T
Tire Material	Rubber	Rubber
DOT Safety Code Left	1A3032 FUT 4024	1A3032 FUT 4024
DOT Safety Code Right	1A3032 FUT 4024	1A3032 FUT 4024

DATA SHEET NO. 1 (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

TEST VEHICLE WEIGHTS

	Units	As Delivered (UVW)			As Tested (ATW)		
		Front	Rear	Total	Front	Rear	Total
Left	kg	577.0	497.5		605.0	570.0	
Right	kg	607.5	514.5		629.5	605.5	
Ratio	%	53.9%	46.1%		51.2%	48.8%	
Totals	kg	1184.5	1012.0	2196.5	1234.5	1175.5	2410.0

TARGET TEST WEIGHT CALCULATION

Measured Parameter	Units	Value
Total Delivered Weight (UVW)	kg	2196.5
Weight of 1 P572E ATD & 1 P572O ATD	kg	141
Rated Cargo/Luggage Weight (RCLW)	kg	79
Calculated Test Vehicle Target Weight (TVTW)	kg	2416.5

TEST VEHICLE ATTITUDES AND CG

	Units	LF	RF	LR	RR	CG (aft of front axle)
As Delivered	mm	939	936	998	986	1606
As Tested	mm	931	924	965	968	1700
Post Test	mm	919	843	967	980	

GENERAL TEST VEHICLE DATA

Measurement Description	Units	Value
Total Vehicle Wheel Base	mm	3485
Total Vehicle Length at Left Side	mm	5361
Total Vehicle Length at Centerline	mm	5476
Total Vehicle Length at Right Side	mm	5368
Weight of Ballast in Cargo Area	kg	28
Weight of Vehicle Components Removed	kg	6
Amount of Stoddard Solvent in Fuel Tank	L	77.6

List of components removed to meet test weight: None.

List of components removed for instrumentation, data box, and equipment installation:
Jack and tools, underbody plastic.

DATA SHEET NO. 1 (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
Test Date: 3/10/2025

TARGET VEHICLE STRUCTURAL MEASUREMENT

	Elements	Pre-Test (mm)
1	Total Length	5476
2	Total Width	1657
3	Bumper Top Height	652
4	Bumper Bottom Height	485
5	Longitudinal Member Top Height	646
6	Distance between Longitudinal Members	707
7	Longitudinal Member Width	60
8	Engine Top Height	1126
9	Engine Bottom Height	355
10	Engine and Gearbox Width	421
11	Front Bumper-Engine Distance	953
12	Front Shock Absorber Fixing Height	730
13	Bonnet Leading Edge Height	1098
14	Front Shock Absorber Fixing Width	1080
15	Front Bumper – Front Axle Distance	709
16	Front Axle – A-Pillar Distance	934
17	A-Pillar – B-Pillar Distance	947
18	B-Pillar – Rear Axle Distance	1604
19	B-Pillar – C-Pillar Distance	862
20	Roof Sill Bottom Height	1675
21	Roof Sill Top Height	1791
22	Floor Sill Bottom Height	434
23	Floor Sill Top Height	614

DATA SHEET NO. 2
SEAT ADJUSTMENT, FUEL SYSTEM, AND STEERING WHEEL DATA


Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

NOMINAL DESIGN RIDING POSITION

The driver seat back is positioned as close as possible to the manufacturer's design angle. For the passenger seat back, seat back is adjusted following Appendix F, "Driver & Passenger Dummy Seating & Positioning Procedures" in the NCAP Test Procedure dated May 2018.

	Degrees
Driver Seat Back Angle	5.4° on outboard headrest post
Passenger Seat Back Angle	3° on outboard headrest post



SEAT FORE/AFT POSITIONS


The driver and passenger seat fore/aft positions are adjusted following Appendix F, "Driver & Passenger Dummy Seating & Positioning Procedures" in the NCAP Test Procedure dated May 2018.

	Total Fore/Aft Travel	Placed in Position #
Driver Seat	248 mm / 31 detents (1st as 1)	125 mm / 12th detent (1st as 0)
Passenger Seat	294 mm / 29 detents (1st as 1)	0 mm / 0th detent (1st as 0)

SEAT BELT UPPER ANCHORAGES

The seat belt upper anchorages are set following the manufacturer's specified position as listed in Form 1.

	Total # of Positions	Placed in Position #
Driver Seat	5 (1st as 1)	0 (1st as 0)
Passenger Seat	5 (1st as 1)	0 (1st as 0)



DATA SHEET NO. 2 (CONTINUED)
SEAT ADJUSTMENT, FUEL SYSTEM, AND STEERING WHEEL DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test


NHTSA No.: M20250301
 Test Date: 3/10/2025

FUEL TANK CAPACITY DATA

	Liters
Usable Capacity of "Standard Tank"	83.3
Usable Capacity of "Optional Tank"	
92-94% of Usable Capacity	76.6 to 78.3
Actual Amount of Solvent used	77.6
1/3 of Usable Capacity	27.8

FUEL PUMP


The vehicle is equipped with an electronic fuel pump. The fuel pump will run when the engine is running. The pump will also briefly run when the ignition key is turned to the "on" position. The filler neck is located on the driver's side.



VEHICLE FUEL TANK ASSEMBLY

STEERING COLUMN ADJUSTMENT

Steering wheel and column adjustments are made so that the steering wheel hub is at the geometric center of the locus it describes when moved through its full range of motion. An aluminum plate is placed across the rim of the steering wheel, an inclinometer is placed on the plate and the angle is measured.



STEERING COLUMN ASSEMBLY


STEERING COLUMN POSITION

	Degrees	Fore/Aft Position (mm)
Lowermost Position 1	71.2	
Geometric Center Position 2	68.2	
Uppermost Position 3	65.2	
Telescoping Steering Wheel Travel		30
Test Position	68.2	15

DATA SHEET NO. 3
DUMMY LONGITUDINAL CLEARANCE DIMENSIONS

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025




LEFT SIDE VIEW

Code	Measurement Description	Driver		Passenger	
		Length (mm)	Angle (°)	Length (mm)	Angle (°)
WA°	Windshield Angle		54.0		
SWA°	Steering Wheel Angle		68.2		
SCA°	Steering Column Angle		21.8		
SA°	Seat Back Angle		5.4		3.0
HZ	Head to Roof (Z)	231	90	318	90
HH	Head to Header	505	14.6	424	28.7
HW	Head to Windshield	597	0	547	0
NR	Nose to Rim	389	13.8		
CD	Chest to Dash	514		355	
CS	Chest to Steering Hub	302	6.7		
RA	Rim to Abdomen	173	0		
KDL	Left Knee to Dash	167	61.5	117	47.7
KDR	Right Knee to Dash	150	20.8	103	34.4
PA°	Pelvic Angle		21.0		21.7
TA°	Tibia Angle		38.7		58.2
SK	Striker to Knee	616	90.7	659	91.8
ST	Striker to Head	611	7.5	555	19.9
SH	Striker to H-Point	233	103.3	333	97.1

DATA SHEET NO. 4
DUMMY LATERAL CLEARANCE DIMENSIONS

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
Test Date: 3/10/2025




FRONT VIEW OF DUMMY

Code	Measurement Description	Units	Driver	Passenger
AD	Arm to Door	mm	61	57
HD	H-Point to Door	mm	124	153
HR	Head to Side Header	mm	202	268
HS	Head to Side Window	mm	362	372
KK	Knee to Knee	mm	322	228
SHY	Striker to H-Point (Y Direction)	mm	168	209
AA	Ankle to Ankle	mm	244	171

**DATA SHEET NO. 5
SEAT BELT POSITIONING DATA**

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
Test Date: 3/10/2025



FRONT VIEW OF DUMMY

SEAT BELT POSITIONING MEASUREMENTS

Measurement Description	Units	Driver	Passenger
PBU - Top surface of reference to belt upper edge	mm	320	280
PBL - Top surface of reference to belt lower edge	mm	230	180

BELT LENGTH DATA


Measurement Description	Units	Driver	Passenger
Shoulder Belt Length as measured on ATD	mm	812	807
Lap Belt Length as measured on ATD	mm	650	667
Remainder of belt on reel	mm	338	326
Total Belt Length for Continuous Webbing Systems	mm	2500	2500

DATA SHEET NO. 6
HIGH-SPEED CAMERA LOCATIONS AND DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
Test Date: 3/10/2025

CAMERA POSITIONS FOR FRONTAL IMPACTS



***Camera locations are approximate and not to scale*

DATA SHEET NO. 6 (CONTINUED)
HIGH-SPEED CAMERA LOCATIONS AND DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

CAMERA LOCATIONS

No.	Camera View	Coordinates* (mm)			Lens (mm)	Speed (fps)
		X	Y	Z		
1	Real-Time Left Overall					30
2	Left Overall	-2470	-5870	-1440	12	1000
3	Driver Close-Up	-1720	-6930	-1860	50	1000
4	Left Front Half	-1180	-5890	-1380	24	1000
5	Left Angle	-7310	-5700	-1920	75	1000
6	Steering Column	-960	-5800	-1250	50	1000
7	Right Overall	-2440	5920	-1450	12	1000
8	Passenger Close-Up	-1790	6900	-1920	50	1000
9	Right Front Half	-1230	5940	-1430	24	1000
10	Right Angle	-7360	5480	-1980	75	1000
11	Windshield	150	0	-2310	12	1000
12	Driver Windshield	200	-370	-2230	25	1000
13	Passenger Windshield	200	370	-2230	25	1000
14	Pit Front	-1050	0	3340	24	1000
15	Pit Rear	-3050	0	3340	24	1000
16	Driver Onboard				12	1000
17	Passenger Onboard				12	1000
18	Real-Time Pan View					30

*COORDINATES:

+X = forward of impact plane


+Y = right of monorail centerline

+Z = below ground level

DATA SHEET NO. 7 **VEHICLE ACCELEROMETER LOCATIONS**

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
Test Date: 3/10/2025



VEHICLE ACCELEROMETER PRE-TEST LOCATIONS

No.	Accelerometer Location	Measurements (mm)		
		X	Y	Z
1	Left Rear Crossmember Accelerometer – X Direction	2092	-400	-757
2	Right Rear Crossmember Accelerometer – X Direction	2101	223	-750
3	Engine Top X	4434	-54	-1145
4	Engine Bottom X	4370	30	-418
5	Left Rear Crossmember Accelerometer – Z Direction	2092	-400	-757
6	Right Rear Crossmember Accelerometer – Z Direction	2101	223	-750
7	Left Rear Crossmember Accelerometer Redundant – X Direction	2092	-400	-757
8	Right Rear Crossmember Accelerometer Redundant – X Direction	2101	223	-750




Reference Points: X - Rear Surface of Vehicle (+ forward)
Y - Vehicle Centerline (+ to right)
Z - Ground Plane (+ down)

DATA SHEET NO. 8 **PHOTOGRAPHIC REFERENCE TARGET LOCATIONS**

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

Item	Value (mm)
A	382
B	829
C	2414
D	610
E	2452
F	95
G	
H	2062
I	1467
J	997
K	986
L	2025
M	2060
N	2044
O	990
P	974
Q	1468



DATA SHEET NO. 9 **LOAD CELL LOCATIONS ON FIXED BARRIER**

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

ADVANCED RESEARCH LOAD CELL BARRIER




Photo for Reference Only

Centerline

A-16	A-15	A-14	A-13	A-12	A-11	A-10	A-09	A-08	A-07	A-06	A-05	A-04	A-03	A-02	A-01
B-16	B-15	B-14	B-13	B-12	B-11	B-10	B-09	B-08	B-07	B-06	B-05	B-04	B-03	B-02	B-01
C-16	C-15	C-14	C-13	C-12	C-11	C-10	C-09	C-08	C-07	C-06	C-05	C-04	C-03	C-02	C-01
D-16	D-15	D-14	D-13	D-12	D-11	D-10	D-09	D-08	D-07	D-06	D-05	D-04	D-03	D-02	D-01
E-16	E-15	E-14	E-13	E-12	E-11	E-10	E-09	E-08	E-07	E-06	E-05	E-04	E-03	E-02	E-01
F-16	F-15	F-14	F-13	F-12	F-11	F-10	F-09	F-08	F-07	F-06	F-05	F-04	F-03	F-02	F-01
G-16	G-15	G-14	G-13	G-12	G-11	G-10	G-09	G-08	G-07	G-06	G-05	G-04	G-03	G-02	G-01
H-16	H-15	H-14	H-13	H-12	H-11	H-10	H-09	H-08	H-07	H-06	H-05	H-04	H-03	H-02	H-01
I-16	I-15	I-14	I-13	I-12	I-11	I-10	I-09	I-08	I-07	I-06	I-05	I-04	I-03	I-02	I-01
J-16	J-15	J-14	J-13	J-12	J-11	J-10	J-09	J-08	J-07	J-06	J-05	J-04	J-03	J-02	J-01
K-16	K-15	K-14	K-13	K-12	K-11	K-10	K-09	K-08	K-07	K-06	K-05	K-04	K-03	K-02	K-01

Load Cells are 121 mm x 121 mm with a 7 mm gap in between each load cell.

DATA SHEET NO. 10
TEST VEHICLE SUMMARY OF RESULTS

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
Test Date: 3/10/2025

INSTRUMENTATION

Instrumentation	Number of Channels Collected
Driver Dummy Data Channels	49
Passenger Dummy Data Channels	49
Vehicle Structure Accelerometers	8
Barrier Channels	0
Total	106

CAMERA COVERAGE

Type of Camera	Number Used in this Test
High-Speed Vehicle Onboard	2
High-Speed Offboard	14
Real-Time	2
Total	18

**DATA SHEET NO. 11
POST-TEST OBSERVATIONS**

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
Test Date: 3/10/2025

TEST DUMMY INFORMATION AND CONTACT LOCATIONS

Description	Driver	Passenger
Dummy Type / Serial No.	HIII 50% / 064	HIII 5% / 142
Head Contact	Frontal Airbag, Headrest	Frontal Airbag, Headrest
Upper Torso Contact	Frontal Airbag	Frontal Airbag
Lower Torso Contact	None	None
Left Knee Contact	Knee Bolster	Glove Box
Right Knee Contact	Knee Bolster	Glove Box

DOOR OPENING, TRUNK OPENING, AND SEAT TRACK INFORMATION

Description	Driver	Passenger
Locked/Unlocked Doors	Doors were unlocked	Doors were unlocked
Front Door Opening	Remained closed and unlocked; opened without tools	Remained closed and unlocked; opened without tools
Rear Door Opening	Remained closed and unlocked; opened without tools	Remained closed and unlocked; opened without tools
Trunk/Hatch/Tailgate Opening	Remained closed; opened without tools	
Seat Track Shift (mm)	0	0
Seat Back Movement	None	None

OTHER VEHICLE POST-TEST OBSERVATIONS

Critical Areas of Performance	Observations and Conclusions
Windshield Damage	None
Window Damage	None
Other Notable Effects	Hood unlatched

VEHICLE REBOUND FROM BARRIER

Measured Parameter	Units	Value
Left Side	mm	988
Center	mm	991
Right Side	mm	949
Average	mm	976


SUPPLEMENTAL RESTRAINT SYSTEM INFORMATION

Restraint Type	Driver		Passenger	
	Mounted	Deployed	Mounted	Deployed
Frontal Airbag	Yes	Yes	Yes	Yes
Curtain Side Airbag	Yes	No	Yes	No
Torso/Pelvis Side Airbag	Yes	No	Yes	No
Knee Airbag	No		No	
Seat Belt Pretensioner	Yes	Yes	Yes	Yes
Seat Belt Load Limiter	Yes	Yes	Yes	Yes
Other				

DATA SHEET NO. 12 VEHICLE PROFILE MEASUREMENTS

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025



DATA SHEET NO. 12 (CONTINUED)
VEHICLE PROFILE MEASUREMENTS

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
Test Date: 3/10/2025

No.	Measurement Description	Pre-Test	Post-Test	Change
1	Total Length of Vehicle at Centerline	5476	5046	-430
2	RSOV to Front of Engine	4524	4482	-42
3	RSOV to Firewall	4245	4196	-49
4	RSOV to Upper Leading Edge of Right Door	3835	3842	7
5	RSOV to Upper Leading Edge of Left Door	3838	3840	2
6	RSOV to Lower Leading Edge of Right Door	3824	3833	9
7	RSOV to Lower Leading Edge of Left Door	3819	3825	6
8	RSOV to Upper Trailing Edge of Right Door	2909	2916	7
9	RSOV to Upper Trailing Edge of Left Door	2910	2915	5
10	RSOV to Lower Trailing Edge of Right Door	3016	3026	10
11	RSOV to Lower Trailing Edge of Left Door	3003	3009	6
12	RSOV to Bottom of "A" Post of Right Side	4008	4023	15
13	RSOV to Bottom of "A" Post of Left Side	4009	4024	15
14	RSOV to Firewall, Right Side	4250	4254	4
15	RSOV to Firewall, Left Side	4248	4250	2
16	RSOV to Steering Column	3479	3549	70
17	Center of Steering Column to "A" Post	275	278	3
18	Center of Steering Column to Headliner	442	448	6
19	RSOV to Right Side of Front Bumper	5368	5073	-295
20	RSOV to Left Side of Front Bumper	5361	5057	-304
21	Length of Engine Block	228	228	0
RD	RSOV to Right Side of Dash Panel	3713	3715	2
CD	RSOV to Center of Dash Panel	3702	3713	11
LD	RSOV to Left Side of Dash Panel	3711	3711	0

All dimensions in mm

DATA SHEET NO. 13
ACCIDENT INVESTIGATION DIVISION DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
Test Date: 3/10/2025

VEHICLE INFORMATION

VIN: 1C6PJTAG3SL502583
Vehicle Size Category: Truck


Wheelbase (mm): 3485
Test Weight (kg): 2410.0

ACCELEROMETER DATA

Accelerometer Locations: As per Data Sheet No. 7
Cal. Procedure/Interval: MGA Procedure / 6 month
Integration Algorithm: Trapezoidal
Linearity: > 99%
Impact Velocity (km/h): 56.43
Velocity Change (km/h): 61.8
Time of Separation (msec) 123

CRUSH PROFILE

Collision Deformation Classification: 12FDEW2
Midpoint of Damage: Centerline
Damage Region Length (mm): 1566
Impact Mode: Frontal



No.	Measurement Description	Units	Pre-Test	Post-Test	Exterior Crush
C1	Crush zone 1 at left side	mm	1639	1943	304
C2	Crush zone 2 at left side	mm	1519	1892	373
C3	Crush zone 3 at left side	mm	1528	1962	434
C4	Crush zone 4 at right side	mm	1526	1955	429
C5	Crush zone 5 at right side	mm	1517	1887	370
C6	Crush zone 6 at right side	mm	1632	1927	295
L	C1 TO C6	mm	1566	1573	7

DATA SHEET NO. 14
VEHICLE INTRUSION MEASUREMENTS

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
Test Program: NCAP Frontal Barrier Impact Test


NHTSA No.: M20250301
Test Date: 3/10/2025

DOOR OPENING WIDTH

Item	Description	Units	Pre-Test	Post-Test	Change
A	Left Side Upper	mm	909	897	-12
B	Left Side Lower	mm	869	866	-3
D	Right Side Upper	mm	910	901	-9
E	Right Side Lower	mm	863	861	-2

WHEELBASE MEASUREMENTS

Item	Description	Units	Pre-Test	Post-Test	Change
C	Left Side Wheelbase	mm	3485	3370	-115
F	Right Side Wheelbase	mm	3490	3395	-95



DATA SHEET NO. 14 (CONTINUED)
VEHICLE INTRUSION MEASUREMENTS


Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

DRIVER COMPARTMENT INTRUSION

Item	Description	Units	Pre-Test	Post-Test	Change
AB	Door Opening (Inside Window Jam)	mm	651	649	-2
CX	Left Knee Bolster to X	mm	227	236	9
DX	Right Knee Bolster to X	mm	231	236	5
EX	Brake Pedal to X	mm	486	489	3
FX	Foot Rest to X	mm	602	598	-4
GX	Center of Steering Column Wheel Hub to X	mm	-8	47	55

X = Front of Seat Track (stationary)



DRIVER COMPARTMENT

DATA SHEET NO. 15
SUMMARY OF INDICANT FMVSS NO. 212 AND FMVSS NO. 219 (PARTIAL) DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

WINDSHIELD MOUNTING DETAILS


Windshield glass is secured to the vehicle frame with a rubber trim and glue.

The standard requires that the post-test retention measurement be a minimum of 75 percent of the pre-test total periphery measurement for vehicles not equipped with occupant passive restraints and 50 percent for each side of the windshield for vehicles which are equipped with occupant passive restraints.

Temperature of windshield molding during test: 21.0°C.

WINDSHIELD PERIPHERY MEASUREMENTS

Measurement	Pre-Test (mm)	Post-Test (mm)	% of Retention
Left Side	1819	1819	100
Right Side	1819	1819	100
Total	3638	3638	100



Item	Units	Value
A	mm	1308
B	mm	237
C	mm	1414
D	mm	458
E	mm	211
F	mm	544

AREA OF PROTECTED ZONE FAILURES

A. Provide coordinates of the area that the protected zone was penetrated more than 0.25 inches by a vehicle component other than one that is normally in contact with the windshield. **None**

X	Y

B. Provide coordinates of the area beneath the protected zone that the inner surface of the windshield was penetrated by a vehicle component. **None**

X	Y

DATA SHEET NO. 16
FMVSS NO. 301 BARRIER IMPACT AND STATIC ROLLOVER RESULTS

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025


FMVSS 301 FUEL SYSTEM INTEGRITY POST IMPACT DATA

Temperature at Time of Impact: 21.0°C

Test Time: 11:56 a.m.

- A. From impact until vehicle motion ceases: (Maximum Allowable = 1 ounce) 0.0 oz.
 B. For the 5 minute period after motion ceases: (Maximum Allowable = 5 ounces) 0.0 oz.
 C. For the following 25 minutes: (Maximum Allowable = 1 ounce / minute) None
 D. Spillage Details: None

FMVSS 301 STATIC ROLLOVER RESULTS



1. The specified fixture rollover rate for each 90° of rotation is 60 to 180 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. Details of Stoddard Solvent spillage: **None**

SOLVENT COLLECTION TIME TABLE IN SECONDS

Test Phase	Rotation Time	Hold Time	Total Time
0° to 90°	109	300	409
90° to 180°	112	300	412
180° to 270°	109	300	409
270° to 360°	110	300	410

DATA SHEET NO. 16 (CONTINUED)
FMVSS 301 BARRIER IMPACT AND STATIC ROLLOVER

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025

FMVSS 301 SPILLAGE TABLE (UNITS IN OUNCES)

Test Phase	First 5 Minutes	Sixth Minute	Seventh Minute	Eight Minute
0° to 90°	0	0	0	
90° to 180°	0	0	0	
180° to 270°	0	0	0	
270° to 360°	0	0	0	


SOLVENT SPILLAGE LOCATION TABLE

Test Phase	Spillage Location
0° to 90°	
90° to 180°	
180° to 270°	
270° to 360°	

DATA SHEET NO. 17
DUMMY/VEHICLE TEMPERATURE STABILIZATION DATA

Test Vehicle: 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Truck
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20250301
 Test Date: 3/10/2025



Serial #	Description	Maximum	Average	Minimum	Units
W1443497	VSC Start Room A - Temp (1038)	21.90	21.58	20.65	°C

**APPENDIX A
PHOTOGRAPHS**

TABLE OF PHOTOGRAPHS

		<u>Page No.</u>
Photo No. 001	Load Cell Location	A-1
Photo No. 002	Pre-Test Load Cell Wall	A-1
Photo No. 003	Post-Test Load Cell Wall	A-2
Photo No. 004	Manufacturer's Label	A-2
Photo No. 005	Tire Placard	A-3
Photo No. 006	2025 Jeep Gladiator Sport 4x4 4-Door Pickup Frontal As Delivered	A-3
Photo No. 007	Left Rear 3-4 View, As Received	A-4
Photo No. 008	Pre-Test Front View of Test Vehicle	A-4
Photo No. 009	Post-Test Front View of Test Vehicle	A-5
Photo No. 010	Pre-Test Left View of Test Vehicle	A-5
Photo No. 011	Post-Test Left View of Test Vehicle	A-6
Photo No. 012	Pre-Test Right View of Test Vehicle	A-6
Photo No. 013	Post-Test Right View of Test Vehicle	A-7
Photo No. 014	Pre-Test Right Front 3-4 View	A-7
Photo No. 015	Post-Test Right Front 3-4 View	A-8
Photo No. 016	Pre-Test Left Rear 3-4 View	A-8
Photo No. 017	Post-Test Left Rear 3-4 View	A-9
Photo No. 018	Pre-Test Windshield View	A-9
Photo No. 019	Post-Test Windshield View	A-10
Photo No. 020	Pre-Test Engine Compartment View	A-10
Photo No. 021	Post-Test Engine Compartment View	A-11
Photo No. 022	Pre-Test Fuel Filler Cap View	A-11
Photo No. 023	Post-Test Fuel Filler Cap View	A-12
Photo No. 024	Pre-Test Front Underbody View	A-12
Photo No. 025	Post-Test Front Underbody View	A-13
Photo No. 026	Pre-Test Rear Underbody View	A-13
Photo No. 027	Post-Test Rear Underbody View	A-14
Photo No. 028	Pre-Test Dummy Cable Routing	A-14
Photo No. 029	Post-Test Dummy Cable Routing	A-15

		<u>Page No.</u>
Photo No. 030	Pre-Test Driver Dummy Front View	A-15
Photo No. 031	Post-Test Driver Dummy Front View	A-16
Photo No. 032	Pre-Test Driver Dummy Window View	A-16
Photo No. 033	Post-Test Driver Dummy Window View	A-17
Photo No. 034	Pre-Test Driver Dummy and Vehicle Interior View	A-17
Photo No. 035	Post-Test Driver Dummy and Vehicle Interior View	A-18
Photo No. 036	Pre-Test Driver's Seat Fore-Aft Markings	A-18
Photo No. 037	Post-Test Driver's Seat Fore-Aft Markings	A-19
Photo No. 038	Pre-Test View of Belt Anchorage for Driver Dummy	A-19
Photo No. 039	Post-Test View of Belt Anchorage for Driver Dummy	A-20
Photo No. 040	Pre-Test View of Belt Buckle and Latch Plate for Driver Dummy	A-20
Photo No. 041	Post-Test View of Belt Buckle and Latch Plate for Driver Dummy	A-21
Photo No. 042	Pre-Test Driver Dummy Feet	A-21
Photo No. 043	Post-Test Driver Dummy Feet	A-22
Photo No. 044	Pre-Test Driver's Side Knee Bolster	A-22
Photo No. 045	Post-Test Driver's Side Knee Bolster	A-23
Photo No. 046	Pre-Test Driver's Side Floorpan	A-23
Photo No. 047	Post-Test Driver's Side Floorpan	A-24
Photo No. 048	Post-Test Driver Dummy Face	A-24
Photo No. 049	Post-Test Driver Dummy Contact with Airbag	A-25
Photo No. 050	Post-Test Driver Dummy Contact with Headrest	A-25
Photo No. 051	Pre-Test View of the Steering Wheel	A-26
Photo No. 052	Post-Test View of the Steering Wheel	A-26
Photo No. 053	Pre-Test Passenger Dummy Front View	A-27
Photo No. 054	Post-Test Passenger Dummy Front View	A-27
Photo No. 055	Pre-Test Passenger Dummy Window View	A-28
Photo No. 056	Post-Test Passenger Dummy Window View	A-28
Photo No. 057	Pre-Test Passenger Dummy and Vehicle Interior	A-29
Photo No. 058	Post-Test Passenger Dummy and Vehicle Interior	A-29
Photo No. 059	Pre-Test Passenger's Seat Fore-Aft Markings	A-30

Photo No. 060	Post-Test Passenger's Seat Fore-Aft Markings	A-30
Photo No. 061	Pre-Test View of Belt Anchorage for Passenger Dummy	A-31
Photo No. 062	Post-Test View of Belt Anchorage for Passenger Dummy	A-31
Photo No. 063	Pre-Test View of Belt Buckle and Latch Plate for Passenger Dummy	A-32
Photo No. 064	Post-Test View of Belt Buckle and Latch Plate for Passenger Dummy	A-32
Photo No. 065	Pre-Test Passenger Dummy Feet	A-33
Photo No. 066	Post-Test Passenger Dummy Feet	A-33
Photo No. 067	Pre-Test Passenger's Side Knee Bolster	A-34
Photo No. 068	Post-Test Passenger's Side Knee Bolster	A-34
Photo No. 069	Pre-Test Passenger's Side Floorpan	A-35
Photo No. 070	Post-Test Passenger's Side Floorpan	A-35
Photo No. 071	Post-Test Passenger Dummy Face	A-36
Photo No. 072	Post-Test Passenger Dummy Contact with Airbag	A-36
Photo No. 073	Post-Test Passenger Dummy Contact with Headrest	A-37
Photo No. 074	Photograph of Ballast Installed in Vehicle	A-37
Photo No. 075	Post-Test Stoddard Solvent Spillage Location View	A-38
Photo No. 076	Post-Test Speed Trap Read-Out	A-38
Photo No. 077	Vehicle at 0 Degree on Static Rollover Device	A-39
Photo No. 078	Vehicle at 90 Degrees on Static Rollover Device	A-39
Photo No. 079	Vehicle at 180 Degrees on Static Rollover Device	A-40
Photo No. 080	Vehicle at 270 Degrees on Static Rollover Device	A-40
Photo No. 081	Vehicle at 360 Degrees on Static Rollover Device	A-41
Photo No. 082	2025 Jeep Gladiator Sport 4x4 4-Door Pickup Frontal Impact Event	A-41
Photo No. 083	Monroney Label Photograph	A-42

PHOTOGRAPH NOT APPLICABLE

Photo No. 001 - Load Cell Location



Photo No. 002 - Pre-Test Load Cell Wall

PHOTOGRAPH NOT AVAILABLE

Photo No. 003 - Post-Test Load Cell Wall



Photo No. 004 - Manufacturer's Label



Photo No. 005 - Tire Placard



Photo No. 006 - 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Frontal As Delivered



Photo No. 007 - Left Rear 3-4 View, As Received



Photo No. 008 - Pre-Test Front View of Test Vehicle



Photo No. 009 - Post-Test Front View of Test Vehicle



Photo No. 010 - Pre-Test Left View of Test Vehicle



Photo No. 011 - Post-Test Left View of Test Vehicle



Photo No. 012 - Pre-Test Right View of Test Vehicle



Photo No. 013 - Post-Test Right View of Test Vehicle



Photo No. 014 - Pre-Test Right Front 3-4 View



Photo No. 015 - Post-Test Right Front 3-4 View



Photo No. 016 - Pre-Test Left Rear 3-4 View



Photo No. 017 - Post-Test Left Rear 3-4 View



Photo No. 018 - Pre-Test Windshield View



Photo No. 019 - Post-Test Windshield View



Photo No. 020 - Pre-Test Engine Compartment View




Photo No. 021 - Post-Test Engine Compartment View



Photo No. 022 - Pre-Test Fuel Filler Cap View



Photo No. 023 - Post-Test Fuel Filler Cap View



Photo No. 024 - Pre-Test Front Underbody View




Photo No. 025 - Post-Test Front Underbody View




Photo No. 026 - Pre-Test Rear Underbody View




Photo No. 027 - Post-Test Rear Underbody View



Photo No. 028 - Pre-Test Dummy Cable Routing



Photo No. 029 - Post-Test Dummy Cable Routing



Photo No. 030 - Pre-Test Driver Dummy Front View



Photo No. 031 - Post-Test Driver Dummy Front View



Photo No. 032 - Pre-Test Driver Dummy Window View



Photo No. 033 - Post-Test Driver Dummy Window View



Photo No. 034 - Pre-Test Driver Dummy and Vehicle Interior View



Photo No. 035 - Post-Test Driver Dummy and Vehicle Interior View



Photo No. 036 - Pre-Test Driver's Seat Fore-Aft Markings



Photo No. 037 - Post-Test Driver's Seat Fore-Aft Markings



Photo No. 038 - Pre-Test View of Belt Anchorage for Driver Dummy



Photo No. 039 - Post-Test View of Belt Anchorage for Driver Dummy



Photo No. 040 - Pre-Test View of Belt Buckle and Latch Plate for Driver Dummy



Photo No. 041 - Post-Test View of Belt Buckle and Latch Plate for Driver Dummy



Photo No. 042 - Pre-Test Driver Dummy Feet



Photo No. 043 - Post-Test Driver Dummy Feet



Photo No. 044 - Pre-Test Driver's Side Knee Bolster



Photo No. 045 - Post-Test Driver's Side Knee Bolster



Photo No. 046 - Pre-Test Driver's Side Floorpan



Photo No. 047 - Post-Test Driver's Side Floorpan



Photo No. 048 - Post-Test Driver Dummy Face



Photo No. 049 - Post-Test Driver Dummy Contact with Airbag



Photo No. 050 - Post-Test Driver Dummy Contact with Headrest



Photo No. 051 - Pre-Test View of the Steering Wheel



Photo No. 052 - Post-Test View of the Steering Wheel



Photo No. 053 - Pre-Test Passenger Dummy Front View



Photo No. 054 - Post-Test Passenger Dummy Front View



Photo No. 055 - Pre-Test Passenger Dummy Window View



Photo No. 056 - Post-Test Passenger Dummy Window View



Photo No. 057 - Pre-Test Passenger Dummy and Vehicle Interior View



Photo No. 058 - Post-Test Passenger Dummy and Vehicle Interior View



Photo No. 059 - Pre-Test Passenger's Seat Fore-Aft Markings



Photo No. 060 - Post-Test Passenger's Seat Fore-Aft Markings



Photo No. 061 - Pre-Test View of Belt Anchorage for Passenger Dummy



Photo No. 062 - Post-Test View of Belt Anchorage for Passenger Dummy



Photo No. 063 - Pre-Test View of Belt Buckle and Latch Plate for Passenger Dummy



Photo No. 064 - Post-Test View of Belt Buckle and Latch Plate for Passenger Dummy



Photo No. 065 - Pre-Test Passenger Dummy Feet



Photo No. 066 - Post-Test Passenger Dummy Feet



Photo No. 067 - Pre-Test Passenger's Side Knee Bolster



Photo No. 068 - Post-Test Passenger's Side Knee Bolster



Photo No. 069 - Pre-Test Passenger's Side Floorpan



Photo No. 070 - Post-Test Passenger's Side Floorpan



Photo No. 071 - Post-Test Passenger Dummy Face



Photo No. 072 - Post-Test Passenger Dummy Contact with Airbag



Photo No. 073 - Post-Test Passenger Dummy Contact with Headrest




Photo No. 074 - Photograph of Ballast Installed in Vehicle

PHOTOGRAPH NOT APPLICABLE

Photo No. 075 - Post-Test Stoddard Solvent Spillage Location View



Photo No. 076 - Post-Test Speed Trap Read-Out



Photo No. 077 - Vehicle at 0 Degrees on Static Rollover Device



Photo No. 078 - Vehicle at 90 Degrees on Static Rollover Device



Photo No. 079 - Vehicle at 180 Degrees on Static Rollover Device

PHOTOGRAPH NOT AVAILABLE

Photo No. 080 - Vehicle at 270 Degrees on Static Rollover Device



Photo No. 081 - Vehicle at 360 Degrees on Static Rollover Device



Photo No. 082 - 2025 Jeep Gladiator Sport 4x4 4-Door Pickup Frontal Impact Event



2025 MODEL YEAR GLADIATOR SPORT 4X4

THIS VEHICLE IS MANUFACTURED TO MEET SPECIFIC UNITED STATES REQUIREMENTS. THIS VEHICLE IS NOT MANUFACTURED FOR SALE OR REGISTRATION OUTSIDE OF THE UNITED STATES.

MANUFACTURER'S SUGGESTED RETAIL PRICE OF THIS MODEL INCLUDING DEALER PREPARATION

Base Price: **\$38,100**

JEOP GLADIATOR SPORT 4X4
Exterior Color: Anvil Clear-Coat Exterior Paint
Interior Color: Black Interior Color
Interior Cloth Low-Back Bucket Seats
Engine: 3.6L V6 24V VVT Engine with Stop/Start
Transmission: 8-Speed Automatic 850RE Transmission

STANDARD EQUIPMENT (UNLESS REPLACED BY OPTIONAL EQUIPMENT)

FUNCTIONAL SAFETY FEATURES
Jep® Wave Membership (Retail Sales/50 States Only)
Supplemental Side Air Bags
Advanced Multistage Front Airbags
Supplemental Front Seat-Mounted Side Air Bags
ParkView® Rear Back-Up Camera
Selo-Speed® Control
Command-Trac® Part-Time 4WD System
Heavy-Duty Dana® 44 Front Axle
Heavy-Duty Dana® 44 Rear Axle
3.73 Axle Ratio
17-Inch x 7.5-Inch Black Steel Styled Wheels
Fuel Tank Skid-Plate Shield
Transmission Skid-Plate
Transfer Case Skid-Plate Shield
7-Pin and 4-Pin Wiring Harness
Electronic Trailer Sway Control
Electronic Stability Control
Electronic Roll Mitigation
Speed Control
Selectable Tire-Fill Alert
Tow-Tool-Kit
Integrated Window Antenna
Push-Button Start
Location Specific Tire Pressure Monitoring Display
INTERIOR FEATURES
Uconnect® 5 with 12.3-Inch Touch Screen Display
Off-Road Info Pages
SiriusXM® 360L with 3-Month Sub Call 800-643-2112
Apple CarPlay®
Google Android Auto™
Alexa Built-In (Wi-Fi® Required)
Handsfree Phone and Audio
Cluster with 3.5-Inch TFT Black and White Display
8 Speakers
Full-Function Media Hub with 2-USB Plus Aux-Port
12-Volt Auxiliary Power Outlet
Air Conditioning
Power Tailgate Lock
Speed-Sensitive Power-Locks

Assembly Point/Port of Entry: TOLEDO, OHIO, U.S.A.

VIN: 1C6-PJTAG3SL-502583

LA-VIN: 0325

SHIP TO: 67967 14
SUNNYSIDE COMPANY
4810 W. ELM ST. ROUTE 120
MCKENRY IL 60050-4019

SHIP TO: 67967 51
SUNNYSIDE COMPANY
4810 W. ELM ST. ROUTE 120
MCKENRY IL 60050-4019

THIS LABEL IS ADDED TO THIS VEHICLE TO COMPLY WITH FEDERAL LAW. THE LABEL CANNOT BE REMOVED OR ALTERED PRIOR TO DELIVERY TO THE ULTIMATE PURCHASER.
* STATE AND/OR LOCAL TAXES IF ANY, LICENSE AND TITLE FEES AND DEALER SUPPLIED AND INSTALLED OPTIONS AND ACCESSORIES ARE NOT INCLUDED IN THIS PRICE. DISCOUNT, IF ANY, IS BASED ON PRICE OF OPTIONS IF PURCHASED SEPARATELY.

Power Windows with Front 1-Touch Down
Tilt / Telescope Steering Column
Steering-Wheel-Mounted Audio Controls
6-Way Manual Adjustable Driver Seat
2-Way Manual Lumbar Adjustable Driver Seat
Behind-Rear-Seat Storage
LED Dome Lamp with On / Off Switch
Front and Rear Floor Mats
EXTERIOR FEATURES
Full-Size Spare Tire

OPTIONAL EQUIPMENT (May Replace Standard Equipment)

Anvil Clear-Coat Exterior Paint \$595
Customer Preferred Package 24X \$2,795
NightHawk
Sport Suspension
Sport Rear Shock Absorbers
20-Inch x 8.0-Inch Painted Black Aluminum Wheels
275/55R20 All-Terrain Tires
Body-Color Freedom Top® 3-Piece Hard Top
Cali Rock Rails
Heavy-Duty Dana® 44 Wide Front Axle
Heavy-Duty Dana® 44 Wide Rear Axle
Trac-Lok® Anti-Spin Rear Differential
Premium Front Bumper with Gloss-Black Accents
Body-Color Fender Flares
Daytime Running Lamp System
Deep-Tint Sunscreen Windows
Power-Heated Mirrors

DESTINATION CHARGE

\$1,895

TOTAL PRICE: *\$43,385

WARRANTY COVERAGE

5-year or 60,000-mile Powertrain Limited Warranty.
3-year or 36,000-mile Basic Limited Warranty.
Ask Dealer for a copy of the limited warranties or see your owner's manual for details.

**5 YEAR / 60,000 MILE
POWERTRAIN WARRANTY**

For more information visit: www.jeep.com
or call 1-877-IAM-JEEP

FCA US LLC

EPA DOT Fuel Economy and Environment

Fuel Economy
19 MPG
combined city/hwy
5.3 gallons per 100 miles

These estimates reflect new EPA methods beginning with 2017 models.
Standard pickups range from 12 to 84 MPG.
The best vehicle rates 140 MPG.

**You spend
\$4,250
more in fuel costs
over 5 years
compared to the
average new vehicle.**

**Annual fuel COST
\$2,750**

Fuel Economy & Greenhouse Gas Rating (tailpipe only)



Smog Rating (tailpipe only)



Actual results will vary for many reasons, including driving conditions and how you drive and maintain your vehicle. The average new vehicle gets 28 MPG and cost \$9,500 to fuel over 5 years. Cost estimates are based on 15,000 miles per year at \$3.50 per gallon. MPGe is miles per gasoline gallon equivalent. Vehicle emissions are a significant cause of climate change and smog.

fuel economy.gov
Calculate personalized estimates and compare vehicles



GOVERNMENT 5-STAR SAFETY RATINGS

Overall Vehicle Score Not Rated
Based on the combined ratings of frontal, side and rollover.
Should ONLY be compared to other vehicles of similar size and weight.

Frontal	Driver	Not Rated
Crash	Passenger	Not Rated

Based on the risk of injury in a frontal impact.
Should ONLY be compared to other vehicles of similar size and weight.

Side	Front seat	Not Rated
Crash	Rear seat	Not Rated

Based on the risk of injury in a side impact.

Rollover ★★★
Based on the risk of rollover in a single-vehicle crash.

Star ratings range from 1 to 5 stars (★★★★★) with 5 being the highest.
Source: National Highway Traffic Safety Administration (NHTSA)
www.safercar.gov or 1-888-327-4236

The safety ratings above are based on Federal Government tests of particular vehicles equipped with certain features and options. The performance of this vehicle may differ.

PARTS CONTENT INFORMATION
FOR VEHICLES IN THIS CARLINE:
U.S./CANADIAN PARTS CONTENT: 74%
MAJOR SOURCES OF FOREIGN PARTS CONTENT:
MEXICO: 15%
NOTE: PARTS CONTENT DOES NOT INCLUDE FINAL ASSEMBLY, DISTRIBUTION, OR OTHER NON-PARTS COSTS.
FOR THIS VEHICLE:
FINAL ASSEMBLY POINT:
TOLEDO, OHIO, U.S.A.
COUNTRY OF ORIGIN:
ENGINE: UNITED STATES
TRANSMISSION: UNITED STATES



VEHICLE PROTECTION
A PRODUCT OF FCA US LLC

Ask for Mopar Vehicle Protection for your vehicle. We built it. We back it.

Photo No. 083 - Monroney Label Photograph

APPENDIX B
DUMMY RESPONSE DATA TRACES

TABLE OF DATA PLOTS

Page No.

List of Data Plots Provided in the Test Report

Figure No. 1.	Driver Head X Acceleration vs. Time	B-1
Figure No. 2.	Driver Head Y Acceleration vs. Time	B-1
Figure No. 3.	Driver Head Z Acceleration vs. Time	B-1
Figure No. 4.	Driver Head Resultant Acceleration vs. Time	B-1
Figure No. 5.	Driver Chest Displacement vs. Time	B-2
Figure No. 6.	Driver Chest X Acceleration vs. Time	B-3
Figure No. 7.	Driver Chest Y Acceleration vs. Time	B-3
Figure No. 8.	Driver Chest Z Acceleration vs. Time	B-3
Figure No. 9.	Driver Chest Resultant Acceleration vs. Time	B-3
Figure No. 10.	Driver Neck Force X vs. Time	B-4
Figure No. 11.	Driver Neck Force Z vs. Time	B-4
Figure No. 12.	Driver Neck Moment Y vs. Time	B-4
Figure No. 13.	Driver Nij (NTF) vs. Time	B-5
Figure No. 14.	Driver Nij (NTE) vs. Time	B-5
Figure No. 15.	Driver Nij (NCF) vs. Time	B-5
Figure No. 16.	Driver Nij (NCE) vs. Time	B-5
Figure No. 17.	Driver Left Femur Force vs. Time	B-6
Figure No. 18.	Driver Right Femur Force vs. Time	B-6
Figure No. 19.	Passenger Head X Acceleration vs. Time	B-7
Figure No. 20.	Passenger Head Y Acceleration vs. Time	B-7
Figure No. 21.	Passenger Head Z Acceleration vs. Time	B-7
Figure No. 22.	Passenger Head Resultant Acceleration vs. Time	B-7
Figure No. 23.	Passenger Chest Displacement vs. Time	B-8
Figure No. 24.	Passenger Chest X Acceleration vs. Time	B-9
Figure No. 25.	Passenger Chest Y Acceleration vs. Time	B-9
Figure No. 26.	Passenger Chest Z Acceleration vs. Time	B-9
Figure No. 27.	Passenger Chest Resultant Z Acceleration vs. Time	B-9

	<u>Page No.</u>
Figure No. 28. Passenger Neck Force X vs. Time	B-10
Figure No. 29. Passenger Neck Force Z vs. Time	B-10
Figure No. 30. Passenger Neck Moment Y vs. Time	B-10
Figure No. 31. Passenger Nij (NTF) vs. Time	B-11
Figure No. 32. Passenger Nij (NTE) vs. Time	B-11
Figure No. 33. Passenger Nij (NCF) vs. Time	B-11
Figure No. 34. Passenger Nij (NCE) vs. Time	B-11
Figure No. 35. Passenger Left Femur Force vs. Time	B-12
Figure No. 36. Passenger Right Femur Force vs. Time	B-12


The following additional dummy and vehicle response data can be found in the R&D section of the NHTSA website at www.nhtsa.gov

Driver Head X Redundant
 Driver Head Y Redundant
 Driver Head Z Redundant
 Driver Head Angular Velocity X
 Driver Head Angular Velocity Y
 Driver Head Angular Velocity Z
 Driver Upper Neck Force Y
 Driver Upper Neck Moment X
 Driver Upper Neck Moment Z
 Driver Chest X Redundant
 Driver Chest Y Redundant
 Driver Chest Z Redundant
 Driver Pelvis X
 Driver Pelvis Y
 Driver Pelvis Z
 Driver Left Femur Redundant
 Driver Right Femur Redundant
 Driver Left Upper Tibia Moment X
 Driver Left Upper Tibia Moment Y


Driver Left Upper Tibia Force Z
Driver Left Lower Tibia Moment X
Driver Left Lower Tibia Moment Y
Driver Left Lower Tibia Force Z
Driver Right Upper Tibia Moment X
Driver Right Upper Tibia Moment Y
Driver Right Upper Tibia Force Z
Driver Right Lower Tibia Moment X
Driver Right Lower Tibia Moment Y
Driver Right Lower Tibia Force Z
Driver Left Foot Fore Z
Driver Left Foot Aft X
Driver Left Foot Aft Z
Driver Right Foot Fore Z
Driver Right Foot Aft X
Driver Right Foot Aft Z
Driver Lap Belt Force
Driver Shoulder Belt Force
Passenger Head X Redundant
Passenger Head Y Redundant
Passenger Head Z Redundant
Passenger Head Angular Velocity X
Passenger Head Angular Velocity Y
Passenger Head Angular Velocity Z
Passenger Upper Neck Force Y
Passenger Upper Neck Moment X
Passenger Upper Neck Moment Z
Passenger Chest X Redundant
Passenger Chest Y Redundant
Passenger Chest Z Redundant
Passenger Pelvis X
Passenger Pelvis Y

Passenger Pelvis Z
Passenger Left Femur Redundant
Passenger Right Femur Redundant
Passenger Left Upper Tibia Moment X
Passenger Left Upper Tibia Moment Y
Passenger Left Upper Tibia Force Z
Passenger Left Lower Tibia Moment X
Passenger Left Lower Tibia Moment Y
Passenger Left Lower Tibia Force Z
Passenger Right Upper Tibia Moment X
Passenger Right Upper Tibia Moment Y
Passenger Right Upper Tibia Force Z
Passenger Right Lower Tibia Moment X
Passenger Right Lower Tibia Moment Y
Passenger Right Lower Tibia Force Z
Passenger Left Foot Fore Z
Passenger Left Foot Aft X
Passenger Left Foot Aft Z
Passenger Right Foot Fore Z
Passenger Right Foot Aft X
Passenger Right Foot Aft Z
Passenger Lap Belt Force
Passenger Shoulder Belt Force
Left Rear Seat Crossmember X
Right Rear Seat Crossmember X
Vehicle Engine Top X
Vehicle Engine Bottom X
Left Rear Seat Crossmember Z
Right Rear Seat Crossmember Z
Left Rear Seat Crossmember Xr
Right Rear Seat Crossmember Xr
Advanced Research Load Cell Barrier – 528 channels


DRIVER HEAD X (g) vs Time (ms)




DRIVER HEAD Y (g) vs Time (ms)




DRIVER HEAD Z (g) vs Time (ms)




DRIVER HEAD Resultant (g) vs Time (ms)



DRIVER CHEST DISPLACEMENT (mm) vs Time (ms)




DRIVER CHEST X (g) vs Time (ms)




DRIVER CHEST Y (g) vs Time (ms)




DRIVER CHEST Z (g) vs Time (ms)




DRIVER CHEST Resultant (g) vs Time (ms)




DRIVER NECK FX (N) vs Time (ms)




DRIVER NECK FZ (N) vs Time (ms)




DRIVER NECK MY (Nm) vs Time (ms)




DRIVER Nij (NTF) () vs Time (ms)




DRIVER Nij (NTE) () vs Time (ms)




DRIVER Nij (NCF) () vs Time (ms)




DRIVER Nij (NCE) () vs Time (ms)




DRIVER LEFT FEMUR (N) vs Time (ms)




DRIVER RIGHT FEMUR (N) vs Time (ms)




PASSENGER HEAD X (g) vs Time (ms)




PASSENGER HEAD Y (g) vs Time (ms)




PASSENGER HEAD Z (g) vs Time (ms)




PASSENGER HEAD Resultant (g) vs Time (ms)







PASSENGER CHEST X (g) vs Time (ms)




PASSENGER CHEST Y (g) vs Time (ms)




PASSENGER CHEST Z (g) vs Time (ms)




PASSENGER CHEST Resultant (g) vs Time (ms)




PASSENGER NECK FX (N) vs Time (ms)




PASSENGER NECK FZ (N) vs Time (ms)




PASSENGER NECK MY (Nm) vs Time (ms)




PASSENGER Nij (NTF) () vs Time (ms)




PASSENGER Nij (NTE) () vs Time (ms)




PASSENGER Nij (NCF) () vs Time (ms)




PASSENGER Nij (NCE) () vs Time (ms)



PASSENGER LEFT FEMUR (N) vs Time (ms)



PASSENGER RIGHT FEMUR (N) vs Time (ms)



APPENDIX C
DUMMY QUALIFICATION AND PERFORMANCE VERIFICATION

QUALIFICATION TEST RESULTS

PRE-TEST

HYBRID III 50TH PERCENTILE MALE - DRIVER ATD

**Hybrid III 50th, External Measurements
SN: 064**

HYBRID III, PART 572, SUBPART E EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (inches)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	34.6–35.0	34.71
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	19.9-20.5	20.31
C	H-POINT HEIGHT	Reference	3.3-3.5	3.38
D	H-POINT LOCATION FROM BACKLINE	Reference	5.3-5.5	5.40
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	3.3-3.7	3.46
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	5.5-6.1	6.09
G	BACK OF ELBOW TO WRIST PIVOT	back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	11.4-12.0	11.48
H	HEAD BACK TO BACKLINE	Back of Skull cap skin to seat rear vertical surface (Reference)	1.6-1.8	1.75
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	13.0-13.6	13.08
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	7.5-8.3	8.13
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	22.8-23.8	23.49
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	16.9-17.9	17.01
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	19.1-19.7	19.22
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	17.8-18.8	18.20

HYBRID III, SUBPART E EXTERIOR DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS		ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 16.9-17.1 in. above seat surface	8.4-9.0	8.43
P	FOOT LENGTH	Tip of toe to rear of heel	9.9-10.5	10.33
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	16.3-17.2	16.65
W	FOOT BREADTH	The widest part of the foot	3.6-4.2	3.94
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 16.9-17.1 in. above seat surface	38.2-39.4	39.25
Z	WAIST CIRCUMFERENCE	Measured 8.9-9.1 in. above seat surface	32.9-34.1	33.89
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	16.9-17.1	17.00
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	8.9-9.1	9.00

NOTE: THE H-POINT IS LOCATED 1.83 INCHES FORWARD AND 2.57 INCHES DOWN FROM THE CENTER OF THE PELVIS ANGLE REFERENCE HOLE.







Head Drop Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 02/18/2025
Test ID: D250511
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	21	Pass
Peak Resultant Acceleration	g	225 to 275	226	Pass
Peak Lateral Acceleration	g	-15.0 to 15.0	1.4	Pass
Unimodal	%	within 10% of peak	4	Pass


Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
HEAD X	Endevco	T30974	11/25/2024	5/27/2025
HEAD Y	Endevco	T30975	11/25/2024	5/27/2025
HEAD Z	Endevco	T30976	11/25/2024	5/27/2025




Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	19	Pass
Pendulum Velocity	m/s	6.89 to 7.13	7.10	Pass
Pendulum Deceleration At 10 ms After T0	g	22.50 to 27.50	23.07	Pass
Pendulum Deceleration At 20 ms After T0	g	17.60 to 22.60	20.45	Pass
Pendulum Deceleration At 30 ms After T0	g	12.50 to 18.50	17.14	Pass
Peak Pendulum Deceleration After 30 ms	g	<= 29.0	17.1	Pass
Deceleration Decay Time to Cross 5 g	ms	34.0 to 42.0	37.9	Pass
Maximum "D" Plane Rotation	deg	64.0 to 78.0	69.6	Pass
Time of Maximum "D" Plane Rotation	ms	57.0 to 64.0	59.9	Pass
"D" Plane Rotation Decay Time To Zero Crossing	ms	113.0 to 128.0	113.4	Pass
Maximum Moment About Occipital Condyle	Nm	88.1 to 108.5	97.9	Pass
Time of Maximum Moment About Occipital Condyle	ms	47.0 to 58.0	50.2	Pass
Positive Moment Decay Time To Zero Crossing	ms	97.0 to 107.0	97.1	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PEND. ACCEL.	Endevco	AH5P1	01/13/2025	7/15/2025
NECK FORCE X	Denton	NG2022FX	05/24/2024	5/24/2025
NECK MOMENT Y	Denton	NG2022MY	05/24/2024	5/24/2025
PEND. POT	Servo	4707	08/21/2024	2/20/2025
HEAD POT	Servo	7297	08/21/2024	2/20/2025


PEND. ACCEL. (g) vs Time (ms)



NECK ROTATION (deg) vs Time (ms)




OCCIPITAL MOMENT (Nm) vs Time (ms)




Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	19	Pass
Pendulum Velocity	m/s	5.95 to 6.19	5.98	Pass
Pendulum Deceleration At 10 ms After T0	g	17.20 to 21.20	18.31	Pass
Pendulum Deceleration At 20 ms After T0	g	14.00 to 19.00	16.61	Pass
Pendulum Deceleration At 30 ms After T0	g	11.00 to 16.00	13.06	Pass
Peak Pendulum Deceleration After 30 ms	g	<= 22.0	13.0	Pass
Deceleration Decay Time to Cross 5 G's	ms	38.0 to 46.0	44.3	Pass
Maximum "D" Plane Rotation	deg	81.0 to 106.0	97.7	Pass
Time of Maximum "D" Plane Rotation	ms	72.0 to 82.0	81.3	Pass
"D" Plane Rotation Decay Time To Zero Crossing	ms	147.0 to 174.0	161.0	Pass
Minimum Moment About Occipital Condyle	Nm	-79.9 to -52.9	-57.0	Pass
Time of Minimum Moment About Occipital Condyle	ms	65.0 to 79.0	75.3	Pass
Negative Moment Decay Time To Zero Crossing	ms	120.0 to 148.0	145.0	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PEND. ACCEL.	Endevco	AH5P1	01/13/2025	7/15/2025
NECK FORCE X	Denton	NG2022FX	05/24/2024	5/24/2025
NECK MOMENT Y	Denton	NG2022MY	05/24/2024	5/24/2025
PEND. POT	Servo	4707	08/21/2024	2/20/2025
HEAD POT	Servo	7297	08/21/2024	2/20/2025


PEND. ACCEL. (g) vs Time (ms)



NECK ROTATION (deg) vs Time (ms)



OCCIPITAL MOMENT (Nm) vs Time (ms)






Thorax Impact Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 02/18/2025
Test ID: D250514
Test Technician: Jonah Pulokas


Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	20.9	Pass
Laboratory Relative Humidity	%	10 to 70	23	Pass
Probe Velocity	m/s	6.58 to 6.82	6.77	Pass
Peak Probe Force	N	5159 to 5893	5456	Pass
Peak Sternum Displacement	cm	6.35 to 7.26	6.84	Pass
Internal Hysteresis	%	69 to 85	72	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PROBE	Endevco	P79577	09/18/2024	3/20/2025
CHEST DISPLACEMENT	Humanetics	064	11/19/2024	5/21/2025


FORCE (N) vs CHEST DISPLACEMENT (cm)



FORCE (N) vs Time (ms)



CHEST DISPLACEMENT (cm) vs Time (ms)






Right Knee Impact Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 02/18/2025
Test ID: D250515
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	22	Pass
Probe Velocity	m/s	2.07 to 2.13	2.10	Pass
Peak Probe Force	N	4715 to 5782	4779	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
KNEE PROBE	Endevco	P82128	12/03/2024	6/4/2025






Left Knee Impact Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 02/18/2025
Test ID: D250516
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	22	Pass
Probe Velocity	m/s	2.07 to 2.13	2.10	Pass
Peak Probe Force	N	4715 to 5782	4822	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
KNEE PROBE	Endevco	P82128	12/03/2024	6/4/2025






Right Hip-Femur Flexion Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 02/18/2025
Test ID: D250519
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	22	Pass
Rotation Rate	deg/s	5.0 to 10.0	6.5	Pass
Moment at 30 Degrees	Nm	<= 94.9	86.0	Pass
Rotation Angle at 203.4 Nm	deg	40.0 to 50.0	44.8	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
LOAD CELL	FTSS	DN7673MY	03/22/2024	3/22/2025
FRAME ANGLE	Servo	3966	09/20/2024	3/22/2025
FEMUR ANGLE	Servo	4714	09/20/2024	3/22/2025






Left Hip-Femur Flexion Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 02/18/2025
Test ID: D250510
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	22	Pass
Rotation Rate	deg/s	5.0 to 10.0	6.6	Pass
Moment at 30 Degrees	Nm	<= 94.9	87.2	Pass
Rotation Angle at 203.4 Nm	deg	40.0 to 50.0	45.6	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
LOAD CELL	FTSS	DN7673MY	03/22/2024	3/22/2025
FRAME ANGLE	Servo	3966	09/20/2024	3/22/2025
FEMUR ANGLE	Servo	4714	09/20/2024	3/22/2025



QUALIFICATION TEST RESULTS

POST-TEST

HYBRID III 50TH PERCENTILE MALE - DRIVER ATD







Head Drop Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 03/11/2025
Test ID: D250741
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.5	Pass
Laboratory Relative Humidity	%	10 to 70	26	Pass
Peak Resultant Acceleration	g	225 to 275	230	Pass
Peak Lateral Acceleration	g	-15.0 to 15.0	-4.4	Pass
Unimodal	%	within 10% of peak	1	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
HEAD X	Endevco	T30974	11/25/2024	5/27/2025
HEAD Y	Endevco	T30975	11/25/2024	5/27/2025
HEAD Z	Endevco	T30976	11/25/2024	5/27/2025






Neck Flexion Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 03/11/2025
Test ID: D250742
Test Technician: Jonah Pulokas


Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	26	Pass
Pendulum Velocity	m/s	6.89 to 7.13	7.0	Pass
Pendulum Deceleration At 10 ms After T0	g	22.50 to 27.50	24.25	Pass
Pendulum Deceleration At 20 ms After T0	g	17.60 to 22.60	21.39	Pass
Pendulum Deceleration At 30 ms After T0	g	12.50 to 18.50	17.31	Pass
Peak Pendulum Deceleration After 30 ms	g	<= 29.0	17.2	Pass
Deceleration Decay Time to Cross 5 g	ms	34.0 to 42.0	38.6	Pass
Maximum "D" Plane Rotation	deg	64.0 to 78.0	72.7	Pass
Time of Maximum "D" Plane Rotation	ms	57.0 to 64.0	58.4	Pass
"D" Plane Rotation Decay Time To Zero Crossing	ms	113.0 to 128.0	114.1	Pass
Maximum Moment About Occipital Condyle	Nm	88.1 to 108.5	103.5	Pass
Time of Maximum Moment About Occipital Condyle	ms	47.0 to 58.0	50.6	Pass
Positive Moment Decay Time To Zero Crossing	ms	97.0 to 107.0	97.3	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PEND. ACCEL.	Endevco	AH5P1	01/13/2025	7/15/2025
NECK FORCE X	Denton	NG2022FX	05/24/2024	5/24/2025
NECK MOMENT Y	Denton	NG2022MY	05/24/2024	5/24/2025
PEND. POT	Servo	4707	02/25/2025	8/27/2025
HEAD POT	Servo	7297	02/25/2025	8/27/2025


PEND. ACCEL. (g) vs Time (ms)



NECK ROTATION (deg) vs Time (ms)




OCCIPITAL MOMENT (Nm) vs Time (ms)




Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	27	Pass
Pendulum Velocity	m/s	5.95 to 6.19	5.98	Pass
Pendulum Deceleration At 10 ms After T0	g	17.20 to 21.20	19.40	Pass
Pendulum Deceleration At 20 ms After T0	g	14.00 to 19.00	17.09	Pass
Pendulum Deceleration At 30 ms After T0	g	11.00 to 16.00	13.11	Pass
Peak Pendulum Deceleration After 30 ms	g	<= 22.0	13.1	Pass
Deceleration Decay Time to Cross 5 G's	ms	38.0 to 46.0	40.9	Pass
Maximum "D" Plane Rotation	deg	81.0 to 106.0	99.6	Pass
Time of Maximum "D" Plane Rotation	ms	72.0 to 82.0	79.6	Pass
"D" Plane Rotation Decay Time To Zero Crossing	ms	147.0 to 174.0	159.4	Pass
Minimum Moment About Occipital Condyle	Nm	-79.9 to -52.9	-60.7	Pass
Time of Minimum Moment About Occipital Condyle	ms	65.0 to 79.0	72.4	Pass
Negative Moment Decay Time To Zero Crossing	ms	120.0 to 148.0	143.7	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PEND. ACCEL.	Endevco	AH5P1	01/13/2025	7/15/2025
NECK FORCE X	Denton	NG2022FX	05/24/2024	5/24/2025
NECK MOMENT Y	Denton	NG2022MY	05/24/2024	5/24/2025
PEND. POT	Servo	4707	02/25/2025	8/27/2025
HEAD POT	Servo	7297	02/25/2025	8/27/2025


PEND. ACCEL. (g) vs Time (ms)



NECK ROTATION (deg) vs Time (ms)



OCCIPITAL MOMENT (Nm) vs Time (ms)






Thorax Impact Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 03/11/2025
Test ID: D250744
Test Technician: Jonah Pulokas


Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	28	Pass
Probe Velocity	m/s	6.58 to 6.82	6.77	Pass
Peak Probe Force	N	5159 to 5893	5425	Pass
Peak Sternum Displacement	cm	6.35 to 7.26	6.81	Pass
Internal Hysteresis	%	69 to 85	72	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PROBE	Endevco	P79577	09/18/2024	3/20/2025
CHEST DISPLACEMENT	Humanetics	064	11/19/2024	5/21/2025


FORCE (N) vs CHEST DISPLACEMENT (cm)



FORCE (N) vs Time (ms)



CHEST DISPLACEMENT (cm) vs Time (ms)






Right Knee Impact Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 03/11/2025
Test ID: D250745
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	29	Pass
Probe Velocity	m/s	2.07 to 2.13	2.13	Pass
Peak Probe Force	N	4715 to 5782	5137	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
KNEE PROBE	Endevco	P82128	12/03/2024	6/4/2025






Left Knee Impact Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 03/11/2025
Test ID: D250746
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	28	Pass
Probe Velocity	m/s	2.07 to 2.13	2.10	Pass
Peak Probe Force	N	4715 to 5782	4994	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
KNEE PROBE	Endevco	P82128	12/03/2024	6/4/2025






Right Hip-Femur Flexion Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 03/11/2025
Test ID: D250749
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	26	Pass
Rotation Rate	deg/s	5.0 to 10.0	6.6	Pass
Moment at 30 Degrees	Nm	<= 94.9	92.3	Pass
Rotation Angle at 203.4 Nm	deg	40.0 to 50.0	45.7	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
LOAD CELL	FTSS	DN7673MY	03/22/2024	3/22/2025
FRAME ANGLE	Servo	3966	09/20/2024	3/22/2025
FEMUR ANGLE	Servo	4714	09/20/2024	3/22/2025






Left Hip-Femur Flexion Test
Hybrid III 50th Percentile Male
ATD Serial No: 064

Test Date: 03/11/2025
Test ID: D250740
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	26	Pass
Rotation Rate	deg/s	5.0 to 10.0	6.5	Pass
Moment at 30 Degrees	Nm	<= 94.9	84.6	Pass
Rotation Angle at 203.4 Nm	deg	40.0 to 50.0	45.7	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
LOAD CELL	FTSS	DN7673MY	03/22/2024	3/22/2025
FRAME ANGLE	Servo	3966	09/20/2024	3/22/2025
FEMUR ANGLE	Servo	4714	09/20/2024	3/22/2025



QUALIFICATION TEST RESULTS

PRE-TEST

HYBRID III 5TH PERCENTILE FEMALE - PASSENGER ATD

Hybrid III, 5th External Measurements
SN: 142

HYBRID III, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	775.0
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	438.2
C	H-POINT HEIGHT	Reference	81.3-86.3	81.8
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	148.3
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	83.0
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	124.4
G	BACK OF ELBOW TO WRIST PIVOT	back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	245.2
H	HEAD BACK TO BACKLINE	Back of Skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	43.4
I	SHOULDER TO- ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	281.1
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	197.2
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	537.2
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376	358.8
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	403.1
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414-439.4	435.2

HYBRID III, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	181.2
P	FOOT LENGTH	Tip of toe to rear of heel	218.5-233.7	227.3
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	475.0
S	HEAD BREADTH	The widest part of the head	137.1-147.3	138.6
T	HEAD DEPTH	Back of the head to the forehead	177.8-188	181.0
U	HIP BREADTH	The widest part of the hip	299.7-314.9	308.4
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	362.1
W	FOOT BREADTH	The widest part of the foot	78.8-94	82.8
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	545.2
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	870.7
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	779.9
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	350.1
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	170.0







Head Drop Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 02/18/2025
Test ID: D250501
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	18	Pass
Peak Resultant Acceleration	g	250 to 300	274	Pass
Peak Lateral Acceleration	g	-15.0 to 15.0	-6.5	Pass
Unimodal	%	within 10% of peak	2	Pass


Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
HEAD X	Endevco	T30974	11/25/2024	5/27/2025
HEAD Y	Endevco	T30975	11/25/2024	5/27/2025
HEAD Z	Endevco	T30976	11/25/2024	5/27/2025




Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	19	Pass
Pendulum Velocity	m/s	6.89 to 7.13	6.96	Pass
Pendulum Velocity At 10 ms After T0	m/s	2.1 to 2.5	2.2	Pass
Pendulum Velocity At 20 ms After T0	m/s	4.0 to 5.0	4.4	Pass
Pendulum Velocity At 30 ms After T0	m/s	5.8 to 7.0	6.8	Pass
Maximum "D" Plane Rotation	Deg	77 to 91	82	Pass
Occipital Condyle Moment within Rotation Corridor	Nm	69 to 83	72	Pass
Positive Moment Time Curve Decay to 10 Nm	ms	80 to 100	87	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PEND. ACCEL.	Endevco	AH5P1	01/13/2025	7/15/2025
NECK FORCE X	Denton	Ng2203FX	01/20/2025	1/20/2026
NECK MOMENT Y	Denton	NG2203MY	01/20/2025	1/20/2026
PEND. POT	Servo	4707	08/21/2024	2/20/2025
HEAD POT	Servo	7297	08/21/2024	2/20/2025


PEND. ACCEL. Velocity (m/s) vs Time (ms)



NECK ROTATION (deg) vs Time (ms)




OCCIPITAL MOMENT (Nm) vs Time (ms)




Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.9	Pass
Laboratory Relative Humidity	%	10 to 70	20	Pass
Pendulum Velocity	m/s	5.95 to 6.19	6.05	Pass
Pendulum Velocity At 10 ms After T0	m/s	1.5 to 1.9	1.68	Pass
Pendulum Velocity At 20 ms After T0	m/s	3.1 to 3.9	3.39	Pass
Pendulum Velocity At 30 ms After T0	m/s	4.6 to 5.6	4.94	Pass
Maximum "D" Plane Rotation	Deg	99 to 114	109.4	Pass
Occipital Condyle Moment within Rotation Corridor	Nm	-53 to -65	-55	Pass
Negative Moment Time Curve Decay to -10 Nm	ms	94 to 114	107	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PEND. ACCEL.	Endevco	AH5P1	01/13/2025	7/15/2025
NECK FORCE X	Denton	Ng2203FX	01/20/2025	1/20/2026
NECK MOMENT Y	Denton	NG2203MY	01/20/2025	1/20/2026
PEND. POT	Servo	4707	08/21/2024	2/20/2025
HEAD POT	Servo	7297	08/21/2024	2/20/2025


PEND. ACCEL. Velocity (m/s) vs Time (ms)



NECK ROTATION (deg) vs Time (ms)



OCCIPITAL MOMENT (Nm) vs Time (ms)






Thorax Impact Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 02/18/2025
Test ID: D250504
Test Technician: Jonah Pulokas


Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.1	Pass
Laboratory Relative Humidity	%	10 to 70	22	Pass
Probe Velocity	m/s	6.59 to 6.83	6.77	Pass
Peak Deflection	mm	50 to 58	53	Pass
Peak Resistive Force w/in Corridor	N	3900 to 4400	4371	Pass
Internal Hysteresis	%	69 to 85	76	Pass
Peak Force 18 mm - 50 mm	N	0 to 4600	4384	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PROBE	Endevco	P79577	09/18/2024	3/20/2025
CHEST DISPLACEMENT	Humanetics	142	10/29/2024	4/30/2025


FORCE (N) vs CHEST DISPLACEMENT (mm)



FORCE (N) vs Time (ms)



CHEST DISPLACEMENT (mm) vs Time (ms)






Right Knee Impact Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 02/18/2025
Test ID: D250505
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	20	Pass
Probe Velocity	m/s	2.07 to 2.13	2.12	Pass
Peak Probe Force	N	3450 to 4060	3463	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
KNEE PROBE	Endevco	P82128	12/03/2024	6/4/2025






Left Knee Impact Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 02/18/2025
Test ID: D250506
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.9	Pass
Laboratory Relative Humidity	%	10 to 70	20	Pass
Probe Velocity	m/s	2.07 to 2.13	2.12	Pass
Peak Probe Force	N	3450 to 4060	3461	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
KNEE PROBE	Endevco	P82128	12/03/2024	6/4/2025







Torso Flexion Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 02/18/2025
Test ID: D250507
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	17	Pass
Initial Angle	deg	0 to 20	17	Pass
Return Angle Relative to Initial	deg	-8 to 8	4	Pass
Force at 45 deg	N	320 to 390	376	Pass
Upper Torso Deflection Rate	deg/s	0.5 to 1.5	1.0	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
LOAD	Interface	479661	01/29/2025	7/31/2025
ANGLE	Seika	494819	05/21/2024	5/21/2025



QUALIFICATION TEST RESULTS

POST-TEST

HYBRID III 5TH PERCENTILE FEMALE - PASSENGER ATD







Head Drop Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 03/11/2025
Test ID: D250731
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	29	Pass
Peak Resultant Acceleration	g	250 to 300	297	Pass
Peak Lateral Acceleration	g	-15.0 to 15.0	2.5	Pass
Unimodal	%	within 10% of peak	3	Pass


Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
HEAD X	Endevco	T30974	11/25/2024	5/27/2025
HEAD Y	Endevco	T30975	11/25/2024	5/27/2025
HEAD Z	Endevco	T30976	11/25/2024	5/27/2025




Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	29	Pass
Pendulum Velocity	m/s	6.89 to 7.13	7.06	Pass
Pendulum Velocity At 10 ms After T0	m/s	2.1 to 2.5	2.2	Pass
Pendulum Velocity At 20 ms After T0	m/s	4.0 to 5.0	4.3	Pass
Pendulum Velocity At 30 ms After T0	m/s	5.8 to 7.0	6.5	Pass
Maximum "D" Plane Rotation	Deg	77 to 91	83	Pass
Occipital Condyle Moment within Rotation Corridor	Nm	69 to 83	75	Pass
Positive Moment Time Curve Decay to 10 Nm	ms	80 to 100	88	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PEND. ACCEL.	Endevco	AH5P1	01/13/2025	7/15/2025
NECK FORCE X	Denton	NG2203FX	01/20/2025	1/20/2026
NECK MOMENT Y	Denton	NG2203MY	01/20/2025	1/20/2026
PEND. POT	Servo	4707	02/25/2025	8/27/2025
HEAD POT	Servo	7297	02/25/2025	8/27/2025


PEND. ACCEL. Velocity (m/s) vs Time (ms)



NECK ROTATION (deg) vs Time (ms)




OCCIPITAL MOMENT (Nm) vs Time (ms)




Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.9	Pass
Laboratory Relative Humidity	%	10 to 70	28	Pass
Pendulum Velocity	m/s	5.95 to 6.19	6.12	Pass
Pendulum Velocity At 10 ms After T0	m/s	1.5 to 1.9	1.76	Pass
Pendulum Velocity At 20 ms After T0	m/s	3.1 to 3.9	3.47	Pass
Pendulum Velocity At 30 ms After T0	m/s	4.6 to 5.6	4.94	Pass
Maximum "D" Plane Rotation	Deg	99 to 114	108.6	Pass
Occipital Condyle Moment within Rotation Corridor	Nm	-53 to -65	-54	Pass
Negative Moment Time Curve Decay to -10 Nm	ms	94 to 114	107	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PEND. ACCEL.	Endevco	AH5P1	01/13/2025	7/15/2025
NECK FORCE X	Denton	NG2203FX	01/20/2025	1/20/2026
NECK MOMENT Y	Denton	NG2203MY	01/20/2025	1/20/2026
PEND. POT	Servo	4707	02/25/2025	8/27/2025
HEAD POT	Servo	7297	02/25/2025	8/27/2025


PEND. ACCEL. Velocity (m/s) vs Time (ms)



NECK ROTATION (deg) vs Time (ms)



OCCIPITAL MOMENT (Nm) vs Time (ms)






Thorax Impact Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 03/11/2025
Test ID: D250734
Test Technician: Jonah Pulokas


Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	20.6 to 22.2	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	27	Pass
Probe Velocity	m/s	6.59 to 6.83	6.61	Pass
Peak Deflection	mm	50 to 58	50	Pass
Peak Resistive Force w/in Corridor	N	3900 to 4400	4075	Pass
Internal Hysteresis	%	69 to 85	75	Pass
Peak Force 18 mm - 50 mm	N	0 to 4600	4379	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
PROBE	Endevco	P79577	09/18/2024	3/20/2025
CHEST DISPLACEMENT	Humanetics	142	10/29/2024	4/30/2025


FORCE (N) vs CHEST DISPLACEMENT (mm)



FORCE (N) vs Time (ms)



CHEST DISPLACEMENT (mm) vs Time (ms)






Right Knee Impact Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 03/11/2025
Test ID: D250735
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.9	Pass
Laboratory Relative Humidity	%	10 to 70	28	Pass
Probe Velocity	m/s	2.07 to 2.13	2.10	Pass
Peak Probe Force	N	3450 to 4060	3625	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
KNEE PROBE	Endevco	P82128	12/03/2024	6/4/2025






Left Knee Impact Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 03/11/2025
Test ID: D250736
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.5	Pass
Laboratory Relative Humidity	%	10 to 70	29	Pass
Probe Velocity	m/s	2.07 to 2.13	2.10	Pass
Peak Probe Force	N	3450 to 4060	3597	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
KNEE PROBE	Endevco	P82128	12/03/2024	6/4/2025







Torso Flexion Test
Hybrid III 5th Percentile Female
ATD Serial No: 142

Test Date: 03/11/2025
Test ID: D250737
Test Technician: Jonah Pulokas

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	°C	18.9 to 25.6	21.4	Pass
Laboratory Relative Humidity	%	10 to 70	28	Pass
Initial Angle	deg	0 to 20	18	Pass
Return Angle Relative to Initial	deg	-8 to 8	3	Pass
Force at 45 deg	N	320 to 390	354	Pass
Upper Torso Deflection Rate	deg/s	0.5 to 1.5	0.8	Pass

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
LOAD	Interface	479661	01/29/2025	7/31/2025
ANGLE	Seika	494819	05/21/2024	5/21/2025



APPENDIX D
TEST EQUIPMENT AND INSTRUMENTATION CALIBRATION

TABLE 1 – DRIVER DUMMY INSTRUMENTATION

Instrument Location			Axis	Hybrid III 50 th S/N 064		
				Serial Number	Manufacturer	Calibration Date
Head Accelerometers	Primary		X	T30960	Endevco	11/19/2024
			Y	P79743	Endevco	11/19/2024
			Z	P79741	Endevco	11/19/2024
	Redundant		X	P79744	Endevco	11/19/2024
			Y	P94834	Endevco	11/19/2024
			Z	P94856	Endevco	11/19/2024
Head Angular Rate Sensors			X	ARS7502	DTS	07/31/2024
			Y	ARS7524	DTS	07/31/2024
			Z	ARS7547	DTS	07/31/2024
Upper Neck Load Cell		Fx, Fy, Fz Mx, My, Mz	NG2022FX	Denton	05/24/2024	
Chest Accelerometers	Primary		X	P86793	Endevco	11/19/2024
			Y	P88348	Endevco	11/19/2024
			Z	P86792	Endevco	11/19/2024
	Redundant		X	P88667	Endevco	11/19/2024
			Y	P94109	Endevco	11/19/2024
			Z	P88666	Endevco	11/19/2024
Chest Potentiometer		X	064	Humanetics	11/19/2024	
Pelvis Accelerometers			X	P97742	Endevco	11/19/2024
			Y	P96038	Endevco	11/19/2024
			Z	P95526	Endevco	11/19/2024
Femur Load Cells	Right	Primary	Z	FG121PFZ	Denton	11/19/2024
		Redundant	Z	FG121RFZ	Denton	11/19/2024
	Left	Primary	Z	FG122PFZ	Denton	11/19/2024
		Redundant	Z	FG122RFZ	Denton	11/19/2024
Tibia Load Cells	Right	Upper	Mx, My, Fz	TG405FZ	Denton	11/12/2024
		Lower	Mx, My, Fz	AG368FZ	Denton	11/11/2024
	Left	Upper	Mx, My, Fz	TG475FZ	Denton	11/12/2024
		Lower	Mx, My, Fz	AG504FZ	Denton	11/12/2024
Foot Accelerometers	Right	Rear	X	T22486	Endevco	11/19/2024
			Z	P97382	Endevco	11/19/2024
		Front	Z	P82120	Endevco	11/19/2024
	Left	Rear	X	T16468	Endevco	11/19/2024
			Z	T32154	Endevco	11/19/2024
		Front	Z	T32190	Endevco	11/19/2024
Seat Belt Load Cells		Lap		SBG161	FTSS	10/21/2024
		Shoulder		SBG157	FTSS	10/21/2024

TABLE 2 – FRONT PASSENGER DUMMY INSTRUMENTATION

Instrument Location			Axis	Hybrid III 5 th S/N 142		
				Serial Number	Manufacturer	Calibration Date
Head Accelerometers	Primary		X	P94799	Endevco	10/29/2024
			Y	P94800	Endevco	10/29/2024
			Z	P94801	Endevco	10/29/2024
	Redundant		X	P94802	Endevco	10/29/2024
			Y	P94803	Endevco	10/29/2024
			Z	P97377	Endevco	10/29/2024
Head Angular Rate Sensors			X	ARS7413	DTS	07/31/2024
			Y	ARS7421	DTS	07/31/2024
			Z	ARS7423	DTS	07/31/2024
Upper Neck Load Cell			Fx, Fy, Fz Mx, My, Mz	NG2203FX	Denton	01/20/2025
Chest Accelerometers	Primary		X	P88719	Endevco	10/29/2024
			Y	P94785	Endevco	10/29/2024
			Z	P94793	Endevco	10/29/2024
	Redundant		X	P95322	Endevco	10/29/2024
			Y	P95370	Endevco	10/29/2024
			Z	T30901	Endevco	10/29/2024
Chest Potentiometer			X	142	Humanetics	10/29/2024
Pelvis Accelerometers			X	P94798	Endevco	10/29/2024
			Y	P82646	Endevco	10/29/2024
			Z	P97705	Endevco	10/29/2024
Femur Load Cells	Right	Primary	Z	FG126PFZ	Denton	10/29/2024
		Redundant	Z	FG126RFZ	Denton	10/29/2024
	Left	Primary	Z	FG127PFZ	Denton	10/29/2024
		Redundant	Z	FG127RFZ	Denton	10/29/2024
Tibia Load Cells	Right	Upper	Mx, My, Fz	TG408FZ	Denton	01/17/2025
		Lower	Mx, My, Fz	AG116FZ	Denton	01/17/2025
	Left	Upper	Mx, My, Fz	TG480FZ	Denton	01/17/2025
		Lower	Mx, My, Fz	AG502FZ	Denton	01/17/2025
Foot Accelerometers	Right	Rear	X	P94795	Endevco	10/29/2024
			Z	P94796	Endevco	10/29/2024
		Front	Z	P94797	Endevco	10/29/2024
	Left	Rear	X	P83167	Endevco	10/29/2024
			Z	P83168	Endevco	10/29/2024
		Front	Z	P83169	Endevco	10/29/2024
Seat Belt Load Cells		Lap		SBG273	FTSS	10/21/2024
		Shoulder		SBG272	FTSS	10/21/2024

TABLE 3 – VEHICLE INSTRUMENTATION

Instrument Location			Axis	Serial Number	Manufacturer	Calibration Date
Crossmember / Rear Seat Accelerometers	Left	Primary	X	T45144	Endevco	02/09/2025
			Z	T45066	Endevco	02/09/2025
		Redundant	X	T45280	Endevco	02/09/2025
	Right	Primary	X	T44840	Endevco	12/04/2024
			Z	T44852	Endevco	12/04/2024
		Redundant	X	T45279	Endevco	02/03/2025
Engine Accelerometers		Top	X	T43504	Endevco	02/14/2025
		Bottom	X	T42427	Endevco	02/09/2025