


REPORT NUMBER: 208-MGA-2022-007

**DUMMY PERFORMANCE CALIBRATIONS
FMVSS 208**

**HONDA OF CANADA MFG., A DIVISION OF HONDA OF CANADA INC.
2022 HONDA CIVIC PASSENGER CAR
NHTSA NO.: C20225305**

**PREPARED BY:
MGA RESEARCH CORPORATION
5000 WARREN ROAD
BURLINGTON, WI 53105**



TEST DATE: DECEMBER 8, 2022

FINAL REPORT DATE: DECEMBER 22, 2022

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
OFFICE OF ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
1200 NEW JERSEY AVENUE, S.E., NVS-220
WASHINGTON, D.C. 20590**

TABLE OF CONTENTS

		<u>Page No.</u>
DUMMY S/N: 510	PRE-TEST CERTIFICATION DATA	1-1
	PASSED ALL CALIBRATION CHECKS	
DUMMY S/N: 510	POST-TEST CERTIFICATION DATA	2-1
	PASSED ALL CALIBRATION CHECKS	
DUMMY S/N: 507	PRE-TEST CERTIFICATION DATA	3-1
	PASSED ALL CALIBRATION CHECKS	
DUMMY S/N: 507	POST-TEST CERTIFICATION DATA	4-1
	PASSED ALL CALIBRATION CHECKS	

EXTERNAL DIMENSIONS

HYBRID III 5 th SN #510, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	786.2
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	450.0
C	H-POINT HEIGHT	Reference	81.3-86.3	84.1
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	148.3
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	82.7
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	133.9
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249.6
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.0
I	SHOULDER TO ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	278.5
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	202.1
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	543.6
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	358.5
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	397.0
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.2

HYBRID III 5 th SN #510, PART 572, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	181.0
P	FOOT LENGTH	Tip of toe to rear of heel	218.5-233.7	221.4
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	482.0
S	HEAD BREADTH	The widest part of the head	137.1-147.3	138.6
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	179.9
U	HIP BREADTH	The widest part of the hip	299.7-314.9	301.5
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	351.4
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	79.0
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	539.5
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	876.4
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	788.3
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	334.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	168.0

DATA SHEET B3
HEAD DROP TEST (572.132) (5th Female)

Dummy Serial Number: 510

Test Date: 11/30/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
 N/A, ONLY one head drop performed
2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
3. The head accelerometer mounting plate screws (10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
4. Accelerometers and their respective mounts are smooth and clean.
5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.6°C</u> |
| Record the minimum temperature: | <u>21.3°C</u> |
| Record the maximum humidity: | <u>20%</u> |
| Record the minimum humidity: | <u>13%</u> |
8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage
9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))
10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the

forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance: 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance: 501 mm

Record the left side distance: 501 mm

X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish: 24.8 micro inches

X 13. The impact surface is rigidly supported. (572.132(c)(4))

X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness: 50.9 mm

Record width: 604 mm


Record length: 595 mm

X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches \pm 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	274 g
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-7.9 g

X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

11/30/2022
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test ID: D222791

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	20	Pass
Peak Resultant Acceleration	G's	250 to 300	274	Pass
Peak Lateral Acceleration	G's	<= +/- 15.0	-7.9	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass





 Laboratory Technician



11/30/2022

 Test Date



 Approved By





DATA SHEET B4
NECK FLEXION TEST (572.132) (5th Female)

Dummy Serial Number: 510

Test Date: 12/01/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

1. It has been at least 30 minutes since the last flexion test. (572.137(q))
 N/A, ONLY one neck test performed
2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.7°C</u> |
| Record the minimum temperature: | <u>21.4°C</u> |
| Record the maximum humidity: | <u>19%</u> |
| Record the minimum humidity: | <u>12%</u> |
4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No damage
5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
- Record findings and actions: No Deterioration; Hardness: Front 89; Back 90.
6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

- X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))
- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:
Neck Flexion Test Results (572.133(b)(1) & 572.133(c)(4)(I & ii))

Parameter		Specification	Results
Pendulum impact speed		6.89 m/s \leq speed \leq 7.13 m/s	7.06 m/s
Pendulum ΔV with respect to impact speed	@ 10 ms	2.1 m/s $\leq \Delta V \leq$ 2.5 m/s	2.4 m/s
	@ 20 ms	4.0 m/s $\leq \Delta V \leq$ 5.0 m/s	4.8 m/s
	@ 30 ms	5.8 m/s $\leq \Delta V \leq$ 7.0 m/s	6.7 m/s
Plane D Rotation		Peak moment* 69 Nm \leq moment \leq 83 Nm during the following rotation range 77° \leq angle \leq 91°	72 Nm @ 81 degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm 80 ms \leq time \leq 100 ms	85 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

12/01/2022
Date

MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D222792

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.7	Pass
Laboratory Relative Humidity		%	10 to 70	19	Pass
Pendulum Speed		m/s	6.89 to 7.13	7.06	Pass
Pendulum Velocity	10 ms	m/s	2.1 to 2.5	2.4	Pass
	20 ms	m/s	4.0 to 5.0	4.8	Pass
	30 ms	m/s	5.8 to 7.0	6.7	Pass
D Plane Rotation	Max	deg	77 to 91	81	Pass
Occipital Condyle Moment within Rotation Corridor		Nm	69 to 83	72	Pass
Positive Moment Time Curve Decay to 10 Nm		ms	80 to 100	85	Pass
Overall Results					Pass





 Laboratory Technician


12/01/2022

 Test Date



 Approved By





DATA SHEET B5
NECK EXTENSION TEST (572.133) (5th Female)

Dummy Serial Number: 510

Test Date: 12/01/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

1. It has been at least 30 minutes since the last extension test. (572.137(q))
 N/A, ONLY one neck test performed
2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.6°C</u> |
| Record the minimum temperature: | <u>21.3°C</u> |
| Record the maximum humidity: | <u>22%</u> |
| Record the minimum humidity: | <u>15%</u> |
4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No damage
5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
- Record findings and actions: No Deterioration; Hardness: Front 89; Back 90.
6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

- X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))
- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:
Neck Extension Test Results (572.133(b)(2) & 572.133(c)(4)(I & ii))

Parameter		Specification	Results
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.12 m/s
Pendulum ΔV with respect to impact speed	@ 10 ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.7 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.5 m/s
	@ 30 ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.1 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	-55 Nm @ 107 degrees
Positive Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	102 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

12/01/2022
Date

**MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE**

ATD Serial No: 510

Test I.D.: D222793

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.6	Pass
Laboratory Relative Humidity		%	10 to 70	22	Pass
Pendulum Speed		m/s	5.95 to 6.19	6.12	Pass
Pendulum Velocity	10 ms	m/s	1.5 to 1.9	1.7	Pass
	20 ms	m/s	3.1 to 3.9	3.5	Pass
	30 ms	m/s	4.6 to 5.6	5.1	Pass
D Plane Rotation	Max	deg	99 to 114	107	Pass
Occipital Condyle Moment within Rotation Corridor		Nm	-65 to -53	-55	Pass
Negative Moment Time Curve Decay to -10 Nm		ms	94 to 114	102	Pass
Overall Results					Pass



Laboratory Technician

12/01/2022
Test Date



Approved By




PENDULUM VELOCITY (m/s) vs TIME (ms)



NECK ROTATION (DEG) vs TIME (ms)





DATA SHEET B6
THORAX IMPACT TEST (572.134) (5th Female)

Dummy Serial Number: 510

Test Date: 12/02/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))
 N/A, ONLY one thorax impact test performed
2. The test fixture conforms to the specifications in Figure 11B.
3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))
4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature:	<u>21.7°C</u>
Record the minimum temperature:	<u>21.4°C</u>
Record the maximum humidity:	<u>32%</u>
Record the minimum humidity:	<u>25%</u>

5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

- No Damage

- Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage:

- The following repairs or replacement was performed. Record:

- X 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))
- X 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504) that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.
- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

- X 16. Complete the following table:
 Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.60 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4218 N
Peak Force** between 18.0 and 50.0 mm chest compression	Peak Force $\leq 4600 \text{ N}$	4355 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	73%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

- X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.



 Signature

12/02/2022

 Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE


ATD Serial No: 510


Test I.D: D222794

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.7	Pass
Relative Humidity	%	10 to 70	32	Pass
Probe Speed	m/s	6.59 to 6.83	6.60	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	N	3900 to 4400	4218	Pass
Internal Hysteresis	%	69 to 85	73	Pass
Peak Force 18 mm - 50 mm	N	<= 4600	4355	Pass
Overall Test Results				Pass


 Laboratory Technician

12/02/2022
 Test Date


 Approved By



DATA SHEET B7
TORSO FLEXION TEST (572.135) (5th Female)

Dummy Serial Number: 510

Test Date: 11/29/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
 N/A, ONLY one torso flexion test performed
2. The test fixture conforms to the specifications in Figure 13B.
3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
 With legs below femurs.
 Without legs below femurs.
4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.7°C</u> |
| Record the minimum temperature: | <u>21.4°C</u> |
| Record the maximum humidity: | <u>37%</u> |
| Record the minimum humidity: | <u>24%</u> |
5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

- X 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- X 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- X 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
 Record reference plane angle (max. allowed 20°): See Result Table
- X 12. Attach the pull cable and the load cell. (572.135(c)(8))
- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at 45° ± 0.5° of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at 45° ± 0.5° of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), 572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle ≤ 20°	18 deg
Torso rotation rate	0.5°/s ≤ rate ≤ 1.5°/s	0.5 deg/sec
Force at 45° ± 0.5°	320 N ≤ force ≤ 390 N	380 N
Final ref. plane angle	Initial ref. plane angle ± 8°	1 deg

 Jon Seve
 Signature

 11/29/2022
 Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D222797


Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	37	Pass
Initial Angle	deg	0 to 20	18	Pass
Return Angle	deg	+/- 8	1	Pass
Force at 45 deg	N	320 to 390	380	Pass
Upper Torso Deflection Rate	deg/s	0.5 to 1.5	0.5	Pass
Overall Result				Pass





 Laboratory Technician

11/29/2022

 Test Date



 Approved By



DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136) (5th Female)

Dummy Serial Number: 510

Test Date: 11/29/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

1. It has been at least 30 minutes since the last knee impact test. (572.137(q))
 N/A, ONLY one knee impact test performed
2. The test fixture conforms to the specifications in Figure 14B.
3. The knee assembly (880105-528L), lower leg structural replacement (880105- 603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))
4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.8°C</u> |
| Record the minimum temperature: | <u>21.5°C</u> |
| Record the maximum humidity: | <u>31%</u> |
| Record the minimum humidity: | <u>24%</u> |
5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))
6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))
7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))
8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))
9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:
Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3682 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.



Signature

11/29/2022
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D222796

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	31	Pass
Probe Speed	m/s	2.07 to 2.13	2.11	Pass
Maximum Force	N	3450 to 4060	3682	Pass
Overall Test Results				Pass



 Laboratory Technician

11/29/2022

 Test Date




 Approved By



TEST DESC: LEFT KNEE
VELOCITY: 6.92 ft/s, 2.11 m/s

TEST DATE: 11/29/2022
TEST #: D222796



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136) (5th Female)

Dummy Serial Number: 510

Test Date: 11/29/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

1. It has been at least 30 minutes since the last knee impact test. (572.137(q))
 N/A, ONLY one knee impact test performed
2. The test fixture conforms to the specifications in Figure 14B.
3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))
4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature:	<u>21.8°C</u>
Record the minimum temperature:	<u>21.5°C</u>
Record the maximum humidity:	<u>31%</u>
Record the minimum humidity:	<u>24%</u>


5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))
6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))
7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))
8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))
9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.
10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))		
Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3886 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.



Signature

11/29/2022
Date

**MGA RESEARCH CORPORATION
 RIGHT KNEE IMPACT TEST
 HYBRID III 5TH PERCENTILE**

ATD Serial No: 510

Test I.D: D222795

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	31	Pass
Probe Speed	m/s	2.07 to 2.13	2.11	Pass
Maximum Force	N	3450 to 4060	3886	Pass
Overall Test Results				Pass



 Laboratory Technician

11/29/2022

 Test Date




 Approved By



TEST DESC: RIGHT KNEE
VELOCITY: 6.92 ft/s, 2.11 m/s


TEST DATE: 11/29/2022
TEST #: D222795



DATA SHEET B10
PART 572 INSTRUMENTATION CALIBRATION INFORMATION

I.D. NO.	MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF LAST CALIBRATION	DATE OF NEXT CALIBRATION
DUMMY INSTRUMENTATION					
HEAD ACCELEROMETERS					
(1) LONGITUDINAL	Endevco	7264C-2KTZ-2-360M17	P79575	11/16/2022	05/18/2023
(2) LATERAL	Endevco	7264C-2KTZ-2-360M17	P79577	11/16/2022	05/18/2023
(3) VERTICAL	Endevco	7264C-2KTZ-2-360M17	P79578	11/16/2022	05/18/2023
NECK TRANSDUCER	Denton	1716A	N1865	10/28/2022	04/29/2023
CHEST ACCELEROMETERS					
(1) LONGITUDINAL	Endevco	7264C-2KTZ-360M17	P88335	11/16/2022	05/18/2023
(2) LATERAL	Endevco	7264C-2KTZ-360M17	P93609	11/16/2022	05/18/2023
(3) VERTICAL	Endevco	7264C-2KTZ-360M17	P88334	11/16/2022	05/18/2023
CHEST POTENTIOMETER	Humanetics	880105-1080	510	11/16/2022	05/18/2023
FEMUR LOAD CELLS					
(1) RIGHT FEMUR	Denton	2121AJLN2	F2179	11/16/2022	5/18/2023
(2) LEFT FEMUR	Denton	2121AJLN2	F2170	11/16/2022	5/18/2023
LABORATORY INSTRUMENTATION					
NECK PENDULUM ACCELEROMETER	Endevco	7231C-750	AH5P1	07/15/2022	01/14/2023
THORAX PENDULUM ACCELEROMETER	Endevco	7264C-2KTZ-360M17	P97372	11/18/2022	05/20/2023
KNEE PENDULUM ACCELEROMETER	Endevco	7264C-2KTZ-2-360M17	P82128	5/31/2022	06/01/2023
NECK ROTATION TRANSDUCER 1 (OPTIONAL)	Servo	14CBI-2897	4707	08/12/2022	02/11/2023
NECK ROTATION TRANSDUCER 2 (OPTIONAL)	Servo	14CBI-2897	7297	08/12/2022	02/11/2023

LABORATORY TECHNICIAN: _____



DATA SHEET B3
HEAD DROP TEST (572.132) (5th Female)

Dummy Serial Number: 510

Test Date: 12/09/2022

Technician: Nathaniel Benjamin

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
 N/A, ONLY one head drop performed
2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
3. The head accelerometer mounting plate screws (10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
4. Accelerometers and their respective mounts are smooth and clean.
5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.6°C</u> |
| Record the minimum temperature: | <u>20.3°C</u> |
| Record the maximum humidity: | <u>27%</u> |
| Record the minimum humidity: | <u>17%</u> |
8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage

X 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))
Record the actual distance: 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))
Record the right side distance: 501 mm
Record the left side distance: 501 mm

X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))
Record actual micro finish: 24.8 micro inches

X 13. The impact surface is rigidly supported. (572.132(c)(4))

X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))
Record thickness: 50.9 mm
Record width: 604 mm
Record length: 595 mm

X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches \pm 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	276 g
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	1.4 g

X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.

Nathaniel Benjamin
Signature

12/09/2022
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510



Test ID: D222841



Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	27	Pass
Peak Resultant Acceleration	G's	250 to 300	276	Pass
Peak Lateral Acceleration	G's	<= +/- 15.0	1.4	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass

Nathaniel Benjamin
 Laboratory Technician

12/09/2022
 Test Date

Jose Salazar
 Approved By





DATA SHEET B4
NECK FLEXION TEST (572.132) (5th Female)

Dummy Serial Number: 510

Test Date: 12/12/2022

Technician: Jon Love

- Pre test calibration
 X Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

- X 1. It has been at least 30 minutes since the last flexion test. (572.137(q))
 X N/A, ONLY one neck test performed
- X 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- X 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|---------------------------------|---------------------------|
| Record the maximum temperature: | <u> 21.6°C </u> |
| Record the minimum temperature: | <u> 20.3°C </u> |
| Record the maximum humidity: | <u> 33% </u> |
| Record the minimum humidity: | <u> 23% </u> |
- X 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No damage
- X 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
- Record findings and actions: No Deterioration; Hardness: Front 89; Back 90.
- X 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

- X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J2111/1 MAR95. (572.137(m))
- X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))
- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:
Neck Flexion Test Results (572.133(b)(1) & 572.133(c)(4)(I & ii))

Parameter		Specification	Results
Pendulum impact speed		6.89 m/s \leq speed \leq 7.13 m/s	6.96 m/s
Pendulum ΔV with respect to impact speed	@ 10 ms	2.1 m/s $\leq \Delta V \leq$ 2.5 m/s	2.4 m/s
	@ 20 ms	4.0 m/s $\leq \Delta V \leq$ 5.0 m/s	4.6 m/s
	@ 30 ms	5.8 m/s $\leq \Delta V \leq$ 7.0 m/s	6.5 m/s
Plane D Rotation		Peak moment* 69 Nm \leq moment \leq 83 Nm during the following rotation range 77° \leq angle \leq 91°	70 Nm @ 81 degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm 80 ms \leq time \leq 100 ms	86 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

12/12/2022
Date

MGA RESEARCH CORPORATION

NECK FLEXION TEST

HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D: D222842

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.6	Pass
Laboratory Relative Humidity		%	10 to 70	33	Pass
Pendulum Speed		m/s	6.89 to 7.13	6.96	Pass
Pendulum Velocity	10 ms	m/s	2.1 to 2.5	2.4	Pass
	20 ms	m/s	4.0 to 5.0	4.6	Pass
	30 ms	m/s	5.8 to 7.0	6.5	Pass
D Plane Rotation	Max	deg	77 to 91	81	Pass
Occipital Condyle Moment within Rotation Corridor		Nm	69 to 83	70	Pass
Positive Moment Time Curve Decay to 10 Nm		ms	80 to 100	86	Pass
Overall Results					Pass





 Laboratory Technician

12/12/2022

 Test Date




 Approved By





TEST DESC: NECK FLEXION
VELOCITY: 22.83 ft/s, 6.96 m/s

TEST DATE: 12/12/2022
TEST #: D222842



DATA SHEET B5
NECK EXTENSION TEST (572.133) (5th Female)

Dummy Serial Number: 510

Test Date: 12/12/2022

Technician: Jon Love

- Pre test calibration
X Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

- X 1. It has been at least 30 minutes since the last extension test. (572.137(q))
 X N/A, ONLY one neck test performed
- X 2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
- X 3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.6°C</u> |
| Record the minimum temperature: | <u>20.3°C</u> |
| Record the maximum humidity: | <u>33%</u> |
| Record the minimum humidity: | <u>23%</u> |
- X 4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- | | |
|------------------------------|------------------|
| Record findings and actions: | <u>No damage</u> |
|------------------------------|------------------|
- X 5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
- | | |
|------------------------------|---|
| Record findings and actions: | <u>No Deterioration; Hardness: Front 89; Back 90.</u> |
|------------------------------|---|
- X 6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

- X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))
- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:
Neck Extension Test Results (572.133(b)(2) & 572.133(c)(4)(I & ii))

Parameter		Specification	Results
Pendulum impact speed		5.95 m/s \leq speed \leq 6.19 m/s	5.98 m/s
Pendulum ΔV with respect to impact speed	@ 10 ms	1.5 m/s $\leq \Delta V \leq$ 1.9 m/s	1.7 m/s
	@ 20 ms	3.1 m/s $\leq \Delta V \leq$ 3.9 m/s	3.5 m/s
	@ 30 ms	4.6 m/s $\leq \Delta V \leq$ 5.6 m/s	5.1 m/s
Plane D Rotation		Peak moment* -65 Nm \leq moment \leq -53 Nm during the following rotation range 99° \leq angle \leq 114°	-58 Nm @ 112 degrees
Positive Moment Decay** (Extension)		Time to decay to -10 Nm 94 ms \leq time \leq 114 ms	103 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

12/12/2022
Date

**MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE**

ATD Serial No: 510



Test I.D.: D222843

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.6	Pass
Laboratory Relative Humidity		%	10 to 70	33	Pass
Pendulum Speed		m/s	5.95 to 6.19	5.98	Pass
Pendulum Velocity	10 ms	m/s	1.5 to 1.9	1.7	Pass
	20 ms	m/s	3.1 to 3.9	3.5	Pass
	30 ms	m/s	4.6 to 5.6	5.1	Pass
D Plane Rotation	Max	deg	99 to 114	112	Pass
Occipital Condyle Moment within Rotation Corridor		Nm	-65 to -53	-58	Pass
Negative Moment Time Curve Decay to -10 Nm		ms	94 to 114	103	Pass
Overall Results					Pass


Laboratory Technician

12/12/2022
Test Date



Approved By





TEST DESC: NECK EXTENSION
VELOCITY: 19.61 ft/s, 5.98 m/s

TEST DATE: 12/12/2022
TEST #: D222843



DATA SHEET B6
THORAX IMPACT TEST (572.134) (5th Female)

Dummy Serial Number: 510

Test Date: 12/09/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))
 N/A, ONLY one thorax impact test performed
2. The test fixture conforms to the specifications in Figure 11B.
3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))
4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature:	<u>21.6°C</u>
Record the minimum temperature:	<u>20.3°C</u>
Record the maximum humidity:	<u>27%</u>
Record the minimum humidity:	<u>17%</u>

5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

- No Damage

- Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage

- The following repairs or replacement was performed. Record

- X 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))
- X 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504) that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.
- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is 12.7 mm ± 1 mm below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is 6.71 m/s ± 0.12 m/s. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

- X 16. Complete the following table:
 Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))

Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.68 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51.0 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4304 N
Peak Force** between 18.0 and 50.0 mm chest compression	Peak Force $\leq 4600 \text{ N}$	4397 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	73%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

- X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.



 Signature

12/09/2022

 Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE


ATD Serial No: 510


Test I.D: D222844

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.6	Pass
Relative Humidity	%	10 to 70	27	Pass
Probe Speed	m/s	6.59 to 6.83	6.68	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	N	3900 to 4400	4304	Pass
Internal Hysteresis	%	69 to 85	73	Pass
Peak Force 18 mm - 50 mm	N	<= 4600	4397	Pass
Overall Test Results				Pass


 Laboratory Technician

12/09/2022
 Test Date


 Approved By



DATA SHEET B7
TORSO FLEXION TEST (572.135) (5th Female)

Dummy Serial Number: 510

Test Date: 12/13/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
 N/A, ONLY one torso flexion test performed
2. The test fixture conforms to the specifications in Figure 13B.
3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
 With legs below femurs.
 Without legs below femurs.
4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.8°C</u> |
| Record the minimum temperature: | <u>20.5°C</u> |
| Record the maximum humidity: | <u>27%</u> |
| Record the minimum humidity: | <u>17%</u> |
5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

- X 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- X 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- X 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
 Record reference plane angle (max. allowed 20°): See Result Table
- X 12. Attach the pull cable and the load cell. (572.135(c)(8))
- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at 45° ± 0.5° of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at 45° ± 0.5° of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), 572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle ≤ 20°	15 deg
Torso rotation rate	0.5°/s ≤ rate ≤ 1.5°/s	0.7 deg/sec
Force at 45° ± 0.5°	320 N ≤ force ≤ 390 N	388 N
Final ref. plane angle	Initial ref. plane angle ± 8°	2 deg

 Jon Seve
 Signature


 12/13/2022
 Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510



Test I.D: D222847

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	27	Pass
Initial Angle	deg	0 to 20	15	Pass
Return Angle	deg	+/- 8	2	Pass
Force at 45 deg	N	320 to 390	388	Pass
Upper Torso Deflection Rate	deg/s	0.5 to 1.5	0.7	Pass
Overall Result				Pass


 Laboratory Technician

12/13/2022
 Test Date


 Approved By



DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136) (5th Female)

Dummy Serial Number: 510

Test Date: 12/09/2022

Technician: Jon Love

- Pre test calibration
X Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

- X 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))
 X N/A, ONLY one knee impact test performed
- X 2. The test fixture conforms to the specifications in Figure 14B.
- X 3. The knee assembly (880105-528L), lower leg structural replacement (880105- 603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))
- X 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature:	<u>21.7°C</u>
Record the minimum temperature:	<u>20.4°C</u>
Record the maximum humidity:	<u>28%</u>
Record the minimum humidity:	<u>18%</u>

- X 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))
- X 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))
- X 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))
- X 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))
- X 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:
Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.09 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3726 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

12/09/2022
Date


MGA RESEARCH CORPORATION

**LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE**

ATD Serial No: 510

Test I.D: D222846

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	28	Pass
Probe Speed	m/s	2.07 to 2.13	2.09	Pass
Maximum Force	N	3450 to 4060	3726	Pass
Overall Test Results				Pass



Laboratory Technician

12/09/2022

Test Date




Approved By



TEST DESC: LEFT KNEE
VELOCITY: 6.86 ft/s, 2.09 m/s

TEST DATE: 12/09/2022
TEST #: D222846



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136) (5th Female)

Dummy Serial Number: 510

Test Date: 12/09/2022

Technician: Jon Love

- Pre test calibration
X Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

- X 1. It has been at least 30 minutes since the last knee impact test. (572.137(q))
 X N/A, ONLY one knee impact test performed
- X 2. The test fixture conforms to the specifications in Figure 14B.
- X 3. The knee assembly (880105-528R), lower leg structural replacement (880105- 603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))
- X 4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature:	<u>21.6°C</u>
Record the minimum temperature:	<u>20.3°C</u>
Record the maximum humidity:	<u>27%</u>
Record the minimum humidity:	<u>17%</u>

- X 5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))
- X 6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))
- X 7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))
- X 8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))
- X 9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:
Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3872 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature


12/09/2022
Date

MGA RESEARCH CORPORATION
RIGHT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 510

Test I.D.: D222845

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	27	Pass
Probe Speed	m/s	2.07 to 2.13	2.10	Pass
Maximum Force	N	3450 to 4060	3872	Pass
Overall Test Results				Pass


 Laboratory Technician


12/09/2022
 Test Date


 Approved By



TEST DESC: RIGHT KNEE
VELOCITY: 6.89 ft/s, 2.10 m/s

TEST DATE: 12/09/2022
TEST #: D222845



DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number: 510

Test Date: 12/13/2022

Technician: Jon Love

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damage	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:



Signature

12/13/2022
Date

Describe the repair or replacement of parts:

Checked by:



Signature

12/13/2022
Date

DATA SHEET B10

PART 572 INSTRUMENTATION CALIBRATION INFORMATION

I.D. NO.	MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF LAST CALIBRATION	DATE OF NEXT CALIBRATION
DUMMY INSTRUMENTATION					
HEAD ACCELEROMETERS					
(1) LONGITUDINAL	Endevco	7264C-2KTZ-2-360M17	P79775	11/16/2022	05/18/2023
(2) LATERAL	Endevco	7264C-2KTZ-2-360M17	P79577	11/16/2022	05/18/2023
(3) VERTICAL	Endevco	7264C-2KTZ-2-360M17	P79578	11/16/2022	05/18/2023
NECK TRANSDUCER	Denton	1716A	N1865	10/28/2022	04/29/2023
CHEST ACCELEROMETERS					
(1) LONGITUDINAL	Endevco	7264C-2KTZ-2-360M17	P88335	11/16/2022	05/18/2023
(2) LATERAL	Endevco	7264C-2KTZ-2-360M17	P93609	11/16/2022	05/18/2023
(3) VERTICAL	Endevco	7264C-2KTZ-2-360M17	P88334	11/16/2022	05/18/2023
CHEST POTENTIOMETER	Humanetics	880105-1080	510	11/16/2022	05/18/2023
FEMUR LOAD CELLS					
(1) RIGHT FEMUR	Denton	2121AJFL	F1826	11/16/2022	05/18/2023
(2) LEFT FEMUR	Denton	2121AJFL	F1827	11/16/2022	05/18/2023
LABORATORY INSTRUMENTATION					
NECK PENDULUM ACCELEROMETER	Endevco	7231C-750	AH5P1	07/15/2022	01/14/2023
THORAX PENDULUM ACCELEROMETER	Endevco	7264C-2KTZ-360M17	P97372	11/18/2022	05/20/2023
KNEE PENDULUM ACCELEROMETER	Endevco	7264C-2KTZ-2-360M17	P82128	11/30/2022	06/01/2023
NECK ROTATION TRANSDUCER 1 (OPTIONAL)	Servo	14CBI-2897	4707	08/12/2022	02/11/2023
NECK ROTATION TRANSDUCER 2 (OPTIONAL)	Servo	14CBI-2897	7297	08/12/2022	02/11/2023

LABORATORY TECHNICIAN: _____



EXTERNAL DIMENSIONS

HYBRID III 5 th SN #507, PART 572, SUBPART O EXTERNAL DIMENSIONS				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
A	TOTAL SITTING HEIGHT	Seat surface to highest point on top of the head.	774.7-800.1	781.1
B	SHOULDER PIVOT HEIGHT	Centerline of shoulder pivot bolt to the seat surface.	431.8-457.2	455.4
C	H-POINT HEIGHT	Reference	81.3-86.3	84.0
D	H-POINT LOCATION FROM BACKLINE	Reference	144.8-149.8	148.0
E	SHOULDER PIVOT FROM BACKLINE	Center of the shoulder clevis to the rear vertical surface of the fixture.	68.6-83.8	79.2
F	THIGH CLEARANCE	Measured at the highest point on the upper femur segment.	119.4-134.6	130.3
G	BACK OF ELBOW TO WRIST PIVOT	Back of the elbow flesh to the wrist pivot in line with the elbow and wrist pivots	243.9-259.1	249
H	HEAD BACK TO BACKLINE	Back of skull cap skin to seat rear vertical surface (Reference)	43.2-48.2	44.8
I	SHOULDER TO ELBOW LENGTH	Measure from the highest point on top of the shoulder clevis to the lowest part of the flesh on the elbow in line with the elbow pivot bolt.	276.8-297.2	280.1
J	ELBOW REST HEIGHT	Measure from the flesh below the elbow pivot bolt to the seat surface.	182.8-203.2	201.0
K	BUTTOCK TO KNEE LENGTH	The forward most part of the knee flesh to the rear vertical surface of the fixture.	520.7-546.1	544.1
L	POPLITEAL HEIGHT	Seat surface to the plane of the horizontal plane of the bottom of the feet.	355.6-376.0	356.5
M	KNEE PIVOT HEIGHT	Centerline of knee pivot bolt to the horizontal plane of the bottom of the feet.	393.7-419.1	394.0
N	BUTTOCK POPLITEAL LENGTH	The rearmost surface of the lower leg to the same point on the rear surface of the buttocks used for dim. "K".	414.0-439.4	434.2

HYBRID III 5 th SN #507, PART 572, SUBPART O EXTERNAL DIMENSIONS, continued				
DIMENSION	DESCRIPTION	DETAILS	ASSEMBLY DIMENSION (mm)	ACTUAL MEASUREMENT
O	CHEST DEPTH WITHOUT JACKET	Measured 304.8 ± 5.1 mm above seat surface	175.3-190.5	186.7
P	FOOT LENGTH	Tip of toe to rear of heel	218.5-233.7	222.0
Q	STANDING HEIGHT	(THEORETICAL)	1501.1	N/A
R	BUTTOCK TO KNEE PIVOT LENGTH	The rear surface of the buttocks to the knee pivot bolt	457.2-482.6	481.3
S	HEAD BREADTH	The widest part of the head	137.1-147.3	138.4
T	HEAD DEPTH	Back of the head to the forehead	177.8-188.0	178.1
U	HIP BREADTH	The widest part of the hip	299.7-314.9	309.6
V	SHOULDER BREADTH	Outside edges of right and left shoulder clevises	350.5-365.7	363.9
W	FOOT BREADTH	The widest part of the foot	78.8-94.0	89.0
X	HEAD CIRCUMFERENCE	Measured at the point as in dim. "T"	528.3-548.7	539.4
Y	CHEST CIRCUMFERENCE (WITH CHEST JACKET)	Measured 345.4 ± 12.7 mm above seat surface	850.9-881.3	863.7
Z	WAIST CIRCUMFERENCE	Measured 165.1 ± 5.1 mm above seat surface	759.5-789.9	787.1
AA	REFERENCE LOCATION FOR MEASUREMENT OF CHEST CIRCUMFERENCE	Reference	332.7-358.1	342.0
BB	REFERENCE LOCATION FOR MEASUREMENT OF WAIST CIRCUMFERENCE	Reference	160.1-170.2	168.0

DATA SHEET B3
HEAD DROP TEST (572.132) (5th Female)

Dummy Serial Number: 507

Test Date: 11/29/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
 N/A, ONLY one head drop performed
2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
3. The head accelerometer mounting plate screws (10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
4. Accelerometers and their respective mounts are smooth and clean.
5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.8°C</u> |
| Record the minimum temperature: | <u>21.5°C</u> |
| Record the maximum humidity: | <u>29%</u> |
| Record the minimum humidity: | <u>22%</u> |
8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- | | |
|------------------------------|------------------|
| Record findings and actions: | <u>No Damage</u> |
|------------------------------|------------------|
9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))
10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the

forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))

Record the actual distance: 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))

Record the right side distance: 501 mm

Record the left side distance: 501 mm

X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))

Record actual micro finish: 24.8 micro inches

X 13. The impact surface is rigidly supported. (572.132(c)(4))

X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))

Record thickness: 50.9 mm

Record width: 604 mm


Record length: 595 mm

X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches \pm 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	268 g
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	0.8 g

X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.


Signature

11/29/2022
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507



Test ID: D222781



Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	29	Pass
Peak Resultant Acceleration	G's	250 to 300	268	Pass
Peak Lateral Acceleration	G's	<= +/- 15.0	0.8	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass


 Laboratory Technician

11/29/2022
 Test Date


 Approved By





DATA SHEET B4
NECK FLEXION TEST (572.132) (5th Female)

Dummy Serial Number: 507

Test Date: 11/29/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive flexion tests are necessary)

1. It has been at least 30 minutes since the last flexion test. (572.137(q))
 N/A, ONLY one neck test performed
2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.7°C</u> |
| Record the minimum temperature: | <u>21.4°C</u> |
| Record the maximum humidity: | <u>30%</u> |
| Record the minimum humidity: | <u>23%</u> |
4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No damage
5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
- Record findings and actions: No Deterioration; Hardness: Front 89; Back 90.
6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

- X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J2111/1 MAR95. (572.137(m))
- X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))
- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:
Neck Flexion Test Results (572.133(b)(1) & 572.133(c)(4)(I & ii))

Parameter		Specification	Results
Pendulum impact speed		6.89 m/s \leq speed \leq 7.13 m/s	6.96 m/s
Pendulum ΔV with respect to impact speed	@ 10 ms	2.1 m/s $\leq \Delta V \leq$ 2.5 m/s	2.3 m/s
	@ 20 ms	4.0 m/s $\leq \Delta V \leq$ 5.0 m/s	4.5 m/s
	@ 30 ms	5.8 m/s $\leq \Delta V \leq$ 7.0 m/s	6.5 m/s
Plane D Rotation		Peak moment* 69 Nm \leq moment \leq 83 Nm during the following rotation range 77° \leq angle \leq 91°	75 Nm @ 82 degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm 80 ms \leq time \leq 100 ms	85 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.


Signature

11/29/2022
Date

MGA RESEARCH CORPORATION

NECK FLEXION TEST

HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D222782

Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.7	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Speed		m/s	6.89 to 7.13	6.96	Pass
Pendulum Velocity	10 ms	m/s	2.1 to 2.5	2.3	Pass
	20 ms	m/s	4.0 to 5.0	4.5	Pass
	30 ms	m/s	5.8 to 7.0	6.5	Pass
D Plane Rotation	Max	deg	77 to 91	82	Pass
Occipital Condyle Moment within Rotation Corridor		Nm	69 to 83	75	Pass
Positive Moment Time Curve Decay to 10 Nm		ms	80 to 100	85	Pass
Overall Results					Pass





 Laboratory Technician

11/29/2022

 Test Date




 Approved By





TEST DESC: NECK FLEXION
VELOCITY: 22.83 ft/s, 6.96 m/s

TEST DATE: 11/29/2022
TEST #: D222782



DATA SHEET B5
NECK EXTENSION TEST (572.133) (5th Female)

Dummy Serial Number: 507

Test Date: 11/29/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

1. It has been at least 30 minutes since the last extension test. (572.137(q))
 N/A, ONLY one neck test performed
2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.7°C</u> |
| Record the minimum temperature: | <u>21.3°C</u> |
| Record the maximum humidity: | <u>43%</u> |
| Record the minimum humidity: | <u>36%</u> |
4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No damage
5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
- Record findings and actions: No Deterioration; Hardness: Front 89; Back 90.
6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

- X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))
- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:
Neck Extension Test Results (572.133(b)(2) & 572.133(c)(4)(I & ii))

Parameter		Specification	Results
Pendulum impact speed		$5.95 \text{ m/s} \leq \text{speed} \leq 6.19 \text{ m/s}$	6.12 m/s
Pendulum ΔV with respect to impact speed	@ 10 ms	$1.5 \text{ m/s} \leq \Delta V \leq 1.9 \text{ m/s}$	1.8 m/s
	@ 20 ms	$3.1 \text{ m/s} \leq \Delta V \leq 3.9 \text{ m/s}$	3.6 m/s
	@ 30 ms	$4.6 \text{ m/s} \leq \Delta V \leq 5.6 \text{ m/s}$	5.4 m/s
Plane D Rotation		Peak moment* $-65 \text{ Nm} \leq \text{moment} \leq -53 \text{ Nm}$ during the following rotation range $99^\circ \leq \text{angle} \leq 114^\circ$	-57 Nm @ 105 degrees
Positive Moment Decay** (Extension)		Time to decay to -10 Nm $94 \text{ ms} \leq \text{time} \leq 114 \text{ ms}$	104 ms


*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.


Signature

11/29/2022
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507



Test I.D.: D222783


Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.7	Pass
Laboratory Relative Humidity		%	10 to 70	30	Pass
Pendulum Speed		m/s	5.95 to 6.19	6.12	Pass
Pendulum Velocity	10 ms	m/s	1.5 to 1.9	1.8	Pass
	20 ms	m/s	3.1 to 3.9	3.6	Pass
	30 ms	m/s	4.6 to 5.6	5.4	Pass
D Plane Rotation	Max	deg	99 to 114	105	Pass
Occipital Condyle Moment within Rotation Corridor		Nm	-65 to -53	-57	Pass
Negative Moment Time Curve Decay to -10 Nm		ms	94 to 114	104	Pass
Overall Results					Pass


 Laboratory Technician

11/29/2022
 Test Date


 Approved By





DATA SHEET B6
THORAX IMPACT TEST (572.134) (5th Female)

Dummy Serial Number: 507

Test Date: 12/02/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))
 N/A, ONLY one thorax impact test performed
2. The test fixture conforms to the specifications in Figure 11B.
3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))
4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature:	<u>21.7°C</u>
Record the minimum temperature:	<u>21.4°C</u>
Record the maximum humidity:	<u>32%</u>
Record the minimum humidity:	<u>25%</u>

5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

- No Damage
 - Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage:

- The following repairs or replacement was performed. Record:

- X 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))
- X 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504) that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.
- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is 12.7 mm ± 1 mm below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is 6.71 m/s ± 0.12 m/s. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

- X 16. Complete the following table:
 Thorax Impact Results (572.134(b) and 572.134(b)(1)&(2))


Parameter*	Specification	Result
Test Probe Speed	$6.59 \text{ m/s} \leq \text{speed} \leq 6.83 \text{ m/s}$	6.68 m/s
Chest Compression	$50.0 \text{ mm} \leq \text{compression} \leq 58.0 \text{ mm}$	51 mm
Peak force** between 50.0 and 58.0 mm chest compression	$3900\text{N} \leq \text{peak force} \leq 4400\text{N}$	4361 N
Peak Force** between 18.0 and 50.0 mm chest compression	Peak Force $\leq 4600 \text{ N}$	4423 N
Internal Hysteresis***	$69\% \leq \text{hysteresis} \leq 85\%$	73%

*Time zero is defined as the time of initial contact between the test probe and the chest skin.

**Force = impactor mass x acceleration (572.134(b)(3))

***Area under loading curve minus the area under the unloading curve divided by the area under the loading curve. (Figure 12B)

- X 17. Plots of chest compression, acceleration, force, force versus deflection follow this sheet.



 Signature

12/02/2022

 Date

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE


ATD Serial No: 507

Test I.D.: D222784A

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.7	Pass
Relative Humidity	%	10 to 70	32	Pass
Probe Speed	m/s	6.59 to 6.83	6.68	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	N	3900 to 4400	4361	Pass
Internal Hysteresis	%	69 to 85	73	Pass
Peak Force 18 mm - 50 mm	N	<= 4600	4423	Pass
Overall Test Results				Pass


 Laboratory Technician


12/02/2022
 Test Date


 Approved By



TEST DESC: THORAX IMPACT
VELOCITY: 21.93 ft/s, 6.68 m/s

TEST DATE: 12/02/2022
TEST #: D222784A



DATA SHEET B7
TORSO FLEXION TEST (572.135) (5th Female)

Dummy Serial Number: 507

Test Date: 11/29/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
 N/A, ONLY one torso flexion test performed
2. The test fixture conforms to the specifications in Figure 13B.
3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
 With legs below femurs.
 Without legs below femurs.
4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.9°C</u> |
| Record the minimum temperature: | <u>21.6°C</u> |
| Record the maximum humidity: | <u>35%</u> |
| Record the minimum humidity: | <u>28%</u> |
5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

- X 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- X 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- X 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
 Record reference plane angle (max. allowed 20°): See Result Table
- X 12. Attach the pull cable and the load cell. (572.135(c)(8))
- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at 45° ± 0.5° of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at 45° ± 0.5° of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), 572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle ≤ 20°	14 deg
Torso rotation rate	0.5°/s ≤ rate ≤ 1.5°/s	1.2 deg/sec
Force at 45° ± 0.5°	320 N ≤ force ≤ 390 N	374 N
Final ref. plane angle	Initial ref. plane angle ± 8°	7 deg

 Jon Seve
 Signature

 11/29/2022
 Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE


ATD Serial No: 142



Test I.D: D222787

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.9	Pass
Laboratory Relative Humidity	%	10 to 70	35	Pass
Initial Angle	deg	0 to 20	14	Pass
Return Angle	deg	+/- 8	7	Pass
Force at 45 deg	N	320 to 390	374	Pass
Upper Torso Deflection Rate	deg/s	0.5 to 1.5	1.2	Pass
Overall Result				Pass


 Laboratory Technician

11/29/2022
 Test Date


 Approved By



DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136) (5th Female)

Dummy Serial Number: 507

Test Date: 11/29/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

1. It has been at least 30 minutes since the last knee impact test. (572.137(q))
 N/A, ONLY one knee impact test performed
2. The test fixture conforms to the specifications in Figure 14B.
3. The knee assembly (880105-528L), lower leg structural replacement (880105- 603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))
4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.7°C</u> |
| Record the minimum temperature: | <u>21.4°C</u> |
| Record the maximum humidity: | <u>30%</u> |
| Record the minimum humidity: | <u>23%</u> |
5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))
6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))
7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))
8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))
9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.


X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:
Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3885 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.



Signature

11/29/2022
Date

MGA RESEARCH CORPORATION
LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D222786

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Speed	m/s	2.07 to 2.13	2.11	Pass
Maximum Force	N	3450 to 4060	3885	Pass
Overall Test Results				Pass


 Laboratory Technician


11/29/2022
 Test Date


 Approved By



TEST DESC: LEFT KNEE
VELOCITY: 6.92 ft/s, 2.11 m/s

TEST DATE: 11/29/2022
TEST #: D222786



DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136) (5th Female)

Dummy Serial Number: 507

Test Date: 11/29/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

1. It has been at least 30 minutes since the last knee impact test. (572.137(q))
 N/A, ONLY one knee impact test performed
2. The test fixture conforms to the specifications in Figure 14B.
3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))
4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature:	<u>21.7°C</u>
Record the minimum temperature:	<u>21.3°C</u>
Record the maximum humidity:	<u>30%</u>
Record the minimum humidity:	<u>23%</u>


5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))
6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))
7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))
8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))
9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.
10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:

Knee Impact Results (572.136(b)(1) and 572.136(c)(5))		
Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.10 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3889 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.


Signature

11/29/2022
Date

**MGA RESEARCH CORPORATION
 RIGHT KNEE IMPACT TEST
 HYBRID III 5TH PERCENTILE**

ATD Serial No: 507

Test I.D.: D222785

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.7	Pass
Laboratory Relative Humidity	%	10 to 70	30	Pass
Probe Speed	m/s	2.07 to 2.13	2.10	Pass
Maximum Force	N	3450 to 4060	3889	Pass
Overall Test Results				Pass


 Laboratory Technician


11/29/2022
 Test Date


 Approved By



TEST DESC: RIGHT KNEE
VELOCITY: 6.89 ft/s, 2.10 m/s

TEST DATE: 11/29/2022
TEST #: D222785



DATA SHEET B10
PART 572 INSTRUMENTATION CALIBRATION INFORMATION

I.D. NO.	MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF LAST CALIBRATION	DATE OF NEXT CALIBRATION
DUMMY INSTRUMENTATION					
HEAD ACCELEROMETERS					
(1) LONGITUDINAL	Endevco	7264C-2KTZ-2-360M17	P85158	11/16/2022	05/18/2023
(2) LATERAL	Endevco	7264C-2KTZ-2-360M17	P85159	11/16/2022	05/18/2023
(3) VERTICAL	Endevco	7264C-2KTZ-2-360M17	P85160	11/16/2022	05/18/2023
NECK TRANSDUCER	Denton	1716A JLN2	N2324	10/20/2022	04/21/2023
CHEST ACCELEROMETERS					
(1) LONGITUDINAL	Endevco	7264C-2KTZ-2-360M17	P79787	11/16/2022	05/18/2023
(2) LATERAL	Endevco	7264C-2KTZ-2-360M17	P86733	11/16/2022	05/18/2023
(3) VERTICAL	Endevco	7264C-2KTZ-2-360M17	P86735	11/16/2022	05/18/2023
CHEST POTENTIOMETER	Servo	14CBI-2897	507	11/16/2022	05/18/2023
FEMUR LOAD CELLS					
(1) RIGHT FEMUR	Denton	2121AJTF	F8151	11/16/2022	05/18/2023
(2) LEFT FEMUR	Denton	2121AJTF	F8152	11/16/2022	05/18/2023
LABORATORY INSTRUMENTATION					
NECK PENDULUM ACCELEROMETER	Endevco	7231C-750	AH5P1	07/15/2022	01/14/2023
THORAX PENDULUM ACCELEROMETER	Endevco	7264C-2KTZ-360M17	P97372	11/18/2022	05/20/2023
KNEE PENDULUM ACCELEROMETER	Endevco	7264C-2KTZ-2-360M17	P82128	5/31/2022	06/01/2023
NECK ROTATION TRANSDUCER 1 (OPTIONAL)	Servo	14CBI-2897	4707	08/12/2022	02/11/2023
NECK ROTATION TRANSDUCER 2 (OPTIONAL)	Servo	14CBI-2897	7297	08/12/2022	02/11/2023

LABORATORY TECHNICIAN: _____



DATA SHEET B3
HEAD DROP TEST (572.132) (5th Female)

Dummy Serial Number: 507

Test Date: 12/13/2022

Technician: Nathaniel Benjamin

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive head drops are necessary)

1. It has been at least 2 hours since the last head drop. (572.132(c)(5))
 N/A, ONLY one head drop performed
2. The head assembly consists of the complete head (880105-100X), the six-axis neck transducer (SA572-S11) or neck transducer structural replacement (78051-383X), and three (3) accelerometers (SA572-S4). (572.132(a))
3. The head accelerometer mounting plate screws (10-24 x 3/8 SHCS) are torqued to 9.0 Nm.
4. Accelerometers and their respective mounts are smooth and clean.
5. Torque the skull cap screws (10-24 x 1/2 SHCS) to 9.0 Nm.
6. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.136(m))
7. The head assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.132(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.8°C</u> |
| Record the minimum temperature: | <u>20.5°C</u> |
| Record the maximum humidity: | <u>27%</u> |
| Record the minimum humidity: | <u>17%</u> |
8. Visually inspect the head skin for cracks, cuts, abrasions, etc. Repair or replace the head skin if the damaged area is more than superficial. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No Damage

X 9. Clean the impact surface of the skin and the impact surface of the fixture with isopropyl alcohol, trichloroethane or equivalent prior to the test. (572.132(c)(2))

X 10. Suspend and orient the head assembly as shown in Figure 5B. The lowest point on the forehead is 376.0 ± 1.0 mm (14.8 ± 0.04 inch) from the impact surface. (572.132(c)(3))
Record the actual distance: 376 mm

NOTE: The masses of the suspension device and the accelerometer cables are to be kept as lightweight as possible to minimize their effect on the test results.

X 11. The 1.57 mm (0.062 inch) diameter holes located on either side of the dummy's head are equidistance within 2 mm from the impact surface. A typical test setup is shown in Figure 6B. (572.132(c)(3))
Record the right side distance: 501 mm
Record the left side distance: 501 mm

X 12. The impact surface is clean and dry and has a micro finish in the range of 203.2×10^{-6} mm (8 micro inches) to 2032.0×10^{-6} mm (80 micro inches) (RMS). (572.132(c)(4))
Record actual micro finish: 24.8 micro inches

X 13. The impact surface is rigidly supported. (572.132(c)(4))

X 14. The impact surface is a flat horizontal steel plate 50.8 mm (2 inches) thick and 610 mm (24 inches) square. (572.132(c)(4))
Record thickness: 50.9 mm
Record width: 604 mm
Record length: 595 mm

X 15. Drop the head assembly from a height of 376.0 ± 1.0 mm (14.8 inches \pm 0.04 inches) by a means that ensures a smooth, instant release onto the impact surface. (572.132(b) & (572.132(c)(4))

X 16. Complete the following table using channel class 1000 data. (572.132(b)):

Parameter	Specification	Result
Peak resultant acceleration	$250 \text{ g} \leq x \leq 300 \text{ g}$	263 g
Resultant versus time history curve	Unimodal	Yes
Oscillations after the main pulse	Less than 10% of the peak resultant acceleration	Yes
Lateral acceleration	y-axis acceleration $\leq 15 \text{ g}$	-0.7 g

X 17. Plots of the x, y, z, and resultant acceleration data follow this sheet.

Nathaniel Benjamin
Signature

12/13/2022
Date

MGA RESEARCH CORPORATION
HEAD DROP TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507



Test ID: D222831



Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	27	Pass
Peak Resultant Acceleration	G's	250 to 300	263	Pass
Peak Lateral Acceleration	G's	<= +/- 15.0	-0.7	Pass
Unimodal	N/A	Yes	Yes	Pass
Oscillations	N/A	within 10% of peak	Yes	Pass
Overall Test Results				Pass

Nathaniel Benjamin
 Laboratory Technician

12/13/2022
 Test Date

Jose Salmeron
 Approved By





- X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))
- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 8B for the flexion test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 6.89 m/s to 7.13 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:
Neck Flexion Test Results (572.133(b)(1) & 572.133(c)(4)(I & ii))

Parameter		Specification	Results
Pendulum impact speed		6.89 m/s \leq speed \leq 7.13 m/s	7.06 m/s
Pendulum ΔV with respect to impact speed	@ 10 ms	2.1 m/s $\leq \Delta V \leq$ 2.5 m/s	2.2 m/s
	@ 20 ms	4.0 m/s $\leq \Delta V \leq$ 5.0 m/s	4.3 m/s
	@ 30 ms	5.8 m/s $\leq \Delta V \leq$ 7.0 m/s	6.2 m/s
Plane D Rotation		Peak moment* 69 Nm \leq moment \leq 83 Nm during the following rotation range 77° \leq angle \leq 91°	72 Nm @ 79 degrees
Positive Moment Decay** (Flexion)		Time to decay to 10 Nm 80 ms \leq time \leq 100 ms	86 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follows this sheet.

Nathaniel Benjamin
Signature

12/13/2022
Date

**MGA RESEARCH CORPORATION
NECK FLEXION TEST
HYBRID III 5TH PERCENTILE**

ATD Serial No: 507



Test I.D: D222832


Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.8	Pass
Laboratory Relative Humidity		%	10 to 70	27	Pass
Pendulum Speed		m/s	6.89 to 7.13	7.06	Pass
Pendulum Velocity	10 ms	m/s	2.1 to 2.5	2.2	Pass
	20 ms	m/s	4.0 to 5.0	4.3	Pass
	30 ms	m/s	5.8 to 7.0	6.2	Pass
D Plane Rotation	Max	deg	77 to 91	79	Pass
Occipital Condyle Moment within Rotation Corridor		Nm	69 to 83	72	Pass
Positive Moment Time Curve Decay to 10 Nm		ms	80 to 100	86	Pass
Overall Results					Pass

Nathaniel Benjamin
Laboratory Technician

12/13/2022
Test Date

Joe Galvez
Approved By





DATA SHEET B5
NECK EXTENSION TEST (572.133) (5th Female)

Dummy Serial Number: 507

Test Date: 12/13/2022

Technician: Nathaniel Benjamin

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive extension tests are necessary)

1. It has been at least 30 minutes since the last extension test. (572.137(q))
 N/A, ONLY one neck test performed
2. The components required for the neck tests include the head assembly (880105-100X), neck (880105-250), bib simulator (880105-371), upper neck adjusting bracket (880105-207), lower neck adjusting bracket (880105-208), six axis neck transducer (SA572-S11) and either three accelerometers (SA572-S4) or their mass equivalent installed in the head assembly as specified in drawing 880105-100X. Data from the accelerometers are not required. (572.133(b))
3. The assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to a test. (572.133(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.8°C</u> |
| Record the minimum temperature: | <u>20.5°C</u> |
| Record the maximum humidity: | <u>27%</u> |
| Record the minimum humidity: | <u>17%</u> |
4. Visually inspect neck assembly for cracks, cuts and separation of the rubber from the metal segments. Note: If the damage resulted from the vehicle crash test in which the dummy was an occupant, the damaged area is to be documented with photography and the post test calibration verification testing completed before any replacement or repairs are made.
- Record findings and actions: No damage
5. Inspect the nodding blocks (78051-351) for any deterioration, but when replacement is necessary, ONLY replace during pre-test calibration. Using a Shore "A" type Durometer, verify the hardness of the nodding blocks is between 80 and 90. Ensure the nodding blocks are installed correctly. (880105-250 and PADI page17).
- Record findings and actions: No Deterioration; Hardness: Front 89; Back 90.
6. Torque the jam nut (9000018) on the neck cable (880105-206) to 1.4 ± 0.2 Nm (12.0 ± 2.0 in-lb). (572.133(c)(2))

- X 7. The data acquisition system, including transducers, conforms to the requirements of SAE Recommended Practice J211/1 MAR95. (572.137(m))
- X 8. The test fixture pendulum conforms to the specifications in Figure 7B. (572.133(c)(3))
- X 9. The head-neck assembly is mounted on the pendulum so the midsagittal plane of the head is vertical and coincides with the plane of motion of the pendulum longitudinal centerline as shown in Figure 9B for the extension test. (572.133(c)(3))
- X 10. Install the transducers or other devices for measuring the "D" plane rotation with respect to the pendulum longitudinal centerline. Note: Plane "D" is the bottom horizontal surface of the skull. These measurement devices should be designed to minimize their influence upon the performance of the head-neck assembly. An example of a measurement device is shown in Figure 10B.
- X 11. With the pendulum resting against the honeycomb material, the neck bracket was adjusted until the longitudinal centerline of the pendulum was perpendicular ± 1 degree to plane "D" on the dummy's head.
- X 12. Release the pendulum and allow it to fall freely from a height to achieve an impact speed of 5.95 m/s to 6.19 m/s as measured at the center of the pendulum accelerometer. (572.133(c)(4)(i))
- X 13. Complete the following table:
Neck Extension Test Results (572.133(b)(2) & 572.133(c)(4)(I & ii))

Parameter		Specification	Results
Pendulum impact speed		5.95 m/s \leq speed \leq 6.19 m/s	6.12 m/s
Pendulum ΔV with respect to impact speed	@ 10 ms	1.5 m/s $\leq \Delta V \leq$ 1.9 m/s	1.7 m/s
	@ 20 ms	3.1 m/s $\leq \Delta V \leq$ 3.9 m/s	3.5 m/s
	@ 30 ms	4.6 m/s $\leq \Delta V \leq$ 5.6 m/s	5.3 m/s
Plane D Rotation		Peak moment* -65 Nm \leq moment \leq -53 Nm during the following rotation range 99° \leq angle \leq 114°	-56 Nm @ 107 degrees
Positive Moment Decay** (Extension)		Time to decay to -10 Nm 94 ms \leq time \leq 114 ms	105 ms

*Moment about the occipital condyle = $M_y - (0.01778 \text{ m} \times F_x)$ (572.133(b)(1)(ii))

M_y = Moment in Nm measured by the transducer

F_x = Force, in N measured by the transducer

**Time zero is defined as the time of initial contact between the pendulum striker plate and the honeycomb material. (572.133(b)(3))

- X 14. Plots of acceleration, velocity, y-axis moment, and x-axis force and y-axis moment about the occipital condyle follow this sheet.

Nathaniel Benjamin
Signature

12/13/2022
Date

MGA RESEARCH CORPORATION
NECK EXTENSION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507



Test I.D.: D222833


Tested Parameter		Units	Specification	Result	Pass/Fail
Laboratory Temperature		deg C	20.6 to 22.2	21.8	Pass
Laboratory Relative Humidity		%	10 to 70	27	Pass
Pendulum Speed		m/s	5.95 to 6.19	6.12	Pass
Pendulum Velocity	10 ms	m/s	1.5 to 1.9	1.7	Pass
	20 ms	m/s	3.1 to 3.9	3.5	Pass
	30 ms	m/s	4.6 to 5.6	5.3	Pass
D Plane Rotation	Max	deg	99 to 114	107	Pass
Occipital Condyle Moment within Rotation Corridor		Nm	-65 to -53	-56	Pass
Negative Moment Time Curve Decay to -10 Nm		ms	94 to 114	105	Pass
Overall Results					Pass


 Laboratory Technician

12/13/2022
 Test Date


 Approved By





DATA SHEET B6
THORAX IMPACT TEST (572.134) (5th Female)

Dummy Serial Number: 507

Test Date: 12/12/2022

Technician: Jonah Pulokas

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive thorax impact tests are necessary)

1. It has been at least 30 minutes since the last thorax impact test. (572.137(q))
 N/A, ONLY one thorax impact test performed
2. The test fixture conforms to the specifications in Figure 11B.
3. The complete assembled dummy (880105-000) is used (572.134(b)) and is dressed in a form fitting cotton stretch above-the-elbow sleeved shirt and above-the-knee pants. The weight of the shirt and pants shall not exceed 0.14 kg. (572.134(c)(1))
4. The dummy assembly soaked at a temperature between 20.6°C (69°F) and 22.2°C (72°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.134(c)(2))

Record the maximum temperature:	<u>21.6°C</u>
Record the minimum temperature:	<u>20.3°C</u>
Record the maximum humidity:	<u>32%</u>
Record the minimum humidity:	<u>22%</u>

5. Remove the chest skin and visually inspect the thorax assembly for cracks, cuts, abrasions, etc. Particular attention should be given to the rib damping material, chest displacement transducer assembly and the rear rib supports. Inspect for rib deformation using the chest depth gage. If any damage is noted repair and/or replace the damaged components unless the damage resulted from the vehicle crash test in which the dummy was an occupant in which case the damage must be documented and post test calibration verification testing completed before any repairs or replacements are made.

- No Damage

- Damage from crash test, no repairs or replacement because this is a post test calibration verification. Record damage

- The following repairs or replacement was performed. Record

- X 6. Seat the dummy, (chest skin still removed) without back and arm supports on the test fixture surface as shown in Figure 11B. The surface must be long enough to support the pelvis and outstretched legs. (572.134(c)(3))
- X 7. Level the ribs both longitudinally and laterally $\pm 0.5^\circ$ and adjust the pelvis angle to $7^\circ \pm 2^\circ$. The angle may be measured using the special H-point tool (TE-2504) that inserts into the pelvic structure and extends outward beyond the pelvic skin surface or by using the surface of the pelvic adaptor block.
- X 8. The midsagittal plane of the dummy is vertical within $\pm 1^\circ$. (572.134(c)(3))
- X 9. The longitudinal centerline of the test probe is centered within ± 2.5 mm of the midsagittal plane of the dummy and is $12.7 \text{ mm} \pm 1 \text{ mm}$ below the horizontal peripheral centerline of the No. 3 rib and is within 0.5° of a horizontal line in the dummy's midsagittal plane. (572.134(c)(4))
- X 10. Align the adjustable neck bracket index marks to the "zero" position.
- X 11. Record locations such as the rear surfaces of the thoracic spine and the lower neck bracket reference with respect to the laboratory coordinate system. These reference measurements are necessary to ensure the dummy is in the same position after the chest skin is installed. The reference locations must be accessible after installation of the chest skin. It may be necessary to leave the chest skin zipper unfastened until the references are checked and fasten it just prior to the test.
- X 12. Install the chest skin and reposition the dummy as described in the preceding paragraph using the reference measurements recorded.
- X 13. Place the arm assemblies horizontal $\pm 2^\circ$ and parallel to the midsagittal plane. The arms are held in place by tightening the adjustment nut that holds the arm yoke to the clavicle assembly.
- X 14. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 180.
- X 15. Impact the anterior surface of the thorax with the test probe so the longitudinal centerline of the probe is within 2° of a horizontal line in the dummy's midsagittal plane at the moment of impact. (572.134(c)(5)) The velocity of the test probe at the time of impact is $6.71 \text{ m/s} \pm 0.12 \text{ m/s}$. (572.134(b)) The probe is guided so there is no significant lateral, vertical or rotational movement during the impact. (572.134(c)(6)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.134(c)(7))

MGA RESEARCH CORPORATION
THORAX IMPACT
HYBRID III 5TH PERCENTILE

ATD Serial No: 507

Test I.D: D222834

Tested Parameter	Units	Specification	Result	Pass/Fail
Temperature	deg C	20.6 to 22.2	21.6	Pass
Relative Humidity	%	10 to 70	32	Pass
Probe Speed	m/s	6.59 to 6.83	6.68	Pass
Peak Deflection	mm	50 to 58	51	Pass
Peak Resistive Force w/in Deflection Corridor	N	3900 to 4400	4346	Pass
Internal Hysteresis	%	69 to 85	73	Pass
Peak Force 18 mm - 50 mm	N	<= 4600	4406	Pass
Overall Test Results				Pass


 Laboratory Technician


12/12/2022
 Test Date


 Approved By



TEST DESC: THORAX IMPACT
VELOCITY: 21.93 ft/s, 6.68 m/s

TEST DATE: 12/12/2022
TEST #: D222834



DATA SHEET B7
TORSO FLEXION TEST (572.135) (5th Female)

Dummy Serial Number: 507

Test Date: 12/13/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive torso flexion tests are necessary)

1. It has been at least 30 minutes since the last torso flexion test. (572.137(q))
 N/A, ONLY one torso flexion test performed
2. The test fixture conforms to the specifications in Figure 13B.
3. The complete assembled dummy (880105-000) is used (572.135(c)(2)).
 With legs below femurs.
 Without legs below femurs.
4. The dummy assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.135(c)(1))
- | | |
|---------------------------------|---------------|
| Record the maximum temperature: | <u>21.8°C</u> |
| Record the minimum temperature: | <u>20.5°C</u> |
| Record the maximum humidity: | <u>26%</u> |
| Record the minimum humidity: | <u>16%</u> |
5. Secure the pelvis to the fixture at the pelvis instrument cavity rear face by threading four ¼ cap screws into the available threaded attachment holes. Tighten the mountings so that the test material is rigidly affixed to the test fixture and the pelvic lumbar joining surface is horizontal. (572.135(c)(3))
6. Attach the loading adapter bracket to the spine of the dummy as shown in Figure 13B. (572.135(c)(4))
7. Inspect and adjust, if necessary, the seating of the abdominal insert within the pelvis cavity and with respect to the torso flesh, assuring that the torso flesh provides uniform fit and overlap with respect to the outside surface of the pelvis flesh. (572.135(c)(5))
8. Flex the dummy forward and back 3 times such that the angle reference plane moves between 0° and 30° with respect to the vertical transverse plane. (572.135(c)(6))

- X 9. Support the dummy such that the angle reference plane is at or near 0° (vertical with respect to the vertical transverse plane). Wait at least 30 minutes before continuing. (572.135(c)(6))
- X 10. Remove all external support that was implemented in 9 above. (572.135(c)(7))
- X 11. Measure the initial orientation angle of the torso reference plane of the seated, unsupported dummy. (572.135(c)(7))
Record reference plane angle (max. allowed 20°): See Result Table
- X 12. Attach the pull cable and the load cell. (572.135(c)(8))
- X 13. Apply a tension force in the midsagittal plane to the pull cable at any upper torso deflection rate between 0.5° and 1.5° per second, until the angle reference plane is at 45° ± 0.5° of flexion relative to the vertical transverse plane. (572.135(c)(9))
- X 14. Maintain angle reference plane at 45° ± 0.5° of flexion for 10 seconds. (572.135(c)(10))
- X 15. As quickly as possible release the force applied to the attachment bracket. (572.135(c)(11))
- X 16. 3 minutes after the release of the force, measure the reference plane angle. (572.135(c)(11))
- X 17. Complete the following table:

Torso Flexion Results (572.135(b), 572.135(c)(7), 572.135(c)(9))

Parameter	Specification	Result
Initial ref. plane angle	Angle ≤ 20°	17 deg
Torso rotation rate	0.5°/s ≤ rate ≤ 1.5°/s	0.5 deg/sec
Force at 45° ± 0.5°	320 N ≤ force ≤ 390 N	354 N
Final ref. plane angle	Initial ref. plane angle ± 8°	7 deg

Jon Seve
Signature

12/13/2022
Date

MGA RESEARCH CORPORATION
TORSO FLEXION TEST
HYBRID III 5TH PERCENTILE

ATD Serial No: 507



Test I.D: D222837

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.8	Pass
Laboratory Relative Humidity	%	10 to 70	26	Pass
Initial Angle	deg	0 to 20	17	Pass
Return Angle	deg	+/- 8	7	Pass
Force at 45 deg	N	320 to 390	354	Pass
Upper Torso Deflection Rate	deg/s	0.5 to 1.5	0.5	Pass
Overall Result				Pass


 Laboratory Technician

12/13/2022
 Test Date


 Approved By



MGA RESEARCH CORPORATION

**LEFT KNEE IMPACT TEST
HYBRID III 5TH PERCENTILE**

ATD Serial No: 507

Test I.D.: D222836

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	33	Pass
Probe Speed	m/s	2.07 to 2.13	2.11	Pass
Maximum Force	N	3450 to 4060	3767	Pass
Overall Test Results				Pass


Laboratory Technician


12/12/2022
Test Date


Approved By



TEST DESC: LEFT KNEE
VELOCITY: 6.92 ft/s, 2.11 m/s

TEST DATE: 12/12/2022
TEST #: D222836



DATA SHEET B8
LEFT KNEE IMPACT TEST (572.136) (5th Female)

Dummy Serial Number: 507

Test Date: 12/12/2022

Technician: Nathaniel Benjamin

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

1. It has been at least 30 minutes since the last knee impact test. (572.137(q))
 N/A, ONLY one knee impact test performed
2. The test fixture conforms to the specifications in Figure 14B.
3. The knee assembly (880105-528L), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-650), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))
4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature:	<u>21.6°C</u>
Record the minimum temperature:	<u>20.3°C</u>
Record the maximum humidity:	<u>33%</u>
Record the minimum humidity:	<u>23%</u>

5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))
6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))
7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))
8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))
9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:
Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.11 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3767 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.

Nathaniel Benjamin
Signature

12/12/2022
Date

DATA SHEET B9
RIGHT KNEE IMPACT TEST (572.136) (5th Female)

Dummy Serial Number: 507

Test Date: 12/12/2022

Technician: Jon Love

- Pre test calibration
 Post test calibration verification

Test attempt no. 1 (when successive knee impact tests are necessary)

1. It has been at least 30 minutes since the last knee impact test. (572.137(q))
 N/A, ONLY one knee impact test performed
2. The test fixture conforms to the specifications in Figure 14B.
3. The knee assembly (880105-528R), lower leg structural replacement (880105-603), lower leg flesh (880105-601), ankle assembly (880105-660), foot assembly (880105-651), and femur load transducer (SA572-S14) (may use the load cell structural replacement (78051-319)) were used. (572.136(b)(1))
4. The knee assembly soaked at a temperature between 18.9°C (66°F) and 25.6°C (78°F) and at a relative humidity from 10% to 70% for a period of at least four (4) hours prior to this test. (572.136(c)(1))

Record the maximum temperature:	<u>21.6°C</u>
Record the minimum temperature:	<u>20.3°C</u>
Record the maximum humidity:	<u>33%</u>
Record the minimum humidity:	<u>23%</u>

5. Mount the test specimen and secure it to the rigid test fixture. (572.136(c)(2))
6. No parts of the foot or tibia contact any exterior surface. (572.136(c)(2))
7. Align the test probe so that throughout its stroke and at contact with the knee it is within 2 degrees of horizontal and collinear with the longitudinal centerline of the femur. (572.136(c)(3))
8. The probe is guided so there is no significant lateral, vertical or rotational movement during the impact with the knee. (572.136(c)(4))
9. The data acquisition system, including transducers, must conform to the requirements of SAE Recommended Practice J211/1 MAR95 (572.136(m)) Class 600.

**MGA RESEARCH CORPORATION
 RIGHT KNEE IMPACT TEST
 HYBRID III 5TH PERCENTILE**

ATD Serial No: 507

Test I.D.: D222835

Tested Parameter	Units	Specification	Result	Pass/Fail
Laboratory Temperature	deg C	18.9 to 25.6	21.6	Pass
Laboratory Relative Humidity	%	10 to 70	33	Pass
Probe Speed	m/s	2.07 to 2.13	2.12	Pass
Maximum Force	N	3450 to 4060	3892	Pass
Overall Test Results				Pass



 Laboratory Technician

12/12/2022

 Test Date




 Approved By



TEST DESC: RIGHT KNEE
VELOCITY: 6.97 ft/s, 2.12 m/s

TEST DATE: 12/12/2022
TEST #: D222835



X 10. Contact the knee with the test probe at a speed between 2.07 m/s and 2.13 m/s. (572.136(c)(5)) Neither the suspension hardware, suspension cables, nor other attachments to the probe, including the velocity vane, make contact with the dummy. (572.136(c)(6))

X 11. Complete the following table:
Knee Impact Results (572.136(b)(1) and 572.136(c)(5))

Parameter	Specification	Result
Probe speed	$2.07 \text{ m/s} \leq \text{speed} \leq 2.13 \text{ m/s}$	2.12 m/s
Peak resistance force*	$3450 \text{ N} \leq \text{force} \leq 4060 \text{ N}$	3892 N

*Force = impactor mass x deceleration (572.136(b)(2))

X 12. Plots of acceleration versus time and force versus time follow this sheet.



Signature

12/12/2022
Date

DATA SHEET B1
DUMMY DAMAGE CHECKLIST

Dummy Serial Number: 507

Test Date: 12/13/2022

Technician: Nathaniel Benjamin

This check sheet is completed as part of the post test calibration verification.

X Perform general cleaning.

Dummy Item	Inspect for	Comments	Damage	OK
Outer skin	Gashes, rips, cracks			X
Head	Ballast secure			X
	General appearance			X
Neck	Broken or cracked rubber			X
	Upper neck bracket firmly attached to the lower neck bracket			X
	Looseness at the condyle joint			X
	Nodding blocks cracked or out of position			X
Spine	Broken or cracks in rubber			X
Ribs	Broken or bent ribs			X
	Broken or bent rib supports			X
	Damping material separated or cracked			X
	Rubber bumpers in place			X
Chest Displacement Assembly	Bent shaft			X
	Slider arm riding in track			X
Transducer leads	Torn cables			X
Accelerometer Mountings	Head mounting secure			X
	Chest mounting secure			X
Knees	Skin condition			X
	Insert (do not remove)			X
	Casting			X
Limbs	Normal movement and adjustment			X
Knee Sliders	Wires intact			X
	Rubber returned to "at rest" position			X
Pelvis	Broken			X
Other				X

If upon visual examination, damage is apparent in any of these areas, the appropriate engineer or engineering technician is to be consulted for a decision on repair or replacement of parts.

Repair or Replacement approved by:

Nathaniel Benjamin
Signature

12/13/2022
Date

Describe the repair or replacement of parts:

Checked by:

Jose Salmeron
Signature

12/13/2022
Date

DATA SHEET B10

PART 572 INSTRUMENTATION CALIBRATION INFORMATION

I.D. NO.	MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF LAST CALIBRATION	DATE OF NEXT CALIBRATION
DUMMY INSTRUMENTATION					
HEAD ACCELEROMETERS					
(1) LONGITUDINAL	Endevco	7264C-2KTZ-2-360M17	P85158	11/16/2022	05/18/2023
(2) LATERAL	Endevco	7264C-2KTZ-2-360M17	P85159	11/16/2022	05/18/2023
(3) VERTICAL	Endevco	7264C-2KTZ-2-360M17	P85160	11/16/2022	05/18/2023
NECK TRANSDUCER	Denton	1716A	N2324	10/20/2022	04/21/2023
CHEST ACCELEROMETERS					
(1) LONGITUDINAL	Endevco	7264C-2KTZ-2-360M17	P79787	11/16/2022	05/18/2023
(2) LATERAL	Endevco	7264C-2KTZ-360M17	P86733	11/16/2022	05/18/2023
(3) VERTICAL	Endevco	7264C-2KTZ-360M17	P86735	11/16/2022	05/18/2023
CHEST POTENTIOMETER	Humanetics	880105-1080	507	11/16/2022	05/18/2023
FEMUR LOAD CELLS					
(1) RIGHT FEMUR	Denton	2121AJTF	F8151	11/16/2022	05/18/2023
(2) LEFT FEMUR	Denton	2121AJTF	F8152	11/16/2022	05/18/2023
LABORATORY INSTRUMENTATION					
NECK PENDULUM ACCELEROMETER	Endevco	7231C-750	AH5P1	07/15/2022	01/14/2023
THORAX PENDULUM ACCELEROMETER	Endevco	7264C-2KTZ-360M17	P97372	11/18/2022	05/20/2023
KNEE PENDULUM ACCELEROMETER	Endevco	7264C-2KTZ-2-360M17	P82128	11/30/2022	06/01/2023
NECK ROTATION TRANSDUCER 1 (OPTIONAL)	Servo	14CBI-2897	4707	08/12/2022	02/11/2023
NECK ROTATION TRANSDUCER 2 (OPTIONAL)	Servo	14CBI-2897	7297	08/12/2022	02/11/2023

LABORATORY TECHNICIAN: Nathaniel Benjamin