

**REPORT NUMBER: 208-MGA-2022-007**

**VEHICLE SAFETY COMPLIANCE TESTING  
FOR  
FMVSS 208, OCCUPANT CRASH PROTECTION  
FMVSS 212, WINDSHIELD MOUNTING  
FMVSS 219, WINDSHIELD INTRUSION (PARTIAL)  
FMVSS 301, FUEL SYSTEM INTEGRITY**

**HONDA OF CANADA MFG., A DIVISION OF HONDA OF CANADA INC.  
2022 HONDA CIVIC PASSENGER CAR  
NHTSA NO.: C20225305**

**PREPARED BY:  
MGA RESEARCH CORPORATION  
5000 WARREN ROAD  
BURLINGTON, WI 53105**



**TEST DATE: DECEMBER 8, 2022**


**FINAL REPORT DATE: DECEMBER 22, 2022**

**FINAL REPORT**

**PREPARED FOR:  
U.S. DEPARTMENT OF TRANSPORTATION  
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION  
ENFORCEMENT  
OFFICE OF VEHICLE SAFETY COMPLIANCE  
1200 NEW JERSEY AVENUE, S.E.  
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, in response to Contract Number 693JJ919D000012.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by:  Date: December 22, 2022  
Jose Galvez, Project Engineer

Reviewed by:  Date: December 22, 2022  
David Winkelbauer, Facility Director

Accepted By: \_\_\_\_\_

Acceptance Date: \_\_\_\_\_

**Technical Report Documentation Page**

1. Report No. 208-MGA-2022-007		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle Final Report of FMVSS 208 Compliance Testing of a 2022 Honda Civic NHTSA No.: C20225305				5. Report Date December 22, 2022	
				6. Performing Organization Code MGA	
7. Author(s) Jose Galvez, Project Engineer				8. Performing Organization Report No. 208-MGA-2022-007	
9. Performing Organization Name and Address MGA Research Corporation 5000 Warren Road Burlington, WI 53105				10. Work Unit No.	
				11. Contract or Grant No. 693JJ919D000012	
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Enforcement Office of Vehicle Safety Compliance Mail Code: NEF-240 1200 New Jersey Avenue, S.E. Washington, D.C. 20590				13. Type of Report and Period Covered 12/8/22	
				14. Sponsoring Agency Code NEF-240	
15. Supplementary Notes					
16. Abstract Compliance tests were conducted on the subject 2022 Honda Civic in accordance with the specifications of the Office of Vehicle Safety Compliance Test Procedure No. TP208-14. Test failures identified were as follows:  TEST FAILURES: None					
17. Key Words  Frontal Impact 56 kmph Vehicle Safety Compliance Testing FMVSS 208, "Occupant Crash Protection" FMVSS 212, "Windshield Mounting" FMVSS 219, (partial), "Windshield Zone Intrusion" FMVSS 301, "Fuel System Integrity"				18. Distribution Statement Copies of this report are available from the following: U.S. Department of Transportation National Highway Traffic Safety Administration Technical Information Services (TIS) Mail Code: NIO-120 1200 New Jersey Avenue, S.E. Washington, DC 20590 Phone: 202-366-2588	
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 156	22. Price

## TABLE OF CONTENTS

<u>Section</u>		<u>Page No</u>
1	Purpose of Compliance Tests	1
2	Tests Performed	2
3	Injury Result Summary for FMVSS 208 Tests	4
4	Discussion of Tests (if applicable)	5
5	Test Data Sheets	6
<u>Data Sheet</u>		
1	COTR Vehicle Work Order	7
2	Report of Vehicle Condition	12
3	Certification Label and Tire Placard Information	14
32	Vehicle Weight, Fuel Tank, and Attitude Data	15
33	Vehicle Accelerometer Locations and Measurements	19
34	Photographic Targets	22
35	Camera Locations	27
36	Dummy Positioning	29
37	Dummy Measurements	45
38	Crash Test	48
40	Accident Investigation Measurements	50
41	Windshield Mounting (FMVSS 212)	52
42	Windshield Zone Intrusion (FMVSS 219)	54
43	Fuel System Integrity (FMVSS 301)	56
<u>Appendix</u>		
A	Crash Test Data	A-1
B	Crash Test Photographs	B-1
C	Instrumentation Calibration	C-1
D	Notice of Test Failure (If Applicable)	D-1

**SECTION 1**  
**PURPOSE OF COMPLIANCE TESTS**

This Federal Motor Vehicle Safety Standard 208 compliance test is part of a program conducted for the National Highway Traffic Safety Administration (NHTSA) by MGA Research Corporation (MGA) under Contract No.: 693JJ919D000012. The purpose of this test was to determine whether the subject vehicle, a 2022 Honda Civic, NHTSA No.: C20225305, meets certain performance requirements of FMVSS 208, "Occupant Crash Protection"; FMVSS 212, "Windshield Mounting"; FMVSS 219, "Windshield Zone Intrusion"; and FMVSS 301, "Fuel System Integrity". The compliance test was conducted in accordance with OVSC Laboratory Test Procedure No.: TP208-14 dated April 16, 2008.

**SECTION 2**  
**TESTS PERFORMED**

Test Vehicle: 2022 Honda Civic  
Test Program: FMVSS 208 Compliance

NHTSA No.: C20225305  
Test Dates: 12/8/22

The following checked items indicate the tests that were performed:

- |                                     |     |   |
|-------------------------------------|-----|---|
| <input type="checkbox"/>            | 1.  | Rear seating position seat belts  |
| <input type="checkbox"/>            | 2.  | Air bag labels (S4.5.1)   |
| <input type="checkbox"/>            | 3.  | Readiness indicator (S4.5.2)  |
| <input type="checkbox"/>            | 4.  | Passenger air bag manual cut-off device (S4.5.4)  |
| <input type="checkbox"/>            | 5.  | Lap belt lockability (S7.1.1.5)   |
| <input type="checkbox"/>            | 6.  | Seat belt warning system (S7.3)   |
| <input type="checkbox"/>            | 7.  | Seat belt contact force (S7.4.3)  |
| <input type="checkbox"/>            | 8.  | Seat belt latch plate access (S7.4.4)   |
| <input type="checkbox"/>            | 9.  | Seat belt retraction (S7.4.5)   |
| <input type="checkbox"/>            | 10. | Seat belt guides and hardware (S7.4.6)  |
| <input type="checkbox"/>            | 11. | Air bag suppression telltale (S19.2.2)  |
| <input type="checkbox"/>            | 12. | Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R)   |
| <input type="checkbox"/>            | 13. | Suppression tests with Newborn infant (Part 572, Subpart K)   |
| <input type="checkbox"/>            | 14. | Suppression tests with 3-year-old dummy (Part 572, Subpart P)   |
| <input type="checkbox"/>            | 15. | Suppression tests with 6-year-old dummy (Part 572, Subpart N)   |
| <input type="checkbox"/>            | 16. | Test of Reactivation of the passenger air bag system with an unbelted 5 <sup>th</sup> percentile female dummy |
| <input type="checkbox"/>            | 17. | Low risk deployment test with 12-month-old dummy (Part 572, Subpart R)  |
| <input type="checkbox"/>            | 18. | Low risk deployment test with 3-year-old dummy (Part 572, Subpart P)  |
| <input type="checkbox"/>            | 19. | Low risk deployment test with 6-year-old dummy (Part 572, Subpart N)  |
| <input type="checkbox"/>            | 20. | Low risk deployment test with 5 <sup>th</sup> female dummy (Part 572, Subpart O)                              |
| <input checked="" type="checkbox"/> | 21. | Impact Tests  |
| <input type="checkbox"/>            |     | Frontal Oblique   |
| <input type="checkbox"/>            |     | Belted 50 <sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a))                            |
| <input type="checkbox"/>            |     | Unbelted 50 <sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1))                       |
| <input type="checkbox"/>            |     | Unbelted 50 <sup>th</sup> male dummy driver and passenger (32 to 56 kmph) (S5.1.2(a)(1) or S5.1.2(b))         |
| <input checked="" type="checkbox"/> |     | Frontal 0°  |
| <input type="checkbox"/>            |     | Belted 50 <sup>th</sup> male dummy driver (0 to 56 kmph) (S5.1.1(b)(2))                                       |
| <input type="checkbox"/>            |     | Belted 50 <sup>th</sup> male dummy passenger (0 to 56 kmph) (S5.1.1.(b)(2))                                   |
| <input checked="" type="checkbox"/> |     | Belted 5 <sup>th</sup> female dummy driver (0 to 56 kmph) (S16.1(a)(2))                                       |
| <input checked="" type="checkbox"/> |     | Belted 5 <sup>th</sup> female dummy passenger (0 to 56 kmph) (S16.1(a)(2))                                    |
| <input type="checkbox"/>            |     | Unbelted 50 <sup>th</sup> male dummy driver (32 to 40 kmph) (S5.1.2(b))                                       |
| <input type="checkbox"/>            |     | Unbelted 50 <sup>th</sup> male dummy passenger (32 to 40 kmph) (S5.1.2(b))                                    |
| <input type="checkbox"/>            |     | Unbelted 5 <sup>th</sup> female dummy driver (32 to 40 kmph) (S16.1(b))                                       |
| <input type="checkbox"/>            |     | Unbelted 5 <sup>th</sup> female dummy passenger (32 to 40 kmph) (S16.1(b))                                    |
| <input type="checkbox"/>            |     | 40% Offset 0° Belted 5 <sup>th</sup> female dummy driver and passenger (0 to 56 kmph) (S18.1)                 |
| <input type="checkbox"/>            | 22. | FMVSS 204 Indicant Test   |
| <input checked="" type="checkbox"/> | 23. | FMVSS 212 Indicant Test   |
| <input checked="" type="checkbox"/> | 24. | FMVSS 219 Indicant Test   |
| <input checked="" type="checkbox"/> | 25. | FMVSS 301 Frontal Test  |
| <input type="checkbox"/>            | 26. | FMVSS 305 Frontal Indicant Test   |

For the crash tests, the vehicle was instrumented with 8 accelerometers. The data from the vehicle and dummies were sampled at 10,000 samples per second and processed as specified in SAE J211/1 MAR95 and FMVSS 208, S4.13.

The dynamic tests were recorded using high-speed digital video.

The vehicle appears to meet the performance requirements to which it was tested.

**SECTION 3**

**INJURY RESULT SUMMARY FOR FMVSS 208 TESTS**

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance

NHTSA No.: C20225305  
 Test Date: 12/8/22

**56 kmph Frontal Crash**

Impact Angle:	0°		
Belted Dummies:	X	Yes	No

Speed Range:		0 to 40 kmph		32 to 40 kmph
		0 to 48 kmph	X	0 to 56 kmph

Test Speed (kmph):	55.4	Test Weight (kg):	1455.1
--------------------	------	-------------------	--------

Driver Dummy:	X	5 <sup>th</sup> female		50 <sup>th</sup> male
Passenger Dummy:	X	5 <sup>th</sup> female		50 <sup>th</sup> male

**5<sup>th</sup> Percentile Female Frontal Crash Test  
 Vehicles certified to S16.1 (a) (1), S16.1 (a) (2), S16.1 (b), or S18.1**

Injury Criteria	Max. Allowable Injury Assessment Values	Driver	Passenger
HIC15	700	348	451
N <sub>te</sub>	1.0	0.4	0.3
N <sub>tf</sub>	1.0	0.1	0.2
N <sub>ce</sub>	1.0	0.4	0.0
N <sub>cf</sub>	1.0	0.1	0.3
Neck Tension	2620 N	787	907
Neck Compression	2520 N	60	565
Chest g	60 g	43	45
Chest Displacement	52 mm	13	14
Left Femur	6805 N	217	987
Right Femur	6805 N	1031	387

**SECTION 4**  
**DISCUSSION OF TESTS**

Test Vehicle: 2022 Honda Civic  
Test Program: FMVSS 208 Compliance

NHTSA No.: C20225305  
Test Dates: 12/8/22

There was no valid data after 30.9 msec on the Bottom of Engine (X) accelerometer during the frontal impact crash test.

**SECTION 5**  
**TEST DATA SHEETS**

Test Vehicle: 2022 Honda Civic  
Test Program: FMVSS 208 Compliance

NHTSA No.: C20225305  
Test Dates: 12/8/22

**DATA SHEET 1**  
**COTR VEHICLE WORK ORDER**

Test Vehicle: 2022 Honda Civic  
Test Program: FMVSS 208 Compliance

NHTSA No.: C20225305  
Test Dates: 12/8/22

COTR Signature: Syed Rahaman

Test to be performed for this vehicle are checked below:

- |                                     |     |  |   |  |  |
|-------------------------------------|-----|--|---|--|--|
| <input checked="" type="checkbox"/> | 1.  | Rear Seating Position Seat Belts   |   |  |  |
| <input checked="" type="checkbox"/> | 2.  | Air Bag Labels (S4.5.1)  |   |  |  |
| <input checked="" type="checkbox"/> | 3.  | Readiness Indicator (S4.5.2)   |   |  |  |
| <input checked="" type="checkbox"/> | 4.  | Passenger Air Bag Manual Cut-off Device (S4.5.4)   |   |  |  |
| <input checked="" type="checkbox"/> | 5.  | Lap Belt Lockability (S7.1.1.5)  |   |  |  |
| <input checked="" type="checkbox"/> | 6.  | Seat Belt Warning System (S7.3)  |   |  |  |
| <input checked="" type="checkbox"/> | 7.  | Seat Belt Contact Force (S7.4.3)   |   |  |  |
| <input checked="" type="checkbox"/> | 8.  | Seat Belt Latch Plate Access (S7.4.4)  |   |  |  |
| <input checked="" type="checkbox"/> | 9.  | Seat Belt Retraction (S7.4.5)  |   |  |  |
| <input checked="" type="checkbox"/> | 10. | Seat Belt Guides and Hardware (S7.4.6)   |   |  |  |
| <input checked="" type="checkbox"/> | 11. | Air bag suppression telltale (S19.2.2)   |   |  |  |
| <input checked="" type="checkbox"/> | 12. | Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R) using the following indicated child restraints (mid-height seat position): |   |  |  |
|                                     |     | Section B – Rear Facing (unbelted and belted rear facing, unbelted forward facing)   |   |  |  |
| <input checked="" type="checkbox"/> |     | Century Smart Fit 4543   | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Cosco Arriva 22-013  | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Evenflo Discovery Adjust Right 212   | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Graco Infant 8457  | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Graco Snugride   | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Peg Perego Viaggio   | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
|                                     |     | Section C – Convertible (unbelted and belted rear facing, unbelted and belted forward facing)  |   |  |  |
| <input checked="" type="checkbox"/> |     | Britax Roundabout E9L02  | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Cosco High Back Booster 22-209   | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Cosco Summit Deluxe 22-262   | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Cosco Touriva 02519  | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Evenflo Generations 352  | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Evenflo Medallion 254  | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Evenflo Tribute V 379  | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Graco ComfortSport   | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Graco Platinum Cargo   | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> |     | Graco Safeseat Step 2  | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |
| <input checked="" type="checkbox"/> | 13. | Suppression tests with newborn infant (Part 572, Subpart K) using the following indicated child restraints (mid-height seat position):           |   |  |  |
|                                     |     | Section A – Car Bed (Belted)   |   |  |  |
| <input checked="" type="checkbox"/> |     | Angel Guard Angel Ride   | <input checked="" type="checkbox"/> Full Rearward | <input checked="" type="checkbox"/> Mid Position | <input checked="" type="checkbox"/> Full Forward |

14. Suppression tests with 3-year-old dummy (Part 572, Subpart P) using the following indicated child restraints where a child restraint is required (mid-height seat position):

Section C – Convertible (Belted forward-facing)

Britax Roundabout E9L02	Full Rearward	Mid Position	Full Forward
Cosco High Back Booster 22-209	Full Rearward	Mid Position	Full Forward
Cosco Summit Deluxe 22-262	Full Rearward	Mid Position	Full Forward
Cosco Touriva 02519	Full Rearward	Mid Position	Full Forward
Evenflo Generations 352	Full Rearward	Mid Position	Full Forward
Evenflo Medallion 254	Full Rearward	Mid Position	Full Forward
Evenflo Tribute V 379	Full Rearward	Mid Position	Full Forward
Graco ComfortSport	Full Rearward	Mid Position	Full Forward
Graco Platinum Cargo	Full Rearward	Mid Position	Full Forward
Graco Safeseat Step 2	Full Rearward	Mid Position	Full Forward

Section D – Toddler/Belt Positioning Booster (Belted)

Britax Roadster 9004	Full Rearward	Mid Position	Full Forward
Cosco High Back Booster 22-209	Full Rearward	Mid Position	Full Forward
Cosco Summit Deluxe 22-262	Full Rearward	Mid Position	Full Forward
Evenflo Generations 352	Full Rearward	Mid Position	Full Forward
Evenflo Right Fit 245	Full Rearward	Mid Position	Full Forward
Graco Platinum Cargo	Full Rearward	Mid Position	Full Forward

15. Suppression tests with representative 3-year-old child using the following indicated child restraints where a child restraint is required (mid-height position).

(Appendix H, Data Sheet 19H and 20H)

Section C – Convertible (Belted forward-facing)

Britax Roundabout E9L02	Full Rearward	Mid Position	Full Forward
Cosco High Back Booster 22-209	Full Rearward	Mid Position	Full Forward
Cosco Summit Deluxe 22-262	Full Rearward	Mid Position	Full Forward
Cosco Touriva 02519	Full Rearward	Mid Position	Full Forward
Evenflo Generations 352	Full Rearward	Mid Position	Full Forward
Evenflo Medallion 254	Full Rearward	Mid Position	Full Forward
Evenflo Tribute V 379	Full Rearward	Mid Position	Full Forward
Graco ComfortSport	Full Rearward	Mid Position	Full Forward
Graco Platinum Cargo	Full Rearward	Mid Position	Full Forward
Graco Safeseat Step 2	Full Rearward	Mid Position	Full Forward

Section D – Toddler/Belt Positioning Booster (Belted)

Britax Roadster 9004	Full Rearward	Mid Position	Full Forward
Cosco High Back Booster 22-209	Full Rearward	Mid Position	Full Forward
Evenflo Right Fit 245	Full Rearward	Mid Position	Full Forward

16. Suppression tests with 3-year-old dummy (Part 572, Subpart P) in the following positions (mid-height seat position):
- Sitting on seat with back against seat back (S22.2.2.1)
    - Full Rearward     Mid Position     Full Forward
  - Sitting on seat with back against reclined seat back (S22.2.2.2)
    - Full Rearward     Mid Position     Full Forward
  - Sitting on seat with back not against seat back (S22.2.2.3)
    - Full Rearward     Mid Position     Full Forward
  - Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
    - Full Rearward     Mid Position     Full Forward
  - Standing on seat, facing forward (S22.2.2.5)
    - Full Rearward     Mid Position     Full Forward
  - Kneeling on seat facing forward (S22.2.2.6)
    - Full Rearward     Mid Position     Full Forward
  - Kneeling on seat facing rearward (S22.2.2.7)
    - Full Rearward     Mid Position     Full Forward
  - Lying on seat (S22.2.2.8)
    - Full Rearward     Mid Position     Full Forward
17. Suppression tests with representative 3-year-old child in the following positions (mid-height seat position):
- Sitting on seat with back against seat back (S22.2.2.1)
    - Full Rearward     Mid Position     Full Forward
  - Sitting on seat with back against reclined seat back (S22.2.2.2)
    - Full Rearward     Mid Position     Full Forward
  - Sitting on seat with back not against seat back (S22.2.2.3)
    - Full Rearward     Mid Position     Full Forward
  - Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
    - Full Rearward     Mid Position     Full Forward
  - Standing on seat, facing forward (S22.2.2.5)
    - Full Rearward     Mid Position     Full Forward
  - Kneeling on seat facing forward (S22.2.2.6)
    - Full Rearward     Mid Position     Full Forward
  - Kneeling on seat facing rearward (S22.2.2.7)
    - Full Rearward     Mid Position     Full Forward
  - Lying on seat (S22.2.2.8)
    - Full Rearward     Mid Position     Full Forward
18. Suppression tests with 6-year-old dummy (Part 572, Subpart N) using the following indicated child restraints where a child restraint is required (mid-height seat position):
- Section D
- |   |  |                                       |                                       |
|---|--|---------------------------------------|---------------------------------------|
| <input type="checkbox"/> Britax Roadster 9004           | <input type="checkbox"/> Full Rearward | <input type="checkbox"/> Mid Position | <input type="checkbox"/> Full Forward |
| <input type="checkbox"/> Cosco High Back Booster 22-209 | <input type="checkbox"/> Full Rearward | <input type="checkbox"/> Mid Position | <input type="checkbox"/> Full Forward |
| <input type="checkbox"/> Cosco Summit Deluxe 22-262     | <input type="checkbox"/> Full Rearward | <input type="checkbox"/> Mid Position | <input type="checkbox"/> Full Forward |
| <input type="checkbox"/> Evenflo Generations 352        | <input type="checkbox"/> Full Rearward | <input type="checkbox"/> Mid Position | <input type="checkbox"/> Full Forward |
| <input type="checkbox"/> Evenflo Right Fit 245          | <input type="checkbox"/> Full Rearward | <input type="checkbox"/> Mid Position | <input type="checkbox"/> Full Forward |
| <input type="checkbox"/> Graco Platinum Cargo           | <input type="checkbox"/> Full Rearward | <input type="checkbox"/> Mid Position | <input type="checkbox"/> Full Forward |

19. Suppression tests with representative 6-year-old child using the following indicated child restraints where a child restraint is required (mid-height seat position):
- Section D
- |                          |                                |                          |               |                          |              |                          |              |
|--------------------------|--------------------------------|--------------------------|---------------|--------------------------|--------------|--------------------------|--------------|
| <input type="checkbox"/> | Britax Roadster 9004           | <input type="checkbox"/> | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |
| <input type="checkbox"/> | Cosco High Back Booster 22-209 | <input type="checkbox"/> | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |
| <input type="checkbox"/> | Cosco Summit Deluxe 22-262     | <input type="checkbox"/> | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |
| <input type="checkbox"/> | Evenflo Generations 352        | <input type="checkbox"/> | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |
| <input type="checkbox"/> | Evenflo Right Fit 245          | <input type="checkbox"/> | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |
| <input type="checkbox"/> | Graco Platinum Cargo           | <input type="checkbox"/> | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |
20. Suppression tests with 6-year-old dummy (Part 572, Subpart N) in the following positions (mid-height seat position):
- |                          |  |               |                          |              |                          |              |  |
|--------------------------|--|---------------|--------------------------|--------------|--------------------------|--------------|--|
| <input type="checkbox"/> | Sitting on seat with back against seat back (S22.2.2.1)                          |               |                          |              |                          |              |  |
| <input type="checkbox"/> | <input type="checkbox"/>   | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |  |
| <input type="checkbox"/> | Sitting on seat with back against reclined seat back (S22.2.2.2)                 |               |                          |              |                          |              |  |
| <input type="checkbox"/> | <input type="checkbox"/>   | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |  |
| <input type="checkbox"/> | Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)      |               |                          |              |                          |              |  |
| <input type="checkbox"/> | <input type="checkbox"/>   | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |  |
| <input type="checkbox"/> | Sitting back in the seat and leaning on the right front passenger door (S24.2.3) |               |                          |              |                          |              |  |
| <input type="checkbox"/> | <input type="checkbox"/>   | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |  |
21. Suppression tests with representative 6-year-old child in the following positions (mid-height seat position):
- |                          |  |               |                          |              |                          |              |  |
|--------------------------|--|---------------|--------------------------|--------------|--------------------------|--------------|--|
| <input type="checkbox"/> | Sitting on seat with back against seat back (S22.2.2.1)                          |               |                          |              |                          |              |  |
| <input type="checkbox"/> | <input type="checkbox"/>   | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |  |
| <input type="checkbox"/> | Sitting on seat with back against reclined seat back (S22.2.2.2)                 |               |                          |              |                          |              |  |
| <input type="checkbox"/> | <input type="checkbox"/>   | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |  |
| <input type="checkbox"/> | Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)      |               |                          |              |                          |              |  |
| <input type="checkbox"/> | <input type="checkbox"/>   | Full Rearward | <input type="checkbox"/> | Mid Position | <input type="checkbox"/> | Full Forward |  |
| <input type="checkbox"/> | Sitting back in the seat and leaning on the right front passenger door (S24.2.3) |               |                          |              |                          |              |  |
22. Test of Reactivation of the Passenger Air Bag System with an Unbelted 5<sup>th</sup> percentile female dummy (S20.3, 22.3, S24.3) (mid-height seat position). Perform this test after the following suppression tests: After each restraint.
23. Test of Reactivation of the Passenger Air Bag System with a 5<sup>th</sup> percentile Female Dummy (S20.3, 22.3, S24.3) (mid-height seat position). Perform this test after the following suppression tests: After each restraint.
24. Low risk deployment test with 12-month-old dummy (Part 572, Subpart R) using the following indicated child restraints (full forward, mid-height seat position)(S20.4):
- Section B
- |                          |                                    |
|--------------------------|------------------------------------|
| <input type="checkbox"/> | Century Smart Fit 4543             |
| <input type="checkbox"/> | Cosco Arriva 22-013                |
| <input type="checkbox"/> | Evenflo Discovery Adjust Right 212 |
| <input type="checkbox"/> | Graco Infant 8457                  |
| <input type="checkbox"/> | Graco Snugride                     |
| <input type="checkbox"/> | Peg Perego Viaggio                 |
- Section C
- |                          |                         |
|--------------------------|-------------------------|
| <input type="checkbox"/> | Britax Roundabout E9L02 |
| <input type="checkbox"/> | Cosco Touriva 02519     |
| <input type="checkbox"/> | Evenflo Medallion 254   |
| <input type="checkbox"/> | Evenflo Tribute V 379   |
| <input type="checkbox"/> | Graco ComfortSport      |

25. Low risk deployment test with 3-year-old dummy (Part 572, Subpart P) in the following positions:  
 Position 1 (rearmost, lowest seat position)  
 Position 2 (mid-height seat position)
26. Low risk deployment test with 6-year-old dummy (Part 572, Subpart N) in the following positions:  
 Position 1 (rearmost, lowest seat position)  
 Position 2 (mid-height seat position)
27. Low risk deployment test with 5<sup>th</sup> female dummy (Part 572, Subpart O) in the following positions:  
 Position 1 (mid-height seat position)  
 Position 2 (mid-height seat position)
28. Impact Tests
- | <input type="checkbox"/>            | Frontal Oblique          | Impact Angle:   | Test Speed: |
|-------------------------------------|--------------------------|---|-------------|
| <input type="checkbox"/>            | <input type="checkbox"/> | Belted 50 <sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a))                    |             |
| <input type="checkbox"/>            | <input type="checkbox"/> | Unbelted 50 <sup>th</sup> male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1))               |             |
| <input type="checkbox"/>            | <input type="checkbox"/> | Unbelted 50 <sup>th</sup> male dummy driver and passenger (32 to 56 kmph) (S5.1.2(a)(2) or S5.1.2(b)) |             |
| <input checked="" type="checkbox"/> | <input type="checkbox"/> | Frontal 0° - Test Speed: 55.4 kmph  |             |
| <input type="checkbox"/>            | <input type="checkbox"/> | Belted 50 <sup>th</sup> male dummy driver (0 to 56 kmph) (S5.1.1(b)(2))                               |             |
| <input type="checkbox"/>            | <input type="checkbox"/> | Belted 50 <sup>th</sup> male dummy passenger (0 to 56 kmph) (S5.1.1.(b)(2))                           |             |
| <input checked="" type="checkbox"/> | <input type="checkbox"/> | Belted 5 <sup>th</sup> female dummy driver (0 to 56 kmph) (S16.1(a)(2))                               |             |
| <input checked="" type="checkbox"/> | <input type="checkbox"/> | Belted 5 <sup>th</sup> female dummy passenger (0 to 56 kmph) (S16.1(a)(2))                            |             |
| <input type="checkbox"/>            | <input type="checkbox"/> | Unbelted 50 <sup>th</sup> male dummy driver (32 to 40 kmph) (S5.1.2(b))                               |             |
| <input type="checkbox"/>            | <input type="checkbox"/> | Unbelted 50 <sup>th</sup> male dummy passenger (32 to 40 kmph) (S5.1.2(b))                            |             |
| <input type="checkbox"/>            | <input type="checkbox"/> | Unbelted 5 <sup>th</sup> female dummy driver (32 to 40 kmph) (S16.1(b))                               |             |
| <input type="checkbox"/>            | <input type="checkbox"/> | Unbelted 5 <sup>th</sup> female dummy passenger (32 to 40 kmph) (S16.1(b))                            |             |
| <input type="checkbox"/>            | <input type="checkbox"/> | 40% Offset 0° Belted 5 <sup>th</sup> female dummy driver and passenger (0 to 56 kmph) (S18.1)         |             |
|                                     |                          | Test Speed:   |             |
29. FMVSS 204 Indicant Test
30. FMVSS 212 Indicant Test
31. FMVSS 219 Indicant Test
32. FMVSS 301 Frontal Test
33. FMVSS 305 Frontal Indicant Test

**DATA SHEET 2**  
**REPORT OF VEHICLE CONDITION**

Test Vehicle: 2022 Honda Civic NHTSA No.: C20225305  
Test Program: FMVSS 208 Compliance Test Dates: 12/8/22

CONTRACT NO.: 693JJ919D000012 Date: 12/15/22  
FROM (Lab and rep name): MGA Research Corporation  
TO: NHTSA, OVSC, NVS-220 The vehicle is owned by MGA Research Corporation

PURPOSE: ( ) Initial Receipt ( ) Received via Transfer (X) Present vehicle condition

MODEL YEAR/MAKE/MODEL/BODY STYLE: 2022 Honda Civic Passenger Car  
MANUFACTURE DATE: 10/22  
NHTSA NO. C20225305 GVWR: 1760 kg (3880 lbs)  
BODY COLOR: Lunar Silver GAWR (Fr): 940 kg (2072 lbs)  
VIN: 2HGFE2F53NH609646 GAWR (Rr): 835 kg (1840 lbs)

ODOMETER READINGS: ARRIVAL (miles): 6 DATE: 11/16/22  
COMPLETION (miles): 8 DATE: 12/8/22

PURCHASE PRICE: (\$) 25,045

DEALER'S NAME: McGrath Honda of St. Charles  
1411 East Main St., St. Charles, IL 60174

- A. All options listed on window sticker are present on the test vehicle:  
 Yes  No
- B. Tires and wheel rims are new and the same as listed:  Yes  No
- C. There are no dents or other interior or exterior flaws:  Yes  No
- D. The vehicle has been properly prepared and is in running condition:  
 Yes  No
- E. Keyless remote is available and working:  Yes  No
- F. The glove box contains an owner's manual, warranty document, consumer information, and extra set of keys:  Yes  No
- G. Proper fuel filler cap is supplied on the test vehicle:  Yes  No
- H. Using permanent marker, identify vehicle with NHTSA number and FMVSS test type(s) on roof line above driver door or for school buses, place a placard with NHTSA number inside the windshield and to the exterior front and rear side of bus:  
 Yes  No
- I. Place vehicle in storage area:  Yes  No
- J. Inspect the vehicle's interior and exterior, including all windows, seats, doors, etc. to confirm that each system is complete and functional per the manufacturer's specifications. Any damage, misadjustment, or other unusual condition that could influence the test program or test results shall be recorded. Report any abnormal condition to the NHTSA COTR before beginning any test:  
 Vehicle OK  Conditions reported below in comment section

Identify the letter above to which any of the following comments apply.

Comments: \_\_\_\_\_  
\_\_\_\_\_

**REPORT OF VEHICLE CONDITION AT THE COMPLETION OF TESTING**

LIST OF FMVSS TESTS PERFORMED BY THIS LAB: FMVSS 208, 212, 219, 301

VEHICLE: 2022 Honda Civic

NHTSA NO.: C20225305

REMARKS: The vehicle is owned by MGA Research Corporation

Equipment that is no longer on the test vehicle as noted on previous page:

Spare Tire and Cover, Jack and Tools, Right Tail Light

Explanation for equipment removal:

Components removed for instrumentation installation and to meet target weight.

Test Vehicle Condition:

35 mph frontal impact damage- front suspension & structure damaged, hood & front quarter panels damaged, radiator damaged, air bags & pretensioners deployed, Stoddard in fuel system

RECORDED BY: Jose Galvez

DATE: 12/15/22

APPROVED BY: David Winkelbauer

DATE: 12/15/22

#####

**RELEASE OF TEST VEHICLE**

The vehicle described above is released from MGA to be delivered to:

The vehicle is owned by MGA Research Corporation

Date:

Time:

Odometer:

Lab Rep's Signature:

Title:

Carrier/Customer Rep:

Date:

**DATA SHEET 3**


**CERTIFICATION LABEL AND TIRE PLACARD INFORMATION**

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Ben Storey

NHTSA No.: C20225305  
 Test Date: 12/8/22

<b>Certification Label (Part 567)</b>	
Manufacturer:	HONDA OF CANADA MFG., A DIVISION OF HONDA CANADA INC.
Date of Manufacture:	10/22
VIN:	2HGFE2F53NH609646
Vehicle Certified As (Pass. Car/MPV/Truck/Bus):	Passenger Car
Front Axle GVWR:	940 kg (2072 lbs)
Rear Axle GVWR:	835 kg (1840 lbs)
Total GVWR:	1760 kg (3880 lbs)

<b>Tire Placard for Motor Vehicles with GVWR of 10,000 lb or Less and Passenger Cars (571.110)</b>	
Vehicle Capacity Weight:	385 kg (850 lbs)
Designated Seating Capacity Front:	2
Designated Seating Capacity Rear:	3
Total Designated Seating Capacity:	5
Recommended Cold Tire Inflation Pressure Front:	225 kpa (33 psi)
Recommended Cold Tire Inflation Pressure Rear:	220 kpa (32 psi)
Recommended Tire Size:	235/40R18
Tire Size on Vehicle:	235/40R18

Signature: 

Date: 12/8/22

## DATA SHEET 32

### VEHICLE WEIGHT, FUEL TANK, AND ATTITUDE DATA

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Ben Storey

NHTSA No.: C20225305  
 Test Date: 12/8/22

IMPACT ANGLE:	0°			
BELTED DUMMIES (YES/NO):	YES			
TEST SPEED:	32 to 56 kmph	0 to 48 kmph	X	0 to 56 kmph
DRIVER DUMMY:	X	5 <sup>th</sup> female		50 <sup>th</sup> male
PASSENGER DUMMY:	X	5 <sup>th</sup> female		50 <sup>th</sup> male

- 1. Fill the transmission with transmission fluid to the satisfactory range.
- 2. Drain fuel from vehicle.
- 3. Run the engine until fuel remaining in the fuel delivery system is used and the engine stops.
- 4. Record the useable fuel tank capacity supplied by the COTR.
- Useable Fuel Tank Capacity supplied by COTR: 46.9 liters (12.4 gallons)
- 5. Record the fuel tank capacity supplied in the owner's manual.
- Useable Fuel Tank Capacity in owner's manual: 46.9 liters (12.4 gallons)
- 6. Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," or gasoline, fill the fuel tank.
- Amount Added: 46.9 liters (12.4 gallons)
- 7. Fill the coolant system to capacity.
- 8. Fill the engine with motor oil to the Max. mark on the dip stick.
- 9. Fill the brake reservoir with brake fluid to its normal level.
- 10. Fill the windshield washer reservoir to capacity.
- 11. Inflate the tires to the tire pressure on the tire placard. If no tire placard is available, inflate the tires to the recommended pressure in the owner's manual.

Tire placard pressure:	RF:	33 psi	LF:	33 psi	RR:	32 psi	LR:	32 psi
Owner's manual pressure:	RF:	33 psi	LF:	33 psi	RR:	32 psi	LR:	32 psi
Actual inflated pressure:	RF:	33 psi	LF:	33 psi	RR:	32 psi	LR:	32 psi

- 12. Record the vehicle weight at each wheel to determine the unloaded vehicle weight (UVW), i.e. "as delivered" weight).

Right Front (kg):	394.2	Right Rear (kg):	260.4
Left Front (kg):	407.8	Left Rear (kg):	257.6
Total Front (kg):	802.0	Total Rear (kg):	518.0
% Total Weight:	60.8	% Total Weight:	39.2
UVW = TOTAL FRONT PLUS TOTAL REAR (KG):		1320.0	

- 13. UVW Test Vehicle Attitude: (All dimensions in millimeters)
- 13.1 Mark a point on the vehicle above the center of each wheel.
- 13.2 Place the vehicle on a level surface.
- 13.3 Measure perpendicular to the level surface to the 4 points marked on the body and record the measurements.

RF:	681	LF:	677	RR:	682	LR:	678
-----	-----	-----	-----	-----	-----	-----	-----

14. Calculate the Rated Cargo and Luggage Weight (RCLW): 45 kg
- 14.1 Does the vehicle have the vehicle capacity weight (VCW) on the certification label or tire placard?
- Yes, go to 14.3
- No, go to 14.2
- 14.2 VCW = Gross Vehicle Weight - UVW
- VCW = \_\_\_\_\_ - \_\_\_\_\_ = \_\_\_\_\_

- 14.3 VCW = 385 kg (850 lbs)
- 14.4 Does the certification or tire placard contain the Designated Seating Capacity (DSC)?
- Yes, go to 14.6
- No, go to 14.5 and skip 14.6
- 14.5 DSC = Total number of seat belt assemblies = \_\_\_\_\_
- 14.6 DSC = 5
- 14.7 RCLW = VCW - (68 kg x DSC) = 385 kg - (68 kg x 5) = 45 kg
- 14.8 Is the vehicle certified as a truck, MPV or bus (see the certification label on the door jamb)?
- Yes, if the calculated RCLW is greater than 136 kg, use 136 kg as the RCLW. (S8.1.1)
- No, use the RCLW calculated in 14.7

15. Fully Loaded Weight (100% fuel fill): 1463.3 kg
- 15.1 Place the appropriate test dummy in both front outboard seating positions.
- Driver:         5<sup>th</sup> female    \_\_\_ 50<sup>th</sup> male
- Passenger:     5<sup>th</sup> female    \_\_\_ 50<sup>th</sup> male

- 15.2 Load the vehicle with the RCLW from 14.7 or 14.8 whichever is applicable.
- 15.3 Place the RCLW in the cargo area. Center the load over the longitudinal centerline of the vehicle. (S8.1.1 (d))
- 15.4 Record the vehicle weight at each wheel to determine the Fully Loaded Weight.

Right Front (kg):	413.7	Right Rear (kg):	310.7
Left Front (kg):	430.0	Left Rear (kg):	308.9
Total Front (kg):	843.7	Total Rear (kg):	619.6
% Total Weight:	57.7	% Total Weight:	42.3
% GVW	53.4	% GVW	47.4
(% GVW = Axle GVW divided by Vehicle GVW)			
Fully Loaded Weight = Total Front Plus Total Rear (kg):	1463.3		

16. Fully Loaded Test Vehicle Attitude: (All dimensions in millimeters)
- 16.1 Place the vehicle on a level surface.
- 16.2 Measure perpendicular to the level surface to the 4 points marked on the body (see 13.1 above) and record the measurements.

RF:	676	LF:	670	RR:	660	LR:	662
-----	-----	-----	-----	-----	-----	-----	-----

17. Drain the fuel system.

18. Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," fill the fuel tank to 92 - 94 percent of useable capacity.

Fuel tank capacity x .94 = 46.9 liters (12.4 gallons) x .94 = 44.1 liters (11.7 gallons)  
 Amount added: 43.6 liters (11.53 gallons) 93.0%

19. Crank the engine to fill the fuel delivery system with Stoddard solvent.

20. Calculate the test weight range.

20.1 Calculated Weight = UVW (see 12 above) + RCLW (see 14 above) + 2x(dummy weight)

$$\underline{1463.0 \text{ kg}} = \underline{1320.0 \text{ kg}} + \underline{45.0 \text{ kg}} + \underline{98.0 \text{ kg}}$$

20.2 Test Weight Range = Calculated Weight (- 4.5 kg, - 9 kg.)

$$\text{Max. Test Weight} = \text{Calculated Test Weight} - 4.5 \text{ kg} = \underline{1458.5 \text{ kg}}$$

$$\text{Min. Test Weight} = \text{Calculated Test Weight} - 9 \text{ kg} = \underline{1454.0 \text{ kg}}$$

21. Remove the RCLW from the cargo area.

22. Drain transmission fluid, engine coolant, motor oil, and windshield washer fluid from the test vehicle so that Stoddard solvent leakage from the fuel system will be evident.

23. Vehicle Components Removed For Weight Reduction:  
Spare Tire and Cover, Jack and Tools, Right Tail Light

24. Secure the equipment and ballast in the load carrying area and distribute it, as nearly as possible, to obtain the proportion of axle weight indicated by the gross axle weight ratings and center it over the longitudinal centerline of the vehicle.

25. If necessary, add ballast to achieve the actual test weight.

N/A

Weight of Ballast: 40.4 kg

26. Ballast, including test equipment, must be contained so that it will not shift during the impact event or interfere with data collection or interfere with high-speed film recordings or affect the structural integrity of the vehicle or do anything else to affect test results. Care must be taken to assure that any attachment hardware added to the vehicle is not in the vicinity of the fuel tank or lines.

27. Record the vehicle weight at each wheel to determine the actual test weight.

Right Front (kg):	415.5	Right Rear (kg):	305.7
Left Front (kg):	428.6	Left Rear (kg):	305.3
Total Front (kg):	844.1	Total Rear (kg):	611.0
% Total Weight:	58.0	% Total Weight:	42.0
% GVW	53.4	% GVW	47.4
(% GVW = Axle GVW divided by Vehicle GVW)			
TOTAL FRONT PLUS TOTAL REAR (kg):			1455.1

28. Is the test weight between the Max. Weight and the Min. Weight (See 20.2)?

Yes

No, explain why not.

29. Test Weight Vehicle Attitude: (all dimensions in millimeters)

29.1 Place the vehicle on a level surface.

29.2 Measure perpendicular to the level surface to the 4 points marked on the body (see 13 above) and record the measurements.

RF:	676	LF:	671	RR:	663	LR:	665
-----	-----	-----	-----	-----	-----	-----	-----

- 30. Summary of test attitude
- 30.1 AS DELIVERED:

RF:	681	LF:	677	RR:	682	LR:	678
-----	-----	-----	-----	-----	-----	-----	-----

AS TESTED:

RF:	676	LF:	671	RR:	663	LR:	665
-----	-----	-----	-----	-----	-----	-----	-----

FULLY LOADED:

RF:	676	LF:	670	RR:	660	LR:	662
-----	-----	-----	-----	-----	-----	-----	-----

- 30.2 Is the “as tested” test attitude equal to or between the “fully loaded” and “as delivered” attitude?

- Yes
- No, explain why not.

REMARKS:

Signature: Ben Stouffer Date: 12/8/22

I certify that I have read and performed each instruction.

**DATA SHEET 33**

**VEHICLE ACCELEROMETER LOCATION AND MEASUREMENT**

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Ben Storey


NHTSA No.: C20225305  
 Test Date: 12/8/22

IMPACT ANGLE:	0°					
BELTED DUMMIES (YES/NO):	YES					
TEST SPEED:	<input type="checkbox"/>	32 to 56 kmph	<input type="checkbox"/>	0 to 48 kmph	<input checked="" type="checkbox"/>	0 to 56 kmph
DRIVER DUMMY:	<input checked="" type="checkbox"/>	X	<input type="checkbox"/>	5 <sup>th</sup> female	<input type="checkbox"/>	50 <sup>th</sup> male
PASSENGER DUMMY:	<input checked="" type="checkbox"/>	X	<input type="checkbox"/>	5 <sup>th</sup> female	<input type="checkbox"/>	50 <sup>th</sup> male

- 1. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the left front outboard seating position intersects the left rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- 2. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the right front outboard seating position intersects the right rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- 3. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect at the top of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- 4. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect the bottom of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- 5. Install an accelerometer on the right front brake caliper to record x-direction accelerations. Record the location on the following chart.
- 6. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the top of the instrument panel. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- 7. Install an accelerometer on the left front brake caliper to record x-direction accelerations. Record the location on the following chart.
- 8. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the floor of the trunk. Install an accelerometer on the trunk floor at this intersection to record z-direction accelerations. Record the location on the following chart.

REMARKS:


I certify that I have read and performed each instruction.

Signature: 

Date: 12/8/22

# VEHICLE ACCELEROMETER LOCATION AND DATA SUMMARY


CENTERLINE OF FRONT WHEELS



TOP VIEW

ACCELEROMETER COORDINATE SYSTEM (POSITIVE DIRECTION SHOWN)

REAR SEAT CUSHION ASSY. FRONT ATTACHMENT BRACKET SUPPORT



LEFT SIDE VIEW

Dimensions Corresponding To The Letters "A" Through "K" (Excluding "I") Are Recorded In The Table On The Following Page.

Accelerometers Corresponding To The Numbers 1 Through 8 Are Specified On The Preceding Page.

**VEHICLE ACCELEROMETER LOCATION AND MEASUREMENTS**

<u>DIMENSION</u>	<u>LENGTH (mm)</u>	
<u>PRETEST VALUES</u>		
<u>A</u> (LH Rear Seat Xmbr)	312	
<u>B</u> (RH Rear Seat Xmbr)	312	
<u>C</u> (Engine Top)	3947	
<u>D</u> (Engine Bottom)	3857	
<u>E</u> (Caliper)	Right Side: 3820	Left Side: 3820
<u>F</u> (Left Caliper)	745	
<u>G</u> (IP)	2991	
<u>H</u> (Seat)	1808	
<u>J</u> (Right Caliper)	745	
<u>K</u> (Trunk)	982	
<u>POST TEST VALUES</u>		
<u>A</u> (LH Rear Seat Xmbr)	312	
<u>B</u> (RH Rear Seat Xmbr)	312	
<u>C</u> (Engine Top)	3940	
<u>D</u> (Engine Bottom)	3600	
<u>E</u> (Caliper)	Right Side: 3658	Left Side: 3660
<u>F</u> (Left Caliper)	686	
<u>G</u> (IP)	2886	
<u>H</u> (Seat)	1784	
<u>J</u> (Right Caliper)	703	
<u>K</u> (Trunk)	982	

**DATA SHEET 34**  
**PHOTOGRAPHIC TARGETS**

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Ben Storey

NHTSA No.: C20225305  
 Test Date: 12/8/22

IMPACT ANGLE:	0°			
BELTED DUMMIES (YES/NO):	YES			
TEST SPEED:	<input type="checkbox"/> 32 to 56 kmph	<input type="checkbox"/> 0 to 48 kmph	<input checked="" type="checkbox"/> 0 to 56 kmph	
DRIVER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male
PASSENGER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male

- 1. **FMVSS 208 vehicle targeting requirements** (See Figures 28A and 28B)
- 1.1 Targets A1 and A2 are on flat rectangular panels.
- 1.2 Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the front on the outboard sides of A1 and A2. The center of each circular target is 100 mm from the one next to it.
- Distance between targets (mm): 100 mm
- 1.3 Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the back on the outboard sides of on A1 and A2. The center of each circular target is 100 mm from the one next to it.
- Distance between targets (mm): 100 mm
- 1.4 The distance between the first circular target at the front of A1 and A2 and the last circular target at the back of A1 and A2 is at least 915 mm.
- Distance between the first and last circular targets (mm): 915 mm
- 1.5 Firmly fix target A1 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy.
- 1.6 Firmly fix target A2 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy.
- 1.7 Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the driver door. The centers of each circular target are at least 610 mm apart.
- Distance between targets (mm): 610 mm
- 1.8 Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the passenger door. The centers of each circular target are at least 610 mm apart.
- Distance between targets (mm): 610 mm
- 1.9 Place tape with squares having alternating colors on the top portion of the steering wheel.
- 1.10 Chalk the bottom portion of the steering wheel.
- 1.11 Is this an offset test?
- Yes, continue with this section**
- No, go to 2.**
- 1.12 Measure the width of the vehicle.  
Vehicle width (mm):
- 1.13 Find the centerline of the vehicle. (½ of the vehicle width)
- 1.14 Find the line parallel to the centerline of the vehicle and 0.1 x vehicle width from the centerline of the vehicle.
- 1.15 Apply 25 mm wide tape with alternating black and yellow squares parallel to and on each side of the line found in 1.14. The edge of each tape shall be 50 mm from the line found in 1.14. The tape shall extend from the bottom of the bumper to the front edge of the windshield. (Figure 28D)

- 2. **Barrier Targeting**
- 2.1 Fix two stationary targets D1 and D2 to the barrier as shown in the Figure 28A. One target is in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy. The other is in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy.
- 2.2 Targets D1 and D2 are on a rectangular panel.
- 2.3 Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted on the sides of the rectangular panel away from the longitudinal centerline of the vehicle. The center of each circular target is 100 mm from the one next to it.
- Distance between circular targets on D1 (mm): 100 mm
- Distance between circular targets on D2 (mm): 100 mm
- 3. **FMVSS 208 Dummy Targeting Requirements**
- 3.1 Place a circular target with black and yellow quadrants on both sides of the driver dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
- 3.2 Place a circular target with black and yellow quadrants on both sides of the passenger dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
- 3.3 Place a circular target with black and yellow quadrants on the outboard shoulder of the driver dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
- 3.4 Place a circular target with black and yellow quadrants on the outboard shoulder of the passenger dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
- 4. **FMVSS 204 Targeting Requirements**
- 4.1 Is an FMVSS 204 indicant test ordered on the "COTR Vehicle Work Order?"
  - Yes, continue with this form.
  - No, this form is complete.
- 4.2 Resection panel (Figure 28C)
  - 4.2.1 The panel deviates no more than 6 mm from perfect flatness when suspended vertically
  - 4.2.2 The 8 targets on the panel are circular targets at least 90 mm in diameter and with black and yellow quadrants.
  - 4.2.3 The center of each of the 4 outer targets are placed within 1 mm of the corners of a square measuring 914 mm on each side.
  - 4.2.4 Locate another square with 228 mm sides and with the center of this square coincident with the center of the 914 mm square.
  - 4.2.5 The center of the 4 inner targets are placed at the midpoints of each of the 228 mm sides.
- 4.3 Place a circular target at least 90 mm in diameter and with black and yellow quadrants on a material (cardboard, metal, etc.) that can be taped to the top of the steering column.
- 4.4 Tape the target from 4.3 to the top of the steering column in a manner that does not interfere with the movement of the steering column in a crash.


REMARKS:

Signature: Ben Stoney


Date: 12/8/22

I certify that I have read and performed each instruction.


# REFERENCE PHOTO TARGETS




# RESECTION PANEL TARGETING ALIGNMENT



## TEST RUN STEERING COLUMN CAMERA VIEW OF TYPICAL TIME ZERO VEHICLE POSITION



# PRE-RUN STEERING COLUMN HIGH SPEED CAMERA VIEW



LEFT SIDE VIEW

**DATA SHEET 35**  
**CAMERA LOCATIONS**

Test Vehicle: 2022 Honda Civic  
Test Program: FMVSS 208 Compliance


NHTSA No.: C20225305  
Test Date: 12/8/22  
Time: 10:40 am

CAMERA NO.	VIEW	CAMERA POSITIONS (mm) *			LENS (mm)	SPEED (fps)
		X	Y	Z		
1	Real Time Left Side View				13	30
2	Left Side View (Barrier face to front seat backs)	1290	-5630	1360	24	1000
3	Left Side View (Driver)	1860	-6830	1840	50	1000
4	Left Side View (B-post aimed toward center of steering wheel)	7480	-5730	1920	75	1000
5	Left Side View (Steering Column)	1040	-5620	1230	50	1000
6	Left Side View (Steering Column)	1030	-5620	790	50	1000
7	Right Side View (Overall)	2010	5510	1450	16	1000
8	Right Side View (Passenger)	1505	6620	1870	50	1000
9	Right Side View (Angle)	7680	5520	1960	75	1000
10	Right Side View (Front door)	1210	5270	1430	24	1000
11	Front View Windshield	-120	0	2310	11	1000
12	Front View Driver	-70	-370	2230	25	1000
13	Front View Passenger	-70	370	2230	25	1000
14	Overhead Barrier Impact View	3020	0	6820	11	1000
15	Pit Camera Engine View	1100	0	-3340	24	1000
16	Pit Camera Fuel Tank View	3240	0	-3340	24	1000

\*COORDINATES:

- +X - forward of impact plane
- +Y - right of monorail centerline
- +Z - above ground level

# CAMERA POSITIONS FOR FMVSS 208



**DATA SHEET 36 - APPENDIX G**  
**DUMMY POSITIONING PROCEDURES**  
**FOR 5<sup>th</sup> PERCENTILE FEMALE DRIVER TEST DUMMY**  
**CONFORMING TO SUBPART O OF PART 572**

Test Vehicle:	<u>2022 Honda Civic</u>	NHTSA No.:	<u>C20225305</u>
Test Program:	<u>FMVSS 208 Compliance</u>	Test Date:	<u>12/8/22</u>
Test Technician:	<u>Keegan Strockis</u>		

IMPACT ANGLE:	0°			
BELTED DUMMIES (YES/NO):	YES			
TEST SPEED:	32 to 40 kmph	0 to 48 kmph	<input checked="" type="checkbox"/>	0 to 56 kmph
DRIVER DUMMY:	<input checked="" type="checkbox"/>	5 <sup>th</sup> female		50 <sup>th</sup> male
PASSENGER DUMMY:	<input checked="" type="checkbox"/>	5 <sup>th</sup> female		50 <sup>th</sup> male

**1. Seat Position**

- 1.1 Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions. (S16.2.10.1, S20.1.9.1, S20.4.1, S22.1.7.1)  
 N/A – No lumbar adjustment
  
- 1.2 Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2, S20.1.9.2, S20.4.1, S22.1.7.1, S22.4.2.1, S22.4.3.1, S24.4.2.1, S26.2.3, S26.3.1)  
 N/A – No additional support adjustment
  
- 1.3 Position an adjustable leg support system in its rearmost position. (8/27/04 interpretation to Toyota)  
 N/A – No adjustable leg support system
  
- 1.4 **Mark** a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion. (S16.3.1.12)
  
- 1.5 Draw a line (seat cushion reference line) through the seat cushion reference point. (S16.3.1.13)
  
- 1.6 Use only the controls that primarily move the seat in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S22.1.7.3)
  
- 1.7 If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S20.1.9.3)  
 N/A – No independent fore-aft seat cushion adjustment
  
- 1.8 Use any part of any control, other than the parts just used for fore-aft positioning, to determine the range of angles of the seat cushion reference line and to set the seat cushion reference line at the mid-angle. (S16.2.10.3.1)  
Maximum angle: 25.6°  
Minimum angle: 19.1°  
Mid-angle: 22.4°

- 1.9 If the seat and/or seat cushion height is adjustable, use any part of any control other than the parts which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-angle found in 1.8. (S16.2.10.3.1)  
 N/A – No seat height adjustment
- 1.10 Use only the controls that primarily move the seat in the fore-aft direction to verify the seat is in the rearmost position.
- 1.11 Use only the controls that primarily move the seat in the fore-aft direction to **mark** the fore-aft seat positions. **Mark** each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and **mark** each detent. For power seats, **mark** only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost.
- 1.12 Use only the controls that primarily move the seat in the fore-aft direction to place the seat in the rearmost position.
- 1.13 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S22.4.3.1, S24.1.2, S24.3.1, S24.4.3.1, S26.2.3, S26.3.1)  
 N/A – No seat height adjustment. Go to 1.18
- 1.14 Use only the controls that primarily move the seat and/or seat cushion in the fore-aft direction to place the seat in the mid-fore-aft position.
- 1.15 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- 1.16 Use only the control that change the seat in the fore-aft direction to place the seat in the foremost position. (S16.2.10.3.2)
- 1.17 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S16.2.10.3.3, S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- 1.18. Is the seat a bucket seat?  
 Yes, go to 1.19 and skip 1.20  
 No, go to 1.20 and skip 1.19
- 1.19 Bucket seats:  
Locate and **mark** for future reference the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S16.3.1.10 & S20.1.10)

- 1.20 Bench seats (complete ONLY the one that is applicable to the seat being marked):  
Locate and **mark** for future reference the longitudinal line on the seat cushion that marks the intersection of the vertical longitudinal plane through the centerline of the steering wheel and the seat cushion upper surface.

## 2. Head Restraint Position

- N/A Vehicle contains automatic head restraints.  
 N/A, there is no head restraint adjustment Go to 3
- 2.1 Adjust the head restraint to its lowest position. (S16.2.10.2, S20.1.9.6, S20.4.1, S22.1.7.6, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)
- 2.2 All adjustments of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. **Mark** the foremost position. (S16.2.10.2 & S16.3.4.4 & S20.1.9.6, S20.4.1, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)
- 2.3 Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and **mark** a horizontal plane through the midpoint of this distance. (S16.3.4.3)  
Vertical height of head restraint: 180 mm  
Mid-point height: 90 mm
3. Is the **steering wheel** adjustable up and down and/or in and out?  
 Yes – go to 3.1  
 No – Go to 4
- 3.1. Find and **mark** for future reference each up and down position. Label three of the positions with the following: H for highest, M for mid-position (if there is no mid-position, label the next lowest adjustment position), and L for lowest.  
 N/A – steering wheel is not adjustable up and down
- 3.2. Find and **mark** for future references each in and out position. Label three of the Positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the next rearmost adjustment position), and R for rearmost.  
 N/A – steering wheel is not adjustable in and out.
- 3.3. Use the markings to position the steering controls in the mid-position or if applicable next lowest detent position. (S16.2.9)
4. Place the SCRIP in the full rearward, mid-height position, and mid-seat cushion angle, determined in Item 1. (S16.3.2.1.1)
5. If the vehicle has an adjustable accelerator pedal, place it in the full forward position. (S16.3.2.2.1)  
 N/A accelerator pedal not adjustable
6. Fully recline the seat back. (S16.3.2.1.2)  
 N/A seat back not adjustable.
7. Place the dummy in the seat with the legs at an angle of 120 degrees to the thighs. The calves should not be touching the seat cushion. (S16.3.2.1.2)
8. Position the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion markings as determined in Item 1.19 or 1.20. (S16.3.2.1.3 and S16.3.2.1.4)

9. Hold down the dummy's thighs and push rearward on the upper torso to maximize the pelvic angle. (S16.3.2.1.5)
10. Set the angle between the legs and the thighs to 120 degrees. (S16.3.2.1.6)
11. Set the transverse distance between the centers of the front of the knees at 160 to 170 mm. (6.3 to 6.7 inches) Center the knee separation with respect to the longitudinal seat cushion marking as determined in Item 1.19 or 1.20. (S16.3.2.1.6)  
Record Knee Separation: 165 mm
12. Push rearward on the dummy's knees until the pelvis contacts the seat back, or the backs of the calves contact the seat cushion, whichever occurs first. (S16.3.2.1.6)  
 Pelvis contacted seat back.  
 Calves contacted seat cushion.
13. Gently rock the upper torso  $\pm$  5 degrees (approximately 51 mm (2 inches)) side-to-side three times. (S16.3.2.1.7)
14. If needed, extend the legs until the feet do not contact the floor pan. The thighs should be resting on the seat cushion. (S16.3.2.1.8)
15. Position the right foot until the foot is in line with a longitudinal vertical plane passing through the center of the accelerator pedal. Maintain the leg and thigh in a vertical plane. (S16.3.2.1.8)
16. Rotate the left leg and thigh laterally to equalize the distance between each knee and the longitudinal seat cushion marking as determined in Item 1.19 or 1.20. (S16.3.2.1.8)
17. Attempt to return the seat to the foremost fore-aft position, mid-height, and seat cushion mid-angle as determined in Item 1. The foot may contact and depress the accelerator and/or change the angle of the foot with respect to the leg. (S16.3.2.1.8)  
 Foremost position achieved. Proceed to step 22.  
 Foremost not achieved because of foot interference. Proceed to step 19.  
 Foremost not achieved because of steering wheel contact.
18. If either of the dummy's legs contact the steering wheel, move the steering wheel up the minimum amount required to avoid contact. If the steering wheel is not adjustable separate the knees the minimum required to avoid contact. (S16.3.2.1.8)  
 N/A- there was no leg contact  
 Steering wheel repositioned  
 Knees separated
19. If the left foot interferes with the clutch or brake pedals, rotate the left foot about the leg to provide clearance. If this is not sufficient, rotate the thigh outboard at the hip the minimum amount required for clearance. (S16.3.2.1.8)  
 N/A, No foot interference with pedals.  
 Foot adjusted to provide clearance.  
 Foot and Thigh adjusted to provide clearance.

20. Continue to move the seat. Use seat controls to line up the seat markings determined during item 1 to set the foremost fore-aft position, mid-height position and the seat cushion mid-angle. If the dummy contacts the interior move the seat rearward until a maximum clearance of 5 mm (0.2 inches) is achieved or the seat is in the closest detent position that does not cause dummy contact. (S16.3.2.1.8)

  Foremost, mid-height position and the seat cushion mid-angle reached

  Dummy contact. Clearance set at maximum of 5 mm

Measured Clearance: \_\_\_\_\_

  Dummy Contact. Seat set at nearest detent position.

Seat position:    detent positions rearward of foremost  
(foremost is position zero)

  21. If the steering wheel was repositioned in step 18, return the steering wheel to the original position. If the steering wheel contacts the dummy before reaching the original position, position the wheel until a maximum clearance of 5 mm (.2 inches) is achieved, or the steering wheel is in the closest detent position that does not cause dummy contact. (S16.3.2.1.8)

  N/A Steering wheel was not repositioned.

  Original position achieved.

  Dummy contact. Clearance set at maximum of 5 mm

Measured Clearance: \_\_\_\_\_

  Dummy Contact. Steering wheel set at nearest detent position.

Steering wheel position:    detent positions upward of original position.  
(Original position is position zero)

X22. If the seat back is adjustable, rotate the seat back forward while holding the thighs in place. Continue rotating the seat back forward until the transverse instrument platform of the dummy head is level  $\pm 0.5$  degrees. If the head cannot be leveled using the seat back adjustment, or the seat back is not adjustable, use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, minimize the angle. (S16.3.2.1.9)

X Head Level Achieved. (Check all that apply)

X Head leveled using the adjustable seat back

   Head leveled using the neck bracket.

Head Angle: 0.3 degrees

   Head Level NOT Achieved. (Check all that apply)

   Head adjusted using the adjustable seat back

   Head adjusted using the neck bracket.

Head Angle: \_\_\_\_\_ degrees

X23. Verify the pelvis is not interfering with the seat bight. (S16.3.2.1.9)

X No interference

   Pelvis moved forward the minimum amount so that it is not caught in the seat bight.

X24. Verify the dummy abdomen is properly installed. (S16.3.2.1.9)

X Abdomen still seated properly into dummy

   Abdomen was adjusted because it was not seated properly into dummy

X25. Head Angle

X N/A, neither the pelvis nor the abdomen were adjusted.

X25.1 Head still level (Go to 26)

25.2 Head level adjusted

   Head Level Achieved. (Check all that apply)

   Head leveled using the adjustable seat back

   Head leveled using the neck bracket.

Head Angle: \_\_\_\_\_ degrees

   Head Level NOT Achieved. (Check all that apply)

   Head level adjusted using the adjustable seat back

   Head level adjusted using the neck bracket.

Head Angle: \_\_\_\_\_ degrees

X 26. If the dummy torso contacts the steering wheel while performing step 22, reposition the steering wheel in the following order to eliminate contact. (S16.3.2.1.9)

X N/A, No dummy torso contact with the steering wheel.

   26.1 Adjust telescoping mechanism.

   N/A No telescoping adjustment.

   Adjustment performed (fill in appropriate change)

Steering wheel moved \_\_\_\_\_ detent positions in the forward direction.

Steering wheel moved \_\_\_\_\_ mm in the forward direction.

   26.2 Adjust tilt mechanism.

   N/A No tilt adjustment.

   No adjustment performed.

   Adjustment performed. (circle one)

Steering wheel moved \_\_\_\_\_ detent positions Upward/Downward.

Steering wheel moved \_\_\_\_\_ degrees Upward/Downward

   26.3 Adjust Seat in the aft direction.

   No Adjustment performed.

   Seat moved aft \_\_\_\_\_ mm from original position.

   Seat moved aft \_\_\_\_\_ detent positions from the original position.

X 27. Measure and set the pelvic angle using the pelvic angle gage TE-2504. The pelvic angle should be 20.0 degrees  $\pm$  2.5 degrees. If the pelvic angle cannot be set to the specified range because the head will not be level or because the dummy will have need major repositioning, adjust the pelvis as closely as possible to the angle range, but keep the head level. (S16.3.2.1.11)

X Pelvic angle set to 20.0 degrees  $\pm$  2.5 degrees.

   Pelvic angle of 20.0 degrees not achieved, the angular difference was minimized.

X Record the pelvic angle: 19.2 degrees

X 28. Check the dummy for contact with the interior after completing adjustments. (S16.3.2.1.12)

X No contact.

   Dummy in contact with interior.

   Seat moved aft \_\_\_\_\_ mm from the previous position.

   Seat moved aft \_\_\_\_\_ detent positions from the previous position.

X 29. Check the dummy to see if additional interior clearance is obtained, allowing the seat to be moved forward. (S16.3.2.1.12)

X N/A, Seat already at foremost position.


   Clearance unchanged. No adjustments required.

   Additional clearance available

   Seat moved Forward \_\_\_\_\_ mm from the previous position.

   Seat moved Forward \_\_\_\_\_ detent positions from the previous position.

30. Driver's foot positioning, right foot. Place the foot perpendicular to the leg and determine if the heel contacts the floor pan at any leg position. If the heel contacts the floor pan proceed to step 31 otherwise, proceed to step 32. (S16.3.2.2.1)
31. Perform the following steps until either all steps are completed, or the foot contacts the accelerator pedal. Step 31.6 shall be completed in all cases. (S16.3.2.2.1(a))
- 31.1 With the rear of the heel contacting the floor pan, move the foot forward until pedal contact occurs or the foot is at the full forward position.
- 31.2 If the vehicle has an adjustable accelerator pedal, move the pedals rearward until pedal contact occurs or the pedals reach the full rearward position.
- 31.3 Extend the leg, allowing the heel to lose contact with the floor until the foot contacts the pedal. Do not raise the toe of the foot higher than the top of the accelerator pedal. If the foot does not contact the pedal, proceed to the next step. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)
- 31.4 Angle the foot to achieve contact between the foot and the pedal. If the foot does not contact the pedal, return the foot to the perpendicular orientation. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)
- 31.5 Align the centerline of the foot with the vertical-longitudinal plane passing through the center of the accelerator pedal. Place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)
- 31.6 Record foot position
- Pedal Contact achieved. Contact occurred at step 31.1
- Heel contacts floor pan
- Heel set \_\_\_\_\_ mm from floor pan.
- Pedal Contact not achieved. Heel set \_\_\_\_\_ mm from the floor pan.



**FIGURE G1**

32. Perform the following steps until either all steps are completed, or the foot contacts the accelerator pedal. Step 32.5 shall be completed in all cases.

32.1 Extend the leg until the foot contacts the pedal. Do not raise the toe of the foot higher than the top of the accelerator pedal. If the foot does not contact the pedal, proceed to the next step. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.1(b) & S16.3.2.2.3)

32.2 If the vehicle has an adjustable accelerator pedal, move the pedals rearward until pedal contact occurs or the pedals reach the full rearward position. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.1(b) & S16.3.2.2.3)  
 N/A No pedal adjustment

32.3 Angle the foot to achieve contact between the foot and the pedal. If the foot does not contact the pedal, return the foot to the perpendicular orientation. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.2 & S16.3.2.2.3)

32.4 Align the centerline of the foot in the same horizontal plane as the centerline of the accelerator pedal. Place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)

32.5 Record foot position

Pedal Contact achieved. Contact occurred at step 31.1.

Heel set \_\_\_\_\_ mm from floor pan.

Pedal Contact not achieved. Heel set \_\_\_ mm from the floor pan.

X 33. Driver's foot positioning, left foot.

X 33.1 Place the foot perpendicular to the leg and determine if the heel contacts the floor pan at any leg position. If the heel contacts the floor pan proceed to step 33.2, otherwise position the leg as perpendicular to the thigh as possible with the foot parallel to the floor pan. (S16.2.2.6)

X 33.2 Place the foot on the toe board with the heel resting on the floor pan as close to the intersection of the floor pan and the toe board as possible. Adjust the angle of the foot if necessary to contact the toe board. If the foot will not contact the toe board, set the foot perpendicular to the leg, and set the heel on the floor pan as far forward as possible. Avoid contact with the brake pedal, clutch pedal, wheel well projection, and footrest. To avoid this contact use the following three manipulations in the order listed, with each subsequent option incorporating the previous, until contact is avoided: rotate the foot about the lower leg (abduction/adduction), plantar flex the foot, rotate the leg outboard about the hip. Movement should be the minimum amount necessary. If it is not possible to avoid all foot contact, give priority to avoiding brake or clutch pedal contact. (S16.2.2.4 & S16.2.2.5 & S16.2.2.7)

No contact

Foot rotated about the leg (abduction/adduction)

Foot rotated about the leg, and foot plantar flexed

Foot rotated about the leg, foot plantar flexed, and the leg rotated about the hip.

X 33.3 Record foot position.

Heel does not contact floor pan.

Heel on floor pan and foot on toe board.

Heel on floor pan and foot not on toe board.

X 34. Driver arm/hand positioning.

X 34.1 Place the dummy's upper arms adjacent to the torso with the arm centerlines as close to a vertical longitudinal plane as possible. (S16.3.2.3.1)

X 34.2 Place the palms of the dummy in contact with the outer part of the steering wheel rim at its horizontal centerline with the thumbs over the steering wheel rim. (S16.3.2.3.2)

X 34.3 If it is not possible to position the thumbs inside the steering wheel rim at its horizontal centerline, then position them above and as close to the horizontal centerline of the steering wheel rim as possible. (S16.3.2.3.3)

X 34.4 Lightly tape the hands to the steering wheel rim so that if the hand of the test dummy is pushed upward by a force of not less than 9 N (2 lb) and not more than 22 N (5 lb), the tape releases the hand from the steering wheel rim. (S16.3.2.3.4)

X 35. Adjustable head restraints

N/A, there is no head restraint adjustment

35.1 If the head restraint has an automatic adjustment, leave it where the system positions the restraint after the dummy is placed in the seat. (S16.3.4.1) Go to 36.

35.2 Adjust each head restraint vertically so that the mid-horizontal plane determined in Item 2 is aligned with the center of gravity (CG) of the dummy head. (S16.3.4.3)

35.3 If the above position is not attainable, move the vertical center of the head restraint to the closest detent below the center of the head CG. (S16.3.4.3)

N/A midpoint position attained in previous step

Headrest set at nearest detent below the head CG

35.4 If the head restraint has a fore and aft adjustment, place the restraint in the foremost position or until contact with the head is made, whichever occurs first. (S16.3.4.4)

36. Driver and passenger manual belt adjustment (for tests conducted with a belted dummy). (S16.3.5)

N/A Dummies are unbelted for this test.

36.1 If an adjustable seat belt D-ring anchorage exists, place it in the manufacturer's design position for a 5th percentile adult female. (S16.3.5.1) **This information will be supplied by the COTR.**

Manufacturer's specified position: 0 of 4; Upper-most defined as 0

Actual Position: 0 of 4; Upper-most defined as 0

36.2 Place the Type 2 manual belt around the test dummy and fasten the latch. (S16.3.5.2)

36.3 Ensure that the dummy's head remains as level as possible. (S16.3.5.3)

36.4 Remove all slack from the lap belt. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this operation four times. Apply a 9 N (2 lbf) to 18 N (4 lbf) tension load to the lap belt. If the belt system is equipped with a tension-relieving device, introduce the maximum amount of slack into the upper torso belt that is recommended by the manufacturer. If the belt system is not equipped with a tension-relieving device, allow the excess webbing in the shoulder belt to be retracted by the retractive force of the retractor. (S16.3.5.4)

I certify that I have read and performed each instruction.

Signature: Keegan Atacker

Date: 12/8/22

**DATA SHEET 36 - APPENDIX G**  
**DUMMY POSITIONING PROCEDURES**

**FOR 5<sup>th</sup> PERCENTILE FEMALE PASSENGER TEST DUMMY**  
**CONFORMING TO SUBPART O OF PART 572**

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Keegan Strockis

NHTSA No.: C20225305  
 Test Date: 12/8/22

IMPACT ANGLE:	0°			
BELTED DUMMIES (YES/NO):	YES			
TEST SPEED:	<input type="checkbox"/> 32 to 40 kmph	<input type="checkbox"/> 0 to 48 kmph	<input checked="" type="checkbox"/> 0 to 56 kmph	
DRIVER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male
PASSENGER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male

     **The passenger seat adjustments are controlled by the adjustments made to the driver's seat. Therefore, positioning of the passenger dummy is made simultaneously with the driver dummy. Adjustments made to the seat to position the driver will override any adjustments that would normally be made to position the passenger. (S16.2.10.3)**

**1. Seat Position**

X 1.1 Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions. (S16.2.10.1, S20.1.9.1, S20.4.1, S22.1.7.1)

     X N/A – No lumbar adjustment

X 1.2 Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2, S20.1.9.2, S20.4.1, S22.1.7.1, S22.4.2.1, S22.4.3.1, S24.4.2.1, S26.2.3, S26.3.1)

     X N/A – No additional support adjustment

X 1.3 Position an adjustable leg support system in its rearmost position. (8/27/04 interpretation to Toyota)

     X N/A – No adjustable leg support system

X 1.4 **Mark** a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion. (S16.3.1.12)

X 1.5 Draw a line (seat cushion reference line) through the seat cushion reference point. (S16.3.1.13)

X 1.6 Use only the controls that primarily move the seat in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S22.1.7.3)

X 1.7 If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S20.1.9.3)

     X N/A – No independent fore-aft seat cushion adjustment

1.8 Use any part of any control, other than the parts just used for fore-aft positioning, to determine the range of angles of the seat cushion reference line and to set the seat cushion reference line at the mid-angle. (S16.2.10.3.1)

Maximum angle: Fixed

Minimum angle: Fixed

Mid-angle: Fixed

1.9 If the seat and/or seat cushion height is adjustable, use any part of any control other than the parts which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-angle found in 1.8. (S16.2.10.3.1)

N/A – No seat height adjustment

1.10 Use only the controls that primarily move the seat in the fore-aft direction to verify the seat is in the rearmost position.

1.11 Use only the controls that primarily move the seat in the fore-aft direction to **mark** the fore-aft seat positions. **Mark** each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and **mark** each detent. For power seats, **mark** only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost.

1.12 Use only the controls that primarily move the seat in the fore-aft direction to place the seat in the rearmost position.

1.13 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S22.4.3.1, S24.1.2, S24.3.1, S24.4.3.1, S26.2.3, S26.3.1)

N/A – No seat height adjustment. Go to 1.18

1.14 Use only the controls that primarily move the seat and/or seat cushion in the fore-aft direction to place the seat in the mid-fore-aft position.

1.15 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)

1.16 Use only the controls that change the seat in the fore-aft direction to place the seat in the foremost position. (S16.2.10.3.2)

1.17 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S16.2.10.3.3, S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)

1.18. Is the seat a bucket seat?

Yes, go to 1.19 and skip 1.20

No, go to 1.20 and skip 1.19

X 1.19 Bucket seats:

Locate and **mark** for future reference the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S16.3.1.10 & S20.1.10)

   1.20 Bench seats:

Locate and **mark** the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S20.2.1.4, S22.2.1.3, S24.2.3, S20.4.4, S22.2.2.1 (b), S22.2.2.3 (b), S22.2.2.4 (a), S22.2.2.5 (a), S22.2.2.6 (a), S22.2.2.7 (a), S24.2.3 (a))

Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel. \_\_\_\_\_

Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. (The vertical plane through this longitudinal centerline is Plane B for suppression.) \_\_\_\_\_

## 2. Head Restraint Position

   N/A Vehicle contains automatic head restraints.

   N/A, there is no head restraint adjustment Go to 3

X 2.1 Adjust the head restraint to its lowest position. (S16.2.10.2, S20.1.9.6, S20.4.1, S22.1.7.6, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)

X 2.2 All adjustments of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. **Mark** the foremost position. (S16.2.10.2 & S16.3.4.4 & S20.1.9.6, S20.4.1, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)

X 2.3 Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and **mark** a horizontal plane through the midpoint of this distance. (S16.3.4.3)

Vertical height of head restraint: 180 mm

Mid-point height: 90 mm

X 3. Place the SCRIP in the full rearward, mid-height position, and mid-seat cushion angle. (S16.3.3.1.1)

X 4. Fully recline the seat back. (S16.3.3.1.2)

   N/A seat back not adjustable.

X 5. Place the dummy in the seat with the legs at an angle of 120 degrees to the thighs. The calves should not be touching the seat cushion. (S16.3.3.1.2)

X 6. Position the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion marking that was determined in item 1.19 or 1.20. (S16.3.3.1.3 and S16.3.3.1.4)

X 7. Hold down the dummy's thighs and push rearward on the upper torso to maximize the pelvic angle. (S16.3.3.1.5)

X 8. Set the angle between the legs and the thighs to 120 degrees. (S16.3.3.1.6)

- X 9. Set the transverse distance between the centers of the front of the knees at 160 to 170 mm. (6.3 to 6.7 inches). Center the knee separation with respect to the longitudinal seat cushion marking that was determined in item 1.19 or 1.20. (S16.3.3.1.6)  
Record Knee Separation: 165 mm
- X 10. Push rearward on the dummy's knees until the pelvis contacts the seat back, or the backs of the calves contact the seat cushion, whichever occurs first. (S16.3.3.1.6)  
   Pelvis contacted seat back.  
X Calves contacted seat cushion.
- X 11. Gently rock the upper torso  $\pm 5$  degrees (approximately 51 mm (2 inches)) side-to-side three times. (S16.3.3.1.7)
- X 12. If needed, extend the legs until the feet do not contact the floor pan. The thighs should be resting on the seat cushion. (S16.3.3.1.8)
- X 13. Use seat controls to line up the seat markings determined during the completion of item 1 to set the foremost fore-aft position, mid-height position and the seat cushion mid-angle. If the dummy contacts the interior move the seat rearward until a maximum clearance of 5 mm (0.2 inches) is achieved or the seat is in the closest detent position that does not cause dummy contact. (S16.3.3.1.8)  
X Foremost, mid-height position and the seat cushion mid-angle reached  
   Dummy contact. Clearance set at maximum of 5 mm  
Measured Clearance: \_\_\_\_\_  
   Dummy Contact. Seat set at nearest detent position.  
Seat position    detent positions rearward of foremost  
(foremost is position zero)
- X 14. If the seat back is adjustable, rotate the seat back forward while holding the thighs in place. Continue rotating the seat back forward until the transverse instrument platform of the dummy head is level  $\pm 0.5$  degrees. If head cannot be leveled using the seat back adjustment, or the seat back is not adjustable, use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, adjust the head as closely as possible to the  $\pm 0.5$  degree range. (S16.3.3.1.9 and S16.3.3.1.10)  
(Check All That Apply)  
   Seat back not adjustable  
   Seat back not independent of driver side seat back  
X Head Level Achieved. (Check all that apply)  
   Head leveled using the adjustable seat back  
   Head leveled using the neck bracket.  
Head Angle: 0.0 degrees  
   Head Level NOT Achieved. (Check all that apply)  
   Head adjusted using the adjustable seat back  
   Head adjusted using the neck bracket.  
Head Angle: \_\_\_\_\_ degrees
- X 15. Verify the pelvis is not interfering with the seat bight. (S16.3.3.1.9)  
X No interference  
   Pelvis moved forward the minimum amount so that it is not caught in the seat bight.
- X 16. Verify the dummy abdomen is properly installed. (S16.3.3.1.9)  
X Abdomen still seated properly into dummy  
   Abdomen was adjusted because it was not seated properly into dummy
- X 17. Head Angle  
X N/A, neither the pelvis nor the abdomen were adjusted.

17.1 Head still level (Go to 18)

17.2 Head level adjusted

Head Level Achieved. (Check all that apply)

Head leveled using the adjustable seat back

Head leveled using the neck bracket.

Head Angle: \_\_\_\_\_ degrees

Head Level NOT Achieved. (Check all that apply)

Head adjusted using the adjustable seat back

Head adjusted using the neck bracket.

Head Angle: \_\_\_\_\_ degrees

18. Measure and set the pelvic angle using the pelvic angle gage TE-2504. The pelvic angle should be 20.0 degrees  $\pm$  2.5 degrees. If the pelvic angle cannot be set to the specified range because the head will not be level or because the dummy will have need major repositioning, adjust the pelvis as closely as possible to the angle range, but keep the head level.

Pelvic angle set to 20.0 degrees  $\pm$  2.5 degrees.

Pelvic angle of 20.0 degrees not achieved, the angular difference was minimized.

Record the pelvic angle: 20.6 degrees

19. Check the dummy for contact with the interior after completing adjustments.

No contact.

Dummy in contact with interior.

Seat moved aft \_\_\_\_\_ mm from the previous position.

Seat moved aft \_\_\_\_\_ detent positions from the previous position.

20. Verify the transverse instrument platform of the dummy head is level  $\pm$  0.5 degrees. Use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, minimize the angle. (S16.3.3.1.9, S16.3.3.1.10, and S16.3.3.1.11)

Head Level Achieved

Head Angle: 0.0 degrees

Head Level NOT Achieved.

Head Angle: \_\_\_\_\_ degrees

21. Check the dummy to see if additional interior clearance is obtained, allowing the seat to be moved forward. (S16.3.3.1.12)

N/A Bench Seat

N/A Seat already at full forward position.

Clearance unchanged. No adjustments required.

Additional clearance available

Seat moved Forward \_\_\_\_\_ mm from the previous position.

Seat moved Forward \_\_\_\_\_ detent positions from the previous position.

Seat moved Forward, Full Forward position reached.

22. Passenger foot positioning. (Indicate final position achieved) (S16.3.3.2)

22.1 Place feet flat on the toe board; OR (S16.3.3.2.1)

22.2 If the feet cannot be placed flat on the toe board, set the feet perpendicular to the lower leg, and rest the heel as far forward on the floor pan as possible; OR (S16.3.3.2.2)

22.3 If the heels do not touch the floor pan, set the legs as perpendicular to the thighs as possible and set the feet parallel to the floor pan. (S16.3.3.2.2)

23. Passenger arm/hand positioning. (S16.3.3.3)

23.1 Place the dummy's upper arms adjacent to the torso with the arm centerlines as close to a vertical longitudinal plane as possible. (S16.3.3.3.1)

23.2 Place the palms of the dummy in contact with the outer part of the thighs (S16.3.3.3.2)

23.3 Place the little fingers in contact with the seat cushion. (S16.3.3.3.3)

24. Adjustable head restraints (S16.3.4)

N/A, there is no head restraint adjustment

24.1 If the head restraint has an automatic adjustment, leave it where the system positions the restraint after the dummy is placed in the seat. (S16.3.4.1) Go to 25.

24.2 Adjust each head restraint vertically so that the horizontal plane determined in Item 2 is aligned with the center of gravity (CG) of the dummy head. (S16.3.4.3)

24.3 If the above position is not attainable, move the vertical center of the head restraint to the closest detent below the center of the head CG. (S16.3.4.3)

N/A midpoint position attained in previous step

Headrest set at nearest detent below the head CG

24.4 If the head restraint has a fore and aft adjustment, place the restraint in the foremost position or until contact with the head is made, whichever occurs first. (S16.3.4.4)

25. Manual belt adjustment (for tests conducted with a belted dummy) (S16.3.5)

N/A, Unbelted test

25.1 If an adjustable seat belt D-ring anchorage exists, place it in the manufacturer's design position for a 5th percentile adult female. **This information will be supplied by the COTR.** (S16.3.5.1)

Manufacturer's specified position: 0 of 4; Upper-most defined as 0

Actual Position: 0 of 4; Upper-most defined as 0

25.2 Place the Type 2 manual belt around the test dummy and fasten the latch. (S16.3.5.2)

25.3 Ensure that the dummy's head remains as level as possible. (S16.3.5.3)

25.4 Remove all slack from the lap belt. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this operation four times. Apply a 9 N (2 lbf) to 18 N (4 lbf) tension load to the lap belt. If the belt system is equipped with a tension-relieving device, introduce the maximum amount of slack into the upper torso belt that is recommended by the manufacturer. If the belt system is not equipped with a tension-relieving device, allow the excess webbing in the shoulder belt to be retracted by the retractive force of the retractor. (S16.3.5.4)

I certify that I have read and performed each instruction.

Signature: Keegan Stracher

Date: 12/8/22


# DATA SHEET 37

## DUMMY MEASUREMENTS

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Keegan Strockis

NHTSA No.: C20225305  
 Test Date: 12/8/22


### DUMMY MEASUREMENTS FOR FRONT SEAT OCCUPANTS



**TEST DUMMY POSITION MEASUREMENTS**

Code	Measurement Description	Driver SN 510		Passenger SN 507	
		Length (mm)	Angle (°)	Length (mm)	Angle (°)
WA	Windshield Angle		24.2		
SWA	Steering Wheel Angle		70.0		
SCA	Steering Column Angle		20.0		
SA	Seat Back Angle (On Headrest Post)		-1.4		-1.0
HZ	Head to Roof (Z)	210		217	
HH	Head to Header	302	48.3	314	44.9
HW	Head to Windshield	652	0.0	680	0.0
HR	Head to Side Header (Y)	256		260	
NR	Nose to Rim	255	0.5		
CD	Chest to Dash	340		382	
CS	Chest to Steering Hub	197	9.0		
RA	Rim to Abdomen	115	0.0		
KDL	Left Knee to Dash	170	41.5	174	
KDR	Right Knee to Dash	159		180	43.7
PA	Pelvic Angle		19.2		20.6
TA	Tibia Angle		42.9		40.6
KK	Knee to Knee (Y)	310		228	
SK	Striker to Knee	665	100.8	673	103.4
ST	Striker to Head	430	30.8	402	30.9
SH	Striker to H-Point	438	122.1	417	124.5
SHY	Striker to H-Point (Y)	301		320	
HS	Head to Side Window	378		380	
HD	H-Point to Door (Y)	174		177	
AD	Arm to Door (Y)	187		99	
AA	Ankle to Ankle	312		162	

# SEAT BELT POSITIONING DATA



## FRONT VIEW OF DUMMY

### SEAT BELT POSITIONING MEASUREMENTS

Measurement Description	Units	Driver	Passenger
PBU - Top surface of reference to belt upper edge	mm	325	325
PBL - Top surface of reference to belt lower edge	mm	240	235

## DATA SHEET 38

### CRASH TEST

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Ben Storey


NHTSA No.: C20225305  
 Test Date: 12/8/22

IMPACT ANGLE:	0°			
BELTED DUMMIES (YES/NO):	YES			
TEST SPEED:	<input type="checkbox"/> 32 to 56 kmph	<input type="checkbox"/> 0 to 48 kmph	<input checked="" type="checkbox"/> 0 to 56 kmph	
DRIVER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male
PASSENGER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male

- 1. Vehicle underbody painted.
- 2. The speed measuring devices are in place and functioning.
- 3. The speed measuring devices are 1.0 m from the barrier (spec. 1.5 m) and 30 cm from the barrier (spec. is 30 cm).
- 4. Convertible top is in the closed position.  
 N/A, not a convertible.
- 5. Instrumentation and wires are placed so motion of dummies during impact is not affected.
- 6. Tires inflated to pressure on tire placard or if it does not have a tire placard because it is not a passenger car, then inflated to the tire pressure specified in the owner information.  
  
225 kpa front left tire 225 kpa specified on tire placard or in owner information  
225 kpa front right tire 225 kpa specified on tire placard or in owner information  
220 kpa rear left tire 220 kpa specified on tire placard or in owner information  
220 kpa rear right tire 220 kpa specified on tire placard or in owner information
- 7. Time zero contacts on barrier in place.
- 8. Pre test zero and shunt calibration adjustments performed and recorded.
- 9. Dummy temperature meets requirements of section 12.2 of the test procedure.
- 10. Vehicle hood closed and latched.
- 11. Transmission placed in neutral.
- 12. Parking brake off.
- 13. Are the heads still level?  
 Yes, go to 14  
 No, Adjust dummy so that head is at the angle recorded in the Appendix F or G data sheets and then continue.
- 14. Ignition in the ON position.
- 15. Doors closed and latched but not locked.
- 16. Post test zero and shunt calibration checks performed and recorded.
- 17. Actual test speed: 55.4 kmph
- 18. Vehicle rebound from the barrier: 60 cm
- 19. Describe whether the doors open after the test and what method is used to open the doors.  
 Left Front Door: Door remained closed and latched; Door opened without tools.  
 Right Front Door: Door remained closed and latched; Door opened without tools.  
 Left Rear Door: Door remained closed and latched; Door opened without tools.  
 Right Rear Door: Door remained closed and latched; Door opened without tools.

20. Describe the contact points of the dummy with the interior of the vehicle.
- Driver Dummy: Head to Air Bag and Headrest; Chest to Air Bag; Knees to Knee Restraint
  - Passenger Dummy: Head to Air Bag and Headrest; Chest to Air Bag; Knees to Knee Restraint

REMARKS:

Signature: 

Date: 12/8/22

I certify that I have read and performed each instruction.

**DATA SHEET 40**  
**ACCIDENT INVESTIGATION MEASUREMENTS**

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Ben Storey

NHTSA No.: C20225305  
 Test Date: 12/8/22

IMPACT ANGLE:	0°			
BELTED DUMMIES (YES/NO):	YES			
TEST SPEED:	<input type="checkbox"/> 32 to 56 kmph	<input type="checkbox"/> 0 to 48 kmph	<input checked="" type="checkbox"/> 0 to 56 kmph	
DRIVER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male
PASSENGER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male

Vehicle Year/Make/Model/Body Style:	2022 Honda Civic Passenger Car
VIN:	2HGFE2F53NH609646
Wheelbase:	2741 mm
Build Date:	10/22
Vehicle Size Category:	3
Test Weight:	1455.1 kg
Front Overhang:	955 mm
Overall Width:	1794 mm
Overall Length Center:	4673 mm


Accelerometer Data	
Location:	As per measurements on Data Sheet 33
Linearity:	>99.9%

Integration Algorithm:	Trapezoidal
Vehicle Impact Speed:	55.4 kmph
Time of Separation:	102.5 ms
Velocity Change:	46.2 kmph

## CRUSH PROFILE

Collision Deformation Classification: 12FDEW2  
 Midpoint of Damage: Vehicle Longitudinal Centerline  
 Damage Region Length (mm): 1404  
 Impact Mode: Frontal Barrier

No.	Measurement Description	Units	Pre-Test	Post-Test	Difference
C1	Crush zone 1 at left side	mm	4529	4119	410
C2	Crush zone 2 at left side	mm	4647	4128	519
C3	Crush zone 3 at left side	mm	4673	4146	527
C4	Crush zone 4 at right side	mm	4673	4145	528
C5	Crush zone 5 at right side	mm	4647	4174	473
C6	Crush zone 6 at right side	mm	4529	4083	446



REMARKS:

Signature: Ben Stoney

Date: 12/8/22

I certify that I have read and performed each instruction.

**DATA SHEET 41**  
**WINDSHIELD MOUNTING (FMVSS 212)**

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Ben Storey

NHTSA No.: C20225305  
 Test Date: 12/8/22

IMPACT ANGLE:	0°			
BELTED DUMMIES (YES/NO):	YES			
TEST SPEED:	<input type="checkbox"/> 32 to 56 kmph	<input type="checkbox"/> 0 to 48 kmph	<input checked="" type="checkbox"/> 0 to 56 kmph	
DRIVER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male
PASSENGER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male

1. Pre-Crash
- 1.1 Describe from visual inspection how the windshield is mounted and describe any trim material.
- Retained with glue, rubber and plastic trim
- 1.2 Mark the longitudinal centerline of the windshield.
- 1.3 Measure pre-crash A, B, and C for the left side and record in the chart below.
- 1.4 Measure pre-crash C, D, and E for the right side and record in the chart below.
- 1.5 Measure from the edge of the retainer or molding to the edge of the windshield.
- Dimension G (mm): 9 mm
2. Post Crash
- 2.1 Can a single thickness of copier type paper (as small a piece as necessary) slide between the windshield and the vehicle body?
- No - Pass. Skip to the table of measurements, complete it by repeating the pre-crash measurements in the post crash column, and calculate the retention percentage, which will be 100%.
- Yes, go to 2.2
- 2.2 Visibly mark the beginning and end of the portions of the periphery where the paper slides between the windshield and the vehicle body.
- 2.3 Measure and record post-crash A, B, C, D, E, and F such that the measurements do not include any of the parts of the windshield where the paper slides between the windshield and the vehicle body.
- 2.4 Calculate and record the percent retention for the right and left side of the windshield.
- 2.5 Is total right side percent retention less than 50%?
- Yes, Fail
- No, Pass
- 2.6 Is total left side percent retention less than 50%?
- Yes, Fail
- No, Pass


## WINDSHIELD RETENTION MEASUREMENTS

	Dimension	Pre-Crash (mm)	Post-Crash (mm)	Percent Retention (Post-Test ÷ Pre-Crash)
Left Side	A	599	599	100%
	B	736	736	100%
	C	836	836	100%
	Total	2171	2171	100%
Right Side	D	599	599	100%
	E	736	736	100%
	F	836	836	100%
	Total	2171	2171	100%

Indicate area of mounting failure: NONE

### FRONT VIEW OF WINDSHIELD

INDICATE WIDTH OF MOLDING



REMARKS: NONE

Signature: Ben Stouffer

Date: 12/8/22

I certify that I have read and performed each instruction.

**DATA SHEET 42**  
**WINDSHIELD ZONE INTRUSION (FMVSS 219)**

Test Vehicle: 2022 Honda Civic  
 Test Program: FMVSS 208 Compliance  
 Test Technician: Ben Storey


NHTSA No.: C20225305  
 Test Date: 12/8/22

IMPACT ANGLE:	0°			
BELTED DUMMIES (YES/NO):	YES			
TEST SPEED:	<input type="checkbox"/> 32 to 56 kmph	<input type="checkbox"/> 0 to 48 kmph	<input checked="" type="checkbox"/> 0 to 56 kmph	
DRIVER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male
PASSENGER DUMMY:	<input checked="" type="checkbox"/> X	5 <sup>th</sup> female		50 <sup>th</sup> male

This standard specifies limits for the displacement of vehicle components into the windshield area during a frontal barrier impact test at any speed up to and including 48 kmph.

- 1. Place a 165 mm diameter rigid sphere, with a mass of 6.8 kg on the instrument panel so that it is simultaneously touching the instrument panel and the windshield. (571.219 S6.1(a))
- 2. Roll the sphere from one side of the windshield to the other while marking on the windshield where the sphere contacts the windshield. (571.219 S6.1(b))
- 3. From the outermost contactable points on the windshield draw a horizontal line to the edges of the windshield. (571.219 S6.1(b))
- 4. Draw a line on the inner surface of the windshield that is 13 mm below the line determined in items 2 and 3.
- 5. After the crash test, record any points where a part of the exterior of the vehicle has marked, penetrated, or broken the windshield.

Provide all dimensions necessary to reproduce the protected area.



**WINDSHIELD DIMENSIONS**

Item	Units	Value
A	mm	1198
B	mm	424
C	mm	1672
D	mm	736
E	mm	503
F	mm	571

AREA OF PROTECTED ZONE FAILURES:

- B. Provide coordinates of the area that the protected zone was penetrated more than 0.25 inches by a vehicle component other than one which is normally in contact with the windshield.

X	Y
NONE	

- C. Provide coordinates of the area beneath the protected zone template that the inner surface of the windshield was penetrated by a vehicle component.

X	Y
NONE	

REMARKS:

I certify that I have read and performed each instruction.

Signature: Ben Stoney

Date: 12/8/22

**DATA SHEET 43**  
**FUEL SYSTEM INTEGRITY (FMVSS 301)**

Test Vehicle: 2022 Honda Civic  
Test Program: FMVSS 208 Compliance  
Test Technician: Chris Roach

NHTSA No.: C20225305  
Test Date: 12/8/22


TYPE OF IMPACT:	35 mph Belted
-----------------	---------------

**Stoddard Solvent Spillage Measurements**

- A. From impact until vehicle motion ceases: 0.0 grams  
(Maximum Allowable = 28 grams)
- B. For the 5 minute period after motion ceases: 0.0 grams  
(Maximum Allowable = 142 grams)
- C. For the following 25 minutes: 0.0 grams  
(Maximum Allowable = 28 grams/minute)
- D. Spillage: NONE

REMARKS: NO SPILLAGE

## FMVSS 301 STATIC ROLLOVER DATA



1. The specified fixture rollover rate for each 90° of rotation is 60 to 180 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. Details of Stoddard Solvent spillage locations: **None**

Test Phase	Rotation Time (sec.)	Hold Time (sec.)	Spillage (grams)
0° to 90°	120	320	0.0
90° to 180°	112	322	0.0
180° to 270°	110	320	0.0
270° to 360°	115	315	0.0

## APPENDIX A

### CRASH TEST DATA


#### TABLE OF DATA PLOTS

		<u>Page No.</u>
Figure No. 1.	Driver Head X Acceleration vs. Time	A-1
Figure No. 2.	Driver Head Y Acceleration vs. Time	A-1
Figure No. 3.	Driver Head Z Acceleration vs. Time	A-1
Figure No. 4.	Driver Head Resultant Acceleration vs. Time	A-1
Figure No. 5.	Driver Head X Velocity vs. Time	A-2
Figure No. 6.	Driver Head Y Velocity vs. Time	A-2
Figure No. 7.	Driver Head Z Velocity vs. Time	A-2
Figure No. 8.	Driver Neck Force X vs. Time	A-3
Figure No. 9.	Driver Neck Force Y vs. Time	A-3
Figure No. 10.	Driver Neck Force Z vs. Time	A-3
Figure No. 11.	Driver Neck Force Resultant vs. Time	A-3
Figure No. 12.	Driver Neck Moment X vs. Time	A-4
Figure No. 13.	Driver Neck Moment Y vs. Time	A-4
Figure No. 14.	Driver Neck Moment Z vs. Time	A-4
Figure No. 15.	Driver Neck Moment Resultant vs. Time	A-4
Figure No. 16.	Driver Chest X Acceleration vs. Time	A-5
Figure No. 17.	Driver Chest Y Acceleration vs. Time	A-5
Figure No. 18.	Driver Chest Z Acceleration vs. Time	A-5
Figure No. 19.	Driver Chest Resultant Acceleration vs. Time	A-5
Figure No. 20.	Driver Chest X Velocity vs. Time	A-6
Figure No. 21.	Driver Chest Y Velocity vs. Time	A-6
Figure No. 22.	Driver Chest Z Velocity vs. Time	A-6
Figure No. 23.	Driver Chest Displacement vs. Time	A-6
Figure No. 24.	Driver Left Femur Force vs. Time	A-7
Figure No. 25.	Driver Right Femur Force vs. Time	A-7
Figure No. 26.	Passenger Head X Acceleration vs. Time	A-8
Figure No. 27.	Passenger Head Y Acceleration vs. Time	A-8
Figure No. 28.	Passenger Head Z Acceleration vs. Time	A-8
Figure No. 29.	Passenger Head Resultant Acceleration vs. Time	A-8
Figure No. 30.	Passenger Head X Velocity vs. Time	A-9


	<u>Page No.</u>	
Figure No. 31.	Passenger Head Y Velocity vs. Time	A-9
Figure No. 32.	Passenger Head Z Velocity vs. Time	A-9
Figure No. 33.	Passenger Neck Force X vs. Time	A-10
Figure No. 34.	Passenger Neck Force Y vs. Time	A-10
Figure No. 35.	Passenger Neck Force Z vs. Time	A-10
Figure No. 36.	Passenger Neck Force Resultant vs. Time	A-10
Figure No. 37.	Passenger Neck Moment X vs. Time	A-11
Figure No. 38.	Passenger Neck Moment Y vs. Time	A-11
Figure No. 39.	Passenger Neck Moment Z vs. Time	A-11
Figure No. 40.	Passenger Neck Moment Resultant vs. Time	A-11
Figure No. 41.	Passenger Chest X Acceleration vs. Time	A-12
Figure No. 42.	Passenger Chest Y Acceleration vs. Time	A-12
Figure No. 43.	Passenger Chest Z Acceleration vs. Time	A-12
Figure No. 44.	Passenger Chest Resultant Acceleration vs. Time	A-12
Figure No. 45.	Passenger Chest X Velocity vs. Time	A-13
Figure No. 46.	Passenger Chest Y Velocity vs. Time	A-13
Figure No. 47.	Passenger Chest Z Velocity vs. Time	A-13
Figure No. 48.	Passenger Chest Displacement vs. Time	A-13
Figure No. 49.	Passenger Left Femur Force vs. Time	A-14
Figure No. 50.	Passenger Right Femur Force vs. Time	A-14
Figure No. 51.	Driver Nij ( $N_{TF}$ ) vs. Time	A-15
Figure No. 52.	Driver Nij ( $N_{TE}$ ) vs. Time	A-15
Figure No. 53.	Driver Nij ( $N_{CF}$ ) vs. Time	A-15
Figure No. 54.	Driver Nij ( $N_{CE}$ ) vs. Time	A-15
Figure No. 55.	Passenger Nij ( $N_{TF}$ ) vs. Time	A-16
Figure No. 56.	Passenger Nij ( $N_{TE}$ ) vs. Time	A-16
Figure No. 57.	Passenger Nij ( $N_{CF}$ ) vs. Time	A-16
Figure No. 58.	Passenger Nij ( $N_{CE}$ ) vs. Time	A-16
Figure No. 59.	Driver Occipital Condyle Moment vs. Time	A-17
Figure No. 60.	Passenger Occipital Condyle Moment vs. Time	A-17
Figure No. 61.	Left Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 62.	Left Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 63.	Right Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 64.	Right Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 65.	Top of Engine X Acceleration vs. Time	A-19

		<u>Page No.</u>
Figure No. 66.	Top of Engine X Velocity vs. Time	A-19
Figure No. 67.	Bottom of Engine X Acceleration vs. Time	A-19
Figure No. 68.	Bottom of Engine X Velocity vs. Time	A-19
Figure No. 69.	Left Brake Caliper X Acceleration vs. Time	A-20
Figure No. 70.	Left Brake Caliper X Velocity vs. Time	A-20
Figure No. 71.	Right Brake Caliper X Acceleration vs. Time	A-20
Figure No. 72.	Right Brake Caliper X Velocity vs. Time	A-20
Figure No. 73.	Instrument Panel X Acceleration vs. Time	A-21
Figure No. 74.	Instrument Panel X Velocity vs. Time	A-21
Figure No. 75.	Trunk Z Acceleration vs. Time	A-21
Figure No. 76.	Trunk Z Velocity vs. Time	A-21


**DRIVER HEAD X (g) vs Time (ms)**




**DRIVER HEAD Y (g) vs Time (ms)**









**DRIVER HEAD Z (g) vs Time (ms)**







**DRIVER HEAD Resultant (g) vs Time (ms)**












**DRIVER CHEST X (g) vs Time (ms)**




**DRIVER CHEST Y (g) vs Time (ms)**




**DRIVER CHEST Z (g) vs Time (ms)**




**DRIVER CHEST Resultant (g) vs Time (ms)**




**DRIVER CHEST X Velocity (kph) vs Time (ms)**




**DRIVER CHEST Y Velocity (kph) vs Time (ms)**




**DRIVER CHEST Z Velocity (kph) vs Time (ms)**




**DRIVER CHEST DISPLACEMENT (mm) vs Time (ms)**










**DRIVER LEFT FEMUR (N) vs Time (ms)**




**DRIVER RIGHT FEMUR (N) vs Time (ms)**









**PASSENGER NECK FX (N) vs Time (ms)**




**PASSENGER NECK FY (N) vs Time (ms)**











**PASSENGER NECK FZ (N) vs Time (ms)**




**PASSENGER NECK FResultant (N) vs Time (ms)**









**PASSENGER CHEST X Velocity (kph) vs Time (ms)**




**PASSENGER CHEST Y Velocity (kph) vs Time (ms)**









**PASSENGER CHEST Z Velocity (kph) vs Time (ms)**




**PASSENGER CHEST DISPLACEMENT (mm) vs Time (ms)**









PASSENGER Nij (NTF) vs Time (ms)




PASSENGER Nij (NTE) vs Time (ms)




PASSENGER Nij (NCF) vs Time (ms)




PASSENGER Nij (NCE) vs Time (ms)







DRIVER NECK MY Occipital Condyle (Nm) vs Time (ms)




PASSENGER NECK MY Occipital Condyle (Nm) vs Time (ms)







**TOP OF ENGINE X (g) vs Time (ms)**




**TOP OF ENGINE X Velocity (kph) vs Time (ms)**




**BOTTOM OF ENGINE X (g) vs Time (ms)**




**BOTTOM OF ENGINE X Velocity (kph) vs Time (ms)**




**LEFT BRAKE CALIPER X (g) vs Time (ms)**




**LEFT BRAKE CALIPER X Velocity (kph) vs Time (ms)**







**RIGHT BRAKE CALIPER X (g) vs Time (ms)**



**RIGHT BRAKE CALIPER X Velocity (kph) vs Time (ms)**





## APPENDIX B

### CRASH TEST PHOTOGRAPHS

#### TABLE OF PHOTOGRAPHS

		<u>Page</u> <u>No.</u>
Photo No. 1.	Vehicle Certification Label	B-1
Photo No. 2.	Tire Placard	B-2
Photo No. 3.	Pre-Test Front View of Test Vehicle	B-3
Photo No. 4.	Post-Test Front View of Test Vehicle	B-4
Photo No. 5.	Pre-Test Left Side View of Test Vehicle	B-5
Photo No. 6.	Post-Test Left Side View of Test Vehicle	B-6
Photo No. 7.	Pre-Test Right Side View of Test Vehicle	B-7
Photo No. 8.	Post-Test Right Side View of Test Vehicle	B-8
Photo No. 9.	Pre-Test Left Front Three-Quarter View of Test Vehicle	B-9
Photo No. 10.	Post-Test Left Front Three-Quarter View of Test Vehicle	B-10
Photo No. 11.	Pre-Test Right Front Three-Quarter View of Test Vehicle	B-11
Photo No. 12.	Post-Test Right Front Three-Quarter View of Test Vehicle	B-12
Photo No. 13.	Pre-Test Right Rear Three-Quarter View of Test Vehicle	B-13
Photo No. 14.	Post-Test Right Rear Three-Quarter View of Test Vehicle	B-14
Photo No. 15.	Pre-Test Left Rear Three-Quarter View of Test Vehicle	B-15
Photo No. 16.	Post-Test Left Rear Three-Quarter View of Test Vehicle	B-16
Photo No. 17.	Pre-Test Rear View of Test Vehicle	B-17
Photo No. 18.	Post-Test Rear View of Test Vehicle	B-18
Photo No. 19.	Pre-Test Windshield View	B-19
Photo No. 20.	Post-Test Windshield View	B-20
Photo No. 21.	Pre-Test Engine Compartment View	B-21
Photo No. 22.	Post-Test Engine Compartment View	B-22
Photo No. 23.	Pre-Test Fuel Filler Cap View	B-23
Photo No. 24.	Post-Test Fuel Filler Cap View	B-24
Photo No. 25.	Pre-Test Front Underbody View	B-25
Photo No. 26.	Post-Test Front Underbody View	B-26
Photo No. 27.	Pre-Test Mid Underbody View	B-27
Photo No. 28.	Post-Test Mid Underbody View	B-28
Photo No. 29.	Pre-Test Mid Rear Underbody View	B-29
Photo No. 30.	Post-Test Mid Rear Underbody View	B-30
Photo No. 31.	Pre-Test Rear Underbody View	B-31
Photo No. 32.	Post-Test Rear Underbody View	B-32
Photo No. 33.	Pre-Test Driver Dummy Front View (head position)	B-33

	<u>Page No.</u>
Photo No. 34. Post-Test Driver Dummy Front View (head position)	B-34
Photo No. 35. Pre-Test Driver Dummy Position Left Side View	B-35
Photo No. 36. Post-Test Driver Dummy Position Left Side View	B-36
Photo No. 37. Pre-Test Driver Dummy Position Left Side View (door open)	B-37
Photo No. 38. Post-Test Driver Dummy Position Left Side View (door open)	B-38
Photo No. 39. Pre-Test Driver Dummy Seat Position	B-39
Photo No. 40. Post-Test Driver Dummy Seat Position	B-40
Photo No. 41. Pre-Test Driver Dummy Feet Position	B-41
Photo No. 42. Post-Test Driver Dummy Feet Position	B-42
Photo No. 43. Pre-Test Driver Side Knee Bolster View	B-43
Photo No. 44. Post-Test Driver Side Knee Bolster View	B-44
Photo No. 45. Post-Test Driver Dummy Airbag Contact	B-45
Photo No. 46. Post-Test Driver Dummy Knee Contact	B-46
Photo No. 47. Post-Test Driver Dummy Head Contact (headrest)	B-47
Photo No. 48. Pre-Test Passenger Dummy Front View (head position)	B-48
Photo No. 49. Post-Test Passenger Dummy Front View (head position)	B-49
Photo No. 50. Pre-Test Passenger Dummy Position Right Side View	B-50
Photo No. 51. Post-Test Passenger Dummy Position Right Side View	B-51
Photo No. 52. Pre-Test Passenger Dummy Position Right Side View (door open)	B-52
Photo No. 53. Post-Test Passenger Dummy Position Right Side View (door open)	B-53
Photo No. 54. Pre-Test Passenger Dummy Seat Position	B-54
Photo No. 55. Post-Test Passenger Dummy Seat Position	B-55
Photo No. 56. Pre-Test Passenger Dummy Feet Position	B-56
Photo No. 57. Post-Test Passenger Dummy Feet Position	B-57
Photo No. 58. Pre-Test Passenger Side Knee Bolster View	B-58
Photo No. 59. Post-Test Passenger Side Knee Bolster View	B-59
Photo No. 60. Post-Test Passenger Dummy Airbag Contact	B-60
Photo No. 61. Post-Test Passenger Dummy Knee Contact	B-61
Photo No. 62. Post-Test Passenger Head Contact (Headrest)	B-62
Photo No. 63. 90 Degree Rollover	B-63
Photo No. 64. 180 Degree Rollover	B-64
Photo No. 65. 270 Degree Rollover	B-65
Photo No. 66. 360 Degree Rollover	B-66
Photo No. 67. Temperature Plot	B-67

MFD. BY HONDA OF CANADA MFG.  
A DIVISION OF HONDA CANADA INC.  
GVWR 3880LBS GAWR F 2072LBS R  
GVWR 1760KG GAWR F 940KG R

10/22  
1840LBS  
835KG

THIS VEHICLE CONFORMS TO ALL APPLICABLE  
FEDERAL MOTOR VEHICLE SAFETY BUMPER  
AND THEFT PREVENTION STANDARDS IN EFFECT  
ON THE DATE OF MANUFACTURE SHOWN ABOVE.  
V.I.N.: 2HGFE2F53NH609646 TYPE: PASSENGER CAR



T23 N AG5 -NH830M -Z -H

MADE IN CANADA

T20 A1



Photo No. 1. Vehicle Certification Label

# TIRE AND LOADING INFORMATION



SEATING CAPACITY: TOTAL 5 FRONT 2 REAR 3

The combined weight of occupants and cargo should never exceed 385kg or 850lbs.

TIRE	SIZE	COLD TIRE PRESSURE	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT	235/40R18 91W	225KPA, 33PSI	
REAR		220KPA, 32PSI	
SPARE	T125/85D16	420KPA, 60PSI	

T20 A1



ssure  
1S.

Photo No. 2. Tire Placard



Photo No. 3. Pre-Test Front View of Test Vehicle




Photo No. 4. Post-Test Front View of Test Vehicle



Photo No. 5. Pre-Test Left Side View of Test Vehicle



Photo No. 6. Post-Test Left Side View of Test Vehicle



Photo No. 7. Pre-Test Right Side View of Test Vehicle



Photo No. 8. Post-Test Right Side View of Test Vehicle



Photo No. 9. Pre-Test Left Front Three-Quarter View of Test Vehicle




Photo No. 10. Post-Test Left Front Three-Quarter View of Test Vehicle



Photo No. 11. Pre-Test Right Front Three-Quarter View of Test Vehicle






Photo No. 13. Pre-Test Right Rear Three-Quarter View of Test Vehicle




Photo No. 14. Post-Test Right Rear Three-Quarter View of Test Vehicle



Photo No. 15. Pre-Test Left Rear Three-Quarter View of Test Vehicle




Photo No. 16. Post-Test Left Rear Three-Quarter View of Test Vehicle



Photo No. 17. Pre-Test Rear View of Test Vehicle



Photo No. 18. Post-Test Rear View of Test Vehicle




Photo No. 19. Pre-Test Windshield View



Photo No. 20. Post-Test Windshield View



Photo No. 21 . Pre-Test Engine Compartment View



Photo No. 22. Post-Test Engine Compartment View



Photo No. 23. Pre-Test Fuel Filler Cap View



Photo No. 24. Post-Test Fuel Filler Cap View




Photo No. 25. Pre-Test Front Underbody View




Photo No. 26. Post-Test Front Underbody View




Photo No. 27. Pre-Test Mid Underbody View




Photo No. 28. Post-Test Mid Underbody View




Photo No. 29. Pre-Test Mid Rear Underbody View



Photo No. 30. Post-Test Mid Rear Underbody View



Photo No. 31. Pre-Test Rear Underbody View




Photo No. 32. Post-Test Rear Underbody View




Photo No. 33. Pre-Test Driver Dummy Front View (head position)



Photo No. 34. Post-Test Driver Dummy Front View (head position)



Photo No. 35. Pre-Test Driver Dummy Position Left Side View



Photo No. 36. Post-Test Driver Dummy Position Left Side View



Photo No. 37. Pre-Test Driver Dummy Position Left Side View (door open)



Photo No. 38. Post-Test Driver Dummy Position Left Side View (door open)



Photo No. 39. Pre-Test Driver Dummy Seat Position




Photo No. 40. Post-Test Driver Dummy Seat Position



Photo No. 41. Pre-Test Driver Dummy Feet Position



Photo No. 42. Post-Test Driver Dummy Feet Position




Photo No. 43. Pre-Test Driver Side Knee Bolster View



Photo No. 44. Post-Test Driver Side Knee Bolster View



Photo No. 45. Post-Test Driver Dummy Airbag Contact



Photo No. 46. Post-Test Driver Dummy Knee Contact



Photo No. 47. Post-Test Driver Dummy Head Contact (headrest)



Photo No. 48. Pre-Test Passenger Dummy Front View (head position)



Photo No. 49. Post-Test Passenger Dummy Front View (head position)




Photo No. 50. Pre-Test Passenger Dummy Position Right Side View



Photo No. 51. Post-Test Passenger Dummy Position Right Side View



Photo No. 52. Pre-Test Passenger Dummy Position Right Side View (door open)



Photo No. 53. Post-Test Passenger Dummy Position Right Side View (door open)



Photo No. 54. Pre-Test Passenger Dummy Seat Position




Photo No. 55. Post-Test Passenger Dummy Seat Position



Photo No. 56. Pre-Test Passenger Dummy Feet Position



Photo No. 57. Post-Test Passenger Dummy Feet Position



Photo No. 58. Pre-Test Passenger Side Knee Bolster View



Photo No. 59. Post-Test Passenger Side Knee Bolster View



Photo No. 60. Post-Test Passenger Dummy Airbag Contact




Photo No. 61. Post-Test Passenger Dummy Knee Contact




Photo No. 62. Post-Test Passenger Dummy Head Contact (headrest)



Photo No. 63. Roll-over 90 Degrees



Photo No. 64. Rollover 180 Degrees



Photo No. 65. Rollover 270 Degrees



Photo No. 66. Roll-over 360 Degrees




Photo No. 67 Temperature Plot

**APPENDIX C**

**INSTRUMENTATION CALIBRATION**

**INSTRUMENTS FOR DRIVER DUMMY NO.: 510**

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	P79575	Endevco	11/16/2022
Head Y	P79577	Endevco	11/16/2022
Head Z	P79578	Endevco	11/16/2022
Neck Load Cell	N1865	Denton	10/28/2022
Chest X	P88335	Endevco	11/16/2022
Chest Y	P93609	Endevco	11/16/2022
Chest Z	P88334	Endevco	11/16/2022
Chest Displacement	510	Humanetics	11/16/2022
Left Femur Load Cell	F1827	Denton	11/16/2022
Right Femur Load Cell	F1826	Denton	11/16/2022

**INSTRUMENTS FOR PASSENGER DUMMY NO.: 507**

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	P85158	Endevco	11/16/2022
Head Y	P85159	Endevco	11/16/2022
Head Z	P85160	Endevco	11/16/2022
Neck Load Cell	N2324	Denton	10/20/2022
Chest X	P79787	Endevco	11/16/2022
Chest Y	P86733	Endevco	11/16/2022
Chest Z	P86735	Endevco	11/16/2022
Chest Displacement	507	Humanetics	11/16/2022
Left Femur Load Cell	F8152	Denton	11/16/2022
Right Femur Load Cell	F8151	Denton	11/16/2022

**VEHICLE INSTRUMENTS**

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Left Rear Seat Crossmember X	T29904	Endevco	07/14/2022
Right Rear Seat Crossmember X	A395069	MSI	08/05/2022
Top of Engine X	A383139	MSI	06/16/2022
Bottom of Engine X	A340744	MSI	08/11/2022
Right Brake Caliper X	A295234	MSI	06/29/2022
Instrument Panel X	P94812	Endevco	10/26/2022
Left Brake Caliper X	T30583	Endevco	07/19/2022
Trunk Z	A416953	MSI	08/18/2022